# X-Mem 1.4.3

Generated by Doxygen 1.8.6

Wed Feb 11 2015 11:56:26

# **Contents**

1	REA	DME			1
2	Hier	archica	l Index		7
	2.1	Class	Hierarchy		7
3	Clas	s Index			9
	3.1	Class	List		9
4	File	Index			11
	4.1	File Lis	st		11
5	Clas	s Docu	mentation	1 1	13
	5.1	xmem	::Parser::A	ction Struct Reference	13
		5.1.1	Member	Function Documentation	13
			5.1.1.1	finished	13
			5.1.1.2	perform	13
	5.2	xmem:	::Arg Struc	t Reference	14
		5.2.1	Detailed	Description	14
	5.3	xmem	::Benchma	rk Class Reference	15
		5.3.1	Detailed	Description	17
		5.3.2	Construc	tor & Destructor Documentation	17
			5.3.2.1	Benchmark	17
		5.3.3	Member	Function Documentation	17
			5.3.3.1	_run_core	17
			5.3.3.2	_start_power_threads	18
			5.3.3.3	_stop_power_threads	18
			5.3.3.4	getAverageDRAMPower	18
			5.3.3.5	getAverageMetric	18
			5.3.3.6	getChunkSize	18
			5.3.3.7	getCPUNode	18
			5.3.3.8	getIterations	19
			5.3.3.9	getLen	19
			E 2 2 10	actNomNodo	10

iv CONTENTS

	5.3.3.11	getMetricOnIter	19
	5.3.3.12	getName	19
	5.3.3.13	getNumThreads	19
	5.3.3.14	getPatternMode	20
	5.3.3.15	getPeakDRAMPower	20
	5.3.3.16	getRWMode	20
	5.3.3.17	getStrideSize	20
	5.3.3.18	hasRun	20
	5.3.3.19	isValid	20
	5.3.3.20	run	20
5.3.4	Member I	Data Documentation	21
	5.3.4.1	_average_dram_power_socket	21
	5.3.4.2	_averageMetric	21
	5.3.4.3	_chunk_size	21
	5.3.4.4	_cpu_node	21
	5.3.4.5	_dram_power_readers	21
	5.3.4.6	_dram_power_threads	21
	5.3.4.7	_hasRun	21
	5.3.4.8	_iterations	21
	5.3.4.9	_len	21
	5.3.4.10	_mem_array	21
	5.3.4.11	_mem_node	21
	5.3.4.12	_metricOnlter	22
	5.3.4.13	_metricUnits	22
	5.3.4.14	_name	22
	5.3.4.15	_num_worker_threads	22
	5.3.4.16	_obj_valid	22
	5.3.4.17	_pattern_mode	22
	5.3.4.18	_peak_dram_power_socket	22
	5.3.4.19	_rw_mode	22
	5.3.4.20	_stride_size	22
	5.3.4.21	_warning	22
xmem::	:Benchmai	rkManager Class Reference	23
5.4.1	Detailed I	Description	23
5.4.2	Construc	tor & Destructor Documentation	23
	5.4.2.1	BenchmarkManager	23
5.4.3	Member I	Function Documentation	23
	5.4.3.1	runAll	23
	5.4.3.2	runLatencyBenchmarks	23
	5.4.3.3	runThroughputBenchmarks	24
	xmem:: 5.4.1 5.4.2	5.3.3.12 5.3.3.13 5.3.3.14 5.3.3.15 5.3.3.16 5.3.3.17 5.3.3.18 5.3.3.19 5.3.3.20 5.3.4 Member 5.3.4.1 5.3.4.2 5.3.4.3 5.3.4.4 5.3.4.5 5.3.4.6 5.3.4.7 5.3.4.8 5.3.4.9 5.3.4.10 5.3.4.11 5.3.4.12 5.3.4.13 5.3.4.14 5.3.4.15 5.3.4.16 5.3.4.17 5.3.4.18 5.3.4.19 5.3.4.19 5.3.4.10 5.3.4.11 5.3.4.12 5.3.4.13 5.3.4.14 5.3.4.15 5.3.4.16 5.3.4.17 5.3.4.18 5.3.4.19 5.3.4.20 5.3.4.21 xmem::Benchma 5.4.1 Detailed 5.4.2 Construct 5.4.2.1 5.4.3 Member 5.4.3.1 5.4.3.2	5.3.3.12       getName         5.3.3.13       getPatternMode         5.3.3.14       getPeakDRAMPower         5.3.3.15       getFeakDRAMPower         5.3.3.16       getStrideSize         5.3.3.17       getStrideSize         5.3.3.18       hasRun         5.3.3.19       isValid         5.3.3.20       run         5.3.4.1       _average_dram_power_socket         5.3.4.2       _averageMetric         5.3.4.3       _chunk_size         5.3.4.4       _cpu_node         5.3.4.5       _dram_power_readers         5.3.4.6       _dram_power_treads         5.3.4.7       _hasRun         5.3.4.8       _iterations         5.3.4.9       _len         5.3.4.10       _mem_array         5.3.4.11       _mem_mode         5.3.4.12       _metricUnits         5.3.4.13       _metricUnits         5.3.4.14       _name         5.3.4.15       _num_worker_threads         5.3.4.16       _obj_valid         5.3.4.17       _pattern_mode         5.3.4.20       _stride_size         5.3.4.21       _warning         xmem::BenchmarkManager Class Reference

CONTENTS

5.5	xmem:	:Configuration	tor Class Reference	24
	5.5.1	Detailed I	Description	25
	5.5.2	Construct	tor & Destructor Documentation	26
		5.5.2.1	Configurator	26
	5.5.3	Member I	Function Documentation	27
		5.5.3.1	configureFromInput	27
		5.5.3.2	getIterationsPerTest	28
		5.5.3.3	getNumWorkerThreads	28
		5.5.3.4	getOutputFilename	28
		5.5.3.5	getStartingTestIndex	28
		5.5.3.6	getWorkingSetSizePerThread	28
		5.5.3.7	isNUMAEnabled	28
		5.5.3.8	latencyTestSelected	28
		5.5.3.9	setUseOutputFile	29
		5.5.3.10	throughputTestSelected	30
		5.5.3.11	useChunk128b	30
		5.5.3.12	useChunk256b	30
		5.5.3.13	useChunk32b	30
		5.5.3.14	useChunk64b	30
		5.5.3.15	useLargePages	30
		5.5.3.16	useOutputFile	31
		5.5.3.17	useRandomAccessPattern	31
		5.5.3.18	useReads	31
		5.5.3.19	useSequentialAccessPattern	31
		5.5.3.20	useStrideN1	31
		5.5.3.21	useStrideN16	31
		5.5.3.22	useStrideN2	32
		5.5.3.23	useStrideN4	32
		5.5.3.24	useStrideN8	32
		5.5.3.25	useStrideP1	32
		5.5.3.26	useStrideP16	32
		5.5.3.27	useStrideP2	32
		5.5.3.28	useStrideP4	32
		5.5.3.29	useStrideP8	33
		5.5.3.30	useWrites	33
		5.5.3.31	verboseMode	33
5.6			untOptionsAction Class Reference	33
	5.6.1		tor & Destructor Documentation	33
		5.6.1.1	CountOptionsAction	33
	5.6.2	Member I	Function Documentation	34

vi CONTENTS

		5.6.2.1	perform	34
5.7	xmem:	:Descriptor	Struct Reference	34
	5.7.1	Detailed I	Description	34
	5.7.2	Member I	Data Documentation	35
		5.7.2.1	check_arg	35
		5.7.2.2	help	35
		5.7.2.3	index	35
		5.7.2.4	longopt	35
		5.7.2.5	shortopt	36
		5.7.2.6	type	36
5.8	xmem:	:ExampleA	arg Class Reference	36
5.9	xmem:	:PrintUsag	eImplementation::FunctionWriter< Function > Struct Template Reference	37
5.10	xmem:	:PrintUsag	eImplementation::IStringWriter Struct Reference	37
5.11	xmem:	:LatencyBe	enchmark Class Reference	37
	5.11.1	Detailed I	Description	38
	5.11.2	Member I	Function Documentation	38
		5.11.2.1	_run_core	38
5.12	xmem:	:PrintUsag	eImplementation::LinePartIterator Class Reference	38
	5.12.1	Member I	Function Documentation	39
		5.12.1.1	next	39
		5.12.1.2	nextRow	39
		5.12.1.3	nextTable	39
5.13	xmem:	:PrintUsag	eImplementation::LineWrapper Class Reference	40
	5.13.1	Construct	tor & Destructor Documentation	40
		5.13.1.1	LineWrapper	40
	5.13.2	Member F	Function Documentation	40
		5.13.2.1	process	40
5.14	xmem:	:LoadWork	ter Class Reference	40
	5.14.1	Detailed I	Description	41
	5.14.2	Construct	tor & Destructor Documentation	41
		5.14.2.1	LoadWorker	41
		5.14.2.2	LoadWorker	41
5.15	xmem:	:MemoryW	orker Class Reference	42
	5.15.1	Detailed I	Description	43
	5.15.2	Construct	tor & Destructor Documentation	43
		5.15.2.1	MemoryWorker	43
	5.15.3	Member F	Function Documentation	43
		5.15.3.1	getAdjustedTicks	43
			getBytesPerPass	43
		5.15.3.3	getElapsedDummyTicks	44

CONTENTS vii

	5.15.3.4 getElapsedTicks	44
	5.15.3.5 getLen	44
	5.15.3.6 getPasses	44
	5.15.3.7 hadWarning	44
5.15.4	Member Data Documentation	44
	5.15.4.1 _adjusted_ticks	44
	5.15.4.2 _bytes_per_pass	44
	5.15.4.3 _completed	44
	5.15.4.4 _cpu_affinity	45
	5.15.4.5 _elapsed_dummy_ticks	45
	5.15.4.6 _elapsed_ticks	45
	5.15.4.7 _len	45
	5.15.4.8 _mem_array	45
	5.15.4.9 _passes	45
	5.15.4.10 _warning	45
5.16 xmem	::MyArg Class Reference	45
5.17 xmem	::Option Class Reference	46
	Detailed Description	47
5.17.2	Constructor & Destructor Documentation	47
	5.17.2.1 Option	47
	5.17.2.2 Option	47
5.17.3	Member Function Documentation	48
	5.17.3.1 append	48
	5.17.3.2 count	48
	5.17.3.3 first	48
	5.17.3.4 isFirst	48
	5.17.3.5 isLast	48
	5.17.3.6 last	48
	5.17.3.7 next	49
	5.17.3.8 nextwrap	49
	5.17.3.9 operator const Option *	49
	5.17.3.10 operator Option *	49
	5.17.3.11 operator=	50
	5.17.3.12 prev	50
	5.17.3.13 prevwrap	50
	5.17.3.14 type	50
5.17.4	Member Data Documentation	50
	5.17.4.1 arg	50
	5.17.4.2 desc	50
	5.17.4.3 name	51

viii CONTENTS

		5.17.4.4 namelen	51
5.18	xmem:	:PrintUsageImplementation::OStreamWriter< OStream > Struct Template Reference	51
5.19	xmem:	:Parser Class Reference	52
	5.19.1	Detailed Description	53
	5.19.2	Constructor & Destructor Documentation	53
		5.19.2.1 Parser	53
	5.19.3	Member Function Documentation	54
		5.19.3.1 error	54
		5.19.3.2 nonOptions	54
		5.19.3.3 nonOptionsCount	55
		5.19.3.4 optionsCount	55
		5.19.3.5 parse	55
5.20	xmem:	:PowerReader Class Reference	56
	5.20.1	Detailed Description	57
	5.20.2	Constructor & Destructor Documentation	57
		5.20.2.1 PowerReader	57
	5.20.3	Member Function Documentation	58
		5.20.3.1 calculateMetrics	58
		5.20.3.2 clear	58
		5.20.3.3 clear_and_reset	58
		5.20.3.4 getAveragePower	58
		5.20.3.5 getLastSample	58
		5.20.3.6 getNumSamples	59
		5.20.3.7 getPeakPower	59
		5.20.3.8 getPowerTrace	59
		5.20.3.9 getPowerUnits	59
		5.20.3.10 getSamplingPeriod	59
		5.20.3.11 name	59
		5.20.3.12 stop	60
	5.20.4	Member Data Documentation	60
		5.20.4.1 _average_power	60
		5.20.4.2 _cpu_affinity	60
		5.20.4.3 _name	60
		5.20.4.4 _num_samples	60
		5.20.4.5 _peak_power	60
		5.20.4.6 _power_trace	60
		5.20.4.7 _power_units	60
		5.20.4.8 _sampling_period	60
		5.20.4.9 _stop_signal	60
5.21	xmem:	:PrintUsageImplementation Struct Reference	61

CONTENTS

	5.21.1	Member Function Documentation	31
		5.21.1.1 isWideChar	31
5.22	xmem:	:Runnable Class Reference	31
	5.22.1	Detailed Description	32
	5.22.2	Member Function Documentation	32
		5.22.2.1 _acquireLock	32
		5.22.2.2 _releaseLock	32
5.23	xmem:	Stats Struct Reference	3
	5.23.1	Detailed Description	34
	5.23.2	Constructor & Destructor Documentation	34
		5.23.2.1 Stats	34
	5.23.3	Member Function Documentation	64
		5.23.3.1 add	64
	5.23.4	Member Data Documentation	64
		5.23.4.1 buffer_max	64
		5.23.4.2 options_max	35
5.24	xmem:	:Parser::StoreOptionAction Class Reference	35
	5.24.1	Constructor & Destructor Documentation	35
		5.24.1.1 StoreOptionAction	35
	5.24.2	Member Function Documentation	66
			66
		5.24.2.2 perform	66
5.25	xmem:	:PrintUsageImplementation::StreamWriter< Function, Stream > Struct Template Reference 6	66
			37
5.27	xmem:	:PrintUsageImplementation::TemporaryWriter< Temporary > Struct Template Reference 6	37
5.28	xmem:	Thread Class Reference	86
	5.28.1	Detailed Description	86
	5.28.2	Constructor & Destructor Documentation	86
		5.28.2.1 Thread	86
			86
	5.28.3	Member Function Documentation	39
			39
		·	69
		5.28.3.3 create_and_start	39
			39
			39
		3 3	39
			69
		•	70
		5.28.3.9 join	70

CONTENTS

			5.28.3.10	started			 	 	 	 	70
			5.28.3.11	validTarget .			 	 	 	 	70
	5.29	xmem:	:Throughpu	utBenchmark (	Class Refer	rence .	 	 	 	 	70
		5.29.1	Detailed [	Description .			 	 	 	 	71
		5.29.2	Member F	unction Docu	mentation		 	 	 	 	71
			5.29.2.1	_run_core .			 	 	 	 	71
	5.30	xmem:	:Timer Clas	ss Reference			 	 	 	 	71
		5.30.1	Detailed [	Description .			 	 	 	 	71
		5.30.2	Member F	unction Docu	mentation		 	 	 	 	72
			5.30.2.1	get_ns_per_t	ick		 	 	 	 	72
			5.30.2.2	get_ticks_per	_sec		 	 	 	 	72
		5.30.3	Member [	Data Documen	ntation		 	 	 	 	72
			5.30.3.1	_ns_per_tick			 	 	 	 	72
			5.30.3.2	_ticks_per_se	эс		 	 	 	 	72
6	File I	Docume	entation								73
•	6.1			p File Referer	nce						73
	0.1	6.1.1	•	Description .							73
	6.2			ernels.cpp File							73
	0.2	6.2.1		Description .							73
	6.3			anager.cpp File							74
		6.3.1		Description .							74
	6.4	src/con		File Reference							74
		6.4.1		Description .							74
	6.5	src/Coi		pp File Refere							75
		6.5.1	Detailed [	Description .			 	 	 	 	75
	6.6	src/incl	lude/Bench	mark.h File Re	eference .		 	 	 	 	75
		6.6.1	Detailed [	Description .			 	 	 	 	75
	6.7	src/incl	ude/bench	mark_kernels.	h File Refe	erence .	 	 	 	 	75
		6.7.1	Detailed [	Description .			 	 	 	 	82
	6.8	src/incl	ude/Bench	markManager	r.h File Refe	erence.	 	 	 	 	82
		6.8.1	Detailed [	Description .			 	 	 	 	82
	6.9	src/incl	ude/comm	on.h File Refe	rence		 	 	 	 	83
		6.9.1	Detailed [	Description .			 	 	 	 	85
		6.9.2	Macro De	finition Docum	nentation .		 	 	 	 	85
			6.9.2.1	BENCHMARI	K_DURATI	ON_SEC	 	 	 	 	85
			6.9.2.2	DEFAULT_LA	ARGE_PAG	GE_SIZE	 	 	 	 	85
			6.9.2.3	DEFAULT_N	UM_L1_CA	ACHES	 	 	 	 	85
			6.9.2.4	DEFAULT_N	UM_L2_CA	ACHES	 	 	 	 	85
			6.9.2.5	DEFAULT_N	UM_L3_CA	ACHES	 	 	 	 	85

CONTENTS xi

	6.9.2.6	DEFAULT_NUM_L4_CACHES	85
	6.9.2.7	DEFAULT_NUM_LOGICAL_CPUS	85
	6.9.2.8	DEFAULT_NUM_NODES	85
	6.9.2.9	DEFAULT_NUM_PHYSICAL_CPUS	85
	6.9.2.10	DEFAULT_NUM_PHYSICAL_PACKAGES	85
	6.9.2.11	DEFAULT_NUM_WORKER_THREADS	86
	6.9.2.12	DEFAULT_PAGE_SIZE	86
	6.9.2.13	DEFAULT_WORKING_SET_SIZE_PER_THREAD	86
	6.9.2.14	LATENCY_BENCHMARK_UNROLL_LENGTH	86
	6.9.2.15	MIN_ELAPSED_TICKS	86
	6.9.2.16	POWER_SAMPLING_PERIOD_SEC	86
	6.9.2.17	RANDOM_CONSTRUCT_WITH_SHUFFLE	86
	6.9.2.18	THROUGHPUT_BENCHMARK_BYTES_PER_PASS	86
	6.9.2.19	USE_TIME_BASED_BENCHMARKS	86
	6.9.2.20	USE_TSC_TIMER	86
6.10	src/include/Config	gurator.h File Reference	87
	6.10.1 Detailed	Description	87
6.11	src/include/Exam	pleArg.h File Reference	87
	6.11.1 Detailed	Description	87
6.12	src/include/Laten	cyBenchmark.h File Reference	88
	6.12.1 Detailed	Description	88
6.13	src/include/Load\	Norker.h File Reference	88
	6.13.1 Detailed	Description	88
6.14	src/include/Memo	pryWorker.h File Reference	88
	6.14.1 Detailed	Description	89
6.15	src/include/MyArg	g.h File Reference	89
	6.15.1 Detailed	Description	89
6.16	•	parser.h File Reference	89
	6.16.1 Detailed	Description	90
6.17		rReader.h File Reference	93
	6.17.1 Detailed	Description	93
6.18	src/include/Runna	able.h File Reference	93
	6.18.1 Detailed	Description	93
6.19		d.h File Reference	93
	6.19.1 Detailed	Description	94
6.20		ghputBenchmark.h File Reference	94
		Description	94
6.21		h File Reference	94
		Description	94
6.22	src/include/win/w	in_common_third_party.h File Reference	94

xii CONTENTS

	6.22.1 Detailed Description	94
6.23	src/include/win/win_CPdhQuery.h File Reference	95
	6.23.1 Detailed Description	95
6.24	src/include/win/WindowsDRAMPowerReader.h File Reference	95
	6.24.1 Detailed Description	95
6.25	src/LatencyBenchmark.cpp File Reference	95
	6.25.1 Detailed Description	95
6.26	src/LoadWorker.cpp File Reference	95
	6.26.1 Detailed Description	95
6.27	src/main.cpp File Reference	96
	6.27.1 Detailed Description	96
6.28	src/MemoryWorker.cpp File Reference	96
	6.28.1 Detailed Description	96
6.29	src/PowerReader.cpp File Reference	96
	6.29.1 Detailed Description	96
6.30	src/Runnable.cpp File Reference	97
	6.30.1 Detailed Description	97
6.31	src/Thread.cpp File Reference	97
	6.31.1 Detailed Description	97
6.32	src/ThroughputBenchmark.cpp File Reference	97
	6.32.1 Detailed Description	97
6.33	src/Timer.cpp File Reference	98
	6.33.1 Detailed Description	98
6.34	src/win/win_common_third_party.cpp File Reference	98
	6.34.1 Detailed Description	98
6.35	src/win/WindowsDRAMPowerReader.cpp File Reference	98
	6.35.1 Detailed Description	98
Index		99

# **Chapter 1**

# **README**

X-Mem: Extensible Memory Benchmarking Tool v1.4.3

The flexible open-source research tool for characterizing memory hierarchy throughput, latency, and power.

Originally authored by Mark Gottscho (Email: mgottscho@ucla.edu) as a Summer 2014 intern at Microsoft Research, Redmond, WA.

This project is under active development. Stay tuned for more updates.

PROJECT REVISION DATE: February 11, 2015.

#### **LICENSE**

The MIT License (MIT)

Copyright (c) 2014 Microsoft

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

# **FEATURES**

This tool is provided as open source with the hope of being useful to the broader research and development community. Here are some of X-Mem's features.

Flexibility: Easy reconfiguration for different combinations of tests

- · Working sets in increments of 4KB, allowing cache up to main memory-level benchmarking
- NUMA support
- · Multi-threading support
- Large page support

2 README

Extensibility: modularity via C++ object-oriented principles

- · Supports rapid addition of new benchmark kernel routines
- · Example: stream triad algorithm, impact of false sharing, etc. are possible with minor changes

Cross-platform: Currently implemented for Windows and GNU/Linux on x86-64 CPUs

- · Designed to allow straightforward porting to other operating systems and ISAs
- · GNU/Linux on ARM port planned

## Memory throughput:

- · Accurate measurement of sustained memory throughput to all levels of cache and memory
- Regular access patterns: forward & reverse sequential as well as strides of 2, 4, 8, and 16 words
- · Random access patterns
- · Read and write
- 32, 64, 128, 256-bit width memory instructions

## Memory latency:

- · Accurate measurement of round-trip memory latency to all levels of cache and memory
- · Loaded and unloaded latency via use of multithreaded load generation

## Memory power:

- · Currently collecting DRAM power via custom driver exposed in Windows performance counter API
- · Support custom power instrumentation through a simple interface that end-users can implement

## Documentation:

• Extensive Doxygen source code comments, PDF manual, HTML

For feature requests, please refer to the contact information at the end of this README.

# **RUNTIME PREREQUISITES**

There are a few runtime prerequisites in order for the software to run correctly.

# HARDWARE:

• Intel x86-64 CPU supporting AVX extensions (Sandy Bridge or later).

## WINDOWS:

- · Microsoft Windows 64-bit, 8.0 or later, Server 2012 or later.
- · Microsoft Visual C++ 2013 Redistributables (64-bit)
- Potentially, Administrator privileges, in order to:
  - use large pages, if the -large\_pages option is selected (see USAGE, below)

- The first time you use -large\_pages on a given Windows machine, you may need to ensure that your Windows user account has the necessary rights to allow lockable memory pages. To do this on Windows 8, run gpedit.msc -> Local Computer Policy -> Computer Configuration -> Windows Settings -> Security Settings -> Local Policies -> User Rights Assignment -> Add your username to "Lock pages in memory". Then log out and then log back in.
- use the PowerReader interface, depending on end-user implementation
- elevate thread priority and pin threads to logical CPUs for improved performance and benchmarking consistency

#### GNU/LINUX:

- GNU utilities with support for C++11. Tested with gcc 4.8.2 on Ubuntu 14.04 LTS.
- libhugetlbfs. You can obtain it at http://libhugetlbfs.sourceforge.net. On Ubuntu systems, you can install using "sudo apt-get install libhugetlbfs0".
- Potentially, administrator privileges, if you plan to use the -large\_pages option.
  - During runtime, if the –large\_pages option is selected, you may need to first manually ensure that large pages are available from the OS. This can be done by running "hugeadm --pool-list". It is recommended to set minimum pool to 1GB (in order to measure DRAM effectively). If needed, this can be done by running "hugeadm --pool-pages-min 2MB:512". Alternatively, run the linux\_setup\_runtime\_hugetlbfs.sh script that is provided with X-Mem.

## **INSTALLATION**

The only file that is needed to run on Windows is xmem-win.exe, and xmem-linux on GNU/Linux. It has no other dependencies aside from the system prerequisites listed above.

# **USAGE**

USAGE: xmem [options]

Options: -c, -chunk\_size A chunk size to use for throughput benchmarks, specified in bits. Allowed values: 32, 64, 128, and 256. If no chunk sizes specified, use 64-bit chunks by default. NOTE: Some chunk sizes may not be supported on your hardware. -f, -output file Output filename to use. If not specified, no output file generated. -h, -help Print usage and exit. -i, -base test index Numerical index of the first benchmark, for tracking unique test IDs. -j, -num\_worker\_threads Number of worker threads to use in relevant benchmarks. This may not exceed the number of logical CPUs in the system. For throughput benchmarks, this is the number of independent loadgenerating threads. For latency benchmarks, this is the number of independent load-generating threads plus one latency measurement thread. -I, -latency Measure memory latency -n, -iterations lterations per benchmark test -r, random\_access Use a random access pattern on throughput benchmarks. WARNING: not yet implemented, results are not correct. -s, -sequential\_access Use a sequential access pattern on throughput benchmarks -t, -throughput Measure memory throughput -u, -force uma Test only CPU/memory NUMA node 0 instead of all combinations. -v, -verbose Verbose mode, increase detail in X-Mem console reporting. -w, -working\_set\_size Working set size per worker thread in KB. This must be a multiple of 4KB. -L, -large\_pages Use large pages if possible. This may enable better memory performance, particularly for random-access patterns, but may not be supported on your system. -R, -reads Use memory reads in throughput benchmarks. -W, -writes Use memory writes in throughput benchmarks. -S, -stride\_size A stride size to use for sequential throughput benchmarks, specified in powers-of-two multiples of the chunk size(s). Allowed values: 1, -1, 2, -2, 4, -4, 8, -8, 16, -16. Positive indicates the forward direction (increasing addresses), while negative indicates the reverse direction.

If a given option is not specified, X-Mem defaults will be used where appropriate.

Examples: xmem -help xmem -h xmem -l -verbose -n5 -chunk\_size=32 -s xmem -t -latency -w524288 -f results.-csv -c32 -c256 -i 101 -u -j2

4 README

## **BUILDING FROM SOURCE**

Before building the source, enable and disable the relevant compile-time options in <a href="src/include/common.h">src/include/common.h</a>, under the section "User-configurable compilation configuration". Please read the comments by each #define statement to understand the context of each option.

After you have set the desired compile-time options, build the source. On Windows, running build-win.bat should suffice. On GNU/Linux, run build-linux.sh.

If you customize your build, make sure you use the "Release" mode for your OS. Do not include debug capabilities as it can dramatically affect performance of the benchmarks, leading to pessimistic results.

#### **BUILD PREREQUISITES**

There are a few software build prerequisites, depending on your platform.

#### WINDOWS:

- · Any version of Visual Studio 2013 64-bit (also known as version 12.0).
- Python 2.7. You can obtain it at http://www.python.org.
- SCons build system. You can obtain it at http://www.scons.org. Build tested with SCons 2.3.4.

#### GNU/LINUX:

- gcc with support for the C++11 standard. Tested with gcc version 4.8.2 on Ubuntu 14.04 LTS for x86-64.
- Python 2.7. You can obtain it at <a href="http://www.python.org">http://www.python.org</a>. On Ubuntu systems, you can install using "sudo apt-get install python2.7". You may need some other Python 2.7 packages as well.
- SCons build system. You can obtain it at <a href="http://www.scons.org">http://www.scons.org</a>. On Ubuntu systems, you can install using "sudo apt-get install scons". Build tested with SCons 2.3.4.
- Kernel support for large (huge) pages. This support can be verified on your Linux installation by running "grep
  hugetlbfs /proc/filesystems". If you do not have huge page support in your kernel, you can build a kernel with
  the appropriate options switched on: "CONFIG\_HUGETLB\_PAGE" and "CONFIG\_HUGETLBFS".
- libhugetlbfs. This is used for allocating large (huge) pages if the —large\_pages runtime option is selected. You can obtain it at http://libhugetlbfs.sourceforge.net. On Ubuntu systems, you can install using "sudo apt-get install libhugetlbfs-dev".

### **DOCUMENTATION BUILD PREREQUISITES**

The following tools are only needed for automatically regenerating source code documentation with HTML and PDF. WINDOWS:

- doxygen tool. You can obtain it at http://www.stack.nl/~dimitri/doxygen.
- LaTeX distribution. You can get a Windows distribution at http://www.miktex.org.
- make for Windows. You can obtain it at http://gnuwin32.sourceforge.net/packages/make.htm. You will have to manually add it to your Windows path.

## GNU/LINUX:

- doxygen tool. You can obtain it at http://www.stack.nl/~dimitri/doxygen. On Ubuntu systems, you can install with "sudo apt-get install doxygen".
- LaTeX distribution. On Ubuntu systems, LaTeX distributed with doxygen should actually be sufficient. You can install with "sudo apt-get install doxygen-latex".
- make. This should be included on any GNU/Linux system.

## SOURCE CODE DOCUMENTATION

The tool comes with built-in Doxygen comments in the source code, which can be used to generate both HTML and LaTeX —> PDF documentation. Documentation is maintained under the doc/ subdirectory. To build documentation after modifying the source, run build-docs-win.bat on Windows, or build-docs-linux.sh on GNU/Linux systems. Note that Doxygen and a LaTeX distribution must be installed on the system.

#### **VERSION CONTROL**

This project is under version control using git. Its master repository is hosted at https://github.com/-Microsoft/X-Mem.git. There is also another fork at https://github.com/nanocad-lab/X--Mem.git, which generally mirrors Microsoft's repository.

# CONTACT, FEEDBACK, AND BUG REPORTS

For questions, comments, criticism, bug reports, and other feedback for this software, please contact Mark Gottscho via email at mgottscho@ucla.edu or via web at http://www.seas.ucla.edu/~gottscho.

For inquiries about this work while conducted at Microsoft, please contact Dr. Mohammed Shoaib at mohammed. - shoaib@microsoft.com or Dr. Sriram Govindan at srgovin@microsoft.com.

## **ACKNOWLEDGMENT**

Mark Gottscho would like to thank Dr. Mohammed Shoaib of Microsoft Research and Dr. Sriram Govindan of Microsoft for their mentorship in the creation of this software. Further thanks to Dr. Bikash Sharma, Mark Santaniello, Mike Andrewartha, and Laura Caulfield of Microsoft for their contributions, feedback, and assistance. Thank you as well to Dr. Jie Liu of Microsoft Research, Dr. Badriddine Khessib and Dr. Kushagra Vaid of Microsoft, and Prof. Puneet Gupta of UCLA for giving me the opportunity to create this work. Finally, Mark would like to thank Dr. Fedor Pikus of Mentor Graphics for teaching him some useful HPC programming techniques.

6 README

# Chapter 2

# **Hierarchical Index**

# 2.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

xmem::Parser::Action	13
xmem::Parser::StoreOptionAction	65
xmem::Stats::CountOptionsAction	33
xmem::Arg	14
xmem::ExampleArg	36
xmem::MyArg	45
xmem::Benchmark	15
xmem::LatencyBenchmark	37
xmem::ThroughputBenchmark	70
xmem::BenchmarkManager	23
•	24
· ·	34
	37
xmem::PrintUsageImplementation::FunctionWriter< Function >	
xmem::PrintUsageImplementation::OStreamWriter< OStream >	
xmem::PrintUsageImplementation::StreamWriter< Function, Stream >	
xmem::PrintUsageImplementation::TemporaryWriter< Temporary >	
	38
	40
	46
	52
	61
xmem::Runnable	61
xmem::MemoryWorker	42
xmem::LoadWorker	40
xmem::PowerReader	56
xmem::Stats	63
xmem::Thread	68
xmem::Timer	71

8 **Hierarchical Index** 

# **Chapter 3**

# **Class Index**

# 3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:	
xmem::Parser::Action	

xmem::Arg	
Functions for checking the validity of option arguments	14
xmem::Benchmark	
Flexible abstract class for any memory benchmark	15
xmem::BenchmarkManager	
Manages running all benchmarks at a high level	23
xmem::Configurator	
Handles all user input interpretation and generates the necessary flags for running benchmarks	24
xmem::Stats::CountOptionsAction	33
xmem::Descriptor	
Describes an option, its help text (usage) and how it should be parsed	34
xmem::ExampleArg	36
xmem::PrintUsageImplementation::FunctionWriter< Function >	37
xmem::PrintUsageImplementation::IStringWriter	37
xmem::LatencyBenchmark	
A type of benchmark that measures unloaded memory latency via random pointer chasing	37
xmem::PrintUsageImplementation::LinePartIterator	38
xmem::PrintUsageImplementation::LineWrapper	40
xmem::LoadWorker	
Multithreading-friendly class to do memory loading	40
xmem::MemoryWorker	
Multithreading-friendly class to run memory access kernels	42
xmem::MyArg	45
xmem::Option	
A parsed option from the command line together with its argument if it has one	46
xmem::PrintUsageImplementation::OStreamWriter< OStream>	51
xmem::Parser	
Checks argument vectors for validity and parses them into data structures that are easier to work	
with	52
xmem::PowerReader	
An abstract base class for measuring power from an arbitrary source. This class is runnable	
using a worker thread	56
xmem::PrintUsageImplementation	61
xmem::Runnable	
A base class for any object that implements a thread-safe run() function for use by Thread objects	61
xmem::Stats	
Determines the minimum lengths of the buffer and options arrays used for Parser	63

13

10 Class Index

xmem::Parser::StoreOptionAction	65
xmem::PrintUsageImplementation::StreamWriter< Function, Stream >	66
xmem::PrintUsageImplementation::SyscallWriter< Syscall >	67
xmem::PrintUsageImplementation::TemporaryWriter< Temporary >	67
xmem::Thread	
Nice wrapped thread interface independent of particular OS API	68
xmem::ThroughputBenchmark	
A type of benchmark that measures memory throughput	70
xmem::Timer	
This class abstracts some characteristics of simple high resolution stopwatch timer. However,	
due to the inability or complexity of abstracting shared hardware timers, this class does not	
actually provide start and stop functions	71

# **Chapter 4**

# File Index

# 4.1 File List

Here is a list of all documented files with brief descriptions:

src/Benchmark.cpp	
Implementation file for the Benchmark class	73
src/benchmark_kernels.cpp	
Implementation file for benchmark kernel functions for doing the actual work we care about. :) .	73
src/BenchmarkManager.cpp	
Implementation file for the BenchmarkManager class	74
src/common.cpp	
Implementation file for common preprocessor definitions, macros, functions, and global con-	
stants	74
src/Configurator.cpp	
Implementation file for the Configurator class and some helper data structures	75
src/LatencyBenchmark.cpp	
Implementation file for the LatencyBenchmark class	95
src/LoadWorker.cpp	
Implementation file for the LoadWorker class	95
src/main.cpp	
Main entry point to the tool	96
src/MemoryWorker.cpp	
Implementation file for the MemoryWorker class	96
src/PowerReader.cpp	
Implementation file for the PowerReader class	96
src/Runnable.cpp	
Implementation file for the Runnable class	97
src/Thread.cpp	
Implementation file for the Thread class	97
src/ThroughputBenchmark.cpp	
Implementation file for the ThroughputBenchmark class	97
src/Timer.cpp	
Implementation file for the Timer class	98
src/include/Benchmark.h	
Header file for the Benchmark class	75
src/include/benchmark_kernels.h	
Header file for benchmark kernel functions for doing the actual work we care about. :)	75
src/include/BenchmarkManager.h	
Header file for the BenchmarkManager class	82
src/include/build_datetime.h	??
src/include/common.h	
Header file for common preprocessor definitions, macros, functions, and global constants	83

12 File Index

src/include/Configurator.h	
Header file for the Configurator class and some helper data structures	87
src/include/ExampleArg.h	
Slightly-modified third-party code related to OptionParser	87
src/include/LatencyBenchmark.h	
Header file for the LatencyBenchmark class	88
src/include/LoadWorker.h	
Header file for the LoadWorker class	88
src/include/MemoryWorker.h	
Header file for the MemoryWorker class	88
src/include/MyArg.h	
Extensions to third-party optionparser-related code	89
src/include/optionparser.h	
This is the only file required to use The Lean Mean C++ Option Parser. Just #include it and	
you're set	89
src/include/PowerReader.h	
Header file for the PowerReader class	93
src/include/Runnable.h	
Header file for the Runnable class	93
src/include/Thread.h	
Header file for the Thread class	93
src/include/ThroughputBenchmark.h	
Header file for the ThroughputBenchmark class	94
src/include/Timer.h	
Header file for the Timer class	94
src/include/win/win_common_third_party.h	
Header file for some third-party helper code for working with Windows APIs	94
src/include/win/win_CPdhQuery.h	
Header and implementation file for some third-party code for measuring Windows OS-exposed	
performance counters	95
src/include/win/WindowsDRAMPowerReader.h	
Header file for the WindowsDRAMPowerReader class	95
src/win/win_common_third_party.cpp	
Implementation file for some third-party helper code for working with Windows APIs	98
src/win/WindowsDRAMPowerReader.cpp	
Implementation file for the WindowsDRAMPowerReader class	98

# **Chapter 5**

# **Class Documentation**

# 5.1 xmem::Parser::Action Struct Reference

Inheritance diagram for xmem::Parser::Action:



# **Public Member Functions**

• virtual bool perform (Option &)

Called by Parser::workhorse() for each Option that has been successfully parsed (including unknown options if they have a Descriptor whose Descriptor::check\_arg does not return ARG\_ILLEGAL.

• virtual bool finished (int numargs, const char \*\*args)

Called by Parser::workhorse() after finishing the parse.

# 5.1.1 Member Function Documentation

5.1.1.1 virtual bool xmem::Parser::Action::finished (int numargs, const char \*\* args) [inline], [virtual]

Called by Parser::workhorse() after finishing the parse.

## **Parameters**

numargs	the number of non-option arguments remaining
args	pointer to the first remaining non-option argument (if numargs $>$ 0).

## Returns

false iff a fatal error has occurred.

Reimplemented in xmem::Parser::StoreOptionAction.

**5.1.1.2** virtual bool xmem::Parser::Action::perform ( Option & ) [inline], [virtual]

Called by Parser::workhorse() for each Option that has been successfully parsed (including unknown options if they have a Descriptor whose Descriptor::check\_arg does not return ARG\_ILLEGAL.

14 Class Documentation

Returns false iff a fatal error has occured and the parse should be aborted.

Reimplemented in xmem::Parser::StoreOptionAction, and xmem::Stats::CountOptionsAction.

The documentation for this struct was generated from the following file:


· src/include/optionparser.h

# 5.2 xmem::Arg Struct Reference

Functions for checking the validity of option arguments.

```
#include <optionparser.h>
```

Inheritance diagram for xmem::Arg:



## **Static Public Member Functions**

• static ArgStatus None (const Option &, bool)

For options that don't take an argument: Returns ARG\_NONE.

static ArgStatus Optional (const Option & option, bool)

Returns ARG\_OK if the argument is attached and ARG\_IGNORE otherwise.

# 5.2.1 Detailed Description

Functions for checking the validity of option arguments.

The following example code can serve as starting place for writing your own more complex CheckArg functions:

```
struct Arg: public option::Arg
{
    static void printError(const char* msg1, const option::Option& opt, const char* msg2)
    {
        fprintf(stderr, "ERROR: %s", msg1);
        fwrite(opt.name, opt.namelen, 1, stderr);
        fprintf(stderr, "%s", msg2);
    }
    static option::ArgStatus Unknown(const option::Option& option, bool msg)
    {
        if (msg) printError("Unknown option '", option, "'\n");
        return option::ARG_ILLEGAL;
    }
    static option::ArgStatus Required(const option::Option& option, bool msg)
    {
        if (option.arg != 0)
            return option::ARG_OK;
        if (msg) printError("Option '", option, "' requires an argument\n");
        return option::ARG_ILLEGAL;
    }
    static option::ArgStatus NonEmpty(const option::Option& option, bool msg)
    {
        if (option.arg != 0 && option.arg[0] != 0)
            return option::ARG_OK;
        if (option.arg != 0 && option.arg[0] != 0)
            return option::ARG_OK;
    }
}
```

```
if (msg) printError("Option '", option, "' requires a non-empty argument\n");
    return option::ARG_ILLEGAL;
}

static option::ArgStatus Numeric(const option::Option& option, bool msg)
{
    char* endptr = 0;
    if (option.arg != 0 && strtol(option.arg, &endptr, 10)){};
    if (endptr != option.arg && *endptr == 0)
        return option::ARG_OK;

    if (msg) printError("Option '", option, "' requires a numeric argument\n");
    return option::ARG_ILLEGAL;
}
};
```

The documentation for this struct was generated from the following file:


· src/include/optionparser.h

# 5.3 xmem::Benchmark Class Reference

Flexible abstract class for any memory benchmark.

```
#include <Benchmark.h>
```

Inheritance diagram for xmem::Benchmark:



## **Public Member Functions**

Benchmark (void \*mem\_array, size\_t len, uint32\_t iterations, uint32\_t num\_worker\_threads, uint32\_t mem\_node, uint32\_t cpu\_node, pattern\_mode\_t pattern\_mode, rw\_mode\_t rw\_mode, chunk\_size\_t chunk\_size, int64\_t stride\_size, std::vector< PowerReader \* > dram\_power\_readers, std::string metricUnits, std::string name)

Constructor.

virtual ∼Benchmark ()

Destructor.

• bool run ()

Runs the benchmark.

void print\_benchmark\_header () const

Prints a header piece of information describing the benchmark to the console.

void report\_benchmark\_info () const

Reports benchmark configuration details to the console.

• void report\_results () const

Reports results to the console.

• bool isValid () const

Checks to see that the object is in a valid state.

bool hasRun () const

Checks to see if the benchmark has run.

• double getMetricOnIter (uint32\_t iter) const

Extracts the metric of interest for a given iteration. Units are interpreted by the inheriting class.

16 Class Documentation

· double getAverageMetric () const

Gets the average benchmark metric across all iterations.

double getAverageDRAMPower (uint32 t socket id) const

Gets the average DRAM power over the benchmark.

double getPeakDRAMPower (uint32\_t socket\_id) const

Gets the peak DRAM power over the benchmark.

• size\_t getLen () const

Gets the length of the memory region in bytes. This is not necessarily the "working set size" depending on multithreading configuration.

• uint32\_t getIterations () const

Gets the number of iterations for this benchmark.

• chunk size t getChunkSize () const

Gets the width of memory access used in this benchmark.

• int64\_t getStrideSize () const

Gets the stride size for this benchmark.

• uint32\_t getCPUNode () const

Gets the CPU NUMA node used in this benchmark.

• uint32 t getMemNode () const

Gets the memory NUMA node used in this benchmark.

uint32\_t getNumThreads () const

Gets the number of worker threads used in this benchmark.

• std::string getName () const

Gets the human-friendly name of this benchmark.

pattern\_mode\_t getPatternMode () const

Gets the pattern mode for this benchmark.

rw\_mode\_t getRWMode () const

Gets the read/write mode for this benchmark.

# **Protected Member Functions**

• virtual bool run core ()=0

The core benchmark function.

bool \_start\_power\_threads ()

Starts the DRAM power measurement threads.

bool \_stop\_power\_threads ()

Stops the DRAM power measurement threads. This is a blocking call.

# **Protected Attributes**

```
void * _mem_array
```

- size\_t \_len
- · uint32\_t \_iterations
- uint32\_t \_num\_worker\_threads
- uint32\_t \_mem\_node
- uint32\_t \_cpu\_node
- pattern\_mode\_t \_pattern\_mode
- rw\_mode\_t \_rw\_mode
- chunk\_size\_t \_chunk\_size
- int64\_t \_stride\_size
- std::vector< PowerReader \* > \_dram\_power\_readers
- std::vector< Thread \* > \_dram\_power\_threads

- std::vector< double > \_metricOnIter
- double \_averageMetric
- std::string \_metricUnits
- std::vector< double > \_average\_dram\_power\_socket
- std::vector< double > \_peak\_dram\_power\_socket
- · std::string \_name
- · bool \_obj\_valid
- bool \_hasRun
- · bool \_warning

# 5.3.1 Detailed Description

Flexible abstract class for any memory benchmark.

This class provides a generic interface for interacting with a benchmark. All benchmarks should be derived from this class.

## 5.3.2 Constructor & Destructor Documentation

5.3.2.1 Benchmark::Benchmark ( void \* mem\_array, size\_t len, uint32\_t iterations, uint32\_t num\_worker\_threads, uint32\_t mem\_node, uint32\_t cpu\_node, pattern\_mode\_t pattern\_mode, rw\_mode\_t rw\_mode, chunk\_size\_t chunk\_size, int64\_t stride\_size, std::vector< PowerReader \* > dram\_power\_readers, std::string metricUnits, std::string name )

# Constructor.

### **Parameters**

mem_array	A pointer to a contiguous chunk of memory that has been allocated for benchmarking among
	potentially several worker threads. This should be aligned to a 256-bit boundary.
len	Length of mem_array in bytes. This must be a multiple of 4 KB and should be at least the
	per-thread working set size times the number of worker threads.
iterations	Number of iterations of the complete benchmark. Used to average results and provide a
	measure of consistency and reproducibility.
passes_per	Number of passes to do in each iteration, to ensure timed section of code is "long enough".
iteration	
num_worker	The number of worker threads to use in the benchmark.
threads	
mem_node	The logical memory NUMA node used in the benchmark.
cpu_node	The logical CPU NUMA node to use for the benchmark.
pattern_mode	This indicates the general type of access pattern used, e.g. sequential or random.
rw_mode	This indicates the general type of read/write mix used, e.g. pure reads or pure writes.
chunk_size	Size of an individual memory access for load-generating worker threads.
stride_size	For sequential access patterns, this is the address distance between successive accesses,
	counted in chunks. Negative values indicate a reversed access pattern. A stride of +/-1 is
	purely sequential.
dram_power	A group of PowerReader objects for measuring DRAM power.
readers	
name	The name of the benchmark to use when reporting to console.

## 5.3.3 Member Function Documentation

**5.3.3.1 virtual bool xmem::Benchmark::\_run\_core()** [protected], [pure virtual]

The core benchmark function.

18 Class Documentation

```
Returns
```

True on success.

Implemented in xmem::LatencyBenchmark, and xmem::ThroughputBenchmark.

```
5.3.3.2 bool Benchmark::_start_power_threads() [protected]
```

Starts the DRAM power measurement threads.

Returns

True on success.

```
5.3.3.3 bool Benchmark::_stop_power_threads( ) [protected]
```

Stops the DRAM power measurement threads. This is a blocking call.

Returns

True on success.

5.3.3.4 double Benchmark::getAverageDRAMPower ( uint32\_t socket\_id ) const

Gets the average DRAM power over the benchmark.

Returns

The average DRAM power for a given socket in watts, or 0 if the data does not exist (power was unable to be collected or the benchmark has not run).

5.3.3.5 double Benchmark::getAverageMetric ( ) const

Gets the average benchmark metric across all iterations.

Returns

The average metric.

5.3.3.6 chunk\_size\_t Benchmark::getChunkSize ( ) const

Gets the width of memory access used in this benchmark.

Returns

The chunk size for this benchmark.

5.3.3.7 uint32\_t Benchmark::getCPUNode ( ) const

Gets the CPU NUMA node used in this benchmark.

Returns

The NUMA CPU node used in this benchmark.

5.3.3.8 uint32\_t Benchmark::getIterations ( ) const

Gets the number of iterations for this benchmark.

Returns

The number of iterations for this benchmark.

5.3.3.9 size\_t Benchmark::getLen ( ) const

Gets the length of the memory region in bytes. This is not necessarily the "working set size" depending on multi-threading configuration.

Returns

Length of the memory region in bytes.

5.3.3.10 uint32\_t Benchmark::getMemNode ( ) const

Gets the memory NUMA node used in this benchmark.

Returns

The NUMA memory node used in this benchmark.

5.3.3.11 double Benchmark::getMetricOnlter ( uint32\_t iter ) const

Extracts the metric of interest for a given iteration. Units are interpreted by the inheriting class.

**Parameters** 

iter Iteration to extract.

Returns

The metric on the iteration specified by the input.

5.3.3.12 std::string Benchmark::getName ( ) const

Gets the human-friendly name of this benchmark.

Returns

The benchmark test name.

5.3.3.13 uint32\_t Benchmark::getNumThreads ( ) const

Gets the number of worker threads used in this benchmark.

Returns

The number of worker threads used in this benchmark.

20 Class Documentation

5.3.3.14 pattern\_mode\_t Benchmark::getPatternMode ( ) const Gets the pattern mode for this benchmark. Returns The pattern mode enumerator. 5.3.3.15 double Benchmark::getPeakDRAMPower ( uint32\_t socket\_id ) const Gets the peak DRAM power over the benchmark. Returns The peak DRAM power for a given socket in watts, or 0 if the data does not exist (power was unable to be collected or the benchmark has not run). 5.3.3.16 rw\_mode\_t Benchmark::getRWMode ( ) const Gets the read/write mode for this benchmark. Returns The read/write mix mode. 5.3.3.17 int64\_t Benchmark::getStrideSize ( ) const Gets the stride size for this benchmark. Returns The stride size in chunks. 5.3.3.18 bool Benchmark::hasRun ( ) const Checks to see if the benchmark has run. Returns True if run() has already completed successfully. 5.3.3.19 bool Benchmark::isValid ( ) const Checks to see that the object is in a valid state. Returns True if the object was constructed correctly and can be used. 5.3.3.20 bool Benchmark::run ( ) Runs the benchmark.

Returns

True on benchmark success

## 5.3.4 Member Data Documentation

```
5.3.4.1 std::vector<double> xmem::Benchmark::_average_dram_power_socket [protected]
```

The average DRAM power in this benchmark, per socket.

```
5.3.4.2 double xmem::Benchmark::_averageMetric [protected]
```

Average metric over all iterations. Unit-less because any benchmark can set this metric as needed. It is up to the descendant class to interpret units.

```
5.3.4.3 chunk_size_t xmem::Benchmark::_chunk_size [protected]
```

Chunk size of memory accesses in this benchmark.

```
5.3.4.4 uint32_t xmem::Benchmark::_cpu_node [protected]
```

The CPU NUMA node used in this benchmark.

```
5.3.4.5 std::vector<PowerReader*> xmem::Benchmark::_dram_power_readers [protected]
```

The power reading objects for measuring DRAM power on a per-socket basis during the benchmark.

```
5.3.4.6 std::vector<Thread*> xmem::Benchmark::_dram_power_threads [protected]
```

The power reading threads for measuring DRAM power on a per-socket basis during the benchmark. These work with the DRAM power readers. Although they are worker threads, they are not counted as the "official" benchmarking worker threads.

```
5.3.4.7 bool xmem::Benchmark::_hasRun [protected]
```

Indicates whether the benchmark has run.

```
5.3.4.8 uint32_t xmem::Benchmark::_iterations [protected]
```

Number of iterations used in this benchmark.

```
5.3.4.9 size_t xmem::Benchmark::_len [protected]
```

Length of the memory region in bytes. This is not the working set size per thread!

```
5.3.4.10 void* xmem::Benchmark::_mem_array [protected]
```

Pointer to the memory region to use in this benchmark.

```
5.3.4.11 uint32_t xmem::Benchmark::_mem_node [protected]
```

The memory NUMA node used in this benchmark.

22 Class Documentation

```
5.3.4.12 std::vector<double> xmem::Benchmark::_metricOnlter [protected]
```

Metrics for each iteration of the benchmark. Unit-less because any benchmark can set this metric as needed. It is up to the descendant class to interpret units.

```
5.3.4.13 std::string xmem::Benchmark::_metricUnits [protected]
```

String representing the units of measurement for the metric.

```
5.3.4.14 std::string xmem::Benchmark::_name [protected]
```

Name of this benchmark.

```
5.3.4.15 uint32_t xmem::Benchmark::_num_worker_threads [protected]
```

The number of worker threads used in this benchmark.

```
5.3.4.16 bool xmem::Benchmark::_obj_valid [protected]
```

Indicates whether this benchmark object is valid.

```
5.3.4.17 pattern_mode_t xmem::Benchmark::_pattern_mode [protected]
```

Access pattern mode.

```
5.3.4.18 std::vector<double> xmem::Benchmark::_peak_dram_power_socket [protected]
```

The peak DRAM power in this benchmark, per socket.

```
5.3.4.19 rw_mode_t xmem::Benchmark::_rw_mode [protected]
```

Read/write mode.

```
5.3.4.20 int64_t xmem::Benchmark::_stride_size [protected]
```

Stride size in chunks for sequential pattern mode only.

```
5.3.4.21 bool xmem::Benchmark::_warning [protected]
```

Indicates whether the benchmarks results might be clearly questionable/inaccurate/incorrect due to a variety of factors.

The documentation for this class was generated from the following files:

- src/include/Benchmark.h
- src/Benchmark.cpp

# 5.4 xmem::BenchmarkManager Class Reference

Manages running all benchmarks at a high level.

#include <BenchmarkManager.h>

#### **Public Member Functions**

• BenchmarkManager (Configurator &config)

Constructor.

∼BenchmarkManager ()

Destructor.

• bool runAll ()

Runs all possible benchmark configurations.

• bool runThroughputBenchmarks ()

Runs the throughput benchmarks.

• bool runLatencyBenchmarks ()

Runs the latency benchmark.

# 5.4.1 Detailed Description

Manages running all benchmarks at a high level.

## 5.4.2 Constructor & Destructor Documentation

5.4.2.1 BenchmarkManager::BenchmarkManager ( Configurator & config )

Constructor.

**Parameters** 

The configuration object containing run-time options for this X-Mem execution instance.

# 5.4.3 Member Function Documentation

5.4.3.1 bool BenchmarkManager::runAll ( )

Runs all possible benchmark configurations.

Returns

True on success.

5.4.3.2 bool BenchmarkManager::runLatencyBenchmarks ( )

Runs the latency benchmark.

Returns

True on benchmarking success.

24 Class Documentation

5.4.3.3 bool BenchmarkManager::runThroughputBenchmarks ( )

Runs the throughput benchmarks.

Returns

True on benchmarking success.

The documentation for this class was generated from the following files:

- src/include/BenchmarkManager.h
- · src/BenchmarkManager.cpp

# 5.5 xmem::Configurator Class Reference

Handles all user input interpretation and generates the necessary flags for running benchmarks.

```
#include <Configurator.h>
```

#### **Public Member Functions**

· Configurator ()

Default constructor. A default configuration is set. You will want to run configureFromInput() most likely.

• Configurator (bool runLatency, bool runThroughput, size\_t working\_set\_size\_per\_thread, uint32\_t num\_worker\_threads, bool use\_chunk\_32b, bool use\_chunk\_64b, bool use\_chunk\_128b, bool use\_chunk\_256b, bool numa\_enable, uint32\_t iterations\_per\_test, bool use\_random\_access\_pattern, bool use\_sequential\_access\_pattern, uint32\_t starting\_test\_index, std::string filename, bool use\_output\_file, bool verbose, bool use\_large\_pages, bool use\_reads, bool use\_writes, bool use\_stride\_p1, bool use\_stride\_n1, bool use\_stride\_p2, bool use\_stride\_p4, bool use\_stride\_n4, bool use\_stride\_p8, bool use\_stride\_n8, bool use stride p16, bool use stride n16)

Specialized constructor for when you don't want to get config from input, and you want to pass it in directly.

int32\_t configureFromInput (int argc, char \*argv[])

Configures the tool based on user's command-line inputs.

• bool latencyTestSelected () const

Indicates if the latency test has been selected.

bool throughputTestSelected () const

Indicates if the throughput test has been selected.

• size\_t getWorkingSetSizePerThread () const

Gets the working set size in bytes for each worker thread, if applicable.

· bool useChunk32b () const

Determines if chunk size of 32 bits should be used in relevant benchmarks.

bool useChunk64b () const

Determines if chunk size of 64 bits should be used in relevant benchmarks.

· bool useChunk128b () const

Determines if chunk size of 128 bits should be used in relevant benchmarks.

• bool useChunk256b () const

Determines if chunk size of 256 bits should be used in relevant benchmarks.

• bool isNUMAEnabled () const

Determines if the benchmarks should test for all CPU/memory NUMA combinations.

uint32\_t getIterationsPerTest () const

Gets the number of iterations that should be run of each benchmark.

• bool useRandomAccessPattern () const

Determines if throughput benchmarks should use a random access pattern.

• bool useSequentialAccessPattern () const

Determines if throughput benchmarks should use a sequential access pattern.

uint32\_t getNumWorkerThreads () const

Gets the number of worker threads to use.

• uint32\_t getStartingTestIndex () const

Gets the numerical index of the first benchmark for CSV output purposes.

std::string getOutputFilename () const

Gets the output filename to use, if applicable.

bool useOutputFile () const

Determines whether to generate an output CSV file.

void setUseOutputFile (bool use)

Changes whether an output file should be used.

• bool verboseMode () const

Determines whether X-Mem is in verbose mode.

• bool useLargePages () const

Determines whether X-Mem should use large pages.

• bool useReads () const

Determines whether reads should be used in throughput benchmarks.

• bool useWrites () const

Determines whether writes should be used in throughput benchmarks.

• bool useStrideP1 () const

Determines if a stride of +1 should be used in relevant benchmarks.

• bool useStrideN1 () const

Determines if a stride of -1 should be used in relevant benchmarks.

• bool useStrideP2 () const

Determines if a stride of +2 should be used in relevant benchmarks.

· bool useStrideN2 () const

Determines if a stride of -2 should be used in relevant benchmarks.

• bool useStrideP4 () const

Determines if a stride of +4 should be used in relevant benchmarks.

• bool useStrideN4 () const

Determines if a stride of -4 should be used in relevant benchmarks.

• bool useStrideP8 () const

Determines if a stride of +8 should be used in relevant benchmarks.

• bool useStrideN8 () const

Determines if a stride of -8 should be used in relevant benchmarks.

· bool useStrideP16 () const

Determines if a stride of +16 should be used in relevant benchmarks.

bool useStrideN16 () const

Determines if a stride of -16 should be used in relevant benchmarks.

## 5.5.1 Detailed Description

Handles all user input interpretation and generates the necessary flags for running benchmarks.

## 5.5.2 Constructor & Destructor Documentation

5.5.2.1 Configurator::Configurator ( bool runLatency, bool runThroughput, size\_t working\_set\_size\_per\_thread, uint32\_t num\_worker\_threads, bool use\_chunk\_32b, bool use\_chunk\_64b, bool use\_chunk\_128b, bool use\_chunk\_256b, bool numa\_enable, uint32\_t iterations\_per\_test, bool use\_random\_access\_pattern, bool use\_sequential\_access\_pattern, uint32\_t starting\_test\_index, std::string filename, bool use\_output\_file, bool verbose, bool use\_large\_pages, bool use\_reads, bool use\_writes, bool use\_stride\_p1, bool use\_stride\_n1, bool use\_stride\_p2, bool use\_stride\_p2, bool use\_stride\_n4, bool use\_stride\_p8, bool use\_stride\_n8, bool use\_stride\_p16, bool use\_stride\_n16

Specialized constructor for when you don't want to get config from input, and you want to pass it in directly.

## **Parameters**

runLatency	Indicates latency benchmarks should be run.
runThroughput	Indicates throughput benchmarks should be run.
working_set	The total size of memory to test in all benchmarks, in bytes, per thread. This MUST be a
size_per_thread	multiple of 4KB pages.
num_worker	The number of threads to use in throughput benchmarks, loaded latency benchmarks, and
threads	stress tests.
use_chunk_32b	If true, include 32-bit chunks for relevant benchmarks.
use_chunk_64b	If true, include 64-bit chunks for relevant benchmarks.
use_chunk	If true, include 128-bit chunks for relevant benchmarks.
128b	
use_chunk	If true, include 256-bit chunks for relevant benchmarks.
256b	
numa_enable	If true, then test all combinations of CPU/memory NUMA nodes.
iterations_per	For each unique benchmark test, this is the number of times to repeat it.
test	
use_random	If true, use random-access patterns in throughput benchmarks.
access_pattern	
use_sequential-	If true, use sequential-access patterns in throughput benchmarks.
_access_pattern	
starting_test	Numerical index to use for the first test. This is an aid for end-user interpreting and post-
index	processing of result CSV file, if relevant.
filename	Output filename to use.
use_output_file	If true, use the provided output filename.
verbose	If true, then X-Mem should be more verbose in its console reporting.
use_large	If true, then X-Mem will attempt to force usage of large pages.
pages	
1	
use_reads	If true, then throughput benchmarks should use reads.
use_writes	If true, then throughput benchmarks should use writes.
use_writes use_stride_p1	If true, then throughput benchmarks should use writes.  If true, include stride of +1 for relevant benchmarks.
use_writes use_stride_p1 use_stride_n1	If true, then throughput benchmarks should use writes.  If true, include stride of +1 for relevant benchmarks.  If true, include stride of -1 for relevant benchmarks.
use_writes use_stride_p1 use_stride_n1 use_stride_p2	If true, then throughput benchmarks should use writes.  If true, include stride of +1 for relevant benchmarks.  If true, include stride of -1 for relevant benchmarks.  If true, include stride of +2 for relevant benchmarks.
use_writes use_stride_p1 use_stride_n1 use_stride_p2 use_stride_n2	If true, then throughput benchmarks should use writes.  If true, include stride of +1 for relevant benchmarks.  If true, include stride of -1 for relevant benchmarks.  If true, include stride of +2 for relevant benchmarks.  If true, include stride of -2 for relevant benchmarks.
use_writes use_stride_p1 use_stride_n1 use_stride_p2 use_stride_n2 use_stride_p4	If true, then throughput benchmarks should use writes.  If true, include stride of +1 for relevant benchmarks.  If true, include stride of -1 for relevant benchmarks.  If true, include stride of +2 for relevant benchmarks.  If true, include stride of -2 for relevant benchmarks.  If true, include stride of +4 for relevant benchmarks.
use_writes use_stride_p1 use_stride_n1 use_stride_p2 use_stride_n2 use_stride_p4 use_stride_n4	If true, then throughput benchmarks should use writes.  If true, include stride of +1 for relevant benchmarks.  If true, include stride of -1 for relevant benchmarks.  If true, include stride of +2 for relevant benchmarks.  If true, include stride of -2 for relevant benchmarks.  If true, include stride of +4 for relevant benchmarks.  If true, include stride of -4 for relevant benchmarks.
use_writes use_stride_p1 use_stride_n1 use_stride_p2 use_stride_n2 use_stride_p4 use_stride_n4 use_stride_p8	If true, then throughput benchmarks should use writes.  If true, include stride of +1 for relevant benchmarks.  If true, include stride of -1 for relevant benchmarks.  If true, include stride of +2 for relevant benchmarks.  If true, include stride of -2 for relevant benchmarks.  If true, include stride of +4 for relevant benchmarks.  If true, include stride of -4 for relevant benchmarks.  If true, include stride of +8 for relevant benchmarks.
use_writes use_stride_p1 use_stride_p2 use_stride_n2 use_stride_p4 use_stride_p8 use_stride_n8	If true, then throughput benchmarks should use writes.  If true, include stride of +1 for relevant benchmarks.  If true, include stride of -1 for relevant benchmarks.  If true, include stride of +2 for relevant benchmarks.  If true, include stride of -2 for relevant benchmarks.  If true, include stride of +4 for relevant benchmarks.  If true, include stride of -4 for relevant benchmarks.  If true, include stride of +8 for relevant benchmarks.  If true, include stride of -8 for relevant benchmarks.
use_writes use_stride_p1 use_stride_n1 use_stride_p2 use_stride_n2 use_stride_p4 use_stride_n4 use_stride_p8	If true, then throughput benchmarks should use writes.  If true, include stride of +1 for relevant benchmarks.  If true, include stride of -1 for relevant benchmarks.  If true, include stride of +2 for relevant benchmarks.  If true, include stride of -2 for relevant benchmarks.  If true, include stride of +4 for relevant benchmarks.  If true, include stride of -4 for relevant benchmarks.  If true, include stride of +8 for relevant benchmarks.

## 5.5.3 Member Function Documentation

## 5.5.3.1 int32\_t Configurator::configureFromInput ( int argc, char \* argv[] )

Configures the tool based on user's command-line inputs.

## **Parameters**

argc	The argc from main().
argv	The argv from main().

## Returns

0 on success.

```
5.5.3.2 uint32_t xmem::Configurator::getIterationsPerTest() const [inline]
Gets the number of iterations that should be run of each benchmark.
Returns
     The iterations for each test.
5.5.3.3 uint32_t xmem::Configurator::getNumWorkerThreads() const [inline]
Gets the number of worker threads to use.
Returns
     The number of worker threads.
5.5.3.4 std::string xmem::Configurator::getOutputFilename() const [inline]
Gets the output filename to use, if applicable.
Returns
     The output filename to use if useOutputFile() returns true. Otherwise return value is "".
5.5.3.5 uint32_t xmem::Configurator::getStartingTestIndex ( ) const [inline]
Gets the numerical index of the first benchmark for CSV output purposes.
Returns
     The starting benchmark index.
5.5.3.6 size_t xmem::Configurator::getWorkingSetSizePerThread() const [inline]
Gets the working set size in bytes for each worker thread, if applicable.
Returns
     The working set size in bytes.
5.5.3.7 bool xmem::Configurator::isNUMAEnabled ( ) const [inline]
Determines if the benchmarks should test for all CPU/memory NUMA combinations.
Returns
     True if all NUMA nodes should be tested.
5.5.3.8 bool xmem::Configurator::latencyTestSelected( ) const [inline]
```

Returns

True if the latency test has been selected to run.

Indicates if the latency test has been selected.

**5.5.3.9** void xmem::Configurator::setUseOutputFile ( bool *use* ) [inline]

Changes whether an output file should be used.

#### **Parameters**

use If true, then use the output file.

5.5.3.10 bool xmem::Configurator::throughputTestSelected ( ) const [inline]

Indicates if the throughput test has been selected.

Returns

True if the throughput test has been selected to run.

5.5.3.11 bool xmem::Configurator::useChunk128b( )const [inline]

Determines if chunk size of 128 bits should be used in relevant benchmarks.

Returns

True if 128-bit chunks should be used.

5.5.3.12 bool xmem::Configurator::useChunk256b() const [inline]

Determines if chunk size of 256 bits should be used in relevant benchmarks.

Returns

True if 256-bit chunks should be used.

5.5.3.13 bool xmem::Configurator::useChunk32b ( ) const [inline]

Determines if chunk size of 32 bits should be used in relevant benchmarks.

Returns

True if 32-bit chunks should be used.

5.5.3.14 bool xmem::Configurator::useChunk64b ( ) const [inline]

Determines if chunk size of 64 bits should be used in relevant benchmarks.

Returns

True if 64-bit chunks should be used.

**5.5.3.15** bool xmem::Configurator::useLargePages ( ) const [inline]

Determines whether X-Mem should use large pages.

#### **Parameters**

True	if large pages should be used.
------	--------------------------------

```
5.5.3.16 bool xmem::Configurator::useOutputFile() const [inline]
```

Determines whether to generate an output CSV file.

#### Returns

True if an output file should be used.

```
5.5.3.17 bool xmem::Configurator::useRandomAccessPattern ( ) const [inline]
```

Determines if throughput benchmarks should use a random access pattern.

#### Returns

True if random access should be used.

```
5.5.3.18 bool xmem::Configurator::useReads ( ) const [inline]
```

Determines whether reads should be used in throughput benchmarks.

#### Returns

True if reads should be used.

```
5.5.3.19 bool xmem::Configurator::useSequentialAccessPattern() const [inline]
```

Determines if throughput benchmarks should use a sequential access pattern.

#### Returns

True if sequential access should be used.

```
5.5.3.20 bool xmem::Configurator::useStrideN1 ( ) const [inline]
```

Determines if a stride of -1 should be used in relevant benchmarks.

#### Returns

True if a stride of -1 should be used.

```
5.5.3.21 bool xmem::Configurator::useStrideN16() const [inline]
```

Determines if a stride of -16 should be used in relevant benchmarks.

## Returns

True if a stride of -16 should be used.

```
5.5.3.22 bool xmem::Configurator::useStrideN2() const [inline]
Determines if a stride of -2 should be used in relevant benchmarks.
Returns
     True if a stride of -2 should be used.
5.5.3.23 bool xmem::Configurator::useStrideN4() const [inline]
Determines if a stride of -4 should be used in relevant benchmarks.
Returns
      True if a stride of -4 should be used.
5.5.3.24 bool xmem::Configurator::useStrideN8 ( ) const [inline]
Determines if a stride of -8 should be used in relevant benchmarks.
Returns
      True if a stride of -8 should be used.
5.5.3.25 bool xmem::Configurator::useStrideP1 ( ) const [inline]
Determines if a stride of +1 should be used in relevant benchmarks.
Returns
      True if a stride of +1 should be used.
5.5.3.26 bool xmem::Configurator::useStrideP16 ( ) const [inline]
Determines if a stride of +16 should be used in relevant benchmarks.
Returns
      True if a stride of +16 should be used.
5.5.3.27 bool xmem::Configurator::useStrideP2( ) const [inline]
Determines if a stride of +2 should be used in relevant benchmarks.
Returns
      True if a stride of +2 should be used.
5.5.3.28 bool xmem::Configurator::useStrideP4( ) const [inline]
Determines if a stride of +4 should be used in relevant benchmarks.
Returns
```

True if a stride of +4 should be used.

Generated on Wed Feb 11 2015 11:56:26 for X-Mem by Doxygen

5.5.3.29 bool xmem::Configurator::useStrideP8() const [inline]

Determines if a stride of +8 should be used in relevant benchmarks.

Returns

True if a stride of +8 should be used.

5.5.3.30 bool xmem::Configurator::useWrites ( ) const [inline]

Determines whether writes should be used in throughput benchmarks.

Returns

True if writes should be used.

5.5.3.31 bool xmem::Configurator::verboseMode() const [inline]

Determines whether X-Mem is in verbose mode.

Returns


True if verbose mode is enabled.

The documentation for this class was generated from the following files:

- src/include/Configurator.h
- src/Configurator.cpp

## 5.6 xmem::Stats::CountOptionsAction Class Reference

Inheritance diagram for xmem::Stats::CountOptionsAction:



#### **Public Member Functions**

- CountOptionsAction (unsigned \*buffer\_max\_)
- bool perform (Option &)

Called by Parser::workhorse() for each Option that has been successfully parsed (including unknown options if they have a Descriptor whose Descriptor::check\_arg does not return ARG\_ILLEGAL.

#### 5.6.1 Constructor & Destructor Documentation

5.6.1.1 xmem::Stats::CountOptionsAction::CountOptionsAction ( unsigned \* buffer\_max\_ ) [inline]

Creates a new CountOptionsAction that will increase \*buffer\_max\_ for each parsed Option.

## 5.6.2 Member Function Documentation

```
5.6.2.1 bool xmem::Stats::CountOptionsAction::perform(Option & ) [inline], [virtual]
```

Called by Parser::workhorse() for each Option that has been successfully parsed (including unknown options if they have a Descriptor whose Descriptor::check arg does not return ARG ILLEGAL.

Returns false iff a fatal error has occured and the parse should be aborted.

Reimplemented from xmem::Parser::Action.

The documentation for this class was generated from the following file:

src/include/optionparser.h

## 5.7 xmem::Descriptor Struct Reference

Describes an option, its help text (usage) and how it should be parsed.

```
#include <optionparser.h>
```

#### **Public Attributes**

· const unsigned index

Index of this option's linked list in the array filled in by the parser.

· const int type

Used to distinguish between options with the same index. See index for details.

const char \*const shortopt

Each char in this string will be accepted as a short option character.

const char \*const longopt

The long option name (without the leading - ).

const CheckArg check\_arg

For each option that matches shortopt or longopt this function will be called to check a potential argument to the option.

const char \* help

The usage text associated with the options in this Descriptor.

#### 5.7.1 Detailed Description

Describes an option, its help text (usage) and how it should be parsed.

The main input when constructing an option::Parser is an array of Descriptors.

#### Example:

#### 5.7.2 Member Data Documentation

#### 5.7.2.1 const CheckArg xmem::Descriptor::check\_arg

For each option that matches shortopt or longopt this function will be called to check a potential argument to the option.

This function will be called even if there is no potential argument. In that case it will be passed NULL as arg parameter. Do not confuse this with the empty string.

See CheckArg for more information.

#### 5.7.2.2 const char\* xmem::Descriptor::help

The usage text associated with the options in this Descriptor.

You can use option::printUsage() to format your usage message based on the help texts. You can use dummy Descriptors where shortopt and longopt are both the empty string to add text to the usage that is not related to a specific option.

See option::printUsage() for special formatting characters you can use in help to get a column layout.

#### Attention

Must be UTF-8-encoded. If your compiler supports C++11 you can use the "u8" prefix to make sure string literals are properly encoded.

#### 5.7.2.3 const unsigned xmem::Descriptor::index

Index of this option's linked list in the array filled in by the parser.

Command line options whose Descriptors have the same index will end up in the same linked list in the order in which they appear on the command line. If you have multiple long option aliases that refer to the same option, give their descriptors the same index.

If you have options that mean exactly opposite things (e.g. <code>-enable-foo</code> and <code>-disable-foo</code>), you should also give them the same <code>index</code>, but distinguish them through different values for type. That way they end up in the same list and you can just take the last element of the list and use its type. This way you get the usual behaviour where switches later on the command line override earlier ones without having to code it manually.

Tip:

Use an enum rather than plain ints for better readability, as shown in the example at Descriptor.

#### 5.7.2.4 const char\* const xmem::Descriptor::longopt

The long option name (without the leading – ).

If this Descriptor should not have a long option name, use the empty string "". NULL is not permitted here!

While shortopt allows multiple short option characters, each Descriptor can have only a single long option name. If you have multiple long option names referring to the same option use separate Descriptors that have the same index and type. You may repeat short option characters in such an alias Descriptor but there's no need to.

## **Dummy Descriptors:**

You can use dummy Descriptors with an empty string for both shortopt and longopt to add text to the usage that is not related to a specific option. See help. The first dummy Descriptor will be used for unknown options (see below).

**Unknown Option Descriptor:** 

The first dummy Descriptor in the list of Descriptors, whose shortopt and longopt are both the empty string, will be used as the Descriptor for unknown options. An unknown option is a string in the argument vector that is not a lone minus '-' but starts with a minus character and does not match any Descriptor's shortopt or longopt. Note that the dummy descriptor's check\_arg function will be called and its return value will be evaluated as usual. I.e. if it returns ARG\_ILLEGAL the parsing will be aborted with Parser::error() ==true. if check\_arg does not return ARG\_ILLEGAL the descriptor's index will be used to pick the linked list into which to put the unknown option.

If there is no dummy descriptor, unknown options will be dropped silently.

#### 5.7.2.5 const char\* const xmem::Descriptor::shortopt

Each char in this string will be accepted as a short option character.

The string must not include the minus character '-' or you'll get undefined behaviour.

If this Descriptor should not have short option characters, use the empty string "". NULL is not permitted here! See longopt for more information.

#### 5.7.2.6 const int xmem::Descriptor::type

Used to distinguish between options with the same index. See index for details.


It is recommended that you use an enum rather than a plain int to make your code more readable.

The documentation for this struct was generated from the following file:

· src/include/optionparser.h

# 5.8 xmem::ExampleArg Class Reference

Inheritance diagram for xmem::ExampleArg:



#### Static Public Member Functions


- static void printError (const char \*msg1, const Option &opt, const char \*msg2)
- static ArgStatus Unknown (const Option & option, bool msg)
- static ArgStatus Required (const Option & option, bool msg)
- static ArgStatus NonEmpty (const Option & option, bool msg)

The documentation for this class was generated from the following file:

• src/include/ExampleArg.h

# 5.9 xmem::PrintUsageImplementation::FunctionWriter< Function > Struct Template Reference

Inheritance diagram for xmem::PrintUsageImplementation::FunctionWriter< Function >:



#### **Public Member Functions**

- virtual void operator() (const char \*str, int size)
   Writes the given number of chars beginning at the given pointer somewhere.
- FunctionWriter (Function \*w)

#### **Public Attributes**

• Function \* write

The documentation for this struct was generated from the following file:

· src/include/optionparser.h

# 5.10 xmem::PrintUsageImplementation::IStringWriter Struct Reference

Inheritance diagram for xmem::PrintUsageImplementation::IStringWriter:



### **Public Member Functions**

virtual void operator() (const char \*, int)
 Writes the given number of chars beginning at the given pointer somewhere.

The documentation for this struct was generated from the following file:


• src/include/optionparser.h

## 5.11 xmem::LatencyBenchmark Class Reference

A type of benchmark that measures unloaded memory latency via random pointer chasing.

#include <LatencyBenchmark.h>

Inheritance diagram for xmem::LatencyBenchmark:



## **Public Member Functions**

LatencyBenchmark (void \*mem\_array, size\_t len, uint32\_t iterations, uint32\_t num\_worker\_threads, uint32\_t mem\_node, uint32\_t cpu\_node, pattern\_mode\_t pattern\_mode, rw\_mode\_t rw\_mode, chunk\_size\_t chunk\_size, int64\_t stride\_size, std::vector< PowerReader \* > dram\_power\_readers, std::string name)

Constructor. Parameters are passed directly to the Benchmark constructor. See Benchmark class documentation for parameter semantics.

virtual ~LatencyBenchmark ()

Destructor.

#### **Protected Member Functions**

virtual bool run core ()

The core benchmark function.

#### **Additional Inherited Members**

## 5.11.1 Detailed Description

A type of benchmark that measures unloaded memory latency via random pointer chasing.

#### 5.11.2 Member Function Documentation

**5.11.2.1** bool LatencyBenchmark::\_run\_core() [protected], [virtual]

The core benchmark function.

Returns

True on success.

Implements xmem::Benchmark.

The documentation for this class was generated from the following files:

- src/include/LatencyBenchmark.h
- src/LatencyBenchmark.cpp

## 5.12 xmem::PrintUsageImplementation::LinePartIterator Class Reference

## **Public Member Functions**

· LinePartIterator (const Descriptor usage[])

Creates an iterator for usage.

bool nextTable ()

Moves iteration to the next table (if any). Has to be called once on a new LinePartIterator to move to the 1st table.

• void restartTable ()

Reset iteration to the beginning of the current table.

• bool nextRow ()

Moves iteration to the next row (if any). Has to be called once after each call to nextTable() to move to the 1st row of the table.

· void restartRow ()

Reset iteration to the beginning of the current row.

bool next ()

Moves iteration to the next part (if any). Has to be called once after each call to nextRow() to move to the 1st part of the row.

• int column ()

Returns the index (counting from 0) of the column in which the part pointed to by data() is located.

• int line ()

Returns the index (counting from 0) of the line within the current column this part belongs to.

• int length ()

Returns the length of the part pointed to by data() in raw chars (not UTF-8 characters).

• int screenLength ()

Returns the width in screen columns of the part pointed to by data(). Takes multi-byte UTF-8 sequences and wide characters into account.

const char \* data ()

Returns the current part of the iteration.

#### 5.12.1 Member Function Documentation

5.12.1.1 bool xmem::PrintUsageImplementation::LinePartIterator::next() [inline]

Moves iteration to the next part (if any). Has to be called once after each call to nextRow() to move to the 1st part of the row.

Return values

false	if moving to next part failed because no further part exists.

See LinePartIterator for details about the iteration.

5.12.1.2 bool xmem::PrintUsageImplementation::LinePartIterator::nextRow() [inline]

Moves iteration to the next row (if any). Has to be called once after each call to nextTable() to move to the 1st row of the table.

**Return values** 

false if moving to next row failed because no further row exists.
---

#### 5.12.1.3 bool xmem::PrintUsageImplementation::LinePartIterator::nextTable() [inline]

Moves iteration to the next table (if any). Has to be called once on a new LinePartIterator to move to the 1st table.

Return values

false	if moving to next table failed because no further table exists.

The documentation for this class was generated from the following file:

· src/include/optionparser.h

## 5.13 xmem::PrintUsageImplementation::LineWrapper Class Reference

#### **Public Member Functions**

• void flush (IStringWriter &write)

Writes out all remaining data from the LineWrapper using write. Unlike process() this method indents all lines including the first and will output a \n at the end (but only if something has been written).

void process (IStringWriter &write, const char \*data, int len)

Process, wrap and output the next piece of data.

LineWrapper (int x1, int x2)

Constructs a LineWrapper that wraps its output to fit into screen columns x1 (incl.) to x2 (excl.).

#### 5.13.1 Constructor & Destructor Documentation

5.13.1.1 xmem::PrintUsageImplementation::LineWrapper::LineWrapper (int x1, int x2) [inline]

Constructs a LineWrapper that wraps its output to fit into screen columns x1 (incl.) to x2 (excl.).

x1 gives the indentation LineWrapper uses if it needs to indent.

#### 5.13.2 Member Function Documentation

5.13.2.1 void xmem::PrintUsageImplementation::LineWrapper::process ( IStringWriter & write, const char \* data, int len ) [inline]

Process, wrap and output the next piece of data.

process() will output at least one line of output. This is not necessarily the data passed in. It may be data queued from a prior call to process(). If the internal buffer is full, more than 1 line will be output.

process() assumes that the a proper amount of indentation has already been output. It won't write any further indentation before the 1st line. If more than 1 line is written due to buffer constraints, the lines following the first will be indented by this method, though.

No \n is written by this method after the last line that is written.

#### **Parameters**

write	where to write the data.
data	the new chunk of data to write.
len	the length of the chunk of data to write.

The documentation for this class was generated from the following file:


· src/include/optionparser.h

## 5.14 xmem::LoadWorker Class Reference

Multithreading-friendly class to do memory loading.

#include <LoadWorker.h>

Inheritance diagram for xmem::LoadWorker:



#### **Public Member Functions**

• LoadWorker (void \*mem\_array, size\_t len, SequentialFunction kernel\_fptr, SequentialFunction kernel\_tummy\_fptr, int32\_t cpu\_affinity)

Constructor for sequential-access patterns.

LoadWorker (void \*mem\_array, size\_t len, RandomFunction kernel\_fptr, RandomFunction kernel\_dummy\_fptr, int32\_t cpu\_affinity)

Constructor for random-access patterns.

virtual ~LoadWorker ()

Destructor.

• virtual void run ()

Thread-safe worker method.

## **Additional Inherited Members**

#### 5.14.1 Detailed Description

Multithreading-friendly class to do memory loading.

## 5.14.2 Constructor & Destructor Documentation

5.14.2.1 LoadWorker::LoadWorker ( void \* mem\_array, size\_t len, SequentialFunction kernel\_fptr, SequentialFunction kernel\_dummy\_fptr, int32\_t cpu\_affinity )

Constructor for sequential-access patterns.

## Parameters

mem_array	Pointer to the memory region to use by this worker.
len	Length of the memory region to use by this worker.
kernel_fptr	Pointer to the sequential core benchmark kernel to use.
kernel_dummy	Pointer to the sequential dummy version of the core benchmark kernel to use.
fptr	
cpu_affinity	Logical CPU identifier to lock this worker's thread to.

5.14.2.2 LoadWorker::LoadWorker ( void \* mem\_array, size\_t len, RandomFunction kernel\_fptr, RandomFunction kernel\_dummy\_fptr, int32\_t cpu\_affinity )

Constructor for random-access patterns.

#### **Parameters**

mem_array	Pointer to the memory region to use by this worker.
len	Length of the memory region to use by this worker.
kernel_fptr	Pointer to the random core benchmark kernel to use.
kernel_dummy	Pointer to the random dummy version of the core benchmark kernel to use.
fptr	
cpu_affinity	Logical CPU identifier to lock this worker's thread to.

The documentation for this class was generated from the following files:


- src/include/LoadWorker.h
- src/LoadWorker.cpp

# 5.15 xmem::MemoryWorker Class Reference

Multithreading-friendly class to run memory access kernels.

#include <MemoryWorker.h>

Inheritance diagram for xmem::MemoryWorker:



#### **Public Member Functions**

• MemoryWorker (void \*mem\_array, size\_t len, int32\_t cpu\_affinity)

Constructor.

virtual ∼MemoryWorker ()

Destructor.

• virtual void run ()=0

Thread-safe worker method.

size\_t getLen ()

Gets the length of the memory region used by this worker.

• uint64\_t getBytesPerPass ()

Gets the number of bytes used in each pass of the benchmark by this worker.

• uint64\_t getPasses ()

Gets the number of passes for this worker.

uint64\_t getElapsedTicks ()

Gets the elapsed ticks for this worker on the core benchmark kernel.

• uint64\_t getElapsedDummyTicks ()

Gets the elapsed ticks for this worker on the dummy version of the core benchmark kernel.

• uint64\_t getAdjustedTicks ()

Gets the adjusted ticks for this worker. This is elapsed ticks minus elapsed dummy ticks.

• bool hadWarning ()

Indicates whether worker's results may be questionable/inaccurate/invalid.

## **Protected Attributes**

- void \* \_mem\_array
- size t len
- int32\_t \_cpu\_affinity
- uint64\_t \_bytes\_per\_pass
- uint64\_t \_passes
- uint64\_t \_elapsed\_ticks
- uint64\_t \_elapsed\_dummy\_ticks
- uint64\_t \_adjusted\_ticks
- · bool \_warning
- bool \_completed

## **Additional Inherited Members**

## 5.15.1 Detailed Description

Multithreading-friendly class to run memory access kernels.

#### 5.15.2 Constructor & Destructor Documentation

5.15.2.1 MemoryWorker::MemoryWorker ( void \* mem\_array, size\_t len, int32\_t cpu\_affinity )

#### Constructor.

#### **Parameters**

mem_array	Pointer to the memory region to use by this worker.
len	Length of the memory region to use by this worker.
passes_per	for size-based benchmarking, this is the number of passes to execute in a single benchmark
iteration	iteration.
cpu_affinity	Logical CPU identifier to lock this worker's thread to.

## 5.15.3 Member Function Documentation

### 5.15.3.1 uint64\_t MemoryWorker::getAdjustedTicks ( )

Gets the adjusted ticks for this worker. This is elapsed ticks minus elapsed dummy ticks.

#### Returns

The adjusted ticks for this worker.

## 5.15.3.2 uint64\_t MemoryWorker::getBytesPerPass ( )

Gets the number of bytes used in each pass of the benchmark by this worker.

## Returns

Number of bytes in each pass.

```
5.15.3.3 uint64_t MemoryWorker::getElapsedDummyTicks ( )
Gets the elapsed ticks for this worker on the dummy version of the core benchmark kernel.
Returns
     The number of elapsed dummy ticks.
5.15.3.4 uint64_t MemoryWorker::getElapsedTicks ( )
Gets the elapsed ticks for this worker on the core benchmark kernel.
Returns
     The number of elapsed ticks.
5.15.3.5 size_t MemoryWorker::getLen()
Gets the length of the memory region used by this worker.
Returns
     Length of memory region in bytes.
5.15.3.6 uint64_t MemoryWorker::getPasses ( )
Gets the number of passes for this worker.
Returns
     The number of passes.
5.15.3.7 bool MemoryWorker::hadWarning ( )
Indicates whether worker's results may be questionable/inaccurate/invalid.
Returns
     True if the worker's results had a warning.
5.15.4 Member Data Documentation
5.15.4.1 uint64_t xmem::MemoryWorker::_adjusted_ticks [protected]
Elapsed ticks minus dummy elapsed ticks.
5.15.4.2 uint64_t xmem::MemoryWorker::_bytes_per_pass [protected]
Number of bytes accessed in each kernel pass.
5.15.4.3 bool xmem::MemoryWorker::_completed [protected]
```

If true, worker completed.

**5.15.4.4** int32\_t xmem::MemoryWorker::\_cpu\_affinity [protected]

The logical CPU affinity for this worker.

**5.15.4.5 uint64\_t xmem::MemoryWorker::\_elapsed\_dummy\_ticks** [protected]

Total elapsed ticks on the dummy kernel routine.

**5.15.4.6** uint64\_t xmem::MemoryWorker::\_elapsed\_ticks [protected]

Total elapsed ticks on the kernel routine.

**5.15.4.7 size\_t xmem::MemoryWorker::\_len** [protected]

The length of the memory region for this worker.

**5.15.4.8 void\* xmem::MemoryWorker::\_mem\_array** [protected]

The memory region for this worker.

**5.15.4.9 uint64\_t xmem::MemoryWorker::\_passes** [protected]

Number of passes.

**5.15.4.10** bool xmem::MemoryWorker::\_warning [protected]


If true, results may be suspect.

The documentation for this class was generated from the following files:

- src/include/MemoryWorker.h
- src/MemoryWorker.cpp

## 5.16 xmem::MyArg Class Reference

Inheritance diagram for xmem::MyArg:



## **Static Public Member Functions**

- static ArgStatus Integer (const Option & option, bool msg)

  Checks an option that it is an integer.
- static ArgStatus NonnegativeInteger (const Option & option, bool msg)

Checks an option that it is a nonnegative integer.

static ArgStatus PositiveInteger (const Option &option, bool msg)

Checks an option that it is a positive integer.

The documentation for this class was generated from the following file:

src/include/MyArg.h

## 5.17 xmem::Option Class Reference

A parsed option from the command line together with its argument if it has one.

```
#include <optionparser.h>
```

#### **Public Member Functions**

· int type () const

Returns Descriptor::type of this Option's Descriptor, or 0 if this Option is invalid (unused).

• int index () const

Returns Descriptor::index of this Option's Descriptor, or -1 if this Option is invalid (unused).

• int count ()

Returns the number of times this Option (or others with the same Descriptor::index) occurs in the argument vector.

· bool isFirst () const

Returns true iff this is the first element of the linked list.

• bool isLast () const

Returns true iff this is the last element of the linked list.

Option \* first ()

Returns a pointer to the first element of the linked list.

Option \* last ()

Returns a pointer to the last element of the linked list.

Option \* prev ()

Returns a pointer to the previous element of the linked list or NULL if called on first().

Option \* prevwrap ()

Returns a pointer to the previous element of the linked list with wrap-around from first() to last().

• Option \* next ()

Returns a pointer to the next element of the linked list or NULL if called on last().

Option \* nextwrap ()

Returns a pointer to the next element of the linked list with wrap-around from last() to first().

void append (Option \*new\_last)

Makes new\_last the new last() by chaining it into the list after last().

• operator const Option \* () const

Casts from Option to const Option\* but only if this Option is valid.

operator Option \* ()

Casts from Option to Option\* but only if this Option is valid.

• Option ()

Creates a new Option that is a one-element linked list and has NULL desc, name, arg and namelen.

Option (const Descriptor \*desc\_, const char \*name\_, const char \*arg\_)

Creates a new Option that is a one-element linked list and has the given values for desc, name and arg.

void operator= (const Option &orig)

Makes \*this a copy of orig except for the linked list pointers.

• Option (const Option &orig)

Makes \*this a copy of orig except for the linked list pointers.

#### **Public Attributes**

• const Descriptor \* desc

Pointer to this Option's Descriptor.

• const char \* name

The name of the option as used on the command line.

· const char \* arg

Pointer to this Option's argument (if any).

· int namelen

The length of the option name.

#### 5.17.1 Detailed Description

A parsed option from the command line together with its argument if it has one.

The Parser chains all parsed options with the same Descriptor::index together to form a linked list. This allows you to easily implement all of the common ways of handling repeated options and enable/disable pairs.

• Test for presence of a switch in the argument vector:

```
if ( options[QUIET] ) ...
```

• Evaluate –enable-foo/–disable-foo pair where the last one used wins:

```
if ( options[FOO].last()->type() == DISABLE ) ...
```

• Cumulative option (-v verbose, -vv more verbose, -vvv even more verbose):

```
int verbosity = options[VERBOSE].count();
```

Iterate over all –file=<fname> arguments:

```
for (Option* opt = options[FILE]; opt; opt = opt->next())
fname = opt->arg; ...
```

#### 5.17.2 Constructor & Destructor Documentation

```
5.17.2.1 xmem::Option:Option (const Descriptor * desc_, const char * name_, const char * arg_ ) [inline]
```

Creates a new Option that is a one-element linked list and has the given values for desc, name and arg.

If name\_points at a character other than '-' it will be assumed to refer to a short option and namelen will be set to 1. Otherwise the length will extend to the first '=' character or the string's 0-terminator.

```
5.17.2.2 xmem::Option:Option (const Option & orig) [inline]
```

Makes \*this a copy of orig except for the linked list pointers.

After this operation \*this will be a one-element linked list.

## 5.17.3 Member Function Documentation

```
5.17.3.1 void xmem::Option::append (Option * new_last ) [inline]
```

Makes new\_last the new last() by chaining it into the list after last().

It doesn't matter which element you call append() on. The new element will always be appended to last().

#### Attention

new\_last must not yet be part of a list, or that list will become corrupted, because this method does not unchain new\_last from an existing list.

```
5.17.3.2 int xmem::Option::count() [inline]
```

Returns the number of times this Option (or others with the same Descriptor::index) occurs in the argument vector.

This corresponds to the number of elements in the linked list this Option is part of. It doesn't matter on which element you call count(). The return value is always the same.

Use this to implement cumulative options, such as -v, -vv, -vvv for different verbosity levels.

Returns 0 when called for an unused/invalid option.

```
5.17.3.3 Option* xmem::Option::first() [inline]
```

Returns a pointer to the first element of the linked list.

Use this when you want the first occurrence of an option on the command line to take precedence. Note that this is not the way most programs handle options. You should probably be using last() instead.

Note

This method may be called on an unused/invalid option and will return a pointer to the option itself.

```
5.17.3.4 bool xmem::Option::isFirst() const [inline]
```

Returns true iff this is the first element of the linked list.

The first element in the linked list is the first option on the command line that has the respective Descriptor::index value.

Returns true for an unused/invalid option.

```
5.17.3.5 bool xmem::Option::isLast() const [inline]
```

Returns true iff this is the last element of the linked list.

The last element in the linked list is the last option on the command line that has the respective Descriptor::index value.

Returns true for an unused/invalid option.

```
5.17.3.6 Option* xmem::Option::last() [inline]
```

Returns a pointer to the last element of the linked list.

Use this when you want the last occurrence of an option on the command line to take precedence. This is the most common way of handling conflicting options.

Note

This method may be called on an unused/invalid option and will return a pointer to the option itself.

Tip:

If you have options with opposite meanings (e.g. -enable-foo and -disable-foo), you can assign them the same Descriptor::index to get them into the same list. Distinguish them by Descriptor::type and all you have to do is check last () ->type () to get the state listed last on the command line.

```
5.17.3.7 Option* xmem::Option::next() [inline]
```

Returns a pointer to the next element of the linked list or NULL if called on last().

If called on last() this method returns NULL. Otherwise it will return the option with the same Descriptor::index that follows this option on the command line.

```
5.17.3.8 Option* xmem::Option::nextwrap() [inline]
```

Returns a pointer to the next element of the linked list with wrap-around from last() to first().

If called on last() this method returns first(). Otherwise it will return the option with the same Descriptor::index that follows this option on the command line.

```
5.17.3.9 xmem::Option::operator const Option * ( ) const [inline]
```

Casts from Option to const Option\* but only if this Option is valid.

If this Option is valid (i.e. desc!=NULL), returns this. Otherwise returns NULL. This allows testing an Option directly in an if-clause to see if it is used:

```
if (options[CREATE])
{
    ...
```

It also allows you to write loops like this:

```
for (Option* opt = options[FILE]; opt; opt = opt->next())
fname = opt->arg; ...
```

```
5.17.3.10 xmem::Option::operator Option * ( ) [inline]
```

Casts from Option to Option\* but only if this Option is valid.

If this Option is valid (i.e. desc!=NULL), returns this. Otherwise returns NULL. This allows testing an Option directly in an if-clause to see if it is used:

```
if (options[CREATE])
{
    ...
}
```

It also allows you to write loops like this:

```
for (Option* opt = options[FILE]; opt; opt = opt->next())
fname = opt->arg; ...
```

```
5.17.3.11 void xmem::Option::operator=( const Option & orig ) [inline]
```

Makes \*this a copy of orig except for the linked list pointers.

After this operation \*this will be a one-element linked list.

```
5.17.3.12 Option* xmem::Option::prev() [inline]
```

Returns a pointer to the previous element of the linked list or NULL if called on first().

If called on first() this method returns NULL. Otherwise it will return the option with the same Descriptor::index that precedes this option on the command line.

```
5.17.3.13 Option* xmem::Option::prevwrap() [inline]
```

Returns a pointer to the previous element of the linked list with wrap-around from first() to last().

If called on first() this method returns last(). Otherwise it will return the option with the same Descriptor::index that precedes this option on the command line.

```
5.17.3.14 int xmem::Option::type() const [inline]
```

Returns Descriptor::type of this Option's Descriptor, or 0 if this Option is invalid (unused).

Because this method (and last(), too) can be used even on unused Options with desc==0, you can (provided you arrange your types properly) switch on type() without testing validity first.

#### 5.17.4 Member Data Documentation

#### 5.17.4.1 const char\* xmem::Option::arg

Pointer to this Option's argument (if any).

NULL if this option has no argument. Do not confuse this with the empty string which is a valid argument.

```
5.17.4.2 const Descriptor* xmem::Option::desc
```

Pointer to this Option's Descriptor.

Remember that the first dummy descriptor (see Descriptor::longopt) is used for unknown options.

#### Attention

desc==NULL signals that this Option is unused. This is the default state of elements in the result array. You don't need to test desc explicitly. You can simply write something like this:

```
if (options[CREATE])
{
    ...
}
```

This works because of operator const Option\*() .

#### 5.17.4.3 const char\* xmem::Option::name

The name of the option as used on the command line.

The main purpose of this string is to be presented to the user in messages.

In the case of a long option, this is the actual argv pointer, i.e. the first character is a '-'. In the case of a short option this points to the option character within the argv string.

Note that in the case of a short option group or an attached option argument, this string will contain additional characters following the actual name. Use namelen to filter out the actual option name only.

#### 5.17.4.4 int xmem::Option::namelen

The length of the option name.

Because name points into the actual argv string, the option name may be followed by more characters (e.g. other short options in the same short option group). This value is the number of bytes (not characters!) that are part of the actual name.

For a short option, this length is always 1. For a long option this length is always at least 2 if single minus long options are permitted and at least 3 if they are disabled.

#### Note


In the pathological case of a minus within a short option group (e.g. -xf-z), this length is incorrect, because this case will be misinterpreted as a long option and the name will therefore extend to the string's 0-terminator or a following '=" character if there is one. This is irrelevant for most uses of name and namelen. If you really need to distinguish the case of a long and a short option, compare name to the argv pointers. A long option's name is always identical to one of them, whereas a short option's is never.

The documentation for this class was generated from the following file:

· src/include/optionparser.h

# 5.18 xmem::PrintUsageImplementation::OStreamWriter< OStream > Struct Template Reference

Inheritance diagram for xmem::PrintUsageImplementation::OStreamWriter< OStream >:



#### **Public Member Functions**

- virtual void operator() (const char \*str, int size)
  - Writes the given number of chars beginning at the given pointer somewhere.
- OStreamWriter (OStream &o)

#### **Public Attributes**

· OStream & ostream

The documentation for this struct was generated from the following file:

· src/include/optionparser.h

## 5.19 xmem::Parser Class Reference

Checks argument vectors for validity and parses them into data structures that are easier to work with.

```
#include <optionparser.h>
```

#### Classes

- struct Action
- · class StoreOptionAction

#### **Public Member Functions**

• Parser ()

Creates a new Parser.

Parser (bool gnu, const Descriptor usage[], int argc, const char \*\*argv, Option options[], Option buffer[], int min\_abbr\_len=0, bool single\_minus\_longopt=false, int bufmax=-1)

Creates a new Parser and immediately parses the given argument vector.

Parser (bool gnu, const Descriptor usage[], int argc, char \*\*argv, Option options[], Option buffer[], int min\_abbr\_len=0, bool single\_minus\_longopt=false, int bufmax=-1)

Parser(...) with non-const argv.

Parser (const Descriptor usage[], int argc, const char \*\*argv, Option options[], Option buffer[], int min\_abbr\_len=0, bool single\_minus\_longopt=false, int bufmax=-1)

```
POSIX Parser(...) (gnu==false).
```

• Parser (const Descriptor usage[], int argc, char \*\*argv, Option options[], Option buffer[], int min\_abbr\_len=0, bool single\_minus\_longopt=false, int bufmax=-1)

```
POSIX Parser(...) (gnu==false) with non-const argv.
```

• void parse (bool gnu, const Descriptor usage[], int argc, const char \*\*argv, Option options[], Option buffer[], int min\_abbr\_len=0, bool single\_minus\_longopt=false, int bufmax=-1)

Parses the given argument vector.

• void parse (bool gnu, const Descriptor usage[], int argc, char \*\*argv, Option options[], Option buffer[], int min\_abbr\_len=0, bool single\_minus\_longopt=false, int bufmax=-1)

```
parse() with non-const argv.
```

• void parse (const Descriptor usage[], int argc, const char \*\*argv, Option options[], Option buffer[], int min\_abbr len=0, bool single minus longopt=false, int bufmax=-1)

POSIX parse() (gnu==false).

• void parse (const Descriptor usage[], int argc, char \*\*argv, Option options[], Option buffer[], int min\_abbr\_- len=0, bool single minus longopt=false, int bufmax=-1)

POSIX parse() (gnu==false) with non-const argv.

• int optionsCount ()

Returns the number of valid Option objects in buffer[].

• int nonOptionsCount ()

Returns the number of non-option arguments that remained at the end of the most recent parse() that actually encountered non-option arguments.

```
• const char ** nonOptions ()
```

Returns a pointer to an array of non-option arguments (only valid if nonOptionsCount() > 0).

• const char \* nonOption (int i)

Returns nonOptions()[i] (without checking if i is in range!).

• bool error ()

Returns true if an unrecoverable error occurred while parsing options.

#### **Friends**

• struct Stats

#### 5.19.1 Detailed Description

Checks argument vectors for validity and parses them into data structures that are easier to work with.

#### Example:

```
int main(int argc, char* argv[])
{
   argc-=(argc>0);   argv+=(argc>0);   // skip program name argv[0] if present
   option::Stats stats(usage, argc, argv);
   option::Option options[stats.options_max], buffer[stats.buffer_max];
   option::Parser parse(usage, argc, argv, options, buffer);

if (parse.error())
   return 1;

if (options[HELP])
...
```

#### 5.19.2 Constructor & Destructor Documentation

5.19.2.1 xmem::Parser::Parser ( bool gnu, const Descriptor usage[], int argc, const char \*\* argv, Option options[],

Option buffer[], int min\_abbr\_len = 0, bool single\_minus\_longopt = false, int bufmax = -1) [inline]

Creates a new Parser and immediately parses the given argument vector.

#### **Parameters**

if true, parse() will not stop at the first non-option argument. Instead it will reorder arguments
so that all non-options are at the end. This is the default behaviour of GNU getopt() but is not
conforming to POSIX.
Note, that once the argument vector has been reordered, the gnu flag will have no further
effect on this argument vector. So it is enough to pass gnu==true when creating Stats.
Array of Descriptor objects that describe the options to support. The last entry of this array
must have 0 in all fields.
The number of elements from argv that are to be parsed. If you pass -1, the number will be
determined automatically. In that case the argv list must end with a NULL pointer.
The arguments to be parsed. If you pass -1 as argc the last pointer in the argv list must
be NULL to mark the end.
Each entry is the first element of a linked list of Options. Each new option that is parsed will
be appended to the list specified by that Option's Descriptor::index. If an entry is not yet used
(i.e. the Option is invalid), it will be replaced rather than appended to.
The minimum length of this array is the greatest Descriptor::index value that occurs in usage
PLUS ONE.

buffer	Each argument that is successfully parsed (including unknown arguments, if they have a Descriptor whose CheckArg does not return ARG ILLEGAL) will be stored in this array. parse()
	scans the array for the first invalid entry and begins writing at that index. You can pass
	bufmax to limit the number of options stored.
min_abbr_len	Passing a value min_abbr_len > 0 enables abbreviated long options. The parser
	will match a prefix of a long option as if it was the full long option (e.gfoob=10 will be
	interpreted as if it was -foobar=10), as long as the prefix has at least min_abbr_len
	characters (not counting the - ) and is unambiguous.
	Be careful if combining min_abbr_len=1 with single_minus_longopt=true be-
	cause the ambiguity check does not consider short options and abbreviated single minus
	long options will take precedence over short options.
single_minus	Passing true for this option allows long options to begin with a single minus. The double
longopt	minus form will still be recognized. Note that single minus long options take precedence over
	short options and short option groups. E.gfile would be interpreted as -file and not
	as -f -i -l -e (assuming a long option named "file" exists).
bufmax	The greatest index in the buffer[] array that parse() will write to is bufmax-1. If there
	are more options, they will be processed (in particular their CheckArg will be called) but not
	stored.
	If you used Stats::buffer_max to dimension this array, you can pass -1 (or not pass bufmax
	at all) which tells parse() that the buffer is "large enough".

#### Attention

Remember that options and buffer store Option objects, not pointers. Therefore it is not possible for the same object to be in both arrays. For those options that are found in both buffer[] and options[] the respective objects are independent copies. And only the objects in options[] are properly linked via Option::next() and Option::prev(). You can iterate over buffer[] to process all options in the order they appear in the argument vector, but if you want access to the other Options with the same Descriptor::index, then you must access the linked list via options[]. You can get the linked list in options from a buffer object via something like options[buffer[i].index()].

#### 5.19.3 Member Function Documentation

```
5.19.3.1 bool xmem::Parser::error() [inline]
```

Returns  ${\tt true}$  if an unrecoverable error occurred while parsing options.

An illegal argument to an option (i.e. CheckArg returns ARG\_ILLEGAL) is an unrecoverable error that aborts the parse. Unknown options are only an error if their CheckArg function returns ARG\_ILLEGAL. Otherwise they are collected. In that case if you want to exit the program if either an illegal argument or an unknown option has been passed, use code like this

```
if (parser.error() || options[UNKNOWN])
  exit(1):
```

5.19.3.2 const char\*\* xmem::Parser::nonOptions() [inline]

Returns a pointer to an array of non-option arguments (only valid if nonOptionsCount () >0 ).

#### Note

- parse() does not copy arguments, so this pointer points into the actual argument vector as passed to parse().
- As explained at nonOptionsCount() this pointer is only changed by parse() calls that actually encounter non-option arguments. A parse() call that encounters only options, will not change nonOptions().

```
5.19.3.3 int xmem::Parser::nonOptionsCount() [inline]
```

Returns the number of non-option arguments that remained at the end of the most recent parse() that actually encountered non-option arguments.

#### Note

A parse() that does not encounter non-option arguments will leave this value as well as nonOptions() undisturbed. This means you can feed the Parser a default argument vector that contains non-option arguments (e.g. a default filename). Then you feed it the actual arguments from the user. If the user has supplied at least one non-option argument, all of the non-option arguments from the default disappear and are replaced by the user's non-option arguments. However, if the user does not supply any non-option arguments the defaults will still be in effect.

```
5.19.3.4 int xmem::Parser::optionsCount() [inline]
```

Returns the number of valid Option objects in buffer[].

#### Note

- The returned value always reflects the number of Options in the buffer[] array used for the most recent call to parse().
- The count (and the buffer[]) includes unknown options if they are collected (see Descriptor::longopt).

5.19.3.5 void xmem::Parser::parse ( bool gnu, const Descriptor usage[], int argc, const char \*\* argv, Option options[],

Option buffer[], int min\_abbr\_len = 0, bool single\_minus\_longopt = false, int bufmax = -1) [inline]

Parses the given argument vector.

#### **Parameters**

gnu	if true, parse() will not stop at the first non-option argument. Instead it will reorder arguments so that all non-options are at the end. This is the default behaviour of GNU getopt() but is not conforming to POSIX.  Note, that once the argument vector has been reordered, the gnu flag will have no further
	effect on this argument vector. So it is enough to pass gnu==true when creating Stats.
usage	Array of Descriptor objects that describe the options to support. The last entry of this array must have 0 in all fields.
argc	The number of elements from <code>argv</code> that are to be parsed. If you pass -1, the number will be determined automatically. In that case the <code>argv</code> list must end with a NULL pointer.
argv	The arguments to be parsed. If you pass -1 as argc the last pointer in the argv list must be NULL to mark the end.
options	Each entry is the first element of a linked list of Options. Each new option that is parsed will be appended to the list specified by that Option's Descriptor::index. If an entry is not yet used (i.e. the Option is invalid), it will be replaced rather than appended to.  The minimum length of this array is the greatest Descriptor::index value that occurs in usage PLUS ONE.

buffer	Each argument that is successfully parsed (including unknown arguments, if they have a Descriptor whose CheckArg does not return ARG ILLEGAL) will be stored in this array. parse()
	scans the array for the first invalid entry and begins writing at that index. You can pass
	bufmax to limit the number of options stored.
min_abbr_len	Passing a value min_abbr_len > 0 enables abbreviated long options. The parser
	will match a prefix of a long option as if it was the full long option (e.gfoob=10 will be
	interpreted as if it was -foobar=10), as long as the prefix has at least min_abbr_len
	characters (not counting the - ) and is unambiguous.
	Be careful if combining min_abbr_len=1 with single_minus_longopt=true be-
	cause the ambiguity check does not consider short options and abbreviated single minus
	long options will take precedence over short options.
single_minus	Passing true for this option allows long options to begin with a single minus. The double
longopt	minus form will still be recognized. Note that single minus long options take precedence over
	short options and short option groups. E.gfile would be interpreted as -file and not
	as -f -i -l -e (assuming a long option named "file" exists).
bufmax	The greatest index in the buffer[] array that parse() will write to is bufmax-1. If there
	are more options, they will be processed (in particular their CheckArg will be called) but not
	stored.
	If you used Stats::buffer_max to dimension this array, you can pass -1 (or not pass bufmax
	at all) which tells parse() that the buffer is "large enough".

#### Attention

Remember that options and buffer store Option objects, not pointers. Therefore it is not possible for the same object to be in both arrays. For those options that are found in both buffer[] and options[] the respective objects are independent copies. And only the objects in options[] are properly linked via Option::next() and Option::prev(). You can iterate over buffer[] to process all options in the order they appear in the argument vector, but if you want access to the other Options with the same Descriptor::index, then you must access the linked list via options[]. You can get the linked list in options from a buffer object via something like options[buffer[i].index()].

The documentation for this class was generated from the following file:


• src/include/optionparser.h

## 5.20 xmem::PowerReader Class Reference

An abstract base class for measuring power from an arbitrary source. This class is runnable using a worker thread.

#include <PowerReader.h>

Inheritance diagram for xmem::PowerReader:



#### **Public Member Functions**

- PowerReader (double sampling\_period, double power\_units, std::string name, int32\_t cpu\_affinity)
   Constructor.
- ∼PowerReader ()

Destructor.

virtual void run ()=0

Starts measuring power at the rate implied by the sampling\_period passed in the constructor. Call stop() to indicate to stop measuring.

• bool stop ()

Signals to stop measuring power. This is a non-blocking call and return does not indicate the measurement has actually stopped.

bool calculateMetrics ()

Calculates the relevant metrics.

• bool clear ()

Clears the stored power data.

bool clear\_and\_reset ()

Clears the stored power data and resets state so that a new thread can be used with this object.

std::vector< double > getPowerTrace ()

Gets the power trace.

double getAveragePower ()

Gets the average power.

• double getPeakPower ()

Gets the peak power.

• double getLastSample ()

Gets the last sample.

• double getSamplingPeriod ()

Gets the sampling period.

• double getPowerUnits ()

Gets the units of samples in watts.

• size\_t getNumSamples ()

Gets the number of samples collected.

std::string name ()

Gets the name of this object.

#### **Protected Attributes**

- · bool \_stop\_signal
- · double power units
- std::string \_name
- int32\_t \_cpu\_affinity
- std::vector< double > \_power\_trace
- double \_average\_power
- · double \_peak\_power
- size\_t \_num\_samples
- · double \_sampling\_period

#### **Additional Inherited Members**

#### 5.20.1 Detailed Description

An abstract base class for measuring power from an arbitrary source. This class is runnable using a worker thread.

#### 5.20.2 Constructor & Destructor Documentation

5.20.2.1 PowerReader::PowerReader ( double sampling\_period, double power\_units, std::string name, int32\_t cpu\_affinity )

Constructor.

## **Parameters**

sampling_period	The time between power samples in seconds.
power_units	The power units for each sample in watts.
name	The human-friendly name of this object.
cpu_affinity	The logical CPU to be used by the thread calling this object's run() method. If negative, any
	CPU is OK (no affinity).

5.20.3	Member Function Documentation		
5.20.3.1	bool PowerReader::calculateMetrics ( )		
Calculat	Calculates the relevant metrics.		
Returns			
Tru	True on success.		
5.20.3.2	bool PowerReader::clear ( )		
Clears the stored power data.			
Returns			
Tru	ue on success.		
5.20.3.3	bool PowerReader::clear_and_reset ( )		
Clears t	Clears the stored power data and resets state so that a new thread can be used with this object.		
Returns			
True on success.			
5.20.3.4	double PowerReader::getAveragePower ( )		
Gets the	e average power.		
Returns			
Th	e average power from the measurements. If no data was collected, returns 0.		
5.20.3.5	double PowerReader::getLastSample ( )		
Gets the last sample.			
Returns			

The last power sample measured.

```
5.20.3.6 size_t PowerReader::getNumSamples ( )
Gets the number of samples collected.
Returns
     Number of samples collected.
5.20.3.7 double PowerReader::getPeakPower ( )
Gets the peak power.
Returns
      The peak power sample from the measurements. If no data was collected, returns 0.
5.20.3.8 std::vector < double > PowerReader::getPowerTrace ( )
Gets the power trace.
Returns
     The measured power trace in a vector. If no data was collected, the vector will be empty.
5.20.3.9 double PowerReader::getPowerUnits ( )
Gets the units of samples in watts.
Returns
      The power units for each measurement sample in watts. For example, if each measurement is in milliwatts,
      then this returns 1e-3.
5.20.3.10 double PowerReader::getSamplingPeriod ( )
Gets the sampling period.
Returns
     The sampling period of the measurements in seconds.
5.20.3.11 std::string PowerReader::name ( )
Gets the name of this object.
Returns
```

The human-friendly name of this PowerReader.

```
5.20.3.12 bool PowerReader::stop ( )
```

Signals to stop measuring power. This is a non-blocking call and return does not indicate the measurement has actually stopped.

Returns

True if it successfully signaled a stop.

```
5.20.4 Member Data Documentation
```

```
5.20.4.1 double xmem::PowerReader::_average_power [protected]
```

The average power.

```
5.20.4.2 int32_t xmem::PowerReader::_cpu_affinity [protected]
```

CPU affinity for any thread using this object's run() method. If negative, no affinity preference.

```
5.20.4.3 std::string xmem::PowerReader::_name [protected]
```

Name of this object.

```
5.20.4.4 size_t xmem::PowerReader::_num_samples [protected]
```

The number of samples collected.

```
5.20.4.5 double xmem::PowerReader::_peak_power [protected]
```

The peak power observed.

```
5.20.4.6 std::vector<double> xmem::PowerReader::_power_trace [protected]
```

The time-ordered list of power samples. The first index is the oldest measurement.

```
5.20.4.7 double xmem::PowerReader::_power_units [protected]
```

Power units in watts.

```
5.20.4.8 double xmem::PowerReader::_sampling_period [protected]
```

Power sampling period in seconds.

```
5.20.4.9 bool xmem::PowerReader::_stop_signal [protected]
```

When true, the run() function should finish after the current sample iteration it is working on.

The documentation for this class was generated from the following files:

- src/include/PowerReader.h
- src/PowerReader.cpp

## 5.21 xmem::PrintUsageImplementation Struct Reference

#### **Classes**

- · struct FunctionWriter
- · struct IStringWriter
- · class LinePartIterator
- · class LineWrapper
- struct OStreamWriter
- · struct StreamWriter
- struct SyscallWriter
- · struct TemporaryWriter

#### Static Public Member Functions

- static void upmax (int &i1, int i2)
- static void **indent** (IStringWriter &write, int &x, int want\_x)
- static bool isWideChar (unsigned ch)

Returns true if ch is the unicode code point of a wide character.

static void printUsage (IStringWriter &write, const Descriptor usage[], int width=80, int last\_column\_min\_percent=50, int last\_column\_own\_line\_max\_percent=75)

#### 5.21.1 Member Function Documentation

```
5.21.1.1 static bool xmem::PrintUsageImplementation::isWideChar ( unsigned ch ) [inline], [static]
```

Returns true if ch is the unicode code point of a wide character.

Note

The following character ranges are treated as wide

```
1100..115F
2329..232A (just 2 characters!)
2E80..A4C6 except for 303F
A960..D7FB
F900..FAFF
FE10..FE6B
FF01..FF66
FFE0..FFE6
1B000.....
```

The documentation for this struct was generated from the following file:

• src/include/optionparser.h


## 5.22 xmem::Runnable Class Reference

A base class for any object that implements a thread-safe run() function for use by Thread objects.

```
#include <Runnable.h>
```

Inheritance diagram for xmem::Runnable:

62 Class Documentation



#### **Public Member Functions**

• Runnable ()

Constructor.

∼Runnable ()

Destructor.

• virtual void run ()=0

Does some "work". Pure virtual method that any derived class must implement in a thread-safe manner.

#### **Protected Member Functions**

bool <u>acquireLock</u> (int32\_t timeout)

Acquires the object lock to access all object state in thread-safe manner.

• bool \_releaseLock ()

Releases the object lock to access all object state in thread-safe manner.

#### 5.22.1 Detailed Description

A base class for any object that implements a thread-safe run() function for use by Thread objects.

#### 5.22.2 Member Function Documentation

**5.22.2.1** bool Runnable::\_acquireLock(int32\_t timeout) [protected]

Acquires the object lock to access all object state in thread-safe manner.

#### **Parameters**

timeout	timeout in milliseconds to acquire the lock. If 0, does not wait at all. If negative, waits indefi-
	nitely.

#### Returns

true on success. If not successful, the lock was not acquired, possibly due to a timeout, or the lock might already be held.

**5.22.2.2 bool Runnable::\_releaseLock( )** [protected]

Releases the object lock to access all object state in thread-safe manner.

#### Returns

true on success. If not successful, the lock is either still held or the call was illegal (e.g., releasing a lock that was never acquired).

The documentation for this class was generated from the following files:

- src/include/Runnable.h
- src/Runnable.cpp

#### 5.23 xmem::Stats Struct Reference

Determines the minimum lengths of the buffer and options arrays used for Parser.

```
#include <optionparser.h>
```

#### Classes

class CountOptionsAction

#### **Public Member Functions**

• Stats ()

Creates a Stats object with counts set to 1 (for the sentinel element).

 Stats (bool gnu, const Descriptor usage[], int argc, const char \*\*argv, int min\_abbr\_len=0, bool single\_minus\_ longopt=false)

Creates a new Stats object and immediately updates it for the given usage and argument vector. You may pass 0 for argc and/or argv, if you just want to update options\_max.

• Stats (bool gnu, const Descriptor usage[], int argc, char \*\*argv, int min\_abbr\_len=0, bool single\_minus\_longopt=false)

Stats(...) with non-const argv.

• Stats (const Descriptor usage[], int argc, const char \*\*argv, int min\_abbr\_len=0, bool single\_minus\_longopt=false)

```
POSIX Stats(...) (gnu==false).
```

- Stats (const Descriptor usage[], int argc, char \*\*argv, int min\_abbr\_len=0, bool single\_minus\_longopt=false)

  POSIX Stats(...) (gnu==false) with non-const argv.
- void add (bool gnu, const Descriptor usage[], int argc, const char \*\*argv, int min\_abbr\_len=0, bool single\_minus longopt=false)

Updates this Stats object for the given usage and argument vector. You may pass 0 for argc and/or argv, if you just want to update options max.

void add (bool gnu, const Descriptor usage[], int argc, char \*\*argv, int min\_abbr\_len=0, bool single\_minus\_longopt=false)

add() with non-const argv.

void add (const Descriptor usage[], int argc, const char \*\*argv, int min\_abbr\_len=0, bool single\_minus\_longopt=false)

POSIX add() (gnu==false).

void add (const Descriptor usage[], int argc, char \*\*argv, int min\_abbr\_len=0, bool single\_minus\_longopt=false)

POSIX add() (gnu==false) with non-const argv.

64 Class Documentation

#### **Public Attributes**

unsigned buffer\_max

Number of elements needed for a buffer[] array to be used for parsing the same argument vectors that were fed into this Stats object.

· unsigned options\_max

Number of elements needed for an options[] array to be used for parsing the same argument vectors that were fed into this Stats object.

#### 5.23.1 Detailed Description

Determines the minimum lengths of the buffer and options arrays used for Parser.

Because Parser doesn't use dynamic memory its output arrays have to be pre-allocated. If you don't want to use fixed size arrays (which may turn out too small, causing command line arguments to be dropped), you can use Stats to determine the correct sizes. Stats work cumulative. You can first pass in your default options and then the real options and afterwards the counts will reflect the union.

#### 5.23.2 Constructor & Destructor Documentation

5.23.2.1 xmem::Stats::Stats (bool gnu, const Descriptor usage[], int argc, const char \*\* argv, int min\_abbr\_len = 0, bool single\_minus\_longopt = false ) [inline]

Creates a new Stats object and immediately updates it for the given usage and argument vector. You may pass 0 for argc and/or argv, if you just want to update options\_max.

Note

The calls to Stats methods must match the later calls to Parser methods. See Parser::parse() for the meaning of the arguments.

#### 5.23.3 Member Function Documentation

5.23.3.1 void xmem::Stats::add ( bool gnu, const Descriptor usage[], int argc, const char \*\* argv, int min\_abbr\_len = 0, bool single minus longopt = false ) [inline]

Updates this Stats object for the given usage and argument vector. You may pass 0 for argc and/or argv, if you just want to update options\_max.

Note

The calls to Stats methods must match the later calls to Parser methods. See Parser::parse() for the meaning of the arguments.

#### 5.23.4 Member Data Documentation

5.23.4.1 unsigned xmem::Stats::buffer\_max

Number of elements needed for a buffer[] array to be used for parsing the same argument vectors that were fed into this Stats object.

Note

This number is always 1 greater than the actual number needed, to give you a sentinel element.

#### 5.23.4.2 unsigned xmem::Stats::options\_max

Number of elements needed for an options[] array to be used for parsing the same argument vectors that were fed into this Stats object.

Note


- · This number is always 1 greater than the actual number needed, to give you a sentinel element.
- This number depends only on the usage, not the argument vectors, because the options array needs exactly one slot for each possible Descriptor::index.

The documentation for this struct was generated from the following file:

· src/include/optionparser.h

## 5.24 xmem::Parser::StoreOptionAction Class Reference

Inheritance diagram for xmem::Parser::StoreOptionAction:



#### **Public Member Functions**

- StoreOptionAction (Parser &parser\_, Option options\_[], Option buffer\_[], int bufmax\_)

  Number of slots in buffer. -1 means "large enough".
- bool perform (Option &option)

Called by Parser::workhorse() for each Option that has been successfully parsed (including unknown options if they have a Descriptor whose Descriptor::check\_arg does not return ARG\_ILLEGAL.

bool finished (int numargs, const char \*\*args)

Called by Parser::workhorse() after finishing the parse.

#### 5.24.1 Constructor & Destructor Documentation

5.24.1.1 xmem::Parser::StoreOptionAction::StoreOptionAction ( Parser & parser\_, Option options\_[], Option buffer\_[], int bufmax\_ ) [inline]

Number of slots in buffer. -1 means "large enough".

Creates a new StoreOption action.

#### **Parameters**

parser_ the parser whose op_count should be updated.  options_ each Option o is chained into the linked list options_[o.desc->index]	

66 Class Documentation

bufmax	number of slots in buffer1 means "large enough".	

#### 5.24.2 Member Function Documentation

5.24.2.1 bool xmem::Parser::StoreOptionAction::finished (int numargs, const char \*\* args ) [inline], [virtual]

Called by Parser::workhorse() after finishing the parse.

#### **Parameters**

numargs	the number of non-option arguments remaining	
args	pointer to the first remaining non-option argument (if numargs $>$ 0).	

#### Returns

false iff a fatal error has occurred.

Reimplemented from xmem::Parser::Action.

```
5.24.2.2 bool xmem::Parser::StoreOptionAction::perform(Option & ) [inline], [virtual]
```

Called by Parser::workhorse() for each Option that has been successfully parsed (including unknown options if they have a Descriptor whose Descriptor::check\_arg does not return ARG\_ILLEGAL.

Returns false iff a fatal error has occured and the parse should be aborted.


Reimplemented from xmem::Parser::Action.

The documentation for this class was generated from the following file:

• src/include/optionparser.h

# 5.25 xmem::PrintUsageImplementation::StreamWriter< Function, Stream > Struct Template Reference

Inheritance diagram for xmem::PrintUsageImplementation::StreamWriter< Function, Stream >:



#### **Public Member Functions**

- virtual void operator() (const char \*str, int size)
   Writes the given number of chars beginning at the given pointer somewhere.
- StreamWriter (Function \*w, Stream \*s)

#### **Public Attributes**

- Function \* fwrite
- Stream \* stream

The documentation for this struct was generated from the following file:

· src/include/optionparser.h

## 5.26 xmem::PrintUsageImplementation::SyscallWriter< Syscall > Struct Template Reference

Inheritance diagram for xmem::PrintUsageImplementation::SyscallWriter< Syscall >:



#### **Public Member Functions**

- virtual void operator() (const char \*str, int size)
   Writes the given number of chars beginning at the given pointer somewhere.
- SyscallWriter (Syscall \*w, int f)

#### **Public Attributes**


- Syscall \* write
- int fd

The documentation for this struct was generated from the following file:

• src/include/optionparser.h

# 5.27 xmem::PrintUsageImplementation::TemporaryWriter< Temporary > Struct Template Reference

Inheritance diagram for xmem::PrintUsageImplementation::TemporaryWriter< Temporary >:



#### **Public Member Functions**

- virtual void operator() (const char \*str, int size)
   Writes the given number of chars beginning at the given pointer somewhere.
- TemporaryWriter (const Temporary &u)

68 Class Documentation

#### **Public Attributes**

· const Temporary & userstream

The documentation for this struct was generated from the following file:

• src/include/optionparser.h

## 5.28 xmem::Thread Class Reference

a nice wrapped thread interface independent of particular OS API

```
#include <Thread.h>
```

#### **Public Member Functions**

- Thread (Runnable \*target)
- ∼Thread ()
- bool create\_and\_start ()
- bool join ()
- bool cancel ()
- int32\_t getExitCode ()
- bool started ()
- bool completed ()
- bool validTarget ()
- · bool created ()
- bool isThreadSuspended ()
- bool isThreadRunning ()
- Runnable \* getTarget ()

## 5.28.1 Detailed Description

a nice wrapped thread interface independent of particular OS API

#### 5.28.2 Constructor & Destructor Documentation

```
5.28.2.1 Thread::Thread ( Runnable * target )
```

Constructor. Does not actually create the real thread or run it.

#### **Parameters**

target The target object to do some work with in a new thread.

```
5.28.2.2 Thread::\simThread ( )
```

Destructor. Immediately cancels the thread if it exists. This can be unsafe!

#### 5.28.3 Member Function Documentation

```
5.28.3.1 bool Thread::cancel ( )
```

Cancels the worker thread immediately. This should only be done in emergencies, as it is effectively killed and undefined behavior might occur.

#### Returns

true if the worker thread was successfully killed.

```
5.28.3.2 bool Thread::completed ( )
```

#### Returns

true if the thread completed, regardless of the manner in which it terminated. Returns false if it has not been started

```
5.28.3.3 bool Thread::create_and_start()
```

Creates and starts the thread immediately if the target Runnable is valid. This invokes the run() method in the Runnable target that was passed in the constructor.

#### Returns

true if the thread was successfully created and started.

```
5.28.3.4 bool Thread::created ( )
```

#### Returns

true if the thread has been created successfully.

```
5.28.3.5 int32_t Thread::getExitCode ( )
```

#### Returns

the exit code of the worker thread if it completed. If it did not complete or has not started, returns 0.

```
5.28.3.6 Runnable * Thread::getTarget ( )
```

#### Returns

a pointer to the target Runnable object

#### 5.28.3.7 bool Thread::isThreadRunning ( )

#### Returns

true if the thread is running. Returns false if the thread has not been created.

70 Class Documentation

```
5.28.3.8 bool Thread::isThreadSuspended ( )
```

Returns

true if the thread is suspended. Returns false if the thread has not been created.

```
5.28.3.9 bool Thread::join ( )
```

Blocks the calling thread until the worker thread managed by this object terminates. For simplicity, this does not support a timeout due to pthreads incompatibility with the Windows threading API. If the worker thread has already terminated, returns immediately. If the worker has not yet started, returns immediately.

Returns

true if the worker thread terminated successfully, false otherwise.

```
5.28.3.10 bool Thread::started ( )
```

Returns

true if the thread has been started, regardless if has completed or not.

```
5.28.3.11 bool Thread::validTarget ( )
```

Returns

true if the Runnable target is valid.

The documentation for this class was generated from the following files:


- src/include/Thread.h
- src/Thread.cpp

## 5.29 xmem::ThroughputBenchmark Class Reference

A type of benchmark that measures memory throughput.

```
#include <ThroughputBenchmark.h>
```

Inheritance diagram for xmem::ThroughputBenchmark:



### **Public Member Functions**

• ThroughputBenchmark (void \*mem\_array, size\_t len, uint32\_t iterations, uint32\_t num\_worker\_threads, uint32\_t mem\_node, uint32\_t cpu\_node, pattern\_mode\_t pattern\_mode, rw\_mode\_t rw\_mode, chunk\_size\_t chunk\_size, int64\_t stride\_size, std::vector< PowerReader \* > dram\_power\_readers, std::string name)

Constructor. Parameters are passed directly to the Benchmark constructor. See Benchmark class documentation for parameter semantics.

• virtual  $\sim$ ThroughputBenchmark ()

Destructor.

#### **Protected Member Functions**

virtual bool \_run\_core ()

The core benchmark function.

#### **Additional Inherited Members**

#### 5.29.1 Detailed Description

A type of benchmark that measures memory throughput.

#### 5.29.2 Member Function Documentation

```
5.29.2.1 bool ThroughputBenchmark::_run_core( ) [protected], [virtual]
```

The core benchmark function.

Returns

True on success.

Implements xmem::Benchmark.

The documentation for this class was generated from the following files:

- · src/include/ThroughputBenchmark.h
- src/ThroughputBenchmark.cpp

## 5.30 xmem::Timer Class Reference

This class abstracts some characteristics of simple high resolution stopwatch timer. However, due to the inability or complexity of abstracting shared hardware timers, this class does not actually provide start and stop functions.

```
#include <Timer.h>
```

#### **Public Member Functions**

• Timer ()

Constructor. This may take a noticeable amount of time.

• uint64\_t get\_ticks\_per\_sec ()

Gets ticks per second for this timer.

• double get\_ns\_per\_tick ()

Gets nanoseconds per tick for this timer.

#### **Protected Attributes**

- uint64 t ticks per sec
- double \_ns\_per\_tick

#### 5.30.1 Detailed Description

This class abstracts some characteristics of simple high resolution stopwatch timer. However, due to the inability or complexity of abstracting shared hardware timers, this class does not actually provide start and stop functions.

72 Class Documentation

## 5.30.2 Member Function Documentation

```
5.30.2.1 double Timer::get_ns_per_tick ( )
```

Gets nanoseconds per tick for this timer.

Returns

the number of nanoseconds per tick

```
5.30.2.2 uint64_t Timer::get_ticks_per_sec ( )
```

Gets ticks per second for this timer.

Returns

The reported number of ticks per second.

#### 5.30.3 Member Data Documentation

```
5.30.3.1 double xmem::Timer::_ns_per_tick [protected]
```

Nanoseconds per tick for this timer.

```
5.30.3.2 uint64_t xmem::Timer::_ticks_per_sec [protected]
```

Ticks per second for this timer.

The documentation for this class was generated from the following files:

- src/include/Timer.h
- src/Timer.cpp

## **Chapter 6**

## **File Documentation**

## 6.1 src/Benchmark.cpp File Reference

Implementation file for the Benchmark class.

```
#include <Benchmark.h>
#include <common.h>
#include <PowerReader.h>
#include <cstdint>
#include <iostream>
#include <vector>
#include <time.h>
```

## 6.1.1 Detailed Description

Implementation file for the Benchmark class.

## 6.2 src/benchmark\_kernels.cpp File Reference

Implementation file for benchmark kernel functions for doing the actual work we care about. :)

```
#include <benchmark_kernels.h>
#include <common.h>
#include <iostream>
#include <random>
#include <algorithm>
```

## 6.2.1 Detailed Description

Implementation file for benchmark kernel functions for doing the actual work we care about. :) Optimization tricks include:

UNROLL macros to manual loop unrolling. This reduces the relative branch overhead of the loop. We don't
want to benchmark loops, we want to benchmark memory! But unrolling too much can hurt code size and
instruction locality, potentially decreasing I-cache utilization and causing extra overheads. This is why we
allow multiple unroll lengths at compile-time.

• volatile keyword to prevent compiler from optimizing the code and removing instructions that we need. The compiler is too smart for its own good!

## 6.3 src/BenchmarkManager.cpp File Reference

Implementation file for the BenchmarkManager class.

```
#include <BenchmarkManager.h>
#include <common.h>
#include <Configurator.h>
#include <cstdint>
#include <stdlib.h>
#include <iostream>
#include <sstream>
#include <assert.h>
```

## 6.3.1 Detailed Description

Implementation file for the BenchmarkManager class.

## 6.4 src/common.cpp File Reference

Implementation file for common preprocessor definitions, macros, functions, and global constants.

```
#include <common.h>
#include <Timer.h>
#include <iostream>
```

#### **Variables**

```
bool xmem::g_verbose = false
size_t xmem::g_page_size
size_t xmem::g_large_page_size
uint32_t xmem::g_num_nodes
uint32_t xmem::g_num_logical_cpus
uint32_t xmem::g_num_physical_cpus
uint32_t xmem::g_num_physical_packages
uint32_t xmem::g_total_l1_caches
uint32_t xmem::g_total_l2_caches
uint32_t xmem::g_total_l3_caches
uint32_t xmem::g_total_l4_caches
uint32_t xmem::g_starting_test_index
uint32_t xmem::g_test_index
```

## 6.4.1 Detailed Description

Implementation file for common preprocessor definitions, macros, functions, and global constants.

## 6.5 src/Configurator.cpp File Reference

Implementation file for the Configurator class and some helper data structures.

```
#include <Configurator.h>
#include <common.h>
#include <optionparser.h>
#include <MyArg.h>
#include <cstdint>
#include <iostream>
#include <string>
```

#### 6.5.1 Detailed Description

Implementation file for the Configurator class and some helper data structures.

#### 6.6 src/include/Benchmark.h File Reference

Header file for the Benchmark class.

```
#include <common.h>
#include <PowerReader.h>
#include <Thread.h>
#include <Runnable.h>
#include <cstdint>
#include <string>
#include <vector>
```

## Classes

· class xmem::Benchmark

Flexible abstract class for any memory benchmark.

#### 6.6.1 Detailed Description

Header file for the Benchmark class.

## 6.7 src/include/benchmark kernels.h File Reference

Header file for benchmark kernel functions for doing the actual work we care about. :)

```
#include <common.h>
#include <cstdint>
#include <cstddef>
```

## **Typedefs**

- typedef int32\_t(\* xmem::SequentialFunction )(void \*, void \*)
- typedef int32\_t(\* xmem::RandomFunction )(uintptr\_t \*, uintptr\_t \*\*, size\_t)

#### **Functions**

bool xmem::determineSequentialKernel (rw\_mode\_t rw\_mode, chunk\_size\_t chunk\_size, int64\_t stride\_size, SequentialFunction \*kernel function, SequentialFunction \*dummy kernel function)

Determines which sequential memory access kernel to use based on the read/write mode, chunk size, and stride size.

• bool **xmem::determineRandomKernel** (rw\_mode\_t rw\_mode, chunk\_size\_t chunk\_size, RandomFunction \*kernel function, RandomFunction \*dummy kernel function)

Determines which random memory access kernel to use based on the read/write mode, chunk size, and stride size.

• bool **xmem::buildRandomPointerPermutation** (void \*start\_address, void \*end\_address, chunk\_size\_t chunk\_size)

Builds a random chain of pointers within the specified memory region.

• int32\_t xmem::dummy\_chasePointers (uintptr\_t \*, uintptr\_t \*\*, size\_t len)

Mimics the \_\_chasePointers() method but doesn't do the memory accesses.

• int32 t xmem::chasePointers (uintptr t \*first address, uintptr t \*\*last touched address, size t len)

Walks over the allocated memory in random order by chasing pointers. TODO update Doxygen comments.

int32\_t xmem::dummy\_empty (void \*, void \*)

Does nothing. Used for measuring the time it takes just to call a benchmark routine via function pointer.

• int32\_t xmem::dummy\_forwSequentialLoop\_Word32 (void \*start\_address, void \*end\_address)

Used for measuring the time spent doing everything in forward sequential Word 32 loops except for the memory access itself.

• int32 t xmem::dummy forwSequentialLoop Word64 (void \*start address, void \*end address)

Used for measuring the time spent doing everything in forward sequential Word 64 loops except for the memory access itself.

• int32 t xmem::dummy forwSequentialLoop Word128 (void \*start address, void \*end address)

Used for measuring the time spent doing everything in forward sequential Word 128 loops except for the memory access itself.

• int32\_t xmem::dummy\_forwSequentialLoop\_Word256 (void \*start\_address, void \*end\_address)

Used for measuring the time spent doing everything in forward sequential Word 256 loops except for the memory access itself.

int32\_t xmem::dummy\_revSequentialLoop\_Word32 (void \*start\_address, void \*end\_address)

Used for measuring the time spent doing everything in reverse sequential Word 32 loops except for the memory access itself.

int32\_t xmem::dummy\_revSequentialLoop\_Word64 (void \*start\_address, void \*end\_address)

Used for measuring the time spent doing everything in reverse sequential Word 64 loops except for the memory access itself.

• int32\_t xmem::dummy\_revSequentialLoop\_Word128 (void \*start\_address, void \*end\_address)

Used for measuring the time spent doing everything in reverse sequential Word 128 loops except for the memory access itself.

• int32 t xmem::dummy revSequentialLoop Word256 (void \*start address, void \*end address)

Used for measuring the time spent doing everything in reverse sequential Word 256 loops except for the memory access itself.

• int32 t xmem::dummy forwStride2Loop Word32 (void \*start address, void \*end address)

Used for measuring the time spent doing everything in forward 2-strided Word 32 loops except for the memory access itself

• int32\_t xmem::dummy\_forwStride2Loop\_Word64 (void \*start\_address, void \*end\_address)

Used for measuring the time spent doing everything in forward 2-strided Word 64 loops except for the memory access itself.

int32\_t xmem::dummy\_forwStride2Loop\_Word128 (void \*start\_address, void \*end\_address)

Used for measuring the time spent doing everything in forward 2-strided Word 128 loops except for the memory access itself.

• int32\_t xmem::dummy\_forwStride2Loop\_Word256 (void \*start\_address, void \*end\_address)

Used for measuring the time spent doing everything in forward 2-strided Word 256 loops except for the memory access itself.

int32\_t xmem::dummy\_revStride2Loop\_Word32 (void \*start\_address, void \*end\_address)

Used for measuring the time spent doing everything in reverse 2-strided Word 32 loops except for the memory access itself

• int32 t xmem::dummy revStride2Loop Word64 (void \*start address, void \*end address)

Used for measuring the time spent doing everything in reverse 2-strided Word 64 loops except for the memory access itself.

int32\_t xmem::dummy\_revStride2Loop\_Word128 (void \*start\_address, void \*end\_address)

Used for measuring the time spent doing everything in reverse 2-strided Word 128 loops except for the memory access itself

int32\_t xmem::dummy\_revStride2Loop\_Word256 (void \*start\_address, void \*end\_address)

Used for measuring the time spent doing everything in reverse 2-strided Word 256 loops except for the memory access itself.

int32\_t xmem::dummy\_forwStride4Loop\_Word32 (void \*start\_address, void \*end\_address)

Used for measuring the time spent doing everything in forward 4-strided Word 32 loops except for the memory access itself

• int32 t xmem::dummy forwStride4Loop Word64 (void \*start address, void \*end address)

Used for measuring the time spent doing everything in forward 4-strided Word 64 loops except for the memory access itself.

int32\_t xmem::dummy\_forwStride4Loop\_Word128 (void \*start\_address, void \*end\_address)

Used for measuring the time spent doing everything in forward 4-strided Word 128 loops except for the memory access itself.

• int32 t xmem::dummy forwStride4Loop Word256 (void \*start address, void \*end address)

Used for measuring the time spent doing everything in forward 4-strided Word 256 loops except for the memory access itself

• int32 t xmem::dummy revStride4Loop Word32 (void \*start address, void \*end address)

Used for measuring the time spent doing everything in reverse 4-strided Word 32 loops except for the memory access itself

• int32\_t xmem::dummy\_revStride4Loop\_Word64 (void \*start\_address, void \*end\_address)

Used for measuring the time spent doing everything in reverse 4-strided Word 64 loops except for the memory access itself.

• int32 t xmem::dummy revStride4Loop Word128 (void \*start address, void \*end address)

Used for measuring the time spent doing everything in reverse 4-strided Word 128 loops except for the memory access itself.

int32\_t xmem::dummy\_revStride4Loop\_Word256 (void \*start\_address, void \*end\_address)

Used for measuring the time spent doing everything in reverse 4-strided Word 256 loops except for the memory access itself

• int32 t xmem::dummy forwStride8Loop Word32 (void \*start address, void \*end address)

Used for measuring the time spent doing everything in forward 8-strided Word 32 loops except for the memory access itself

int32\_t xmem::dummy\_forwStride8Loop\_Word64 (void \*start\_address, void \*end\_address)

Used for measuring the time spent doing everything in forward 8-strided Word 64 loops except for the memory access itself

int32\_t xmem::dummy\_forwStride8Loop\_Word128 (void \*start\_address, void \*end\_address)

Used for measuring the time spent doing everything in forward 8-strided Word 128 loops except for the memory access itself.

int32\_t xmem::dummy\_forwStride8Loop\_Word256 (void \*start\_address, void \*end\_address)

Used for measuring the time spent doing everything in forward 8-strided Word 256 loops except for the memory access itself.

• int32\_t xmem::dummy\_revStride8Loop\_Word32 (void \*start\_address, void \*end\_address)

Used for measuring the time spent doing everything in reverse 8-strided Word 32 loops except for the memory access itself.

• int32 t xmem::dummy\_revStride8Loop\_Word64 (void \*start\_address, void \*end\_address)

Used for measuring the time spent doing everything in reverse 8-strided Word 64 loops except for the memory access itself.

int32\_t xmem::dummy\_revStride8Loop\_Word128 (void \*start\_address, void \*end\_address)

Used for measuring the time spent doing everything in reverse 8-strided Word 128 loops except for the memory access itself.

• int32 t xmem::dummy revStride8Loop Word256 (void \*start address, void \*end address)

Used for measuring the time spent doing everything in reverse 8-strided Word 256 loops except for the memory access itself.

int32\_t xmem::dummy\_forwStride16Loop\_Word32 (void \*start\_address, void \*end\_address)

Used for measuring the time spent doing everything in forward 16-strided Word 32 loops except for the memory access itself.

• int32 t xmem::dummy forwStride16Loop Word64 (void \*start address, void \*end address)

Used for measuring the time spent doing everything in forward 16-strided Word 64 loops except for the memory access itself.

int32\_t xmem::dummy\_forwStride16Loop\_Word128 (void \*start\_address, void \*end\_address)

Used for measuring the time spent doing everything in forward 16-strided Word 128 loops except for the memory access itself.

• int32 t xmem::dummy forwStride16Loop Word256 (void \*start address, void \*end address)

Used for measuring the time spent doing everything in forward 16-strided Word 256 loops except for the memory access itself.

• int32\_t xmem::dummy\_revStride16Loop\_Word32 (void \*start\_address, void \*end\_address)

Used for measuring the time spent doing everything in reverse 16-strided Word 32 loops except for the memory

• int32 t xmem::dummy revStride16Loop Word64 (void \*start address, void \*end address)

Used for measuring the time spent doing everything in reverse 16-strided Word 64 loops except for the memory access itself

• int32\_t xmem::dummy\_revStride16Loop\_Word128 (void \*start\_address, void \*end\_address)

Used for measuring the time spent doing everything in reverse 16-strided Word 128 loops except for the memory access itself.

int32\_t xmem::dummy\_revStride16Loop\_Word256 (void \*start\_address, void \*end\_address)

Used for measuring the time spent doing everything in reverse 16-strided Word 256 loops except for the memory access itself.

int32\_t xmem::dummy\_randomLoop\_Word32 (uintptr\_t \*first\_address, uintptr\_t \*\*last\_touched\_address, size t len)

Used for measuring the time spent doing everything in random Word 32 loops except for the memory access itself. TODO update Doxygen comments.

• int32\_t xmem::dummy\_randomLoop\_Word64 (uintptr\_t \*first\_address, uintptr\_t \*\*last\_touched\_address, size t len)

Used for measuring the time spent doing everything in random Word 64 loops except for the memory access itself. TODO update Doxygen comments.

int32\_t xmem::dummy\_randomLoop\_Word128 (uintptr\_t \*first\_address, uintptr\_t \*\*last\_touched\_address, size t len)

Used for measuring the time spent doing everything in random Word 128 loops except for the memory access itself. TODO update Doxygen comments.

• int32\_t xmem::dummy\_randomLoop\_Word256 (uintptr\_t \*first\_address, uintptr\_t \*\*last\_touched\_address, size t len)

Used for measuring the time spent doing everything in random Word 256 loops except for the memory access itself. TODO update Doxygen comments.

• int32 t xmem::forwSequentialRead Word32 (void \*start address, void \*end address)

Walks over the allocated memory forward sequentially, reading in 32-bit chunks.

• int32 t xmem::forwSequentialRead Word64 (void \*start address, void \*end address)

Walks over the allocated memory forward sequentially, reading in 64-bit chunks.

int32\_t xmem::forwSequentialRead\_Word128 (void \*start\_address, void \*end\_address)

Walks over the allocated memory forward sequentially, reading in 128-bit chunks.

• int32\_t xmem::forwSequentialRead\_Word256 (void \*start\_address, void \*end\_address)

Walks over the allocated memory forward sequentially, reading in 256-bit chunks.

- int32\_t xmem::revSequentialRead\_Word32 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory reverse sequentially, reading in 32-bit chunks.
- int32\_t xmem::revSequentialRead\_Word64 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory reverse sequentially, reading in 64-bit chunks.
- int32\_t xmem::revSequentialRead\_Word128 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory reverse sequentially, reading in 128-bit chunks.
- int32\_t xmem::revSequentialRead\_Word256 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory reverse sequentially, reading in 256-bit chunks.
- int32\_t xmem::forwSequentialWrite\_Word32 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory forward sequentially, writing in 32-bit chunks.
- int32\_t xmem::forwSequentialWrite\_Word64 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory forward sequentially, writing in 64-bit chunks.
- int32\_t xmem::forwSequentialWrite\_Word128 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory forward sequentially, writing in 128-bit chunks.
- int32\_t xmem::forwSequentialWrite\_Word256 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory forward sequentially, writing in 256-bit chunks.
- int32\_t xmem::revSequentialWrite\_Word32 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory reverse sequentially, writing in 32-bit chunks.
- int32\_t xmem::revSequentialWrite\_Word64 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory reverse sequentially, writing in 64-bit chunks.
- int32\_t xmem::revSequentialWrite\_Word128 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory reverse sequentially, writing in 128-bit chunks.
- int32\_t xmem::revSequentialWrite\_Word256 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory reverse sequentially, writing in 256-bit chunks.
- int32\_t xmem::forwStride2Read\_Word32 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 2, reading in 32-bit chunks.
- int32\_t xmem::forwStride2Read\_Word64 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 2, reading in 64-bit chunks.
- int32\_t xmem::forwStride2Read\_Word128 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 2, reading in 128-bit chunks.
- int32\_t xmem::forwStride2Read\_Word256 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 2, reading in 256-bit chunks.
- int32\_t xmem::revStride2Read\_Word32 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in reverse strides of size 2, reading in 32-bit chunks.
- int32\_t xmem::revStride2Read\_Word64 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in reverse strides of size 2, reading in 64-bit chunks.
- int32\_t xmem::revStride2Read\_Word128 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in reverse strides of size 2, reading in 128-bit chunks.
- int32\_t xmem::revStride2Read\_Word256 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in reverse strides of size 2, reading in 256-bit chunks.
- int32\_t xmem::forwStride2Write\_Word32 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 2, writing in 32-bit chunks.
- int32\_t xmem::forwStride2Write\_Word64 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 2, writing in 64-bit chunks.
- int32\_t xmem::forwStride2Write\_Word128 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 2, writing in 128-bit chunks.
- int32\_t xmem::forwStride2Write\_Word256 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 2, writing in 256-bit chunks.
- int32\_t xmem::revStride2Write\_Word32 (void \*start\_address, void \*end\_address)
   Walks over the allocated memory in reverse strides of size 2, writing in 32-bit chunks.
- int32\_t xmem::revStride2Write\_Word64 (void \*start\_address, void \*end\_address)

Walks over the allocated memory in reverse strides of size 2, writing in 64-bit chunks.

• int32\_t xmem::revStride2Write\_Word128 (void \*start\_address, void \*end\_address)

Walks over the allocated memory in reverse strides of size 2, writing in 128-bit chunks.

- int32\_t xmem::revStride2Write\_Word256 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in reverse strides of size 2, writing in 256-bit chunks.
- int32\_t xmem::forwStride4Read\_Word32 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 4, reading in 32-bit chunks.
- int32\_t xmem::forwStride4Read\_Word64 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 4, reading in 64-bit chunks.
- int32\_t xmem::forwStride4Read\_Word128 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 4, reading in 128-bit chunks.
- int32\_t xmem::forwStride4Read\_Word256 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 4, reading in 256-bit chunks.
- int32\_t xmem::revStride4Read\_Word32 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in reverse strides of size 4, reading in 32-bit chunks.
- int32\_t xmem::revStride4Read\_Word64 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in reverse strides of size 4, reading in 64-bit chunks.
- int32\_t xmem::revStride4Read\_Word128 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in reverse strides of size 4, reading in 128-bit chunks.
- int32\_t xmem::revStride4Read\_Word256 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in reverse strides of size 4, reading in 256-bit chunks.
- int32\_t xmem::forwStride4Write\_Word32 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 4, writing in 32-bit chunks.
- int32\_t xmem::forwStride4Write\_Word64 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 4, writing in 64-bit chunks.
- int32\_t xmem::forwStride4Write\_Word128 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 4, writing in 128-bit chunks.
- int32\_t xmem::forwStride4Write\_Word256 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 4, writing in 256-bit chunks.
- int32\_t xmem::revStride4Write\_Word32 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in reverse strides of size 4, writing in 32-bit chunks.
- int32\_t xmem::revStride4Write\_Word64 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in reverse strides of size 4, writing in 64-bit chunks.
- int32\_t xmem::revStride4Write\_Word128 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in reverse strides of size 4, writing in 128-bit chunks.
- int32\_t xmem::revStride4Write\_Word256 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in reverse strides of size 4, writing in 256-bit chunks.
- int32\_t xmem::forwStride8Read\_Word32 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 8, reading in 32-bit chunks.
- int32\_t xmem::forwStride8Read\_Word64 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 8, reading in 64-bit chunks.
- int32\_t xmem::forwStride8Read\_Word128 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 8, reading in 128-bit chunks.
- int32\_t xmem::forwStride8Read\_Word256 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 8, reading in 256-bit chunks.
- int32\_t xmem::revStride8Read\_Word32 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in reverse strides of size 8, reading in 32-bit chunks.
- int32\_t xmem::revStride8Read\_Word64 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in reverse strides of size 8, reading in 64-bit chunks.
- int32\_t xmem::revStride8Read\_Word128 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in reverse strides of size 8, reading in 128-bit chunks.

- int32\_t xmem::revStride8Read\_Word256 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in reverse strides of size 8, reading in 256-bit chunks.
- int32\_t xmem::forwStride8Write\_Word32 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 8, writing in 32-bit chunks.
- int32\_t xmem::forwStride8Write\_Word64 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 8, writing in 64-bit chunks.
- int32\_t xmem::forwStride8Write\_Word128 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 8, writing in 128-bit chunks.
- int32\_t xmem::forwStride8Write\_Word256 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 8, writing in 256-bit chunks.
- int32\_t xmem::revStride8Write\_Word32 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in reverse strides of size 8, writing in 32-bit chunks.
- int32\_t xmem::revStride8Write\_Word64 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in reverse strides of size 8, writing in 64-bit chunks.
- int32\_t xmem::revStride8Write\_Word128 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in reverse strides of size 8, writing in 128-bit chunks.
- int32\_t xmem::revStride8Write\_Word256 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in reverse strides of size 8, writing in 256-bit chunks.
- int32\_t xmem::forwStride16Read\_Word32 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 16, reading in 32-bit chunks.
- int32\_t xmem::forwStride16Read\_Word64 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 16, reading in 64-bit chunks.
- int32\_t xmem::forwStride16Read\_Word128 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 16, reading in 128-bit chunks.
- int32\_t xmem::forwStride16Read\_Word256 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 16, reading in 256-bit chunks.
- int32\_t xmem::revStride16Read\_Word32 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in reverse strides of size 16, reading in 32-bit chunks.
- int32\_t xmem::revStride16Read\_Word64 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in reverse strides of size 16, reading in 64-bit chunks.
- int32\_t xmem::revStride16Read\_Word128 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in reverse strides of size 16, reading in 128-bit chunks.
- int32\_t xmem::revStride16Read\_Word256 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in reverse strides of size 16, reading in 256-bit chunks.
- int32\_t xmem::forwStride16Write\_Word32 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 16, writing in 32-bit chunks.
- int32\_t xmem::forwStride16Write\_Word64 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 16. writing in 64-bit chunks.
- int32\_t xmem::forwStride16Write\_Word128 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 16, writing in 128-bit chunks.
- int32\_t xmem::forwStride16Write\_Word256 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in forward strides of size 16, writing in 256-bit chunks.
- int32\_t xmem::revStride16Write\_Word32 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in reverse strides of size 16, writing in 32-bit chunks.
- int32\_t xmem::revStride16Write\_Word64 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in reverse strides of size 16, writing in 64-bit chunks.
- int32\_t xmem::revStride16Write\_Word128 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in reverse strides of size 16, writing in 128-bit chunks.
- int32\_t xmem::revStride16Write\_Word256 (void \*start\_address, void \*end\_address)

  Walks over the allocated memory in reverse strides of size 16, writing in 256-bit chunks.

int32\_t xmem::randomRead\_Word32 (uintptr\_t \*first\_address, uintptr\_t \*\*last\_touched\_address, size\_-t len)

Walks over the allocated memory in random order, reading in 32-bit chunks. TODO update Doxygen comments.

• int32\_t xmem::randomRead\_Word64 (uintptr\_t \*first\_address, uintptr\_t \*\*last\_touched\_address, size\_t len)

Walks over the allocated memory in random order, reading in 64-bit chunks. TODO update Doxygen comments.

int32\_t xmem::randomRead\_Word128 (uintptr\_t \*first\_address, uintptr\_t \*\*last\_touched\_address, size\_t len)

Walks over the allocated memory in random order, reading in 128-bit chunks. TODO update Doxygen comments.

int32\_t xmem::randomRead\_Word256 (uintptr\_t \*first\_address, uintptr\_t \*\*last\_touched\_address, size\_t len)

Walks over the allocated memory in random order, reading in 256-bit chunks. TODO update Doxygen comments.

int32\_t xmem::randomWrite\_Word32 (uintptr\_t \*first\_address, uintptr\_t \*\*last\_touched\_address, size\_t len)

Walks over the allocated memory in random order, writing in 32-bit chunks. TODO update Doxygen comments.

• int32\_t xmem::randomWrite\_Word64 (uintptr\_t \*first\_address, uintptr\_t \*\*last\_touched\_address, size\_t len)

Walks over the allocated memory in random order, writing in 64-bit chunks. TODO update Doxygen comments.

• int32\_t xmem::randomWrite\_Word128 (uintptr\_t \*first\_address, uintptr\_t \*\*last\_touched\_address, size\_t len)

Walks over the allocated memory in random order, writing in 128-bit chunks. TODO update Doxygen comments.

int32\_t xmem::randomWrite\_Word256 (uintptr\_t \*first\_address, uintptr\_t \*\*last\_touched\_address, size\_t len)

Walks over the allocated memory in random order, writing in 256-bit chunks. TODO update Doxygen comments.

#### 6.7.1 Detailed Description

Header file for benchmark kernel functions for doing the actual work we care about. :)

## 6.8 src/include/BenchmarkManager.h File Reference

Header file for the BenchmarkManager class.

```
#include <common.h>
#include <Timer.h>
#include <PowerReader.h>
#include <Benchmark.h>
#include <ThroughputBenchmark.h>
#include <LatencyBenchmark.h>
#include <Configurator.h>
#include <cstdint>
#include <vector>
#include <fstream>
```

#### Classes

· class xmem::BenchmarkManager

Manages running all benchmarks at a high level.

#### 6.8.1 Detailed Description

Header file for the BenchmarkManager class.

#### 6.9 src/include/common.h File Reference

Header file for common preprocessor definitions, macros, functions, and global constants.

```
#include <cstdint>
#include <cstddef>
```

#### **Macros**

- #define VERSION "1.4.3"
- #define KB 1024
- #define MB 1048576
- #define MB 4 4194304
- #define MB\_16 16777216
- #define MB 64 67108864
- #define MB\_256 268435456
- #define MB\_512 536870912
- #define GB 1073741824
- #define GB 4 4294967296
- #define DEFAULT\_PAGE\_SIZE 4\*KB
- #define DEFAULT LARGE PAGE SIZE 2\*MB
- #define DEFAULT\_WORKING\_SET\_SIZE\_PER\_THREAD DEFAULT\_PAGE\_SIZE
- #define DEFAULT NUM WORKER THREADS 1
- #define DEFAULT NUM NODES 0
- #define DEFAULT NUM PHYSICAL PACKAGES 0
- #define DEFAULT\_NUM\_PHYSICAL\_CPUS 0
- #define DEFAULT\_NUM\_LOGICAL\_CPUS 0
- #define DEFAULT\_NUM\_L1\_CACHES 0
- #define DEFAULT\_NUM\_L2\_CACHES 0
- #define DEFAULT\_NUM\_L3\_CACHES 0
- #define DEFAULT\_NUM\_L4\_CACHES 0
- #define MIN\_ELAPSED\_TICKS 10000
- #define UNROLL2(x) x x
- #define UNROLL4(x) UNROLL2(x) UNROLL2(x)
- #define UNROLL8(x) UNROLL4(x) UNROLL4(x)
- #define UNROLL16(x) UNROLL8(x) UNROLL8(x)
- #define UNROLL32(x) UNROLL16(x) UNROLL16(x)
- #define UNROLL64(x) UNROLL32(x) UNROLL32(x)
- #define UNROLL128(x) UNROLL64(x) UNROLL64(x)
- #define UNROLL256(x) UNROLL128(x) UNROLL128(x)
   #define UNROLL512(x) UNROLL256(x) UNROLL256(x)
- #define UNROLL1024(x) UNROLL512(x) UNROLL512(x)
- #define UNROLL2048(x) UNROLL1024(x) UNROLL1024(x)
- #define UNROLL4096(x) UNROLL2048(x) UNROLL2048(x)
- #define UNROLL8192(x) UNROLL4096(x) UNROLL4096(x)
- #define UNROLL16384(x) UNROLL8192(x) UNROLL8192(x)
- #define UNROLL32768(x) UNROLL16384(x) UNROLL16384(x)
- #define UNROLL65536(x) UNROLL32768(x) UNROLL32768(x)
- #define LATENCY\_BENCHMARK\_UNROLL\_LENGTH 512
- #define USE TSC TIMER
- #define USE TIME BASED BENCHMARKS
- #define BENCHMARK DURATION SEC 4
- #define THROUGHPUT BENCHMARK BYTES PER PASS 4096
- #define RANDOM CONSTRUCT WITH SHUFFLE
- #define POWER\_SAMPLING\_PERIOD\_SEC 1

#### **Typedefs**

typedef uint32 t xmem::Word32 t

#### **Enumerations**

enum pattern\_mode\_t { SEQUENTIAL, RANDOM, NUM\_PATTERN\_MODES }

Memory access patterns are broadly categorized by sequential or random-access.

enum rw\_mode\_t { READ, WRITE, NUM\_RW\_MODES }

Memory access batterns are broadly categorized by reads and writes.

• enum chunk size t {

```
\label{eq:chunk_32b} \mbox{CHUNK\_64b}, \mbox{CHUNK\_128b}, \mbox{CHUNK\_256b}, \\ \mbox{NUM\_CHUNK\_SIZES} \, \}
```

Legal memory read/write chunk sizes in bits.

#### **Functions**

• void xmem::print\_welcome\_message()

Prints a basic welcome message to the console with useful information.

void xmem::print\_types\_report ()

Prints the various C/C++ types to the console for this machine.

void xmem::print\_compile\_time\_options ()

Prints compile-time option information to the console.

void xmem::test\_timers ()

Tests any enabled timers and outputs results to the console for sanity checking.

void xmem::test\_thread\_affinities ()

Checks to see if the calling thread can be locked to all logical CPUs in the system, and reports to the console the progress.

• bool xmem::lock\_thread\_to\_numa\_node (uint32\_t numa\_node)

Sets the affinity of the calling thread to the lowest numbered logical CPU in the given NUMA node. TODO: Improve this functionality, it is quite limiting.

bool xmem::unlock\_thread\_to\_numa\_node ()

Clears the affinity of the calling thread to any given NUMA node.

bool xmem::lock\_thread\_to\_cpu (uint32\_t cpu\_id)

Sets the affinity of the calling thread to a given logical CPU.

bool xmem::unlock\_thread\_to\_cpu ()

Clears the affinity of the calling thread to any given logical CPU.

• int32\_t xmem::cpu\_id\_in\_numa\_node (uint32\_t numa\_node, uint32\_t cpu\_in\_node)

Gets the CPU ID for a logical CPU of interest in a particular NUMA node. For example, if numa\_node is 1 and cpu\_-in\_node is 2, and there are 4 logical CPUs per node, then this will give the answer 6 (6th CPU), assuming CPU IDs start at 0.

• size\_t xmem::compute\_number\_of\_passes (size\_t working\_set\_size\_KB)

Computes the number of passes to use for a given working set size in KB, when size-based benchmarking mode is enabled at compile-time. You may want to change this implementation to suit your needs. See the compile-time options in common.h.

bool xmem::config page size ()

Queries the page sizes from the system and sets relevant global variables.

void xmem::init\_globals ()

Initializes useful global variables.

int32\_t xmem::query\_sys\_info ()

Sets up global variables based on system information at runtime.

uint64\_t xmem::start\_timer ()

Query the timer for the start of a timed section of code.

• uint64\_t xmem::stop\_timer ()

Query the timer for the end of a timed section of code.

#### 6.9.1 Detailed Description

Header file for common preprocessor definitions, macros, functions, and global constants.

6.9.2 Macro Definition Documentation

6.9.2.1 #define BENCHMARK\_DURATION\_SEC 4

RECOMMENDED VALUE: At least 2. Number of seconds to run in each benchmark.

6.9.2.2 #define DEFAULT\_LARGE\_PAGE\_SIZE 2\*MB

Default platform large page size in bytes. This generally should not be relied on, but is a failsafe.

6.9.2.3 #define DEFAULT\_NUM\_L1\_CACHES 0

Default number of L1 caches.

6.9.2.4 #define DEFAULT\_NUM\_L2\_CACHES 0

Default number of L2 caches.

6.9.2.5 #define DEFAULT\_NUM\_L3\_CACHES 0

Default number of L3 caches.

6.9.2.6 #define DEFAULT\_NUM\_L4\_CACHES 0

Default number of L4 caches.

6.9.2.7 #define DEFAULT\_NUM\_LOGICAL\_CPUS 0

Default number of logical CPU cores.

6.9.2.8 #define DEFAULT\_NUM\_NODES 0

Default number of NUMA nodes.

6.9.2.9 #define DEFAULT\_NUM\_PHYSICAL\_CPUS 0

Default number of physical CPU cores.

6.9.2.10 #define DEFAULT\_NUM\_PHYSICAL\_PACKAGES 0

Default number of physical packages.

6.9.2.11 #define DEFAULT\_NUM\_WORKER\_THREADS 1

Default number of worker threads to use.

6.9.2.12 #define DEFAULT\_PAGE\_SIZE 4\*KB

Default platform page size in bytes. This generally should not be relied on, but is a failsafe.

6.9.2.13 #define DEFAULT\_WORKING\_SET\_SIZE\_PER\_THREAD DEFAULT\_PAGE\_SIZE

Default working set size in bytes.

6.9.2.14 #define LATENCY\_BENCHMARK\_UNROLL\_LENGTH 512

Number of unrolls in the latency benchmark pointer chasing core function.

6.9.2.15 #define MIN\_ELAPSED\_TICKS 10000

If any routine measured fewer than this number of ticks its results should be viewed with suspicion. This is because the latency of the timer itself will matter.

6.9.2.16 #define POWER\_SAMPLING\_PERIOD\_SEC 1

RECOMMENDED VALUE: 1. Sampling period in seconds for all power measurement mechanisms.

6.9.2.17 #define RANDOM\_CONSTRUCT\_WITH\_SHUFFLE

RECOMMENDED ENABLED. In random-access kernels, generate a pointer chasing pattern using a random shuffle, which has a chance of creating small cycles. Much faster to run but strictly less correct. O(N)

6.9.2.18 #define THROUGHPUT\_BENCHMARK\_BYTES\_PER\_PASS 4096

RECOMMENDED VALUE: 4096. Number of bytes read or written per pass of any ThroughputBenchmark. This must be less than or equal to the minimum working set size, which is currently 4 KB.

6.9.2.19 #define USE\_TIME\_BASED\_BENCHMARKS

RECOMMENDED ENABLED. All benchmarks run for an estimated amount of time, and the figures of merit are computed based on the amount of memory accesses completed in the time limit. This mode has more consistent runtime across different machines, memory performance, and working set sizes, but may have more conservative measurements for differing levels of cache hierarchy (overestimating latency and underestimating throughput).

6.9.2.20 #define USE\_TSC\_TIMER

RECOMMENDED ENABLED. Use the Intel Time Stamp Counter native hardware timer. Only use this if you know what you are doing.

## 6.10 src/include/Configurator.h File Reference

Header file for the Configurator class and some helper data structures.

```
#include <common.h>
#include <optionparser.h>
#include <MyArg.h>
#include <cstdint>
#include <string>
```

#### Classes

· class xmem::Configurator

Handles all user input interpretation and generates the necessary flags for running benchmarks.

#### **Enumerations**

enum optionIndex {
 UNKNOWN, ALL, CHUNK\_SIZE, OUTPUT\_FILE,
 HELP, BASE\_TEST\_INDEX, NUM\_WORKER\_THREADS, MEAS\_LATENCY,
 ITERATIONS, RANDOM\_ACCESS\_PATTERN, SEQUENTIAL\_ACCESS\_PATTERN, MEAS\_THROUGHPUT,
 NUMA\_DISABLE, VERBOSE, WORKING\_SET\_SIZE\_PER\_THREAD, USE\_LARGE\_PAGES,
 USE\_READS, USE\_WRITES, STRIDE\_SIZE}

Enumerates all possible types of command-line options.

#### **Variables**

• const Descriptor xmem::usage []

Command-line option descriptors as needed by stuff in optionparser.h>. This is basically the help message content.

#### 6.10.1 Detailed Description

Header file for the Configurator class and some helper data structures.

## 6.11 src/include/ExampleArg.h File Reference

Slightly-modified third-party code related to OptionParser.

```
#include <optionparser.h>
#include <cstdint>
#include <stdio.h>
```

#### Classes

class xmem::ExampleArg

#### 6.11.1 Detailed Description

Slightly-modified third-party code related to OptionParser.

## 6.12 src/include/LatencyBenchmark.h File Reference

Header file for the LatencyBenchmark class.

```
#include <Benchmark.h>
#include <common.h>
#include <cstdint>
#include <string>
```

#### **Classes**

· class xmem::LatencyBenchmark

A type of benchmark that measures unloaded memory latency via random pointer chasing.

## 6.12.1 Detailed Description

Header file for the LatencyBenchmark class.

#### 6.13 src/include/LoadWorker.h File Reference

Header file for the LoadWorker class.

```
#include <MemoryWorker.h>
#include <benchmark_kernels.h>
```

#### **Classes**

· class xmem::LoadWorker

Multithreading-friendly class to do memory loading.

#### 6.13.1 Detailed Description

Header file for the LoadWorker class.

## 6.14 src/include/MemoryWorker.h File Reference

Header file for the MemoryWorker class.

```
#include <Runnable.h>
#include <cstdint>
```

#### **Classes**

• class xmem::MemoryWorker

Multithreading-friendly class to run memory access kernels.

#### 6.14.1 Detailed Description

Header file for the MemoryWorker class.

## 6.15 src/include/MyArg.h File Reference

Extensions to third-party optionparser-related code.

```
#include <ExampleArg.h>
#include <cstdint>
#include <stdio.h>
#include <cstdlib>
```

#### Classes

· class xmem::MyArg

#### 6.15.1 Detailed Description

Extensions to third-party optionparser-related code.

## 6.16 src/include/optionparser.h File Reference

This is the only file required to use The Lean Mean C++ Option Parser. Just #include it and you're set.

#### Classes

• struct xmem::Descriptor

Describes an option, its help text (usage) and how it should be parsed.

· class xmem::Option

A parsed option from the command line together with its argument if it has one.

struct xmem::Arg

Functions for checking the validity of option arguments.

struct xmem::Stats

Determines the minimum lengths of the buffer and options arrays used for Parser.

class xmem::Parser

Checks argument vectors for validity and parses them into data structures that are easier to work with.

- · struct xmem::Parser::Action
- class xmem::Stats::CountOptionsAction
- · class xmem::Parser::StoreOptionAction
- struct xmem::PrintUsageImplementation
- · struct xmem::PrintUsageImplementation::IStringWriter
- struct xmem::PrintUsageImplementation::FunctionWriter< Function >
- struct xmem::PrintUsageImplementation::OStreamWriter< OStream >
- struct xmem::PrintUsageImplementation::TemporaryWriter< Temporary >
- struct xmem::PrintUsageImplementation::SyscallWriter< Syscall >
- struct xmem::PrintUsageImplementation::StreamWriter< Function, Stream >
- · class xmem::PrintUsageImplementation::LinePartIterator
- class xmem::PrintUsageImplementation::LineWrapper

#### **Typedefs**

typedef ArgStatus(\* xmem::CheckArg )(const Option &option, bool msg)

Signature of functions that check if an argument is valid for a certain type of option.

#### **Enumerations**

enum ArgStatus { xmem::ARG\_NONE, xmem::ARG\_OK, xmem::ARG\_IGNORE, xmem::ARG\_ILLEGAL }

Possible results when checking if an argument is valid for a certain option.

#### **Functions**

template<typename OStream >
 void xmem::printUsage (OStream &prn, const Descriptor usage[], int width=80, int last\_column\_min\_ percent=50, int last\_column\_own\_line\_max\_percent=75)

Outputs a nicely formatted usage string with support for multi-column formatting and line-wrapping.

- template<typename Function >
   void xmem::printUsage (Function \*prn, const Descriptor usage[], int width=80, int last\_column\_min\_ percent=50, int last\_column\_own\_line\_max\_percent=75)
- template<typename Temporary >
   void xmem::printUsage (const Temporary &prn, const Descriptor usage[], int width=80, int last\_column\_ min percent=50, int last\_column own line max\_percent=75)
- template<typename Syscall >
   void xmem::printUsage (Syscall \*prn, int fd, const Descriptor usage[], int width=80, int last\_column\_min\_ percent=50, int last\_column\_own\_line\_max\_percent=75)
- template<typename Function, typename Stream >
   void xmem::printUsage (Function \*prn, Stream \*stream, const Descriptor usage[], int width=80, int last\_column\_min\_percent=50, int last\_column\_own\_line\_max\_percent=75)

#### 6.16.1 Detailed Description

This is the only file required to use The Lean Mean C++ Option Parser. Just #include it and you're set. The Lean Mean C++ Option Parser handles the program's command line arguments (argc, argv). It supports the short and long option formats of getopt(), getopt\_long() and getopt\_long\_only() but has a more convenient interface. The following features set it apart from other option parsers:

#### Highlights:

- It is a header-only library. Just #include "optionparser.h" and you're set.
- It is freestanding. There are no dependencies whatsoever, not even the C or C++ standard library.
- It has a usage message formatter that supports column alignment and line wrapping. This aids localization because it adapts to translated strings that are shorter or longer (even if they contain Asian wide characters).
- Unlike getopt() and derivatives it doesn't force you to loop through options sequentially. Instead you can
  access options directly like this:
  - Test for presence of a switch in the argument vector:
     if (options[QUIET]) ...
  - Evaluate -enable-foo/-disable-foo pair where the last one used wins:
    if ( options[FOO].last()->type() == DISABLE ) ...
  - Cumulative option (-v verbose, -vv more verbose, -vvv even more verbose): int verbosity = options[VERBOSE].count();
  - Iterate over all –file=<fname> arguments:

```
for (Option* opt = options[FILE]; opt; opt = opt->next())
fname = opt->arg; ...
```

If you really want to, you can still process all arguments in order:

```
for (int i = 0; i < p.optionsCount(); ++i) {
   Option& opt = buffer[i];
   switch(opt.index()) {
    case HELP:
        case VERBOSE: ...
    case FILE:        fname = opt.arg; ...
    case UNKNOWN: ...</pre>
```

Despite these features the code size remains tiny. It is smaller than uClibc's GNU getopt() and just a couple 100 bytes larger than uClibc's SUSv3 getopt().

(This does not include the usage formatter, of course. But you don't have to use that.)

#### Download:

Tarball with examples and test programs: optionparser-1.3.tar.gz Just the header (this is all you really need): optionparser.h

#### Changelog:

Version 1.3: Compatible with Microsoft Visual C++.

Version 1.2: Added Option::namelen and removed the extraction of short option characters into a special buffer.

Changed Arg::Optional to accept arguments if they are attached rather than separate. This is what GNU getopt() does and how POSIX recommends utilities should interpret their arguments.

**Version 1.1:** Optional mode with argument reordering as done by GNU getopt(), so that options and non-options can be mixed. See Parser::parse().

#### Feedback:

Send questions, bug reports, feature requests etc. to: optionparser-feedback (a) lists.-sourceforge.net

#### Example program:

(Note: option::\* identifiers are links that take you to their documentation.)

```
#include <iostream>
#include "optionparser.h"
enum optionIndex { UNKNOWN, HELP, PLUS };
const option::Descriptor usage[] =
 {UNKNOWN, 0,"", ""
                           ,option::Arg::None, "USAGE: example [options] \n\"
                                                  "Options:" },
 {HELP, 0,"", "help",option::Arg::None, " --help \tPrint usage and exit."}, {PLUS, 0,"p", "plus",option::Arg::None, " --plus, -p \tIncrement count."}, {UNKNOWN, 0,"", "",option::Arg::None, "\nExamples:\n"
                                                    example --unknown -- --this_is_no_option\n"
                                                  " example -unk --plus -ppp file1 file2\n"
 {0,0,0,0,0,0}
};
int main(int argc, char* argv[])
  argc-=(argc>0); argv+=(argc>0); // skip program name argv[0] if present
  option::Stats stats(usage, argc, argv);
  option::Option options[stats.options_max], buffer[stats.buffer_max];
  option::Parser parse(usage, argc, argv, options, buffer);
  if (parse.error())
  if (options[HELP] || argc == 0) {
    option::printUsage(std::cout, usage);
    return 0;
  std::cout << "--plus count: " <<
    options[PLUS].count() << "\n";
  for (option::Option* opt = options[UNKNOWN]; opt; opt = opt->next())
    std::cout << "Unknown option: " << opt->name << "\n";
```

```
for (int i = 0; i < parse.nonOptionsCount(); ++i) std::cout << "Non-option #" << i << ": " << parse.nonOption(i) << "\n";}
```

#### Option syntax:

• The Lean Mean C++ Option Parser follows POSIX getopt() conventions and supports GNU-style getopt\_long() long options as well as Perl-style single-minus long options (getopt\_long\_-only()).

- short options have the format -X where X is any character that fits in a char.
- short options can be grouped, i.e. -X -Y is equivalent to -XY.
- a short option may take an argument either separate (-X foo) or attached (-Xfoo). You can make the parser accept the additional format -X=foo by registering X as a long option (in addition to being a short option) and enabling single-minus long options.
- an argument-taking short option may be grouped if it is the last in the group, e.g. -ABCXfoo or -ABCX foo (foo is the argument to the -X option).
- a lone minus character '-' is not treated as an option. It is customarily used where a file name is expected to refer to stdin or stdout.
- long options have the format -option-name.
- the option-name of a long option can be anything and include any characters. Even = characters will work, but don't do that.
- [optional] long options may be abbreviated as long as the abbreviation is unambiguous. You can set a minimum length for abbreviations.
- [optional] long options may begin with a single minus. The double minus form is always accepted, too.
- a long option may take an argument either separate (-option arg ) or attached (-option=arg ). In the attached form the equals sign is mandatory.
- an empty string can be passed as an attached long option argument: -option-name= . Note the distinction between an empty string as argument and no argument at all.
- an empty string is permitted as separate argument to both long and short options.
- Arguments to both short and long options may start with a '-' character. E.g. -X-X, -X or -long-X=-X. If -X and -long-X take an argument, that argument will be "-X" in all 3 cases.
- If using the built-in Arg::Optional, optional arguments must be attached.
- the special option (i.e. without a name) terminates the list of options. Everything that follows is a non-option argument, even if it starts with a '-' character. The itself will not appear in the parse results.
- the first argument that doesn't start with '-' or '-' and does not belong to a preceding argument-taking option, will terminate the option list and is the first non-option argument. All following command line arguments are treated as non-option arguments, even if they start with '-'.

NOTE: This behaviour is mandated by POSIX, but GNU getopt() only honours this if it is explicitly requested (e.g. by setting POSIXLY\_CORRECT).

You can enable the GNU behaviour by passing true as first argument to e.g. Parser::parse().

• Arguments that look like options (i.e. '-' followed by at least 1 character) but aren't, are NOT treated as non-option arguments. They are treated as unknown options and are collected into a list of unknown options for error reporting.

This means that in order to pass a first non-option argument beginning with the minus character it is required to use the – special option, e.g.

```
program -x -- --strange-filename
```

In this example, <code>-strange-filename</code> is a non-option argument. If the <code>-</code> were omitted, it would be treated as an unknown option.

See option::Descriptor::longopt for information on how to collect unknown options.

#### 6.17 src/include/PowerReader.h File Reference

Header file for the PowerReader class.

```
#include <common.h>
#include <Runnable.h>
#include <cstdint>
#include <vector>
#include <string>
```

#### Classes

· class xmem::PowerReader

An abstract base class for measuring power from an arbitrary source. This class is runnable using a worker thread.

## 6.17.1 Detailed Description

Header file for the PowerReader class.

## 6.18 src/include/Runnable.h File Reference

Header file for the Runnable class.

```
#include <cstdint>
```

#### **Classes**

class xmem::Runnable

A base class for any object that implements a thread-safe run() function for use by Thread objects.

#### 6.18.1 Detailed Description

Header file for the Runnable class.

## 6.19 src/include/Thread.h File Reference

Header file for the Thread class.

```
#include <Runnable.h>
#include <cstdint>
```

#### **Classes**

· class xmem::Thread

a nice wrapped thread interface independent of particular OS API

## 6.19.1 Detailed Description

Header file for the Thread class.

## 6.20 src/include/ThroughputBenchmark.h File Reference

Header file for the ThroughputBenchmark class.

```
#include <Benchmark.h>
#include <common.h>
#include <cstdint>
#include <string>
```

#### Classes

· class xmem::ThroughputBenchmark

A type of benchmark that measures memory throughput.

## 6.20.1 Detailed Description

Header file for the ThroughputBenchmark class.

#### 6.21 src/include/Timer.h File Reference

Header file for the Timer class.

```
#include <cstdint>
```

## Classes

· class xmem::Timer

This class abstracts some characteristics of simple high resolution stopwatch timer. However, due to the inability or complexity of abstracting shared hardware timers, this class does not actually provide start and stop functions.

#### 6.21.1 Detailed Description

Header file for the Timer class.

## 6.22 src/include/win/win\_common\_third\_party.h File Reference

Header file for some third-party helper code for working with Windows APIs.

## 6.22.1 Detailed Description

Header file for some third-party helper code for working with Windows APIs.

## 6.23 src/include/win/win\_CPdhQuery.h File Reference

Header and implementation file for some third-party code for measuring Windows OS-exposed performance counters

### 6.23.1 Detailed Description

Header and implementation file for some third-party code for measuring Windows OS-exposed performance counters.

## 6.24 src/include/win/WindowsDRAMPowerReader.h File Reference

Header file for the WindowsDRAMPowerReader class.

#### 6.24.1 Detailed Description

Header file for the WindowsDRAMPowerReader class.

## 6.25 src/LatencyBenchmark.cpp File Reference

Implementation file for the LatencyBenchmark class.

```
#include <LatencyBenchmark.h>
#include <common.h>
#include <Timer.h>
#include <benchmark_kernels.h>
#include <iostream>
#include <random>
#include <assert.h>
#include <time.h>
```

#### 6.25.1 Detailed Description

Implementation file for the LatencyBenchmark class.

## 6.26 src/LoadWorker.cpp File Reference

Implementation file for the LoadWorker class.

```
#include <LoadWorker.h>
#include <benchmark_kernels.h>
#include <common.h>
#include <Timer.h>
#include <iostream>
```

## 6.26.1 Detailed Description

Implementation file for the LoadWorker class.

## 6.27 src/main.cpp File Reference

#### main entry point to the tool

```
#include <common.h>
#include <build_datetime.h>
#include <Configurator.h>
#include <BenchmarkManager.h>
#include <iostream>
#include <string>
```

#### **Functions**

• int main (int argc, char \*argv[])

The main entry point to the program.

### 6.27.1 Detailed Description

main entry point to the tool This tool is designed to measure bandwidth and latency of the memory system using several access patterns, strides, and working set sizes. The primary goal is to measure DRAM performance, although it can also measure cache performance depending on the configuration.

## 6.28 src/MemoryWorker.cpp File Reference

Implementation file for the MemoryWorker class.

```
#include <MemoryWorker.h>
```

#### 6.28.1 Detailed Description

Implementation file for the MemoryWorker class.

## 6.29 src/PowerReader.cpp File Reference

Implementation file for the PowerReader class.

```
#include <PowerReader.h>
#include <common.h>
#include <cstdint>
#include <vector>
#include <iostream>
```

## 6.29.1 Detailed Description

Implementation file for the PowerReader class.

## 6.30 src/Runnable.cpp File Reference

Implementation file for the Runnable class.

```
#include <Runnable.h>
#include <iostream>
```

#### **Variables**

· return false

## 6.30.1 Detailed Description

Implementation file for the Runnable class.

## 6.31 src/Thread.cpp File Reference

Implementation file for the Thread class.

```
#include <Thread.h>
#include <stdlib.h>
#include <iostream>
```

#### **Variables**

- return false
- return true

## 6.31.1 Detailed Description

Implementation file for the Thread class.

## 6.32 src/ThroughputBenchmark.cpp File Reference

Implementation file for the ThroughputBenchmark class.

```
#include <ThroughputBenchmark.h>
#include <common.h>
#include <LoadWorker.h>
#include <Thread.h>
#include <Timer.h>
#include <iostream>
#include <assert.h>
#include <time.h>
```

#### 6.32.1 Detailed Description

Implementation file for the ThroughputBenchmark class.

## 6.33 src/Timer.cpp File Reference

Implementation file for the Timer class.

```
#include <Timer.h>
#include <common.h>
```

## 6.33.1 Detailed Description

Implementation file for the Timer class.

## 6.34 src/win/win\_common\_third\_party.cpp File Reference

Implementation file for some third-party helper code for working with Windows APIs.

## 6.34.1 Detailed Description

Implementation file for some third-party helper code for working with Windows APIs.

## 6.35 src/win/WindowsDRAMPowerReader.cpp File Reference

Implementation file for the WindowsDRAMPowerReader class.

## 6.35.1 Detailed Description

Implementation file for the WindowsDRAMPowerReader class.

## Index

$\sim$ Thread	xmem::PowerReader, 60
xmem::Thread, 68	_ns_per_tick
_acquireLock	xmem::Timer, 72
xmem::Runnable, 62	_num_samples
_adjusted_ticks	xmem::PowerReader, 60
xmem::MemoryWorker, 44	_num_worker_threads
_averageMetric	xmem::Benchmark, 22
xmem::Benchmark, 21	_obj_valid
_average_dram_power_socket	xmem::Benchmark, 22
xmem::Benchmark, 21	_passes
_average_power	xmem::MemoryWorker, 45
xmem::PowerReader, 60	_pattern_mode
_bytes_per_pass	xmem::Benchmark, 22
xmem::MemoryWorker, 44	_peak_dram_power_socket
_chunk_size	xmem::Benchmark, 22
xmem::Benchmark, 21	_peak_power
_completed	xmem::PowerReader, 60
xmem::MemoryWorker, 44	_power_trace
_cpu_affinity	xmem::PowerReader, 60
xmem::MemoryWorker, 44	_power_units
xmem::PowerReader, 60	xmem::PowerReader, 60
_cpu_node	_releaseLock
xmem::Benchmark, 21	xmem::Runnable, 62
_dram_power_readers	_run_core
xmem::Benchmark, 21	xmem::Benchmark, 17
_dram_power_threads	xmem::LatencyBenchmark, 38
xmem::Benchmark, 21	xmem::ThroughputBenchmark, 7
_elapsed_dummy_ticks	_rw_mode
xmem::MemoryWorker, 45	xmem::Benchmark, 22
_elapsed_ticks	_sampling_period
xmem::MemoryWorker, 45	xmem::PowerReader, 60
_hasRun	_start_power_threads
xmem::Benchmark, 21	xmem::Benchmark, 18
iterations	_stop_power_threads
xmem::Benchmark, 21	xmem::Benchmark, 18
len	_stop_signal
xmem::Benchmark, 21	xmem::PowerReader, 60
xmem::MemoryWorker, 45	_stride_size
•	xmem::Benchmark, 22
_mem_array	_ticks_per_sec
xmem::Benchmark, 21	xmem::Timer, 72
xmem::MemoryWorker, 45	_warning
_mem_node	xmem::Benchmark, 22
xmem::Benchmark, 21	xmem::MemoryWorker, 45
_metricOnIter	
xmem::Benchmark, 21	add
_metricUnits	xmem::Stats, 64
xmem::Benchmark, 22	append
_name	xmem::Option, 48
xmem::Benchmark, 22	arg

xmem::Option, 50	xmem::MemoryWorker, 43
	getAverageDRAMPower
Benchmark	xmem::Benchmark, 18
xmem::Benchmark, 17	getAverageMetric
BenchmarkManager	xmem::Benchmark, 18
xmem::BenchmarkManager, 23	getAveragePower
buffer_max	xmem::PowerReader, 58
xmem::Stats, 64	getBytesPerPass
calculateMetrics	xmem::MemoryWorker, 43
	getCPUNode
xmem::PowerReader, 58 cancel	xmem::Benchmark, 18
	getChunkSize
xmem::Thread, 69	xmem::Benchmark, 18
check_arg	getElapsedDummyTicks
xmem::Descriptor, 35 clear	xmem::MemoryWorker, 43
xmem::PowerReader, 58	getElapsedTicks
clear and reset	xmem::MemoryWorker, 44
xmem::PowerReader, 58	getExitCode
	xmem::Thread, 69
common.h	getIterations
DEFAULT_NUM_NODES, 85	xmem::Benchmark, 18
DEFAULT_PAGE_SIZE, 86	getIterationsPerTest
MIN_ELAPSED_TICKS, 86	xmem::Configurator, 27
USE_TSC_TIMER, 86	getLastSample
completed	xmem::PowerReader, 58
xmem::Thread, 69	getLen
Configurator	xmem::Benchmark, 19
xmem::Configurator, 26	xmem::MemoryWorker, 44
configureFromInput	-
xmem::Configurator, 27	getMemNode
count	xmem::Benchmark, 19
xmem::Option, 48	getMetricOnIter
CountOptionsAction	xmem::Benchmark, 19
xmem::Stats::CountOptionsAction, 33	getName
create_and_start	xmem::Benchmark, 19
xmem::Thread, 69	getNumSamples
created	xmem::PowerReader, 58
xmem::Thread, 69	getNumThreads
DEEALUT NUM NODEO	xmem::Benchmark, 19
DEFAULT_NUM_NODES	getNumWorkerThreads
common.h, 85	xmem::Configurator, 28
DEFAULT_PAGE_SIZE	getOutputFilename
common.h, 86	xmem::Configurator, 28
desc	getPasses
xmem::Option, 50	xmem::MemoryWorker, 44
	getPatternMode
error	xmem::Benchmark, 19
xmem::Parser, 54	getPeakDRAMPower
finished	xmem::Benchmark, 20
	getPeakPower
xmem::Parser::Action, 13 xmem::Parser::StoreOptionAction, 66	xmem::PowerReader, 59
first	getPowerTrace
	xmem::PowerReader, 59
xmem::Option, 48	getPowerUnits
get_ns_per_tick	xmem::PowerReader, 59
xmem::Timer, 72	getRWMode
	xmem::Benchmark, 20
get_ticks_per_sec	
xmem::Timer, 72	getSamplingPeriod
getAdjustedTicks	xmem::PowerReader, 59

getStartiogSize xmem::Sontifugator, 28 getStrideSize xmem::Benchmark, 20 yetTarpet xmem::Defion, 28 yetWorkingSetSizePerThread xmem::Configurator, 28 yetWorkingSetSizePerThread xmem::Defion, 28 yetWorkingSetSizePerThread xmem::Descriptor, 35 yetme::Descriptor, 36 yetme::Descriptor, 36 yetme::Descriptor, 36 yetme::Descriptor, 35 yetme::Descriptor, 36		
getStrideSize xmem:Benchmark, 20 getTarget xmem:Benchmark, 20 getTarget xmem:Thread, 69 getWorkingSetSizePerThread xmem:Configurator, 28 llerator, 39 nextTable getWorkingSetSizePerThread xmem:Configurator, 28 llerator, 39 nextTable getWorkingSetSizePerThread xmem:MemoryWorker, 44 nasRun xmem:Benchmark, 20 nonOptions xmem:Configurator, 35 londex xmem:Descriptor, 35 londex xmem:Option, 48 sixLast xmem:Option, 48 sixLast xmem:Configurator, 28 sixThreadRuning xmem:Thread, 69 sixThreadRuning xmem:Thread, 69 sixThreadRuning xmem:PrintUsageImplementation, 61 six xmem:Parser, 55 londer xmem:PrintUsageImplementation, 61 six xmem:Option, 48 latencyTestSelected xmem:Doption, 48 latencyTestSelected xmem:Doption, 48 latencyTestSelected xmem:Doption, 48 latencyTestSelected xmem:Descriptor, 35 late xmem:Configurator, 28 LineWrapper xmem:Descriptor, 35 late xmem:Doption, 48 latencyTestSelected xmem:Doption, 48 latencyTestSelected xmem:Doption, 48 latencyTestSelected xmem:Doption, 49 londer xmem:Doption, 49 londer latencyTestSelected xmem:PrintUsageImplementation:LineWrapper, 40 longopt xmem:Descriptor, 35 latencyTestSelected xmem:Doption, 40 longopt xmem:Doption, 50 longopt xmem:Doption, 51 lo	getStartingTestIndex	xmem::PrintUsageImplementation::LinePart-
xmem::Benchmark, 20 getWorkingSetSizePerThread xmem::Configurator, 28 hadWarning xmem::Benchmark, 20 happer xmem::Descriptor, 35 index xmem::Option, 48 isTiread. 69 isThreadSuspended xmem::Configurator, 28 isThreadSuspended xmem::PrintUsageImplementation::LinePart- Illerator, 39 nextwrap nextrestor, 39 nextwrap nextronologion, 4 nonOptions xmem:PrintUsageImplementation:LinePart nextronologion, 4 nonOptions xmem:PrintUsageImplementation:LinePart nextronologion, 4 nonOptions xmem:PrintUsageImplementation	xmem::Configurator, 28	Iterator, 39
xmem::Benchmark, 20 getWorkingSetSizePerThread xmem::Configurator, 28 hadWarning xmem::MemoryWorker, 44 hasRun xmem::Descriptor, 35 index xmem::Option, 48 isLast xmem::Option, 48 isThread, 69 isThreadSuspended xmem::Thread, 69 isWildChar xmem::PrintUsageImplementation::LineVarapper, xmem::PrintUsageImplementation::LineWrapper xmem::Doption, 48 isThreadSuspended xmem::Thread, 69 isWildChar xmem::Option, 48 latencyTestSelected xmem::PrintUsageImplementation::LineWrapper xmem::PrintUsageImplementation::L	getStrideSize	nextRow
getTarget xmem::Thread, 69 getWorkingSetSizePerThread xmem::Configurator, 28 hadWarning xmem::MemoryWorker, 44 hasRun xmem::Descriptor, 35 index xmem::Descriptor, 35 index xmem::Option, 48 isTreadSunning xmem::Coption, 48 isLast xmem::Option, 48 isNUMAEnabled xmem::Thread, 69 isThreadSupended xmem::PrintUsageImplementation, 61 sitThreadSupended xmem::PrintUsageImplementation, 61 sitThreadSupended xmem::PrintUsageImplementation:LineWrapper xmem::Doption, 48 latency TestSelected xmem::Doption, 48 latency TestSelected xmem::Doption, 48 latency TestSelected xmem::Doption, 48 latency TestSelected xmem::Descriptor, 35  Index xmem::Doption, 48 latency TestSelected xmem::Doption, 48 latency TestSelected xmem::Descriptor, 35  Index xmem::Doption, 48 latency TestSelected xmem::Doption, 49  CoadWorker xmem::Descriptor, 35  Index xmem::Descriptor, 35  Index xmem::Doption, 49  Options max xmem::Parser, 55  Parser xmem::Parser, 55  Parser xmem::Parser, 55  Parser xmem::Parser::StoreOptionAction, 66  xmem::Stats:-CountOptionsAction, 34  PowerReader xmem::PrintUsageImplementation::LineWrapper, 40  LoadWorker xmem::Descriptor, 35  Index xmem::Descrip	-	xmem··Printl IsageImplementation··I inePart-
xmem::Thread, 69 gotWorkingSetIs2ePerThread xmem::Configurator, 28 hadWarning xmem::MemoryWorker, 44 hasRun xmem::Benchmark, 20 help xmem::Descriptor, 35 index xmem::Descriptor, 35 index xmem::Descriptor, 35 index xmem::Option, 48 isLast xmem::Option, 48 isLast xmem::Option, 48 isIntread, 69 isThread, 69 isThread, 69 isValid xmem::Thread, 69 isValid xmem::PinitUsageImplementation, 61 xmem::Parser, 54  xmem::Option, 49 operator const Option * xmem::Option, 49 operator option, 49 operator ymem::Option, 49 operator ymem::Option, 49 operator xmem::Option, 49 operator ymem::Option, 49 operator xmem::Option, 49 operator xmem::Option, 49 operator ymem::Option, 49 operator xmem::Option, 49 operator option 4 operator xmem::Option, 49 operator option, 49 operator option 4 operator option, 49 operator option 4 operator xmem::Option, 49 operator option, 49 operator option 4 operator option, 49 operator option 4 operator option, 49 operator option 4 operator option, 49 option, 40		- ·
getWorkingSetSizePerThread xmem::Configurator, 28 hadWarning xmem::MemoryWorker, 44 hasRun xmem::Benchmark, 20 help xmem::Descriptor, 35 index xmem::Descriptor, 35 index xmem::Option, 48 isLast xmem::Option, 48 isLast xmem::Option, 48 isNUMAEnabled xmem::Thread, 69 isThreadRuning xmem::Parsed, 54 xmem::Option, 48 isThreadRuning xmem::Thread, 69 isWideChar xmem::PrintUsageImplementation, 61 ast xmem::Option, 48 isLast xmem::Option, 48 isThreadRuning xmem::Thread, 69 isWideChar xmem::PrintUsageImplementation, 61 ast xmem::Option, 48 latencyTestSelected xmem::Thread, 70 xmem::Parser; 55 Parser xmem::Parser; 55 Parser xmem:-Parser; 55 perforn xmem::Parser; 55 perforn xmem::Parser, 55 perforn xmem::Parser; 55 perforn xmem::Parser; 55 perforn		
hadWarning mem::MemoryWorker, 44 hasRun mem::Benchmark, 20 help mem::Descriptor, 35 index mem::Option, 48 isLast mem::Option, 48 isThreadRunning mem::Thread, 69 isThreadSuspended mem::PrintUsageImplementation, 61 isWidchar mem::PrintUsageImplementation::LineWrapper, 40 LoadWorker mem::PrintUsageImplementation::LineWrapper, 40 LoadWorker mem::Descriptor, 35 mame  mame mem::Option, 18 laters mem::Option, 48 latencyTestSelected mem::PrintUsageImplementation::LineWrapper, 40 LoadWorker mem::Descriptor, 35 mame mem::Descriptor, 35 mamelen mem::Option, 51 mem::PowerReader, 59 mamelen mem::Option, 51 mem::Configurator, 28 mem::Option, 18 mem::Configurator, 28 mem::Descriptor, 35 mem::PowerReader, 59 mamelen mem::Option, 51 mem::PowerReader, 59 mamelen mem::Option, 51 mem::PowerReader, 59 mamelen mem::Option, 51 mem::Configurator, 28 mem::Configurator, 28 mem::Option, 51 mem::PowerReader, 59 mamelen mem::Option, 51 mem::PowerReader, 59 mem::Option, 50 monormic mem::PowerReader, 59 mem::Option, 50 monormic mem::PowerReader, 59 mem::PowerReader, 5		
hadWarning xmem::MemoryWorker, 44 hasRun xmem::Benchmark, 20 help xmem::Descriptor, 35 index xmem::Option, 48 isLast xmem::Option, 48 isNUMAEnabled xmem::Thread, 69 isValid xmem::Benchmark, 20  isValid xmem::PrintUsageImplementation, 61  join xmem::PrintUsageImplementation::LineWrapper, 40 LoadWorker xmem::Descriptor, 35   MIN_ELAPSED_TICKS common, h, 86 MemoryWorker xmem::Dotion, 43  mame xmem::Dotion, 43  mame xmem::Dotion, 48  assultat xmem::Dotion, 49  operator Option, 40  xmem::Option, 40  xmem::Option, 40  xmem::Parser:.StoreOptionAction, 66  xmem::Parser:.StoreOptionAction, 66  xmem::Option, 50  prevwrap xmem::Option, 50  pr	getWorkingSetSizePerThread	xmem::PrintUsageImplementation::LinePart-
hadWarning xmem::MemoryWorker, 44 nonOptions xmem::Parser, 54 nonOptions xmem::Parser, 54 nonOptions Count xmem::Descriptor, 35	xmem::Configurator, 28	Iterator, 39
hadWarning xmem::MemoryWorker, 44 nonOptions xmem::Parser, 54 nonOptions xmem::Parser, 54 nonOptions Count xmem::Descriptor, 35	_	nextwrap
mem::MemoryWorker, 44 hasRun mem::Benchmark, 20 help mem::Descriptor, 35 index mem::Descriptor, 35 index mem::Descriptor, 35 isFirst mem::Option, 48 isLast mem::Option, 48 isINUMAEnabled mem::Thread, 69 isThreadRunning mem::Thread, 69 isValid mem::PhirtUsageImplementation, 61 ast mem::Option, 48 latencyTestSelected mem::Configurator, 28 LineWrapper mem::PrintUsageImplementation::LineWrapper, 40 LoadWorker mem::Descriptor, 35  MIN_ELAPSED_TICKS common.h, 86 MemoryWorker mem::Option, 51 mem::PowerReader, 59 namelen mem::Coption, 51 mem::Coption, 52 mem::Coption,	hadWarning	
hasRun xmem::Benchmark, 20 holp xmem::Descriptor, 35 index xmem::Descriptor, 35 isFirst xmem::Option, 48 isLast xmem::Option, 48 isNUMAEnabled xmem::Configurator, 28 isThreadRunning xmem::Thread, 69 isThreadSuspended xmem::PrintUsageImplementation, 61 isvalid xmem::Option, 48 latencyTestSelected xmem::Option, 48 latencyTestSelected xmem::Option, 48 latencyTestSelected xmem::PrintUsageImplementation::LineWrapper, xmem::Option, 48 latencyTestSelected xmem::PrintUsageImplementation::LineWrapper, xmem::Descriptor, 35 istail xmem::Descriptor, 35 istail xmem::PrintUsageImplementation::LineWrapper, xmem::Option, 50 istail xmem::PrintUsageImplementation::LineWrapper, xmem::PrintUsageImple	_	•
xmem::Benchmark, 20 help xmem::Descriptor, 35  index xmem::Option, 48 isLast xmem::Option, 48 isNUMAEnabled xmem::Thread, 69 isThreadBunning xmem::Benchmark, 20 isWideChar xmem::PrintUsageImplementation, 61 ast xmem::Option, 48 latencyTestSelected xmem::Option, 48 latencyTestSelected xmem::PrintUsageImplementation::LineWrapper, 40 LoadWorker xmem::Descriptor, 35  MIN_ELAPSED_TICKS common.h, 86 MemoryWorker, 43 name xmem::Option, 51 xmem::PowerReader, 59 namelen xmem::Option, 51 xmem::Option, 47 xmem::Option, 47		•
help xmem::Descriptor, 35  index xmem::Descriptor, 35  isFirst xmem::Option, 48 isLast xmem::Option, 48 isNUMAEnabled xmem::Thread, 69 isThreadSuspended xmem::PrintUsageImplementation, 61  isWidchar xmem::Option, 48  istolia  ix xmem::Option, 49  Option xmem::Parser, 54  operator const Option * xmem::Option, 49  operator* yeprator* yepronon* yeprator* ye		xmem::Parser, 54
index	xmem::Benchmark, 20	nonOptionsCount
index xmem::Descriptor, 35 isFirst xmem::Option, 48 isLast xmem::Onligurator, 28 isThreadRunning xmem::Thread, 69 isValid xmem::PorintUsageImplementation::LineWrapper xmem::Option, 48 latencyTestSelected xmem::Portior, 35  isRedWorker xmem::Descriptor, 35  imame xmem::Option, 48  MemoryWorker xmem::Descriptor, 35  index xmem::Descriptor, 35  isRed isLast xmem::Option, 48  AlatencyTestSelected xmem::Descriptor, 35  MIN_ELAPSED_TICKS common.h, 86  MemoryWorker xmem::MemoryWorker, 43  name xmem::Option, 51 xmem::PowerReader, 59 namelen xmem::Option, 51 xmem::Descriptor, 51 next  operator const Option * xmem::Option, 49 operator Cption * xmem::Option, 49 operator Cption * xmem::Option, 49 operator Cption * xmem::Option, 49 operator Option * xmem::Option, 49 operator Option, 4 option, 49 operator Option, 4 operator Option, 4 operator Option, 4 options. def options.Count xmem::Option, 47 optionsmax xmem::Parser::Stats, 0a, 4 optionsPax vmem::Parser:Stats, 0a, 4 optionsPax vmem::Parser:Stats, 0a operator vmem::Option, 49 operator vmem::Option, 49 operator vmem::Option, 49 operator operator vmem::Option, 49 operator operator vmem::Option, 49 operator op	help	xmem::Parser, 54
index xmem::Descriptor, 35  isFirst xmem::Option, 48 isLast xmem::Option, 48 isNUMAEnabled xmem::Configurator, 28 isThreadRunning xmem::Thread, 69 isValid xmem::PrintUsageImplementation, 61  ist xmem::Option, 48 iatencyTestSelected xmem::PrintUsageImplementation::LineWrapper xmem::PrintUsageImplementation::LineWrapper xmem::PrintUsageImplementation::LineWrapper xmem::Descriptor, 35  MIN_ELAPSED_TICKS common, 1, 86  MemoryWorker xmem::Option, 51 xmem::PowerReader, 59 namelen xmem::PowerReader, 59 namelen xmem::Option, 51 xmem::PowerReader, 59 namelen xmem::Option, 51 xmem::PowerReader, 59 namelen xmem::Option, 51 xmem::PowerReader, 58 perform xmem::Option, 49 operator o Qtion * xmem::Option, 49 operator o Qtion * xmem::Option, 49 operator = Qption, 49 operator = xmem::Option, 49 operator = Qption, 49 operator = Qption = xmem::Option, 49 operator = xmem::Option, 49 operator = Qption = xmem::Option, 49 operator = xmem::Option, 40 options.Cnin xmem::Option, 47 options.Cnin xmem::Parser::Stats, 64 options.Count xmem::Descriptor, 45 options.Count xmem::Des	xmem::Descriptor, 35	
index xmem::Descriptor, 35  isFirst xmem::Option, 48 isLast xmem::Onfigurator, 28 isThreadRunning xmem::Thread, 69 isValid xmem::PrintUsageImplementation, 61  ist xmem::Option, 48 iatencyTestSelected xmem::PrintUsageImplementation::LineWrapper xmem::PrintUsageImplementation::LineWrapper xmem::Descriptor, 35  IMIN_ELAPSED_TICKS common, 1, 86  MemoryWorker xmem::Option, 51 xmem::PowerReader, 59 namelen xmem::PowerReader, 59 namelen xmem::Option, 51 xmem::PowerReader, 58 perform xmem::Option, 49 operator o Qption, 49 operator o perator= xmem::Option, 49 operator= xmem::Option, 47 options_Act xmem::Parser, 55 Parser xmem::Parser, 55 Parser xmem::Parser, 55 Parser xmem::Parser::Action, 13 xmem::Parser::Action, 15 xmem::PowerReader perform xmem::Parser::Action, 13 xmem::Parser::Acti		operator const Option *
xmem::Descriptor, 35 isFirst xmem::Option, 48 isLast xmem::Option, 48 isNUMAEnabled xmem::Configurator, 28 isThreadSuspended xmem::Thread, 69 isValid xmem::PrintUsageImplementation, 61 xmem::Option, 48 latencyTestSelected xmem::Configurator, 28 litenewrapper xmem::Option, 48 latencyTestSelected xmem::Descriptor, 35  MIN_ELAPSED_TICKS common, 1, 86 MemoryWorker xmem::Option, 51 xmem::PowerReader, 59 namelen xmem::Option, 51 xmem::Option, 48 xmem::Option, 48 xmem::Option, 51 xmem::Option, 48 xmem::Option, 48 xmem::Option, 48 xmem::Option, 48 xmem::Option, 48 xmem::Option, 48 xmem::Option, 49 xmem::Parser::Stote xmem::Option, 49 xmem::Parser::Stote xmem::Opti	index	
isFirst xmem::Option, 48 isLast xmem::Configurator, 28 isThreadRunning xmem::Thread, 69 isValid xmem::Benchmark, 20 isWideChar xmem::Option, 48 ister in xmem::PrintUsageImplementation, 61 isx xmem::Option, 48 latencyTestSelected xmem::Configurator, 28 litenexyTestSelected xmem::Descriptor, 35  IMN_ELAPSED_TICKS common.h, 86 MemoryWorker xmem::Option, 51 xmem::PowerReader, 59 namelen xmem::Option, 51 xmem::PowerReader, 28 shortopt xmem::Option, 51 xmem::BenchmarkManager, 23 runThroughputEenchmarks xmem::BenchmarkManager, 23 name xmem::Option, 51 xmem::Configurator, 28 shortopt		•
xmem::Option, 48 isLast xmem::Configurator, 28 isNUMAEnabled xmem::Configurator, 28 isThreadRunning xmem::Thread, 69 isValid xmem::Benchmark, 20 isWideChar xmem::PrintUsageImplementation, 61 isx xmem::Option, 48 latencyTestSelected xmem::Configurator, 28 LineWrapper xmem::PrintUsageImplementation::LineWrapper xmem::PrintUsageImplementation::LineWrapper xmem::Descriptor, 35  MIN_ELAPSED_TICKS common.h, 86 MemoryWorker xmem::Option, 51 xmem::PowerReader, 59 namelen xmem::Option, 51 xmem::PowerReader, 59 namelen xmem::Option, 51 x		operator Option *
isLast xmem::Option, 48		xmem::Option, 49
isLast xmem::Option, 48 isNUMAEnabled xmem::Configurator, 28 isThreadRunning xmem::Thread, 69 isValid xmem::Benchmark, 20 isWideChar xmem::PrintUsageImplementation, 61 isx xmem::Option, 48 latencyTestSelected xmem::Configurator, 28 LineWrapper xmem::Postorion, 48 LatencyTestSelected xmem::Descriptor, 35  MIN_ELAPSED_TICKS common.h, 86 MemoryWorker xmem::Option, 51 xmem::PowerReader, 59 namelen xmem::Option, 51	xmem::Option, 48	operator=
isNUMAEnabled xmem::Configurator, 28 isThreadRunning xmem::Thread, 69 isThreadSuspended xmem::Benchmark, 20 isWideChar xmem::PrintUsageImplementation, 61 xmem::Thread, 70 xmem::Thread, 70 xmem::Configurator, 28 last xmem::Option, 48 last xmem::Configurator, 28 LineWrapper xmem::PrintUsageImplementation::LineWrapper, 40 LoadWorker xmem::Descriptor, 35  MIN_ELAPSED_TICKS common.h, 86 MemoryWorker xmem::MemoryWorker, 43 name xmem::Potion, 51 xmem::PowerReader, 59 namelen xmem::Option, 51 xmem::PowerReader, 59 namelen xmem::Option, 51 xmem::PowerReader, 59 namelen xmem::Ooption, 51 xmem::Configurator, 28 xmem::Descriptor, 35  options xmem::Descriptor, 35 xmem::Parser, 55 parser xmem::Parser, 55 parser xmem::Parser, 55 parser xmem::Parser::Action, 13 xmem::Parser::StoreOptionAction, 66 xmem::Stats::CountOptionsAction, 34 prevwam::Stats::CountOptionsAction, 34 prevwam::Stats::CountOptionsAction, 34 prevwam::Stats::CountOptionsAction, 34 prevwam::Stats::CountOptionsAction, 34 prevwam::Stats::CountOptionsAction, 50 prevwam::Stats::CountOptionsAction, 50 prevwam::Stats::CountOptionsAction, 50 prevwam::Option, 50 process xmem::Option, 50 process xmem::PrintUsageImplementation::LineWrapper, 40 xmem::PrintUsageImplementation::LineWrapper, xmem::PrintUsageImplementation::Li	isLast	
isNUMAEnabled xmem::Configurator, 28 isThreadRunning xmem::Thread, 69 isThreadSuspended xmem::Thread, 69 isValid xmem::Parser, 55 isWideChar xmem::PrintUsageImplementation, 61 parser xmem::Parser, 53 perform xmem::Parser: \$50 perform xmem::PowerReader, \$50 perform xmem::PowerReader, \$50 perform xmem::Parser::Parser: \$50 perform xmem::Parser::Ation, 13 perform xmem::PowerReader, \$50 perform xmem::PowerReader, \$50 perform xmem::Parser::Ation, 13 perform xmem::PowerReader, \$50 perform xmem::Parser::Ation, 13 perform xmem::Parse	xmem::Option, 48	
xmem::Configurator, 28 isThreadHunning xmem::Thread, 69 isThreadSuspended xmem::Thread, 69 isValid xmem::Benchmark, 20 parse xmem::Parser, 55 parser xmem::Parser::Action, 13 xmem::Parser::StoreOptionAction, 66 xmem::Stats::CountOptionsAction, 34 perform xmem::Stats::CountOptionsAction, 34 powerReader xmem::PowerReader, 57 prev xmem::PowerReader, 57 prev xmem::PowerReader, 57 prev xmem::Descriptor, 35 process xmem::PrintUsageImplementation::LineWrapper, xmem::Descriptor, 35 process xmem::PrintUsageImplementation::LineWrapper, 40 xmem::PowerReader, 57 process xmem::PrintUsageImplementation::LineWrapper, 40 xmem::Benchmark, 20 runAll xmem::Benchmark, 20 runAll xmem::BenchmarkManager, 23 runLatencyBenchmarks xmem::BenchmarkManager, 23 runThroughputBenchmarks xmem::BenchmarkManager, 23 runThroughputBenchmarks xmem::BenchmarkManager, 23 runThroughputBenchmarks xmem::BenchmarkManager, 23 runThroughputBenchmarks xmem::BenchmarkManager, 23 particular process parser is toreOption, 51 process p	•	
isThreadRunning		xmem::Option, 47
is Thread-Hunning xmem::Thread, 69 is ThreadSuspended xmem::Benchmark, 20 is WideChar xmem::PrintUsageImplementation, 61		options_max
xmem::Thread, 69 isThreadSuspended xmem::Benchmark, 20 isWideChar xmem::PrintUsageImplementation, 61  xmem::Thread, 70  last xmem::Option, 48 latencyTestSelected xmem::Configurator, 28 LineWrapper xmem::DasceImplementation::LineWrapper, 40  LoadWorker xmem::Descriptor, 35  MIN_ELAPSED_TICKS common.h, 86 MemoryWorker xmem::MemoryWorker, 43 name xmem::Option, 51 xmem::PowerReader, 59 namelen xmem::Option, 51 xmem::Configurator, 28 xmem::Configurator, 28 xmem::Configurator, 28 xmem::Configurator, 28 xmem::Configurator, 28 yprocess xmem::Parser::S5 xmem::Parser::S0reOptionAction, 66 xmem::Parser::StoreOptionAction, 66 xmem::Parser::StoreOptionAction, 66 xmem::Parser::StoreOptionAction, 13 xmem::P		
is l'hreadSuspended xmem::Thread, 69 is Valid xmem::Benchmark, 20 is WildeChar xmem::PrintUsageImplementation, 61 perform xmem::Parser, 53 perform xmem::Parser::StoreOptionAction, 66 xmem::Chats::CountOptionsAction, 34 perform xmem::Configurator, 28 prev xmem::PowerReader xmem::PowerReader ymem::PrintUsageImplementation::LineWrapper xmem::PrintUsageImplementation::LineWrapper xmem::Descriptor, 35 run xmem::Benchmark, 20 runAll xmem::Benchmark ymem::Benchmarks xmem::Benchmarks x	xmem::Thread, 69	•
xmem::I hread, 69 isValid xmem::Benchmark, 20 isWideChar xmem::PrintUsageImplementation, 61  xmem::PrintUsageImplementation, 61  xmem::Parser, 55  Parser xmem::Parser, 53 perform xmem::Parser::StoreOptionAction, 13 xmem::Parser::StoreOptionAction, 66 xmem::Stats::CountOptionsAction, 34  PowerReader xmem::PowerReader, 57 prev xmem::PowerReader, 57 prev xmem::Option, 50 prevwrap xmem::Option, 50 prevwrap xmem::PrintUsageImplementation::LineWrapper, 40 LoadWorker xmem::LoadWorker, 41 longopt xmem::Descriptor, 35  MIN_ELAPSED_TICKS common.h, 86 MemoryWorker xmem::MemoryWorker, 43 name xmem::Option, 51 xmem::PowerReader, 59 namelen xmem::Option, 51	isThreadSuspended	•
isValid xmem::Benchmark, 20 xmem::PrintUsageImplementation, 61  perform xmem::Option, 48 latencyTestSelected xmem::Configurator, 28 LineWrapper xmem::LoadWorker xmem::LoadWorker, 41 longopt xmem::Descriptor, 35  MIN_ELAPSED_TICKS common.h, 86 MemoryWorker xmem::MemoryWorker, 43 xmem::Option, 51	•	xmemParser, 55
xmem::Benchmark, 20 isWideChar xmem::PrintUsageImplementation, 61  xmem::PrintUsageImplementation, 61  xmem::Parser, 55  perform xmem::Parser::Action, 13 xmem::Parser::StoreOptionAction, 66 xmem::Stats::CountOptionsAction, 34  PowerReader xmem::PowerReader, 57  prev xmem::Option, 48  latencyTestSelected xmem::PrintUsageImplementation::LineWrapper xmem::PrintUsageImplementation::LineWrapper, 40  LoadWorker xmem::Descriptor, 35  MIN_ELAPSED_TICKS common.h, 86  MemoryWorker xmem::MemoryWorker, 43  name xmem::Option, 51 xmem::Configurator, 28		
isWideChar		parse
xmem::PrintUsageImplementation, 61 xmem::Parser, 53  perform xmem::Thread, 70 xmem::Darser::StoreOptionAction, 66 xmem::Stats::CountOptionsAction, 34  PowerReader xmem::Configurator, 28 LineWrapper xmem::PrintUsageImplementation::LineWrapper, 40 LoadWorker xmem::Descriptor, 35  MIN_ELAPSED_TICKS common.h, 86 MemoryWorker xmem::MemoryWorker, 43 name xmem::Option, 51 xmem::Descriptor, 55 namelen xmem::Option, 51 xmem::Option, 50		xmem::Parser, 55
join xmem::Thread, 70 perform xmem::Parser::Action, 13 xmem::Parser::StoreOptionAction, 66 xmem::Stats::CountOptionsAction, 34  PowerReader xmem::Configurator, 28 LineWrapper xmem::PrintUsageImplementation::LineWrapper, 40 LoadWorker xmem::Descriptor, 35  MIN_ELAPSED_TICKS common.h, 86 MemoryWorker xmem::MemoryWorker, 43 name xmem::Option, 51 xmem::Option, 50 x	isWideChar	Parser
join xmem::Thread, 70 xmem::Parser::Action, 13 xmem::Parser::StoreOptionAction, 66 xmem::Parser::StoreOptionAction, 66 xmem::Stats::CountOptionsAction, 34 PowerReader xmem::Configurator, 28 prev xmem::PowerReader, 57 prev xmem::PrintUsageImplementation::LineWrapper xmem::PrintUsageImplementation::LineWrapper xmem::Descriptor, 35 run  MIN_ELAPSED_TICKS xmem::Benchmark, 20 runAll xmem::MemoryWorker, 43 runLatencyBenchmarks xmem::Benchmarks xmem::	xmem::PrintUsageImplementation, 61	xmem··Parser_53
xmem::Thread, 70  xmem::Thread, 70  xmem::Parser::Action, 13 xmem::Parser::StoreOptionAction, 66 xmem::Stats::CountOptionsAction, 34  PowerReader xmem::PowerReader, 57  xmem::PowerReader, 57  xmem::PowerReader, 57  prev xmem::PrintUsageImplementation::LineWrapper, 40  LoadWorker xmem::LoadWorker, 41  longopt xmem::Descriptor, 35  MIN_ELAPSED_TICKS common.h, 86  MemoryWorker xmem::MemoryWorker, 43  run  mame xmem::Option, 51 xmem::PowerReader, 57  prevwrap xmem::Option, 50 prevwrap xmem::PrintUsageImplementation::LineWrapper, 40  xmem::Benchmark, 20 runAll xmem::Benchmarks xmem::Configurator, 28  namelen xmem::Option, 51 xmem::Configurator, 28  next		
xmem::1nread, 70  last xmem::Option, 48  katencyTestSelected xmem::Configurator, 28  LineWrapper xmem::PrintUsageImplementation::LineWrapper, 40  LoadWorker xmem::Descriptor, 35  MIN_ELAPSED_TICKS common.h, 86  MemoryWorker xmem::MemoryWorker, 43  run  MIM_ELAPSED_TICKS common.h, 86  MemoryWorker xmem::Option, 51 xmem::Option, 51 xmem::PowerReader, 57  prev xmem::Option, 50 prevwrap xmem::Option, 50 prevwrap xmem::PrintUsageImplementation::LineWrapper, 40  xmem::Benchmark, 20 runAll xmem::BenchmarkManager, 23 runLatencyBenchmarks xmem::BenchmarkManager, 23 runLatencyBenchmarks xmem::BenchmarkManager, 23 runThroughputBenchmarks xmem::BenchmarkManager, 23 xmem::BenchmarkManager, 23 xmem::BenchmarkManager, 23 xmem::Dotton, 51 xmem::PowerReader, 59 namelen xmem::Option, 51 xmem::Configurator, 28 shortopt	join	•
last xmem::Option, 48	xmem::Thread, 70	
xmem::Option, 48 latencyTestSelected xmem::Configurator, 28 LineWrapper xmem::PrintUsageImplementation::LineWrapper, 40 LoadWorker xmem::Descriptor, 35  MIN_ELAPSED_TICKS common.h, 86 MemoryWorker xmem::MemoryWorker, 43  name xmem::Option, 51 xmem::PowerReader, 57 prev xmem::Option, 50 prevwrap xmem::Option, 50 prevwrap xmem::PrintUsageImplementation::LineWrapper, 40  xmem::PrintUsageImplementation::LineWrapper, 40  xmem::Benchmark, 20 runAll xmem::BenchmarkManager, 23 runLatencyBenchmarks xmem::BenchmarkManager, 23 runThroughputBenchmarks xmem::BenchmarkManager, 23 setUseOutputFile xmem::Configurator, 28 next		xmem::Parser::StoreOptionAction, 66
xmem::Option, 48PowerReaderlatencyTestSelectedxmem::PowerReader, 57xmem::Configurator, 28prevLineWrapperxmem::Option, 50xmem::PrintUsageImplementation::LineWrapper, 40prevwrapLoadWorkerxmem::Option, 50xmem::LoadWorker, 41processxmem::Descriptor, 35runMIN_ELAPSED_TICKSxmem::Benchmark, 20common.h, 86runAllMemoryWorkerxmem::BenchmarkManager, 23xmem::MemoryWorker, 43runLatencyBenchmarksxmem::BenchmarkManager, 23namerunThroughputBenchmarksxmem::PowerReader, 59xmem::BenchmarkManager, 23namelensetUseOutputFilexmem::Option, 51xmem::Configurator, 28name::Option, 51xmem::Configurator, 28	last	xmem::Stats::CountOptionsAction, 34
latencyTestSelected xmem::Configurator, 28 LineWrapper xmem::PrintUsageImplementation::LineWrapper, 40 LoadWorker xmem::LoadWorker, 41 ymm::PrintUsageImplementation::LineWrapper, xmem::PrintUsageImplementation::LineWrapper, xmem::PrintUsageImplementation::LineWrapper, 40 LoadWorker xmem::LoadWorker, 41 ymm::PrintUsageImplementation::LineWrapper, 40 xmem::Descriptor, 35 ymm::Benchmark, 20 ym		PowerReader
xmem::Configurator, 28 LineWrapper xmem::PrintUsageImplementation::LineWrapper, 40 LoadWorker xmem::LoadWorker, 41 longopt xmem::Descriptor, 35  MIN_ELAPSED_TICKS common.h, 86  MemoryWorker xmem::MemoryWorker, 43 runLatencyBenchmark, 20 runAll xmem::BenchmarkManager, 23 runLatencyBenchmarks xmem::BenchmarkManager, 23 runLatencyBenchmarks xmem::BenchmarkManager, 23 runThroughputBenchmarks xmem::Configurator, 28 shortopt		
LineWrapper xmem::PrintUsageImplementation::LineWrapper, 40  LoadWorker xmem::LoadWorker, 41 longopt xmem::Descriptor, 35  MIN_ELAPSED_TICKS common.h, 86  MemoryWorker xmem::MemoryWorker, 43  run  MemoryWorker xmem::Option, 51	•	
xmem::PrintUsageImplementation::LineWrapper, 40  LoadWorker xmem::LoadWorker, 41  longopt xmem::Descriptor, 35  MIN_ELAPSED_TICKS common.h, 86  MemoryWorker xmem::MemoryWorker, 43  xmem::MemoryWorker, 43  xmem::Descripton, 51 xmem::PowerReader, 59  namelen xmem::Option, 51 xmem	xmem::Configurator, 28	•
LoadWorker process xmem::Descriptor, 41 xmem::PrintUsageImplementation::LineWrapper, 40 xmem::Descriptor, 35 run  MIN_ELAPSED_TICKS xmem::Benchmark, 20 runAll  MemoryWorker xmem::MemoryWorker, 43 runLatencyBenchmarks xmem::BenchmarkManager, 23 runThroughputBenchmarks xmem::PowerReader, 59 ramelen xmem::Option, 51 xmem::PowerReader, 59 rest under the company of the	LineWrapper	xmem::Option, 50
LoadWorker xmem::LoadWorker, 41 longopt xmem::Descriptor, 35  MIN_ELAPSED_TICKS common.h, 86  MemoryWorker xmem::MemoryWorker, 43  name xmem::Option, 51 xmem::PowerReader, 59  namelen xmem::Option, 51 xmem::Configurator, 28 shortopt	xmem::PrintUsageImplementation::LineWrapper.	prevwrap
LoadWorker		xmem::Option, 50
xmem::LoadWorker, 41  longopt xmem::Descriptor, 35  MIN_ELAPSED_TICKS common.h, 86  MemoryWorker xmem::MemoryWorker, 43  runLatencyBenchmarkManager, 23  runLatencyBenchmarks xmem::BenchmarkManager, 23  runLatencyBenchmarks xmem::BenchmarkManager, 23  runLatencyBenchmarks xmem::BenchmarkManager, 23  runThroughputBenchmarks xmem::BenchmarkManager, 23  runThroughputBenchmarks xmem::BenchmarkManager, 23  runThroughputBenchmarks xmem::Configurator, 28  setUseOutputFile xmem::Configurator, 28  shortopt		•
longopt xmem::Descriptor, 35  run  MIN_ELAPSED_TICKS common.h, 86  MemoryWorker xmem::MemoryWorker, 43  runLatencyBenchmarkManager, 23  runLatencyBenchmarks xmem::BenchmarkManager, 23  runLatencyBenchmarks xmem::BenchmarkManager, 23  runThroughputBenchmarks xmem::BenchmarkManager, 23  runThroughputBenchmarks xmem::BenchmarkManager, 23  runThroughputBenchmarks xmem::BenchmarkManager, 23  xmem::PowerReader, 59  namelen xmem::Option, 51 xmem::Configurator, 28 shortopt		•
run  MIN_ELAPSED_TICKS xmem::Benchmark, 20 common.h, 86  MemoryWorker xmem::BenchmarkManager, 23 xmem::MemoryWorker, 43  runLatencyBenchmarkS xmem::BenchmarkManager, 23 runLatencyBenchmarks xmem::BenchmarkManager, 23 runThroughputBenchmarks xmem::Option, 51 xmem::PowerReader, 59  namelen setUseOutputFile xmem::Option, 51 xmem::Configurator, 28 shortopt	xmem::LoadWorker, 41	
MIN_ELAPSED_TICKS xmem::Benchmark, 20 common.h, 86  MemoryWorker xmem::BenchmarkManager, 23 xmem::MemoryWorker, 43  runLatencyBenchmarks xmem::BenchmarkManager, 23 runThroughputBenchmarks xmem::Option, 51 xmem::PowerReader, 59  namelen setUseOutputFile xmem::Option, 51 xmem::Configurator, 28 shortopt	longopt	40
MIN_ELAPSED_TICKS xmem::Benchmark, 20 common.h, 86  MemoryWorker xmem::BenchmarkManager, 23 xmem::MemoryWorker, 43  runLatencyBenchmarks xmem::BenchmarkManager, 23 runThroughputBenchmarks xmem::Option, 51 xmem::PowerReader, 59  namelen setUseOutputFile xmem::Option, 51 xmem::Configurator, 28 shortopt	xmem::Descriptor, 35	
common.h, 86  MemoryWorker xmem::BenchmarkManager, 23  runLatencyBenchmarks xmem::BenchmarkManager, 23  runThroughputBenchmarks xmem::Option, 51 xmem::PowerReader, 59  namelen xmem::Option, 51 xmem::Option, 51 xmem::Option, 51 xmem::Configurator, 28 shortopt	• •	run
common.h, 86  MemoryWorker xmem::BenchmarkManager, 23  runLatencyBenchmarks xmem::BenchmarkManager, 23  runThroughputBenchmarks xmem::Option, 51 xmem::PowerReader, 59  namelen xmem::Option, 51 xmem::Option, 51 xmem::Option, 51 xmem::Configurator, 28 shortopt	MIN ELAPSED TICKS	xmem::Benchmark, 20
MemoryWorker xmem::BenchmarkManager, 23  xmem::MemoryWorker, 43  runLatencyBenchmarks xmem::BenchmarkManager, 23  runThroughputBenchmarks xmem::Option, 51 xmem::PowerReader, 59  namelen xmem::Option, 51 xmem::Option, 51 xmem::Option, 51 xmem::Configurator, 28 shortopt	<del>-</del> -	runAll
xmem::MemoryWorker, 43  runLatencyBenchmarks		
name runThroughputBenchmarks xmem::Option, 51 xmem::BenchmarkManager, 23 xmem::PowerReader, 59 namelen setUseOutputFile xmem::Option, 51 xmem::Configurator, 28 next shortopt		
name runThroughputBenchmarks xmem::Option, 51 xmem::BenchmarkManager, 23 xmem::PowerReader, 59 namelen setUseOutputFile xmem::Option, 51 xmem::Configurator, 28 next shortopt	xmem::MemoryWorker, 43	
xmem::Option, 51 xmem::BenchmarkManager, 23 xmem::PowerReader, 59 namelen setUseOutputFile xmem::Option, 51 xmem::Configurator, 28 next shortopt		xmem::BenchmarkManager, 23
xmem::Option, 51 xmem::BenchmarkManager, 23 xmem::PowerReader, 59 namelen setUseOutputFile xmem::Option, 51 xmem::Configurator, 28 next shortopt	name	runThroughputBenchmarks
xmem::PowerReader, 59 namelen setUseOutputFile xmem::Option, 51 xmem::Configurator, 28 next shortopt	xmem::Option, 51	
namelen setUseOutputFile xmem::Option, 51 xmem::Configurator, 28 shortopt		<b></b> - / -
xmem::Option, 51 xmem::Configurator, 28 next shortopt		setLiseOutputFile
next shortopt		
xmem::Option, 49 xmem::Descriptor, 36		
	xmem::Option, 49	xmem::Descriptor, 36

src/Benchmark.cpp, 73	vmom::Configurator 20
• • • • • • • • • • • • • • • • • • • •	xmem::Configurator, 30
src/BenchmarkManager.cpp, 74	useChunk64b
src/Configurator.cpp, 75	xmem::Configurator, 30
src/LatencyBenchmark.cpp, 95	useLargePages
src/LoadWorker.cpp, 95	xmem::Configurator, 30
src/MemoryWorker.cpp, 96	useOutputFile
src/PowerReader.cpp, 96	xmem::Configurator, 31
src/Runnable.cpp, 97	useRandomAccessPattern
··	
src/Thread.cpp, 97	xmem::Configurator, 31
src/ThroughputBenchmark.cpp, 97	useReads
src/Timer.cpp, 98	xmem::Configurator, 31
src/benchmark_kernels.cpp, 73	useSequentialAccessPattern
src/common.cpp, 74	xmem::Configurator, 31
src/include/Benchmark.h, 75	useStrideN1
src/include/BenchmarkManager.h, 82	xmem::Configurator, 31
src/include/Configurator.h, 87	useStrideN16
src/include/ExampleArg.h, 87	
	xmem::Configurator, 31
src/include/LatencyBenchmark.h, 88	useStrideN2
src/include/LoadWorker.h, 88	xmem::Configurator, 31
src/include/MemoryWorker.h, 88	useStrideN4
src/include/MyArg.h, 89	xmem::Configurator, 32
src/include/PowerReader.h, 93	useStrideN8
src/include/Runnable.h, 93	xmem::Configurator, 32
src/include/Thread.h, 93	useStrideP1
src/include/ThroughputBenchmark.h, 94	xmem::Configurator, 32
src/include/Timer.h, 94	useStrideP16
src/include/benchmark_kernels.h, 75	xmem::Configurator, 32
src/include/common.h, 83	useStrideP2
src/include/optionparser.h, 89	xmem::Configurator, 32
src/include/win/WindowsDRAMPowerReader.h, 95	useStrideP4
src/include/win/win_CPdhQuery.h, 95	xmem::Configurator, 32
src/include/win/win_common_third_party.h, 94	useStrideP8
src/main.cpp, 96	xmem::Configurator, 32
src/win/WindowsDRAMPowerReader.cpp, 98	useWrites
• •	
src/win/win_common_third_party.cpp, 98	xmem::Configurator, 33
started	r I <del>T</del>
xmem::Thread, 70	validTarget
Stats	xmem::Thread, 70
xmem::Stats, 64	verboseMode
stop	xmem::Configurator, 33
xmem::PowerReader, 59	
StoreOptionAction	xmem::Arg, 14
•	xmem::Benchmark, 15
xmem::Parser::StoreOptionAction, 65	_averageMetric, 21
Thursd	_average_dram_power_socket, 21
Thread	
xmem::Thread, 68	_chunk_size, 21
throughputTestSelected	_cpu_node, 21
xmem::Configurator, 30	_dram_power_readers, 21
type	_dram_power_threads, 21
xmem::Descriptor, 36	_hasRun, 21
xmem::Option, 50	_iterations, 21
иноннорион, ос	_len, 21
USE_TSC_TIMER	_mem_array, 21
common.h, 86	_mem_node, 21
useChunk128b	_metricOnlter, 21
xmem::Configurator, 30	_metricUnits, 22
useChunk256b	_name, 22
xmem::Configurator, 30	_num_worker_threads, 22
useChunk32b	_obj_valid, <mark>22</mark>

_pattern_mode, 22	useStrideP16, 32
_peak_dram_power_socket, 22	useStrideP2, 32
_run_core, 17	useStrideP4, 32
_rw_mode, 22	useStrideP8, 32
_start_power_threads, 18	useWrites, 33
_stop_power_threads, 18	verboseMode, 33
_stride_size, 22	xmem::Descriptor, 34
_warning, 22	check_arg, 35
Benchmark, 17	help, 35
getAverageDRAMPower, 18	index, 35
getAverageMetric, 18	longopt, 35
getCPUNode, 18	shortopt, 36
getChunkSize, 18	type, 36
getIterations, 18	xmem::ExampleArg, 36
getLen, 19	xmem::LatencyBenchmark, 37
getMemNode, 19	_run_core, 38
getMetricOnIter, 19	xmem::LoadWorker, 40
getName, 19	LoadWorker, 41
getNumThreads, 19	xmem::MemoryWorker, 42
getPatternMode, 19	_adjusted_ticks, 44
getPeakDRAMPower, 20	_bytes_per_pass, 44
getRWMode, 20	_completed, 44
getStrideSize, 20	_cpu_affinity, 44
hasRun, 20	_elapsed_dummy_ticks, 45
isValid, 20	_elapsed_ticks, 45
run, 20	_len, 45
xmem::BenchmarkManager, 23	_mem_array, 45
BenchmarkManager, 23	_passes, 45
runAll, 23	_warning, 45
runLatencyBenchmarks, 23	getAdjustedTicks, 43
runThroughputBenchmarks, 23	getBytesPerPass, 43
xmem::Configurator, 24	getElapsedDummyTicks, 43
Configurator, 26	getElapsedTicks, 44
configureFromInput, 27	getLen, 44
getIterationsPerTest, 27	getPasses, 44
getNumWorkerThreads, 28	hadWarning, 44
getOutputFilename, 28	MemoryWorker, 43
getStartingTestIndex, 28	xmem::MyArg, 45
getWorkingSetSizePerThread, 28	xmem::Option, 46
isNUMAEnabled, 28	append, 48
latencyTestSelected, 28	arg, 50
setUseOutputFile, 28	count, 48
throughputTestSelected, 30	desc, 50
useChunk128b, 30	first, 48
useChunk256b, 30	isFirst, 48
useChunk32b, 30	isLast, 48
useChunk64b, 30	last, 48
useLargePages, 30	name, <mark>51</mark>
useOutputFile, 31	namelen, 51
useRandomAccessPattern, 31	next, 49
useReads, 31	nextwrap, 49
useSequentialAccessPattern, 31	operator const Option *, 49
useStrideN1, 31	operator Option *, 49
useStrideN16, 31	operator=, 49
useStrideN2, 31	Option, 47
useStrideN4, 32	prev, 50
useStrideN8, 32	prevwrap, 50
useStrideP1, 32	type, 50

xmem::Parser, 52	_acquireLock, 62
error, 54	_releaseLock, 62
nonOptions, 54	xmem::Stats, 63
nonOptionsCount, 54	add, 64
optionsCount, 55	buffer_max, 64
parse, 55	options_max, 64
Parser, 53	Stats, 64
xmem::Parser::Action, 13	xmem::Stats::CountOptionsAction, 33
finished, 13	CountOptionsAction, 33
perform, 13	perform, 34
xmem::Parser::StoreOptionAction, 65	xmem::Thread, 68
finished, 66	$\sim$ Thread, 68
perform, 66	cancel, 69
StoreOptionAction, 65	completed, 69
xmem::PowerReader, 56	create_and_start, 69
_average_power, 60	created, 69
_cpu_affinity, 60	getExitCode, 69
_name, 60	getTarget, 69
num samples, 60	isThreadRunning, 69
peak power, 60	isThreadSuspended, 69
_power_trace, 60	join, 70
_power_units, 60	started, 70
_sampling_period, 60	Thread, 68
stop signal, 60	validTarget, 70
calculateMetrics, 58	xmem::ThroughputBenchmark, 70
clear, 58	_run_core, 71
clear_and_reset, 58	xmem::Timer, 71
getAveragePower, 58	_ns_per_tick, 72
getLastSample, 58	_ticks_per_sec, 72
getNumSamples, 58	get_ns_per_tick, 72
getPeakPower, 59	get_ticks_per_sec, 72
getPowerTrace, 59	
getPowerUnits, 59	
getSamplingPeriod, 59	
name, 59	
PowerReader, 57	
stop, 59	
xmem::PrintUsageImplementation, 61	
isWideChar, 61	
xmem::PrintUsageImplementation::FunctionWriter<	
Function >, 37	
xmem::PrintUsageImplementation::IStringWriter, 37	
xmem::PrintUsageImplementation::LinePartIterator, 38	
next, 39	
nextRow, 39	
nextTable, 39	
xmem::PrintUsageImplementation::LineWrapper, 40	
LineWrapper, 40	
process, 40	
xmem::PrintUsageImplementation::OStreamWriter< O-	
Stream >, 51	
xmem::PrintUsageImplementation::StreamWriter<	
Function, Stream >, 66	
xmem::PrintUsageImplementation::SyscallWriter<	
Syscall >, 67	
xmem::PrintUsageImplementation::TemporaryWriter<	
Temporary >, 67	
xmem::Runnable, 61	