



Experiment No.4
Experiment on Hadoop Map-Reduce
Date of Performance: 07/08/2023
Date of Submission: 14/08/2023



Aim:- To write a program to implement a word count program using MapReduce.

Theory:

WordCount is a simple program which counts the number of occurrences of each word in a given text input data set. WordCount fits very well with the MapReduce programming model making it a great example to understand the Hadoop Map/Reduce programming style. The implementation consists of three main parts:

1. Mapper
2. Reducer
3. Driver

Step-1:- Write a Mapper

A Mapper overrides the map function from the Class "org.apache.hadoop.mapreduce.Mapper" which provides <key, value> pairs as the input. A Mapper implementation may output <key,value> pairs using the provided Context .

Input value of the WordCount Map task will be a line of text from the input data file and the key would be the line number <line_number, line_of_text> . Map task outputs <word, one> for each word in the line of text. Pseudo-code void Map (key, value){ for each word x in value:

```
output.collect(x,1);
```

```
}
```

Step-2:- Write a Reducer

A Reducer collects the intermediate <key,value> output from multiple map tasks and assemble a single result. Here, the WordCount program will sum up the occurrence of each word to pairs as <word, occurrence>. Pseudo-code



```
void Reduce (keyword, <list of  
value>){ for each x in <list of  
value>:  
sum+=x;  
  
final_output.collect(keyword, sum);  
  
}
```

Code:

```
import java.io.IOException;  
import java.util.StringTokenizer;  
import org.apache.hadoop.io.IntWritable;  
import org.apache.hadoop.io.LongWritable;  
import org.apache.hadoop.io.Text;  
import org.apache.hadoop.mapreduce.Mapper;  
import org.apache.hadoop.mapreduce.Reducer;  
import org.apache.hadoop.conf.Configuration;  
import org.apache.hadoop.mapreduce.Job;  
import org.apache.hadoop.mapreduce.lib.input.TextInputFormat;  
import org.apache.hadoop.mapreduce.lib.output.TextOutputFormat;  
import org.apache.hadoop.mapreduce.lib.input.FileInputFormat;  
import org.apache.hadoop.mapreduce.lib.output.FileOutputFormat;  
import org.apache.hadoop.fs.Path;  
public class WordCount  
{ public static class Map extends Mapper<LongWritable,Text,Text,IntWritable>  
{ public void map(LongWritable key, Text value,Context context) throws
```

```
IOException,InterruptedException{
```



```
String line = value.toString();
```

```
StringTokenizer tokenizer = new  
StringTokenizer(line); while  
(tokenizer.hasMoreTokens()) {  
    value.set(tokenizer.nextToken());  
    context.write(value, new  
    IntWritable(1));  
}  
}  
}
```

```
public static class Reduce extends  
Reducer<Text,IntWritable,Text,IntWritable> { public void  
reduce(Text key, Iterable<IntWritable> values,Context context)  
throws IOException,InterruptedException { int sum=0;  
for(IntWritable x: values)  
}  
context.write(key, new IntWritable(sum));  
}  
}
```

```
public static void main(String[] args)  
throws Exception {  
    Configuration conf= new Configuration();  
    Job job = new Job(conf,"My Word Count  
    Program");  
    job.setJarByClass(WordCount.class);  
    job.setMapperClass(Map.class);  
    job.setReducerClass(Reduce.class);  
    job.setOutputKeyClass(Text.class);  
    job.setOutputValueClass(IntWritable.clas
```



```
s);
job.setInputFormatClass(TextInputForma
t.class);
job.setOutputFormatClass(TextOutputFor
mat.class);
Path outputPath = new Path(args[1]);

//Configuring the input/output path from the filesystem into the job

FileInputFormat.addInputPath(job,newPath(args[0]));
FileOutputFormat.setOutputPath(job, new Path(args[1]));

//deleting the output path automatically from hdfs so that we don't
have to delete it explicitly
outputPath.getFileSystem(conf).delete(outpu
tPath); //exiting the job only if the flag value
becomes false
System.exit(job.waitForCompletion(true) ? 0 : 1);

}

}
```



Output:

The screenshot shows the Hadoop Overview page for localhost:9820 (active). The page has a green header with tabs: Hadoop, Overview, Datanodes, Datanode Volume Failures, Snapshot, Startup Progress, and Utilities. The Overview tab is selected, showing a table with the following information:

Started:	Wed Sep 13 04:30:53 +0530 2023
Version:	3.2.4, r7e5d9983b388e372fe640f21f048f2f2ae6e9eba
Compiled:	Tue Jul 12 17:28:00 +0530 2022 by ubuntu from branch-3.2.4
Cluster ID:	CID-146566e0-d77a-44ee-a644-d41c94627871
Block Pool ID:	BP-1532262397-192.168.12.89-1692767105768

Below the table is a Summary section. It states: Security is off. Safemode is off. 3 files and directories, 1 blocks (1 replicated blocks, 0 erasure coded block groups) = 4 total filesystem object(s). Heap Memory used 93.19 MB of 204.5 MB Heap Memory. Max Heap Memory is 889 MB. Non Heap Memory used 51.98 MB of 53.3 MB Committed Non Heap Memory. Max Non Heap Memory is <unbounded>.

Configured Capacity:	417.65 GB
Configured Remote Capacity:	0 B
DFS Used:	345 B (0%)

The screenshot shows an IDE with the WordCount program code. The code is in a file named WC_Mapper.java. It includes the following imports:

```
package org.samarth;
import java.io.IOException;
import java.util.StringTokenizer;
import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.LongWritable;
import org.apache.hadoop.io.Text;
import org.apache.hadoop.mapred.MapReduceBase;
import org.apache.hadoop.mapred.Mapper;
import org.apache.hadoop.mapred.OutputCollector;
import org.apache.hadoop.mapred.Reporter;
```

The code defines a public class WC_Mapper that extends MapReduceBase and implements Mapper<LongWritable, Text, Text, IntWritable>. It has the following methods:

```
private final static IntWritable one = new IntWritable(1);
private Text word = new Text();

public void map(LongWritable key, Text value, OutputCollector<Text, IntWritable> output,
Reporter reporter) throws IOException {
    String line = value.toString();
    StringTokenizer tokenizer = new StringTokenizer(line);
    while (tokenizer.hasMoreTokens()) {
        word.set(tokenizer.nextToken());
        output.collect(word, one);
    }
}
```



Vidyavardhini's College of Engineering & Technology

Department of Computer Engineering

```
package org.samarth;

import java.io.IOException;
import java.util.Iterator;
import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.Text;
import org.apache.hadoop.mapred.MapReduceBase;
import org.apache.hadoop.mapred.OutputCollector;
import org.apache.hadoop.mapred.Reducer;
import org.apache.hadoop.mapred.Reporter;

2 usages
public class WC_Reducer extends MapReduceBase implements Reducer<Text,IntWritable,Text,IntWritable> {
    public void reduce(Text key, Iterator<IntWritable> values,OutputCollector<Text,IntWritable> output,
        Reporter reporter) throws IOException {
        int sum=0;
        while (values.hasNext()) {
            sum+=values.next().get();
        }
        output.collect(key,new IntWritable(sum));
    }
}
```

```
import java.io.IOException;
import org.apache.hadoop.fs.Path;
import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.Text;
import org.apache.hadoop.mapred.FileInputFormat;
import org.apache.hadoop.mapred.FileOutputFormat;
import org.apache.hadoop.mapred.JobClient;
import org.apache.hadoop.mapred.JobConf;
import org.apache.hadoop.mapred.TextInputFormat;
import org.apache.hadoop.mapred.TextOutputFormat;

1 usage
public class WC_Runner {
    public static void main(String[] args) throws IOException{
        JobConf conf = new JobConf(WC_Runner.class);
        conf.setJobName("WordCount");
        conf.setOutputKeyClass(Text.class);
        conf.setOutputValueClass(IntWritable.class);
        conf.setMapperClass(WC_Mapper.class);
        conf.setCombinerClass(WC_Reducer.class);
        conf.setReducerClass(WC_Reducer.class);
        conf.setInputFormat(TextInputFormat.class);
        conf.setOutputFormat(TextOutputFormat.class);
        FileInputFormat.setInputPaths(conf,new Path(args[0]));
        FileOutputFormat.setOutputPath(conf,new Path(args[1]));
        JobClient.runJob(conf);
    }
}
```




```
Command Prompt
Microsoft Windows [Version 10.0.22000.2295]
(c) Microsoft Corporation. All rights reserved.

C:\Users\admin>cd Desktop

C:\Users\admin\Desktop>hadoop fs -mkdir /input

C:\Users\admin\Desktop>hadoop fs -put input.txt /input

C:\Users\admin\Desktop>
```



Browse Directory

/input

Go!

Show

25

entries

Search:

<input type="checkbox"/>		Permission		Owner		Group		Size		Last Modified		Replication		Block Size		Name	
<input type="checkbox"/>		-rw-r--r--		admin		supergroup		36 B		Sep 13 04:53		1		128 MB		input.txt	

Showing 1 to 1 of 1 entries

Previous

1

Next

Hadoop, 2022.



Vidyavardhini's College of Engineering & Technology

Department of Computer Engineering


The screenshot shows the Hadoop web interface at localhost:9870. A modal window titled "File information - input.txt" is open, displaying details for the file "input.txt". The modal includes tabs for "Download", "Head the file (first 32K)", and "Tail the file (last 32K)". The "Block Information" section shows the block ID as 1073741825, block pool ID as BP-1815554947-192.168.137.1-1695993949979_0001, generation stamp as 1001, size as 75, and availability as LAPTOP-K02APR2F.mshome.net. The "File contents" section shows the text: "Hello World", "Hello My name is Samarth Pandey I am Samarth", and "Welcome to World".

```
Command Prompt
C:\Users\samar\Desktop>hadoop fs -mkdir /input
C:\Users\samar\Desktop>hadoop fs -put input.txt /input
C:\Users\samar\Desktop>hadoop jar C:\Users\samar\IdeaProjects\WordCount\target\hadoop-mapreduce--3.2.4.jar wordcount /input/input.txt /output
2023-09-29 18:57:08,319 INFO client.RMProxy: Connecting to ResourceManager at /0.0.0.0:8032
2023-09-29 18:57:09,763 INFO mapreduce.JobResourceUploader: Disabling Erasure Coding for path: /tmp/hadoop-yarn/staging/samar/.staging/job_1695993949979_0001
2023-09-29 18:57:10,326 INFO input.FileInputFormat: Total input files to process : 1
2023-09-29 18:57:10,697 INFO mapreduce.JobSubmitter: number of splits:1
2023-09-29 18:57:11,007 INFO mapreduce.JobSubmitter: Submitting tokens for job: job_1695993949979_0001
2023-09-29 18:57:11,010 INFO mapreduce.JobSubmitter: Executing with tokens: []
2023-09-29 18:57:11,200 INFO conf.Configuration: resource-types.xml not found
2023-09-29 18:57:11,380 INFO resource.ResourceUtils: Unable to find 'resource-types.xml'.
2023-09-29 18:57:11,723 INFO impl.YarnClientImpl: Submitted application application_1695993949979_0001
2023-09-29 18:57:11,814 INFO mapreduce.Job: The url to track the job: http://LAPTOP-K02APR2F:8088/proxy/application_1695993949979_0001/
2023-09-29 18:57:11,816 INFO mapreduce.Job: Running job: job_1695993949979_0001
2023-09-29 18:57:27,135 INFO mapreduce.Job: Job job_1695993949979_0001 running in uber mode : false
2023-09-29 18:57:27,136 INFO mapreduce.Job: map 0% reduce 0%
2023-09-29 18:57:35,308 INFO mapreduce.Job: map 100% reduce 0%
2023-09-29 18:57:43,413 INFO mapreduce.Job: map 100% reduce 100%
2023-09-29 18:57:44,434 INFO mapreduce.Job: Job job_1695993949979_0001 completed successfully
2023-09-29 18:57:45,177 INFO mapreduce.Job: Counters: 54
File System Counters
  FILE: Number of bytes read=126
  FILE: Number of bytes written=478089
  FILE: Number of read operations=0
  FILE: Number of large read operations=0
  FILE: Number of write operations=0
  HDFS: Number of bytes read=177
  HDFS: Number of bytes written=76
  HDFS: Number of read operations=8
  HDFS: Number of large read operations=0
  HDFS: Number of write operations=2
  HDFS: Number of bytes read erasure-coded=0
Job Counters
  Launched map tasks=1
  Launched reduce tasks=1
  Data-local map tasks=1
  Total time spent by all maps in occupied slots (ms)=5488
  Total time spent by all reduces in occupied slots (ms)=5838
  Total time spent by all map tasks (ms)=5488
  Total time spent by all reduce tasks (ms)=5838
  Total vcore-milliseconds taken by all map tasks=5488
  Total vcore-milliseconds taken by all reduce tasks=5838
  Total megabyte-milliseconds taken by all map tasks=5619712
  Total megabyte-milliseconds taken by all reduce tasks=5978112
Map-Reduce Framework
  Map input records=3
```



Vidyavardhini's College of Engineering & Technology

Department of Computer Engineering



Browse Directory

/


Show 25 entries Search:

Permission	Owner	Group	Size	Last Modified	Replication	Block Size	Name
drwxr-xr-x	samar	supergroup	0 B	Sep 29 18:56	0	0 B	input
drwxr-xr-x	samar	supergroup	0 B	Sep 29 18:57	0	0 B	output
drwxr-xr-x	samar	supergroup	0 B	Sep 29 18:57	0	0 B	tmp

Showing 1 to 3 of 3 entries

Previous 1 Next

Hadoop, 2022.





Conclusion:

MapReduce is a programming paradigm that enables massive scalability across hundreds or thousands of servers in a Hadoop cluster. It framework for processing and analyzing large datasets by dividing them into smaller tasks that can be distributed across a cluster of computers. The way we manage large data has been completely transformed by the flexible and reliable MapReduce framework, which is still a useful tool for data processing and analysis. WordCount is a simple program which counts the number of occurrences of each word in a given text input data set.

In this experiment, we successfully implemented program for word count using MapReduce.