



## Vidyavardhini's College of Engineering & Technology

### Department of Computer Engineering

**Aim:** To study the object segmentation.

**Objective:** To study the object segmentation using watershed algorithm. Example image segmentation with watershed algorithm.

### Theory:

Image segmentation is the process of dividing an image into several disjoint small local areas or cluster sets according to certain rules and principles. The watershed algorithm is a computer vision technique used for image region segmentation “**outline of an object**”.

### Watershed Algorithm:

The watershed algorithm uses topographic information to divide an image into multiple segments or regions. The algorithm views an image as a topographic surface, each pixel representing a different height. The watershed algorithm uses this information to identify catchment basins, similar to how water would collect in valleys in a real topographic map. The watershed algorithm identifies the local minima, or the lowest points, in the image. These points are then marked as markers.

The algorithm then floods the image with different colors, starting from these marked markers. As the color spreads, it fills up the catchment basins until it reaches the boundaries of the objects or regions in the image. The Catchment Basin in the watershed algorithm refers to a region in the image that is filled by the spreading color starting from a marker. The catchment basin is defined by the boundaries of the object or region in the image and the local minima in the intensity values of the pixels. The algorithm uses the catchment basins to divide the image into separate regions and then identifies the boundaries between the basins to create a segmentation of the image for object recognition, image analysis, and feature extraction tasks.




## Vidyavardhini's College of Engineering & Technology

### Department of Computer Engineering


The whole process of the watershed algorithm can be summarized in the following steps:

- **Marker placement:** The first step is to place markers on the local minima, or the lowest points, in the image. These markers serve as the starting points for the flooding process.
- **Flooding:** The algorithm then floods the image with different colors, starting from the markers. As the color spreads, it fills up the catchment basins until it reaches the boundaries of the objects or regions in the image.
- **Catchment basin formation:** As the color spreads, the catchment basins are gradually filled, creating a segmentation of the image. The resulting segments or regions are assigned unique colors, which can then be used to identify different objects or features in the image.
- **Boundary identification:** The watershed algorithm uses the boundaries between the different colored regions to identify the objects or regions in the image. The resulting segmentation can be used for object recognition, image analysis, and feature extraction tasks.

Sure Background




Distance Transform






Vidyavardhini's College of Engineering & Technology  
Department of Computer Engineering

Sure Foreground



Unknown



**Code:**

```
import cv2
import numpy as np
from IPython.display import Image, display
from matplotlib import pyplot as plt

def imshow(img, ax=None):
    if ax is None:
        ret, encoded = cv2.imencode("/content/sample_data/pic1.jpeg", img)
        display(Image(encoded))
    else:
        ax.imshow(cv2.cvtColor(img, cv2.COLOR_BGR2RGB))
        ax.axis('off')

img = cv2.imread("/content/sample_data/pic1.jpeg")
gray = cv2.cvtColor(img, cv2.COLOR_BGR2GRAY)
```



## Vidyavardhini's College of Engineering & Technology

### Department of Computer Engineering

```
imshow(img)

ret, bin_img = cv2.threshold(gray, 0,255, cv2.THRESH_BINARY_INV
+cv2.THRESH_OTSU)

imshow(bin_img)

kernel = cv2.getStructuringElement(cv2.MORPH_RECT, (3, 3))

bin_img = cv2.morphologyEx(bin_img,cv2.MORPH_OPEN,kernel,iterations=2)

imshow(bin_img)

fig, axes = plt.subplots(nrows=2,ncols=2, figsize=(8, 8))

sure_bg = cv2.dilate(bin_img, kernel,iterations=3)

imshow(sure_bg, axes[0,0])

axes[0, 0].set_title('Sure Background')

dist = cv2.distanceTransform(bin_img,cv2.DIST_L2, 5)

imshow(dist, axes[0,1])

axes[0, 1].set_title('Distance Transform')

ret, sure_fg = cv2.threshold(dist, 0.5* dist.max(), 255, cv2.THRESH_BINARY)

sure_fg = sure_fg.astype(np.uint8)

imshow(sure_fg, axes[1,0])

axes[1, 0].set_title('Sure Foreground')

unknown = cv2.subtract(sure_bg,sure_fg)

imshow(unknown, axes[1,1])


axes[1, 1].set_title('Unknown')

plt.show()
```



Vidyavardhini's College of Engineering & Technology  
Department of Computer Engineering

**Output:**





Vidyavardhini's College of Engineering & Technology  
Department of Computer Engineering







Vidyavardhini's College of Engineering & Technology  
Department of Computer Engineering

Sure Background



Distance Transform



Sure Foreground



Unknown





## Vidyavardhini's College of Engineering & Technology Department of Computer Engineering

### **Conclusion:**

Image segmentation is the process of dividing an image into several groups or cluster sets according to certain rules and principles. By dividing an image into segments, you can process only the important segments of the image instead of processing the entire image. The watershed algorithm divides a picture into various sections or segments using topographic data. Each pixel in an image is interpreted by the algorithm as a different height on a topographic surface.

In this experiment, we successfully implemented object segmentation using watershed algorithm.