

# GPU Computing With Apache Spark And Python

Siu Kwan Lam  
Continuum Analytics



SPARK SUMMIT 2016  
DATA SCIENCE AND ENGINEERING AT SCALE



# ANACONDA®



- I'm going to use Anaconda throughout this presentation.
- Anaconda is a free Mac/Win/Linux Python distribution:
  - Based on conda, an open source package manager
  - Installs both *Python* and *non-Python* dependencies
  - Easiest way to get the software I will talk about today
- <https://www.continuum.io/downloads>





# Overview

- Why Python?
- Using GPU in PySpark
  - An example: Image registration
  - Accelerate: Drop-in GPU-accelerated functions
  - Numba: JIT Custom GPU-accelerated functions
- Tips & Tricks





# WHY PYTHON?





# Why is Python so popular?

- Straightforward, productive language for *system administrators, programmers, scientists, analysts and hobbyists*
- Great community:
  - Lots of tutorial and reference materials
  - Vast ecosystem of useful libraries
  - Easy to interface with other languages






[Home](#) [Installation](#) [Documentation](#) [Examples](#)

Google Custom Search

Search x

Fork me on GitHub



# scikit-learn

Machine Learning in Python

- Simple and efficient tools for data mining and data analysis
- Accessible to everybody, and reusable in various contexts
- Built on NumPy, SciPy, and matplotlib
- Open source, commercially usable - BSD license

## Classification

Identifying to which category an object belongs to.

**Applications:** Spam detection, Image recognition.

**Algorithms:** SVM, nearest neighbors, random forest, ... — Examples

## Regression

Predicting a continuous-valued attribute associated with an object.

**Applications:** Drug response, Stock prices.  
**Algorithms:** SVR, ridge regression, Lasso, ... — Examples

## Clustering

Automatic grouping of similar objects into sets.

**Applications:** Customer segmentation, Grouping experiment outcomes  
**Algorithms:** k-Means, spectral clustering, mean-shift, ... — Examples

## Dimensionality reduction

Reducing the number of random variables to consider.

**Applications:** Visualization, Increased efficiency  
**Algorithms:** PCA, feature selection, non-negative matrix factorization. — Examples

## Model selection

Comparing, validating and choosing parameters and models.

**Goal:** Improved accuracy via parameter tuning  
**Modules:** grid search, cross validation, metrics. — Examples

## Preprocessing

Feature extraction and normalization.

**Application:** Transforming input data such as text for use with machine learning algorithms.  
**Modules:** preprocessing, feature extraction. — Examples







# But... Python is slow!

- *Pure, interpreted Python is slow.*
- Python excels at interfacing with other languages used in HPC:
  - C: ctypes, CFFI, Cython
  - C++: Cython, Boost.Python
  - FORTRAN: f2py
- Secret: Most scientific Python packages put the speed critical sections of their algorithms in a compiled language.





# Is there another way?

- Switching languages for speed in your projects can be a little clunky
- Generating compiled functions for the wide range of data types can be tedious
- How can we use cutting edge hardware, like GPUs?







An example for using GPU in PySpark

# IMAGE REGISTRATION






# Image Registration

- An experiment to demonstrate GPU usage
- The problem:
  - stitch image fragments
  - fragments are randomly orientated, translated and scaled.
- phase-correlation for image registration
  - FFT heavy







## Basic Algorithm




top 1




top 2



top 3




top 4





## Basic Algorithm





# Setup

- conda can create a local environment for Spark for you:

```
conda create -n spark -c anaconda-cluster python=3.5 spark \
    accelerate ipython-notebook
```

```
source activate spark
```

```
IPYTHON_OPTS="notebook" ./bin/pyspark # starts jupyter notebook
```





# Performance Bottleneck

- Most of the time spent in 2D FFT

```
def cross_power_spectrum(im0, im1):  
    f0 = numpy.fft.fft2(im0)  
    f1 = numpy.fft.fft2(im1)  
    eps = 1e-15  
    cps = (f0 * f1.conjugate()) / (abs(f0) * abs(f1) + eps)  
    return abs(numpy.fft.ifft2(cps))
```







# ACCELERATE DROP-IN GPU-ACCELERATED FUNCTIONS





# Accelerate

- Commercial licensed
- Hardware optimized numerical functions
- SIMD optimized via MKL
- GPU accelerated via CUDA





# CUDA Library Bindings: cuFFT

In [2]: `from accelerate.cuda import fft`

```
arr = np.random.random(10**6).astype(np.float32)
out = np.zeros_like(arr, dtype=np.complex64)
fft.fft(arr, out)
```

Out[2]: `array([ 5.00258000e+05 +0.j , -1.29911041e+01-79.63054657j,
 -2.77468071e+01+74.94405365j, ..., 1.35268259e+00 +1.04822063j,
 1.32095528e+00 +1.1744678j , 8.91982377e-01 +1.14550018j]), dtype=complex64)`

In [3]: `%timeit`

```
res1 = np.fft.fft(arr)
```

100 loops, best of 3: 16.6 ms per loop

MKL accelerated FFT

In [4]: `%timeit`

```
res2 = fft.fft(arr, out)
```

100 loops, best of 3: 7.33 ms per loop

**>2x speedup** incl. host<->device round trip  
on GeForce GT 650M



# CPS with GPU drop-in

- Replace *numpy* FFT with *accelerate* version

```
from accelerate.cuda import fft as cufft

def cross_power_spectrum(im0, im1):
    f0 = im0.astype(numpy.complex64)
    f1 = im1.astype(numpy.complex64)
    cufft.fft_inplace(f0)
    cufft.fft_inplace(f1)
    eps = 1e-15
    cps = (f0 * f1.conjugate()) / (abs(f0) * abs(f1) + eps)
    cufft.ifft_inplace(cps)
    return abs(cps)
```





# CPS with GPU drop-in

- Replace *numpy* FFT with *accelerate* version

```
from accelerate.cuda import fft as cufft

def cross_power_spectrum(im0, im1):
    f0 = im0.astype(numpy.complex64)
    f1 = im1.astype(numpy.complex64)
    cufft.fft_inplace(f0)
    cufft.fft_inplace(f1)
    eps = 1e-15
    cps = (f0 * f1.conjugate()) / (abs(f0) * abs(f1) + eps)
    cufft.ifft_inplace(cps)
    return abs(cps)
```

CPU-GPU transfer

CPU-GPU transfer





# NUMBA JIT CUSTOM GPU-ACCELERATED FUNCTIONS







# Numba

- Opensource licensed
- A Python JIT as a CPython library
- Array/numerical subset
- Targets CPU and GPU





# Supported Platforms


OS	HW	SW
• Windows (7 and later)	• 32 and 64-bit x86 CPUs	• Python 2 and 3
• OS X (10.7 and later)	• <b>CUDA-capable NVIDIA GPUs</b>	• NumPy 1.7 through 1.11
• Linux (~RHEL 5 and later)	• HSA-capable AMD GPUs	
	• Experimental support for ARMv7 (Raspberry Pi 2)	





# How Does Numba Work?

```
@jit
def do_math(a, b):
    ...
>>> do_math(x, y)
```



# Ufuncs—Map operation for ND arrays



```
In [1]: import numpy as np
import math
from numba import vectorize

@vectorize(["float32(float32, float32)",
           "float64(float64, float64)"], target='cpu')
def cpu_some_trig(x, y):
    return math.cos(x) + math.sin(y)

@vectorize(["float32(float32, float32)",
           "float64(float64, float64)"], target='cuda')
def cuda_some_trig(x, y):
    return math.cos(x) + math.sin(y)
```



# Ufuncs—Map operation for ND arrays



In [1]:

```
import numpy as np
import math
from numba import vectorize
```

Decorator for creating ufunc

```
@vectorize(["float32(float32, float32)",
           "float64(float64, float64)"], target='cpu')
```

List of supported type signatures

```
def cpu_some_trig(x, y):
    return math.cos(x) + math.sin(y)
```

Code generation target

```
@vectorize(["float32(float32, float32)",
           "float64(float64, float64)"], target='cuda')
```

```
def cuda_some_trig(x, y):
    return math.cos(x) + math.sin(y)
```







# GPU Ufuncs Performance

```
In [2]: nelem = 10 ** 6  
xs = np.random.random(nelem).astype(np.float32)  
ys = np.random.random(nelem).astype(np.float32)
```

```
In [3]: %%timeit  
res1 = cpu_some_trig(xs, ys)  
  
100 loops, best of 3: 18.8 ms per loop
```

```
In [4]: %%timeit  
res2 = cuda_some_trig(xs, ys)  
  
100 loops, best of 3: 4.19 ms per loop
```

**4x speedup** incl. host<->device round trip  
on GeForce GT 650M







# Numba in Spark

- Compiles to IR on client
  - Or not if type information is not available yet
- Send IR to workers
- Finalize to machine code on workers



# CPS with cuFFT + GPU ufuncs



```
@vectorize(['complex64(float32)',  
           'complex64(float64)',  
           'complex64(uint8)'], target='cuda')  
def as_complex64(x):  
    return np.complex64(x)
```

cuFFT

```
def cross_power_spectrum(im0, im1):  
    f0 = as_complex64(cuda.to_device(im0))  
    f1 = as_complex64(cuda.to_device(im1))  
    cufft.fft_inplace(f0)  
    cufft.fft_inplace(f1)  
    d_cps = elemwise_mult_conjugate(f0, f1)  
    cufft.ifft_inplace(d_cps)  
    cps = complex_abs(d_cps).copy_to_host()  
    return cps
```

explicit memory transfer

```
@vectorize(['complex64(complex64, complex64)'], target='cuda')  
def elemwise_mult_conjugate(f0, f1):  
    eps = 1e-15  
    return (f0 * f1.conjugate()) / (abs(f0) * abs(f1) + eps)
```

```
@vectorize(['float32(complex64)'], target='cuda')  
def complex_abs(x):  
    return abs(x)
```



# TIPS & TRICKS





# Operate in Batches

- GPUs have many-cores
- Best to do many similar task at once
- GPU kernel launch has overhead
- prefer *mapPartitions*, *mapValues* over *map*





# Under-utilization of GPU

- PySpark spawns 1 Python process per core
- Only 1 CUDA process per GPU at a time
- **Under-utilize** the GPU easily
- GPU context-switching between processes





# Under-utilization of GPU (Fix)

- `nvidia-cuda-mps-control`
- Originally for MPI
- Allow multiple process per GPU
- Reduce per-process overhead
- Increase GPU utilization
  - 10-15% speedup in our experiment







# Summary

- Anaconda:
  - creates Spark environment for experimentation
  - manages Python packages for use in Spark
- Accelerate:
  - Pre-built GPU functions within PySpark
- Numba:
  - JIT custom GPU functions within PySpark



# THANK YOU.

email: [slam@continuum.io](mailto:slam@continuum.io)



**ANACONDA**  
by Continuum Analytics®



**SPARK SUMMIT 2016**  
DATA SCIENCE AND ENGINEERING AT SCALE

# Extras



SPARK SUMMIT 2016  
DATA SCIENCE AND ENGINEERING AT SCALE



# NUMBA: A PYTHON JIT COMPILER





# Compiling Python

- Numba is a type-specializing compiler for Python functions
- Can translate Python syntax into machine code if all type information can be deduced when the function is called.
- Code generation done with:
  - LLVM (for CPU)
  - NVVM (for CUDA GPUs).






# How Does Numba Work?

@jit

```
def do_math(a, b):
```

```
...
```

```
>>> do_math(x, y)
```







# Numba on the CPU

```
In [87]: @jit(nopython=True)
def nan_compact(x):
    out = np.empty_like(x)
    out_index = 0
    for element in x:
        if not np.isnan(element):
            out[out_index] = element
            out_index += 1
    return out[:out_index]
```

```
In [88]: a = np.random.uniform(size=10000)
a[a < 0.2] = np.nan
np.testing.assert_equal(nan_compact(a), a[~np.isnan(a)])
```

```
In [89]: %timeit a[~np.isnan(a)]
%timeit nan_compact(a)
```

10000 loops, best of 3: 52  $\mu$ s per loop

100000 loops, best of 3: 19.6  $\mu$ s per loop





# Numba on the CPU

Numba decorator  
(nopython=True not required)

```
In [87]: @jit(nopython=True)
def nan_compact(x):
    out = np.empty_like(x)
    out_index = 0
    for element in x:
        if not np.isnan(element):
            out[out_index] = element
            out_index += 1
    return out[:out_index]
```

Array Allocation

Looping over ndarray x as an iterator

Using numpy math functions

Returning a slice of the array

```
In [88]: a = np.random.uniform(size=10000)
a[a < 0.2] = np.nan
np.testing.assert_equal(nan_compact(a), a[~np.isnan(a)])
```

```
In [89]: %timeit a[~np.isnan(a)]
%timeit nan_compact(a)
```

10000 loops, best of 3: 52  $\mu$ s per loop  
100000 loops, best of 3: 19.6  $\mu$ s per loop

2.7x speedup!





# CUDA Kernels in Python

```
In [2]: @numba.cuda.jit
def zero_suppression_gpu(x, threshold, out):
    i = numba.cuda.grid(1)

    while i < x.size:
        element = x[i]
        if abs(element) > threshold:
            out[i] = element
        else:
            out[i] = 0

    i += numba.cuda.gridsize(1)
```





# CUDA Kernels in Python

Decorator will infer type signature when you call it

```
In [2]: @numba.cuda.jit
def zero_suppression_gpu(x, threshold, out):
    i = numba.cuda.grid(1)

    while i < x.size:
        element = x[i]
        if abs(element) > threshold:
            out[i] = element
        else:
            out[i] = 0

    i += numba.cuda.gridsize(1)
```

Helper function to compute  
 $\text{blockIdx.x} * \text{blockDim.x} + \text{threadIdx.x}$

NumPy arrays have expected  
attributes and indexing

Helper function to compute  
 $\text{blockDim.x} * \text{gridDim.x}$





# Calling the Kernel from Python

```
In [3]: # Create some sample data and an output array
x = np.random.randint(-4096, 4096, size=100000).astype(np.int16)
out = np.empty_like(x)

# Pick configuration and launch
threadsperblock = 256
blockspergrid = (x.size + (threadsperblock - 1)) // threadsperblock
zero_suppression_gpu[threadsperblock, blockspergrid](x, 50, out)

print(out)

[ 2447 -3900      0 ..., 3323 -1089 1995]
```

Works just like CUDA C, except we handle allocating and copying data to/from the host if needed







# Handling Device Memory Directly

```
In [6]: %timeit zero_suppression_gpu[threadsperblock, blockspergrid](x, 50, out)
```

The slowest run took 7.42 times longer than the fastest. This could mean that an intermediate result is being cached.

1000 loops, best of 3: 927  $\mu$ s per loop

```
In [7]: gpu_x = numba.cuda.to_device(x)
        gpu_out = numba.cuda.to_device(out)

        %timeit zero_suppression_gpu[threadsperblock, blockspergrid](gpu_x, 50, gpu_out)
```

1000 loops, best of 3: 198  $\mu$ s per loop

Memory allocation matters in small tasks.








# NUMBA IN SPARK







# Using Numba with Spark

```
In [37]: random_arrays = [np.random.randint(-4096, 4096, size=10000).astype(np.int16)
                        for i in range(1000)]
chunks = sc.parallelize(random_arrays)
```

```
In [38]: @numba.jit(nopython=True)
def zero_suppression(x, threshold):
    result = np.empty_like(x)
    for i in range(x.shape[0]):
        if np.abs(x[i]) > threshold:
            result[i] = x[i]
        else:
            result[i] = 0
    return result
```

```
In [39]: %timeit np.where(np.abs(random_arrays[0]) > 25, random_arrays[0], 0)
%timeit zero_suppression(random_arrays[0], 25)
```

The slowest run took 6.77 times longer than the fastest. This could mean that an intermediate result is being cached.

10000 loops, best of 3: 41.6  $\mu$ s per loop

The slowest run took 5202.15 times longer than the fastest. This could mean that an intermediate result is being cached.

10000 loops, best of 3: 20.9  $\mu$ s per loop

```
In [40]: chunks.map(lambda x: zero_suppression(x, 25)).first()
```

```
Out[40]: array([-43, -3824, -3618, ..., 349, -3929, -4018], dtype=int16)
```





# Using CUDA Python with Spark

```
In [1]: import numpy as np
        from numba import cuda
```

```
@cuda.jit("(float32[:,], float32[:,])")
def foo(inp, out):
    i = cuda.grid(1)
    if i < out.size:
        out[i] = inp[i] ** 2
```

Define CUDA kernel  
Compilation happens here

```
In [2]: def gpu_work(xs):
        inp = np.asarray(list(xs), dtype=np.float32)
        out = np.zeros_like(inp)
        block_size = 32 * 4
        grid_size = (inp.size + block_size - 1) // block_size
        foo[grid_size, block_size](inp, out)
        return out
```

Wrap CUDA kernel launching  
logic

```
In [3]: rdd = sc.parallelize(list(range(100)))
        rdd.getNumPartitions()
```

Creates Spark RDD (8 partitions)


```
Out[3]: 8
```

```
In [4]: rdd = rdd.mapPartitions(gpu_work)
        print(rdd.collect())
```

Apply gpu\_work on each partition



## Compilation and Code Delivery





## Compilation and Code Delivery

