

Team : hmm

Inha University

Minkyum Kim

Jongmin Jung

Jinhyeon Kim

Prof. Yeongho Kim

Inha University

Team : hmm

Coach : Prof. Yeongho Kim

Contestant : Minkyum Kim, Jongmin Jung, Jinhyeon Kim

Contents

1. Graph

1. Dijkstra
2. Floyd-Warshall
3. Minimum Spanning Tree
4. Topological Sort
5. Strongly Connected Components
6. Maximum Flow
7. Bipartite Matching
8. Lowest Common Ancestor

2. Data Structure

1. Segment Tree
2. Fenwick Tree with Lazy Propagation
3. Segment Tree with Lazy Propagation
4. Merge Sort Tree
5. Segment Tree(OpeningSound)
6. Segment Tree with Lazy Propagation(OpeningSound)

3. String

1. KMP
2. Rabin-Karp
3. Trie
4. Aho-Corasick

5. Suffix Array and Longest Common Prefix Array
6. Manacher
7. Z

4. Math

1. Greatest Common Divisor and Least Common Multiple
2. Sieve of Eratosthenes
3. Binomial Coefficient
4. Matrix Exponential
5. Fast Fourier Transform
6. Berlekamp-Massey
7. Extended Euclidean Algorithm

5. Geometry

1. CCW
2. Convex Hull
3. Line Intersection

6. Others

1. Decimal in python
2. Fraction in python
3. Bit Operations
4. Coordinate Compression
5. Knuth Optimization
6. Some Prime Numbers
7. Longest Increasing Subsequence
8. Rope
9. PBDS Set
10. Divide and Conquer Optimization

7. Tips

1. Graph

1. Dijkstra

```
typedef pair<ll, int> p;
const ll INF = 1e12;
auto dijkstra = [&](int start, vector<p> e[]) -> vector<ll>{
    vector<ll> v(N + 1);
    for (auto &i : v) i = INF;
    priority_queue<p, vector<p>, greater<p>> pq;
    v[start] = 0; pq.push({ 0, start });
    while (!pq.empty()) {
        ll cost, des, next, there;
        tie(cost, des) = pq.top(); pq.pop();
        for (auto k : e[des]) {
            tie(next, there) = k; next += cost;
            if (v[there] > next) {
                v[there] = next;
                pq.push({ next, there });
            }
        }
    }
    return v;
};
```

2. Floyd-Warshall

```
const int INF = 1000000000;
int N, M, dist[101][101];
int main() {
    cin >> N >> M;
    for (int i = 1; i <= N; i++) {
        for (int j = 1; j <= N; j++) {
            dist[i][j] = i == j ? 0 : INF;
        }
    }
    for (int i = 1; i <= M; i++) {
        int in1, in2, in3;
        cin >> in1 >> in2 >> in3;
        dist[in1][in2] = min(dist[in1][in2], in3);
    }
}
```

```
for (int k = 1; k <= N; k++) {
    for (int i = 1; i <= N; i++) {
        for (int j = 1; j <= N; j++) {
            dist[i][j] = min(dist[i][j], dist[i][k] + dist[k][j]);
        }
    }
}
for (int i = 1; i <= N; i++) {
    for (int j = 1; j <= N; j++) {
        cout << dist[i][j] << ' ';
    }
    cout << '\n';
}
}
```

3. Minimum Spanning Tree

```
typedef tuple<int, int, int> t;
int uf[10001];
int N, M, in1, in2, in3;
priority_queue<t, vector<t>, greater<t>> pq;
int find(int a) {
    if (uf[a] == a) return a;
    return uf[a] = find(uf[a]);
}
void merge(int a, int b) {
    a = find(a);
    b = find(b);
    if (a != b) uf[b] = a;
}
int main() {
    cin >> N >> M;
    for (int i = 0; i < M; i++) {
        cin >> in1 >> in2 >> in3;
        pq.push({ in3, in1, in2 }); //Distance, Start, End
    }
    for (int i = 1; i <= N; i++) uf[i] = i; //Union-Find Initialization
    ll cnt = 0, ans = 0;
    while (!pq.empty()) {
        if (cnt == N - 1) break; //N - 1 connections are enough for a spanning tree
        tie(cost, st, se) = pq.top();
```

```

    pq.pop();
    if (find(st) == find(se)) continue;
    merge(st, se);
    cnt++; ans += cost;
}
cout << ans;
}

```

4. Topological Sort

```

int main() {
    int N, M;
    int indegree[32001] = { 0 };
    vector<int> edge[32001], res;
    queue<int> q;
    cin >> N >> M;
    for (int i = 1; i <= M; i++) {
        int in1, in2;
        cin >> in1 >> in2;
        indegree[in2]++;
        edge[in1].push_back(in2);
    }
    for (int i = 1; i <= N; i++) {
        if (indegree[i] == 0) q.push(i);
    }
    for (int i = 1; i <= N; i++) {
        if (q.empty()) {
            cout << "Cannot Sort";
            return 0;
        }
        int cur = q.front();
        q.pop();
        res.push_back(cur);
        for (int next : edge[cur]) {
            if (--indegree[next] == 0) q.push(next);
        }
    }
    for (int i = 0; i < res.size(); i++) {
        cout << res[i] << ' ';
    }
}

```

5. Strongly Connected Components

```

const int MAX = 10001;
int V, E;
vector<int> edge[MAX];
int sccCnt; //How many SCCs?
vector<vector<int>> SCC; //Stores Vertices of each SCCs
int dfsCnt, dfsn[MAX], sccInd[MAX];
bool finished[MAX];
stack<int> s;
int makeSCC(int cur) { //return index cur's SCC number
    dfsn[cur] = ++dfsCnt;
    s.push(cur);
    int res = dfsn[cur];
    for (int next : edge[cur]) {
        if (dfsn[next] == 0) res = min(res, makeSCC(next));
        else if (finished[next] == 0) res = min(res, dfsn[next]);
    }
    if (res == dfsn[cur]) {
        vector<int> curSCC;
        while (1) {
            int t = s.top();
            s.pop();
            curSCC.push_back(t);
            finished[t] = 1;
            sccInd[t] = sccCnt;
            if (t == cur) break;
        }
        //sort(curSCC.begin(), curSCC.end());
        SCC.push_back(curSCC);
        sccCnt++;
    }
    return res;
}
int main() {
    cin >> V >> E;
    for (int i = 0; i < E; i++) {
        int in1, in2;
        cin >> in1 >> in2;
        edge[in1].push_back(in2);
    }
}

```

```

}
for (int i = 1; i <= V; i++) if (dfs[i] == 0) makeSCC(i);
//sort(SCC.begin(), SCC.end());
//cout << sccCnt << '\n';
for (auto& curSCC : SCC) {
    for (int cur : curSCC) {
        cout << cur << ' ';
    }
    cout << '\n';
}
}

```

6. Maximum Flow

```

const int MAX = 800;
const ll INF = 2100000000;
int c[MAX][MAX], f[MAX][MAX], visited[MAX];
vector<int> edge[MAX];
/*
S에서 T로 가는 증가 경로 구하기(에드몬드 카프)
S : 시작점, T : 도착점
c[a][b] : a에서 b로 흐를 수 있는 최대 양 (Capacity)
f[a][b] : a에서 b로 흐른 실제 양 (Flow)
조건
용량 제한 : f[a][b] <= c[a][b]
유량의 대칭성 : f[a][b] == -f[b][a]
나오는 유량의 합 == 들어오는 유량의 합
*/
int maxFlow(int S, int T);
int bfs(int S, int T);
int maxFlow(int S, int T) {
    int result = 0;
    while (1) {
        int flow = bfs(S, T);
        if (!flow) break;
        result += flow;
    }
    return result;
}
int bfs(int S, int T) {
    memset(visited, -1, sizeof(visited));

```

```

queue<int> q;
q.push(S);
while (!q.empty()) {
    int cur = q.front();
    q.pop();
    for (int next : edge[cur]) { //방문했는지, 용량이 남아 있는지 체크
        if (c[cur][next] - f[cur][next] <= 0) continue;
        if (visited[next] != -1) continue;
        q.push(next);
        visited[next] = cur; //cur->next 경로 기억
        if (next == T) break; //도착했을 경우 종료
    }
}
if (visited[T] == -1) return 0;
int flow = INF;
for (int i = T; i != S; i = visited[i]) { //최소 유량 탐색
    flow = min(flow, c[visited[i]][i] - f[visited[i]][i]);
}
for (int i = T; i != S; i = visited[i]) { //최소 유량 추가
    f[visited[i]][i] += flow;
    f[i][visited[i]] -= flow;
}
return flow;
}
int main() {
    int N; cin >> N;
    for (int i = 0; i < N; i++) {
        int in1, in2, in3;
        cin >> in1 >> in2 >> in3;
        c[in1][in2] += in3;
        c[in2][in1] += in3;
        edge[in1].push_back(in2);
        edge[in2].push_back(in1);
    }
    int S, T; cin >> S >> T;
    cout << maxFlow(S, T);
}

```

7. Bipartite Matching

```

vector<int> v[MAXN];

```

```

int nbook[MAXN];
bool vish[MAXN];
int human[MAXN];
int n, m;
int a, b;
bool dfs(int h) {
    vish[h] = true;
    for (int a : v[h]) {
        if (nbook[a] == 0 || !vish[nbook[a]] && dfs(nbook[a])) {
            nbook[a] = h;
            human[h] = a;
            return true;
        }
    }
    return false;
}
int main() {
    ios::sync_with_stdio();
    cin.tie(0); cout.tie(0);
    cin >> n >> m;
    for (int i = 1; i <= m; i++) {
        cin >> a >> b;
        v[a].push_back(b);
    }
    int ans = 0;
    for (int i = 1; i <= n; i++) {
        if (human[i] == 0) {
            fill(vish, vish + 1 + n, false);
            ans += dfs(i);
        }
    }
    cout << ans;
}

```

8. Lowest Common Ancestor

```

int t, n, p1, p2, root;
int p[20][10001], depth[10001], visit[10001], ind[10001];
vector<vector<int>> v;
void dfs(int cur) {
    visit[cur] = true;

```

```

    for (auto i : v[cur]) {
        if (!visit[i]) {
            depth[i] = depth[cur] + 1;
            p[0][i] = cur;
            dfs(i);
        }
    }
}
int lca(int x, int y) {
    if (depth[x] > depth[y]) swap(x, y);
    for (int i = 19; i >= 0; i--) {
        int dif = depth[y] - depth[x];
        if (dif >= (1 << i)) y = p[i][y];
    }
    if (x == y) return x;
    for (int i = 19; i >= 0; i--) {
        if (p[i][x] != p[i][y]) {
            x = p[i][x];
            y = p[i][y];
        }
    }
    return p[0][x];
}
int main() {
    cin >> n;
    v.resize(n + 1);
    for (int i = 0; i < n - 1; i++) {
        cin >> p1 >> p2;
        v[p1].push_back(p2);
        ind[p2]++;
    }
    for (int i = 1; i <= n; i++) {
        if (!ind[i]) {
            root = i;
            break;
        }
    }
    dfs(root);
    for (int i = 1; i < 20; i++)
        for (int j = 1; j <= n; j++)

```

```

        p[i][j] = p[i - 1][p[i - 1][j]];
    cin >> p1 >> p2;
    cout << lca(p1, p2) << '\n';

```

2. Data Structure

1. Segment Tree

```

struct SegTree {
    ll sz, st, dep;
    vector<ll> pw2, v;
    SegTree(ll size) {
        ll k = 1;
        for (int i = 0; i < 30; i++) pw2.push_back(k, k <= 1;
        sz = size; v.resize(sz * 4, 0); dep = 1;
        while(1) {
            if (sz <= pw2[dep - 1]) break;
            dep++;
        }
        st = pw2[dep - 1] - 1;
    }
    void init(ll val) {
        for (int i = 1; i < 4 * sz; i++) v[i] = val;
    }
    ll val(ll ind) {
        return v[st + ind];
    }
    void update(ll ind, ll val) {
        v[st + ind] = val; ind = (ind + 1) / 2;
        for (int i = dep - 1; i >= 1; i--) {
            ll cur = pw2[i - 1] - 1 + ind;
            v[cur] = v[cur * 2] + v[cur * 2 + 1];
            ind = (ind + 1) / 2;
        }
    }
    ll query(ll start, ll end) {
        ll ret = 0;
        start += st; end += st;
        while (start <= end) {
            if (start % 2 == 1) ret += v[start];

```

```

            if (end % 2 == 0) ret += v[end];
            start = (start + 1) / 2;
            end = (end - 1) / 2;
        }
        return ret;
    }
};

```

2. Fenwick Tree with Lazy Propagation

```

struct lazy {
    struct fenwick {
        ll sz;
        ll *arr;
        fenwick(int size) {
            sz = size + 1;
            arr = new ll[sz];
            fill(arr, arr + sz, 0);
        }
        void update(int i, ll x) {
            while (i <= sz) {
                arr[i] += x;
                i += i & -i;
            }
        }
        ll sum(int i) const {
            ll x = 0;
            while (i) {
                x += arr[i];
                i -= i & -i;
            }
            return x;
        }
    };
};

fenwick *suma, *sumb;
lazy(int size) {
    suma = new fenwick(size);
    sumb = new fenwick(size);
}

void add(int L, int R, ll val) {
    suma->update(L, val);

```

```

suma->update(R + 1, -val);
sumb->update(L, (1LL - L)*val);
sumb->update(R + 1, 1LL * R*val);
}
ll query(int L, int R) {
    ll ans = 0;
    ans += suma->sum(R)*R + sumb->sum(R);
    ans -= suma->sum(L - 1)*(L - 1) + sumb->sum(L - 1);
    return ans;
}
};

```

3. Segment Tree with Lazy Propagation

```

void propagate(ll lo, ll hi, ll node) {
    if (!lazy[node])return;
    else {
        if (lo != hi) {
            lazy[node * 2] += lazy[node];
            lazy[node * 2 + 1] += lazy[node];
        }
    }
    seg[node] += lazy[node] * (hi - lo + 1);
    lazy[node] = 0;
}

ll update(ll lo, ll hi, ll val, ll node, ll x, ll y) {
    propagate(x, y, node);
    if (hi < x || y < lo)return seg[node];
    if (lo <= x && y <= hi) {
        lazy[node] += val;
        propagate(x, y, node);
        return seg[node];
    }
    ll mid = (x + y) >> 1;
    return seg[node] = update(lo, hi, val, node * 2, x, mid) + update(lo, hi, val, node * 2 + 1,
mid + 1, y);
}

ll query(ll lo, ll hi, ll node, ll x, ll y) {
    propagate(x, y, node);
    if (hi < x || y < lo)return 0;
    if (lo <= x && y <= hi)return seg[node];
}

```

```

ll mid = (x + y) >> 1;
return query(lo, hi, node * 2, x, mid) + query(lo, hi, node * 2 + 1, mid + 1, y);
}

```

4. Merge Sort Tree

```

struct MergeSortTree {
    ll sz, st, dep;
    vector<vector<ll>> v; vector<ll> pw2;
    MergeSortTree(ll size) {
        ll k = 1;
        for (int i = 0; i < 30; i++)pw2.push_back(k), k <=<= 1;
        sz = size; v.resize(sz * 4); dep = 1;
        while (1) {
            if (sz <= pw2[dep - 1])break;
            dep++;
        }
        st = pw2[dep - 1] - 1;
    }
    void make(vector<ll> in) {
        for (int i = 0; i < sz; i++) {
            v[st + i].push_back(in[i]);
        }
        int ind = st, cnt = sz;
        while (ind > 0) {
            ind = (ind + 1) / 2; cnt = (cnt + 1) / 2;
            for (int i = 0; i < cnt; i++) {
                v[ind + i].resize(v[(ind + i) * 2].size() + v[(ind + i) * 2 + 1].size());
                merge(v[(ind + i) * 2].begin(), v[(ind + i) * 2].end(),
                    v[(ind + i) * 2 + 1].begin(), v[(ind + i) * 2 + 1].end(),
                    v[ind + i].begin()
                );
            }
            if (ind == 1)break;
        }
    }
    ll query(ll start, ll end, ll val) {
        ll ret = 0;
        start += st; end += st;
        while (start <= end) {
            if (start % 2 == 1) {

```



```

        auto k = upper_bound(v[start].begin(), v[start].end(), val) - v[start].begin();
        ret += v[start].size() - k;
    }
    if (end % 2 == 0) {
        auto k = upper_bound(v[end].begin(), v[end].end(), val) - v[end].begin();
        ret += v[end].size() - k;
    }
    start = (start + 1) / 2;
    end = (end - 1) / 2;
}
return ret;
}
};

```

5. Segment Tree(OpeningSound)

```

ll mseg(int left, int right, int node) {
    if (left == right) {
        return seg[node] = arr[left];
    }
    int mid = (left + right) / 2;
    return seg[node] = (mseg(left, mid, node * 2) % MOD) * (mseg(mid + 1, right, node * 2 + 1) % MOD);
}

ll update(int left, int right, int node, int change, int diff) {
    if (!(left <= change && right >= change))
        return seg[node];
    if (left == right)
        return seg[node] = arr[left];
    int mid = (left + right) / 2;
    return seg[node] = (update(left, mid, node * 2, change, diff) % MOD) * (update(mid + 1, right, node * 2 + 1, change, diff) % MOD) % MOD;
}

ll gop(int left, int right, int node, int first, int end) {
    if (first <= left && right <= end)
        return seg[node];
    if (first > right || left > end)
        return 1;
    int mid = (left + right) / 2;
    return (gop(left, mid, node * 2, first, end) % MOD) * (gop(mid+1, right, node * 2+1, first, end) % MOD) % MOD;
}

```

```

    }
}

int main() {
    ios::sync_with_stdio(0);
    cin.tie(0), cout.tie(0);
    cin >> N >> M >> K;
    for (int i = 1; i <= N; i++) {
        cin >> arr[i];
    }
    mseg(1, N, 1);
    for (int i = 1; i <= M+K; i++) {
        int a, b, c;
        cin >> a >> b >> c;
        if (a == 1) {
            arr[b] = c;
            update(1, N, 1, b, c);
        }
        else {
            cout << gop(1, N, 1, b, c) << '\n';
        }
    }
}

```

5. Segment Tree with Lazy Propagation(OpeningSound)

```

void lazyche(int leng, int node) {
    if (lazy[node]) {
        seg[node] += leng * lazy[node];
        if (leng != 1) {
            lazy[node * 2] += lazy[node];
            lazy[node * 2+1] += lazy[node];
        }
        lazy[node] = 0;
    }
}

ll mseg(int left, int right, int node) {
    if (left == right)
        return seg[node] = arr[left];
    int mid = (left + right) / 2;
    return seg[node] = mseg(left, mid, node * 2) + mseg(mid + 1, right, node * 2 + 1);
}

```

```

}

void update(int left, int right, int node, int start, int end, int diff) {
    int leng = right - left + 1;
    lazyche(leng, node);
    if (start <= left && right <= end){
        seg[node] += leng * diff;
        if (leng != 1) {
            lazy[node * 2] += diff;
            lazy[node * 2 + 1] += diff;
        }
        return;
    }
    if (start > right || end < left)
        return;
    int mid = (left + right) / 2;
    update(left, mid, node * 2, start, end, diff);
    update(mid+1, right, node * 2+1, start, end, diff);
    seg[node] = seg[node * 2] + seg[node * 2 + 1];
}

ll sseg(int left, int right, int node, int start, int end) {
    int leng = right - left + 1;
    lazyche(leng, node);
    if (start <= left && right <= end)
        return seg[node];
    if (start > right || end < left)
        return 0;
    int mid = (left + right) / 2;
    return sseg(left, mid, node * 2, start, end) + sseg(mid + 1, right, node * 2+1, start, end);
}

int main() {
    ios::sync_with_stdio(0);
    cin.tie(0); cout.tie(0);
    cin >> N >> Q1 >> Q2;
    for (int i = 1; i <= N; i++)
        cin >> arr[i];
    mseg(1, N, 1);
    int Q12 = Q1 + Q2;
    for (int i = 1; i <= Q12; i++) {

```

```

        int a, b, c, d;
        cin >> a;
        if (a == 1) {
            cin >> b >> c;
            cout << sseg(1, N, 1, b, c) << '\n';
        }
        else {
            cin >> b >> c >> d;
            update(1, N, 1, b, c, d);
        }
    }
}

```

3. String

1. KMP

```

string src, tar;
vector<int> fail, KMP;
void getFail(string t) {
    fail.resize(t.length());
    int j = 0;
    for (int i = 1; i < t.length(); ++i) {
        while (j > 0 && t[i] != t[j]) j = fail[j - 1];
        if (t[i] == t[j]) fail[i] = ++j;
    }
}

void getKMP(string s, string t) {
    int sLen = s.length(), tLen = t.length(), j = 0;
    for (int i = 0; i < sLen; ++i) {
        while (j > 0 && s[i] != t[j]) j = fail[j - 1];
        if (s[i] == t[j]) {
            if (j == tLen - 1) {
                KMP.push_back(i - tLen + 1 + 1);
                j = fail[j];
            }
            else j++;
        }
    }
}

```

```

int main() {
    getline(cin, src); getline(cin, tar);
    getFail(tar);
    getKMP(src, tar);
    cout << KMP.size() << "\n";
    for (int i : KMP) {
        cout << i << " ";
    }
}

```

2. Rabin-Karp

```

const int MOD = 1000000007;
ll mod(ll n) { if (n >= 0) return n % MOD; return ((-n / MOD + 1) * MOD + n) % MOD; }
int L;
string src;
int rabinKarp(int len) {
    ll H = 0, power = 1;
    unordered_map<int, vector<int>> hashTable;
    for (int i = 0; i <= src.length() - len; ++i) {
        if (i == 0) {
            for (int j = 0; j < len; ++j) {
                H = mod(H + 1LL * src[j] * power);
                if (j < len - 1) power = mod(power * 127);
            }
        }
        else {
            H = mod(127 * (H - 1LL * src[i - 1] * power) + src[i + len - 1]);
        }
        if (hashTable[H].size() == 0) hashTable[H].push_back(i);
        else {
            for (int pos : hashTable[H]) {
                for (int p = 0; p < len; ++p) {
                    if (src[pos + p] != src[i + p]) break;
                    if (p == len - 1) return true;
                }
            }
            hashTable[H].push_back(i);
        }
    }
    return false;
}

```

```

}
3. Trie
struct Trie;
typedef pair<char, Trie*> pct;
struct Trie {
    vector<pct> child;
    bool isRet;
    Trie() {
        isRet = false;
    }
    ~Trie() {
        for (pct c : child) delete c.second;
    }
    void insert(const char* key) {
        int k = *key;
        if (k == '\0') {
            isRet = true;
            return;
        }
        for (pct c : child) {
            if (c.first == k) {
                c.second->insert(key + 1);
                return;
            }
        }
        child.push_back(pct(*key, new Trie));
        child.back().second->insert(key + 1);
    }
    bool demoFunc(const char* key) {
        int k = *key;
        if (isRet && k == '\0') return true;
        for (pct c : child) {
            if (c.first == k) return c.second->demoFunc(key + 1);
        }
        return false;
    }
};
int main() {
    Trie* root = new Trie;
}

```

```

int n; cin >> n;
for (int i = 0; i < n; ++i) {
    string input; cin >> input;
    root->insert(input.c_str());
}
int m; cin >> m;
for (int i = 0; i < m; ++i) {
    string input; cin >> input;
    cout << (root->demoFunc(input.c_str()) ? "YES" : "NO") << "\n";
}
delete root;
}

```

4. Aho-Corasick

```

struct Trie {
    unordered_map<char, Trie*> child;
    Trie* fail;
    bool isRet = false;
    void push(string& s) {
        Trie* cur = this;
        for (char const& c : s) {
            if (cur->child.find(c) == cur->child.end())
                cur->child[c] = new Trie;
            cur = cur->child[c];
            cur->fail = this;
        }
        cur->isRet = true;
    }
    void build() {
        queue<Trie*> Q;
        for (auto const& p : child)
            if (p.second) Q.push(p.second);
        while (!Q.empty()) {
            Trie* cur = Q.front(); Q.pop();
            for (auto const& c : cur->child) {
                Trie* p = cur->fail;
                while (p != this && p->child.find(c.first) == p->child.end()) p = p->fail;
                p = p->child[c.first];
                if (!p) p = this;
                c.second->fail = p;
            }
        }
    }
}

```

```

        if (p->isRet) c.second->isRet = true;
        Q.push(c.second);
    }
}
bool ask(string& s) {
    Trie* p = this;
    for (char& c : s) {
        while (p != this && p->child.find(c) == p->child.end()) p = p->fail;
        p = p->child[c];
        if (!p) p = this;
        if (p->isRet) return 1;
    }
    return 0;
}
};
int main() {
    Trie* root = new Trie;
    int N, Q;
    string input;
    cin >> N; while (N--) {
        cin >> input; root->push(input);
    }
    root->build();
    cin >> Q; while (Q--) {
        cin >> input; cout << (root->ask(input) ? "YES" : "NO") << "\n";
    }
}

```

5. Suffix Array and Longest Common Prefix Array

```

const char baseChar = '`'; // @ for uppercase ` for lowercase
const int baseSize = 27; // 27 : 59
vector<int> suffixArray, LCPArray;
void getLCP(vector<int>& sa, vector<int>& lcpa, string& s) {
    int i, j, k, u = 0, m = baseSize, sLen = s.length();
    sa.resize(sLen, 0); lcpa.resize(sLen, 0);
    vector<int> cnt(max(sLen, m), 0), x(sLen, 0), y(sLen, 0);
    for (i = 0; i < sLen; ++i) cnt[x[i] - baseChar]++;
    for (i = 0; i < m; ++i) cnt[i] += (i == 0 ? 0 : cnt[i - 1]);
    for (i = sLen - 1; i >= 0; --i) sa[--cnt[x[i]]] = i;
}

```

```

for (int len = 1, p = 1; p < sLen; len <= 1, m = p + 1) {
    for (i = sLen - len - 1, p = 0; ++i < sLen;) y[p++] = i;
    for (i = 0; i < sLen; ++i) if (sa[i] >= len) y[p++] = sa[i] - len;
    for (i = 0; i < m; ++i) cnt[i] = 0;
    for (i = 0; i < sLen; ++i) cnt[x[y[i]]]++;
    for (i = 0; i < m; ++i) cnt[i] += (i == 0 ? 0 : cnt[i - 1]);
    for (i = sLen - 1; i >= 0; --i) sa[--cnt[x[y[i]]]] = y[i];
    swap(x, y); p = 1; x[sa[0]] = 1;
    for (i = 0; i < sLen - 1; ++i) x[sa[i + 1]] = sa[i] + len < sLen && sa[i + 1] + len < sLen &&
y[sa[i]] == y[sa[i + 1]] && y[sa[i] + len] == y[sa[i + 1] + len] ? p : ++p;
}
vector<int> rank(sLen, 0);
for (i = 0; i < sLen; i++) rank[sa[i]] = i;
for (i = 0; i < sLen; ++i) if (k = rank[i]) {
    j = sa[k - 1];
    while (i + u < sLen && j + u < sLen && s[i + u] == s[j + u]) u++;
    lcpa[k] = u;
    u = u ? u - 1 : 0;
}
}
int main() {
    string s; cin >> s;
    getLCP(suffixArray, LCPArray, s);
    cout << "SA: "; for (int i = 0; i < s.length(); ++i) cout << suffixArray[i] << " "; cout << "\n";
    cout << "LA: "; for (int i = 0; i < s.length(); ++i) cout << LCPArray[i] << " "; cout << "\n";
}

```

6. Manacher

```

vector<int> manacher(string& src) {
    int srcLen = src.size(); src.resize(srcLen * 2 + 1, '#');
    for (int i = srcLen - 1; i >= 0; --i) src[i * 2 + 1] = src[i], src[i] = '#';
    int c = 0, r = 0, len = src.size();
    vector<int> ret(len, 0);
    for (int i = 0; i < len; ++i) {
        int sym = 2 * c - i;
        if (i < r) ret[i] = min(r - i, ret[sym]);
        while (i - ret[i] > 0 && i + ret[i] - 1 < len && src[i - ret[i] - 1] == src[i + ret[i] + 1])
ret[i]++;
        if (ret[i] + i > r) r = ret[i] + i, c = i;
    }
}

```

```

return ret;
}
int main() {
    string src; cin >> src;
    vector<int> pal = manacher(src);
    for (int i : pal) cout << i << ' ';
}
7. Z
vector<int> Z;
void getZ(string& src) {
    int l = 0, r = 0, len = src.length();
    Z.resize(len);
    for (int i = 1; i < len; i++) {
        Z[i] = max(0, min(Z[i - 1], r - i));
        while (src[i + Z[i]] && src[Z[i]] == src[i + Z[i]]) Z[i]++;
        if (i + Z[i] > r) l = i, r = i + Z[i];
    }
    Z[0] = len; // Z[0] = 0;
}

```

```

int main() {
    string src; cin >> src;
    getZ(src);
    for (auto i : Z) cout << i << " ";
}

```

4. Math

1. Greatest Common Divisor, Least Common Multiple

```

ll gcd(ll a, ll b) { for (; b; a %= b, swap(a, b)); return a; }
ll lcm(ll a, ll b) { return a * b / gcd(a, b); }

```

2. Sieve of Eratosthenes

```

const ll MAX = 100001;
bool isprime[MAX];
void sieve(){
    fill(isprime, isprime + MAX, 1);
    isprime[1] = 0;
    for (int i = 2; i*i <= MAX; i++) {
        if (isprime[i]) {
            for (int j = i*i; j < MAX; j += i) {

```

```

        isprime[j] = 0;
    }
}
}

```

3. Binomial Coefficient

```

const ll MOD = 1000000007;
const ll MAX_NUM = 4000001;
ll f[MAX_NUM];
ll mypow(ll base, ll exp, ll MOD) {
    ll ans = 1;
    while (exp > 0) {
        if (exp % 2 != 0) {
            ans *= base;
            ans %= MOD;
        }
        base *= base;
        base %= MOD;
        exp /= 2;
    }
    return ans;
}
void nCrInit() {
    f[0] = 1; f[1] = 1;
    for (int i = 2; i <= MAX_NUM - 1; i++) {
        f[i] = f[i - 1] * i;
        f[i] %= MOD;
    }
}
ll nCr(int n, int r) {
    return (f[n] * mypow((f[r] * f[n - r]) % MOD, MOD - 2, MOD)) % MOD;
}
int main() {
    ll n, r;
    nCrInit();
    cin >> n >> r;
    cout << nCr(n, r) << "\n";
}

```

4. Matrix Exponential

```

ll a[3][3], a2[3][3], ans[3][3], temp[3][3], N;
void mult(ll a[3][3], ll b[3][3]) {
    for (int i = 0; i < 3; i++) {
        for (int j = 0; j < 3; j++) {
            for (int k = 0; k < 3; k++) {
                temp[i][j] += a[i][k] * b[k][j];
                temp[i][j] %= 1000000007;
            }
        }
    }
    for (int i = 0; i < 3; i++) {
        for (int j = 0; j < 3; j++) {
            a[i][j] = temp[i][j];
            temp[i][j] = 0;
        }
    }
}
int main() {
    cin >> N; N--;
    /*
    행렬 설명
    a : 가운데 거듭제곱되는 행렬
        초기화는 점화식으로 유도된 행렬로 한다.
    a2 : 거듭제곱된 결과가 저장되는 행렬
        초기화는 영행렬로 한다.
    temp : mult함수에서 사용되는 임시 행렬
    ans : 답이 저장되어 있는 행렬.
        초기화를 할 때는 ans[0][i]의 폴로 베이스 값을 저장해놓는다.
    mult(ans, a2)를 하면 ans[0][i]에 원하는 값이 들어간다.
    */
    for (int i = 0; i < 3; i++) {
        for (int j = 0; j < 3; j++) {
            a[i][j] = 1;
            if (i == j) a2[i][i] = 1;
        }
    }
    a[0][0] = a[1][1] = 0;
    ans[0][0] = ans[0][1] = ans[0][2] = 1;
    while (N > 0) {
        if (N % 2 == 1) {

```

```

    mult(a2, a);
}
mult(a, a);
N /= 2;
}
mult(ans, a2);
cout << (ans[0][0] + ans[0][1] + ans[0][2]) % 1000000007;
}

```

5. Fast Fourier Transform

```

using ld = double;
using base = complex<ld>;
const ld pi = acos(-1);
void fft(vector<base> &A, bool f) {
    int k = A.size(), i, j, l, t;
    base w, x, y; ld th;
    for (i = 1, j = 0; i < k; i++) {
        for (l = k >> 1; j >= l; l >>= 1) j -= l;
        j += l; if (i < j) swap(A[i], A[j]);
    }
    for (i = 1; i < k; i <= 1, t--) {
        th = (f ? -pi : pi) / i;
        w = base(cos(th), sin(th));
        for (j = 0; j < k; j += i + i) {
            for (l = 0; l < i; l++) {
                if (l & 2047) x *= w;
                else x = l ? base(cos(th * l), sin(th * l)) : 1;
                y = x * A[l | i | j];
                A[l | i | j] = A[l | j] - y;
                A[l | j] += y;
            }
        }
    }
    if (f) for (i = 0; i < k; i++) {
        A[i] /= k;
    }
}
vector<ll> mult(vector<ll> &X, vector<ll> &Y) { //return vector's size is |X| + |Y| - 1
    ll s, i, j;
    for (s = 1; s < X.size() + Y.size(); s <= 1);
}

```

```

vector<base> P(s), Q(s);
vector<ll> Z(X.size() + Y.size() - 1);
for (i = 0; i < X.size(); i++)
    P[i] = base(X[i] >> 12, X[i] & 4095);
for (i = 0; i < Y.size(); i++)
    Q[i] = base(Y[i] >> 12, Y[i] & 4095);
fft(P, 0); fft(Q, 0);
for (i = 0; i + i <= s; i++) {
    j = i ? s - i : 0;
    base v1 = P[i] + conj(P[j]), v2 = conj(P[i]) - P[j];
    tie(P[i], Q[i], P[j], Q[j]) = make_tuple(
        v1 * Q[i], conj(v2) * conj(Q[j]),
        conj(v1) * Q[j], -v2 * conj(Q[i]));
}
fft(P, 1); fft(Q, 1);
for (i = 0; i < Z.size(); i++) {
    Z[i] = (((ll)round(P[i].real()) << 23) + ((ll)round(Q[i].real()) >> 1)
        + ((ll)round(P[i].imag() + Q[i].imag()) << 11));
}
return Z;
}

```

6. Berlekamp-Massey

```

ll ipow(ll x, ll p) {
    ll ret = 1, piv = x;
    while(p){
        if(p & 1) ret = ret * piv % MOD;
        piv = piv * piv % MOD;
        p >>= 1;
    }
    return ret;
}
vector<ll> berlekamp_massey(vector<ll> x) {
    vector<ll> ls, cur;
    ll lf, ld;
    for(int i = 0; i < x.size(); i++) {
        ll t = 0;
        for(int j = 0; j < cur.size(); j++) {
            t = (t + 1ll * x[i - j - 1] * cur[j]) % MOD;
        }
    }
}

```

```

if((t - x[i]) % MOD == 0) continue;
if(cur.empty()) {
    cur.resize(i + 1);
    lf = i;
    ld = (t - x[i]) % MOD;
    continue;
}
ll k = -(x[i] - t) * ipow(ld, MOD - 2) % MOD;
vector<ll> c(i - lf - 1);
c.push_back(k);
for(auto &j : ls) c.push_back(-j * k % MOD);
if(c.size() < cur.size()) c.resize(cur.size());
for(int j = 0; j < cur.size(); j++) {
    c[j] = (c[j] + cur[j]) % MOD;
}
if(i - lf + (ll)ls.size() >= (ll)cur.size()) {
    tie(ls, lf, ld) = make_tuple(cur, i, (t - x[i]) % MOD);
}
cur = c;
}
for(auto &i : cur) i = (i % MOD + MOD) % MOD;
return cur;
}
ll get_nth(vector<ll> rec, vector<ll> dp, ll n) {
    ll m = rec.size();
    vector<ll> s(m), t(m);
    s[0] = 1;
    if(m != 1) t[1] = 1;
    else t[0] = rec[0];
    auto mul = [&rec](vector<ll> v, vector<ll> w) {
        int m = v.size();
        vector<ll> t(2 * m);
        for(int j = 0; j < m; j++) {
            for(int k = 0; k < m; k++) {
                t[j + k] += 1ll * v[j] * w[k] % MOD;
                if(t[j + k] >= MOD) t[j + k] -= MOD;
            }
        }
    };
    for(int j = 2 * m - 1; j >= m; j--) {
        for(int k = 1; k <= m; k++) {

```

```

            t[j - k] += 1ll * t[j] * rec[k - 1] % MOD;
            if(t[j - k] >= MOD) t[j - k] -= MOD;
        }
    }
    t.resize(m);
    return t;
};
while(n) {
    if(n & 1) s = mul(s, t);
    t = mul(t, t);
    n >>= 1;
}
ll ret = 0;
for(int i = 0; i < m; i++) ret += 1ll * s[i] * dp[i] % MOD;
return ret % MOD;
}
ll guess_nth_term(vector<ll> x, ll n){
    if(n < x.size()) return x[n];
    vector<ll> v = berlekamp_massey(x);
    if(v.empty()) return 0;
    return get_nth(v, x, n);
}

```

7. Extended Euclidean Algorithm

```

tuple<ll, ll, ll> euclid(ll x, ll y) {
    if (x < y) swap(x, y);
    if (y == 0) return { x, 1, 0 };
    ll g, x1, y1; tie(g, x1, y1) = euclid(y, x%y);
    return { g, y1, x1 - (x / y) * y1 };
}
ll inv = (get<2>(euclid(base, MOD)) + MOD) % MOD;

```

5. Geometry

1. CCW

```

//determines direction of 3 points
ll ccw(const point& A, const point& B, const point& C) {
    ll t = 1LL * (B.x - A.x)*(C.y - A.y) - 1LL * (B.y - A.y)*(C.x - A.x);
    if (t > 0) return 1; //Counter-Clockwise
    if (t == 0) return 0; //Line

```



```
    return -1; //Clockwise
}
```

2. Convex Hull

```
const int MAX = 100000;
```

```
struct point {
    int x, y; //실제 위치
    int p, q; //기준점으로부터 상대 위치
    point() : point(0, 0, 1, 0) {}
    point(int x1, int y1) : point(x1, y1, 1, 0) {}
    point(int x1, int y1, int p1, int q1) : x(x1), y(y1), p(p1), q(q1) {}
    bool operator<(const point& O) {
        if (1LL * q*O.p != 1LL * p*O.q) return 1LL * q*O.p < 1LL * p*O.q;
        if (y != O.y) return y < O.y;
        return x < O.x;
    }
};
```

```
point p[MAX];
```

```
int main() {
    int N;
    cin >> N;
    for (int i = 0; i < N; i++) {
        int in1, in2;
        cin >> in1 >> in2;
        p[i] = point(in1, in2);
    }
    sort(p, p + N);
    for (int i = 1; i < N; i++) {
        p[i].p = p[i].x - p[0].x;
        p[i].q = p[i].y - p[0].y;
    }
    sort(p + 1, p + N); //반시계 방향 정렬
    stack<int> cvh;
    cvh.push(0); cvh.push(1);
    int next = 2;
    while (next < N) {
        while (cvh.size() >= 2) {
            int fst, scd;
            fst = cvh.top();
            cvh.pop();
```

```
            scd = cvh.top();
            if (ccw(p[scd], p[fst], p[next]) > 0) {
                cvh.push(fst);
                break;
            }
        }
        cvh.push(next++);
    }
    cout << cvh.size();
}
```

3. Line Intersection

```
struct point {
    int x, y;
    point(int x, int y) {
        this->x = x;
        this->y = y;
    }
    bool operator< (point a) {
        if (a.x != this->x) {
            return a.x < this->x;
        }
        else {
            return a.y < this->y;
        }
    }
    bool operator<= (point a) {
        if (a.x == this->x && a.y == this->y) return 1;
        if (a.x != this->x) {
            return a.x < this->x;
        }
        else {
            return a.y < this->y;
        }
    }
};

bool isIntersect(pair<point, point> line1, pair<point, point> line2) {
    point p1 = line1.first;
    point p2 = line1.second;
    point p3 = line2.first;
```

```

point p4 = line2.second;
int l1 = ccw(p1, p2, p3) * ccw(p1, p2, p4);
int l2 = ccw(p3, p4, p1) * ccw(p3, p4, p2);
if (l1 == 0 && l2 == 0) {
    if (p2 < p1) swap(p1, p2);
    if (p4 < p3) swap(p3, p4);
    return (p3 <= p2 && p1 <= p4);
}
return (l1 <= 0 && l2 <= 0);
}

```

6. Others

1. Decimal in python

```

import decimal; D = decimal.Decimal
# 정밀도 설정
decimal.getcontext().prec = 28000
# Decimal 객체에 인자 넘겨주기
g = D(1/(10**200))

```

2. Fraction in python

```

Import fractions; F = fractions.Fraction
F(f.numerator, f.denominator)

```

3. Bit Operations

```

k & (1 << N) // return N-th bit of k
k | (1 << N) // make N-th bit of k to 1
k & ~(1 << N) // make N-th bit of k to 0
k & ~k // return least index of bit which has value 1

```

4. Coordinate Compression

```

ll getind(ll in){
    return lower_bound(a.begin(), a.end(), in) - a.begin();
}

```

```

sort(a.begin(), a.end());
a.erase(unique(a.begin(), a.end()), a.end());

```

5. Knuth Optimization

Optimization of $O(N^3)$ DP to $O(N^2)$

Condition 0 : $dp[i][j]$ is defined under $1 \leq i \leq j \leq n$

Condition 1 : $dp[i][j] = \min(dp[i][k] + dp[k + 1][j]) + cost[i][j]$

Condition 2 : under $a \leq b \leq c \leq d$, $cost[a][c] + cost[b][d] \leq cost[a][d] + cost[b][c]$

Condition 3 : under $a \leq b \leq c \leq d$, $cost[b][c] \leq cost[a][d]$

Original $O(N^3)$ DP :

```

for(i = 1; i <= n; i++){
    for(j = i; j < n; j++){
        for(k = j + 1; k < i; k++){
            dp[i][j] = min(dp[i][j] , dp[i][k] + dp[k + 1][j]);
        }
        dp[i][j] += C[i][j];
    }
}

```

Optimized $O(N^2)$ DP :

```

for(i=1; i<=n; i++){
    for(j=i; j<n; j++){
        dp[i][j] = MAX;
        for(k=A[i][j - 1]; k<=A[i + 1][j]; k++){ //상수 번 반복
            if(dp[i][j] > dp[i][k] + dp[k + 1][j]){
                dp[i][j] = dp[i][k] + dp[k + 1][j];
                A[i][j] = k;
            }
        }
        dp[i][j] += C[i][j];
    } //A[i][j] = minimum k to minimize dp[i][j]
} //A[i][j - 1] <= A[i][j] <= A[i + 1][j]

```

6. Some Prime Numbers

127, 131, 137, 139, 10007, 100003, 998244353, 1000000007, 10000000009

7. Longest Increasing Subsequence

```

typedef pair<int, int> p;
vector<int> lis(const vector<int> &v) {
    if (v.empty())return{};
    vector<int> prev(v.size());
    vector<p> res;
    for (int i = 0; i < v.size(); i++) {
        auto it = lower_bound(res.begin(), res.end(), p{ v[i],0 });
        if (it == res.end())res.emplace_back(), it = res.end() - 1;
        *it = { v[i],i };
        prev[i] = it == res.begin() ? 0 : (it - 1)->second;
    }
    int L = res.size(), cur = res.back().second;
    vector<int> ans(L);
}

```

```

while (L--)&ans[L] = cur, cur = prev[cur];
return ans;
}

```

8. Rope

```

#include <ext/rope>
using namespace __gnu_cxx;
rope<char> rp;
rp.append(str.c_str());
rp.substr(pos, len).c_str()
rp.insert(pos, str);
rp.erase(pos, len);

```

9. PBDS Set

```

#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;
tree<int,null_type,less<int>,rb_tree_tag,tree_order_statistics_node_update> s;
s.order_of_key(k) : number of items in a set that are strictly smaller than k
s.find_by_order(k) : k-th element in a set (counting from zero)

```

10. Divide and Conquer Optimization

Condition 1 : $d[t][i] = \min_{k < i} (d[t-1][k] + c[k][i])$


Condition 2 : $a[t][j] = d[t][i]$ 를 만족시키는 최소 k 라고 할 때 $a[t][i] \leq a[t][i+1]$

```


function<void(ll, ll, ll, ll)> dnc = [&](ll s, ll e, ll l, ll r) -> void {
    if (s > e) return;
    ll m = (s + e) / 2;
    ll k = max(l, m - D);
    for (int i = k; i <= min(m, r); i++) {
        if ((m - k) * T[m] + V[k] < (m - i) * T[m] + V[i]) k = i;
    }
    ans = max(ans, (m - k) * T[m] + V[k]);
    dnc(s, m - 1, l, k);
    dnc(m + 1, e, k, r);
};

```

7. Tips



1. Minimum Cut of vertices is same as Maximum Flow of Vertices.



2. Minimum Vertex Cover is same as Maximum Matching.

3. Maximum Independent Set is Number of Vertices - Minimum Vertex Cover.

4. If node C is between node A and node B in a tree,

$\{LCA(A, C) == C \ \&\& \ LCA(A, B) == LCA(C, B)\} \ || \ \{LCA(B, C) == C \ \&\& \ LCA(A, B) == LCA(C, A)\}$ is true.

5. Derangement : $dp[i] = (i - 1) * (dp[i - 1] + dp[i - 2])$;

6. Erasing particular value in a vector

```

void erase(vector<int> &v, int val){
    for(auto it = v.begin(); it != v.end(); ){
        if(*it == val) it = v.erase(it);
        else it++;
    }
}

```

7. Partition of Number

Let $dp[n][k]$ be the number of cases dividing n to k numbers.

a. $dp[n][1] = dp[n][n] = 1$

b. $dp[n][k] = dp[n - k][1] + dp[n - k][2] + \dots + dp[n - k][k]$

c. $dp[n][k] = dp[n - 1][k - 1] + dp[n - k][k]$

8. Fermat's Little Theorem

If p is a prime number and a is not divisible by p , $a^{(p-1)} \% p == 1$ is true.

9. Binary Search

```
while (l <= r) {  
    int mid = (l + r) / 2;  
    if (!check(mid))  
        r = mid - 1;  
    else  
        l = mid + 1;  
}
```