



Technical Data Sheet

BAYFERROX® 340

Description

Туре	Black pigment
Delivery form	Powder
Chemical class Colour Index CAS-No. REACH registration no.	Synthetic iron oxide Fe₃O₄ Pigment black 11 (77499) 1317-61-9 01-2119457646-28

Specified Color Data

Colour values and tinting strength				
Standard	Bayferrox	340		
Year	2021			
Binder: Test paste based on a non drying alkyd resin	Reduction with titanion	um dioxide (1:5)	Test method No. 001 41	
∆ a*	-0.7	0.7		
∆ b*	-0.9	0.9		
ΔE* _{ab}		1.0		
Binder: Barytes Relative tinting strength [%]	95	105	Test method No. 003 41	

Specified Technical Data

Technical Data	min	max	Test method
Water-soluble content [%]		1.75	similar to DIN EN ISO 787-3:2000
Sieve residue (0.045 mm sieve) [%]		0.1	DIN EN ISO 787-7:2009
pH value	4	8	DIN EN ISO 787-9:1995





BAYFERROX® 340

Informative Technical Data (guide values)

Fe ₃ O ₄ content [%] ⁵³	>		95.8	Test method Information about the determination of iron oxide 41
Loss on ignition at 1000 °C, 0.5 h [%] ⁵	<		5.0	DIN 55913-2:1972
Moisture content (after production) [%]	<		4.0	DIN EN ISO 787-2:2021
Particle shape			spherical	Electron micrographs
Predominant particle size [µm]	~		0.15	Electron micrographs
Oil absorption [g/100 g]	~		18	DIN EN ISO 787-5:1995
Tamped density [g/ml]		8.0	- 1.2	similar to DIN EN ISO 787-11:1995
Density [g/ml]	~		4.6	DIN EN ISO 787-10:1995

⁵ In iron oxide black pigments, a chemical transformation (oxidation) is also recorded when determing the loss on ignition.

⁴¹ Please use our contact form on the Internet at www.bayferrox.com for more information.

 $^{^{\}scriptscriptstyle 45}$ Colour values after matching of the tinting strength parameter Y, i.e. Δ L*=0

⁵³ Minor elements may arise from the raw materials used. However, these are firmly bound to the crystal lattice as ions.



BAYFERROX® 340



Packaging

Our products are supplied in various types of packaging. To find out in which types of packaging this product is offered, please ask your local contact or use our contact form on the Internet at www.bayferrox.com

Transport and Storage

General storage conditions: Protect against weathering. Store in a dry place and avoid extreme

fluctuations in temperature.

Maximum storage temperature: During storage, temperatures above 80 ° C are to be avoided since

irreversible changes in the color of the pigment can occur.

Special conditions for opened

packaging:

Shelf life:

Close bags after use to prevent the absorption of moisture and

contamination.

This product has an excellent shelf life. We recommend that this product is used within ten years of the date of manufacture and limit our product warranty to this period. During the first ten years after the date of manufacture we are able to ensure compliance with this specification, provided the material has been stored as stated above and the packaging materials remain undamaged. It must be taken into account that the packaging mean can have a shelf life considerably shorter than the one for this product. All

recommendations and warnings given on the packaging must strictly be adhered to. Deviations from storage conditions can lead to undesired changes on side of the packaging materials. These succumb to ageing which may also lead to compromising their capability. Concerning their estimated service life we differentiate

between the following packaging materials:

With respect to our Bulk Bags we recommend to avoid UV-radiation because the sewing material of the lifting loops is stabilized against degradation by UV-radiation for appr. 1000 h incident sun radiation for the climate of Central Europe. A more intense sun radiation can shorten this period significantly. In cases of doubt the lifting loops

must be checked thoroughly.

Safety

Classification The product is not classified as dangerous under the relevant EC

Directives and corresponding national regulations valid in the individual EU member states. It is not dangerous according to

transport regulations.

In countries outside the EU, compliance with the respective national legislation concerning the classification, packaging, labelling and

transport of dangerous substances must be ensured.

Additional Information The safety data sheet should be observed. This contains

information on handling, product safety and ecology.

The safety data sheet is available at www.bayferrox.com.







Status of Registration

The components of this product are listed on the following inventories:

Europe: USA: Canada: Australia: New Zealand:

EINECS TSCA-active DSL AICS NZIOC

Philippines: Japan: Korea: China: Taiwan: PICCS ENCS + ISHL ECL IECSC TCSI