editi A0 on material 20010100869 code 4	The	3.2 rest
20 8 27.5		
8 5 19.5	technical requirement:  1 . To deburr, the sharp angle is too blunt;  2 . No note of the chamfer C0.2;  3 . Drawing for all hole position tolerance dimensions ± 0.1mm;  4 . Reference to 3D drawing for unannotated dimension;  5 . The surface to prevent scraping, bumping, crushing, deformation and c  6 . Surface treatment, sandblasting prototype oxidation, black;	other bad.
The linear tolerance is GB / T1804-m; the shape tolerance is GB / desi gn Enda  Linear basic ruler, pole  The linear tolerance is GB / T1804-m; the shape tolerance is GB / desi gn Enda  Value of the linear tolerance is GB / T1804-m; the shape tolerance is GB / desi gn Enda  Value of the linear tolerance is GB / T1804-m; the shape tolerance is GB / desi gn Enda	Jie Xinhua Technology erial	5061 5V05P

					of inch section, limit deviation value	±0.2	±0.3	±0.5	±0	±1.8.2	±2	e and verify ratif	,		St:	age	ua	weight	scale	figure	JXHSV05P-02026-a
		tab	Change the content	date	Straight degree peace The	≤10 0.05	> 10~30	30~100	> 100- 300~1 0.4	000	> 1000~3					arking	 tity		Scure	numbe r	JAN154051 02020 a
	tio n				surface degree is not noted Toleran ce value		0.1	0.2	0.4	0.0	00 0.8		1,	, the 1			1	0.0	2:1	nam e	Reinforcement block