technical requirement:  1. Use 100% new material for all materials, 2. All materials must be confirmed by samples before production; 3, the appearance surface frosted, grain reference sample; 4, the product can not be deformed, not allowed to have strain, shrinkage and air lines and other surface defects; 5, the surface of the parts is clean, free of oil, chips,	
The linear tolerance is GB / T1804-m; the shape tolerance is GB / Gesi gn Zepeng T1804-m; the shape tolerance is GB / Gesi gn Zepeng T1804-m; the shape tolerance is GB / Gesi gn Zepeng T1804-m; the shape tolerance is GB / Gesi gn Zepeng T1804-m; the shape tolerance is GB / Gesi gn Zepeng T1804-m; the shape tolerance is GB / T1804-m; the shape tolerance is GB / Gesi gn Zepeng T1804-m; the shape tolerance is GB / T1804-m; the shape tolerance is GB / Gesi gn Zepeng T1804-m; the shape tolerance is GB / T1804-m; the shape tolerance is GB / Gesi gn Zepeng T1804-m; the shape tolerance is GB / T1804-m; t	ck)

2-\$.1

1.47

editi

on

A1

29

material 2004020085 code 95

				of inch section, limit	±0.2	±0.3	±0.5	±0.8	±1.2	±2	1	and rify										
	~			deviation value								atify			S	tage		qua	weight	scale	figure	JXHSV05P-02006-d
A1	$\bigcirc$	1 . Add 2 steps;	2024.4.8	Straight degree	≤10	>	>	>	>	>					n	narkin	ıg	ntity			numbe	
	tab	Change the content	date	peace The	0.05	10~30	30~100	100~300	300~100	1000~30							-				r	
tio n				surface degree is not noted Toleran ce value		0.1	0.2	0.4	0 0.6	00 0.8			1, the	1				1	0.0	2:1	nam e	Z-axis belt pressure plate 2