

editi	Α0
on	
material code	20040200859 6





- technical requirement:

 1. Fire rating: material flame retardant, automatically extinguished within 10 seconds after leaving the flame;

 2. Use 100% new material for all materials,

 3. All materials must be confirmed by samples before production;

 4, the appearance surface frosted, grain reference sample;

 5, the product can not be deformed, not allowed to have strain, shrinkage and air lines and other surface defects;

 6, the surface of the parts is clean, free of oil, chips, dust, etc.

 7, the surface to prevent scraping, bumping, crushing, deformation and other bad."

 8. Compliance with the latest RoHS regulations:

- 8. Compliance with the latest RoHS regulations;9. No noted dimension, refer to 3D drawings;10. Material color: black

			The linear tolerance is GB / T1804-m; the shape tolerance is GB / T1184-K							gn	Wang Enda	2024/2/24	Jie Xinhua Technology	mat erial	ABS+PC
Ī			Linear basic ruler, pole	>6~30		> 120~400	> 400~100 0	> 1000~20 00	> 2000~40 00	examin			Co., LTD	type	SV05P

				of inch section, limit deviation value	±0.2	±0.3	±0.5	±0.8	±1.2	±2	e and verify ratify			Stac	1P	qua	weight	scale	figure	JXHSV05P-02011-d
edi	tab	Change the content	date	Straight degree peace The	≤10 0.05	l .		> 100~300	> 300~100	> 1000~30				-	king	ntity		Scare	numbe r	34131031 0 <u>2</u> 011 u
tio n				surface degree is not noted Toleran ce		0.1	0.2	0.4	0 0.6	00 0.8		1, the	1			1	0.0	5:1	nam e	stop block