

Version

material

change content

date

Technical requirements: 1. Dimensions with "±" in the picture are important inspection items; 2. If the dimensional tolerance is not noted, the tolerance is ±0.2mm; 3. Specification: Transistor EPC-05A20M 1010 24V double ball bearing 15000r/min 1.8-2.2 CFM 2X-47 500; 4. Terminals should be checked with heat-shrinkable tubes; 5. There should be no dirt or damage on the external surface, and there should be no broken copper wire inside the connector; 6. The connector can withstand 1000VDC voltage; 7. When the damage, no deformation or rust in the terminals; 8. The wire must comply with UL certification; 9. Comply with the company's color code standard, or color at 200°C/95; 10. Comply with RoHS (the European market also complies with REACH requirements); 11. Comply with the "Administrative Measures for the Restriction of the Use of Hazardous Substances in Electrical and Electronic Products".

batch level

allow

count

Number

McGraw-Hill

trace

Wire

describ

material

No.

2023/11/24

28AWG(0.5A)

Jie Xinhua Technology Co., Ltd.

stage mark

quantity

1

weight

Proportion

1:1

name

drawing number

model

material

JXH SV05P-06039-f

quantity

3010 Turbofan

SV05P

Unit

PCS

Material coding

Version

Book

200003000567

A0

3010 Turbofan

EFC-03A24M

24V

Double ball bearing

15000r/min

30.0

24.0

30.0/24.0

150+5mm

1.25-3Y white plastic shell

red black yellow

2x Ø2.5 penetrate