


A0 version	on material
code 200402008613	



Technical requirements: 1. All materials use 100% new materials. 2. All materials must be sample confirmed before production; 3. The appearance is frosted, and the texture refers to the sample; 4. The product cannot be deformed, and no strains, shrinkage or air marks are allowed. and other surface defects; 5. The surface of the parts is clean and free of oil, chips, dust, etc.6. The surface is protected from scratches, bumps, bruises, deformation and other defects.

7. Comply with the latest RoHS regulatory requirements; 8. No dimensions are noted, please refer to the 3D drawing; 9. Material color: black

				Linear tolerances are implemented according to GB/T1184 in level; geometric tolerances are implemented according to GB/T1184-K level.							design	Xiao Zepeng	2024/2/24	Jie Xinhua Technology Co., Ltd.				Drawing number	Black	
				Limit deviation values for linear basic size segments	> 6 ~ 30	> 30 ~ 120	> 120 ~ 400	> 400 ~ 1000	> 1000 ~ 2000	> 2000 ~ 4000		review					model material	ABS SV05P		
					±0.2	±0.3	±0.5	±0.8	±1.2	±2		approve		stage mark	quantity	weight	Proportion	JXHSV05P-07206-d		
Version	mark	change content	date	Unspecified tolerance values for straightness and flatness	≤10	> 10 ~ 30	> 30 ~ 100	> 100 ~ 300	> 300 ~ 1000	> 1000 ~ 3000		1 in total		Picture 1		1		3:1	name	limit switch stop