

technical requirement:
Surface treatment: sandblasting oxidation, gray, PANTONE 430C, the sample shall prevail;
1. To deburr, the sharp angle is too blunt;
2. No note of the chamfer C0.2;
3. Drawing for all hole position tolerance dimensions ± 0.1mm;
4. Reference to 3D drawing for unannotated dimension;

- 5. The surface to prevent scraping, bumping, crushing, deformation and other bad.

	The linear tolerance is GB / T1804-m; the shape tolerance is GB / T1184-K							desi an	Wang Enda	2024/3/9	Jie Xinhua Technology	mat erial	6061
		> 6~30		> 120~400	> 400~100 0	> 1000~20 00	> 2000~40 00	examin			Co., LTD	type	SV05P
sec lim	ction,	±0.2	±0.3	±0.5	±0.8	±1.2	±2	e and verify			Chara and any later and a	£	D// IC/ /0FD 02002

	\perp				value										markin	na	ntity			numbe	
					Straight degree	≤10	>	>	>	>	>					3				r	
ed tio	i ta	ab	Change the content	date	peace The	0.05	1		l	300~100		-	1, the	1			1	0.2	1:2	nam	The front
n					surface degree is		0.1	0.2	0.4	0 06	00		,							e	profile
					not noted					0.6	0.0										
					Toleran ce																
					value																