
3MF Test Specification

Specification & Reference Guide



Version	2.0.0
Status	Published

THESE MATERIALS ARE PROVIDED "AS IS." The contributors expressly disclaim any warranties (express, implied, or otherwise), including implied warranties of merchantability, non-infringement, fitness for a particular purpose, or title, related to the materials. The entire risk as to implementing or otherwise using the materials is assumed by the implementer and user. IN NO EVENT WILL ANY MEMBER BE LIABLE TO ANY OTHER PARTY FOR LOST PROFITS OR ANY FORM OF INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES OF ANY CHARACTER FROM ANY CAUSES OF ACTION OF ANY KIND WITH RESPECT TO THIS DELIVERABLE OR ITS GOVERNING AGREEMENT, WHETHER BASED ON BREACH OF CONTRACT, TORT (INCLUDING NEGLIGENCE), OR OTHERWISE, AND WHETHER OR NOT THE OTHER MEMBER HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Revisions:

Version	Changes	Date/Editor
1.0	Initial Release	JZ - 6/28/19
1.1	Added Beam Lattice Test Suite	JZ - 4/24/20
1.2	Change after review	JZ - 5/13/20
1.21	Fix Numbering Typos, added 4 test cases	JZ - 5/17/20
1.22	Misc tweaks to test cases	JZ - 6/20/20
1.23	Additional changes to beam lattice test cases	JZ - 7/3/20
1.24	Removed Test P_BXX_2005_02.3mf as it is a duplicate of a negative test case	JZ-7/9/20
1.25	Add ballmode test cases	JZ - 10/14/20
1.26	Minor test case edits	JZ - 10/18/20
1.27	Final Ball mode test edits	JZ - 11/24/20
1.30	Add Secure Content test cases	JZ - 11/25/20
1.31	Minor updates to Secure Content negative test cases	JZ - 11/30/20
1.32	A few changes to ballmode test cases for beam lattice	JZ - 12/8/20
1.33	Minor changes to Secure Content positive test cases	JZ - 12/10/20
1.34	Fixes for GitHub Test_Suite issues 65, 66. Modified positive test cases 321_01, 506_01, 304_04, and added negative test case 405_04.	JZ - 12/19/20
1.35	Addressed Github Test Suite issues 69, 68, 67, 62, and 56	JZ - 4/15/21
2.0.0	Release	JZ - 6/18/21

1 Contents

R	evision	ns:	2
2	Intr	oduction	4
3	Ter	ms and Acronyms	4
4	Sco	pe	4
5	Tes	t Suite Organization	5
	5.1	Test Case Numbering	5
	5.2	Test Case Template	6
	5.3	basematerials name Attribute Mapping	7
6	Tes	t Case Definitions	8
	6.1	Positive OPC Test Cases	8
	6.2	Negative OPC Test Cases	10
	6.3	Positive 3MF Core Test Cases	12
	6.4	Negative 3MF Core Test Cases	24
	6.5	Positive 3MF Material Extension Test Cases	32
	6.6	Negative Material Extension Test Cases	51
	6.7	Positive Production Extension Test Cases	54
	6.8	Negative Production Extension Test Cases	60
	6.9	Miscellaneous 3MF Test Cases	62
	6.10	Positive 3MF Slice Extension Test Cases	68
	6.11	Negative Slice Extension Test Cases	74
	6.12	Positive Beam Lattice Extension Test Cases	76
	6.13	Negative Beam Lattice Extension Test Cases	86
	6.14	Positive Secure Content Extension Test Cases	89
	6.15	Negative Secure Content Extension Test Cases	96
A	ppendi	ix A - Test Object Library	101
Α	ppendi	ix B – Color, Texture, Lattice Tables	108
Α	ppendi	ix C - Test Case to Test Suite Mapping	117
Α	ppendi	ix D – Secure Content Test Keys and IDs	133

2 Introduction

The 3D Manufacturing Format, or 3MF, describes the set of conventions for the use of XML and other widely available technologies to describe the content and appearance of one or more 3D models. It is written for developers who are building systems to process 3MF content.

A primary goal of this specification is to ensure the interoperability of independently created software and hardware systems that produce or consume 3MF content. This specification defines a set of test cases that can be used to validate 3MF consumer and producer implementations.

3 Terms and Acronyms

The following terms and abbreviations are used in this document:

Term	Description
3MF	3D Manufacturing Format
OPC	Open Packaging Conventions
DUT	Device Under Test

4 Scope

Execution of a 3MF test suite will provide a robust characterization of the Device Under Test's (DUT) behavior by providing a wide variety of both valid and invalid 3MF content based upon each of the conformance statements and schemas in the specifications that define 3MF. Collectively, running all the test cases developed as part of this test suite will provide the following test coverage:

- The DUT can successfully process 3MF files that include valid permutations of mandatory characteristics defined in the supported 3MF XML schemas
- The DUT can successfully process 3MF files that both include and exclude valid permutations of optional characteristics defined in the supported 3MF XML schemas
- The DUT can successfully process 3MF files that conform to valid permutations of the mandatory and optional OPC, Core, Material, Slice, and Production conformance requirements defined in 3MF technical specifications
- The DUT can gracefully handle invalid 3MF file content

Test cases are based on the following versions of the 3MF Specifications:

- Office Open XML File Formats Open Packaging Conventions December 2012
- 3MF Core Specification Version 1.2.3
- 3MF Materials and Properties Extension Version 1.2.1
- 3MF Production Specification Version 1.1.2
- 3MF Slice Specification Version 1.0.2
- 3MF Beam Lattice Extension Version 1.2.0
- 3MF Secure Content Extension 1.0.3

5 Test Suite Organization

Test cases defined in this specification may support one or more 3MF extensions and may belong to one or more test suites. The table below documents the seven supported test suites.

Suite Name	Core	3MF Extensions				
		Slice	Production	Material	Beam Lattice	Secure Content
Test Suite 1	•	•	•			
Test Suite 2	•		•	•		
Test Suite 3	•					
Test Suite 4	•	•				
Test Suite 5	•		•			
Test Suite 6	•			•		
Test Suite 7	•		• (1)		•	
Test Suite 8	•	(2)	•	(2)		•

⁽¹⁾UUID used, but extension not required

Note that Appendix C provides a mapping as to which test cases are contained in which test suites.

5.1 Test Case Numbering

Test Cases will use the following syntax for numbering: **U_VWX_YYYY_ZZ**

- U: P = positive, N = Negative
- V: S = Slice Used, B = Beam Lattice Used, E = Secure Content Used, X = Neither Beam, Slice, or Secure Content used
- W: P = Production Used, X = Production not used
- X: M = Material Used, X = Material not used
- YYYY: Test case number
- ZZ: Test case iteration

Examples:

- **P_SPX_0123_02** This is positive test case 123, iteration 02, that uses the Slice and Production Extensions
- **N_XXM_0234_04** This is negative test case 234, iteration 04, that uses the Material Extension
- **P_BXX_0432_01** This is a positive test case 432, iteration 01, that uses the Beam Lattice Extension.

⁽²⁾Several test files in the suite requires this extension

Test case definitions in this document may use "???" placeholders for the 3MF extension labels, such as P_???_0123_02. Users should refer to Appendix C to determine the specific 3MF extension combinations supported for a test case.

5.2 Test Case Template


The following template will be used for test case definition. Note a general test scenario is followed by one or more iterations of a test case required to validate the conformance requirements targeted.

N_???_0123 Test Scenario Name

Test Scenario Description	3MF test files where the StartPart relationship defined in _rels/.rels does not point
	to the root 3d Model part
Pass/Fail Criteria	Printer rejects 3MF File
Test Case Iterations	01 - StartPart points at non-existent part
	02 - StartPart points at non-root model
	03 - StartPart points at Thumbnail
	03 - Etc.

Where practical, each 3MF test file will contain a 300 X 300-pixel thumbnail showing the expected result of rendering the 3MF file on a consumer as shown below. An example is shown below. These thumbnails are captured from a variety of applications and are not meant to be used as a definitive acceptance criterion. Note that shading and other lighting effects used by application may slightly alter the apparent colors.


Expected Result




Note that the expected result thumbnails were captured using a variety of 3MF display rendering applications including 3D Builder, NetFabb, 3D Paint, QualtyLogic's 3MF previewer, MeshLab rendered PLY files, and other applications. Each of these applications placed the 3D object in a different orientation and many objects needed to be rotated to show the intent of the test when capturing the thumbnails. Point being that users may need to rotate their 3MF images to get them in alignment with the thumbnail before comparing results and that thumbnail to thumbnail the orientations may differ.

Where the rendered 3MF file might differ between a display and printer, thumbnails of both renderings will be provided. The basematerials displaycolor attribute and the display properties which can be applied to resources only impact the appearance of the object on a display, not a printer. So, in these situations, the thumbnail labels "Most Robust Rendering" represents the appearance on a display and the rendering labels "basematerials Ignored" represents the appearance of the printer output assuming a neutral gray colored native material color.

Expected Results







Some test suites at the time they were written, such as beam lattice and secure content, did not have available implementations that render color. So, thumbnails are presented as monochrome images even though in some cases the test intent is to show the difference in color . The thumbnail images for test cases where this is an issue will have the notation "Monochrome Image" on them.

5.3 basematerials name Attribute Mapping

Some printer implementations may require that the name attribute the basematerials base sub element be mapped to a physical material. The test cases use a standardized format for materials names: material_0, material_1, material_2, etc.

Implementations can simply map the same physical material to these names.

6 Test Case Definitions

6.1 Positive OPC Test Cases

6.1.1 P_???_0101 Content Type Variation

Test Scenario Description	Verify that content type mapping is case insensitive and that overrides do take precedence of the default extension definitions.
Pass/Fail Criteria	01 to 03 – Printer should process correctly
Test Case Iterations	 O1 – Create a content type where the case of the content type extension differs from the case used by the model part. The extension should be case insensitive. O2 – Create a 3MF 3D model part with no extension, and use a content type override to define the content type of that part. O3 – Define a content type override for a 3D model part whose case differs from the 3D model part name. The override should be case insensitive.
Requirement Reference	ECMA-375,4 Conformance ID: M2.9, M2.13, M1.2

6.1.2 P_???_0102 Content Type Overrides

Test Scenario Description	Various permutations of content type overrides
Pass/Fail Criteria	01 to 03 – Printer should process correctly
Test Case Iterations	 O1 – Create a test case where content types contains no default for ".model" but rather has an explicit override for each model part. Rename the extensions of the model parts to something other than ".model" O2 – Create a test case where content types contains a default for ".model" and an override for the 3D model part. Rename the extensions of the model part reference in the override to something other than ".model" O3 – Create a test file with a thumbnail. Leave the default mapping for ".model" as is. Rename the thumbnail extension to ".model" and define an override for the thumbnail mapped to the appropriate type for a thumbnail.
Requirement Reference	ECMA-375,4 Conformance ID: M2.4, M2.12, M2.9

6.1.3 P_???_0103 Unused Default Mapping

Test Scenario Description	Unused default content type mapping
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – Include an unused default mapping (to Thumbnail) that is not used (i.e., no Thumbnail in package)
Requirement Reference	ECMA-375,4 Conformance ID: O2.5

6.1.4 P_???_0104 Model/Texture Part Names

Test Scenario Description	Various character mappings in part names
Pass/Fail Criteria	01 to 03 – Printer should process correctly
Test Case Iterations	01 – Create 3MF file with model part names that use alphanumeric characters
	from 0-9, a-z, A-Z, and the following unreserved characters: ~
	02 – Create 3MF file with model part names that use alphanumeric characters
	that include the following reserved characters: @ ! \$ () +,;=
	03 – Deleted
	Deleted
	04 – Model name and related relationship referenced using escaped Unicode characters. Include part name and part number with unescaped Unicode
	05 - Texture2dl name and related relationship referenced using escaped
	Unicode characters. Include part name and part number with unescaped Unicode
Requirement Reference	ECMA-375,4 Conformance ID: M1.17, M3.2, O1.4, M2.12

6.1.5 P_???_0106 Thumbnail Image Size Range

Test Scenario Description	Various thumbnail image sizes
Pass/Fail Criteria	01 to 02 – Printer should process correctly
Test Case Iterations	01– Use a large jpg thumbnail image typical of a photo from a phone02– Use an extremely small (20 pixel) PNG Thumbnail image
Requirement Reference	ECMA-375,4 Conformance ID: M1.72

6.1.6 **P_???_0107 TargetMode**

Test Scenario Description	Valid relationship target mode permutations
Pass/Fail Criteria	01 to 02 – Printer should process correctly
Test Case Iterations	 O1 – Root 3MF file with relationship to a non-root model file that omits the TargetMode attribute O2 – Root 3MF file with relationship to a non-root model file that uses a TargetMode = "Internal" attribute
Requirement Reference	ECMA-375,4 Conformance ID: O1.5

6.2 Negative OPC Test Cases

6.2.1 N_???_0202 Path Segment Period Ending

Test Scenario Description	Path segment that ends with a period
Pass/Fail Criteria	01 – Printer should generate error
Test Case Iterations	01 – Create a path segment that ends with a period. As the operating system will not allow subdirectories ending in a period and zip utilities also disallow periods at the end, the best this test case can do is use a period at the end of an existing referenced path in the XML
Requirement Reference	ECMA-375,4 Conformance ID: M1.9

6.2.2 N_???_0203 Path Segment Only Period

Test Scenario Description	Path segment with only a period
Pass/Fail Criteria	01 – Printer should generate error
Test Case Iterations	01 – Create a path segment with only a period. As the operating system will not allow subdirectories with just a period and zip utilities also disallow standalone periods, the best this test case can do is use a period as part of an existing referenced path in the XML
Requirement Reference	ECMA-375,4 Conformance ID: M1.10

6.2.3 N_???_0204 Relationship Content Parameter and Target Attribute

Test Scenario Description	Add a parameter to the relationships part
Pass/Fail Criteria	01, 02 – Printer should generate error
Test Case Iterations	 O1 – Add a parameter to the relationships part content type (i.e ?cow="Moo"). Printer should reject. O2 – Test where the capitalization of the thumbnail extension zip part name differs from the capitalization used in the relationship Target attribute
Requirement Reference	ECMA-375,4 Conformance ID: M1.22

6.2.4 N_???_0205 Duplicate Content Type

Test Scenario Description	Duplicate content type mappings
Pass/Fail Criteria	01 to 02 – Printer should generate error
Test Case Iterations	01 – Add duplicate default content type mappings for the ".model" extension 02 – Add a duplicate override content type for a 2D model part
Requirement Reference	ECMA-375,4 Conformance ID: M2.5

6.2.5 N_???_0206 Empty Extension Content Type

Test Scenario Description	Content type with an empty extension
Pass/Fail Criteria	01 – Printer should generate error
Test Case Iterations	01 -Create a content type with an empty extension (i.e. "")
Requirement Reference	ECMA-375,4 Conformance ID: M2.6

6.2.6 N_???_0207 Empty Partname String

Test Scenario Description	Override with an empty partname string
Pass/Fail Criteria	01 – Printer should generate error
Test Case Iterations	01 – Create a content type override with an empty partname string
Requirement Reference	ECMA-375,4 Conformance ID: M2.7

6.2.7 **N_???_0208 Unicode in Zip Name**

Test Scenario Description	Use unescaped Unicode characters in a zip file name and relationship reference
Pass/Fail Criteria	01, 02 — Printer should generate error
Test Case Iterations	01 – Unicode string in model name and related relationship reference
	02 – Unicode string in texture2d file and related relationship reference
Requirement Reference	

6.3 Positive 3MF Core Test Cases

6.3.1 P_???_0302 StartPart Location and Name

Test Scenario Description	Create a simple 3MF file, then reposition and rename the StartPart pointed to by the .rels file
Pass/Fail Criteria	01 to 03 – Successfully render object with no processing errors
Test Case Iterations	 01 – Reposition StartPart at root of package. 02 – Reposition the StartPart (3DModel.model) several sub folders deep 03 – Rename the root model to something other than 3DModel.Model (maintain. model extension)
Requirement Reference	Link to Requirement in 3MF Specification

6.3.2 **P_???_0304** Part Relationships

Test Scenario Description	Create a 3MF file that contains the appropriate relationship pointers to a Print
	Ticket, Thumbnail, and Core Properties Parts
Pass/Fail Criteria	02 – Printer should ignore extra thumbnail
	03 – Printer should process the file correctly
	04 – Printer should process the file correctly
Test Case Iterations	
	02 – Include two package level thumbnails in the same OPC package
	03 – Have a package level and object level thumbnail reference point to the same png file.
	prig me.
	04 – Change the ID of the StartPart relationship ID in the root .rels file to something other than "rel0" that includes "_" as a leading character
Requirement Reference	Link to Requirement in 3MF Specification

6.3.3 **P_???_0306 Units**

Test Scenario Description	Create a simple 3MF file, then modify the 3D model files to support each of the supported enumerations for the unit attribute of the Model element
Pass/Fail Criteria	01 to 07 – Printer should process correctly
Test Case Iterations	Modify the build transform matrix of the 3D model file such that each of the images have the same size and positioning regardless of the unit used. 01 – Micron 02 – Millimeter 03 – Centimeter 04 – Inch 05 – Foot 06 – Meter 07 – Unspecified (should default to millimeter)
Requirement Reference	Link to Requirement in 3MF Specification

6.3.4 **P_???_0307 Metadata - Core**

Test Scenario Description	Create a simple 3MF file, then add metadata elements from the core specification to the 3D model parts
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – Include the metadata values defined in table 8-1 of the Core specification into the 3D model parts. Syntax for metadata is <metadata name="title">this is a title</metadata>
Requirement Reference	Link to Requirement in 3MF Specification

6.3.5 **P_???_0308 Metadata - Vendor**

Test Scenario Description	Create a simple 3MF file, then add vendor specific metadata elements to the 3D model parts.
Pass/Fail Criteria	01 - Printer should process correctly, ignoring the vendor specific metadata values
Test Case Iterations	O1 – Include the vendor specific metadata values defined to 3D model files xmlns:v="http://schemas.qualitylogic.com/vendorspecific" <metadata name="v:anyname">this is a test</metadata>
Requirement Reference	Link to Requirement in 3MF Specification

6.3.6 **P_???_0309** Overlapping objects

Test Scenario Description	Create a 3MF file such that two objects are overlapping such that the positive full rule is applied by the printer
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – Use 3D Builder to position the two instances of the test object such that the two objects overlap with empty space in the middle of the overlapping segments of the object. Make sure objects stay at least 30mm x 35mm x 30mm away from the origin of the print bed.
Requirement Reference	Link to Requirement in 3MF Specification

6.3.7 P_???_0310 Build Item

Test Scenario Description	Create a simple 3MF file with two objects, but with only one item referenced in a build item
Pass/Fail Criteria	01 – Printer should process correctly, although only the object in the build item should be rendered
Test Case Iterations	01 – Add both test objects to 3D builder, confirm two items are listed in the build element (modify if needed), then remove one item from the build object. The resulting test file should render a single object although it contains two objects
Requirement Reference	Link to Requirement in 3MF Specification

6.3.8 **P_???_0311 Build Item Transform**

Test Scenario Description	Create a simple 3MF file with one object, but two build items each referencing the same object, applying a different build item transform on one item
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – Modify one build item transform matrix to position the two objects such that they are non-intersecting
Requirement Reference	Link to Requirement in 3MF Specification

6.3.9 P_???_0312 Base Material References

Test Scenario Description	Create a simple 3MF file with one object and add a basematerials to the 3dmodel
	file
Pass/Fail Criteria	01 – Printer should NOT render the colors, but should print the object in its native
	material color
Test Case Iterations	01 – Specify a color in the object element via a reference to the basematerials
	definition. For triangles, do the following:
	-Include pid, p1, p2, p3 attributes for blue in one triangle. This will override the
	object pid and pindex for the rendering of this triangle
	For Test suites that do not support the material extension include the following:
	-Select one triangle element and omit the P1, P2, and P3 attributes, but include the
	pid attribute. This will result in the default object pid and pindex being used for the
	triangles rendering
	-Select a triangle and omit the PID attribute, but include the P1, p2, and p3
	attributes. This will result in the triangles p1, p2, and p3 attribute index values
	being mapped against the pid value at the object level for rendering.
	NOTE: Basematerials references are for display only and will not impact the printer
	rendered output.
Requirement Reference	Link to Requirement in 3MF Specification

6.3.10 **P_???_0313 JPEG Thumbnail**

Test Scenario Description	Create a simple 3MF file with a JPEG Thumbnail
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – Create a 3MF with a jpeg thumbnail at the package level
Requirement Reference	Link to Requirement in 3MF Specification

6.3.11 P_???_0314 solidsupport, support, surface

Test Scenario Description	Create a 3MF document with two objects. Modify the object type attribute in the 3D object such that one object had a type of "model" and the other one of the following: "solidsupport", "support"
Pass/Fail Criteria	01 – Printer should process correctly, although rendering of support may be device dependent
Test Case Iterations	 01 – model and solidsupport 02 – model and support 03 – model and support where support only has 3 triangles 04 – model and surface 05 - model and solidsupport not inside component
Requirement Reference	Link to Requirement in 3MF Specification

6.3.12 P_???_0315 Name Attribute White Space

Test Scenario Description	White space in name attribute of object
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – Modify the name attribute of the object element to include leading, trailing, and intermediate white space including the space character and tab
Requirement Reference	Link to Requirement in 3MF Specification

6.3.13 P_???_0316 Model Element Language Attribute

Test Scenario Description	Omit the lang attribute
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – Omit the lang attribute from the model element
Requirement Reference	Link to Requirement in 3MF Specification

6.3.14 P_???_0317 Duplicates of Multiple Mesh Objects

Test Scenario Description	Duplicates of multiple mesh objects
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – A test case that use 3 different mesh objects defined in the same root model parts to build 24 objects, 8 of each via build item element on the build platform. Objects should be positions both adjacent in XY space, and stacked in the Z space.
Requirement Reference	Link to Requirement in 3MF Specification

6.3.15 **P_???_0318** Positive Fill Rule

Test Scenario Description	Objects with patterns that trigger positive fill rule
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – This is a very limited test of the fill rule outlined in the core specification which defines the behavior when two features in the same mesh intersect. Define two mesh objects each with overlapping features. The first is a composite mesh object with a cube containing an embedded cylinder with 3 surfaces coplanar to the cube. The second is a composite mesh object with a cylinder intersecting a torus ring.
Requirement Reference	<u>Link to Requirement in 3MF Specification</u>

6.3.16 P_???_0319 Undetermined Language

Test Scenario Description	Undetermined language
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – Define test file where model lang attribute is "und".
Requirement Reference	Link to Requirement in 3MF Specification

6.3.17 **P_???_0321 Negative Determinant**

Test Scenario Description	Create mesh with negative determinant
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – Create transform with negative determinant and a mesh with negative object volume
Requirement Reference	Link to Requirement in 3MF Specification

6.3.18 **P_???_0322 JPEG APP1 Marker**

Test Scenario Description	JPEG thumbnail Image with APP1 Marker
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – JPEG thumbnail Image and texture with APP1 Marker
Requirement Reference	Link to Requirement in 3MF Specification

6.3.19 P_???_0323 PNG Specification Support

Test Scenario Description	Various headers in PNG files
Pass/Fail Criteria	01 to 02 – Printer should process correctly
Test Case Iterations	01 – PGN texture with tRNS and iCCP (include one or more in test case) 02 – PNG thumbnail with one of the MUST ignore items: sRGM, cHRM, gAMA, sBIT (include one or more in test case)
Requirement Reference	Link to Requirement in 3MF Specification

6.3.20 **P_???_0324**

6.3.21 Object Thumbnail Relationship

Test Scenario Description	Thumbnail relationship to non-root model
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – Associate a thumbnail via relationship and object attribute with a non-root model file.
Requirement Reference	Link to Requirement in 3MF Specification

6.3.22 P_???_0325 Two Segment Model Part Name

Test Scenario Description	Two segment model part name
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – Modify Content Types so that extension ".model" is ".part", then model balance of test file to use this extension placing parts in the default /3D folder
Requirement Reference	Link to Requirement in 3MF Specification

6.3.23 P_???_0326 Identity Singular Transform Matrix

Test Scenario Description	Object with Identity and singular matrix transform
Pass/Fail Criteria	01 to 03 – Printer should process correctly
Test Case Iterations	01 – Create a build item with no transform matrix
	02 – Create a build item with an identity transform matrix
	03 – Create a build item with a singular transform matrix
Requirement Reference	Link to Requirement in 3MF Specification

6.3.24 **P_???_0327 Interlocking Objects**

<u> </u>	
Test Scenario Description	3MF test file with interlocking objects
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – Use build item transforms to create a set of 2 interlocking, but not overlapping objects.
Requirement Reference	Link to Requirement in 3MF Specification

6.3.25 **P_???_0328 Overlapping Objects**

Test Scenario Description	3MF test file with Overlapping objects
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – Specify build item transform so that two objects overlap
	02 – illustrate overlapping objects that have plains that are coplanar and show which material should have precedence (that last one rendered).
Requirement Reference	Link to Requirement in 3MF Specification

6.3.26 **P_???_0329 Part Number Attribute**

Test Scenario Description	Use of PartNumber attribute of Object
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – Include a PartNumber attribute in object element in a test file
Requirement Reference	Link to Requirement in 3MF Specification

6.3.27 P_???_0330 Minimal Self-Intersections

Test Scenario Description	Mesh object with self-intersections
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – Create a mesh object with self-intersections. Printer will most likely correct self-intersection triangles in mesh object.
Requirement Reference	Link to Requirement in 3MF Specification

6.3.28 **P_???_0331 Non-Degeneracy**

Test Scenario Description	Mesh object with zero area triangle
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – Create a mesh image with a zero-area triangle. Printer will most likely ignore zero-area triangle in mesh object.
Requirement Reference	Link to Requirement in 3MF Specification

6.3.29 **P_???_0333 Decimal Precision**

Test Scenario Description	Various permutations of decimal precision
Pass/Fail Criteria	0 to 03 – Printer should process correctly
Test Case Iterations	01 – Use 3D vertex values with no decimal places to define mesh object
	02 – Use 3D vertex values with 10 decimal places to define mesh object
	03 – Use 3D vertex and unit of meter such that changes in very small decimal values impact the object shape in a meaningful way
Requirement Reference	Link to Requirement in 3MF Specification

6.3.30 **P_???_0334 JPEG Image Markers**

Test Scenario Description	Thumbnail JPEG images with different markers
Pass/Fail Criteria	01 to 02 – Printer should process correctly
Test Case Iterations	 O1 – Test case with JPEG Thumbnail that contains the APPO marker. O2 – Test case with JPEG Thumbnail that contains the APP2, APP13, and APP14 marker.
Requirement Reference	Link to Requirement in 3MF Specification

6.3.31 P_???_0335 Object Thumbnail Attribute

Test Scenario Description	Thumbnail JPEG images with different markers
Pass/Fail Criteria	01 to 04 – Printer should process correctly
Test Case Iterations	 O1 – Define a thumbnail from an object with mesh data using the thumbnail attribute. Use a PNG Thumbnail image. Make sure to include appropriate relationship pointers. O2 – Define a thumbnail from an object with a component reference using the thumbnail attribute. Use a JPEG thumbnail image. Make sure to include appropriate relationship pointers. O3 – Use a thumbnail attribute on a model element in a root model, and if the production extension is supported, on a non-root model part O4 – Use a texture rather than thumbnail relationship type associated with thumbnails at the package, model, and object level
Requirement Reference	<u>Link to Requirement in 3MF Specification</u>

6.3.32 **P_???_0336 Custom Part - Preserve**

Test Scenario Description	Custom part with and without a root relationship mustPreserve type
Pass/Fail Criteria	01 to 02 – Printer should process correctly
Test Case Iterations	01 – Define a custom part with no mustPreserve root relationship
	02 – Define a custom part with a mustPreserve root relationship
Requirement Reference	Link to Requirement in 3MF Specification

6.3.33 P_???_0337 metadatagroup, preserve, type

Test Scenario Description	Test metadatagroup in build item and object. Use preserve and type attributes in metadata where it is allowed to appear
Pass/Fail Criteria	01 to 06 – Printer should process correctly
Test Case Iterations	Use the table below to construct various iterations of metadata at the model, build item, and object level, conditionally using the preserve and type attribute.
Requirement Reference	Link to Requirement in 3MF Specification

Iteration	Model	Object	Build item	Preserve	Туре	Other
	Metadata	metadatagroup	metadatagroup			
01	Description			false		
	Title			true		
	Copyright				string	
	CreationDate				date	
	LicenseTerms			true	string	
	x:vendor1			false		
	x:vendor2			true		
	x:vendor3				string	
	x:vendor4				date	
	x:vendor5			true	integer	
02		x:vendor1				
		x:vendor2		false		
		x:vendor3		true		
		x:vendor4			string	
		x:vendor5			date	
		x:vendor6		true	integer	
03			x:vendor1			
			x:vendor2	false		
			x:vendor3	true		
			x:vendor4		string	
			x:vendor5		date	
			x:vendor6	true	integer	
04	x:vendor1			true	string	
		x:vendor2		true	string	
			x:vendor3	true	string	
05	Description			true	string	
		Title		true	string	s/ignore
			LicenseTerms	true	string	s/ignore
06	x:vendor1			true	string	
		x:vendor2		true	string	Non-roo
			x:vendor1	true	string	

6.3.34 **P_???_0338 Near Zero Volume**

Test Scenario Description	Transform that result in near zero volume printable object
Pass/Fail Criteria	01 – Printer should not generate error
Test Case Iterations	01 – Create a simple test case, then change the build item transform so that the object has close to zero volume. Output may be device dependent.
Requirement Reference	Link to Requirement in 3MF Specification

6.3.35 **P_???_0339** Not Required Extension

	<u> </u>
Test Scenario Description	Confirm printer will ignore content that is not from a required extension of not supported by the renderer
Pass/Fail Criteria	01 – Printer should not generate error
Test Case Iterations	01 – Create a simple test case with content from a namespace that is not required and is for 3MF core or extension namespaces. The renderer should ignore the content.
Requirement Reference	Link to Requirement in 3MF Specification

6.3.36 P_???_0340 Invalid Mesh, Valid Slicestack

Test Scenario Description	These are sliced test cases that have mesh with anomalies. The expectation is that the files will render correctly on a printer as the mesh is not needed for rendering. Note that in test case 01, 02, and 04 slice stacks have been inserted in the test file that does not match the mesh.
Pass/Fail Criteria	01 to 04 — Printer should not generate error
Test Case Iterations	01 - Create negative volume mesh, but with valid slicestack
	02 – Positive volume mesh with negative determinant transform, but with valid slicestack
	03 -Reverse order of vertices such that normal face is pointing inward, but with valid slicestack
Requirement Reference	Link to Requirement in 3MF Specification

6.4 Negative 3MF Core Test Cases

6.4.1 **N_???_0402 Invalid StartPart**

Test Scenario Description	Create a simple 3MF file, then modify so that the relationship StartPart such that does not resolve to a valid model root file
Pass/Fail Criteria	01 to 04 - Printer error should be generated stating that the file cannot be processed
Test Case Iterations	01 – Use an incorrect folder name in the StartPart Target 02 – Use an incorrect file name in the StartPath Target 03 – Point the StartPart to a thumbnail or non-root file 04 – Specify a StartPart relationship with a TargetMode="External" and a URL Target (i.e. http://www)
Requirement Reference	Link to Requirement in 3MF Specification

6.4.2 **N_???_0403 External References**

Test Scenario Description	Create a simple 3MF file, then modify so that there are external relationships in the root relationship file
Pass/Fail Criteria	01 – printer error
Test Case Iterations	01 – Specify a Thumbnail relationship in the root rels file with TargetMode="External" and a root model URL Target (i.e. http://www)
Requirement Reference	Link to Requirement in 3MF Specification

6.4.3 **N_???_0404 Invalid Content Type**

Test Scenario Description	Create a simple 3MF file, then modify to create invalid combinations of content types in the [Content.Types].xml file. Refer to Appendix C of Core Spec.
Pass/Fail Criteria	01 to 04 – Printer error should be generated stating that the file cannot be processed
Test Case Iterations	01 – In the [Content.Types].xml, modify the extension "model" to "item", such that a content type for "model" does not exist
	02 – In the [Content.Types].xml, modify the ContentType for "model" to "application/vnd.ms-package.xxxxx-3dmodel+xm", such that the content type for "model" is invalid
	03 – In the [Content.Types].xml, modify the ContentType for ".rels" to "application/vnd.openxmlformats-package.xxxxx-relationships+xml", such that the content type for ".rel" is invalid
	04 – In the [Content.Types].xml, modify the ContentType for "png" to "image/xxxpng", such that the content type for "png" is invalid
Requirement Reference	Link to Requirement in 3MF Specification- Could not find

6.4.4 N_???_0405 Invalid Relationships

Test Scenario Description	Create a simple 3MF file, then modify to create invalid relationship pointers. The test file will require a Thumbnail image.
Pass/Fail Criteria	01 to 05 – Printer Error
Test Case Iterations	01 – Add a Thumbnail to a 3MF file with invalid root relationship target to the Thumbnail part
	02 – Add an incorrect relationship "Type" attribute value in the root .rels file for the relationship that points to the StartPart
	03 – Add an incorrect relationship "Type" attribute value in the 3dmodel.model.rels file for the relationship that points to a non-root model file
	04 – Use a numeric leading digit for the root model's relationship iD
	05 – Add an incorrect relationship "Type" attribute value in root .rels part for the relationship that points to the Thumbnail
Requirement Reference	Link to Requirement in 3MF Specification

6.4.5 N_???_0406 Duplicate Relationship

Test Scenario Description	Create a simple 3MF file, then modify to create duplicate relationship pointers
Pass/Fail Criteria	01 to 02 – Printer Error
Test Case Iterations	 O1 – Modify the root .rels file so that there are identical instances of the start part pointer to the root model file, but using unique IDs (rel0 and rel1) O2 – Modify the 3dmodel.model.rels file so that there are two instances of a pointer to the same non-root model file, but with unique IDs.
Requirement Reference	Link to Requirement in 3MF Specification

6.4.6 N_???_0407 Missing Relationship Target

Test Scenario Description	Create a simple 3MF file, then modify relationship pointers
Pass/Fail Criteria	01 to 02 – Printer Error
Test Case Iterations	 O1 – Modify the 3dmodel.model.rels file so that the relationship target part name for the non-root model part does not match the part name in the 3MF document. O2 – Rename the 3dmodel.model.rels file so that it has a name that does not map to the 3dmodel.model part (i.e. wrongmodel.model.rels.)
Requirement Reference	Link to Requirement in 3MF Specification

6.4.7 **N_???_0409 Use of Space Attribute**

Test Scenario Description	Create a simple 3MF file, then modify XML encoding of root element to use the unsupported "space" attribute
Pass/Fail Criteria	01 – Printer Error
Test Case Iterations	01 – Modify the second line of the 3dmodel.model file to include the following attribute definition to the model element: xml:space="preserve"
Requirement Reference	Link to Requirement in 3MF Specification

6.4.8

6.4.9 **N_???_0410** Invalid Metadata

Test Scenario Description	Create a simple 3MF file, then add unrecognized vendor specific metadata elements to the 3D and 2D model parts, as well as duplicate names in metadata
Pass/Fail Criteria	01 to 04 – Printer should generate error
Test Case Iterations	01 – Include the vendor specific metadata value to the 3D model part with no declared namespace prefix in the Model element <metadata name="x:anyname">this is a test</metadata>
	02 – Include the vendor specific metadata value to the 2D model part
	Use the following metadata value in both test cases 01 and 02: <metadata name="x:anyname">this is a test</metadata>
	03 – Include the same metadata name from Table 8-1 of the core specification twice in the 3D model part
	<metadata name="Title">this is a title</metadata> <metadata name="Title">this is another title</metadata>
	04 - Include the same metadata name from Table 8-1 of the core specification twice in the 2D model part
	Use the following metadata values in both test cases 03 and 04: <metadata name="Title">this is a title</metadata> <metadata name="Title">this is another title</metadata>
Requirement Reference	Link to Requirement in 3MF Specification

6.4.10 N_???_0411 Non Unique Triangle Indices

Test Scenario Description	Create a simple 3MF file, then modify on triangle indices so that the vertex references are not unique
Pass/Fail Criteria	01 – Printer should generate error, although it is unclear if the printer will parse the 3D file in this level of detail.
Test Case Iterations	01 – Modify on triangle indices so that the vertex references are not unique
Requirement Reference	Link to Requirement in 3MF Specification

6.4.11

6.4.12 **N_???_0412 Invalid Index Range**

Test Scenario Description	Create a simple 3MF file that has out of range index references to vertex values
Pass/Fail Criteria	01 – Printer should generate error
Test Case Iterations	01 – Modify a 3DModel triangle vertex attribute (v1, v2, or v3) so that it is +2 larger than the number of vertexes
	02 – Modify a 2DModel polygon segment vertex attribute (v2) so that it is +2 larger than the number of vertexes
	03 – Modify a 2DModel polygon startv attribute (v2) so that it is +2 larger than the number of vertexes
	04 – Add a test case where the vertices element is missing altogether from a slice stack, but polygons are defined with invalid vertex index references.
Requirement Reference	Link to Requirement in 3MF Specification

6.4.13 **N_???_0413 Non-Unique ID Values**

Test Scenario Description	Create a simple 3MF file that has non- unique values for relationships in the same. rels file and the resources group (object ID) of a part
Pass/Fail Criteria	01 and 02 – Printer should generate error
Test Case Iterations	 O1 – Create a 3MF file with two items in the build item path. Modify the 3dmodel.model.rels file to create duplicate IDs. O2 – Create a 3MF file with two objects with the same ID values
Requirement Reference	Link to Requirement in 3MF Specification OPC

6.4.14 **N_???_0415** Absolute Path Names

Test Scenario Description	Scenarios involving invalid paths
Pass/Fail Criteria	01 to 04 – Printer should generate error
Test Case Iterations	01 – Define a model part name with a leading period and reference that part in a component reference
	02 – Attempt to reference a non-root model part using a relative component path attribute
	03 – Attempt to reference a non-root model part using a relative build path attribute
	04 – Attempt to reference a non-root model part in path using the path only in the component path element, omitting the part name
Requirement Reference	Link to Requirement in 3MF Specification

6.4.15 **N_???_0416 Negative Volume Mesh**

Test Scenario Description	Object with negative volume mesh
Pass/Fail Criteria	01 and 02 – Printer should generate error
Test Case Iterations	01 - Create negative volume mesh02 - Positive volume mesh with negative determinant transform
Requirement Reference	Link to Requirement in 3MF Specification

6.4.16 N_???_417 Prior Object References

Test Scenario Description	Create a forward reference scenario in the root model file
Conformance Statement ID(s)	Core-M1.60, Core-M1.33
Base Test Object(s)	S11_cube_NA.3mf
Pass/Fail Criteria	01 – Printer should generate error
Test Case Iterations	O1 – Create a forward reference by defining an object with a reference to a slicestackID before that slice stack appears in the XML stream
Requirement Reference	Link to Requirement in 3MF Specification

6.4.17 N_???_0418 Inward Facing Normal Face

Test Scenario Description	Mesh with inward facing normal face
Pass/Fail Criteria	01 – Printer should generate error
Test Case Iterations	01 -Reverse order of vertices such that normal face is pointing inwards.
Requirement Reference	Link to Requirement in 3MF Specification

6.4.18 **N_???_0419 CMYK Images**

Test Scenario Description	JPEG thumbnail Image with CMYK
Pass/Fail Criteria	01 – Printer should generate error
Test Case Iterations	01 – JPEG thumbnail Image with CMYK
Requirement Reference	Link to Requirement in 3MF Specification

6.4.19

6.4.20 **N_???_0420 Data Type Definitions**

Test Scenario Description	DTD declaration
- /- !! - !	
Pass/Fail Criteria	01 – Printer should generate error
Test Case Iterations	01 – Include a DTD declaration as follows after the XML header:
	note [</th
	ELEMENT note (to,from,heading,body)
	ELEMENT to (#PCDATA)
	ELEMENT from (#PCDATA)
	ELEMENT heading (#PCDATA)
	ELEMENT body (#PCDATA)
]>
Requirement Reference	Link to Requirement in 3MF Specification

6.4.21 **N_???_0421** Transforms

Test Scenario Description	Various transforms that result in invalid printable objects
Pass/Fail Criteria	01 to 02 – Printer should generate error
Test Case Iterations	01 – Create a simple test case, then change the build item transform so that it is outside the printable area of the printer with a portion of the image in a negative quadrant
Requirement Reference	Link to Requirement in 3MF Specification

6.4.22 **N_???_0422** Commas and German locale

Test Scenario Description	Specifying non en-US locale in model element
Pass/Fail Criteria	01 – Printer should generate error
Test Case Iterations	01 –specify the lang attribute in all model elements (core model) to "de-de" and modify all decimal places as commas (,).
Requirement Reference	Link to Requirement in 3MF Specification

6.4.23

6.4.24 N_???_0424 Material in Object with Component

Test Scenario Description	Add basematerials reference to object with a component
Pass/Fail Criteria	01 – Printer should generate error
Test Case Iterations	01 – Create an 3mf file with a colorgroup or basematerials defined, and specify a pid and pindex attribute in an object element that contains a component subelement that point to other objects.
Requirement Reference	Link to Requirement in 3MF Specification

6.4.25 N_???_0426 Model with Less Than 4 Triangles

Test Scenario Description	Mesh object with only 3 triangles
Pass/Fail Criteria	01 – Printer should generate error
Test Case Iterations	01 – Create invalid mesh object with only 3 triangles
Requirement Reference	Link to Requirement in 3MF Specification

6.4.26 N_???_0427 Duplicate 3D Vertex and Non-Manifold Edge

Test Scenario Description	Mesh object with duplicate 3D Vertex and non-manifold edges
Pass/Fail Criteria	01 – Printer should generate error
Test Case Iterations	01 – Create a non-manifold mesh image and duplicate 3D vertex. Printer may ignore non-manifold mesh object and duplicate vertex.
Requirement Reference	Link to Requirement in 3MF Specification

6.4.27 **N_???_0428** Required Extension

Test Scenario Description	Confirm printer will generate an error if a required extension is listed in the requiredextensions attribute of the model element that the renderer does not support
Pass/Fail Criteria	01 – Printer should generate error
Test Case Iterations	01 – Create a simple test case with content from a namespace that is required. The required extension should be a mock extension.
Requirement Reference	Link to Requirement in 3MF Specification

6.5 Positive 3MF Material Extension Test Cases

The Material Extension test cases will utilize the predefined colors, gradients, textures, and multiproperties defined in Appendix B. To the extent that specific colorgroups, textures, gradients, or multiproperties are not specified in the test case definition, the test case developer shall iterate through a random selection of the defined resources in Appendix B.

6.5.1 **P_???_0501 Default Material Color**

Test Scenario Description	Demonstrate use of object pid and pindex attributes as a default material color if a
	triangle does not have a material color specified
Pass/Fail Criteria	01 to 09 – Printer should process correctly
Test Case Iterations	01 - Multiproperties as default object color. Apply colorgroup to at least one triangle to demonstrate that only triangles with undefined material color are impacted by the default.
	02 - Texture as default object color. Apply colorgroup to at least one triangle to demonstrate that only triangles with undefined material color are impacted by the default.
	03 - Colorgroup as default object color. Texture at least one triangle to demonstrate that only triangles with undefined material color are impacted by the default.
	04 - No material color specified in object or triangles
	05 - Deleted
	06 - Deleted.
	07 – Texture as a default color where tex2coord pointed to by pindex is a u v value greater than 1 1
	08 – Multipropertes as a default color where tex2coord pointed to by pindex is a u v value greater than 1 1
	09 Texture with tilestyle of "none" as a default color where tex2coord pointed to by pindex is a u v value greater than 11.
Requirement Reference	Link to Requirement in 3MF Specification

6.5.2 P_???_0502 Triangle P1, 2, 3 Usage

Test Scenario Description	Demonstrate that If p1 is not specified, then the default property is assigned to the triangle. If p2 or p3 is unspecified then p1 is used for the entire triangle.
Pass/Fail Criteria	01 to 05 – Printer should process correctly
Test Case Iterations	01 - Just p1 Specified 02 - Just p1 and p2 Specified
	03 - Just p1 and p3 Specified
	04 - p2 and p3 Specified, but not p1 – With default object color defined
	05 - p1, p2, and p3 unspecified
Requirement Reference	Link to Requirement in 3MF Specification

6.5.3 P_???_0503 Ignoring Unsupported Materials

Test Scenario Description	Demonstrate that the printer ignores both basematerials and compositematerials
Pass/Fail Criteria	01 to 08– Printer should process correctly
Test Case Iterations	01 - Use basematerials as object default. Also map colorgroup to one triangle
	02 - Use compositematerials as object default. Also map colorgroup to one triangle
	03 - Use basematerials as triangle PID/P1 with colorgroup as object default
	04 - Use compositematerials as triangle PID/P1 with texture as object default
	05 - Use basematerials as multiproperties pids component. Map multiproperties as object default. The multiproperties should also include a colorgroup which should get rendered.
	06 - Use composite material as multiproperties pids component. Map multiproperties as object default. The multiproperties should also include a colorgroup which should get rendered.
	07 - Use basematerials as multiproperties pids component. Map multiproperties as triangle PID/P1 with texture as object default. The multiproperties should also include a colorgroup which should get rendered.
	08 - Use compositematerials as multiproperties pids component. Map multiproperties as triangle PID/P1 with colorgroup as object default. The multiproperties should also include a colorgroup which should get rendered.
Requirement Reference	Link to Requirement in 3MF Specification – Says N/A in the old mat spec

6.5.4 **P_???_0504** Opaque first Layer

Test Scenario Description	Demonstrate that the first layer of material color applied to an object is opaque
·	both when defined as an object default and as triangle specific
Pass/Fail Criteria	01 to 07 – Printer should process correctly
Test Case Iterations	01 – Use a colorgroup color with transparent alpha values to demonstrate the first layer applied to an object is opaque
	02 – Use a texture with transparent alpha values to demonstrate the first layer applied to an object is opaque
	03 – Use a colorgroup color with transparent alpha values to demonstrate the first layer of multiproperties is opaque. The second layer should also be partially transparent to illustrate the effect using a texture.
	04 – Use a texture with transparent alpha values to demonstrate the first layer of multiproperties is opaque. The second layer should also be partially transparent to illustrate the effect.
	05 – Use a multiproperties with 3 materials/colors, with the 2^{nd} and 3^{rd} layer being partially opaque. Demonstrate that the 1^{st} and 2^{nd} layer are opaque once merged together.
	06 - Use a texture that uses tilestyle of "none" with uv values great than 1 with a transparent object default color
	07 – Use a multiproperties with the first layer as basematerials and the second layer a transparent texture.
Requirement Reference	Link to Requirement in 3MF Specification couldn't find in any of the specs

6.5.5 **P_???_0505** Pindices List

Test Scenario Description	Demonstrate the behavior when too few or too many items are listed in the pindices list.
Pass/Fail Criteria	01 to 03 – Printer should process correctly
Test Case Iterations	 01 - In multiproperties have a pindices list that is one values shorter than the pids list. Demonstrate that an index value of zero is used for the omitted pindices value. For this test case have the omitted pids be colorgroup 02 - In multiproperties have a pindices list that is one value shorter than the pids list. Demonstrate that an index value of zero is used for the omitted pindices value. For this test case have the omitted pids be texture 03 - Demonstrate in multiproperties that if pindices includes one extra value greater that the number of pids values, the printer should ignore the extra value
Requirement Reference	Link to Requirement in 3MF Specification

6.5.6 P_???_0506 Multiple Material Colors and Groups

Test Scenario Description	Utilities define multiple groups of material colors and utilize multiple colors from
·	each group.
Pass/Fail Criteria	01 to 04 – Printer should process correctly
Test Case Iterations	 O1 – Define and utilize multiple colorgroup references on an object, using multiple indexed items from each colorgroup. Include in this scenario the following: -Select one triangle element and omit the P1, P2, and P3 attributes, but include the pid attribute. This will result in the default object pid and pindex being used for the triangles rendering -Select a triangle and omit the PID attribute, but include the P1, p2, and p3 attributes. This will result in the triangles p1, p2, and p3 attribute index values being mapped against the pid value at the object level for rendering. O2 – Define and utilize multiple texture2dgroup references on an object, using multiple indexed items from texture2dgroup O3 - Define and utilize multiple multiproperties references on an object, using more than one material/color in each multiprop1erty O4 – On the same object use one each of the following: Colorgroup, texture, and multiproperties
Requirement Reference	Link to Requirement in 3MF Specification no conformance id

6.5.7 **P_???_0507 Material Stress Tests**

Test Scenario Description	Large numbers of material color components in a test file
Pass/Fail Criteria	01 to 09 – Printer should process correctly
Test Case Iterations	01 – Use 120 texture2d images mapped to 120 texture2groups. Paint one object with each of the defined textures
	02 – Use 100,000 text2coord mappings on one object
	03 – Use more than 1,000 colorgroups each with one color. Paint one object with each of the defined colorgroups.
	04 – Use more than 1,000 colors in one colorgroup to paint an object
	05 – Define 120 multiproperties each with three multi sub elements and two pids values. Paint one object with each of the multiproperties.
	06 – Use 2,500+ multi sub element indices in one multiproperties with two pids values. Paint one object with each of the defined multiproperties values.

	 07 – A multiproperties listing 7 entries in pids and pindices. The same texture pids references can be interleaved. 08 - Extremely small text2coord values (at the level of a pixel) 09 - Extremely large text2coord values (such to cause 1000 tiles)
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.5.8 P_???_0508 Real World Textured Objects

Test Scenario Description	Paint textures on a variety of real world objects
Pass/Fail Criteria	01 to 14 – Printer should process correctly
Test Case Iterations	The following table listing specific textures from Appendix B to specific real world objects in Appendix A:
	01 - brmarble.jpg - N22_ChessHorse_high
	02 - droplets.png - M11_box_NA
	03 - grmarble.jpg - M12_Extruder_Bowden_Adapterc_low
	04 - oak.png - M11_Ventilated Build Platform_low
	05 - pitissue.jpg - M12_role_drum_NA
	06 - purmesh.png - N33_Duck_NA
	07 - quads.jpg - M12_SW_Extruder-Hinged-Block_high
	08 - photo_1.jpg - M11_stereographic_maze_lowres_NA
	09 - photo_1.png_16 - M12_Tristruder_18mm_Probe_Mount_high
	10 - photo_2.jpg - M21_flex_coupler_NA
	11 - photo_3.png - N32_alligator_228_low
	12 - photo_4.jpg - M22_FPV_Pod_Camera_Plate_NA
	13 - photo_5.jpg - M22_FPV_Pod_Half_NA
	14 - photo_6.png - N23_Deer_high
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.5.9 **P_???_0509** Positive Ordering

Test Scenario Description	Demonstrate that colorgroup, texture2group, and multiproperties can be interleaved in resources as long as there are no forward references
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – D efine model part with the following ordering of materials in the resources element: colorgroup, texture2d, texture2dgroup, multiproperties, texture2d, colorgroup, texture2dgroup, multiproperties, object. There should be no forward references and all materials should be referenced in an object's triangles.
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.5.10 **P_???_0510 Color Groups**

Test Scenario Description	Description
Pass/Fail Criteria	01 to 04 – Printer should process correctly
Test Case Iterations	01 - Define one colorgroup with 10 colors, use all colors on one object
	02 - Define two colorgroups, each with 10 colors. Interleave use of colors from the two different colorgroups on the same object's triangles
	03 - Define one colorgroup with 10 colors, use each color as the default color on a separate object
	04 - Define two colorgroups, each with 4 colors. Interleave use of colors from the two different colorgroups as the default color on separate objects
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.5.11 **P_???_0511** Color Values

Test Scenario Description	Demonstrate iterating through values for the color attribute of colorgroup
Pass/Fail Criteria	01 to 04 – Printer should process correctly
Test Case Iterations	01 - Iterate through all 256 red channel values displaying each value in a triangle in the same object while omitting the alpha channel (#XX0000)
	02 - Iterate through all 256 green channel values displaying each value in a triangle in the same object while omitting the alpha channel (#00XX00)
	03 - Iterate through all 256 blue channel values displaying each value in a triangle in the same object while omitting the alpha channel (#0000XX)
	04 - Iterate through all 256 RGB channel values concurrently with an opaque alpha channel value in a triangle in the same object (#XXXXXXFF)
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.5.12 **P_???_0512 Gradients**

Test Scenario Description	Demonstrate use various gradients using the standard gradient patterns defined in Appendix B
Pass/Fail Criteria	01 to 06 – Printer should process correctly
Test Case Iterations	 01 - Use Gradient_1, Gragient_2, and Gradient_3 using a color value that omits alpha (#XXXXXX) 02 - Use Gradient4, Gragient_5, and Gradient_6 using a color value that includes an opaque alpha (#XXXXXXFF) 03_Use Gradient_7, Gragient_8, and Gradient_9 using a color value that includes a 50% transparent alpha (#XXXXXX9F) as part of a multiproperties definition where texture is the first layer and partially transparent gradient in the second layer 04- Use a gradient as the 2nd layer in a multiproperties with a mixture of color values for p1, p2, and p3 that have no alpha channel (#XXXXXXX) and a partially transparent color value (#XXXXXX2f) 06 - Create gradient across all 6 sides of a cube such that the transition between triangles and faces of the cube appear seamless
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.5.13 **P_???_0513 Transparency**

Test Scenario Description	Use multiproperties to effect various alpha channel transparency behaviors
Pass/Fail Criteria	01 to 05 – Printer should process correctly
Test Case Iterations	 01 - Iterate through all 256 alpha channel values for color using a static RGB color for triangle attributes P1, P2, and P3 as the second layer of a multiproperties 02 - With a solid color as the first layer, use the alpha channel versions of the brmarble_A and droplets_A Small Texture Swatches (Appendix H) as the second layer in multiproperties 03 - With a Gradient_5 as the first layer, use the alpha channel versions of the grmarble_A and oak_A Small Texture Swatches (Appendix H) as the second layer in multiproperties 04 - With a brmarble.jpg texture as the first layer, use the alpha channel versions of the pitissue_A and purmesh_A Small Texture Swatches (Appendix H) as the second layer in multiproperties 05 - Multiproperties with second layer with tilestyle of "none" and UV values greater than 1 and a default color that is partially transparent.
Requirement Reference	Link to Requirement in 3MF Specification blank

6.5.14 **P_???_0514 Textures**

Demonstrate the use of textures in a variety of ways. These test cases use a variety of texture patterns defines in Appendix 8 Pass/Fail Criteria Test Case Iterations 01-Create a cube where each side of the cube uses one of the jpg versions of the Small Texture Swatches 02-Create a cube where each side of the cube uses one of the png versions of the Small Texture Swatches 03-Create a cube where each side of the cube alternates use of jpg and PNG images from the Small Texture Swatches 04 - Create objects that are painted completely with the photo_1 Large Texture Images. The test file should have 4 objects, each utilizing jpg and png forms of the Photo_1 Image. 05 - Create objects that are painted completely with the photo_2 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_2 Image. 06 - Create objects that are painted completely with the photo_3 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_3 Image. 07 - Create objects that are painted completely with the photo_4 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_4 Image. 08 - Create objects that are painted completely with the photo_5 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_6 Image. 09 - Create objects that are painted completely with the photo_5 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_6 Image. 10 - Define 7 texture2dgroups each using a different texture2d image from the Small Texture Swatches with alpha channel data. Use each texture2d group to paint at least 1 triangle on the same object 11 - Define 7 texture2dgroups each using a different texture2d image from the Small Texture Swatches with alpha channel data. Include each texture2d group as the second where p1, p2, and p3 point to the same coordinate on the texture. And a second where p1, p2, and p3 po	6.5.14 P_???_0514 Tex	
Test Case Iterations 01 to 12 – Printer should process correctly 01-Create a cube where each side of the cube uses one of the jpg versions of the Small Texture Swatches 02-Create a cube where each side of the cube uses one of the png versions of the Small Texture Swatches 03-Create a cube where each side of the cube uses one of the png versions of the Small Texture Swatches 04 - Create objects that are painted completely with the photo_1 Large Texture Images. The test file should have 4 objects, each utilizing jpg and png forms of the Photo_1 Image. 05 - Create objects that are painted completely with the photo_2 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_2 Image. 06 - Create objects that are painted completely with the photo_3 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_3 Image. 07 - Create objects that are painted completely with the photo_4 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_4 Image. 08 - Create objects that are painted completely with the photo_5 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_5 Image. 09 - Create objects that are painted completely with the photo_5 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_5 Image. 10 - Define 7 texture2dgroups each using a different texture2d image from the Small Texture Swatches without alpha channel data. Use each texture2d group to paint at least 1 triangle on the same object 11 - Define 7 texture2dgroups each using a different texture2d image from the Small Texture Swatches with out alpha channel data. Include each texture2d group as the second layer in a multiproperties, then paint at least 1 triangle on the same object with each multiproperties, then paint at least 1 triangle on the same object where p1, p2, and p3 point to the same coordinate to	Test Scenario Description	Demonstrate the use of textures in a variety of ways. These test cases use a variety
10Create a cube where each side of the cube uses one of the jpg versions of the Small Texture Swatches 102-Create a cube where each side of the cube uses one of the png versions of the Small Texture Swatches 103-Create a cube where each side of the cube alternates use of jpg and PNG images from the Small Texture Swatches 104 - Create objects that are painted completely with the photo_1 Large Texture Images. The test file should have 4 objects, each utilizing jpg and png forms of the Photo_1 Image. 105 - Create objects that are painted completely with the photo_2 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_2 Image. 106 - Create objects that are painted completely with the photo_3 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_3 Image. 107 - Create objects that are painted completely with the photo_4 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_4 Image. 108 - Create objects that are painted completely with the photo_5 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_5 Image. 109 - Create objects that are painted completely with the photo_6 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_5 Image. 109 - Create objects that are painted completely with the photo_6 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_5 Image. 109 - Create objects that are painted completely with the photo_6 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_5 Image. 109 - Create objects that are painted completely with the photo_6 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_5 Image. 109 - Create objects that are painted completely with the photo_6 Large Texture Images. The test file		
O2-Create a cube where each side of the cube uses one of the png versions of the Small Texture Swatches O3-Create a cube where each side of the cube alternates use of jpg and PNG images from the Small Texture Swatches O4 - Create objects that are painted completely with the photo_1 Large Texture Images. The test file should have 4 objects, each utilizing jpg and png forms of the Photo_1 Image. O5 - Create objects that are painted completely with the photo_2 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_2 Image. O6 - Create objects that are painted completely with the photo_3 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_3 Image. O7 - Create objects that are painted completely with the photo_4 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_4 Image. O8 - Create objects that are painted completely with the photo_5 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_5 Image. O9 - Create objects that are painted completely with the photo_5 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_6 Image. O9 - Create objects that are painted completely with the photo_6 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_6 Image. 10 - Define 7 texture2dgroups each using a different texture2d image from the Small Texture Swatches with alpha channel data. Use each texture2d group to paint at least 1 triangle on the same object 11 - Define 7 texture2dgroups each using a different texture2d image from the Small Texture Swatches with alpha channel data. Include each texture2d group as the second layer in a multiproperties, then paint at least 1 triangle on the same object with each multiproperties		
O3-Create a cube where each side of the cube alternates use of jpg and PNG images from the Small Texture Swatches O4 - Create objects that are painted completely with the photo_1 Large Texture Images. The test file should have 4 objects, each utilizing jpg and png forms of the Photo_1 Image. O5 - Create objects that are painted completely with the photo_2 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_2 Image. O6 - Create objects that are painted completely with the photo_3 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_3 Image. O7 - Create objects that are painted completely with the photo_4 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_4 Image. O8 - Create objects that are painted completely with the photo_5 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_5 Image. O9 - Create objects that are painted completely with the photo_6 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_6 Image. O9 - Create objects that are painted completely with the photo_6 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_6 Image. 10 - Define 7 texture2dgroups each using a different texture2d image from the Small Texture Swatches without alpha channel data. Use each texture2d group to paint at least 1 triangle on the same object 11 - Define 7 texture2dgroups each using a different texture2d image from the Small Texture Swatches with alpha channel data. Include each texture2d group as the second layer in a multiproperties, then paint at least 1 triangle on the same object with each multiproperties. 12 - Map a texture with no area to a triangle. Repeat twice for two different triangles. One where p2, and p3 point to the same coordinate on the texture. And a second where p1, p2, and p3 poin	Test Case Iterations	
from the Small Texture Swatches 04 - Create objects that are painted completely with the photo_1 Large Texture Images. The test file should have 4 objects, each utilizing jpg and png forms of the Photo_1 Image. 05 - Create objects that are painted completely with the photo_2 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_2 Image. 06 - Create objects that are painted completely with the photo_3 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_3 Image. 07 - Create objects that are painted completely with the photo_4 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_4 Image. 08 - Create objects that are painted completely with the photo_5 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_5 Image. 09 - Create objects that are painted completely with the photo_6 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_6 Image. 10 - Define 7 texture2dgroups each using a different texture2d image from the Small Texture Swatches without alpha channel data. Use each texture2d group to paint at least 1 triangle on the same object 11 - Define 7 texture2dgroups each using a different texture2d image from the Small Texture Swatches with alpha channel data. Include each texture2d group as the second layer in a multiproperties, then paint at least 1 triangle on the same object with each multiproperties, then paint at least 1 triangle on the same object with each multiproperties, then paint at least 1 triangle on the same object with each multiproperties. The paint at least 1 triangle on the same object with each multiproperties. The paint at least 1 triangle on the same object with each multiproperties.		
Images. The test file should have 4 objects, each utilizing jpg and png forms of the Photo_1 Image. 05 - Create objects that are painted completely with the photo_2 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_2 Image. 06 - Create objects that are painted completely with the photo_3 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_3 Image. 07 - Create objects that are painted completely with the photo_4 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_4 Image. 08 - Create objects that are painted completely with the photo_5 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_5 Image. 09 - Create objects that are painted completely with the photo_6 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_6 Image. 10 - Define 7 texture2dgroups each using a different texture2d image from the Small Texture Swatches without alpha channel data. Use each texture2d group to paint at least 1 triangle on the same object 11 - Define 7 texture2dgroups each using a different texture2d image from the Small Texture Swatches with alpha channel data. Include each texture2d group as the second layer in a multiproperties, then paint at least 1 triangle on the same object with each multiproperties, then paint at least 1 triangle on the same object with each multiproperties.		
Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_2 Image. 06 - Create objects that are painted completely with the photo_3 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_3 Image. 07 - Create objects that are painted completely with the photo_4 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_4 Image. 08 - Create objects that are painted completely with the photo_5 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_5 Image. 09 - Create objects that are painted completely with the photo_6 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_6 Image. 10 - Define 7 texture2dgroups each using a different texture2d image from the Small Texture Swatches without alpha channel data. Use each texture2d group to paint at least 1 triangle on the same object 11 - Define 7 texture2dgroups each using a different texture2d image from the Small Texture Swatches with alpha channel data. Include each texture2d group as the second layer in a multiproperties, then paint at least 1 triangle on the same object with each multiproperties.		Images. The test file should have 4 objects, each utilizing jpg and png forms of the
Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_3 Image. 07 - Create objects that are painted completely with the photo_4 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_4 Image. 08 - Create objects that are painted completely with the photo_5 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_5 Image. 09 - Create objects that are painted completely with the photo_6 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_6 Image. 10 - Define 7 texture2dgroups each using a different texture2d image from the Small Texture Swatches without alpha channel data. Use each texture2d group to paint at least 1 triangle on the same object 11 - Define 7 texture2dgroups each using a different texture2d image from the Small Texture Swatches with alpha channel data. Include each texture2d group as the second layer in a multiproperties, then paint at least 1 triangle on the same object with each multiproperties. 12 - Map a texture with no area to a triangle. Repeat twice for two different triangles. One where p2, and p3 point to the same coordinate on the texture. And a second where p1, p2, and p3 point to the same coordinate. Coordinate points used		Images. The test file should have 2 objects, each utilizing jpg and png forms of the
Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_4 Image. 08 - Create objects that are painted completely with the photo_5 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_5 Image. 09 - Create objects that are painted completely with the photo_6 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_6 Image. 10 - Define 7 texture2dgroups each using a different texture2d image from the Small Texture Swatches without alpha channel data. Use each texture2d group to paint at least 1 triangle on the same object 11 - Define 7 texture2dgroups each using a different texture2d image from the Small Texture Swatches with alpha channel data. Include each texture2d group as the second layer in a multiproperties, then paint at least 1 triangle on the same object with each multiproperties 12 - Map a texture with no area to a triangle. Repeat twice for two different triangles. One where p2, and p3 point to the same coordinate on the texture. And a second where p1, p2, and p3 point to the same coordinate. Coordinate points used		Images. The test file should have 2 objects, each utilizing jpg and png forms of the
Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_5 Image. 09 - Create objects that are painted completely with the photo_6 Large Texture Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_6 Image. 10 - Define 7 texture2dgroups each using a different texture2d image from the Small Texture Swatches without alpha channel data. Use each texture2d group to paint at least 1 triangle on the same object 11 - Define 7 texture2dgroups each using a different texture2d image from the Small Texture Swatches with alpha channel data. Include each texture2d group as the second layer in a multiproperties, then paint at least 1 triangle on the same object with each multiproperties 12 - Map a texture with no area to a triangle. Repeat twice for two different triangles. One where p2, and p3 point to the same coordinate on the texture. And a second where p1, p2, and p3 point to the same coordinate. Coordinate points used		Images. The test file should have 2 objects, each utilizing jpg and png forms of the
Images. The test file should have 2 objects, each utilizing jpg and png forms of the Photo_6 Image. 10 - Define 7 texture2dgroups each using a different texture2d image from the Small Texture Swatches without alpha channel data. Use each texture2d group to paint at least 1 triangle on the same object 11 - Define 7 texture2dgroups each using a different texture2d image from the Small Texture Swatches with alpha channel data. Include each texture2d group as the second layer in a multiproperties, then paint at least 1 triangle on the same object with each multiproperties 12 - Map a texture with no area to a triangle. Repeat twice for two different triangles. One where p2, and p3 point to the same coordinate on the texture. And a second where p1, p2, and p3 point to the same coordinate. Coordinate points used		Images. The test file should have 2 objects, each utilizing jpg and png forms of the
Small Texture Swatches without alpha channel data. Use each texture2d group to paint at least 1 triangle on the same object 11 - Define 7 texture2dgroups each using a different texture2d image from the Small Texture Swatches with alpha channel data. Include each texture2d group as the second layer in a multiproperties, then paint at least 1 triangle on the same object with each multiproperties 12 - Map a texture with no area to a triangle. Repeat twice for two different triangles. One where p2, and p3 point to the same coordinate on the texture. And a second where p1, p2, and p3 point to the same coordinate. Coordinate points used		Images. The test file should have 2 objects, each utilizing jpg and png forms of the
Small Texture Swatches with alpha channel data. Include each texture2d group as the second layer in a multiproperties, then paint at least 1 triangle on the same object with each multiproperties 12 – Map a texture with no area to a triangle. Repeat twice for two different triangles. One where p2, and p3 point to the same coordinate on the texture. And a second where p1, p2, and p3 point to the same coordinate. Coordinate points used		Small Texture Swatches without alpha channel data. Use each texture2d group to
triangles. One where p2, and p3 point to the same coordinate on the texture. And a second where p1, p2, and p3 point to the same coordinate. Coordinate points used		Small Texture Swatches with alpha channel data. Include each texture2d group as the second layer in a multiproperties, then paint at least 1 triangle on the same
		triangles. One where p2, and p3 point to the same coordinate on the texture. And a second where p1, p2, and p3 point to the same coordinate. Coordinate points used
Requirement Reference Link to Requirement in 3MF Specification N/A	Requirement Reference	Link to Requirement in 3MF Specification N/A

6.5.15 **P_???_0515 PNG Formats**

Test Scenario Description	Demonstrate each of the allowable basic png formats utilizing the Public Domain PngSuite shown in Appendix B
Pass/Fail Criteria	01 to 03 – Printer should process correctly
Test Case Iterations	 O1 - Positive - Use each of the png files defined in the Basic Format Public Domain PNG Suite (Appendix B) as a triangle texture on the same object O2 - Use each of the PNG files defined in the Public Domain PNG Suite (Appendix B) that have an alpha channel as the second layer of a multiproperties such that the alpha behavior of the png files is apparent. O3 - All png images in the public test suite, including basic format tests.
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.5.16 **P_???_0516** Multiproperties

Test Scenario Description	Demonstrate various combinations of colorgroup and texture as part of multiproperties. This test cases references a standard set of multiproperties combinations defined in Appendix B
Pass/Fail Criteria	01 to 08 – Printer should process correctly
Test Case Iterations	01 - Define Multiproperties_1 and _2, and use each of them to paint on triangle on an object
	02 - Define Multiproperties_3 and _4, and use each of them to paint on triangle on an object
	03 - Define Multiproperties_5 and _6, and use each of them to paint on triangle on an object
	04 - Define Multiproperties_7 and _8, and use each of them to paint on triangle on an object
	05 - Multiproperties with only one property defined in pids
	06 - Use the same texture multiple times in a pids/pindex reference in multiproperties
	07 - Demonstrate monochrome and color images with the default alpha channel blending using multiproperties
	08 - Demonstrate monochrome and color images using the multiply blend method using multiproperties
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.5.17 **P_???_0517 Texture2D**

6.5.1/ P_???_0517 Tex	
Test Scenario Description	Demonstrate various texture2D bounding box and tile style behaviors
Pass/Fail Criteria	01 to 35 – Printer should process correctly
Test Case Iterations	01 - Demonstrate that the default tilestyleu and tilestylev attribute default is wrap
	02 - Demonstrate that the default box attribute values are "0 0 1 1"
	04 - Specify the tilestyleu attributes without the box or tilestylev attribute using a non-default value for tilestyleu (mirror or clamp)
	05 - Specify the tilestylev attribute without the box or tilestyleu attribute using a non-default value for tilestylev (mirror or clamp)
	Note: Demonstrate various combinations of wrap, mirror, and clamp as part of color and image transparency. Default tex2coord greater than 1 to trigger tiling.
	08 - Texture: u=wrap v=wrap 09 - Texture: u=mirror v=mirror
	10 - Texture: u=clamp v=clamp
	11 - Texture: u=wrap v=mirror
	12 - Texture: u=mirror v=wrap
	13 - Texture: u=clamp v=wrap
	14 - Texture: u=wrap v=clamp
	15 - Texture: u=mirror v=clamp
	16 - Texture: u=clamp v=mirror
	20 – Demonstrate clamp, mirror and wrap behavior on separate triangles of the same object using the photo_4.jpg, photo_5.png, and photo_5.jpeg images respectively
	21 – Use negative text2cood values to texture a triangle with wrap and mirror. The origin tile will be flipped in both the u and v direction.
	22 – Use negative v text2cood values to texture a triangle using a clamp and mirror tilestyle.
	23 – Use wrap on all 6 sides of a cube
	24 – Use mirror on all 6 sides of a cube
	25 – Use clamp on all 6 sides of a cube
	26 – Use a texture with an alpha channel with a tilestyle of mirror.
	Note: Demonstrate various combination of a tilestyle of "none" with wrap, mirror, and clamp as part of color and image transparency. Default tex2coord greater than 1 to trigger tiling and a default object color unless specified otherwise
	27 - Texture: u=none v=none (negative uv to show all 4 sides)28 - Texture: u=none v=none, basematerials as object default color, negative uv to show all 4 sides of coordinate space

	29 - Texture: u=none v=wrap
	30 - Texture: u=wrap v=none
	31 – Texture: u=mirror v=none
	32 – Texture: u=none v=mirror
	33 – Texture: u=clamp v=none
	34 - Texture: u= none v=clamp
	35 – Tilestyle of "none' on all 6 sides of a cube
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.5.18 **P_???_0518 Texture2dGroup**

0.5.18 P_???_0518 Tex	-
Test Scenario Description	Demonstrate various mapping of text2coord attribute values of the texture2dgroup element
Pass/Fail Criteria	01 to 15 – Printer should process correctly
Test Case Iterations	01 - text2coord u v values between 0 and 1 mapped to vertices such that the image aspect ratio is maintained
	02 - text2coord u v values between 0 and .1 mapped to vertices such that the image aspect ratio is maintained
	03 - text2coord u v values between 5 and 10 mapped to vertices such that the image aspect ratio is maintained and tiling is triggered
	04 - text3coord u values such to create an obvious and exaggerated stretching of the image in the u axis
	05 - text3coord v values such to create an obvious and exaggerated stretching of the image in the v axis
	06 - text3coord u v values such to create an obvious and exaggerated stretching of the image in both the u v axis
	07 - text3coord u values such to create an obvious and exaggerated stretching of the image in both the u v axis as well as tiling of at least 3 instances of the image in a triangle
	08 - Use negative text2coord u and v values to map the texture to a triangle using the quad.jpg Small Texture Swatch with specified uv coordinate where the distance between vertex points is not greater than 1 (no tiling). Device UV coordinates: once with just u negative, once with just v negative, and once with both u and v negative. Use all the coordinates to map a texture to a single triangle.
	09 - use negative text2coord u and v values to map the texture to triangles using the oakNumbers.png Small Texture Swatch with UV coordinate values between -1 and -3 (tiling). Use all the coordinates to map a texture to a single triangle.
	10 – Repeat test case 09 with a tilestyle of mirror for u and v
	11 - Repeat test case 09 with a tilestyle of clamp for u and v

	 12 - Texture with mapped uv values all greater than 1. 13 - Repeat test case 08 with tilestyle of "none" 14 - Repeat test case 09 with tilestyle of "none" 15 - Repeat test case 12 with tilestyle of "none"
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.5.19 **P_???_0519 "e" Notation**

Test Scenario Description	Demonstrate the use of e notation rather than decimal values in one location to conform that implementation can handle that representation of a float
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – Demonstrate the use of e notation with negative values on mesh vertex coordinate.
Requirement Reference	Link to Requirement in 3MF Specification N/E

6.5.20 P_???_0520 Overlapping Material Colors

Test Scenario Description	Demonstrate that the last voxel rendered takes precedence when two objects overlap in a coplanar fashion.
Pass/Fail Criteria	01 to 03 – Last color of last coplanar object rendered should have precedence
Test Case Iterations	01 - 2 objects overlapping with gradient and textured surfaces coplanar both referenced from build items
	02 - 2 cubes defined in same object mesh with overlapping gradient and textured surfaces coplanar (Note in Thumbnail master that the result may be device dependent where two layers are coplanar), although rules state that the last overlapping triangle rendered should have precedence.
	03 - 2 cubes defined in separate objects with overlapping gradient and textured surfaces coplanar with each object referenced from components in the same object, with a single build item referenced to the assembly
Requirement Reference	Link to Requirement in 3MF Specification

6.5.21 **P_???_0521** Units of Measure

Test Scenario Description	Demonstrate that units of measure declared in the model units attribute does not impact the appearance of textures.
Pass/Fail Criteria	01– Printer should process correctly
Test Case Iterations	01 - Display textured object (photo_4.jpg) in the same OPC package multiple times using separate model files, with each model file containing a different unit attribute value. Use the default (no units - millimeter), inch, and centimeters. Objects should be generated such that the object vertex values are the native units of measure with the object being the same size without the need for transform scaling.
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.5.22 **P_???_0522 Transform Impact**

Test Scenario Description	Illustrate the impact that transforms have on texture and gradient patterns. These		
	test cases use the predefined gradients and textures defined in Appendix B.		
Pass/Fail Criteria	01 to 02 – Printer should process correctly		
Test Case Iterations	 O1 - Create an object with both gradient_5 and texture quads.jpg. Reference the same object from 4 build items, with each reference using a different transform matrix scaling O2 - Create an object with both gradient_5 and texture quads.jpg. Reference the same object from one object with 4 component references, with each component reference using a different transform matrix for scaling and positioning. 		
Requirement Reference	Link to Requirement in 3MF Specification N/A		

6.5.23 P_???_0523 OPC Package Location

Test Scenario Description	Define objects with Colorgroups, textures, and multipropertiescan in different locations in the OPC package. Each object should utilize a solid color from colorgroups, a gradient from colorgroups, a texture, and multiproperties that uses both colorgroup as a base layer and a texture with an alpha channel.
Pass/Fail Criteria	01 to 04 – Printer should process correctly
Test Case Iterations	 01 - Root and non-root model parts in same package 02 - non-root model parts only, referenced by root build item 03 - non-root model parts only, referenced by component
Requirement Reference	 04 – Use tilestyle combinations of wrap, mirror, clamp, and none on various sides of a single cube that whose object is in a non root model. Link to Requirement in 3MF Specification N/A

6.5.24

6.5.25 P_???_0524 Whitespace in Delimited Values

Test Scenario Description	Use multiple tab, space, CR, LF characters between space delimited attributes. The schema validation
Pass/Fail Criteria	01 to 02 – Printer should process correctly
Test Case Iterations	For each of the space delimited attributes noted in the test cases below, include multiple space characters, tab CR, and LF in one set of space delimited values. O1 – Include multiple whitespace characters in the following attributes: pids and pindices. O2 - Include multiple whitespace values in both a build item and component transform matrix.
Requirement Reference	Link to Requirement in 3MF Specification

6.5.26 **P_???_0525 Permutations of Layers**

Test Scenario Description	Iterate through a set of test cases, each using a unique combination of materials, alpha data, padding, tiling, gradients, and other characteristics. This is not intended to be an exhaustive list, but rather a reasonable sampling of the possibilities. Basic combinations of layers to include: • colorgroup + texture • texture + color group • colorgroup + texture + texture • texture + colorgroup + texture
Pass/Fail Criteria	01 to 59 – Printer should process correctly
Test Case Iterations	The table on the following page details each test case and the layer characteristics using the following legend: CG = Colorgroup TX = Texture MP = Multiproperties OP = Opaque TR = Transparent SC = Solid Color GC = Gradient Color GA = Gradient Alpha WR = Wrapped (presumes tex2coord uv > 1) MR = Mirrored (presumes tex2coord uv > 1) CL = Clamped (presumes tex2coord uv > 1) NO = None (presumes tex2coord uv > 1) - One or both tilestyles as none
Requirement Reference	Link to Requirement in 3MF Specification N/A

Test Iteration	Object Default	Layer 1	Layer 2	Layer 3
01	CG	CG SC OP	TX_TR	
02	CG	CG_SC_TR	TX TR WR	
03	CG	CG_GC_OP	TX_TR_MR	
04	CG	CG_SC_OP	TX_TR_CL	
05	Deleted			
06	MP	CG_SC_TR	TX TR	
07	TX	CG_GC_OP	TX_TR_WR	
08	CG	CG_SC_TR	TX_TR_MR	
09	MP	CG_GC_OP	TX_TR_CL	
10	TX	CG_SC_OP	TX_OP	
11	TX	CG_SC_TR	TX_OP_WR	
12	CG	TX_OP	CG_SC_TR	
13	CG	TX_TR	CG_SC_TR	
14	CG	TX_OP_WR	CG_GC_TR	
15	CG	TX_OP_MR	CG_SC_GA	
16	CG	TX_OP_CL	CG_GC_GA	
17	CG	TX_OP	CG_SC_TR	
18	MP	TX_OP_WR	CG_GC_TR	
19	TX	TX OP MR CG SC GA		
20	CG	TX OP CL	CG GC GA	
21	CG	CG_SC_OP	TX_TR	TX_TR_MR
22	CG	CG_SC_TR	TX_TR_WR	TX TR MR
23	CG	CG GC OP	TX TR MR	TX TR WR
24	CG	CG_SC_OP	TX_TR_CL	TX_TR
25	MP	CG_SC_TR	TX_TR	TX_TR_CL
26	TX	CG_GC_OP	TX_TR_WR	TX_TR
27	CG	CG_SC_TR	TX_TR_MR	TX_TR_CL
28	MP	CG_GC_OP	TX_TR_CL	TX_TR_MR
29	TX	CG_SC_OP	TX_OP	TX_TR_WR
30	TX	CG_SC_TR	TX_OP_WR	TX TR
31	CG	TX_TR	CG_SC_TR	TX_TR_MR
32	CG	TX_OP_WR	CG_GC_TR	TX_TR_WR
33	CG	TX_OP_MR	CG_SC_GA	TX_TR
34	CG	TX_OP_CL	CG_GC_GA	TX_TR_CL
35	CG	TX_OP	CG_SC_TR	TX_TR_MR
36	MP	TX_OP_WR	CG_GC_TR	TX_TR_CL
37	TX	TX_OP_MR	CG_SC_GA	TX_TR_MR
38	CG	TX_OP_CL	CG_GC_GA	TX_TR_WR
39	CG	TX_TR	TX_OP_MR	
40	CG	TX_TR_WR	TX_TR_CL	
41	CG	CG_SC_TR TX_TR_NO_OP		
42	TX	CG_GC_OP TX_TR_NO_TR		
43	TX	CG_SC_TR	TX_OP_NO_TR	

44	CG	CG_SC_TR	TX_TR_NO_OP	
45	CG	TX_OP_NO_OP	CG_GC_TR	
46	MP	TX_OP_NO_TR	CG_GC_TR	
47	CG	CG_SC_TR	TX_TR_NO_TR	TX_TR_MR
48	CG	CG_GC_OP	TX_TR_MR	TX_TR_NO_TR
49	TX	CG_GC_OP	TX_TR_NO_TR	TX_TR
50	basematerials	CG_SC_OP	TX_TR_NO (no default)	TX_TR_NO(no default)
51	TX	CG_SC_TR	TX_OP_NO_TR	TX_TR
52	CG	TX_OP_NO_TR	CG_GC_TR	TX_TR_NO_TR
53	basematerials	TX_OP_NO (no default)	P_NO (no default)	
54	CG	TX_OP_CL	CG_GC_GA	TX_TR_NO_TR
55	CG	CG_GC_OP	TX_TR_WR	TX_TR_NO_TR
56	CG	basematerials	TX_TR_NO	TX_TR_NO (Mix Blend)
57	CG	basematerials	TX_TR_NO	TX_TR_NO (Mult Blend
58	CG	basematerials	TX_TR_NO	CG_GC_TR (Mix Blend)
59	CG	basematerials	CG_GC_TR	TX_TR_NO (Mult Blend)

6.5.27 **P_???_0526 Filters**

Test Scenario Description	Test the various valid enumerations for the texture2d elements filter attribute
Pass/Fail Criteria	01 to 09 – Printer should process correctly
Test Case Iterations	Use the table below to render adjacent triangles using various filter and scaling combinations. The image selected and the scaling factors should be selected to make the interpolation method used as obvious as possible. Each test iteration has two scenarios with each presented on the upper or lower horizontal surface of a rectangular object. Most test cases will use a jpg image.
Requirement Reference	Link to Requirement in 3MF Specification

Iteration	TextureGroup	Multi	Downscale	Upscale	No Filter Attribute	Auto	Linear	Nearest
01	X (B)			Х	Х			
	X (T)			Х		Х		
02	X (B)			Х		Х		
	X (T)			Х			Х	
03	X (B)			Х		Х		
	X (T)			Х				Х
04	X (B)			Х			Х	
	X (T)			Х				Х
05	X (B)		Х		Х			
	X (T)		Х			Х		
06	X (B)		Х				Х	
	X (T)		Х					Х
07		X (B)	Х				Х	
		X (T)		Х				Х
08		X (B)		Х		Х		
		X (T)		Х		•	Х	
09	Х	Х	Х	Х	Х	Х	Х	Х
(1)		•		•		•		

¹⁾A single object that uses a variety of filter configurations using png images

6.5.28 **P_???_0529 Display Properties**

Test Scenario Description	Include an example of each supported display property. The printer should ignore the display property and render the mesh without influence from the display			
	property values.			
Pass/Fail Criteria	01– 05 Printer should process correctly			
Test Case Iterations	01 – colorGroup displaypropertyid mapped to pbspeculardisplayproperties			
	02 – colorGroup displaypropertyid mapped to pbmetallicdisplayproperties			
	03 – texture2dgroup displaypropertyid mapped to			
	pbmetallictexturedisplayproperties			
	04 – texture2dgroup displaypropertyid mapped to pbspeculartexturedisplayproperties			
	05 – basematerials displaypropertyid mapped to translucentdisplayproperties			
	06 - basematerials displaypropertyid mapped to translucentdisplayproperties with multiproperties "stamp" over transparacy.			
Requirement Reference	Link to Requirement in 3MF Specification TBD			

6.5.29 P_???_0530 Blend Method

Test Scenario Description	Exercise blendmethods in a variety of permutations of colorgroup, texture, any tylestyle enumerations. Note that the default "mix" behavior is tested extensively elsewhere, so the focus of this testing will be on the use of multiply either independently or in combination with mix.
Pass/Fail Criteria	01 to 08–Printer should process correctly
Test Case Iterations	See tables below.
Requirement Reference	Link to Requirement in 3MF Specification TBD

Characteristics combinations uses in test case definitions below.

ID	Blend Method When ID used as layer 2 or above		Solid	Gradient	Texture	Wrap	Mirror	Clamp	None
	When ID used as	layer 2 or above	Color	Color					
	Mix With layer below	Multiply With layer below							
Α	х		х						
В	х			Х					
С		Х	Х						
D		Х		Х					
E	х				Х	Х			
F	х				Х		Х		
G	х				Х			Х	
Н	х				Х				Х
ı		X			Х	Х			
J		X			Х		Х		
K		X			Х			Х	
L		X			х				х

Test	Layer 1	Layer 2	Layer 3	Comment
Iteration				
01	1	С		Multiply solid color with texture
02	В	J		Multiply texture with gradient color
03	K	Α	L	Mix solid color with texture, then multiply texture
04	В	L	I	Multiply texture with gradient, multiply texture
05	J	Α	K	Mix solid color with texture, multiply texture
06	L	D	Н	Multiply gradient with texture, then Mix texture
07	Base	J	I	basematerials as 1 st layer. Multiply texture with texture
08	Α	K	L	Multiply texture with solid color, multiply texture
				basematerials as default object color
09	Α	Α		Test case to illustrate impact of not converting to linear RBG
		Red		space prior to alpha blending. If the render to not covert to
		50% alpha		linear space the image will darker in general.

6.6 Negative Material Extension Test Cases

6.6.1 **N_???_0601** No Default Color

Test Scenario Description	Define a material color on a triangle without the required default material color specified on the object
Pass/Fail Criteria	01 to 02 – Printer should generate an error
Test Case Iterations	O1 – Triangle with material color, root model object with no default material color O2 – Triangle with material color, non- root model object with no default material color
Requirement Reference	Link to Requirement in 3MF Specification

6.6.2 **N_???_0602 Duplicate IDs**

Test Scenario Description	Duplicate material color IDs in model file.
Pass/Fail Criteria	01 to 04 – Printer should generate an error
Test Case Iterations	01 – Duplicate colorgroup ID attribute values
	02 – Duplicate texture2dgroup ID attribute values
	03 – Duplicate texture2d ID attribute values
	04 – Duplicate multiproperties ID attribute values
Requirement Reference	Link to Requirement in 3MF Specification

6.6.3 N_???_0604 Multiproperties pids References

Test Scenario Description	Verify that the printer rejects multiple colorgroup references multiproperties and ignores the use of another multiproperties as part of a multiproperties pids reference							
Pass/Fail Criteria	01 to 03 – Printer should generate an error							
Test Case Iterations	01 – Include two colorgroup references in multiproperties pids							
	02 — Include references to another multiproperties group in multiproperties pids							
	03 – basematerials as layer 2 of multiproperties							
	reference 01 to 03 – Printer should generate an error 01 – Include two colorgroup references in multiproperties pids 02 – Include references to another multiproperties group in multiproperties pid 03 – basematerials as layer 2 of multiproperties 03 – Basematerials as bot layer 1 and 2 of multiproperies							
Requirement Reference	Link to Requirement in 3MF Specification Could not find							

6.6.4

6.6.5 N_???_0605 Invalid Texture Relationship Mapping

Test Scenario Description	Description
Pass/Fail Criteria	01 to 02 – Printer should generate an error
Test Case Iterations	 O1 – Define a texture relationship in a .rels file that uses in incorrect type (use a "model" relationship type) in a test file that uses a texture O2 – Omit a relationship in .rels to a texture file used in a test case
Requirement Reference	Link to Requirement in 3MF Specification

6.6.6 N_???_0606 Material Forward Reference

Test Scenario Description	Define forward references for material color resources where a prerequisite component has not yet been defined when referenced.
Pass/Fail Criteria	01 to 03 – Printer should generate an error
Test Case Iterations	01 - Texture2dgroup in resources before referenced texture2d
	02 - Multiproperties in resources before referenced texture2dgroup
	03 - Multiproperties in resources before referenced colorgroup
Requirement Reference	Link to Requirement in 3MF Specification could not find

6.6.7 **N_???_0607 Out of Order Resources**

element: colorgroup, texture2d, texture2dgroup, multiproperties, object (This invalid), texture2d, colorgroup, texture2dgroup, multiproperties, object. There	
Test Case Iterations	•
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.6.8

6.6.9 **N_???_0608 Out of Range Color**

Test Scenario Description	Use invalid color value
Pass/Fail Criteria	01 – Printer should generate an error
Test Case Iterations	01 – Use a value outside hex range in color (#FFHFFF) for a color defined in a colorgroup
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.6.10 N_???_0609 Incorrect Material IDs and Indexes

Test Scenario Description	Demonstrate various incorrect ID references
Pass/Fail Criteria	01 to 11 – Printer should generate an error
Test Case Iterations	 01 - Incorrect multiproperties pids reference 02 - Incorrect texture2dgroup reference to texture2d (textid) 03 - Incorrect (max+1) index to color in multiproperties(pindices) 04 - Incorrect (max+1) index to texture in multiproperties (pindices) 05 - Incorrect (max+1) triangle p1 index to a colorgroup 06 - Incorrect (max+1) triangle p2 index to a texture 07 - Incorrect (max+1) triangle p3 index to a multiproperties 08 - Incorrect (max+1) object pindex index to a colorgroup 09 - Incorrect (max+1) object pindex index to a texture 10 - Incorrect (max+1) object pindex index to multiproperties 11 - Incorrect object pid reference
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.6.11 N_???_0610 Misc Path and ContentType

	7.
Test Scenario Description	Miscellaneous invalid values
Pass/Fail Criteria	01 to 03 – Printer should generate an error
Test Case Iterations	01 – invalid path to texture file from texture2d
	02 –Invalid texture2d ContentType attribute value (other than image/jpeg or image/png)
	03 –Invalid [content_Types].xml ContentType attribute value (other than image/jpeg or image/png)
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.7 Positive Production Extension Test Cases

The table below maps the possible permutations of parts and XML objects required to traverse from the StartPart object to the slices. Each set of relationships is defined by a letter, with the green highlight showing the target of the relationship. Test cases will be defined by listing a sequence of relationship letters together, such as "A, F, R, J". This table will be used to define test cases in subsequent sections.

Table 1.1

Relationships																								
Root Model Build Item –	Α	В	С													Q	R						\exists	
objectid Only (local)																								
Root Model Build Item –				D	Ε													S						
objectid + Path (remote)																								
Root Model Object – w/o slicestackid Attr	Α					F																	\dashv	
Component -> objectid of local mesh object																								
Root Model Object – w/o slicestackid Attr Component -> remote objectid + path of remote mesh object		В					G	Н																
Root Model Object – with slicestackid Attr Component -> objectid of local mesh object																Q			T	U				
Root Model Object – with slicestackid Attr																	R						Х	Υ
Component -> remote objectid + path of																	1						$ \hat{\ } $	
remote mesh object																								
						_				_														
Root Model Object – with slicestackid Attr Local mesh			С			F			ı	J														
Root Model Object – w/o slicestackid Attr																			Т					
Local mesh																								
Root Model Slice Stack –									ı														\exists	Y
Local Slices (ID)																								
Root Model Slice Stack –										J	Κ													
Remote Sliceref (slicestackid + slicepath)																								
Non-Root Model Object – w/o slicestackid				D			G					M												
Component -> objectid of local mesh object																								
Non-Root Model Object – with slicestackid																		S			٧	W		
Component -> objectid of local mesh object																								
Non-Root Model Object – with slicestackid					Е			Н				M	N	0									\dashv	
Local mesh																								
Non-Root Model Object – w/o slicestackid Local mesh																					V		Χ	
Non-Root Model Slice Stack – Local Slices (ID)											K		N							U		W		
Non-Root Model Slice Stack –														0	Р								\dashv	_
Remote Sliceref (slicestackid + slicepath)																								
Another Non-Root Model Slice Stack – Local Slices (ID)															Р									

6.7.1 **PP_701 Object and Slice Mapping**

Test Scenario Description	Construct sliced 3MF test files that iterate through the possible mapping relationships between Build Items, Objects, Components, and Slice Stacks. This will require slicing a number of individual 3MF files, then concatenating the data together in a single 3MF file.
Conformance Statement ID(s)	Prod-O1.3, Slice-M1.17, Slice-O1.1, Slice-O1.2, Prod-O1.2
Base Test Object(s)	S11_cube_NA.3mf S11_octahedron_NA.3mf S11_hex_pyramid_NA.3mf S12_cylinder_low.3mf
Pass/Fail Criteria	01 to 14 – Printer should process correctly
Test Case Iterations	01 – Create a 3MF file with relationships "A, F, I" from table 1.1
	02 – Create a 3MF file with relationships "A, F, J, K" from table 1.1
	03 – Deleted
	04 – Create a 3MF file with relationships "B, G, M, N" from table 1.1
	05 – Create a 3MF file with relationships "B, G, M, O, P" from table 1.1
	06 – Create a 3MF file with relationships "B, H, N" from table 1.1
	07 – Create a 3MF file with relationships "B, H, O, P" from table 1.1
	08 – Create a 3MF file with relationships "C, I" from table 1.1
	09 – Create a 3MF file with relationships "C, J, K" from table 1.1
	10 – Deleted
	11 – Create a 3MF file with relationships "D, M, N" from table 1.1
	12 – Create a 3MF file with relationships "D, M, O, P" from table 1.1
	13 – Create a 3MF file with relationships "E, N" from table 1.1
	14 – Create a 3MF file with relationships "E, O, P" from table 1.1
Requirement Reference	Link to Requirement in 3MF Specification

The table below maps the possible permutations of parts and XML objects required to traverse from the StartPart object to various mesh representations in the OPC file. Each set of relationships is defined by a letter, with the green highlight showing the target of the relationship. Test cases will be defined by listing a sequence of relationship letters together, such as "A, F, R, J". This table will be used to define test cases in subsequent sections.

Table 1.2

Relationships									
Root Model Build Item –	Α	В	С						
objectid Only (local)									
Root Model Build Item –				D	Ε				
objectid + Path (remote)									
Root Model Object –	Α					F			
Component -> objectid of local mesh object									
Root Model Object –		В					G	Н	
Component -> remote objectid + path of remote mesh object									
Root Model Object –			С			F			
Local mesh									
Non-Root Model Object -				D			G		М
Component -> objectid of local mesh object									
Non-Root Model Object –					Е			Н	М
Local mesh									

6.7.2 **P_???_0702 Object Mapping**

Test Scenario Description	Construct 3MF test files that iterate through the possible mapping relationships between Build Items, Objects, and Components.
Pass/Fail Criteria	01 to 06 – Printer should process correctly
Test Case Iterations	01 – Create a 3MF file with relationships "A, F" from table 1.2
	(root build item -> root object w/component -> root object w/mesh)
	02 – Create a 3MF file with relationships "B, G, M" from table 1.2
	(root build item -> root object w/component -> non-root object w/component -> non-root object w/mesh)
	03 – Create a 3MF file with relationships "B, H from table 1.2
	(root build item -> root object w/component -> non-root object w/mesh)
	04 – Create a 3MF file with relationships "C" from table 1.2 (root build item -> root object w/mesh)
	05 – Create a 3MF file with relationships "D, M" from table 1.2
	(root build item -> non-root object w/component -> non-root object w/mesh)
	06 – Create a 3MF file with relationships "E" from table 1.2
	(root build item -> non-root object w/mesh)
Requirement Reference	Link to Requirement in 3MF Specification

6.7.3 **P_???_0703 Object Mapping 2**

6.7.3 P_???_0703 Obje	•
Test Scenario Description	Construct 3MF test files that iterate through the possible mapping relationships between Build Items, Objects, and Components.
Pass/Fail Criteria	01 to 12 – Printer should process correctly
Test Case Iterations	01 – Create a 3MF file with two build items which point directly to root part mesh objects. Modify build item transform so they don't overlap.
	02 – Create a 3MF file with two build items which point at two objects that define components, which in turn point at locally defined mesh objects. Modify build item transform so they don't overlap.
	03 – Create a 3MF file with two build items which point at two objects that define components, which in turn point at remote parts with mesh objects and via the component path element. Modify build item transform so they don't overlap.
	04 – Create a 3MF file with build items including one each of the following objects: Local mesh, local mesh via Object component, remote mesh via Object component. Modify build item transform so they don't overlap.
	05 – Create 3MF file with two build items pointed at the same local mesh object. Modify build item transform so they don't overlap.
	06 – Create a 3MF file with two build items pointed to the same remote part mesh object, modify build item transform so they don't overlap.
	07 – Create a 3MF file with an object with two components that contain objectid references to two local root part mesh objects. Modify component so they don't overlap.
	08 – Create a 3MF file with an object that points to another object with two components that contain objectid references to locally defined mesh objects. Modify component transform so they don't overlap.
	09 – Create a 3MF file with an object with two components which point at remote parts with mesh objects via the component path element. Modify component transform so they don't overlap.
	10 – Create a 3MF file with an object with three components that includes one each of the following objects: Local mesh, local mesh via another Object component, remote mesh via path. Modify component transform so they don't overlap.
	11 – Create 3MF file with an object with two components pointed at the same local mesh object. Modify build item transform so they don't overlap.
	12 – Create a 3MF file with an object with two components pointed to the same remote part mesh object via path. Modify build item transform so they don't overlap. Include model level metadata in non-root model file.
Requirement Reference	Link to Requirement in 3MF Specification could not find

6.7.4 PP_704 Object and Slice Mapping

Test Scenario Description	Construct sliced 3MF test files that iterate through the possible mapping relationships between Build Items, Objects, Components, and Slice Stacks. This will require slicing a number of individual 3MF files, the concatenating the data together in a single 3MF file.
Conformance Statement ID(s)	Prod-O1.3, Slice-M1.17, Slice-O1.1, Slice-O1.2, Prod-O1.2
Base Test Object(s)	S11_cube_NA.3mf S11_octahedron_NA.3mf S11_hex_pyramid_NA.3mf S12_cylinder_low.3mf
Pass/Fail Criteria	01 to 04 – Printer should process correctly
Test Case Iterations	 O1 – Create a 3MF file with a slicestack that contains two Sliceref slicepath objects pointing to remote slice stacks. The composite of the slice stacks should comprise one object. The following test cases define the slicestackID in an object with component references. The downstream 3D objectID references will not contain a slicestackID. Note that the letters in parenthesis indicate that there is a reference from the object to both the slicestack and the 3D mesh object. O2– Create a 3MF file with relationships "Q, (TU)" from table 1.1 O3 – Create a 3MF file with relationships "R, (XY)" from table 1.1 O4 – Create a 3MF file with relationships "S, (VW)" from table 1.1
Requirement Reference	<u>Link to Requirement in 3MF Specification</u>

6.7.5 P_???_0705 Duplicates of Separate Parts

Test Scenario Description	Multiple part build using production extensions
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – A test case that use 3 different mesh objects defined in separate parts to build 30 objects, 10 of each via build item element on the build platform. Objects should be positioned both adjacent in XY space, and Stacked in the Z space.
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.7.6 P_???_0706 Build Item Non-Root Model

Test Scenario Description	Build item in a non-root model file
Pass/Fail Criteria	01 – Printer should ignore
Test Case Iterations	01 – File with a build item in a non-root model file. Printer should ignore.
Requirement Reference	Link to Requirement in 3MF Specification

6.8 Negative Production Extension Test Cases

6.8.1 N_???_0801 Incorrect Mapping of IDs and Paths

Test Scenario Description	Construct 3MF test files that have incorrect mapping relationships between Build Items, Objects, and Components. The files generated in test case P_???_0701_01 through P_???_0701_18 will be used as a resource for these test cases. Test case developers can select a test case from this group that has the targeted mapping modified as defined below.
Pass/Fail Criteria	01 to 09 – Printer should generate an error
Test Case Iterations	01 – Modify existing test case to create an incorrect objectid mapping using relationship "A" defined in table 1.2 in section 5.7
	02 – Modify existing test case to create an incorrect objectid mapping using relationship "E" defined in table 1.2 in section 5.7
	03 – Modify existing test case to create an incorrect path mapping using relationship "E" defined in table 1.2 in section 5.7
	04 – Modify existing test case to create an incorrect objectid mapping using relationship "F" defined in table 1.2 in section 5.7
	05 – Modify existing test case to create an incorrect objectid mapping using relationship "H" defined in table 1.2 in section 5.7
	06 – Modify existing test case to create an incorrect path mapping using relationship "H" defined in table 1.2 in section 5.7
	07 – Modify existing test case to create an incorrect slicestackid mapping using relationship "I" defined in table 1.1 in section 5.7
	08 – Modify existing test case to create an incorrect slicestackid mapping using relationship "K" defined in table 1.1 in section 5.7
	09 – Modify existing test case to create an incorrect slicepath mapping using relationship "K" defined in table 1.1 in section 5.7
Requirement Reference	Link to Requirement in 3MF Specification could not find

6.8.2 **N_???_0802 UUIDs**

Test Scenario Description	Create a 3MF document file with missing UUID values or duplicate UUIDs.
Pass/Fail Criteria	01 to 05 – Printer should generate an error
Test Case Iterations	01 – Missing UUID in Build item
	02 – Missing UUID in object with local mesh
	03 – Missing UUID in component
	04 – Duplicate UUID between two objects
	05 – Missing UUID in Build element
Requirement Reference	Link to Requirement in 3MF Specification

6.8.3 N_???_0803 Restricted Mappings

Test Scenario Description	The conformance rules restrict the use of path on the component element of non-root model parts.
Pass/Fail Criteria	01– Printer should generate an error
Test Case Iterations	01 – Create a 3MF file that contains three 3D model parts. The root model has an object component reference to the second, and the second has an object component reference to the third.
Requirement Reference	Link to Requirement in 3MF Specification

6.9 Miscellaneous 3MF Test Cases

6.9.1 **P_???_0901** Test Synthetic Low Res

Test Scenario Description	Generate 3MF files for each of the Synthetic low res and NA Test objects defined in Appendix A
Pass/Fail Criteria	01 to 12 – Printer should process correctly
Test Case Iterations	01 – S11_Cube
	02 – S11_Cube_Fillet_Low
	03 – S11_Dodecahedron_NA
	04 – S11_Hex_Pyramid_NA
	05 – S11_Octahedron_NA
	06 – S11_Pentagon_Prism_NA
	07 – S11_Rectangle_Pyramid_NA
	08 – S11_Cone_Low
	09 – S11_Cylinder_Low
	10 – S11_Ellipsoid_Low
	11 – S12_Sphere_Low
	12 – S12_Torus_Low
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.9.2 **P_???_0902** Synthetic High Res

Test Scenario Description	Generate 3MF files for each of the Synthetic high res Test objects defined in Appendix A
	N/A
Pass/Fail Criteria	01 to 06 – Printer should process correctly
Test Case Iterations	01 – S11_Cube_Fillet_High
	02 – S12_Cone_High
	03 – S12_Cylinder_High
	04 – S12_Ellipsoid_High
	05 – S12_Sphere_High
	06 – S12_Torus_High
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.9.3 P_???_0903 Natural Low Res and NA

Test Scenario Description	Generate 3MF files for each of the Natural low res and NA Test objects defined in Appendix A
Pass/Fail Criteria	01 to 06 – Printer should process correctly
Test Case Iterations	01 – N22_ChessHorse_Low 02 – N23_Deer_Low 03 – N32_Alligator_228_Low 04 – N32_Shell_Low 06- N33_Duck_NA
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.9.4 **P_???_0904** Natural High Res

Test Scenario Description	Generate 3MF files for each of the Natural high res Test objects defined in Appendix A
Pass/Fail Criteria	01 to 04 – Printer should process correctly
Test Case Iterations	01 – N22_ChessHorse_High 02 – N23_Deer_High 03 – N32_Alligator_228_High 04 – N32_Shell_High
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.9.5 **P_???_0905** Real World Low Res and NA

Test Scenario Description	Generate 3MF files for each of the Real World low res and NA Test objects defined in Appendix A
Pass/Fail Criteria	01 to 13 – Printer should process correctly
Test Case Iterations	01 – M11_Box_NA
	02 – M11_Snorkel_Low
	03 – M11_Stereographic_Maze_Low
	04 – M11_Ventilated Build Platform_low
	05 – M12_Extruder_Bowden_Adapterc_low
	06 – M12_role_drum_NA
	07 – M12_SW_Extruder-Hinged-Block_low
	08 – M12_Tristruder_18mm_Probe_MouN_???_Olow
	09 – M21_flex_coupler_NA
	10 – M21_headphone_rest_low
	12 – M21_stereographic_flat_math2_low
	13 – M22_FPV_Pod_Half_NA
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.9.6 **P_???_0906** Real World High Res

Test Scenario Description	Generate 3MF files for each of the Real World high res Test objects defined in Appendix A
Pass/Fail Criteria	01 to 06 – Printer should process correctly
Test Case Iterations	01 - M11_Snorkle_high 02 - M11_Ventilated Build Platform_high 03 - M12_Extruder_Bowden_Adapterc_high 04 - M12_SW_Extruder-Hinged-Block_high 05 - M12_Tristruder_18mm_Probe_MouN_???_Ohigh 06 - M21_headphone_rest_high
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.9.7 P_???_0907 Assembly Low Res and NA

Test Scenario Description	Generate 3MF files for each of the xx Assembly and NA Test objects defined in Appendix A
Pass/Fail Criteria	01 to 04 – Printer should process correctly
Test Case Iterations	01 – chainassembly_low 02 – octohedron5_NA 03 – raindrop_low 04 – randomplacemeN_???_ONA
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.9.8 **P_???_0909 Stress Tests**

Test Scenario Description	Generate 3MF that may stress the resource or implementation boundaries of the printer
Pass/Fail Criteria	01 to 08 – Printer should process correctly
Pass/Fail Criteria Test Case Iterations	01 − Create a small cube (8x8x8mm) object. Replicate both the object 1000 times within the root model part. Create a thumbnail for each object and reference in the object element and the root model .rels part. This test will exercise the following stress points: Number of items in a relationship file (1000) Number of object elements in a resource element (1000) Number of build items in a build element (1000) Number of build items in a build element (1000) This varies of some of some of the allowable x axis build space, with a slice thickness of 80 microns. Divide the slicestack part into 1000 separate part slices and add the appropriate slicesref pointers to each of the parts to a single slicestack. This test will exercise the following stress points: O3− Create a 3D part and use 180-character long string that contains Cyrillic and Kanjii characters in metadata content, and the max value of 2147483647 in the following places in the XML: Dattribute value for an object Partnumber attribute value object element O4 − create a 3D part with characteristics likely to require more than 10,000 vectors in a single polygon to render a single layer. Use 5,000 small cylinders arranged as 100 spokes, each consisting of 50 slightly overlapping adjacent cylinders. O5 − Create a 3D part that when slices will produce will produce 10,000 polygons for a single slice O6 − create a 3D part with characteristics likely to require more than 10,000 separate polygons to render a single layer. Use a matrix of 10,000 small non overlapping rectangular objects O7 − Leverage the test case defined in 01 above and place each of the 1000 objects in a separate non-root model file. Reference these objects from the build items using the path attribute
	component path attributes, then have the build items point to the object containing the components.
Dominoment Defenses	Link to Descriptions and in 2005 Consideration 2016
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.9.9 **P_???_0910 Transform Matrices**

Test Scenario Description	Modify the allowable transform matrix elements for a 3MF file
Pass/Fail Criteria	01 to 06 – Printer should process correctly
	01 – Render the same object multiple times using each of the various build item transforms. For tests with no slice stack, elements to modify include m00, m01, m02, m10, m11, m12, m20, m21m m22 m30, m31, and m32 in a build item transform. For tests that include slice stack data, modify m00, m01, m10, m11, m30, m31, and m32
	02 – Render the same object multiple times using each of the various component item transforms. For tests with no slice stack, elements to modify include Modify m00, m01, m02, m10 m11, m12, m20, m21m m22 m30, m31, and m32 in a component item transform. For tests that include slice stack data, modify m00, m01, m10, m11, m30, m31, and m32
	03 – Use all 12 transform matrix elements (7 elements for tests with slice stack data) in a single build item transform such the impact of each element is obvious
	04 – Use all 12 transform matrix elements (7 elements for tests with slice stack data) in a single component transform such the impact of each element is obvious
	05 – Create a file with a build item pointing to an object with components, then an object with mesh. Modify the transforms in the build item and each of the object components to create a cascading effect using all 12 transform elements (7 elements for tests with slice stack data) in both the build item and component transforms.
	06 – Create a file where the transform attribute is used in a non-root model component element
Requirement Reference	Link to Requirement in 3MF Specification Blank

6.9.10 **P_???_0911** Maze Geometry

Test Scenario Description	A 3MF file that will result in a more complex geometry
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – Create an object that represents a complex maze involving a large number of vector variations
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.9.11 **P_???_0912** XY Axis Positioning

Test Scenario Description	Objects around perimeter of print bed
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – Create 3MF file with a number of object positioned around the periphery of the allowable XY axis
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.9.12 **P_???_0913 Overlapping Objects**

Test Scenario Description	Create 3mF parts that are overlapping
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – Create 3MF file with a number of partially overlapping objects that coexist in the same XY plane.
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.9.13 **P_???_0914** namespace prefixes

Test Scenario Description	Modify namespace prefixes of extensions so they are something other than "m" and 'p" for material and production
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – Modify a simple 3MF file such that the namespace prefix used for the material and production extensions is something other than "m" or "p" by modifying the xmlns declarations in the model element. Also update the prefixes used in requiredextensions to match the new prefixes
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.9.14 **P_???_0915 Object Pointers**

Test Scenario Description	A 3MF test job with various object relationships
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – Create a 3MF file that uses Build item path references to two separate parts containing mesh objects.
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.10 Positive 3MF Slice Extension Test Cases

6.10.1 P_???_1501 Meshresolution Attribute

Test Scenario Description	Valid enumerations of meshresolution
Pass/Fail Criteria	01 to 03 – Printer should process correctly
Test Case Iterations	01 – Use fullres meshresolution attribute
	02 – Use lowres meshresolution attribute
	03 – Omit meshresolution from the model element
Requirement Reference	Link to Requirement in 3MF Specification

6.10.2 **P_???_1502** Transform Matrices

Test Scenario Description	Modify the allowable transform matrix elements for a sliced 3MF file (i.e. planar transformation)
Pass/Fail Criteria	01 to 06 – Printer should process correctly
Test Case Iterations	01 – Modify M0, M11, M30, M31, and M32 in a build item transform
	02 – Modify M0, M11, M30, M31, and M32 in a component transform
	03 – Modify M0, M01, M10, M11, and M32 in a build item transform
	04 – Modify M0, M01, M10, M11, and M32 in a component transform
	05 – Create a sliced file with a build item pointing to an object with components, then an object with mesh. Add or modify the transforms in the build item and each of the object components to create a cascading effect using transform elements M0, M01, M10, M11, M30, M31, and M32.
Requirement Reference	Link to Requirement in 3MF Specification Blank

6.10.3 **P_???_1503 Slice Increments**

Test Scenario Description	Vary Z-axis slice increments
Pass/Fail Criteria	01 to 03 – Printer should process correctly
Test Case Iterations	01 – Generate 3MF file with small slice increments (10 microns)
	02 – Generate 3MF file with large slice increments (2mm)
	03 – Generate 3MF file with discontinuous slice increments between 80 and 500 microns
Requirement Reference	Link to Requirement in 3MF Specification

6.10.4 P_???_1504 Multiple Slicestack References, Mismatched Ztop and Zbottom

Test Scenario Description	Multiple sliceref's in a single slicestack
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – Create scenario where there are two Sliceref slicestack references, with a mismatch between the last ztop and the second Sliceref zbottom.
Requirement Reference	Link to Requirement in 3MF Specification

6.10.5 P_???_1505 Polygon Definition with Positive Fill Rule

Test Scenario Description	Polygon positive fill rule permutations
Pass/Fail Criteria	01 to 03 – Printer should process correctly
Test Case Iterations	Test case with Polygon definition requiring application of the positive fill rule. Scenario should include each of the positive file rule example shown in section 4.1.1 of the core specification. 01 – Example 1 02 – Example 2 03 – Example 3
Requirement Reference	Link to Requirement in 3MF Specification

6.10.6 P_???_1506 Ignore Object Level Material Mapping

Test Scenario Description	Scenario that uses basematerials references in polygon segment references. Printer should ignore.
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – Create a slice stack that uses the segment p1, p2, and pid. Define two basematerials and multiple colors within each base materials. Use the attributes on several segments to override the object level material mapping. Printer should ignore attributes.
Requirement Reference	Link to Requirement in 3MF Specification

6.10.7 P_???_1507 Multiple Polygons Representing a Slice

Test Scenario Description	3MF object where the sliced data has multiple polygons in a single slice layer.
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – Multiple polygons representing a slice
Requirement Reference	Link to Requirement in 3MF Specification

6.10.8 P_???_1508 Collapsing Proximal Vertices

Test Scenario Description	Identical and near identical vertices used in a polygon definition
Pass/Fail Criteria	01 to 02 – Printer should process correctly
Test Case Iterations	 O1 – Create a series of 2D vertices that are almost identical, then use those vertices in the polygon segment definition O2 – Create a series of 2D vertices that are identical, then use those vertices in the polygon segment definition
Requirement Reference	Link to Requirement in 3MF Specification

6.10.9 P_???_1509 Small of number of vertices and polygons

Test Scenario Description	Variations in number of vertices and polygons
Pass/Fail Criteria	01 to 04 – Printer should process correctly
Test Case Iterations	01 – Slicestack layers with 3 segments elements per polygon
	02 – Slicestack layer with approximately 400 segments elements per polygon
	03 – Slicestack layer with 1 polygon
	04 – Slicestack layer with approximately 100 polygons
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.10.10 **P_???_1510** Complex 2D Geometries

Test Scenario Description	A 3MF file that will result in a more complex sliced 2D geometry
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – Slice an object that represents a complex maze involving a large number of 2D vector variations
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.10.11 **P_???_1511 Z-Axis Offsets**

Test Scenario Description	3MF files with varying slice thicknesses
Pass/Fail Criteria	01 to 06 – Printer should process correctly
Test Case Iterations	01 – Slice an object at 100 microns
	02 – Slice an object at 200 microns
	03 – Slice an object at 300 microns
	04 – Slice an object at 400 microns
	05 – Slice an object at 500 microns
	06 – Object sliced with 20% segments of slicestack at 100, 200, 300, 400, and 500 microns
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.10.12 **P_???_1512 XY Axis Positioning**

Test Scenario Description	Objects around perimeter of print bed
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – Create 3MF file with a number of object positioned around the periphery of the allowable XY axis
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.10.13 **P_???_1513 Multiple Slice Stacks**

Test Scenario Description	Create sliced 3mF files that contain multiple slice stacks
Pass/Fail Criteria	01 to 03 – Printer should process correctly
Test Case Iterations	 O1 – Create 3MF file with a number of non-overlapping objects that coexist in the same XY plane. Independent slice stacks for each object should be in root model part. O2 – Create 3MF file with a number of non-overlapping objects that coexist in the same XY plane. Independent slice stacks for each object should exist in separate slice stack parts, each pointed to using a sliceref element in the root model part.
	03 – Create 3MF file with a number of partially overlapping objects that coexist in the same XY plane. Independent slice stacks for each object should exist in separate slice stack parts, each pointed to using a sliceref element in the root model part.
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.10.14 **P_???_1514 Duplicate IDs**

Test Scenario Description	Duplicate slicestack ID values
Pass/Fail Criteria	01 to 02– Printer should process correctly
Test Case Iterations	 O1 – Duplicate slicestack IDs split between a root model file and a non-root model file O2 – Create a sliced 3MF package where two mesh objects that reside as separate parts use the same ID
Requirement Reference	Link to Requirement in 3MF Specification

6.10.15

6.10.16 **P_???_1515** namespace prefixes

Test Scenario Description	Modify namespace prefixes of extensions so they are something other than "s" and 'p" for production and slice
Pass/Fail Criteria	01 – Printer should process correctly
Test Case Iterations	01 – Modify a simple slice file such that the namespace prefix used for the slice and production extensions is something other than "s" or "p" by modifying the xmlns declarations in the model element. Also update the prefixes used in requiredextensions to match the new prefixes
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.10.17 **P_???_1516 Slicestack Object Pointers**

Test Scenario Description	A 3MF test job with various slicestack to object relationships
Pass/Fail Criteria	01 to 02– Printer should process correctly
Test Case Iterations	O1 – Create a sliced 3MF file that uses Build item path references to two separate parts containing mesh objects. Those two mesh object parts should point to a single model file containing two separate slicestacks in the same file, with each object pointed at a separate stack O2 – Create a sliced 3MF file that uses Build item path references to two
	separate parts containing mesh objects. Those two mesh object parts should point to a single model file containing one slicestack in the file, with each object pointed at the same slicestack. Modify build item transform so objects do not overlap
Requirement Reference	Link to Requirement in 3MF Specification N/A

6.10.18 **P_???_1517** Polygon Slice

Test Scenario Description	Odd polygon definition
Pass/Fail Criteria	01 t0 02– Printer should ignore
Test Case Iterations	01 – Closed no area (Overlapping 2 segments) 02 – No polygons
Requirement Reference	Link to Requirement in 3MF Specification

6.10.19 **P_???_1518 Slicestack Precedence**

Test Scenario Description	A object could contain a reference slicestack and that same object could be part of a component that also contains a slicestack reference. The component slicestack that prevails must be the one at the component level
Pass/Fail Criteria	01 – Printer should print component defined slicestack
Test Case Iterations	01 — Map two different slicestacks to the same object. One directly the other via a component reference. Have the mesh output reflect the slicestack precedence of using the component slicestack
Requirement Reference	Link to Requirement in 3MF Specification

6.11 Negative Slice Extension Test Cases

6.11.1 **N_???_1601** Transform Matrices

Test Scenario Description	Invalid values in transform matrix
Pass/Fail Criteria	01 to 05 – Printer should generate error
Test Case Iterations	01 – Use a non-zero value in a transform for M02 in a build Item transform
	02 – Use a non-zero value in a transform for M12 in a build Item transform
	03 – Use a non-zero value in a transform for M20 in a build Item transform
	04 – Use a non-zero value in a transform for M21 in a component transform
	05 – Use a value other than 1 for M22 in a component transform
Requirement Reference	Link to Requirement in 3MF Specification

6.11.2 N_???_1604 Locally Defined Slice Stack and Sliceref

Test Scenario Description	Invalid Sliceref self-reference
Pass/Fail Criteria	01 – Printer should generate error
Test Case Iterations	01 – Have Sliceref point to the same part that contains the Sliceref statement referring to a locally defined slice stack
Requirement Reference	Link to Requirement in 3MF Specification

6.11.3 N ??? 1605 Two Layered Slicestack Reference Abstraction

_	
Test Scenario Description	Invalid 2 layers of abstraction in slicestack Sliceref references
Pass/Fail Criteria	01 – Printer should generate error
Test Case Iterations	01 – Define slicestack references with two layers of abstraction from the original slicestack
Requirement Reference	Link to Requirement in 3MF Specification could not find

6.11.4 **N_???_1606 Ztop Smaller Than Zbottom**

Test Scenario Description	Ztop Smaller Than Zbottom in sliced file
Pass/Fail Criteria	01 – Printer should generate error
Test Case Iterations	01 – Define slice with ztop smaller the zbottom value
Requirement Reference	Link to Requirement in 3MF Specification

6.11.5 N_???_1607 Ztop Lower Than Preceding Value

Test Scenario Description	Ztop lower than preceding value in sliced file
Pass/Fail Criteria	01 – Printer should generate error
Test Case Iterations	01 – ztop slice value that is lower than the preceding value
Requirement Reference	Link to Requirement in 3MF Specification

6.11.6 N_???_1608 Non-Distinct v2 Attributes

Test Scenario Description	Non-distinct v2 references in polygon definition
Pass/Fail Criteria	01 – Printer should generate error
Test Case Iterations	01 – Sequential segments with the same v2 attribute index
Requirement Reference	Link to Requirement in 3MF Specification

6.11.7 **N_???_1609** Polygon Slice Descriptions

Test Scenario Description	Invalid polygon definitions
Pass/Fail Criteria	01 to 03 – Printer should generate error
Test Case Iterations	01 – Polygon with a single point 02 – Open Polygon
Requirement Reference	Link to Requirement in 3MF Specification

6.11.8 **N_???_1610 Unique Slicestack ID**

Test Scenario Description	Duplicate slicestack ID values
Pass/Fail Criteria	01– Printer should generate error
Test Case Iterations	01 – Duplicate slicestack IDs in same local file
Requirement Reference	Link to Requirement in 3MF Specification

6.11.9 **N_???_1612 Overlapping Slicestacks**

Test Scenario Description	Generate a sliced 3MF file with overlapping slicestacks
Pass/Fail Criteria	01 – Printer should generate error
Test Case Iterations	01 – Scenario where there two slicerefs in a slice stack, but the Z-axis alignment of the vertically adjacent slicestacks referenced are overlapping
Requirement Reference	Link to Requirement in 3MF Specification

6.12 Positive Beam Lattice Extension Test Cases

Note that the beam lattice test suite does not contain tests for the 3MF Core specification requirements, so the OPC and Core test cases should be run from Suite3_Core in addition to the beam lattice test cases

The following guideline will be used for implementation of Beam Lattice test cases:

- All tests will have beamlattice schema set as a required extension in the model element. Tests that include balls will have the ball schema as a required extension unless noted otherwise in the test case description.
- Tests will define a 3MF consortium copyright in metadata
- Expected result PNG files will be embedded in each test file
- Tests will include the UUID attribute where required in the production extension, although the production extension will not be listed as a required extension. Support for other production extension functionality will not be included in test cases, not will the functionality of any additional 3MF extensions
- Rendered objects in each test case should stay within the following boundaries:
 printable-box="(35000.0,35000.0) (200000.0,200000.0,200000.0)"
- In general, most test cases will include some token triangular mesh representation as that will be the typical use case for this 3MF extension.
- Tests involving pid, pindex, p1, or p2 attributes will map to the displaycolor attribute
 of basematerials with the knowledge that this will impact only display rendering and
 NOT printer output which will be monochrome.

6.12.1 P_BXX_2001 Beams and Triangular Mesh

Test Scenario Description	Render beam lattice both with and without triangular mesh representation
Pass/Fail Criteria	01 to 03 Printer should process correctly
Test Case Iterations	01 – Standalone beam lattice with no triangle element defined
	02 – Standalone beam lattice with empty triangle element defined
	03 – Beam lattice with triangular mesh representation
Requirement Reference	

6.12.2 P_ BXX_2002 beamlattice Default Characteristics

Test Scenario Description	Exercise beamlattice attributes that control the default characteristics of the beams. Attributes tested include pid, pindex, radius, and cap (hemisphere, Butt, sphere).
Pass/Fail Criteria	01 to 06 - Printer should process correctly
Test Case Iterations	 O1 – Define several beam lattice structures each with a different default beam radius value O2 – Demonstrate that if no beamlattice element pid and pindex values are specified, the object level pid and pindex attributes when pointed to the basematerials displaycolor impact the default color of the beams rendered on a display O3 – Demonstrate that the beamlattice element's pid and pindex attributes
	override the object level pid and pindex values and that these beamlattice attributes impact only the rendering of beams on a display, not triangular mesh 04 – Demonstrate that omitting the beamlattice element's cap attribute and specifying "sphere" for this attribute have an equivalent effect 05 – Define several beam lattices structures each with a different default beam cap value including hemisphere, sphere, and butt (no beam cap1 or cap2 specified). Use r1 or r2 beam attributes to taper beams such that sphere caps can be differentiated from hemisphere caps
	06 – Define just beam element's cap1 or cap2 element to demonstrate that the cap enumeration not defined at the beam level uses the beamlattice cap specified.
Requirement Reference	

6.12.3 P_ BXX_2003 beamlattice minlength

Test Scenario Description	Test the beamlattice element's minlength attribute using lattice structures with varying lengths, demonstrating the cutoff at which beam no longer render
Pass/Fail Criteria	01 to 04– Printer should process correctly
Test Case Iterations	 01 – Define a beam lattice structure with graduated lengths of beams, demonstrate different minlength cutoffs. 02 – Define a beam lattice structure where all beams are smaller than minlegth. Include a triangular mesh representation so something renders 03 - Define zero length beam with the beam elements v1 and v2 attributes pointed different vertices.

_	
Requirement Reference	
reduirement keierence	

6.12.4 P_ BXX_2004 clippingmode and clippingmesh

	ippingmode and enppingmeen
Test Scenario Description	Utilize the inside and outside clipping modes with a variant of triangular mesh geometries to clip beam lattice structures
Pass/Fail Criteria	01 to 06 – Printer should process correctly
Test Case Iterations	01 – Demonstrate that omitting clippingmode has the effect of doing nothing even if a clippingmesh is defined
	02 – Demonstrate that specifying "none" has the effect of doing nothing even if a clippingmesh is defined
	03 – Demonstrate inside clipping
	04 – Demonstrate outside clipping
	05 – Demonstrate that triangular mesh is not impacted by clippingmode of inside even if the clippingmesh intersects the triangular mesh object with mesh and lattice part of same object
	06 – Demonstrate that triangular mesh is not impacted by clippingmode of outside even if the clippingmesh intersects the triangular mesh object with mesh and lattice part of same object
	07 –Exercise several complex mesh geometries used as a clippingmesh using both inside and outside clipping
	08 – Demonstrate effect where there is no intersect between the beam lattice and the clippingmesh using both inside and outside clipping mode. For inside, no beams will get clipped, for outside all beams will get clipped.
	09 – Demonstrate effect where there is a 100% intersect between the beam lattice and the clippingmesh using both inside and outside clipping mode. For inside, all beams will get clipped, for outside no beams will get clipped.
	10 - Demonstrate that specifying a clippingmode of "none" with no clippingmesh defined does not cause the rendered to generate an exception
	11 - Demonstrate that triangular mesh is not impacted by clippingmode of inside even if the clippingmesh intersects the triangular mesh object with mesh and lattice as separate objects
	12 - Demonstrate that triangular mesh is not impacted by clippingmode of outside even if the clippingmesh intersects the triangular mesh object with mesh and lattice as separate objects
Requirement Reference	

6.12.5 P_ BXX_2005 representationmesh

Test Scenario Description	Include a representationmesh in a 3MF package with beam lattice structures
Pass/Fail Criteria	01 to 02 – Printer should process correctly
Test Case Iterations	01 – Triangular mesh representation of beamlattice as a representationmesh
Requirement Reference	

6.12.6 **P_ BXX_2006 Basic Beams**

Test Scenario Description	Demonstrate various basic beam configurations
Pass/Fail Criteria	01 to 04– Printer should process correctly
Test Case Iterations	01 – Lattice structure with a single beam
	02 – Lattice structure with multiple intersecting beams
	03 – Lattice structure with beams intersecting triangular mesh geometry. Renderable mesh and lattice in separate objects
	04 – Test with multiple non-interconnected beams
	05 – Lattice structure with beams intersecting triangular mesh geometry. Renderable mesh and lattice in same object
Requirement Reference	

6.12.7 P_ BXX_2007 Beam Lattice Vertex Mapping

Test Scenario Description	Demonstrate various mappings of the beam element's v1 and v2 attribute to vertex's
Pass/Fail Criteria	01 to 02 – Printer should process correctly
Test Case Iterations	 01 – Beams defined with v1 and V2, no optional attributes, pointed at vertex indices both shared and not shared with triangular mesh 02 – Illustrate 12 standard beam lattice drawn from Netfabb's ability to export lattice structures. Refer to Appendix B,
Requirement Reference	

6.12.8 P_ BXX_2008 beam r1 and r2 attributes

Test Scenario Description	Exercise a range of the beam elements r1 and r1 attributes beam radius values
Pass/Fail Criteria	01 to 05 – Printer should process correctly
Test Case Iterations	01 – Illustrate that r1 overrides beamlattice radius default
	02 – Range of r1 radius values (no r2)
	03 – Illustrate that r2 uses r1 value if r2 not defined.
	04 – Range of r2 radius values (r1 fixed value)
	05 – Illustrate a range of v1 and v2 radius values
Requirement Reference	

6.12.9 P_ BXX_2009 beam Resource Mapping

Test Scenario Description	Range of values for the beam element's pid, p1, and p2 attributes with colors mapped to the displaycolor attribute of basematerials
Pass/Fail Criteria	01 to 03– Printer should process correctly
Test Case Iterations	01 – Demonstrate that pid overrides the beamlattice level pid
	02 – Range of index values for p1
	03 – Range of index values for p1 and p2. Both values must be the same.
Requirement Reference	

6.12.10 **P_ BXX_2010 beam Cap**

Test Scenario Description	Range of values for the beam element's cap1 and cap2 attributes including values for sphere, butt, and hemisphere
Pass/Fail Criteria	01 to 05– Printer should process correctly
Test Case Iterations	01 – Demonstrate that cap1 explicitly defined cap values at the beamlattice level
	02 – Define several beam lattices structures each with different cap1 or cap2 values including hemisphere, sphere, and butt.
	03 – Demonstrate that cap2 overrides explicitly defined cap values at the beamlattice level
	04 –Matrix of combos of Cap1 and Cap2 attribute values. Use r1 or r2 beam attributes to taper beams such that sphere caps can be differentiated from hemisphere caps
Requirement Reference	

6.12.11 **P_ BXX_2011 beamsets**

Test Scenario Description	Test of beamset references. Note that beamset does not impact the rendered appearance of the objects. There is currently no defined method of referencing beamsets in metadata.
Pass/Fail Criteria	01 to 03– Printer should process correctly
Test Case Iterations	01 – Define a single beamset with one beam ref
	02 – Define multiple beamsets with multiple beam ref
	03 – Include beamset name and identifier attributes
Requirement Reference	

6.12.12 **P_ BXX_2012 Units**

Test Scenario Description	Create a simple 3MF file with beam lattice structures, then modify the 3D model files to support each of the supported enumerations for the unit attribute of the Model element.
Pass/Fail Criteria	01 to 07– Printer should process correctly
Test Case Iterations	01 – Micron
	02 – Millimeter
	03 – Centimeter
	04 – Inch
	05 – Foot
	06 – Meter
	07 – Unspecified
Requirement Reference	

6.12.13 **P_ BXX_2013 Object Type**

Test Scenario Description	Render beam lattices structures with various object element type attribute values
Pass/Fail Criteria	01 to 03– Printer should process correctly
Test Case Iterations	01 – beamlattice defined in object of type "solidsupport"02 – beamlattice defined in object of type undefined (omit attribute)
	03 – beamlattice defined in object of type "model"
Requirement Reference	

6.12.14 P_ BXX_2014 Beams and Triangles

Test Scenario Description	Combinations of beam of triangular mesh and beam lattice structures
Pass/Fail Criteria	01 to 02– Printer should process correctly
Test Case Iterations	 01 – Mesh with minimum number of triangles and beam lattice 02 – Coplanar triangle mesh and beam lattice. Impact on display color
Requirement Reference	

6.12.15 **P_ BXX_2015 Component, build, and transform**

Test Scenario Description	Exercise beam lattice structures referenced via a component, in a build object, and transformed.
Pass/Fail Criteria	01 to 07– Printer should process correctly
Test Case Iterations	01 – Beam lattice stored in an object referenced by a component
	02 – Transform of a component that has a beam lattice definition (translate, scale, rotate, shear). Lattice Only
	03 – Built item transform of object with both beam lattice and triangular mesh (translate, scale, rotate, shear)
	04 – Build item compound transform from both component and build transform perspective. Lattice and Mesh Object.
	05 – Built item reference to matrix of objects: beam lattice only, triangle mesh only, both triangle mesh and beam mesh
	06 – Demonstrate that transforms are applied to clippingmesh
	07 – Implement a 3MF file where a transform is applied to a representationmesh
Requirement Reference	

6.12.16 **P_ BXX_2016 Fill Rules**

Test Scenario Description	Demonstrate fill rules are applied with overlapping lattice structures and intersecting lattice and triangular mesh objects
Pass/Fail Criteria	01– Printer should process correctly
Test Case Iterations	01 – Test case with objects that illustrate the intersection of beam lattice structures and triangle mesh such that the fill rules are invoked.
Requirement Reference	

6.12.17 **P_ BXX_2017 Overlapping Beam surface**

Test Scenario Description	Validate that with overlapping beams, the last beam rendered take precedence
	in terms of rendering color
Pass/Fail Criteria	01– Printer should process correctly
Test Case Iterations	01 – test with overlapping beams and different displaycolor values. Control of rendering by order in build item list
Requirement Reference	

6.12.18 **P_ BXX_2018 ballmode attributes**

Test Scenario Description	
Pass/Fail Criteria	01– 04 Printer should process correctly
Test Case Iterations	 01 – ballmode attribute omitted and ballmode of none should have equivalent effect 02 – ballmode of mixed, demonstrate that only vertices refered in the ball object result in balls rendering 03 – ballmode of all, demonstrate that all vertices at beam endpoints have balls rendered with nothing specified in the balls object 04 – ballmode of all, with some balls specified in the balls object with a differentiated diameter overriding the default diameter
Requirement Reference	

6.12.19 **P_ BXX_2019** ballmode resource property overrides

Test Scenario Description	
Pass/Fail Criteria	01– 04 Printer should process correctly
Test Case Iterations	01 – Override the beamlattice pindex attribute with ball pid and p value
	02 – 2 scenarios with balls: PID and "index" defined at object level only, PID and "index" at beamlattice level overriding object level
	03 – Demonstrate that omitting pid "index" (such as pindex) at beam, ball, or beamlattice level causes default pid and index to be used at next level up
	04 – Demonstrate that omitting pid at beam, ball, or beamlattice level causes lower level index to be mapped to default higher level pid
Requirement Reference	

6.12.20 P_ BXX_2020 ball radius and index

Test Scenario Description	
Pass/Fail Criteria	01– 05 Printer should process correctly
Test Case Iterations	01 – Range of beamlattice ballradius and ball r size values relative to beam size
	02 – balls element containing just one ball sub-element
	03 – Combination of balls on different lattice shapes, both default ballradius and radius defined at the ball level on various objects
	04 – Multiple balls mapped onto same lattice endpoint
	05 – Omit the ball r value, should use default ballradius value
Requirement Reference	

6.12.21 P_ BXX_2021 Misc ballmode tests

Test Scenario Description	
Pass/Fail Criteria	01– 07 Printer should process correctly
Test Case Iterations	01 – Beams made of segments and intersects. Make sure balls render at each segment beam endpoint vertex with a ballmode of "all"
	02 – Ball intersecting mesh, beams, end caps, and other ball
	03 – clippingmesh that intersects a ball using inside clippingmode
	04 – Tapered beams with balls, interactions between various cap type/radius and balls at same vertex
	05 – objects with balls using non-default unit type
	06 – Component anisotropic transform of object that that includes balls
	07 – Build item isotropic transform of object that includes balls
	08 – Illustrate impact of anisotropic scaling on a ball
	09 – Illustrate use of ballref in a beamset
	10 – Test case that contains balls, but the ball schema is not a required extension.
Requirement Reference	

6.13 Negative Beam Lattice Extension Test Cases

6.13.1 **N_ BXX_2501 Invalid ID**

Test Scenario Description	Test invalid Beam Lattice extension ID mappings
Pass/Fail Criteria	01 to 04– Printer should generate error
Test Case Iterations	01 – invalid ID for beamlattice element's clippingmesh attribute
	02 – invalid ID for beamlattice element's representationmesh attribute
	03 – invalid ID for beamlattice element's pid attribute
	04 – invalid ID for beam element's pid attribute
Requirement Reference	

6.13.2 N_ BXX_2502 Invalid Index Reference

Test Scenario Description	Test invalid Beam Lattice extension index mappings
Pass/Fail Criteria	01 to 06 – Printer should generate error
Test Case Iterations	01 – invalid index for beamlattice element's pindex attribute
	02 – invalid index for beam element's v1 attribute
	03 – invalid index for beam element's v2 attribute
	04 – invalid index for beam element's p1 attribute
	05 – invalid index for beam element's p2 attribute
	06 – invalid index for beamset element's ref attribute
Requirement Reference	

6.13.3 N_ BXX_2503 Miscellaneous Errors

Test Scenario Description	Miscellaneous error conditions
Pass/Fail Criteria	02, 04 to 08 – Printer should generate error
Test Case Iterations	01 - Deleted
	02 – Include beam lattice on an object with a type other than model or solidsupport
	03 - Beam with v1 and v2 pointing to same vertex.
	04 – Beam with r2 attribute defined without r1
	05 - Beamlattice with pid specified but no pid specified at object level
	06 - Beam with pid specified but no pid specified at object level
	07 – Invalid clippingmode enumeration
	08 — Invalid cap mode enumeration at the beanlattice level
Requirement Reference	

6.13.4 N_ BXX_2504 clippingmesh Exceptions

Test Scenario Description	Error conditions related to clippingmesh
Pass/Fail Criteria	01 to 05 – Printer should generate error
Test Case Iterations	01 – clippingmode other than none with no clippingmesh
	02 – clippingmesh as component object
	03 – clippingmesh as self-reference
	04 – clippingmesh with beam lattice
	05 – clippingmesh as a forward reference
Requirement Reference	

6.13.5 N_ BXX_2505 representationmesh Exceptions

Test Scenario Description	Error conditions related to representationmesh
Pass/Fail Criteria	01 to 04 – Printer should generate error
Test Case Iterations	01 – representationmesh as component object
	02 – representationmesh as self-reference
	03 – representationmesh with beam lattice
	04 – representationmesh as a forward reference
Requirement Reference	

6.13.6 N_ BXX_2506 ballmode Exceptions

Test Scenario Description	Error conditions related to ballmode
Pass/Fail Criteria	01 to 07 – Printer should generate error
Test Case Iterations	01 – Missing ballradius if ballmode other than none
	02 – ball vindex points to an out of range index in vertices
	03 – ball vindex points to a vertex mapped to other than a beam endpoint
	04 – ball pid maps to an out of range property ID
	05 – ball p attribute points to an out of range index in the properties (pid)
	06 – ballref index attribute points to an out of range index in balls
	07 – Invalid ballmode enumeration
Requirement Reference	

Note that some negative test cases may have device dependent behavior. In particular an invalid attribute enumeration might just cause the default enumeration to be used rather than fail.

6.14 Positive Secure Content Extension Test Cases

Note that the secure content test suite does not contain tests for the 3MF Core specification requirements nor a full set of production extension test cases, so all test cases should be run from Suite5_Core_Prod in addition to the secure content test cases.

The following guidelines will be used for implementation of Secure Content test cases:

- The consumer under test should behave as if it is identified by the
 consumerid="test3mf01", even though for their production code they use a
 different consumerid. Secondly, the consumer under test should embed the
 private key shown in Appendix D and map this to keyid= "test3mfkek01" in
 order to be able to decrypt the test case's encrypted content.
- The consumerid and keyid noted above will be stored in the test case keystore part and these identifiers will be mapped to all encrypted content that the consumer under test is expected to decrypt unless noted otherwise.
- All secure content will use the PKI key pair defined in Appendix D for encrypting and decrypting secure content accessible to the test consumer.
- Test Case extension variations in addition to Secure Content will include:
 - o Production Extension All test cases exception except one
 - Material Extension One test case encrypting a texture PNG part
 - o Production and Slice Extension One Test Case encrypting a slice stack
- Unless noted otherwise, renderable content in secure content test cases will consist of a common triangular mesh part.
- Out of scope for Secure Content Testing are parts that do not impact printer consumer. This includes:
 - OPC root package parts including Thumbnail, Core Properties, and Digital Signatures which are not allowed to be encrypted
 - Texture used by Material Extension Display Properties
 - Print Ticket Part
- All model parts unless otherwise noted will have required extensions set to both secure content and production extensions
- Tests will include 3MF Consortium copyright in metadata
- Positive tests will include thumbnail PNG images
- Rendered objects in each test case should stay within the following boundaries: printable-box="(35000.0,35000.0,35000.0) (200000.0,200000.0,200000.0)"
- Encrypted content in test file will use typical naming conventions followed by a postfix of "_encrypted" on the root portion of the file name. Example: "3dmodel_encrypted.model"
- Test packages will include a Metadata directory tree with unencrypted versions of encrypted parts that the consumer under test has access rights to decrypt. Metadata file naming will use a "_decrypted" postfix on the name of the encrypted content part. Example: 3dmodel_encrypted.model_decrypted
- Unless specified otherwise, there will be at least one consumer defined in the keystore for each test package

- Unless noted otherwise, test cases will have a KEK wrapped CEK always appear in the accessright element of the test file even though the CEK could be communicated out of band.
- Model parts may reference encrypted content for which the consumer does not
 have permission to access. It is assumed that the printers will reject these
 packages while editors may gracefully ignore content it can't decrypt. Test cases
 with encrypted content without access rights for the test consumer to decrypt will
 be considered negative test cases but will be grouped such that editors can use
 them to test their ability to gracefully ignore content they cannot decrypt.
- All test cases will include a must preserve relationship for the keystore in the root rels file
- It is assumed that the test consumer will only have one usable decryption key (test3mfkek01), although negative test cases may present the test consumer with alternate keyid values
- Only the required symmetric (AES256-GCM) and asymmetric (RSA2048 OAEP) encryption algorithms will be used for test cases, although the secure content specification allows for other encryption schemes
- Test cases that do not otherwise specify compression or hash algorithm, will use a random selection of SHA1 or SHA256 hash functions, and compressed or uncompressed content.
- The public key will be included in the keyvalue element unless otherwise specified
- All test cases will use a 96 bit initialization vectors and 128 bit tags, although other lengths are allowed by the secure content specification.
- Unique secret keys, initialization vectors, and aad (if any) will be used for the symmetric encryption of content across all test cases in the test suite.
- Unless otherwise stated, test cases will have a single resourcedatagroup object containing one accessright object and one resourcedata object
- The following kekparam attributes will be used for test cases
 - o SHA256:
 - wrappingalgorithm=" "http://www.w3.org/2009/xmlenc11#rsa-oaep"
 - mgfalgorithm="http://www.w3.org/2009/xmlenc11#mgf1sha256"
 - digestmethod="http://www.w3.org/2001/04/xmlenc#sha256"
 - SHA1 variation 1
 - wrappingalgorithm="http://www.w3.org/2001/04/xmlenc#rsa-oaepmgf1p"
 - SHA1 variation 2 (assumes SHA1 mfg and digest)
 - wrappingalgorithm=" "http://www.w3.org/2009/xmlenc11#rsa-oaep""
 - SHA1 variation 3 (assumes sha1 digest)
 - wrappingalgorithm="http://www.w3.org/2009/xmlenc11#rsaoaep"
 - mgfalgorithm = "http://www.w3.org/2009/xmlenc11#mgf1sha1"
 - SHA1 variation 4
 - wrappingalgorithm="http://www.w3.org/2009/xmlenc11#rsaoaep"
 - mgfalgorithm = "http://www.w3.org/2009/xmlenc11#mgf1sha1"
 - digestmethod="http://www.w3.org/2000/09/xmldsig#sha1"

6.14.1 P_EPX_2101 Paths to Encrypted Content

Test Scenario Description	Test consumers ability to traverse the 3MF package structure to find 3MF content
Pass/Fail Criteria	01 to 03 Printer should process correctly
Test Case Iterations	 01 – Encrypted content pointed to by the component path (sha1, comp) 02 – Encrypted content pointed to by the build item path (sha256, comp) 03 – Test case with a mixture of non-root model encrypted and unencrypted content (sha1, comp)
Requirement Reference	

6.14.2 P_EPX_2102 Material and Slice Extension Tests

Test Scenario Description	Test scenarios with encrypted content specific to the Material and Slice Extension specifications
Pass/Fail Criteria	01 to 02 Printer should process correctly
Test Case Iterations	 O1 – Test case with encrypted texture2d file mapped to Texture2dGroup in root model. Requires Material Extension support (sha256) O2 – Test case with non-root model referencing an encrypted model file with slicestack. Requires Slice Extension support (sha1, comp)
Requirement Reference	

6.14.3 **P_EPX_2103 Custom Parts**

Test Scenario Description	Test consumers ability to ignore the presence of encrypted custom parts
Pass/Fail Criteria	01 Printer should process correctly
Test Case Iterations	01 – Include an encrypted custom part with a mustPreserve relationship in the root.rels, an entry in keystore, but not otherwise referenced in 3MF model parts. (sha256, comp)
Requirement Reference	

6.14.4 **P_EPX_2104 KEK Encryption**

Test Scenario Description	Test scenarios with various KEK attribute variations
·	
Pass/Fail Criteria	01 to 05 Printer should process correctly
Test Case Iterations	 01 – Test case with SHA256 kekparams as shown in secure content test guidelines (comp) 02 – Test case with SHA1 variation 1 kekparams as shown in secure content test
	guidelines (comp) 03 – Test case with SHA1 variation 2 kekparams as shown in secure content test
	guidelines
	04 – Test case with SHA1 variation 3 kekparams as shown in secure content test guidelines
	05 – Test case with SHA1 variation 4 kekparams as shown in secure content test guidelines (comp)
Requirement Reference	

6.14.5 **P_EPX_2105 Compression**

Test Scenario Description	Test scenarios with various CEK compression characteristics
Pass/Fail Criteria	01 to 03 Printer should process correctly
Test Case Iterations	 O1 – Compression set to none (sha256) O2 – Compression set to deflate. Note: for this test case, the decrypted raw deflate file should be saved in metadata to aide in debugging compression related issues. (sha1) O3 – Compression attribute omitted (sha256)
Requirement Reference	

6.14.6 P_EPX_2106 Composite CEK Encryption/Compression

Test Scenario Description	Variations of encryption and compression in a single 3MF package
Pass/Fail Criteria	01 to 05 Printer should process correctly
Test Case Iterations	01 – A single test package with encrypted content that uses all the variations of SHA1, SHA256, compression, and no compression
	The following test cases will use a variety of 3MF model part sizes and geometries to add variation to the content being compressed and symmetrically encrypted.
	02 -Size and Geometry variation 1 (sha1, comp)
	03 -Size and Geometry variation 2 (sha1, comp)
	04 -Size and Geometry variation 3 (sha1, comp)
	05 -Size and Geometry variation 4 (sha256, comp)
Requirement Reference	

6.14.7 P_EPX_2107 Miscellaneous Tests

Test Scenario Description	Miscellaneous test cases
Pass/Fail Criteria	01 to 03 Printer should process correctly
Test Case Iterations	01 – Test case omitting the keyvalue element. Should not impact rendering as it is optional (sha1, comp)
	02 – Used extended secure content header length, which should not impact rendering (sha1)
	03 - Omit keyid attribute. Content encrypted with test public key. Consumer should default to using test private key to decrypt (sha256)
	04 – Include two resourcedatagroups that use the same CEK and have the same keyuuid (sha1, comp & sha1, comp)
Requirement Reference	

6.14.8 P_EPX_2108 resourceDataGroup

Test Scenario Description	Various mappings between the resourceDataGroup and encrypted content
Pass/Fail Criteria	01 to 03 Printer should process correctly
Test Case Iterations	 01 – Test case with multiple resourcedatagroup objects mapped to test consumer (sha1, comp) 02 – Two Components with two groups of models, representing two assemblies. Each assembly with their own CEK in the same resourcedatagroup. Each model in a different file and resourcedata. (sha256, comp) 03 – Keystore with multiple resourcedata element objects in a single resourcedatagroup (sha256 & sha256, comp)
Requirement Reference	

6.14.9 **P_EPX_2109 Access Rights**

Test Scenario Description	Variations in access right permissions
Pass/Fail Criteria	01 Printer should process correctly
Test Case Iterations	01 – Keystore with multiple accessright objects in a single resourcedatagroup pointing to same resourceData (sha256, comp)
Requirement Reference	

6.14.10 **P_EPX_2110** aad Attribute

Test Scenario Description	Variations of aad
Pass/Fail Criteria	01 to 03 Printer should process correctly
Test Case Iterations	01 – No aad element in payload (sha1)
	02 –aad element in payload with no value (sha256)
	03 — Correct aad value used (sha1, comp)
Requirement Reference	

6.14.11 **P_EPX_2111** Relationships and Content Types

	71
Test Scenario Description	Valid permutations of Secure Content related relationships and Content Types
Pass/Fail Criteria	01 to 02 Printer should process correctly
Test Case Iterations	 01 – Keystore defined in content types with a default extension (sha256, comp) 02 – Keystore defined in content types with an override using a name other than "keystore.xml" (sha1, comp)
Requirement Reference	

6.15 Negative Secure Content Extension Test Cases

6.15.1 N_ EPX_2601 Invalid Index Mapping

Test Scenario Description	Test out of bounds index mappings
Pass/Fail Criteria	01– Printer should generate error
Test Case Iterations	01 – Invalid index in consumerindex attribute
Requirement Reference	

6.15.2 **N_ EPX_2602** No Access rights

Test Scenario Description	Test scenarios where the consumer does not have any rights to encrypted content
Pass/Fail Criteria	01 to 03– Printer should generate error
Test Case Iterations	01 – Keystore has no consumers or access rights listed.
	02 – Keystore has consumers in list, but none of them map to the test consumerid. Content encrypted with non-test public key
	03 – Keystore has test consumerid listed but does not have a matching test keyid. Content encrypted with non-test public key
	04 – Keystore has test consumerid listed but omits the keyid attribute. Content encrypted with non-test public key
Requirement Reference	

6.15.3 **N_ EPX_2603 Decryption Exceptions**

Test Scenario Description	Tests where encrypted content mapped to the consumer cannot be successfully decrypted. Test values will use incorrect values, but ise valid URI/base64 formats
Pass/Fail Criteria	01 to 08– Printer should generate error
Test Case Iterations	01 – Incorrect wrappingalgorithm attribute value (edit SHA1 value)
	02 – Incorrect mgfalgorithm attribute value (edit SHA256 value)
	03 – Incorrect digestmethod attribute value (edit SHA256 value)
	04 – Incorrect ciphervalue element value
	05 – Incorrect encryptionalgorithm attribute value
	06 – Incorrect iv element value
	07 – Incorrect tag element value
	08 – Incorrect aad element value
Requirement Reference	

6.15.4 N_ EPX_2604 Limited Access Rights

These test cases in this section are expected to fail on printer consumers as some 3MF content will be mapped to encrypted files for which the consumer does not have permission. Consumer editors may pass these tests if the can gracefully ignore the content for which they do not have permission.

Test Scenario Description	Test scenarios where the consumer DUT has access to some, but not all of the encrypted content.
Pass/Fail Criteria	01 to 04– Printer should generate error, editors may successfully process package by ignoring content it cannot encrypt.
Test Case Iterations	 O1 – Test case with additional consumerid with associated encrypted content, some overlapping the test consumer, some unique to the alternate consumer. The CEK for the alternate consumerid will be wrapped with a different PKI pair than the test consumerid O2 – Test case with unencrypted renderable content in root model, but with no encrypted content mapped to the test consumerid. Content encrypted with non-test public key
	 03 – Test case with test consumer listed twice, with a test keyid and an alternate keyid respectively. The associated encrypted content for the alternate keyid will partially overlap the test keyid, with the balance being unique. The CEK for the alternate keyID will be wrapped with a different PKI pair than the test consumerid. Note that this test case will be a clone of test case 01, with the only difference being the mapping of the consumerid and keyid in keystore. 04 – Test case with unencrypted renderable content in root model, but with unrecognized Test keyid's for encrypted content. Content encrypted with nontest public key.
Requirement Reference	

6.15.5 N_ EPX_2605 Miscellaneous Exceptions

Test Scenario Description	Miscellaneous negative test scenarios
Pass/Fail Criteria	01 to 06– Printer should generate error
Test Case Iterations	01 – Encrypt a non-root model relationship file, with and encrypted file relations ships defined and keystore entries for the relationship file
	02 – Invalid compressed data
	03 – Bad Secure Content magic value
	04 – Invalid Secure Content header length
	05 – Encrypt the root model file, include all the expected mappings in keystore and root ,rels for the root model file
	06 – Invalid compression attribute enumeration (resourcedatagroup:resourcedata:cekparams compression attribute)
	07 – Use a binary file editor modify the content of test case P_EPX-2110_03. This modification should generate a decryption error.
Requirement Reference	

6.15.6 N_ EPX_2606 Relationship and Content Type Exceptions

Test Scenario Description	Various invalid relationship and content type mappings
Pass/Fail Criteria	01 to 03– Printer should generate error
Test Case Iterations	01 – Missing relationship for encrypted content mapped to 3MF model and with entries in keystore.
	02 –Keystore relationship missing from root .rels
	03 – Keystore content type missing from contentTypes part
Requirement Reference	

6.15.7 **N_ EPX_2607 Invalid Paths**

Test Scenario Description	Various invalid path mappings
Pass/Fail Criteria	01 to 05– Printer should generate error
Test Case Iterations	01 — Invalid resourcedatagroup:resourcedata path
	02 –Invalid encrypted file relationship target path
	03 – invalid root .rels keystore relationship target path
	04 – Same path for encrypted content specified multiple times in keystore resourcedata elements
Requirement Reference	

Appendix A - Test Object Library

3MF test case definitions may reference one or more test objects as defined in the following tables. Objects were generated from the following sources:

Created by QualityLogic Staff using SolidWorks and exported to STL files
SolidWorks SLDPRT files found on Thingiverse.com with Creative Commons license
allowing commercial use, exported to STL files
STL file found on Thingiverse.com with Creative Commons license allowing
commercial use
Created, then export from application such as NetFabb and Creo.

Objects where we have the SLDPRT file provide the greatest control over the mesh resolution, and a SolidWorks icon is shown in the tables below where we have access to this file type.

The object names define the nature and complexity of the object using the following format:

ABC_DDDD_EEEE

A = Object type
 □ S - Synthetic object, primarily simple geometric objects □ N - Natural objects, things found in nature □ M - Man-made objects, typically manufactured □ A - Assembly objects, sets of objects that comprise an assembly
B = Level of Detail where 1 is the least detailed and 3 is the most detailed
C = Level of curvature - Impacts triangle generation, 1 is least, 3 is most
DDDD = Object name
EEEE = Triangle count (High, Low, NA), differentiate same file captured at differing triangle densities

The categorization and ratings of objects are very subjective, with the only intent of these ratings being to assist in the selection of objects for test files.

Synthetic Objects

Object Name	Triangles	Image	Size (x, y, z) Attribution Link
S11_cube_NA	12		100, 100, 100 mm
S11_cube_fillet_high S11_cube_fillet_low	2,092 84		100, 100, 100 mm
S11_dodecahedron_NA	36		130, 137, 110 mm
S11_hex_pyramid_NA	10		76, 65.82, 90.42 mm
S11_octahedron_NA	8		57.74, 57.74, 100 mm
S11_pentagon_prism_NA	16		97.08, 92.33, 100 mm

S11_rectangle_pyramid_NA	8	No.	100, 40, 34.64 mm
S12_cone_high S12_cone_low	1,440 62		55, 55, 95 mm
S12_cylinder_high S12_cylinder_low	2,880 120	SW SW	50, 50, 100 mm
S12_ellipsoid_high S12_ellipsoid_low	545,760 2530		100, 100, 30 mm
S12_sphere_high S12_sphere_low	516,960 2,352		100, 100, 100 mm
S12_torus_high S12_torus_low	26,642 2,700		100, 100, 20 mm

Natural Objects

Object Name	Triangles	Image	Size (x, y, z) Attribution Link
N22_ChessHorse_high N22_ChessHorse_low	44,612 7,126		55.24, 67.07, 100 mm chessHorse by jbarrettoda is licensed under the Creative Commons - Attribution license.
N23_Deer_high N23_Deer_low	49,324 9,864		26.67, 75, 71.41 mm Deer by YahooJAPAN is licensed under the Creative Commons - Attribution license
N32_alligator_228_high N32_alligator_228_low	209,652 56,862		85, 121, 25 Alligator by willie is licensed under the Creative Commons - Public Domain Dedication license
N32_shell_high N32_shell_low	250,498 62,520		64.75, 75, 56.73 mm Unknown author
N33_Duck_NA	11,578		84.11, 68.58, 53 mm Duck by Roboduck is licensed under the Creative Commons - Attribution license

Man-Made, Manufactured Objects

Object Name	Triangles	Image	Size (x, y, z) Attribution Link
M11_box_NA	41,022	a les w	170, 11, 48 mm Geeetech GT2560 housing by lukie80 is licensed under the Creative Commons - Attribution license
M11_Snorkle_high M11_Snorkle_low	1,524,106 8,838		FJ Cruiser Snorkel Grill by LordNova2 is licensed under the Creative Commons - Attribution - Share Alike license
M11_stereographic_maze_lowres_NA	16,524		199, 199, 175 mm Customizable stereographic projection lowres bythreonin is licensed under the Creative Commons - Attribution - Share Alike license
M11_Ventilated Build Platform_high M11_Ventilated Build Platform_low	210,302 12,638		100, 100, 6 mm Ventilated Build Platform by deherzog is licensed under the Public Domain license
M12_Extruder_Bowden_Adapterc_high M12_Extruder_Bowden_Adapterc_low	20,662 792	SW	bowden capable gregs extruder with adapters bynicksears is licensed under the Creative Commons - Attribution - Share Alike license
M12_role_drum_NA	35,232		295, 296, 100 mm Rouleau de PLA / ABS dispenser roll by Alf_Arobaseis licensed under the GNU - GPL license
M12_SW_Extruder-Hinged-Block_high M12_SW_Extruder-Hinged-Block_low	77,148 792		bowden capable gregs extruder with adapters bynicksears is licensed under the Creative Commons - Attribution - Share Alike license

M12_Tristruder_18mm_Probe_MouN_???_ Ohigh M12_Tristruder_18mm_Probe_MouN_???_ Olow	12,856 7,384	82, 62, 38 mm Prusa i3 Tristruder with 18mm Probe Mount byinsapio is licensed under the Creative Commons - Attribution license
M21_flex_coupler_NA	14,558	50, 50, 100 mm Flex Coupler with Embedded Hardware by ChayesSAS is licensed under the Creative Commons - Attribution - Share Alike license
M21_headphone_rest_high M21_headphone_rest_low	189,060 1,816	91, 42, 65 mm HyperX Cloud Headset rest/stand by thatcloudguy is licensed under the Creative Commons - Attribution - Share Alike license
M22_FPV_Pod_Camera_Plate_NA	17,912	81.87, 35.03, 100 mm FPV Pod (Pan) - Hawkeye 1700 - GoPro/Xiaomi Yi + Board Cam Mount by BI0K3 is licensed under theCreative Commons - Attribution - Share Alikelicense
M22_FPV_Pod_Half_NA	47,476	80, 72, 155 mm FPV Pod (Pan) - Hawkeye 1700 - GoPro/Xiaomi Yi + Board Cam Mount by BI0K3 is licensed under the Creative Commons - Attribution - Share Alikelicense

Assembly Objects

Object Name	Triangles	Image	Size (x, y, z) Attribution Link
chainassembly_low	13,020		173, 121, 223 mm
octohedron5_NA	40		122, 95, 129 mm
raindrop_low	25,350		270, 382, 319 mm
randomplacemeN_???_ONA	2608		209, 191, 270 mm

Appendix B - Color, Texture, Lattice Tables

The following textures and colors will be referenced in test case scenarios to simply the definition of test case intent as it applies to the 3MF Material and Properties Extension.

Standard Colors (from 3D Builder)

Name	RGB	Swatch
White	#FFFFF	
	#FFFFFFF	
Black	#00000	
	#00000FF	
Gray	#808080	
	#808080FF	
Dark red	#880015	
	#880015FF	
Red	#EC1B23	
	#EC1B23FF	
Orange	#FF7F25	
	#FF7F25FF	
Yellow	#FEF100	
	#FEF100FF	
Lime	#B5E61D	
	#B5E61DFF	
Green	#21BB4C	
	#21BB4CFF	
Turquoise	#00A0E8	
	#00A0E8FF	
Indigo	#3E47CB	
	#3E47CBFF	
Purple	#A349A4	
	#A349A4FF	

Saturated Colors

RGB	Swatch
#FF0000	
#FF0000FF	
#00FF00	
#00FF00FF	
#0000FF	
#0000FFFF	
#FFFF00	
#FFFF00FF	
#FF00FF	
#FF00FFFF	
#00FFFF	
#00FFFFF	
#FFFFF	
#FFFFFFF	
#00000	
#00000FF	
	#FF0000 #FF000FF #00FF00 #00FF00FF #0000FF #0000FFF #0000FFF #FFFF00 #FFFF00FF #FF00FF #FF00FF #00FFFF #00FFFF #00FFFF #00FFFF #0FFFFFFFF

^{*}Upper case RGB = FF, Lower Case rgb = 00

Gradient Combinations

Name	P1	P2	Р3	
Gradient_01	White	Black	Gray	
Gradient_02	Dark red	Red	Orange	
Gradient_03	Yellow	Lime	Green	
Gradient_04	Turquoise	Indigo	Purple	
Gradient_05	Rgb	rGb	rgB	
Gradient_06	RGb	RgB	rGB	
Gradient_07	RGB	Rgb	rgb	
Gradient_08	RGB	rGb	rgb	
Gradient_09	RGB	rgB	rgb	

Small Texture Swatches (from 3D Builder)

Name/File	Size	Swatch	Swatch W/Alpha
brmarble.jpg brmarble.png brmarble_A.png	128 X 128		•
droplets.jpg droplets.png droplets_A.png droplets_mono.png droplets_mono_A.png	128 X 128		
grmarble.jpg grmarble.png grmarble_A.png	128 X 128		
oak.jpg oak.png oak_A.png oakNumbers.png	128 X 128	1 2/3	
		4	
pitissue.jpg pitissue.png pitissue_A.png	128 X 128		\$ \$
purmesh.jpg purmesh.png purmesh_A.png	128 X 128		
quads.jpg quads.png quads_A.png	720 X 720		


PNG without alpha are 24 bit, with alpha are 32 bit

Large Texture Images (Pixabay - No Attribution Required)

Name/File	Size/	Photo
Name/File	Original File Name	Photo
photo_1.jpg photo_1.png photo_1.png_48 photo_1.png_16 16/48 = bit depth	1280 X 833 background-1655938_1280.jpg	
photo_2.jpg photo_2.png	1280 X 829 background-2090828_1280.jpg	
photo_3.jpg photo_3.png	1280 X 1280 checkerboard-1943243_1280.png	
photo_4.jpg photo_4.png	1280 X 720 complex-664440_1280.jpg	
photo_5.jpg photo_5.jpg	1280 X 853 snail-shells-65358_1280.jpg	
photo_6.jpg photo_6.png	960 X 1280 substances-43315_1280.jpg	

Name/File	Size/	Photo
	Original File Name	
Woman_200.jpg Woman_3000.jpg	200 X 200 3000 X 3000 woman-101542.jpg	
Horse_350.png Horse_4000.png	350 X 350 4000 X 4000 Created in Paint Program	H H H H H H H H H H H H H H H H H H H
		HERRERRERRER DEREKERRER ARRERRER KERRERRE

Public Domain PngSuite - Basic Formats





Multi-Property Sets

Name	Layer 1	Layer 2	Layer 3
MultiProp_1	Solid Color Lime	Texture brmarble_A.png	
MultiProp_2	Gradient3	Texture grmarble_A.png	
MultiProp_3	Texture oak.jpg	Solid Color Yellow Alpha #7f	
MultiProp_4	Texture photo_3.jpg	Gradient_05 Alpha #00 on P1	
MultiProp_5	Texture photo_6.png	Texture droplets_A.png	
MultiProp_6	GradieN_???_07	Texture droplets_A.png	Texture pitissue_A.png
MultiProp_7	Texture photo_4.jpg	Solid Color Orange Alpha #7F	Texture oak_A.png
MultiProp_8	Texture purmesh.png	Texture brmarble_A.png	Gradient Alpha of #3f on P1, P2, P3

Beam Lattice Structures

The following beam lattice geometries are representative of lattices that will be used in test cases. Lattice structures may be mapped to a specific geometric shape as show in Appendix A. Application programs such as NetFabb will be used to generation 3MF XML Beam lattice objects for inclusion in test cases. The lattices show below are representative of the lattices that will be used in test cases.





Appendix C - Test Case to Test Suite Mapping

The tables below provide a mapping as to which test cases are supported in each of the 7 test suites. The test case name will start with an indication as to whether it is a positive of negative test case (P or N) followed by the three-digit extension indicator shown in the column header (i.e. SPX), then the test case ID (0101_01) . This will result in a test case number such as $P_SPX_0101_01$.

Positive Test Cases

Test			Suites	and Exter	nsions Su	pported		
Case	Suite 1 SPX	Suite 2 XPM	Suite 3 XXX	Suite 4 SXX	Suite 5 XPX	Suite 6 XXM	Suite 7 BXX	Suite 8 EPX
OPC								
0101_01	•	•	•	•	•	•		
0101_02	•	•	•	•	•	•		
0101_03	•	•	•	•	•	•		
0102_01	•	•	•	•	•	•		
0102_02	•	•	•	•	•	•		
0102_03	•	•	•	•	•	•		
0103_01	•	•	•	•	•	•		
0104_01	•	•	•	•	•	•		
0104_02	•	•	•	•	•	•		
0104_04	•	•	•	•	•	•		
0104_05		•				•		
0106_01	•	•	•	•	•	•		
0106_02	•	•	•	•	•	•		
0107_01	•	•		•	•			
0107_02	•	•		•	•			
Core	Suite 1	Suite 2	Suite 3	Suite 4	Suite 5	Suite 6	Suite 7	Suite 8
0302_01	•	•	•	•	•	•		
0302_02	•	•	•	•	•	•		
0302_03	•	•	•	•	•	•		
0304_02	•	•	•	•	•	•		
0304_03	•	•	•	•	•	•		
0304_04	•	•	•	•	•	•		
0306_01	•	•	•	•	•	•		
0306_02	•	•	•	•	•	•		
0306_03	•	•	•	•	•	•		
0306_04	•	•	•	•	•	•		
0306_05	•	•	•	•	•	•		1
0306_06	•	•	•	•	•	•		
0306_07	•	•	•	•	•	•		1
0307_01	•	•	•	•	•	•		1
0308_01	•	•	•	•	•	•		1
0309_01	•	•	•	•	•	•		
0310_01	•	•	•	•	•	•		1
0311_01	•	•	•	•	•	•		
0312_01	•	•	•	•	•	•		1
0313_01	•	•	•	•	•	•		
0314_01	•	•	•	•	•	•		

0314_02	•	•	•	•	•	•		
0314_03		•	•		•	•		
0314_03		•	•		•	•		
0314_04		•	•		•	•		
0314_03	•	•	•	•	•			
0315_01		•				•		
	•	•	•	•	•			
0317_01	•		•	•	•	•		
0318_01	•	•	•	•	•	•		
0319_01	•	•	•	•	•	•		
0321_01	•	•	•	•	•	•		
0322_01	•	•	•	•	•	•		
0323_01	•	•	•	•	•	•		
0323_02	•	•	•	•	•	•		
0324_01	•	•			•			
0325_01	•	•	•	•	•	•		
0326_01	•	•	•	•	•	•		
0326_02	•	•	•	•	•	•		
0326_03		•	•		•	•		
0327_01	•	•	•	•	•	•		
0328_01	•	•	•	•	•	•		
0328_02	•	•	•	•	•	•		
0329_01	•	•	•	•	•	•		
0330_01	•	•	•	•	•	•		
0331_01	•	•	•	•	•	•		
0333 01	•	•	•	•	•	•		
0333 02	•	•	•	•	•	•		
0333_03		•	•		•	•		
0334 01	•	•	•	•	•	•		
0334_02	•	•	•	•	•	•		
0335 01	•	•	-	•	•	-		
0335_01	•	•	•	•	•	•		
0335_02	•	•	•	•	•	•		
0335_03	•	•	•	•	•	•		
0335_04	•	•	•	•	•	•		
0336_01	•							
		•	•	•	•	•		
0337_01	•	•	•	•	•	•		
0337_02	•	•	•	•	•	•		
0337_03	•	•	•	•	•	•		
0337_04	•	•	•	•	•	•		
0337_05	•	•	•	•	•	•		
0337_06	•	•			•			
0338_01	•	•	•	•	•	•		
0339_01	•	•	•	•	•	•		
0340_01	•			•				
0340_02	•			•				
0340_03	•			•				
Material	Suite 1	Suite 2	Suite 3	Suite 4	Suite 5	Suite 6	Suite 7	Suite 8
0501_01		•				•		
0501_02		•				•		
0501_03		•				•		
0501_04		•				•		

OSO1 OSO OSO	0501_07	•		•	
0501 09 0 0502 01 0 0502 02 0 0502 02 0 0502 03 0 0 0 0 0 0 0 0 0					
0502 01 0 0 0 0 0 0 0 0 0		•		•	
0502 02 0 0 0 0 0 0 0 0					
0502 03		+			
0502 04					
0502 05 0 0 0 0 0 0 0 0 0					
0503 01 0 0 0 0 0 0 0 0 0					
0503 02					
0503 03		+			
0503 04					
0503 05					
0503 06					
0503 07 • • • 0503 08 • 0504 01 • 0504 01 • 0504 02 • • 0504 02 • • 0504 02 • • 0504 02 • • 0504 03 • • 0504 05 • • 0504 05 • • 0504 06 • • 0504 06 • • 0505 02 • • 0505 02 • • 0505 02 • • 0505 02 • • 0505 02 • • 0505 02 • • 0505 02 • • 0505 02 • • 0505 02 • • 0505 02 • • 0505 02 • • 0505 02 • • 0506 02 • • 0506 02 • • 0506 02 • • 0507 02 • • 0507 02 • • 0507 02 • • 0507 02 • • 0507 02 • •					
0503_08 • • • 0504_01 • • 0504_02 • • 0504_03 • • • 0504_03 • • • 0504_03 • • • • • • 0504_04 • <td></td> <td></td> <td></td> <td></td> <td></td>					
0504 01					
0504 02					
0504 03					
0504 04					
0504_05 • • • • • • • • • • • • • • • • •					
0504_06 • • • • • • • • • • • • • • • • •					
0504_07 • • • • • • • • • • • • • • • • •					
0505_01 • • • • • • • • • • • • • • • • •				•	
0505_02 • • • • • • • • • • • • • • • • •				•	
0505_03 • • • • • • • • • • • • • • • • •					
0506_01 • • • • • • • • • • • • • • • • •		•		•	
0506_02 • •<		•		•	
0506_03 • • • • • • • • • • • • • • • • •		•		•	
0506_04 • • • 0507_01 • • 0507_02 • • 0507_02 • <td></td> <td>•</td> <td></td> <td>•</td> <td></td>		•		•	
0507_01 • </td <td></td> <td>•</td> <td></td> <td>•</td> <td></td>		•		•	
0507_02 • • • 0507_03 • • 0507_03 •		•		•	
0507_03 • </td <td></td> <td>•</td> <td></td> <td>•</td> <td></td>		•		•	
0507_04 • • 0507_05 • 0507_06 • 0507_07 • 0507_07 • • 0507_08 • • • 0507_09 • <td></td> <td>•</td> <td></td> <td>•</td> <td></td>		•		•	
0507_05 • • • • • • • • • • • • • • • • •	0507_03	•		•	
0507_06 • • • • • • • • • • • • • • • • •		•		•	
0507_07 • • • • • • • • • • • • • • • • •	0507_05	•		•	
0507_08 • • 0507_09 • • 0508_01 • • 0508_02 • • 0508_03 • • 0508_04 • • 0508_05 • • 0508_06 • • 0508_07 • • 0508_08 • • 0508_09 • • 0508_10 • • 0508_11 • •		•		•	
0507_09 • </td <td>_</td> <td>•</td> <td></td> <td>•</td> <td></td>	_	•		•	
0508_01 • </td <td>0507_08</td> <td>•</td> <td></td> <td>•</td> <td></td>	0507_08	•		•	
0508_02 • </td <td>0507_09</td> <td>•</td> <td></td> <td>•</td> <td></td>	0507_09	•		•	
0508_03 • </td <td></td> <td>•</td> <td></td> <td>•</td> <td></td>		•		•	
0508_04 • </td <td></td> <td>•</td> <td></td> <td>•</td> <td></td>		•		•	
0508_04 • </td <td>0508_03</td> <td>•</td> <td></td> <td>•</td> <td></td>	0508_03	•		•	
0508_06 • </td <td>0508_04</td> <td>•</td> <td></td> <td>•</td> <td></td>	0508_04	•		•	
0508_06 • </td <td></td> <td>•</td> <td></td> <td>•</td> <td></td>		•		•	
0508_07 • </td <td></td> <td>•</td> <td></td> <td>•</td> <td></td>		•		•	
0508_08 • </td <td></td> <td>•</td> <td></td> <td>•</td> <td></td>		•		•	
0508_09 • • 0508_10 • • 0508_11 • •		•		•	
0508_10 • 0508_11 •		•		•	
0508_11 • •				•	
				•	
	0508_12	•		•	

0508_13	•			•	
0508_14	•			•	
0509_01	•			•	
0510_01	•			•	
0510 02	•			•	
0510_03	•			•	
0510_03	•			•	
0511_01	•			•	
0511_02	•			•	
0511_02	•			•	
0511_03	•			•	
0512_04	•			•	
0512_01	•			•	
0512_02	•			•	
0512_04	•			•	
0512_04				•	
0512_06	•				
	•			•	
0513_02	•			•	
0513_03	•			•	
0513_04	•			•	
0513_05	•			•	
0514_01	•			•	
0514_02	•			•	
0514_03	•			•	
0514_04	•			•	
0514_05	•			•	
0514_06	•			•	
0514_07	•			•	
0514_08	•			•	
0514_09	•			•	
0514_10	•			•	
0514_11	•			•	
0514_12	•			•	
0515_01	•			•	
0515_02	•			•	
0515_03	•			•	
0516_01	•			•	
0516_02	•			•	
0516_03	•			•	
0516_04	•			•	
0516_05	•			•	
0516_06	•			•	
0516_07	•			•	
0516_08	•			•	
0517_01	•			•	
0517_02	•			•	
0517_04	•			•	
0517_05	•			•	
0517_08	•		·	•	
0517_09	•			•	
0517_10	•			•	

0517_11	•		•	
0517_12	•		•	
0517_13	•		•	
0517_14	•		•	
0517_15	•		•	
0517_16	•		•	
0517_10	•		•	
0517_21	•		•	
0517_22	•		•	
0517_22	•		•	
0517_23	•		•	
0517_24	•		•	
0517_26	•		•	
0517_27	•		•	
0517_28	•		•	
0517_28	•		•	
0517_29	•		•	
0517_31	•		•	
0517_31				
0517_32	•		•	
0517_33				
0517_34	•		•	
0517_35	•		•	
	•		•	
0518_02	•		•	
0518_03	•		•	
0518_04	•		•	
0518_05	•		•	
0518_06	•		•	
0518_07	•		•	
0518_08	•		•	
0518_09	•		•	
0518_10	•		•	
0518_11	•		•	
0518_12	•		•	
0518_13	•		•	
0518_14	•		•	
0518_15	•		•	
0519_01	•		•	
0520_01	•		•	
0520_02	•		•	
0520_03	•		•	
0521_01	•			
0522_01	•		•	
0522_02	•		•	
0523_01	•			
0523_02	•			
0523_03	•			
0523_04	•			
0524_01	•		•	
0524_02	•		•	
0525_01	•		•	

0525_02	•		•	
0525_03	•		•	
0525_03	•		•	
0525_06	•		•	
0525_07	•		•	
0525_07	•		•	
0525_09	•		•	
0525_10	•		•	
0525_10	•		•	
0525_12	•		•	
0525_13				
0525_14	•		•	
0525_15	•		•	
0525_16	•		•	
	•		•	
0525_17	•		•	
0525_18	•		•	
0525_19	•		•	
0525_20	•		•	
0525_21	•		•	
0525_22	•		•	
0525_23	•		•	
0525_24	•		•	
0525_25	•		•	
0525_26	•		•	
0525_27	•		•	
0525_28	•		•	
0525_29	•		•	
0525_30	•		•	
0525_31	•		•	
0525_32	•		•	
0525_33	•		•	
0525_34	•		•	
0525_35	•		•	
0525_36	•		•	
0525_37	•		•	
0525_38	•		•	
0525_39	•		•	
0525_40	•		•	
0525_41	•		•	
0525_42	•		•	
0525_43	•		•	
0525_44	•		•	
0525_45	•		•	
0525_46	•		•	
0525_47	•		•	
0525_48	•		•	
0525_49	•		•	
0525_50	•		•	
0525_51	•		•	
0525_52	•		•	
0525_53	•		•	

0525_54		•				•		
0525_55		•				•		
0525_55								
		•				•		
0525_57		•				•		
0525_58		•				•		
0525_59		•				•		
0526_01		•				•		
0526_02		•				•		
0526_03		•				•		
0526_04		•				•		
0526_05		•				•		
0526_06		•				•		
0526_07		•				•		
0526_08		•				•		
0526_09		•				•		
0529_01		•				•		
0529_02		•				•		
0529_03		•				•		
0529_04		•				•		
0529_05		•				•		
0529_06		•				•		
0530_01		•				•		
0530_02		•				•		
0530_03		•				•		
0530_04		•				•		
0530_05		•				•		
0530_06		•				•		
0530_07		•				•		
0530_08		•				•		
0530 09		•				•		
Production	Suite 1	Suite 2	Suite 3	Suite 4	Suite 5	Suite 6	Suite 7	Suite 8
0701_01	•							
0701_02	•							
0701_04	•							
0701 05	•							
0701_06	•							
0701 07	•							
0701_08	•							
0701_09	•							
0701_11	•							
0701 12	•							
0701_13	•							
0701_14	•							
0702_01		•			•			
0702_01		•			•			
0702_03		•			•			
0702_03		•			•			
0702_04		•			•			
0702_05		•			•			
0702_00	•	•			•			
0703_01	•	•			•			
0/03_02			<u> </u>					

0703 03	•	•			•			
0703_03	•	•			•			
0703_01	•	•			•			
0703_06	•	•			•			
0703_07	•	•			•			
0703_07	•	•			•			
0703_08	•	•			•			
0703_09	•	•			•			
0703_10	•	•			•			
0703_11	•							
0703_12		•			•			
0704_01	•							
0704_02	•							
	•							
0704_04	•	_			_			
0705_01	•	•			•			
0706_01	• Cuito 1	• Suite 2	Cuito 2	Cuito 1	• Suite 5	Cuito 6	Suite 7	Cuito 9
Misc	Suite 1					Suite 6	Suite /	Suite 8
0901_01	•	•	•	•	•	•		
0901_02	•	•	•	•	•	•		
0901_03	•	•	•	•	•	•		
0901_04	•	•	•	•	•	•		
0901_05	•	•	•	•	•	•		
0901_06	•	•	•	•	•	•		
0901_07	•	•	•	•	•	•		
0901_08	•	•	•	•	•	•		
0901_09	•	•	•	•	•	•		
0901_10	•	•	•	•	•	•		
0901_11	•	•	•	•	•	•		
0901_12	•	•	•	•	•	•		
0902_01	•	•	•	•	•	•		
0902_02	•	•	•	•	•	•		
0902_03	•	•	•	•	•	•		
0902_04	•	•	•	•	•	•		
0902_05	•	•	•	•	•	•		
0902_06	•	•	•	•	•	•		
0903_01	•	•	•	•	•	•		
0903_02	•	•	•	•	•	•		
0903_03	•	•	•	•	•	•		
0903_04	•	•	•	•	•	•		
0903_06	•	•	•	•	•	•		
0904_01	•	•	•	•	•	•		
0904_02	•	•	•	•	•	•		
0904_03	•	•	•	•	•	•		
0904_04	•	•	•	•	•	•		
0905_01	•	•	•	•	•	•		
0905_02	•	•	•	•	•	•		
0905_03	•	•	•	•	•	•		
0905_04	•	•	•	•	•	•		
0905_05	•	•	•	•	•	•		
0905_06	•	•	•	•	•	•		
0905_07	•	•	•	•	•	•		

0905_08	•	•	•	•	•	•		
0905_09	•	•	•	•	•	•		
0905 10	•	•	•	•	•	•		
0905 12	•	•	•	•	•	•		
0905_12	•	•	•	•	•	•		
0906_01	•	•	•	•	•	•		
0906_02	•	•	•	•	•	•		
0906_02	•	•	•	•	•	•		
0906_04	•	•	•	•	•	•		
0906_05	•	•	•	•	•	•		
0906_06	•	•	•	•	•	•		
0900_00	•	•	•	•	•	•		
0907_01	•	•	•	•	•	•		
0907_02	•	•	•	•				
0907_03	•	•			•	•		
0907_04		•	•	•	•	•		
0909_01	•	•	•	•	•	•		
0909_02	•			•				
	•	•	•	•	•	•		
0909_04		•	•		•	•		
0909_05		•	•		•	•		
0909_06	•	_		•	_			
0909_07		•			•			
0909_08		•			•			
0910_01	•	•	•	•	•	•		
0910_02	•	•	•	•	•	•		
0910_03	•	•	•	•	•	•		
0910_04	•	•	•	•	•	•		
0910_05	•	•	•	•	•	•		
0910_06	•	•			•			
0911_01	•	•	•	•	•	•		
0912_01	•	•	•	•	•	•		
0913_01	•	•	•	•	•	•		
0914_01	•	•		•	•	•		
0915_01	Code 1	• Continue 2	College 2	Cuit- 1	Cuite F	C. it - C	C.: 7	Cosite o
Slice	Suite 1	Suite 2	Suite 3	Suite 4	Suite 5	Suite 6	Suite 7	Suite 8
1501_01	•			•				
1501_02	•			•				
1501_03	•			•				
1502_01	•			•				
1502_02	•			•				
1502_03	•			•				
1502_04	•			•				
1502_05	•			•				
1503_01	•			•				
1503_02	•			•				
1503_03	•			•				
1504_01	•			•				
1505_01	•			•				
1505_02	•			•				
1505_03	•			•				
1506_01	•	İ	I	•	İ	İ		İ

1507.01	1	l	1			1		
1507_01	•			•				
1508_01	•			•				
1508_02	•			•				
1509_01	•			•				
1509_02	•			•				
1509_03	•			•				
1509_04	•			•				
1510_01	•			•				
1511_01	•			•				
1511_02	•			•				
1511_03	•			•				
1511_04	•			•				
1511_04								
	•			•				
1511_06	•			•				
1512_01	•			•				
1513_01	•			•				
1513_02	•			•				
1513_03	•			•				
1514_01	•			•				
1514_02	•							
1515_01	•			•				
1516_01	•							
1516_02	•							
1517_01	•			•				
1517_02	•			•				
	1							
1518 01	•			•				
1518_01 Beam		Suite 2	Suite 3		Suite 5	Suite 6	Suite 7	Suite 8
Beam	• Suite 1	Suite 2	Suite 3	• Suite 4	Suite 5	Suite 6	Suite 7	Suite 8
Beam 2001_01		Suite 2	Suite 3		Suite 5	Suite 6	•	Suite 8
Beam 2001_01 2001_02		Suite 2	Suite 3		Suite 5	Suite 6	•	Suite 8
Beam 2001_01 2001_02 2001_03		Suite 2	Suite 3		Suite 5	Suite 6	•	Suite 8
Beam 2001_01 2001_02 2001_03 2002_01		Suite 2	Suite 3		Suite 5	Suite 6	•	Suite 8
Beam 2001_01 2001_02 2001_03 2002_01 2002_02		Suite 2	Suite 3		Suite 5	Suite 6	•	Suite 8
Beam 2001_01 2001_02 2001_03 2002_01 2002_02 2002_03		Suite 2	Suite 3		Suite 5	Suite 6	•	Suite 8
Beam 2001_01 2001_02 2001_03 2002_01 2002_02 2002_03 2002_04		Suite 2	Suite 3		Suite 5	Suite 6	•	Suite 8
Beam 2001_01 2001_02 2001_03 2002_01 2002_02 2002_03 2002_04 2002_05		Suite 2	Suite 3		Suite 5	Suite 6	•	Suite 8
Beam 2001_01 2001_02 2001_03 2002_01 2002_02 2002_03 2002_04 2002_05 2002_06		Suite 2	Suite 3		Suite 5	Suite 6	•	Suite 8
Beam 2001_01 2001_02 2001_03 2002_01 2002_02 2002_03 2002_04 2002_05 2002_06 2003_01		Suite 2	Suite 3		Suite 5	Suite 6	•	Suite 8
Beam 2001_01 2001_02 2001_03 2002_01 2002_02 2002_03 2002_04 2002_05 2002_06 2003_01 2003_02		Suite 2	Suite 3		Suite 5	Suite 6	•	Suite 8
Beam 2001_01 2001_02 2001_03 2002_01 2002_02 2002_03 2002_04 2002_05 2002_06 2003_01 2003_02 2003_03		Suite 2	Suite 3		Suite 5	Suite 6	•	Suite 8
Beam 2001_01 2001_02 2001_03 2002_01 2002_02 2002_03 2002_04 2002_05 2002_06 2003_01 2003_02 2004_01		Suite 2	Suite 3		Suite 5	Suite 6	•	Suite 8
Beam 2001_01 2001_02 2001_03 2002_01 2002_02 2002_03 2002_04 2002_05 2002_06 2003_01 2003_02 2003_03 2004_01 2004_02		Suite 2	Suite 3		Suite 5	Suite 6	•	Suite 8
Beam 2001_01 2001_02 2001_03 2002_01 2002_02 2002_03 2002_04 2002_05 2002_06 2003_01 2003_02 2004_01 2004_02 2004_03		Suite 2	Suite 3		Suite 5	Suite 6	•	Suite 8
Beam 2001_01 2001_02 2001_03 2002_01 2002_02 2002_03 2002_04 2002_05 2002_06 2003_01 2003_02 2004_01 2004_02 2004_03 2004_04		Suite 2	Suite 3		Suite 5	Suite 6	•	Suite 8
Beam 2001_01 2001_02 2001_03 2002_01 2002_02 2002_03 2002_04 2002_05 2002_06 2003_01 2003_02 2004_01 2004_02 2004_03		Suite 2	Suite 3		Suite 5	Suite 6	•	Suite 8
Beam 2001_01 2001_02 2001_03 2002_01 2002_02 2002_03 2002_04 2002_05 2002_06 2003_01 2003_02 2004_01 2004_02 2004_03 2004_04		Suite 2	Suite 3		Suite 5	Suite 6	•	Suite 8
Beam 2001_01 2001_02 2001_03 2002_01 2002_02 2002_03 2002_04 2002_05 2002_06 2003_01 2003_02 2004_01 2004_02 2004_04 2004_05 2004_06		Suite 2	Suite 3		Suite 5	Suite 6	•	Suite 8
Beam 2001_01 2001_02 2001_03 2002_01 2002_02 2002_03 2002_04 2002_05 2002_06 2003_01 2003_02 2004_01 2004_02 2004_03 2004_04 2004_05 2004_07		Suite 2	Suite 3		Suite 5	Suite 6	· · · · · · · · · · · · · · · · · · ·	Suite 8
Beam 2001_01 2001_02 2001_03 2002_01 2002_02 2002_03 2002_04 2002_05 2002_06 2003_01 2003_02 2004_01 2004_02 2004_03 2004_04 2004_05 2004_06 2004_07 2004_08		Suite 2	Suite 3		Suite 5	Suite 6		Suite 8
Beam 2001_01 2001_02 2001_03 2002_01 2002_02 2002_03 2002_04 2002_05 2003_01 2003_02 2004_01 2004_02 2004_03 2004_04 2004_05 2004_06 2004_07 2004_08 2004_09		Suite 2	Suite 3		Suite 5	Suite 6		Suite 8
Beam 2001_01 2001_02 2001_03 2002_01 2002_02 2002_03 2002_04 2002_05 2002_06 2003_01 2003_02 2004_01 2004_02 2004_03 2004_04 2004_05 2004_06 2004_07 2004_08 2004_09 2004_10		Suite 2	Suite 3		Suite 5	Suite 6		Suite 8
Beam 2001_01 2001_02 2001_03 2002_01 2002_02 2002_03 2002_04 2002_05 2003_01 2003_02 2004_01 2004_02 2004_03 2004_04 2004_05 2004_06 2004_07 2004_08 2004_09		Suite 2	Suite 3		Suite 5	Suite 6		Suite 8

2005 01		1	1			
2006 02 2006 03	2005_01				•	
2006 03					•	
2006_04					•	
2006 05					•	
2007 01					•	
2007 02	2006_05				•	
2008 01	2007_01				•	
2008 02	2007_02				•	
2008 03 2008 04 2008 05 2009 01 2009 02 2009 03 2010 01 2010 02 2010 03 2010 04 2011 01 2011 03 2012 01 2012 03 2012 04 2012 03 2012 04 2012 05 2012 05 2012 05 2013 01 2014 01 2015 05 2015 06 2015 07 2015 08 2015 06 2015 07 2015 08 2015 06 2015 07 2015 08 2015 06 2015 07 2015 08 2016 01 2017 01 2018 01 2018 02 2018 03 2019 01 2018 01 2019 0	2008_01				•	
2008 04	2008_02				•	
2008 05	2008_03				•	
2008 05	2008 04				•	
2009 01					•	
2009 02					•	
2010 01					•	
2010 01					•	
2010_02						
2010_03 2010_04 2011_01 2011_02 2011_03 2012_01 2012_02 2012_03 2012_04 2012_05 2012_06 2012_07 2013_01 2013_02 2013_03 2014_01 2014_02 2015_03 2015_04 2015_05 2015_06 2015_07 2015_06 2015_07 2015_06 2015_07 2016_01 2015_07 2015_06 2015_07 2015_06 2015_07 2016_01 2017_01 2018_02 2018_03 2018_04 2019_02 2018_03 2018_04 2019_001 2019_00						
2010_04 • 2011_01 • 2011_02 • 2011_03 • 2012_01 • 2012_02 • 2012_03 • 2012_04 • 2012_05 • 2012_06 • 2012_07 • 2013_01 • 2013_02 • 2013_03 • 2014_01 • 2015_02 • 2015_01 • 2015_02 • 2015_03 • 2015_04 • 2015_05 • 2015_06 • 2015_07 • 2016_01 • 2018_04 • 2018_02 • 2018_04 • 2019_01 •			+			
2011_01 • 2011_02 • 2011_03 • 2012_01 • 2012_02 • 2012_03 • 2012_04 • 2012_05 • 2012_06 • 2013_01 • 2013_01 • 2013_03 • 2014_01 • 2015_03 • 2015_01 • 2015_02 • 2015_03 • 2015_04 • 2015_05 • 2015_06 • 2015_07 • 2015_08 • 2015_07 • 2015_08 • 2015_07 • 2016_01 • 2018_03 • 2018_04 • 2019_01 • 2019_02 •						
2011_02 • 2012_01 • 2012_02 • 2012_03 • 2012_04 • 2012_05 • 2012_06 • 2012_07 • 2013_01 • 2013_03 • 2014_01 • 2015_03 • 2015_01 • 2015_02 • 2015_03 • 2015_04 • 2015_05 • 2015_06 • 2015_07 • 2016_01 • 2017_01 • 2018_03 • 2018_03 • 2018_04 • 2018_04 • 2018_04 • 2019_01 • 2019_01 •						
2011_03 • 2012_01 • 2012_03 • 2012_04 • 2012_05 • 2012_06 • 2012_07 • 2013_01 • 2013_02 • 2013_03 • 2014_01 • 2015_02 • 2015_02 • 2015_03 • 2015_04 • 2015_05 • 2015_06 • 2015_07 • 2015_08 • 2015_07 • 2016_01 • 2018_01 • 2018_02 • 2018_03 • 2019_01 • 2019_02 •			+			
2012_01 • 2012_02 • 2012_03 • 2012_04 • 2012_05 • 2012_06 • 2012_07 • 2013_01 • 2013_02 • 2013_03 • 2014_01 • 2015_01 • 2015_02 • 2015_03 • 2015_04 • 2015_05 • 2015_06 • 2015_07 • 2016_01 • 2017_01 • 2018_03 • 2018_04 • 2018_04 • 2019_02 •						
2012_02 • 2012_04 • 2012_05 • 2012_06 • 2012_07 • 2013_01 • 2013_02 • 2013_03 • 2014_01 • 2015_01 • 2015_02 • 2015_03 • 2015_05 • 2015_06 • 2015_06 • 2015_07 • 2016_01 • 2017_01 • 2018_01 • 2018_02 • 2018_03 • 2018_04 • 2019_02 •						
2012_03 • 2012_05 • 2012_06 • 2012_07 • 2013_01 • 2013_02 • 2013_03 • 2014_01 • 2015_01 • 2015_02 • 2015_03 • 2015_03 • 2015_04 • 2015_05 • 2015_06 • 2015_07 • 2016_01 • 2017_01 • 2018_02 • 2018_03 • 2018_04 • 2019_01 • 2019_02 •						
2012_04 • 2012_05 • 2012_07 • 2013_01 • 2013_02 • 2013_03 • 2014_01 • 2015_01 • 2015_02 • 2015_03 • 2015_03 • 2015_04 • 2015_05 • 2015_06 • 2015_07 • 2016_01 • 2017_01 • 2018_02 • 2018_03 • 2018_04 • 2019_01 • 2019_02 •						
2012_05 • 2012_06 • 2012_07 • 2013_01 • 2013_02 • 2014_01 • 2014_02 • 2015_01 • 2015_02 • 2015_03 • 2015_04 • 2015_05 • 2015_06 • 2015_07 • 2016_01 • 2017_01 • 2018_01 • 2018_02 • 2018_03 • 2018_04 • 2019_01 • 2019_02 •						
2012_06 • 2012_07 • 2013_01 • 2013_02 • 2013_03 • 2014_01 • 2014_02 • 2015_01 • 2015_02 • 2015_03 • 2015_04 • 2015_05 • 2015_06 • 2015_07 • 2016_01 • 2017_01 • 2018_01 • 2018_02 • 2018_03 • 2019_01 • 2019_02 •						
2012_07 • 2013_01 • 2013_02 • 2013_03 • 2014_01 • 2014_02 • 2015_01 • 2015_02 • 2015_03 • 2015_04 • 2015_05 • 2015_06 • 2015_07 • 2016_01 • 2017_01 • 2018_01 • 2018_02 • 2018_03 • 2019_01 • 2019_02 •						
2013_01 • 2013_02 • 2013_03 • 2014_01 • 2015_01 • 2015_02 • 2015_03 • 2015_04 • 2015_05 • 2015_06 • 2015_07 • 2016_01 • 2017_01 • 2018_03 • 2018_04 • 2019_01 • 2019_02 •						
2013_02 • 2014_01 • 2014_02 • 2015_01 • 2015_02 • 2015_03 • 2015_04 • 2015_05 • 2015_06 • 2015_07 • 2016_01 • 2018_01 • 2018_02 • 2018_03 • 2019_01 • 2019_02 •						
2013_03 • 2014_01 • 2015_01 • 2015_02 • 2015_03 • 2015_04 • 2015_05 • 2015_06 • 2015_07 • 2016_01 • 2018_01 • 2018_02 • 2018_03 • 2019_01 • 2019_02 •						
2014_01 • 2014_02 • 2015_01 • 2015_02 • 2015_03 • 2015_04 • 2015_05 • 2015_06 • 2015_07 • 2016_01 • 2018_01 • 2018_02 • 2018_03 • 2019_01 • 2019_02 •						
2014_02 • 2015_01 • 2015_02 • 2015_03 • 2015_04 • 2015_05 • 2015_06 • 2015_07 • 2016_01 • 2017_01 • 2018_01 • 2018_02 • 2018_03 • 2019_01 • 2019_02 •						
2015_01 • 2015_02 • 2015_03 • 2015_04 • 2015_05 • 2015_06 • 2015_07 • 2016_01 • 2017_01 • 2018_01 • 2018_02 • 2018_03 • 2019_01 • 2019_02 •						
2015_02 • 2015_03 • 2015_04 • 2015_05 • 2015_06 • 2015_07 • 2016_01 • 2017_01 • 2018_01 • 2018_02 • 2018_03 • 2019_01 • 2019_02 •						
2015_03 • 2015_04 • 2015_05 • 2015_06 • 2015_07 • 2016_01 • 2017_01 • 2018_01 • 2018_02 • 2018_03 • 2018_04 • 2019_01 • 2019_02 •					•	
2015_04 • 2015_05 • 2015_06 • 2015_07 • 2016_01 • 2017_01 • 2018_01 • 2018_02 • 2018_03 • 2018_04 • 2019_01 • 2019_02 •					•	
2015_05 • 2015_06 • 2015_07 • 2016_01 • 2017_01 • 2018_01 • 2018_02 • 2018_03 • 2018_04 • 2019_01 • 2019_02 •					•	
2015_06 • 2015_07 • 2016_01 • 2017_01 • 2018_01 • 2018_02 • 2018_03 • 2018_04 • 2019_01 • 2019_02 •					•	
2015_07 • 2016_01 • 2017_01 • 2018_01 • 2018_02 • 2018_03 • 2018_04 • 2019_01 • 2019_02 •					•	
2016_01 • 2017_01 • 2018_01 • 2018_02 • 2018_03 • 2018_04 • 2019_01 • 2019_02 •					•	
2017_01 • 2018_01 • 2018_02 • 2018_03 • 2018_04 • 2019_01 • 2019_02 •					•	
2018_01 • 2018_02 • 2018_03 • 2018_04 • 2019_01 • 2019_02 •					•	
2018_02 • 2018_03 • 2018_04 • 2019_01 • 2019_02 •					•	
2018_03 • 2018_04 • 2019_01 • 2019_02 •					•	
2018_04 • • • • • • • • • • • • • • • • • • •					•	
2019_01 • · · · · · · · · · · · · · · · · · ·					•	
2019_02	2018_04				•	
					•	
	2019_02				•	
	2019_03				•	

2019_04 • 2020_01 • 2020_02 • 2020_03 • 2020_04 • 2020_05 • 2021_01 • 2021_02 • 2021_03 • 2021_04 • 2021_05 • 2021_06 • 2021_07 •	
2020_02 • 2020_03 • 2020_04 • 2020_05 • 2021_01 • 2021_02 • 2021_03 • 2021_04 • 2021_05 • 2021_06 •	
2020_03 • 2020_04 • 2020_05 • 2021_01 • 2021_02 • 2021_03 • 2021_04 • 2021_05 • 2021_06 •	
2020_04 • 2020_05 • 2021_01 • 2021_02 • 2021_03 • 2021_04 • 2021_05 • 2021_06 •	
2020_05 • 2021_01 • 2021_02 • 2021_03 • 2021_04 • 2021_05 • 2021_06 •	
2021_01 • 2021_02 • 2021_03 • 2021_04 • 2021_05 • 2021_06 •	
2021_01 • 2021_02 • 2021_03 • 2021_04 • 2021_05 • 2021_06 •	
2021_02 • 2021_03 • 2021_04 • 2021_05 • 2021_06 •	
2021_03 • 2021_04 • 2021_05 • 2021_06 •	
2021_04 • • • • • • • • • • • • • • • • • • •	
2021_05 2021_06 •	
2021_06	
2021 0/	
2021 00	
2021-09	
2021-10 • • • • • • • • • • • • • • • • • • •	0
Secure Suite 1 Suite 2 Suite 3 Suite 4 Suite 5 Suite 6 Suite 7 Suite 7	ď
2101_01	
2101_02	
2101_03	
2102_01	
2102_02	
2103_01	
2104_01	
2104_02	
2104_03	
2104_04	
2104 05	
2105_01	
2105_02	
2105_03	
2106_01	
2106_02	
2106_03	
2106_03	
2106_05	
2107_01	
2107_02	
2107_03	
2108_01	
2108_02	
2108_03	
2109_01	
2110_01	
2110_02	
2110_03	
2111_01	

Negative Test Cases

Test			Suites	and Exte	nsions Su	pported		
Case	Suite 1 SPX	Suite 2 XPM	Suite 3 XXX	Suite 4 SXX	Suite 5 XPX	Suite 6 XXM	Suite 7 BXX	Suite 8 EPX
OPC	_							
0202_01	•	•	•	•	•	•		
0203_01	•	•	•	•	•	•		
0204 01	•	•	•	•	•	•		
0204 02	•	•	•	•	•	•		
0205 01	•	•	•	•	•	•		
0205 02	•	•	•	•	•	•		
0206 01	•	•	•	•	•	•		
0207 01	•	•	•	•	•	•		
0208 01	•	•	•	•	•	•		
0208 02		•				•		
Core	Suite 1	Suite 2	Suite 3	Suite 4	Suite 5	Suite 6	Suite 7	Suite 8
0402 01	•	•	•	•	•	•		
0402 02	•	•	•	•	•	•		
0402 03	•	•	•	•	•	•		
0402 04	•	•	•	•	•	•		
0403 01	•	•	•	•	•	•		
0404 01	•	•	•	•	•	•		
0404 02	•	•	•	•	•	•		
0404 03	•	•	•	•	•	•		
0404 04	•	•	•	•	•	•		
0405 01	•	•	•	•	•	•		
0405 02	•	•	•	•	•	•		
0405_02	•	•			•			
0405_03	•	•	•	•	•	•		
0405_04	•	•	•	•	•	•		
0406 01	•	•	•	•	•	•		
0406_01	•	•			•			
0407 01	•	•			•			
0407_01	•	•	•	•	•	•		
0409_01	•	•	•	•	•	•		
0410 01	•	•	•	•	•	•		
0410_01	•			•				
0410_02	•	•	•	•	•	•		
0410_03	•			•				
0410_04	•	•	•	•	•	•		
0411_01	•	•	•	•	•	•		
0412_01	•			•				
0412_02	•			•				
0412_03	•			•				
0412_04	•	•		•	•			
0413_01	•	•	•	•	•	•		
0415_02			•	•		•		
0415_01	•	•			•			
0415_02	•	•			•			
	•	•			•			
0415_04		•			•			

0416_01		•	•		•	•		
0416_02		•	•		•	•		
0417 01	•			•				
0418_01		•	•		•	•		
0419_01	•	•	•	•	•	•		
0420_01	•	•	•	•	•	•		
0421 01	•	•	•	•	•	•		
0421_01	•	•	•	•	•	•		
0424_01	•	•	•	•	•	•		
0424_01		•	•		•	•		
0420_01	•	•	•	•	•	•		
0427_01	•	•	•	•	•	•		
Material	Suite 1	Suite 2	Suite 3	Suite 4	Suite 5	Suite 6	Suite 7	Suite 8
0601_01	Suite 1	•	Suite 5	Suite 4	Suite 5	•	Suite 7	Suite 0
0601_01		•						
0601_02		•				•		
0602_01		•				•		
0602_02		•				•		
0602_03		•				•		
0604 01		•				•		
0604_01		•				•		
0604_02		•				•		
0604_03		•				•		
0605_01		•				•		
0605_01		•				•		
0605_02		•				•		
0606_01		•				•		
0606_02		•				•		
0607_01		•				•		
0608_01		•				•		
0609 01		•				•		
0609_02		•				•		
0609_03		•				•		
0609_04		•				•		
0609_05		•				•		
0609_06		•				•		
0609_07		•				•		
0609_07		•				•		
0609_09		•				•		
0609_09		•				•		
0609_11		•				•		
0610_01		•				•		
0610_02		•				•		
0610_02		•				•		
Production	Suite 1	Suite 2	Suite 3	Suite 4	Suite 5	Suite 6	Suite 7	Suite 8
0801_01	•	•			•			
0801_02	•	•			•			
0801_03	•	•			•			
0801_04	•	•			•			
0801_05	•	•			•			
0801_06	•	•			•			

0801_07	•							
0801_08	•							
0801_09	•							
0802_01	•	•			•			
0802_01	•	•			•			
0802_03	•	•			•			
0802_03	•	•			•			
0802_05	•	•			•			
0803_01	•	•			•			
Slice	Suite 1	Suite 2	Suite 3	Suite 4	Suite 5	Suite 6	Suite 7	Suite 8
1601_01	•	Saite 2	Saite 3	•	Suite 5	Suite 0	Suite 7	Suite 0
1601_02	•			•				
1601_03	•			•				
1601_04	•			•				
1601_05	•			•				
1604_01	•			•				
1604_01	•			•				
1606_01	•			•				
1607_01	•			•				
1608_01	•			•				
1609_01	•			•				
1609_01	•			•				
1610_01	•			•				
1612_01	•			•				
Beam	Suite 1	Suite 2	Suite 3	Suite 4	Suite 5	Suite 6	Suite 7	Suite 8
2501 01	Juice 1	Juile 2	Juile 3	Juile 4	Juile J	Juille 0	•	Juile 0
2501_01							•	
2501_03							•	
2501_03							•	
2502_01							•	
2502_01							•	
2502_02							•	
2502_03							•	
2502_04							•	
2502_05							•	
2503_02							•	
2503_02							•	
2503_03							•	
2503_04							•	
2503_06							•	
2503_07							•	
2503_07							•	
2504_01							•	
2504_01							•	
2504_03							•	
2504_03							•	
2504_04							•	
2504_05							•	
2505_01							•	
2505_02							•	
2505_04							•	

2506 01		1	ı	1		ı	1	ı	1
2506_03								•	
2506_04 2506_05 2506_06 Secure Suite 1 Suite 2 Suite 3 Suite 4 Suite 5 Suite 6 Suite 7 Suite 8 2601_01 2602_01 2602_02 2603_03 2603_02 2603_03 2603_05 2603_05 2603_06 2603_07 2604_01 2604_02 2604_03 2605_01 2605_05 2605_05 2605_06 2605_07 2606_01 2606_02 2606_03 2607_01 2607_02 2607_03								•	
Secure Suite 1 Suite 2 Suite 3 Suite 4 Suite 5 Suite 6 Suite 7 Suite 8								•	
Secure Suite 1 Suite 2 Suite 3 Suite 4 Suite 5 Suite 6 Suite 7 Suite 8								•	
Secure Suite 1 Suite 2 Suite 3 Suite 4 Suite 5 Suite 6 Suite 7 Suite 8 2601_01								•	
2601_01 • 2602_02 • 2602_03 • 2603_01 • 2603_02 • 2603_03 • 2603_04 • 2603_05 • 2603_06 • 2603_08 • 2604_01 • 2604_02 • 2604_03 • 2605_01 • 2605_02 • 2605_03 • 2605_04 • 2605_05 • 2605_06 • 2605_07 • 2606_01 • 2606_02 • 2606_03 • 2607_01 • 2607_02 • 2607_03 •	2506_06							_	
2602_01 • 2602_02 • 2603_01 • 2603_02 • 2603_03 • 2603_04 • 2603_05 • 2603_06 • 2603_07 • 2603_08 • 2604_01 • 2604_02 • 2604_03 • 2604_04 • 2605_01 • 2605_02 • 2605_03 • 2605_04 • 2605_05 • 2605_06 • 2605_07 • 2606_01 • 2606_02 • 2606_03 • 2607_01 • 2607_02 • 2607_03 •	Secure	Suite 1	Suite 2	Suite 3	Suite 4	Suite 5	Suite 6	Suite 7	Suite 8
2602_02 • 2602_03 • 2603_01 • 2603_02 • 2603_03 • 2603_04 • 2603_05 • 2603_06 • 2603_07 • 2603_08 • 2604_01 • 2604_02 • 2604_03 • 2604_04 • 2605_01 • 2605_02 • 2605_03 • 2605_04 • 2605_05 • 2605_06 • 2605_07 • 2606_01 • 2606_02 • 2606_03 • 2607_02 • 2607_03 •	2601_01								•
2602_03									•
2603_01	2602_02								•
2603_02	2602_03								•
2603_03	2603_01								•
2603_04 • 2603_05 • 2603_06 • 2603_07 • 2603_08 • 2604_01 • 2604_02 • 2604_03 • 2604_04 • 2605_01 • 2605_02 • 2605_03 • 2605_04 • 2605_05 • 2605_06 • 2605_07 • 2606_01 • 2606_02 • 2606_03 • 2607_01 • 2607_02 • 2607_03 •	2603_02								•
2603_05 • 2603_06 • 2603_07 • 2603_08 • 2604_01 • 2604_02 • 2604_03 • 2604_04 • 2605_01 • 2605_02 • 2605_03 • 2605_04 • 2605_05 • 2605_06 • 2605_07 • 2606_01 • 2606_02 • 2606_03 • 2607_01 • 2607_02 • 2607_03 •	2603_03								•
2603 06 • 2603 07 • 2603 08 • 2604_01 • 2604_02 • 2604_03 • 2604_04 • 2605_01 • 2605_02 • 2605_03 • 2605_04 • 2605_05 • 2605_06 • 2605_07 • 2606_01 • 2606_02 • 2606_03 • 2607_01 • 2607_02 • 2607_03 •	2603_04								•
2603 07 • 2604 01 • 2604 02 • 2604 03 • 2605 01 • 2605 02 • 2605 03 • 2605 04 • 2605 05 • 2605 07 • 2606 01 • 2606 02 • 2607 01 • 2607 02 • 2607 03 •	2603_05								•
2603_08 • 2604_01 • 2604_02 • 2604_03 • 2604_04 • 2605_01 • 2605_02 • 2605_03 • 2605_04 • 2605_05 • 2605_06 • 2605_07 • 2606_01 • 2606_02 • 2607_01 • 2607_02 • 2607_03 •	2603_06								•
2604_01 • 2604_02 • 2604_03 • 2604_04 • 2605_01 • 2605_02 • 2605_03 • 2605_04 • 2605_05 • 2605_06 • 2605_07 • 2606_01 • 2606_02 • 2607_01 • 2607_02 • 2607_03 •	2603_07								•
2604_02 • 2604_04 • 2605_01 • 2605_02 • 2605_03 • 2605_04 • 2605_05 • 2605_06 • 2606_01 • 2606_02 • 2607_01 • 2607_02 • 2607_03 •	2603_08								•
2604_03 • 2605_01 • 2605_02 • 2605_03 • 2605_04 • 2605_05 • 2605_06 • 2605_07 • 2606_01 • 2606_02 • 2607_01 • 2607_02 • 2607_03 •	2604_01								•
2604_04 • 2605_01 • 2605_02 • 2605_03 • 2605_04 • 2605_05 • 2605_06 • 2605_07 • 2606_01 • 2606_02 • 2607_01 • 2607_02 • 2607_03 •	2604_02								•
2605_01 • 2605_02 • 2605_03 • 2605_04 • 2605_05 • 2605_06 • 2605_07 • 2606_01 • 2606_02 • 2607_01 • 2607_02 • 2607_03 •	2604_03								•
2605_02 • 2605_03 • 2605_04 • 2605_05 • 2605_06 • 2605_07 • 2606_01 • 2606_02 • 2606_03 • 2607_01 • 2607_02 • 2607_03 •	2604 04								•
2605_02 • 2605_03 • 2605_04 • 2605_05 • 2605_06 • 2605_07 • 2606_01 • 2606_02 • 2606_03 • 2607_01 • 2607_02 • 2607_03 •	2605 01								•
2605_03 • 2605_04 • 2605_05 • 2605_06 • 2605_07 • 2606_01 • 2606_02 • 2606_03 • 2607_01 • 2607_02 • 2607_03 •	2605 02								•
2605_05 • 2605_06 • 2605_07 • 2606_01 • 2606_02 • 2606_03 • 2607_01 • 2607_02 • 2607_03 •	2605 03								•
2605_06 • 2605_07 • 2606_01 • 2606_02 • 2606_03 • 2607_01 • 2607_02 • 2607_03 •	2605_04								•
2605_06 • 2605_07 • 2606_01 • 2606_02 • 2606_03 • 2607_01 • 2607_02 • 2607_03 •	2605 05								•
2605_07 • 2606_01 • 2606_02 • 2606_03 • 2607_01 • 2607_02 • 2607_03 •									•
2606_01 • 2606_02 • 2606_03 • 2607_01 • 2607_02 • 2607_03 •	2605 07								•
2606_02 • 2606_03 • 2607_01 • 2607_02 • 2607_03 •									•
2606_03									•
2607_01 •									•
2607_02 • • • • • • • • • • • • • • • • • • •									•
2607_03									•
									•
2007 01	2607 04								•

Appendix D - Secure Content Test Keys and IDs

The Secure Content test suites uses the following well known customerid and keyid which is mapped to the PKI public and private keys also show below:

- consumerid="test3mf01"
- keyid="test3mfkek01

----BEGIN PUBLIC KEY----

MIIBIjANBgkqhkiG9w0BAQEFAAOCAQ8AMIIBCgKCAQEAubdl5ZV99+wA/1vUZeeM 8KQaSQ7dV0W9Vw7PNlXszRdoavwW4D/e70cajoeJ3TJfarA9zdE3pBVzXsja5VM1 axzrPCQn77VvFFTLsMa1lBz3UZckKK7dAVuoREQCH6042/4UGhvKmVoGq9jt0xMV 0CBIgWNgfviE6tuiiezGkoPEJXBbhg0WXNe6JSxYI3fRkjjPh8fHSla5Jil6L+Xr T/n6ehShlLN960tn8suxu1AaXuRvdimZNxVgK7VQKcYQbfKDfpzEi5Jfd2UKxmuK n/87nrreFYaZCeTjFbadP7FkB8wdSGGCctsdRfkl/pCBkdLrGsv7Is6jRlW7M0Zo BQIDAQAB

----END PUBLIC KEY----

----BEGIN RSA PRIVATE KEY----

MIIEogIBAAKCAQEAubdl5ZV99+wA/1vUZeeM8KQaSQ7dV0W9Vw7PN1XszRdoavwW 4D/e70cajoeJ3TJfarA9zdE3pBVzXsja5VM1axzrPCQn77VvFFTLsMa11Bz3UZck KK7dAVuoREQCH6042/4UGhvKmVoGq9jt0xMV0CBIgWNgfviE6tuiiezGkoPEJXBb hg0WXNe6JSxYI3fRkjjPh8fHSla5Jil6L+XrT/n6ehShlLN960tn8suxu1AaXuRv dimZNxVqK7VQKcYQbfKDfpzEi5Jfd2UKxmuKn/87nrreFYaZCeTjFbadP7FkB8wd SGGCctsdRfkl/pCBkdLrGsv7Is6jRlW7M0ZoBQIDAQABAoIBAAHH8Pm5K8qXYFES m+BYTqE2KaxesJ+4Iv81PKZ8P3eeDFnOThfbdPNdfrM00I2/AGxBAW66XWq86+zS R0sgt6ft0JG01Q928XhD8eohlbc0aejF5spfFu5+5we0kUKlgiCV+LJhZt1+pAa8 31cBXVmwHZHkFpZRItEvxwjElQjtp1co+kmCudew4ffpPBPUw7TSuOWuQVjo+d5M h0xaZzMjjxSornv4LRAm1D4NoCabuCx7jRY2qOql39nwCWi922vssbEjAUq4+862 Jqe/ted4xIGCk8DP+bwxj3WboLjkM4yp/5AcLGkaovhjupLXru4wDqsWr8wbgwV1 BmzUydcCgYEAvDaO6t58uk0kWVEmlGEueln4AfIUjgjo51qbbb23WsPQTZtlp7N0 /qNNKsWktr0ZPRIdIFcxTprd+gy5LGozQGz41J2lT+9DGsmo3dB2e47r+uKDnNwm legp+4LYFiXGLGDNonn7ESSec4Xj8z8YosVHskr64ptPCOzYzmDCkW8CgYEA/Jqj wLKOYgBVoUTEZQfMe295VKaKrxtqprYCTHF9J9lysxg2WfIVJByoVnpkmy2EI+Mw +ubtPrx71Cx413dem/S1aOOIsqJPqdFkc+AERV6ZeT1NWLCgzWoczW/N5ZdneUkW a0i0B0olAiC9b5zx9HB+p1bm7xEL3zL6OUDPu8sCgYBflkXXOs+Vvn/rbK9vRDva n765Hj0aNaQze2zcuzFXw4MTJwzlstqESGN0iZQxyq/6uCxatG2yQiziRXv19qm4 2p81PCstAZLPFAPTQ4ApGFj4vfmhvJ0RM1u/BKDB/sU63J8TGWhNOI/Qk/tFGpJk eFUFU9c/JylomwExLyshuQKBgFd2o+SA7tP4Ea45RVdGEANdYcFxuOtQrujydHFL im5V2GUyqP8T10YdthvbXSJt7CcQ71CwzMzALpAUpfLVHikZ3gZnYlmX4cWG/yUw F8p9Kt7T3wqqqEMfzsFDSSOJ/QX9zI1xLwSnI5FNDMqsqQpeOTxv1p5IZLfvyrww OL1pAoGAM/ZoL7qWenZAzD1Gdzo9HlrxlxBJPnr+ZdYqrJZdo/TwARY8LZu07Vsu aY1ZAqLlkBARRtypmGj04PGbWWRZ3Pn/M5/FgjGa5M9hVnvLJSBklE7tfKLB4KL5 eMADI7JuelOqfKBxXrp8IlzVlU8Mk0VQRw6hjq1zNKLJtD4EFq4=

----END RSA PRIVATE KEY----