

Lecture 23: Optimization I

Seyed-Hosein Attarzadeh-Niaki

Based on slides by Peter Marwedel

Embedded Real-Time Systems

1

Review

- Worst-case execution time problem
- Programs as Graphs
- Challenges of Execution Time Analysis
- Current Approaches
- Limitations and Future Directions

Embedded Real-Time Systems

2


Outline

- Task level concurrency management
- High-level optimizations
 - Floating-point to fixed-point conversion
 - Simple loop transformations
 - Loop tiling/blocking
 - Loop splitting
 - Array folding

Task-level concurrency management

- **Granularity:** size of tasks (e.g. in instructions)
 - Readable *specifications* vs. efficient *implementations*
 - possibly require different task structures.
- ☞ Granularity changes

Merging of tasks




- Reduced overhead of context switches,
- More global optimization of machine code,
- Reduced overhead for inter-process/task communication.

Embedded Real-Time Systems

5

Splitting of tasks




- No blocking of resources while waiting for input,
- more flexibility for scheduling, possibly improved result.

Embedded Real-Time Systems

6


Merging and splitting of tasks

- The most appropriate task graph granularity depends upon the context
 -  merging and splitting may be required.
- Merging and splitting of tasks should be done automatically, depending upon the context.

Embedded Real-Time Systems

7

Automated rewriting of the task system Example (in FlowC language)




Embedded Real-Time Systems

8

Parts of a system that need rewriting

Tasks blocking after they have already started running



Embedded Real-Time Systems

9


Work by Cortadella et al.

- Transform each of the tasks into a special formalism (Petri net),
- Generate one global Petri net from the nets of the tasks,
- Partition global net into “sequences of transitions”
- Generate one task from each such sequence

Embedded Real-Time Systems

10


Result, as published by Cortadella



Embedded Real-Time Systems

11

Optimized version of Tin



Embedded Real-Time Systems


12

Fixed-Point Data Format

• Floating-Point vs. Fixed-Point

- *exponent*, mantissa
- Floating-Point
 - automatic computation and update of each exponent at run-time
- Fixed-Point
 - implicit exponent
 - determined off-line

• Integer vs. Fixed-Point



© Ki-Il Kum, et al

Embedded Real-Time Systems

13

Floating-Point to Fixed-Point Conversion

Pros

- Lower cost
- Faster
- Lower power consumption
- Sufficient SQNR, *if properly scaled*
- Suitable for portable applications

Cons


- Decreased dynamic range
- Finite word-length effect, *unless properly scaled*
 - Overflow and excessive quantization noise
- Extra programming effort

© Ki-Il Kum, et al. (Seoul National University): A Floating-point To Fixed-point C Converter For Fixed-point Digital Signal Processors, 2nd SUIF Workshop, 1996

Embedded Real-Time Systems

14


Development Procedure



Embedded Real-Time Systems

© Ki-Il Kum, et al¹⁵

Range Estimator



Range Estimation C Program

```
float iir1(float x)
{
    static float s = 0;
    float y;

    y = 0.9 * s + x;
    range(y, 0);
    s = y;
    range(s, 1);


    return y;
}
```

Embedded Real-Time Systems

© Ki-Il Kum, et al

16

Operations in fixed point program



Embedded Real-Time Systems

17

Floating-Point to Fixed-Point Program Converter

Fixed-Point C Program

```
int iir1(int x)
{
    static int s = 0;
    int y;
    y=sll(mulh(29491,s)+ (x>> 5),1);
    s = y;
    return y;
}
```


- mulh
 - to access the upper half of the multiplied result
 - target dependent implementation
- sll
 - to remove 2nd sign bit
 - opt. overflow check

IWL of variable x, y, s are 0, 4, 4

Embedded Real-Time Systems

© Ki-Il Kum, et al 18


Performance Comparison – Machine Cycles - Fourth Order IIR Filter



Embedded Real-Time Systems

© Ki-II Kum, et al 19


Performance Comparison – Machine Cycles -



Embedded Real-Time Systems

© Ki-II Kum, et al 20

Performance Comparison - SNR -



Embedded Real-Time Systems

© Ki-Il Kum, et al 21

Matlab Fixed-Point Designer

Provides data types and tools for optimizing and implementing fixed-point and floating-point algorithms on embedded hardware.

- Data Type Exploration
- Automated Data Typing
- Embedded Implementation
- Testing and Debugging



Embedded Real-Time Systems

22

Simple Loop Transformations



- Loop permutation
- Loop fusion, loop fission
- Loop unrolling

Embedded Real-Time Systems

23

Impact of Memory Allocation on Efficiency

Row major order (C) **Array $p[j][k]$** Column major order (FORTRAN)



Embedded Real-Time Systems


24

Best performance of innermost loop corresponds to rightmost array index

Two loops, assuming row major order (C):

for (k=0; k<=m; k++) for (j=0; j<=n; j++)) p[j][k] = ...	for (j=0; j<=n; j++) for (k=0; k<=m; k++) p[j][k] = ...
---	---

Same behavior for homogeneous memory access, but:



↑ Poor cache behavior Good cache behavior ↑

☞ memory architecture dependent optimization

Embedded Real-Time Systems

25

Program Transformation: “Loop interchange”

Example:

```
...#define iter 400000
int a[20][20][20];
void computeijk() {int i,j,k;
    for (i = 0; i < 20; i++) {
        for (j = 0; j < 20; j++) {
            for (k = 0; k < 20; k++) {
                a[i][j][k] += a[i][j][k];}}}}
void computeikj() {int i,j,k;
    for (i = 0; i < 20; i++) {
        for (j = 0; j < 20; j++) {
            for (k = 0; k < 20; k++) {
                a[i][k][j] += a[i][k][j] ;}}}}...
start=time(&start);for(z=0;z<iter;z++)computeijk();
end=time(&end);
printf("ijk=%16.9f\n",1.0*difftime(end,start));
(SUIF interchanges array indexes instead of loops)
```

☞ Improved locality

Embedded Real-Time Systems


26

Results: Strong Influence of The Memory Architecture

Loop structure: i j k

Dramatic impact of locality

Processor	Ti C6xx	Sun SPARC	Intel Pentium
reduction to [%]	~ 57%	35%	3.2 %



Not always the same impact ..

[Till Buchwald, Diploma thesis, Univ. Dortmund, Informatik 12, 12/2004]

Embedded Real-Time Systems

27

Program Transformation:

“Loop fusion” (merging), “loop fission”

for(j=0; j<=n; j++) p[j]= ... ; for (j=0; j<=n; j++) , p[j]= p[j] + ...	↔	for (j=0; j<=n; j++) {p[j]= ... ; p[j]= p[j] + ...}
--	---	---

Loops small enough to
allow zero overhead

Loops

Better locality for
access to p.

Better chances for
parallel execution.

Which of the two versions is best?

Architecture-aware compiler should select best version.

Embedded Real-Time Systems

28

Example: simple loops

```
#define size 30
#define iter 40000
int a[size][size];
float b[size][size];
```

```
void ss1() {int i,j;
  for (i=0;i<size;i++){
    for (j=0;j<size;j++){
      a[i][j] += 17;}}
  for(i=0;i<size;i++){
    for (j=0;j<size;j++){
      b[i][j] -=13;}}}
```


```
void ms1() {int i,j;
  for (i=0;i< size;i++){
    for (j=0;j<size;j++){
      a[i][j] +=17;    }
    for (j=0;j<size;j++){
      b[i][j] -=13; }}}}
```

```
void mm1() {int i,j;
  for(i=0;i<size;i++){
    for(j=0;j<size;j++){
      a[i][j] += 17;
      b[i][j] -= 13;}}}
```

Embedded Real-Time Systems

29

Results: simple loops



Merged loops superior; except Sparc with -o3

Embedded Real-Time Systems

30

Loop unrolling

```
for (j=0; j<=n; j++)  
p[j]= ... ;
```



```
for (j=0; j<=n; j+=2)  
{p[j]= ... ; p[j+1]= ... }
```

factor = 2

- **Better locality** for access to p.
- Less branches per execution of the loop.
 - More opportunities for optimizations.
- Tradeoff between code size and improvement.
- Extreme case: completely unrolled loop (no branch).

Embedded Real-Time Systems

31


Example: matrixmult

```
#define s 30  
#define iter 4000  
int  
a[s][s],b[s][s],c[s][s];  
void compute(){int i,j,k;  
  for(i=0;i<s;i++){  
    for(j=0;j<s;j++){  
      for(k=0;k<s;k++){  
        c[i][k]+=  
          a[i][j]*b[j][k];  
      }  
    }  
  }  
}  
  
extern void compute2()  
{int i, j, k;  
  for (i = 0; i < 30; i++) {  
    for (j = 0; j < 30; j++) {  
      for (k = 0; k <= 28; k += 2)  
      {  
        int *suif_tmp;  
        suif_tmp = &c[i][k];  
        *suif_tmp=  
        *suif_tmp+a[i][j]*b[j][k];  
        int *suif_tmp;  
        suif_tmp=&c[i][k+1];  
        *suif_tmp=*suif_tmp  
          +a[i][j]*b[j][k+1];  
      }  
    }  
  }  
  return;}  
}
```

Embedded Real-Time Systems

32

Results



Benefits quite small; penalties may be large

[Till Buchwald, Diploma thesis, Univ. Dortmund, Informatik 12, 12/2004]

Embedded Real-Time Systems


33

Results: benefits for loop dependences

Processor	Ti C6xx
reduction to [%]	

```
#define s 50
#define iter 150000
int a[s][s], b[s][s];
void compute() {
    int i,k;
    for (i = 0; i < s; i++) {
        for (k = 1; k < s; k++) {
            a[i][k] = b[i][k];
            b[i][k] = a[i][k-1];
        }
    }
}
```

Small benefits;



[Till Buchwald, Diploma thesis, Univ. Dortmund, Informatik 12, 12/2004]

Embedded Real-Time Systems

34

Loop Tiling/Blocking


- Speed of memories is increasing at a slower rate than that of processors.
- Small memories are faster than large memories -> use memory hierarchy
- Possible “small” memories include caches and scratch-pad memories.
 - Significant *reuse factor* for the information in these memories is required
 - Try to fit the active data into fast memories

Embedded Real-Time Systems

35

Impact of Caches on Execution Times?

- Execution time for traversal of linked list, stored in an array, each entry comprising NPAD*8 Bytes



- Pentium P4
- 16 kB L1 data cache, 4 cycles/access
- 1 MB L2 cache, 14 cycles/access
- Main memory, 200 cycles/access

U. Drepper: *What every programmer should know about memory**, 2007, <http://www.akkadia.org/drepper/cpumemory.pdf>; Dank an Prof. Teubner (LS6) für Hinweis auf diese Quelle
 * In Anlehnung an das Papier „David Goldberg, *What every programmer should know about floating point arithmetic*, *ACM Computing Surveys*, 1991 (auch für diesen Kurs benutzt).

Embedded Real-Time Systems

© Graphik: U. Drepper, 2007

36

Cycles/access as a function of the size of the list




Figure 3.10: Sequential Read Access, NPAD=0

* prefetching succeeds

\$ prefetching fails


Embedded Real-Time Systems

© Graphics: U. Drepper, 2007

37

Impact of TLB misses and larger caches

Elements on different pages; run time increase when exceeding the size of the TLB



Larger caches are shifting the steps to the right




Figure 3.14: Advantage of Larger L2/L3 Caches

Embedded Real-Time Systems

© Graphics: U. Drepper, 2007

38

Program transformation


Loop tiling/loop blocking: - Original version -

```

for (i=0; i<N; i++)
  for (j=0; j<N; j++) {
    r=0; /* to be allocated to a register*/
    for (k=0; k<N; k++)
      r += X[i,k] * Y[k,j]
    Z[i][j]=r;
  }

```

% Never reusing information in the cache for Y and Z if N is large or cache is small ($2 N^3$ references for Z).



39

Loop tiling/loop blocking

- tiled version -


```

for (ii=0; ii<N; ii+=B)
  for (jj=0; jj<N; jj+=B)
    for (kk=0; kk<N; kk+=B)
      for (i=ii; i<min(ii+B-1,N); i++) {
        for (j=jj; j<min(jj+B-1, N); j++)
          r=0; /* to be allocated to a register*/
          for (k=kk; k<min(kk+B-1, N); k++)
            r+= X[i][k] * Y[k][j]
          Z[i][j]=r;
      }

```

Reuse factor of
B-1 for Z, N for Y
 $O(N^3/(B-1))$
accesses to
main memory


*Compiler
should select
best option*



Monica Lam: The Cache Performance and Optimization of Blocked Algorithms, ASPLOS, 1991

Example

In practice, results by Buchwald are disappointing. One of the few cases where an improvement was achieved:
Source: similar to matrix mult.




[Till Buchwald, Diploma thesis, Univ. Dortmund, Informatik 12, 12/2004]

Embedded Real-Time Systems

41

Loop (Nest) Splitting

- Example: Separation of margin handling
 - Regular computation for pixels in image filtering
 - At image margins, neighbors do not exist
 - Straightforward implementation: check boundaries in the inner loop
 - Efficient implementation: Split loops



Embedded Real-Time Systems

42

Loop nest from MPEG-4 full search motion estimation

```

for (z=0; z<20; z++)
for (x=0; x<36; x++) {x1=4*x;
for (y=0; y<49; y++) {y1=4*y;
for (k=0; k<9; k++) {x2=x1+k-4;
for (l=0; l<9; ) {y2=y1+l-4;
for (i=0; i<4; i++) {x3=x1+i; x4=x2+i;
for (j=0; j<4;j++) {y3=y1+j; y4=y2+j;
if (x3<0 || 35<x3||y3<0||48<y3)
then_block_1; else else_block_1;
if (x4<0|| 35<x4||y4<0||48<y4)
then_block_2; else else_block_2;
}}}}

```



analysis of polyhedral domains,
selection with genetic algorithm

```

for (z=0; z<20; z++)
for (x=0; x<36; x++) {x1=4*x;
for (y=0; y<49; y++)

```

```

if (x>=10||y>=14)
for (; y<49; y++)
for (k=0; k<9; k++)
for (l=0; l<9;l++) )
for (i=0; i<4; i++)
for (j=0; j<4;j++) {
then_block_1; then_block_2}
else {y1=4*y;
for (k=0; k<9; k++) {x2=x1+k-4;
for (l=0; l<9; ) {y2=y1+l-4;
for (i=0; i<4; i++) {x3=x1+i; x4=x2+i;
for (j=0; j<4;j++) {y3=y1+j; y4=y2+j;
if (0 || 35<x3 ||0 || 48<y3)
then-block-1; else else-block-1;
if (x4<0|| 35<x4||y4<0||48<y4)
then_block_2; else else_block_2;
}}}}


```

[H. Falk et al., Inf 12, UniDo, 2002]

Embedded Real-Time Systems

43

Results for loop nest splitting - Execution times -




Cycle counts can be reduced by up to about 75% (to 25 % of original value).

[H. Falk et al., Inf 12, UniDo, 2002]

Embedded Real-Time Systems

44

Results for loop nest splitting - Code sizes -



45

Array Folding

- Some applications (e.g., multimedia) include large arrays.
- At any particular time only a subset of array elements is needed.
- Maximum number of elements needed: *address reference window*




Embedded Real-Time Systems

46

Classical Memory Allocation

- Each array is allocated the maximum of the space it requires during the entire execution time
- Unfolded array




Embedded Real-Time Systems


47

Improved Memory Allocation

Inter-array folding



Intra-array folding



Embedded Real-Time Systems

48

Application


- Array folding is implemented in the DTSE optimization proposed by IMEC. Array folding adds div and mod ops. Optimizations required to remove these costly operations.
- At IMEC, ADOPT address optimizations perform this task. For example, modulo operations are replaced by pointers (indexes) which are incremented and reset.

```

for(i=0; i<20; i++)
  B[i % 4];

tmp=0;
for(i=0; i<20; i++)
  if(tmp >= 4)
    tmp -=4;
  B[tmp];
  tmp ++;


```



Embedded Real-Time Systems

49

Results (Mcycles for cavity benchmark)



Embedded Real-Time Systems

50