

ACW Raspberry Pi Kiosk Setup Guide

Follow this guide to make the Pi boot straight into the fullscreen slideshow.

1. Put the project on the Pi

Clone or copy the repository to a stable location. The examples below assume:

```
/opt/acw-screen-updater
```

Then install the Python dependencies:

```
cd /opt/acw-screen-updater
python3 -m pip install -r requirements.txt
```

2. Test the app manually

Run a refresh once, then start the local web app:

```
python3 -m pi_display.refresh
python3 -m pi_display.web
```

Open these URLs on the Pi to confirm the dashboard and display are working:

- <http://localhost:8080/>
- <http://localhost:8080/fullscreen.html?includeClasses=false>

Use the dashboard to upload a promo video and link it to an event. The fullscreen screen should then show the video first and the booking slide second.

3. Install the systemd services

Copy these files from the repository into `/etc/systemd/system/`:

- `systemd/acw-display.service`
- `systemd/acw-refresh.service`
- `systemd/acw-refresh.timer`

Then enable them:

```
sudo systemctl daemon-reload
sudo systemctl enable --now acw-display.service
sudo systemctl enable --now acw-refresh.timer
```

Check service status:

```
sudo systemctl status acw-display.service
sudo systemctl status acw-refresh.timer
```

4. Create the kiosk launcher script

Create this file on the Pi:

```
/opt/acw-screen-updater/scripts/start-kiosk.sh
#!/bin/bash
set -e

export DISPLAY=:0
export XAUTHORITY=/home/pi/.Xauthority

xset s off
xset -dpms
xset s noblank

chromium-browser \
  --kiosk \
```

```
--incognito \  
--disable-infobars \  
--noerrdialogs \  
--check-for-update-interval=31536000 \  
--overscroll-history-navigation=0 \  
http://localhost:8080/fullscreen.html?includeClasses=false
```

Make it executable:

```
chmod +x /opt/acw-screen-updater/scripts/start-kiosk.sh
```

5. Create the autostart desktop entry

If needed, create the autostart folder first:

```
mkdir -p /home/pi/.config/autostart
```

Then create this file:

```
/home/pi/.config/autostart/acw-display.desktop  
[Desktop Entry]  
Type=Application  
Name=ACW Display  
Exec=/opt/acw-screen-updater/scripts/start-kiosk.sh  
X-GNOME-Autostart-enabled=true
```

6. Adjust values if needed

- If your Pi username is not pi, change /home/pi/.Xauthority and the autostart path to match your real home folder.
- If Chromium is installed as chromium instead of chromium-browser, swap that command in the launcher script.
- If you want classes included in the display, change the URL to `http://localhost:8080/fullscreen.html?includeClasses=true`.

7. Reboot and verify

After reboot, the Pi should:

- start the ACW web app
- run scheduled refreshes in the background
- open Chromium in kiosk mode
- display the fullscreen slideshow automatically

From another device on the same network, you can open the dashboard at

`http://<pi-ip>:8080/` to upload videos and change event associations.

8. Useful maintenance commands

```
sudo systemctl restart acw-display.service  
sudo systemctl start acw-refresh.service  
journalctl -u acw-display.service -n 100 --no-pager  
journalctl -u acw-refresh.service -n 100 --no-pager
```

Quick checklist

- Project copied to /opt/acw-screen-updater
- Dependencies installed
- Refresh and web app tested manually

- systemd units enabled
- start-kiosk.sh created and made executable
- acw-display.desktop created
- Pi reboots into the fullscreen display