

viRUs

Team Reference Document

29/07/2015

CONTENTS

1. Code Templates	2
1.1. Basic Configuration	2
1.2. C++ Header	2
1.3. Java Template	2
2. Data Structures	2
2.1. Union-Find	2
2.2. Segment Tree	2
2.3. Fenwick Tree	3
2.4. Matrix	3
2.5. AVL Tree	3
2.6. Heap	5
2.7. Dancing Links	5
2.8. Misof Tree	6
2.9. <i>k</i> -d Tree	6
2.10. Sqrt Decomposition	7
2.11. Monotonic Queue	7
3. Graphs	7
3.1. Single-Source Shortest Paths	7
3.2. Strongly Connected Components	8
3.3. Cut Points and Bridges	8
3.4. Euler Path	8
3.5. Bipartite Matching	9
3.6. Maximum Flow	9
3.7. Minimum Cost Maximum Flow	10
3.8. All Pairs Maximum Flow	11
3.9. Heavy-Light Decomposition	11
3.10. Tarjan’s Off-line Lowest Common Ancestors Algorithm	12
4. Strings	12
4.1. Suffix Array	12
4.2. Aho-Corasick Algorithm	12
4.3. The <i>Z</i> algorithm	13
4.4. Eertree	13
5. Mathematics	13
5.1. Big Integer	13
5.2. Binomial Coefficients	15
5.3. Euclidean algorithm	15
5.4. Trial Division Primality Testing	15
5.5. Miller-Rabin Primality Test	15
5.6. Sieve of Eratosthenes	16
5.7. Modular Multiplicative Inverse	16

5.8. Chinese Remainder Theorem	16
5.9. Linear Congruence Solver	16
5.10. Numeric Integration	16
5.11. Fast Fourier Transform	16
5.12. Formulas	16
5.13. Numbers and Sequences	17
6. Geometry	17
6.1. Primitives	17
6.2. Polygon	18
6.3. Convex Hull	18
6.4. Line Segment Intersection	19
6.5. Great-Circle Distance	19
6.6. Triangle Circumcenter	19
6.7. Closest Pair of Points	19
6.8. 3D Primitives	19
6.9. Polygon Centroid	20
6.10. Formulas	20
7. Other Algorithms	20
7.1. 2SAT	20
7.2. Stable Marriage	21
7.3. Algorithm X	21
7.4. <i>n</i> th Permutation	22
7.5. Cycle-Finding	22
7.6. Dates	22
8. Useful Information	22
8.1. Tips & Tricks	22
8.2. Fast Input Reading	22
8.3. Bit Hacks	22

1. CODE TEMPLATES

1.1. Basic Configuration. Vim and (Caps Lock = Escape) configuration.

```
o.yqtxmal ekrpat # setxkbmap dvorak for dvorak on qwerty
setxkbmap -option caps:escape
set -o vi
xset r rate 150 100
cat > ~/.vimrc
set nosp et sw=4 ts=4 sts=4 si cindent hi=1000 nu ru noeb showcmd showmode
syn on | colorscheme slate
```

1.2. C++ Header. A C++ header.

```
#include <bits/stdc++.h>-----// 84
using namespace std;-----// 16
template <class T> int size(const T &x) { return x.size(); }-----// 5f
#define rep(i,a,b) for (__typeof(a) i=(a); i<(b); ++i)-----// 6c
#define iter(it,c) for (__typeof((c).begin()) it = (c).begin(); it != (c).end(); ++it)
typedef pair<int, int> ii;-----// 44
typedef vector<int> vi;-----// 9d
typedef vector<ii> vii;-----// eb
typedef long long ll;-----// 47
const int INF = 2147483647;-----// db
-----// d8
const double EPS = 1e-9;-----// 18
const double pi = acos(-1);-----// ec
typedef unsigned long long ull;-----// 30
typedef vector<vi> vvi;-----// 92
typedef vector<vii> vvii;-----// fc
template <class T> T mod(T a, T b) { return (a % b + b) % b; }-----// 3f
```

1.3. Java Template. A Java template.

```
import java.util.*;-----// 37
import java.math.*;-----// 89
import java.io.*;-----// 28
-----// a3
public class Main {-----// 17
---public static void main(String[] args) throws Exception {-----// 02
-----Scanner in = new Scanner(System.in);-----// ef
-----PrintWriter out = new PrintWriter(System.out, false);-----// 62
-----// code-----// e6
-----out.flush();-----// 56
---}-----// 79
}-----// 00
```

2. DATA STRUCTURES

2.1. Union-Find.

```
struct union_find {-----// 42
---vi p; union_find(int n) : p(n, -1) { }-----// 28
---int find(int x) { return p[x] < 0 ? x : p[x] = find(p[x]); }-----// ba
---bool unite(int x, int y) {-----// 6c
-----int xp = find(x), yp = find(y);-----// 64
-----if (xp == yp) return false;-----// 0b
```

```
-----if (p[xp] < p[yp]) p[xp] += p[yp], p[yp] = xp;-----// 3a
-----else p[yp] += p[xp], p[xp] = yp;-----// 3e
-----return true; }-----// 0b
----int size(int x) { return -p[find(x)]; } };-----// 28
```

2.2. Segment Tree.

```
#ifdef SEG_MIN-----// 03
const int ID = INF;-----// 56
int f(int a, int b) { return min(a, b); }-----// 4f
#else-----// 0e
const int ID = 0;-----// 3e
int f(int a, int b) { return a + b; }-----// dd
#endif-----// 16
struct segment_tree {-----// ab
---int n; vi data, lazy;-----// dd
---segment_tree() {}-----// 93
---segment_tree(const vi &arr) : n(size(arr)), data(4*n), lazy(4*n,INF) {-----// f1
---mk(arr, 0, n-1, 0); }-----// e9
---int mk(const vi &arr, int l, int r, int i) {-----// 12
---if (l == r) return data[i] = arr[l];-----// 5b
---int m = (l + r) / 2;-----// de
---return data[i] = f(mk(arr, l, m, 2*i+1), mk(arr, m+1, r, 2*i+2)); }-----// 0a
---int query(int a, int b) { return q(a, b, 0, n-1, 0); }-----// f6
---int q(int a, int b, int l, int r, int i) {-----// 22
---propagate(l, r, i);-----// 12
---if (r < a || b < l) return ID;-----// c7
---if (a <= l && r <= b) return data[i];-----// ce
---int m = (l + r) / 2;-----// 7a
---return f(q(a, b, l, m, 2*i+1), q(a, b, m+1, r, 2*i+2)); }-----// 5c
---void update(int i, int v) { u(i, v, 0, n-1, 0); }-----// 90
---int u(int i, int v, int l, int r, int j) {-----// 02
---propagate(l, r, j);-----// ae
---if (r < i || i < l) return data[j];-----// 92
---if (l == i && r == i) return data[j] = v;-----// 4a
---int m = (l + r) / 2;-----// cb
---return data[j] = f(u(i, v, l, m, 2*j+1), u(i, v, m+1, r, 2*j+2)); }-----// 34
---void range_update(int a, int b, int v) { ru(a, b, v, 0, n-1, 0); }-----// 71
---int ru(int a, int b, int v, int l, int r, int i) {-----// e0
---propagate(l, r, i);-----// 19
---if (l > r) return ID;-----// cc
---if (r < a || b < l) return data[i];-----// d9
---if (l == r) return data[i] += v;-----// 5f
---if (a <= l && r <= b) return (lazy[i] = v) * (r - l + 1) + data[i];-----// 76
---int m = (l + r) / 2;-----// e7
---return data[i] = f(ru(a, b, v, l, m, 2*i+1),-----// 0e
---ru(a, b, v, m+1, r, 2*i+2)); }-----// f2
---}-----// 47
---void propagate(int l, int r, int i) {-----// b5
---if (l > r || lazy[i] == INF) return;-----// 83
---data[i] += lazy[i] * (r - l + 1);-----// 99
---if (l < r) {-----// dd
```

```

-----if (lazy[2*i+1] == INF) lazy[2*i+1] = lazy[i];-----// ee
-----else lazy[2*i+1] += lazy[i];-----// 72
-----if (lazy[2*i+2] == INF) lazy[2*i+2] = lazy[i];-----// dd
-----else lazy[2*i+2] += lazy[i];-----// a4
-----}-----// e9
-----lazy[i] = INF;-----// c4
-----}-----// 2c
};-----// 17

```

2.3. Fenwick Tree.

```

struct fenwick_tree {-----// 98
--int n; vi data;-----// d3
---fenwick_tree(int _n) : n(_n), data(vi(n)) { }-----// db
---void update(int at, int by) {-----// 76
-----while (at < n) data[at] += by, at |= at + 1; }-----// fb
---int query(int at) {-----// 71
-----int res = 0;-----// c3
-----while (at >= 0) res += data[at], at = (at & (at + 1)) - 1;-----// 37
-----return res; }-----// e4
---int rsq(int a, int b) { return query(b) - query(a - 1); }-----// be
};-----// 57
struct fenwick_tree_sq {-----// d4
--int n; fenwick_tree x1, x0;-----// 18
---fenwick_tree_sq(int _n) : n(_n), x1(fenwick_tree(n)),-----// 2e
-----x0(fenwick_tree(n)) { }-----// 7c
---// insert f(y) = my + c if x <= y-----// 17
---void update(int x, int m, int c) { x1.update(x, m); x0.update(x, c); }-----// 45
---int query(int x) { return x*x1.query(x) + x0.query(x); }-----// 73
};-----// 13
void range_update(fenwick_tree_sq &s, int a, int b, int k) {-----// 89
---s.update(a, k, k * (1 - a)); s.update(b+1, -k, k * b); }-----// 7f
int range_query(fenwick_tree_sq &s, int a, int b) {-----// 15
---return s.query(b) - s.query(a-1); }-----// f3

```

2.4. Matrix.

```

template <class K> bool eq(K a, K b) { return a == b; }-----// 2a
template <> bool eq<double>(double a, double b) { return abs(a - b) < EPS; }-----// a7
template <class T>-----// 53
class matrix {-----// 85
public:-----// be
---int rows, cols;-----// d3
---matrix(int r, int c) : rows(r), cols(c), cnt(r * c) {-----// 34
-----data.assign(cnt, T(0)); }-----// d0
---matrix(const matrix& other) : rows(other.rows), cols(other.cols),-----// fe
-----cnt(other.cnt), data(other.data) { }-----// ed
---T& operator()(int i, int j) { return at(i, j); }-----// e0
---void operator +=(const matrix& other) {-----// c9
-----rep(i,0,cnt) data[i] += other.data[i]; }-----// 2e
---void operator -=(const matrix& other) {-----// f2
-----rep(i,0,cnt) data[i] -= other.data[i]; }-----// 52
---void operator *=(T other) {-----// 14
-----rep(i,0,cnt) data[i] *= other; }-----// dd

```

```

---matrix<T> operator +(const matrix& other) {-----// cb
---matrix<T> res(*this); res += other; return res; }-----// d5
---matrix<T> operator -(const matrix& other) {-----// a0
---matrix<T> res(*this); res -= other; return res; }-----// f5
---matrix<T> operator *(T other) {-----// 60
---matrix<T> res(*this); res *= other; return res; }-----// 73
---matrix<T> operator *(const matrix& other) {-----// 0a
---matrix<T> res(rows, other.cols);-----// d7
---rep(i,0,rows) rep(j,0,other.cols) rep(k,0,cols)-----// 4b
-----res(i, j) += at(i, k) * other.data[k * other.cols + j];-----// 08
---return res; }-----// 58
---matrix<T> transpose() {-----// 3a
---matrix<T> res(cols, rows);-----// fe
---rep(i,0,rows) rep(j,0,cols) res(j, i) = at(i, j);-----// 2b
---return res; }-----// 23
---matrix<T> pow(int p) {-----// da
---matrix<T> res(rows, cols), sq(*this);-----// e6
---rep(i,0,rows) res(i, i) = T(1);-----// 09
---while (p) {-----// ea
---if (p & 1) res = res * sq;-----// 66
---p >>= 1;-----// 17
---if (p) sq = sq * sq;-----// 85
---} return res; }-----// 18
---matrix<T> rref(T &det) {-----// bd
---matrix<T> mat(*this); det = T(1);-----// 6b
---for (int r = 0, c = 0; c < cols; c++) {-----// 33
---int k = r;-----// 42
---while (k < rows && eq<T>(mat(k, c), T(0))) k++;-----// 59
---if (k >= rows) continue;-----// aa
---if (k != r) {-----// fd
---det *= T(-1);-----// 06
---rep(i,0,cols)-----// 2f
---swap(mat.at(k, i), mat.at(r, i));-----// 01
---} det *= mat(r, r);-----// 35
---T d = mat(r,c);-----// 31
---rep(i,0,cols) mat(r, i) /= d;-----// 9e
---rep(i,0,rows) {-----// d3
---T m = mat(i, c);-----// 0f
---if (i != r && !eq<T>(m, T(0)))-----// ba
---rep(j,0,cols) mat(i, j) -= m * mat(r, j);-----// 30
---} r++;-----// 48
---} return mat; }-----// f6
private:-----// a6
---int cnt;-----// 99
---vector<T> data;-----// 7a
---inline T& at(int i, int j) { return data[i * cols + j]; }-----// b6
};-----// b3

```

2.5. AVL Tree.

```

#define AVL_MULTISSET 0-----// b5
-----// 61

```

```

template <class T>-----// 22
class avl_tree {-----// ff
public:-----// f6
    struct node {-----// 45
        T item; node *p, *l, *r;-----// a6
        int size, height;-----// 33
        node(const T &item, node *p = NULL) : item(item), p(p),-----// 4f
            l(NULL), r(NULL), size(1), height(0) { } };-----// 0d
    avl_tree() : root(NULL) { }-----// 5d
    node *root;-----// 91
    node* find(const T &item) const {-----// 65
        node *cur = root;-----// b4
        while (cur) {-----// 8b
            if (cur->item < item) cur = cur->r;-----// 71
            else if (item < cur->item) cur = cur->l;-----// cd
            else break; }-----// 4f
        return cur; }-----// 84
    node* insert(const T &item) {-----// 4e
        node *prev = NULL, **cur = &root;-----// 60
        while (*cur) {-----// aa
            prev = *cur;-----// f0
            if ((*cur)->item < item) cur = &((*cur)->r);-----// 1b
        }-----// 0a
        if AVL_MULTISSET-----// eb
            else cur = &((*cur)->l);-----// ff
        else-----// ff
            else if (item < (*cur)->item) cur = &((*cur)->l);-----// 54
            else return *cur;-----// 54
        }-----// af
    }-----// ec
    node *n = new node(item, prev);-----// eb
    *cur = n, fix(n); return n; }-----// 29
    void erase(const T &item) { erase(find(item)); }-----// 67
    void erase(node *n, bool free = true) {-----// 58
        if (!n) return;-----// 96
        if (!n->l && n->r) parent_leg(n) = n->r, n->r->p = n->p;-----// 12
        else if (n->l && !n->r) parent_leg(n) = n->l, n->l->p = n->p;-----// 6b
        else if (n->l && n->r) {-----// 6c
            node *s = successor(n);-----// e5
            erase(s, false);-----// 0a
            s->p = n->p, s->l = n->l, s->r = n->r;-----// 5a
            if (n->l) n->l->p = s;-----// 0b
            if (n->r) n->r->p = s;-----// ed
            parent_leg(n) = s, fix(s);-----// 82
            return;-----// e5
        } else parent_leg(n) = NULL;-----// de
        fix(n->p), n->p = n->l = n->r = NULL;-----// 43
        if (free) delete n; }-----// 23
    node* successor(node *n) const {-----// 23
        if (!n) return NULL;-----// 37
        if (n->r) return nth(0, n->r);-----// 23
        node *p = n->p;-----// a7
        while (p && p->r == n) n = p, p = p->p;-----// 9e
        return p; }-----// c7
    node* predecessor(node *n) const {-----// b4
        if (!n) return NULL;-----// dd
        if (n->l) return nth(n->l->size-1, n->l);-----// 10
        node *p = n->p;-----// ea
        while (p && p->l == n) n = p, p = p->p;-----// 6d
        return p; }-----// e7
    inline int size() const { return sz(root); }-----// ef
    void clear() { delete_tree(root), root = NULL; }-----// 84
    node* nth(int n, node *cur = NULL) const {-----// e4
        if (!cur) cur = root;-----// e5
        while (cur) {-----// 29
            if (n < sz(cur->l)) cur = cur->l;-----// 75
            else if (n > sz(cur->l)) n -= sz(cur->l) + 1, cur = cur->r;-----// cd
            else break;-----// c0
        } return cur; }-----// ed
    int count_less(node *cur) {-----// ec
        int sum = sz(cur->l);-----// bf
        while (cur) {-----// 6f
            if (cur->p && cur->p->r == cur) sum += 1 + sz(cur->p->l);-----// 5c
            cur = cur->p;-----// eb
        } return sum; }-----// a0
private:-----// d5
    inline int sz(node *n) const { return n ? n->size : 0; }-----// 3f
    inline int height(node *n) const { return n ? n->height : -1; }-----// a6
    inline bool left_heavy(node *n) const {-----// a0
        return n && height(n->l) > height(n->r); }-----// a8
    inline bool right_heavy(node *n) const {-----// 27
        return n && height(n->r) > height(n->l); }-----// c8
    inline bool too_heavy(node *n) const {-----// 0b
        return n && abs(height(n->l) - height(n->r)) > 1; }-----// f8
    void delete_tree(node *n) {-----// fd
        if (n) { delete_tree(n->l), delete_tree(n->r); delete n; } }-----// ef
    node*& parent_leg(node *n) {-----// 6a
        if (!n->p) return root;-----// ac
        if (n->p->l == n) return n->p->l;-----// 83
        if (n->p->r == n) return n->p->r;-----// cc
        assert(false); }-----// 20
    void augment(node *n) {-----// 72
        if (!n) return;-----// 0e
        n->size = 1 + sz(n->l) + sz(n->r);-----// 93
        n->height = 1 + max(height(n->l), height(n->r)); }-----// 41
#define rotate(l, r) \
    node *l = n->l; \
    l->p = n->p; \
    parent_leg(n) = l; \
    n->l = l->r; \
    if (l->r) l->r->p = n; \
    l->r = n, n->p = l;

```

Reykjavík University

5

-----augment(n), augment(l)-----// 81

---void left_rotate(node *n) { rotate(r, l); }-----// 45

---void right_rotate(node *n) { rotate(l, r); }-----// ca

---void fix(node *n) {-----// 0d

-----while (n) { augment(n);-----// 69

-----if (too_heavy(n)) {-----// 4c

-----if (left_heavy(n) && right_heavy(n->l)) left_rotate(n->l);-----// a9

-----else if (right_heavy(n) && left_heavy(n->r))-----// b9

-----right_rotate(n->r);-----// 08

-----if (left_heavy(n)) right_rotate(n);-----// 93

-----else left_rotate(n);-----// d5

-----n = n->p; }-----// 28

-----n = n->p; } } }-----// a2

-----rep(i,0,len) newq[i] = q[i], newloc[i] = loc[i];-----// d7

-----memset(newloc + len, 255, (newlen - len) << 2);-----// 3e

-----delete[] q, delete[] loc;-----// 76

-----loc = newloc, q = newq, len = newlen;-----// 9e

#else-----// 8e

-----assert(false);-----// 23

#endif-----// 2a

-----}-----// 37

-----assert(loc[n] == -1);-----// 4e

-----loc[n] = count, q[count++] = n;-----// cf

-----if (fix) swim(count-1); }-----// b9

---void pop(bool fix = true) {-----// 4f

-----assert(count > 0);-----// 4d

-----loc[q[0]] = -1, q[0] = q[--count], loc[q[0]] = 0;-----// 66

-----if (fix) sink(0);-----// bb

-----}-----// bc

---int top() { assert(count > 0); return q[0]; }-----// 1f

---void heapify() { for (int i = count - 1; i > 0; i--)-----// d5

-----if (cmp(i, (i - 1) / 2)) swp(i, (i - 1) / 2); }-----// 43

---void update_key(int n) {-----// 62

-----assert(loc[n] != -1), swim(loc[n]), sink(loc[n]); }-----// ca

---bool empty() { return count == 0; }-----// 7e

---int size() { return count; }-----// 5f

---void clear() { count = 0, memset(loc, 255, len << 2); } }-----// de

2.6. Heap.

#define RESIZE-----// d0

#define SWP(x,y) tmp = x, x = y, y = tmp-----// fb

struct default_int_cmp {-----// 8d

---default_int_cmp() { }-----// 35

---bool operator()(const int &a, const int &b) { return a < b; } }-----// e9

template <class Compare = default_int_cmp>-----// 30

class heap {-----// 05

private:-----// 39

---int len, count, *q, *loc, tmp;-----// 0a

---Compare _cmp;-----// 98

---inline bool cmp(int i, int j) { return _cmp(q[i], q[j]); }-----// a0

---inline void swp(int i, int j) {-----// 1c

-----SWP(q[i], q[j]), SWP(loc[q[i]], loc[q[j]]); }-----// 67

---void swim(int i) {-----// 33

-----while (i > 0) {-----// 1a

-----int p = (i - 1) / 2;-----// 77

-----if (!cmp(i, p)) break;-----// a9

-----swp(i, p), i = p; } }-----// 93

---void sink(int i) {-----// ce

-----while (true) {-----// 3c

-----int l = 2*i + 1, r = l + 1;-----// b4

-----if (l >= count) break;-----// d5

-----int m = r >= count || cmp(l, r) ? l : r;-----// cc

-----if (!cmp(m, i)) break;-----// 42

-----swp(m, i), i = m; } }-----// 1d

public:-----// cd

---heap(int init_len = 128) : count(0), len(init_len), _cmp(Compare()) {-----// 17

-----q = new int[len], loc = new int[len];-----// f8

-----memset(loc, 255, len << 2); }-----// f7

---heap() { delete[] q; delete[] loc; }-----// 09

---void push(int n, bool fix = true) {-----// b7

-----if (len == count || n >= len) {-----// 0f

#ifdef RESIZE-----// a9

-----int newlen = 2 * len;-----// 22

-----while (n >= newlen) newlen *= 2;-----// 2f

-----int *newq = new int[newlen], *newloc = new int[newlen];-----// e3

2.7. Dancing Links.

template <class T>-----// 82

struct dancing_links {-----// 9e

---struct node {-----// 62

-----T item;-----// dd

-----node *l, *r;-----// 32

-----node(const T &item, node *_l = NULL, node *_r = NULL)-----// 6d

-----: item(_item), l(_l), r(_r) {-----// 6d

-----if (l) l->r = this;-----// 97

-----if (r) r->l = this;-----// 81

-----}-----// 2d

};-----// d3

---node *front, *back;-----// aa

---dancing_links() { front = back = NULL; }-----// 72

---node *push_back(const T &item) {-----// 83

-----back = new node(item, back, NULL);-----// c4

-----if (!front) front = back;-----// d2

-----return back;-----// c0

};-----// a9

---node *push_front(const T &item) {-----// 4a

-----front = new node(item, NULL, front);-----// 47

-----if (!back) back = front;-----// 10

-----return front;-----// cf

};-----// b6

---void erase(node *n) {-----// a0

-----if (!n->l) front = n->r; else n->l->r = n->r;-----// ab

```

-----if (!n->r) back = n->l; else n->r->l = n->l;-----// 1b
--}-// 7b
--void restore(node *n) {-----// 82
-----if (!n->l) front = n; else n->l->r = n;-----// a5
-----if (!n->r) back = n; else n->r->l = n;-----// 9d
--}-// eb
};-----// 5e

```

2.8. Misof Tree.

```

#define BITS 15-----// 7b
struct misof_tree {-----// fe
--int cnt[BITS][1<<BITS];-----// aa
--misof_tree() { memset(cnt, 0, sizeof(cnt)); }-----// b0
--void insert(int x) { for (int i = 0; i < BITS; cnt[i++][x]++, x >= 1); }-----// 5a
--void erase(int x) { for (int i = 0; i < BITS; cnt[i++][x]--, x >= 1); }-----// 49
--int nth(int n) {-----// 8a
--int res = 0;-----// a4
--for (int i = BITS-1; i >= 0; i--)-----// 99
--if (cnt[i][res <= 1] <= n) n -= cnt[i][res], res |= 1;-----// f4
--return res;-----// 3a
--}-// b5
};-----// 0a

```

2.9. k-d Tree.

```

#define INC(c) ((c) == K - 1 ? 0 : (c) + 1)-----// 77
template <int K>-----// cd
class kd_tree {-----// 7e
public:-----// c7
--struct pt {-----// 78
--double coord[K];-----// d6
--pt() {}-----// c1
--pt(double c[K]) { rep(i,0,K) coord[i] = c[i]; }-----// 15
--double dist(const pt &other) const {-----// a5
--double sum = 0.0;-----// 6c
--rep(i,0,K) sum += pow(coord[i] - other.coord[i], 2.0);-----// 5e
--return sqrt(sum); } }-----// ba
--struct cmp {-----// de
--int c;-----// a9
--cmp(int _c) : c(_c) {}-----// a0
--bool operator()(const pt &a, const pt &b) {-----// 00
--for (int i = 0, cc; i <= K; i++) {-----// a7
--cc = i == 0 ? c : i - 1;-----// 36
--if (abs(a.coord[cc] - b.coord[cc]) > EPS)-----// 54
--return a.coord[cc] < b.coord[cc];-----// f4
--}-----// 72
--return false; } }-----// b9
--struct bb {-----// 2d
--pt from, to;-----// 66
--bb(pt _from, pt _to) : from(_from), to(_to) {}-----// 93
--double dist(const pt &p) {-----// f4
--double sum = 0.0;-----// 16
--rep(i,0,K) {-----// fc

```

```

-----if (p.coord[i] < from.coord[i])-----// a9
--sum += pow(from.coord[i] - p.coord[i], 2.0);-----// ed
-----else if (p.coord[i] > to.coord[i])-----// d7
--sum += pow(p.coord[i] - to.coord[i], 2.0);-----// 7a
--}-// 21
--return sqrt(sum); }-----// 53
--bb bound(double l, int c, bool left) {-----// 9c
--pt nf(from.coord), nt(to.coord);-----// 39
--if (left) nt.coord[c] = min(nt.coord[c], l);-----// 2a
--else nf.coord[c] = max(nf.coord[c], l);-----// fc
--return bb(nf, nt); } }-----// d7
--struct node {-----// 04
--pt p; node *l, *r;-----// cf
--node(pt _p, node *_l, node *_r) : p(_p), l(_l), r(_r) { } }-----// cb
--node *root;-----// 16
--// kd_tree() : root(NULL) { }-----// 66
--kd_tree(vector<pt> pts) { root = construct(pts, 0, size(pts) - 1, 0); }-----// 35
--node* construct(vector<pt> &pts, int from, int to, int c) {-----// 4f
--if (from > to) return NULL;-----// 87
--int mid = from + (to - from) / 2;-----// ac
--nth_element(pts.begin() + from, pts.begin() + mid,-----// c0
--pts.begin() + to + 1, cmp());-----// d3
--return new node(pts[mid], construct(pts, from, mid - 1, INC(c)),-----// 36
--construct(pts, mid + 1, to, INC(c))); }-----// 97
--bool contains(const pt &p) { return _con(p, root, 0); }-----// fd
--bool _con(const pt &p, node *n, int c) {-----// 82
--if (!n) return false;-----// d7
--if (cmp(c)(p, n->p)) return _con(p, n->l, INC(c));-----// 46
--if (cmp(c)(n->p, p)) return _con(p, n->r, INC(c));-----// 1c
--return true; }-----// 58
--void insert(const pt &p) { _ins(p, root, 0); }-----// 1e
--void _ins(const pt &p, node* &n, int c) {-----// 80
--if (!n) n = new node(p, NULL, NULL);-----// 3b
--else if (cmp(c)(p, n->p)) _ins(p, n->l, INC(c));-----// cb
--else if (cmp(c)(n->p, p)) _ins(p, n->r, INC(c)); }-----// 2b
--void clear() { _clr(root); root = NULL; }-----// 56
--void _clr(node *n) { if (n) _clr(n->l), _clr(n->r), delete n; }-----// 43
--pt nearest_neighbour(const pt &p, bool allow_same=true) {-----// f1
--assert(root);-----// c0
--double mn = INFINITY, cs[K];-----// 66
--rep(i,0,K) cs[i] = -INFINITY;-----// e4
--pt from(cs);-----// d3
--rep(i,0,K) cs[i] = INFINITY;-----// c9
--pt to(cs);-----// 4e
--return _nn(p, root, bb(from, to), mn, 0, allow_same).first;-----// ae
--}-----// a0
--pair<pt, bool> _nn(-----// cd
--const pt &p, node *n, bb b, double &mn, int c, bool same) {-----// 65
--if (!n || b.dist(p) > mn) return make_pair(pt(), false);-----// 6f
--bool found = same || p.dist(n->p) > EPS, l1 = true, l2 = false;-----// a1
--pt resp = n->p;-----// b7

```


Reykjavík University7

-----if (found) mn = min(mn, p.dist(resp));-----// 4d

-----node *n1 = n->l, *n2 = n->r;-----// 49

-----rep(i,0,2) {-----// 07

-----if (i == 1 || cmp(c)(n->p, p)) swap(n1, n2), swap(l1, l2);-----// 2b

-----pair<pt, bool> res =-----// 6e

-----_nn(p, n1, b.bound(n->p.coord[c], c, l1), mn, INC(c), same);-----// 6a

-----if (res.second && (!found || p.dist(res.first) < p.dist(resp)))-----// f6

-----resp = res.first, found = true;-----// 37

-----}-----// 57

-----return make_pair(resp, found); } }-----// 05

void push(int x) {-----// 20

-----S.push(x);-----// e2

-----M.push(M.empty() ? x : min(M.top(), x)); }-----// 92

-----int top() { return S.top(); }-----// f1

-----int mn() { return M.top(); }-----// 02

-----void pop() { S.pop(); M.pop(); }-----// fd

-----bool empty() { return S.empty(); }-----// d2

};-----// 74

struct min_queue {-----// b4

-----min_stack inp, outp;-----// 3d

-----void push(int x) { inp.push(x); }-----// 6b

-----void fix() {-----// 5d

-----if (outp.empty()) while (!inp.empty())-----// 3b

-----outp.push(inp.top()), inp.pop();-----// 8e

-----}-----// 3f

-----int top() { fix(); return outp.top(); }-----// dc

-----int mn() {-----// 39

-----if (inp.empty()) return outp.mn();-----// 01

-----if (outp.empty()) return inp.mn();-----// 90

-----return min(inp.mn(), outp.mn()); }-----// 97

-----void pop() { fix(); outp.pop(); }-----// 4f

-----bool empty() { return inp.empty() && outp.empty(); }-----// 65

};-----// 60

2.10. Sqrt Decomposition.

struct segment {-----// b2

-----vi arr;-----// 8c

-----segment(vi _arr) : arr(_arr) { } }-----// 11

vector<segment> T;-----// a1

int K;-----// dc

void rebuild() {-----// 17

-----int cnt = 0;-----// 14

-----rep(i,0,size(T))-----// b1

-----cnt += size(T[i].arr);-----// d1

-----K = static_cast<int>(ceil(sqrt(cnt)) + 1e-9);-----// 4c

-----vi arr(cnt);-----// 14

-----for (int i = 0, at = 0; i < size(T); i++)-----// 79

-----rep(j,0,size(T[i].arr))-----// a4

-----arr[at++] = T[i].arr[j];-----// f7

-----T.clear();-----// 4c

-----for (int i = 0; i < cnt; i += K)-----// 79

-----T.push_back(segment(vi(arr.begin()+i, arr.begin()+min(i+K, cnt))));-----// f0

}-----// 03

int split(int at) {-----// 71

-----int i = 0;-----// 8a

-----while (i < size(T) && at >= size(T[i].arr))-----// 6c

-----at -= size(T[i].arr), i++;-----// 9a

-----if (i >= size(T)) return size(T);-----// 83

-----if (at == 0) return i;-----// 49

-----T.insert(T.begin() + i + 1, segment(vi(T[i].arr.begin() + at, T[i].arr.end())));-----// af

-----T[i] = segment(vi(T[i].arr.begin(), T[i].arr.begin() + at));-----// ac

-----return i + 1;-----// ea

}-----// 5f

void insert(int at, int v) {-----// 6a

-----vi arr; arr.push_back(v);-----// 67

-----T.insert(T.begin() + split(at), segment(arr));-----// cc

}-----// be

void erase(int at) {-----// da

-----int i = split(at); split(at + 1);-----// 6b

-----T.erase(T.begin() + i);-----// 4b

}-----// 4b

2.11. Monotonic Queue.

struct min_stack {-----// d8

-----stack<int> S, M;-----// fe

3. GRAPHS

3.1. Single-Source Shortest Paths.

3.1.1. Dijkstra's algorithm.

int *dist, *dad;-----// 46

struct cmp {-----// a5

-----bool operator()(int a, int b) {-----// bb

-----return dist[a] != dist[b] ? dist[a] < dist[b] : a < b; }-----// e6

};-----// 41

pair<int*, int*> dijkstra(int n, int s, vii *adj) {-----// 53

-----dist = new int[n];-----// 84

-----dad = new int[n];-----// 05

-----rep(i,0,n) dist[i] = INF, dad[i] = -1;-----// 80

-----set<int, cmp> pq;-----// 98

-----dist[s] = 0, pq.insert(s);-----// 1f

-----while (!pq.empty()) {-----// 47

-----int cur = *pq.begin(); pq.erase(pq.begin());-----// 58

-----rep(i,0,size(adj[cur])) {-----// a6

-----int nxt = adj[cur][i].first,-----// a4

-----ndist = dist[cur] + adj[cur][i].second;-----// 3a

-----if (ndist < dist[nxt]) pq.erase(nxt),-----// 2d

-----dist[nxt] = ndist, dad[nxt] = cur, pq.insert(nxt);-----// eb

-----}-----// d2

-----}-----// df

-----return pair<int*, int*>(dist, dad);-----// e3

}-----// 9b

3.1.2. Bellman-Ford algorithm.

```

int* bellman_ford(int n, int s, vii* adj, bool& has_negative_cycle) {-----// cf
---has_negative_cycle = false;-----// 47
---int* dist = new int[n];-----// 7f
---rep(i,0,n) dist[i] = i == s ? 0 : INF;-----// df
---rep(i,0,n-1) rep(j,0,n) if (dist[j] != INF)-----// 4d
-----rep(k,0,size(adj[j]))-----// 88
-----dist[adj[j][k].first] = min(dist[adj[j][k].first],
-----dist[j] + adj[j][k].second);-----// e1
---rep(j,0,n) rep(k,0,size(adj[j]))-----// f8
---if (dist[j] + adj[j][k].second < dist[adj[j][k].first])-----// 37
-----has_negative_cycle = true;-----// f1
---return dist;-----// 78
}-----// a9

```

3.2. Strongly Connected Components.

3.2.1. Kosaraju's algorithm.

```

#include "../data-structures/union_find.cpp"-----// 5e
-----// 11
vector<bool> visited;-----// 66
vi order;-----// 9b
-----// a5

void scc_dfs(const vvi &adj, int u) {-----// a1
---int v; visited[u] = true;-----// e3
---rep(i,0,size(adj[u]))-----// 2d
---if (!visited[v = adj[u][i]]) scc_dfs(adj, v);-----// a2
---order.push_back(u);-----// 02
}-----// 53
-----// 63

pair<union_find, vi> scc(const vvi &adj) {-----// c2
---int n = size(adj), u, v;-----// f8
---order.clear();-----// 20
---union_find uf(n);-----// a8
---vi dag;-----// 61
---vvi rev(n);-----// c5
---rep(i,0,n) rep(j,0,size(adj[i])) rev[adj[i][j]].push_back(i);-----// 7e
---visited.resize(n, fill(visited.begin(), visited.end(), false));-----// 80
---rep(i,0,n) if (!visited[i]) scc_dfs(rev, i);-----// 4e
---fill(visited.begin(), visited.end(), false);-----// 59
---stack<int> S;-----// bb
---for (int i = n-1; i >= 0; i--) {-----// 96
-----if (visited[order[i]]) continue;-----// db
-----S.push(order[i]), dag.push_back(order[i]);-----// 68
-----while (!S.empty()) {-----// 9e
-----visited[u = S.top()] = true, S.pop(), uf.unite(u, order[i]);-----// b3
-----rep(j,0,size(adj[u])) if (!visited[v = adj[u][j]]) S.push(v);-----// 1b
-----}-----// 61
---}-----// 57
---return pair<union_find, vi>(uf, dag);-----// 2b
}-----// 92

```

3.3. Cut Points and Bridges.

```

#define MAXN 5000-----// f7
int low[MAXN], num[MAXN], curnum;-----// d7
void dfs(const vvi &adj, vi &cp, vii &bri, int u, int p) {-----// 22
---low[u] = num[u] = curnum++;-----// a3
---int cnt = 0; bool found = false;-----// 97
---rep(i,0,size(adj[u])) {-----// ae
-----int v = adj[u][i];-----// 56
-----if (num[v] == -1) {-----// 3b
-----dfs(adj, cp, bri, v, u);-----// ba
-----low[u] = min(low[u], low[v]);-----// be
-----cnt++;-----// e0
-----found = found || low[v] >= num[u];-----// 30
-----if (low[v] > num[u]) bri.push_back(ii(u, v));-----// bf
-----} else if (p != v) low[u] = min(low[u], num[v]); }-----// 76
---if (found && (p != -1 || cnt > 1)) cp.push_back(u); }-----// 3e
pair<vi,vii> cut_points_and_bridges(const vvi &adj) {-----// 76
---int n = size(adj);-----// c8
---vi cp; vii bri;-----// fb
---memset(num, -1, n << 2);-----// 45
---curnum = 0;-----// 07
---rep(i,0,n) if (num[i] == -1) dfs(adj, cp, bri, i, -1);-----// 7e
---return make_pair(cp, bri); }-----// 4c

```

3.4. Euler Path.

```

#define MAXV 1000-----// 2f
#define MAXE 5000-----// 87
vi adj[MAXV];-----// ff
int n, m, indeg[MAXV], outdeg[MAXV], res[MAXE + 1];-----// 49
ii start_end() {-----// 30
---int start = -1, end = -1, any = 0, c = 0;-----// 74
---rep(i,0,n) {-----// 20
-----if (outdeg[i] > 0) any = i;-----// 63
-----if (indeg[i] + 1 == outdeg[i]) start = i, c++;-----// 5a
-----else if (indeg[i] == outdeg[i] + 1) end = i, c++;-----// 13
-----else if (indeg[i] != outdeg[i]) return ii(-1,-1);-----// c1
---}-----// ed
---if ((start == -1) != (end == -1) || (c != 2 && c != 0)) return ii(-1,-1);-----// 54
---if (start == -1) start = end = any;-----// 5e
---return ii(start, end);-----// a2
}-----// eb

bool euler_path() {-----// b4
---ii se = start_end();-----// 8a
---int cur = se.first, at = m + 1;-----// b6
---if (cur == -1) return false;-----// ac
---stack<int> s;-----// 1c
---while (true) {-----// b3
-----if (outdeg[cur] == 0) {-----// 0d
-----res[--at] = cur;-----// bd
-----if (s.empty()) break;-----// c6
-----cur = s.top(); s.pop();-----// 06

```



```
-----} else s.push(cur), cur = adj[cur][--outdeg[cur]];-----// 9e
---}------// a4
---return at == 0;-----// ac
}------// 22
```

3.5. Bipartite Matching.

3.5.1. Alternating Paths algorithm.

```
vi* adj;-----// cc
bool* done;-----// b1
int* owner;-----// 26
int alternating_path(int left) {-----// da
---if (done[left]) return 0;-----// 08
---done[left] = true;-----// f2
---rep(i,0,size(adj[left])) {-----// 1b
-----int right = adj[left][i];-----// 46
-----if (owner[right] == -1 || alternating_path(owner[right])) {-----// f6
-----owner[right] = left; return 1;-----// f2
-----} }-----// 88
---return 0; }-----// 41
```

3.5.2. Hopcroft-Karp algorithm. Running time is $O(|E|\sqrt{|V|})$.

```
#define MAXN 5000-----// f7
int dist[MAXN+1], q[MAXN+1];-----// b8
#define dist(v) dist[v == -1 ? MAXN : v]-----// 0f
struct bipartite_graph {-----// 2b
---int N, M, *L, *R; vi *adj;-----// fc
---bipartite_graph(int _N, int _M) : N(_N), M(_M),-----// 8d
-----L(new int[N]), R(new int[M]), adj(new vi[N]) {}-----// cd
---bipartite_graph() { delete[] adj; delete[] L; delete[] R; }-----// 89
---bool bfs() {-----// f5
-----int l = 0, r = 0;-----// 37
-----rep(v,0,N) if(L[v] == -1) dist(v) = 0, q[r++] = v;-----// f9
-----else dist(v) = INF;-----// aa
-----dist(-1) = INF;-----// f2
-----while(l < r) {-----// ba
-----int v = q[l++];-----// 50
-----if(dist(v) < dist(-1)) {-----// f1
-----iter(u, adj[v]) if(dist(R[*u]) == INF)-----// 9b
-----dist(R[*u]) = dist(v) + 1, q[r++] = R[*u];-----// 79
-----}-----// b8
-----}-----// 0d
---return dist(-1) != INF;-----// 43
---}-----// 2c
---bool dfs(int v) {-----// 26
---if(v != -1) {-----// d8
---iter(u, adj[v])-----// 99
---if(dist(R[*u]) == dist(v) + 1)-----// 74
---if(dfs(R[*u])) {-----// 40
---R[*u] = v, L[v] = *u;-----// 47
---return true;-----// a2
---}-----// 17
```

```
-----dist(v) = INF;-----// 62
-----return false;-----// 3c
-----}-----// 3d
-----return true;-----// ae
-----}-----// 0f
---void add_edge(int i, int j) { adj[i].push_back(j); }-----// 92
---int maximum_matching() {-----// a2
---int matching = 0;-----// 71
---memset(L, -1, sizeof(int) * N);-----// 72
---memset(R, -1, sizeof(int) * M);-----// bf
---while(bfs()) rep(i,0,N)-----// 3e
---matching += L[i] == -1 && dfs(i);-----// 1d
---return matching;-----// ec
---}-----// 8b
};-----// b7
```

3.6. Maximum Flow.

3.6.1. Dinic's algorithm. An implementation of Dinic's algorithm that runs in $O(|V|^2|E|)$.

```
#define MAXV 2000-----// ba
int q[MAXV], d[MAXV];-----// e6
struct flow_network {-----// 12
---struct edge {-----// 1e
---int v, cap, nxt;-----// ab
---edge() { }-----// 38
---edge(int _v, int _cap, int _nxt) : v(_v), cap(_cap), nxt(_nxt) { }-----// bc
---};-----// 6e
---int n, ecnt, *head, *curh;-----// 46
---vector<edge> e, e_store;-----// 1f
---flow_network(int _n, int m = -1) : n(_n), ecnt(0) {-----// d3
---e.reserve(2 * (m == -1 ? n : m));-----// 24
---head = new int[n], curh = new int[n];-----// 6b
---memset(head, -1, n * sizeof(int));-----// 56
---}-----// 77
---void destroy() { delete[] head; delete[] curh; }-----// f6
---void reset() { e = e_store; }-----// 87
---void add_edge(int u, int v, int uv, int vu = 0) {-----// cd
---e.push_back(edge(v, uv, head[u])); head[u] = ecnt++;-----// c9
---e.push_back(edge(u, vu, head[v])); head[v] = ecnt++;-----// 89
---}-----// 14
---int augment(int v, int t, int f) {-----// 3f
---if (v == t) return f;-----// 6d
---for (int &i = curh[v], ret; i != -1; i = e[i].nxt)-----// f9
---if (e[i].cap > 0 && d[e[i].v] + 1 == d[v])-----// cc
---if ((ret = augment(e[i].v, t, min(f, e[i].cap))) > 0)-----// 1f
---return (e[i].cap -= ret, e[i^1].cap += ret, ret);-----// ac
---return 0;-----// 19
---}-----// fd
---int max_flow(int s, int t, bool res = true) {-----// 31
---if(s == t) return 0;-----// 9d
---e_store = e;-----// 57
---int f = 0, x, l, r;-----// 0e
```

```
-----while (true) {-// b5
-----memset(d, -1, n * sizeof(int));-----// a8
-----l = r = 0, d[q[r++] = t] = 0;-----// 0e
-----while (l < r)-----// 7a
-----for (int v = q[l++], i = head[v]; i != -1; i = e[i].nxt)-----// a2
-----if (e[i^1].cap > 0 && d[e[i].v] == -1)-----// 29
-----d[q[r++] = e[i].v] = d[v]+1;-----// 28
-----if (d[s] == -1) break;-----// a0
-----memcpy(curh, head, n * sizeof(int));-----// 10
-----while ((x = augment(s, t, INF)) != 0) f += x;-----// a6
-----}-----// 96
-----if (res) reset();-----// 21
-----return f;-----// b6
-----}-----// 1b
};-----// 3b
```

3.6.2. *Edmonds Karp’s algorithm.* An implementation of Edmonds Karp’s algorithm that runs in $O(|V||E|^2)$.

```
#define MAXV 2000-----// ba
int q[MAXV], d[MAXV], p[MAXV];-----// 7b
struct flow_network {-// 5e
--struct edge {-// fc
--int v, cap, nxt;-----// cb
--edge(int _v, int _cap, int _nxt) : v(_v), cap(_cap), nxt(_nxt) { }-----// 7a
--};-----// 31
--int n, ecnt, *head;-----// 39
--vector<edge> e, e_store;-----// ea
--flow_network(int _n, int m = -1) : n(_n), ecnt(0) {-// 34
--e.reserve(2 * (m == -1 ? n : m));-----// 92
--memset(head = new int[n], -1, n << 2);-----// 58
--}-----// 3a
--void destroy() { delete[] head; }-----// d5
--void reset() { e = e_store; }-----// 1b
--void add_edge(int u, int v, int uv, int vu=0) {-// 7c
--e.push_back(edge(v, uv, head[u])); head[u] = ecnt++;-----// 4c
--e.push_back(edge(u, vu, head[v])); head[v] = ecnt++;-----// bc
--}-----// ef
--int max_flow(int s, int t, bool res = true) {-// 12
--if (s == t) return 0;-----// d6
--e_store = e;-----// 9e
--int f = 0, l, r, v;-----// 6f
--while (true) {-// 42
--memset(d, -1, n << 2);-----// 3b
--memset(p, -1, n << 2);-----// 92
--l = r = 0, d[q[r++] = s] = 0;-----// 5f
--while (l < r)-----// 2c
--for (int u = q[l++], i = head[u]; i != -1; i = e[i].nxt)-----// c6
--if (e[i].cap > 0 &&
--d[v = e[i].v] == -1 || d[u] + 1 < d[v])-----// 8a
--d[v] = d[u] + 1, p[q[r++] = v] = i;-----// d5
--if (p[t] == -1) break;-----// 4f
```

```
-----int x = INF, at = p[t];-----// b1
-----while (at != -1) x = min(x, e[at].cap), at = p[e[at^1].v];-----// 8a
-----at = p[t], f += x;-----// 2d
-----while (at != -1)-----// cd
-----e[at].cap -= x, e[at^1].cap += x, at = p[e[at^1].v];-----// 2e
-----}-----// 47
-----if (res) reset();-----// 3b
-----return f;-----// bc
-----}-----// 05
};-----// 75
```

3.7. **Minimum Cost Maximum Flow.** Running time is $O(|V|^2|E|\log |V|)$.

```
#define MAXV 2000-----// ba
int d[MAXV], p[MAXV], pot[MAXV];-----// 80
struct cmp {-// d1
--bool operator ()(int i, int j) {-// 8a
--return d[i] == d[j] ? i < j : d[i] < d[j];-----// 89
--}-----// df
};-----// cf
struct flow_network {-// eb
--struct edge {-// 9a
--int v, cap, cost, nxt;-----// ad
--edge(int _v, int _cap, int _cost, int _nxt)-----// ec
--: v(_v), cap(_cap), cost(_cost), nxt(_nxt) { }-----// c4
--};-----// ad
--int n, ecnt, *head;-----// 46
--vector<edge> e, e_store;-----// 4b
--flow_network(int _n, int m = -1) : n(_n), ecnt(0) {-// dd
--e.reserve(2 * (m == -1 ? n : m));-----// e6
--memset(head = new int[n], -1, n << 2);-----// 6c
--}-----// f3
--void destroy() { delete[] head; }-----// ac
--void reset() { e = e_store; }-----// 88
--void add_edge(int u, int v, int cost, int uv, int vu=0) {-// b4
--e.push_back(edge(v, uv, cost, head[u])); head[u] = ecnt++;-----// 43
--e.push_back(edge(u, vu, -cost, head[v])); head[v] = ecnt++;-----// 53
--}-----// 16
--ii min_cost_max_flow(int s, int t, bool res = true) {-// 6d
--if (s == t) return ii(0, 0);-----// 34
--e_store = e;-----// 70
--memset(pot, 0, n << 2);-----// 24
--int f = 0, c = 0, v;-----// d4
--while (true) {-// 29
--memset(d, -1, n << 2);-----// fd
--memset(p, -1, n << 2);-----// b7
--set<int, cmp> q;-----// d8
--q.insert(s); d[s] = 0;-----// 1d
--while (!q.empty()) {-// 04
--int u = *q.begin();-----// dd
--q.erase(q.begin());-----// 20
--for (int i = head[u]; i != -1; i = e[i].nxt) {-// 02
```

```
-----if (e[i].cap == 0) continue;-----// 1c
-----int cd = d[u] + e[i].cost + pot[u] - pot[v = e[i].v];-----// 1d
-----if (d[v] == -1 || cd < d[v]) {-----// d2
-----if (q.find(v) != q.end()) q.erase(q.find(v));-----// e2
-----d[v] = cd; p[v] = i;-----// f7
-----q.insert(v);-----// 74
-----}-----// 6c
-----}-----// 1b
-----}-----// da
-----if (p[t] == -1) break;-----// 09
-----int x = INF, at = p[t];-----// e8
-----while (at != -1) x = min(x, e[at].cap), at = p[e[at^1].v];-----// 32
-----at = p[t], f += x;-----// 43
-----while (at != -1)-----// 53
-----e[at].cap -= x, e[at^1].cap += x, at = p[e[at^1].v];-----// 95
-----c += x * (d[t] + pot[t] - pot[s]);-----// 44
-----rep(i,0,n) if (p[i] != -1) pot[i] += d[i];-----// 86
-----}-----// 4e
-----if (res) reset();-----// d7
-----return ii(f, c);-----// 9f
-----}-----// 4c
};-----// ec
```

3.8. All Pairs Maximum Flow.

3.8.1. *Gomory-Hu Tree*. An implementation of the Gomory-Hu Tree. The spanning tree is constructed using Gusfield’s algorithm in $O(|V|^2)$ plus $|V| - 1$ times the time it takes to calculate the maximum flow. If Dinic’s algorithm is used to calculate the max flow, the running time is $O(|V|^3|E|)$.

```
#include "dinic.cpp"-----// 58
-----// 25
bool same[MAXV];-----// 59
pair<vii, vvi> construct_gh_tree(flow_network &g) {-----// 77
----int n = g.n, v;-----// 5d
----vii par(n, ii(0, 0)); vvi cap(n, vi(n, -1));-----// 49
----rep(s,1,n) {-----// 9e
-----int l = 0, r = 0;-----// 08
-----par[s].second = g.max_flow(s, par[s].first, false);-----// 54
-----memset(d, 0, n * sizeof(int));-----// c8
-----memset(same, 0, n * sizeof(int));-----// b7
-----d[q[r++] = s] = 1;-----// cb
-----while (l < r) {-----// d4
-----same[v = q[l++]] = true;-----// f6
-----for (int i = g.head[v]; i != -1; i = g.e[i].nxt)-----// da
-----if (g.e[i].cap > 0 && d[g.e[i].v] == 0)-----// 9a
-----d[q[r++] = g.e[i].v] = 1;-----// 1f
-----}-----// d4
-----rep(i,s+1,n)-----// 35
-----if (par[i].first == par[s].first && same[i]) par[i].first = s;-----// 93
-----g.reset();-----// 87
----}-----// 22
----rep(i,0,n) {-----// 34
----int mn = INF, cur = i;-----// ac
```

```
-----while (true) {-----// c9
-----cap[cur][i] = mn;-----// 3b
-----if (cur == 0) break;-----// 37
-----mn = min(mn, par[cur].second), cur = par[cur].first;-----// e8
-----}-----// de
-----}-----// 99
-----return make_pair(par, cap);-----// 75
}-----// f6
int compute_max_flow(int s, int t, const pair<vii, vvi> &gh) {-----// 2a
----if (s == t) return 0;-----// 7a
----int cur = INF, at = s;-----// 57
----while (gh.second[at][t] == -1)-----// e0
----cur = min(cur, gh.first[at].second), at = gh.first[at].first;-----// 00
----return min(cur, gh.second[at][t]);-----// 09
}-----// 07
```

3.9. Heavy-Light Decomposition.

```
#include "../data-structures/segment_tree.cpp"-----// 16
struct HLD {-----// 25
----int n, curhead, curloc;-----// d9
----vi sz, head, parent, loc;-----// 81
----vvi below; segment_tree values;-----// 96
----HLD(int _n) : n(_n), sz(n, 1), head(n), parent(n, -1), loc(n), below(n) {-----// 4f
----vi tmp(n, ID); values = segment_tree(tmp); }-----// a7
----void add_edge(int u, int v) { below[parent[v] = u].push_back(v); }-----// f8
----void update_cost(int u, int v, int c) {-----// 12
----if (parent[v] == u) swap(u, v); assert(parent[u] == v);-----// 9f
----values.update(loc[u], c); }-----// 9a
----void csz(int u) { rep(i,0,size(below[u]))-----// 61
----csz(below[u][i]), sz[u] += sz[below[u][i]]; }-----// e7
----void part(int u) {-----// da
----head[u] = curhead; loc[u] = curloc++;-----// cc
----int best = -1;-----// 55
----rep(i,0,size(below[u]))-----// 0f
----if (best == -1 || sz[below[u][i]] > sz[best]) best = below[u][i];-----// 7d
----if (best != -1) part(best);-----// 26
----rep(i,0,size(below[u]))-----// 44
----if (below[u][i] != best) part(curhead = below[u][i]); }-----// 84
----void build() { int u = curloc = 0;-----// c4
----while (parent[u] != -1) u++;-----// d4
----csz(u); part(curhead = u); }-----// 38
----int lca(int u, int v) {-----// 81
----vi uat, vat; int res = -1;-----// e9
----while (u != -1) uat.push_back(u), u = parent[head[u]];-----// 5c
----while (v != -1) vat.push_back(v), v = parent[head[v]];-----// 1f
----u = size(uat) - 1, v = size(vat) - 1;-----// a4
----while (u >= 0 && v >= 0 && head[uat[u]] == head[vat[v]])-----// fe
----res = (loc[uat[u]] < loc[vat[v]] ? uat[u] : vat[v]), u--, v--;-----// 13
----return res; }-----// 3b
----int query_upto(int u, int v) { int res = ID;-----// bf
----while (head[u] != head[v])-----// 81
```

```
-----res = f(res, values.query(loc[head[u]], loc[u])),-----// 66
-----u = parent[head[u]];-----// 72
-----return f(res, values.query(loc[v] + 1, loc[u])); }-----// d7
----int query(int u, int v) { int l = lca(u, v);-----// fb
-----return f(query_upto(u, l), query_upto(v, l)); } };-----// 21
```

3.10. Tarjan’s Off-line Lowest Common Ancestors Algorithm.

```
#include "../data-structures/union_find.cpp"-----// 5e
struct tarjan_olca {-----// 87
----int *ancestor;-----// 39
----vi *adj, answers;-----// dd
----vii *queries;-----// 66
----bool *colored;-----// 97
----union_find uf;-----// 70
----tarjan_olca(int n, vi *_adj) : adj(_adj), uf(n) {-----// 78
-----colored = new bool[n];-----// 8d
-----ancestor = new int[n];-----// f2
-----queries = new vii[n];-----// 3e
-----memset(colored, 0, n);-----// 6e
----}-----// 6b
----void query(int x, int y) {-----// d3
-----queries[x].push_back(ii(y, size(answers)));-----// a0
-----queries[y].push_back(ii(x, size(answers)));-----// 14
-----answers.push_back(-1);-----// ca
----}-----// 6b
----void process(int u) {-----// 85
-----ancestor[u] = u;-----// 1a
-----rep(i,0,size(adj[u])) {-----// ce
-----int v = adj[u][i];-----// dd
-----process(v);-----// e8
-----uf.unite(u,v);-----// 55
-----ancestor[uf.find(u)] = u;-----// 1d
-----}-----// 57
-----colored[u] = true;-----// b9
-----rep(i,0,size(queries[u])) {-----// d7
-----int v = queries[u][i].first;-----// 89
-----if (colored[v]) {-----// cb
-----answers[queries[u][i].second] = ancestor[uf.find(v)];-----// 63
-----}-----// d0
-----}-----// 40
----}-----// a9
};-----// 1e
```

4. STRINGS

4.1. Suffix Array. An $O(n \log^2 n)$ construction of a Suffix Tree.

```
struct entry { ii nr; int p; };-----// f9
bool operator <(const entry &a, const entry &b) { return a.nr < b.nr; }-----// 77
struct suffix_array {-----// 87
----string s; int n; vii P; vector<entry> L; vi idx;-----// b6
----suffix_array(string _s) : s(_s), n(size(s)) {-----// a3
----L = vector<entry>(n), P.push_back(vi(n)), idx = vi(n);-----// 12
```

```
-----rep(i,0,n) P[0][i] = s[i];-----// 5c
-----for (int stp = 1, cnt = 1; cnt >> 1 < n; stp++, cnt <= 1) {-----// 86
-----P.push_back(vi(n));-----// 53
-----rep(i,0,n)-----// 6f
-----L[L[i].p = i].nr = ii(P[stp - 1][i],-----// e2
-----i + cnt < n ? P[stp - 1][i + cnt] : -1);-----// 43
-----sort(L.begin(), L.end());-----// 5f
-----rep(i,0,n)-----// a8
-----P[stp][L[i].p] = i > 0 &&-----// 3a
-----L[i].nr == L[i - 1].nr ? P[stp][L[i - 1].p] : i;-----// 55
-----}-----// 8b
-----rep(i,0,n) idx[P[size(P) - 1][i]] = i;-----// 17
----}-----// d9
----int lcp(int x, int y) {-----// 71
----int res = 0;-----// d6
----if (x == y) return n - x;-----// bc
----for (int k = size(P) - 1; k >= 0 && x < n && y < n; k--)-----// fe
----if (P[k][x] == P[k][y]) x += 1 << k, y += 1 << k, res += 1 << k;-----// b7
----return res;-----// bc
----}-----// f1
};-----// f6
```

4.2. Aho-Corasick Algorithm.

```
struct aho_corasick {-----// 78
----struct out_node {-----// 3e
----string keyword; out_node *next;-----// f0
----out_node(string k, out_node *n) : keyword(k), next(n) { }-----// 26
----};-----// b9
----struct go_node {-----// 40
----map<char, go_node*> next;-----// 6b
----out_node *out; go_node *fail;-----// 3e
----go_node() { out = NULL; fail = NULL; }-----// 0f
----};-----// c0
----go_node *go;-----// b8
----aho_corasick(vector<string> keywords) {-----// 4b
----go = new go_node();-----// 77
----iter(k, keywords) {-----// f2
----go_node *cur = go;-----// a2
----iter(c, *k)-----// 6e
----cur = cur->next.find(*c) != cur->next.end() ? cur->next[*c] :-----// 97
----(cur->next[*c] = new go_node());-----// af
----cur->out = new out_node(*k, cur->out);-----// 3f
----}-----// eb
----queue<go_node*> q;-----// 2c
----iter(a, go->next) q.push(a->second);-----// db
----while (!q.empty()) {-----// 07
----go_node *r = q.front(); q.pop();-----// e0
----iter(a, r->next) {-----// 18
----go_node *s = a->second;-----// 55
----q.push(s);-----// b5
----go_node *st = r->fail;-----// 53
```

```
-----while (st && st->next.find(a->first) == st->next.end())-----// 0e #define MAXN 100100-----// 29
-----st = st->fail;-----// b3 #define SIGMA 26-----// e2
-----if (!st) st = go;-----// 0b #define BASE 'a'-----// a1
-----s->fail = st->next[a->first];-----// c1 char *s = new char[MAXN];-----// db
-----if (s->fail) {-----// 98 struct state {-----// 33
-----if (!s->out) s->out = s->fail->out;-----// ad ----int len, link, to[SIGMA];-----// 24
-----else {-----// 5b } *st = new state[MAXN+2];-----// 57
-----out_node* out = s->out;-----// b8 struct eertree {-----// 78
-----while (out->next) out = out->next;-----// b4 ----int last, sz, n;-----// ba
-----out->next = s->fail->out;-----// 62 ----eertree() : last(1), sz(2), n(0) {-----// 83
-----}-----// a6 ----st[0].len = st[0].link = -1;-----// 3f
-----}-----// 81 ----st[1].len = st[1].link = 0; }-----// 34
-----}-----// 55 ----int extend() {-----// c2
-----}-----// bf ----char c = s[n++]; int p = last;-----// 25
-----}-----// de ----while (n - st[p].len - 2 < 0 || c != s[n - st[p].len - 2]) p = st[p].link;
-----vector<string> search(string s) {-----// c4 ----if (!st[p].to[c-BASE]) {-----// 82
-----vector<string> res;-----// 79 ----int q = last = sz++;-----// 42
-----go_node *cur = go;-----// 85 ----st[p].to[c-BASE] = q;-----// fc
-----iter(c, s) {-----// 57 ----st[q].len = st[p].len + 2;-----// c5
-----while (cur && cur->next.find(*c) == cur->next.end())-----// df ----do { p = st[p].link;-----// 04
-----cur = cur->fail;-----// b1 ----} while (p != -1 && (n < st[p].len + 2 || c != s[n - st[p].len - 2]));
-----if (!cur) cur = go;-----// 92 ----if (p == -1) st[q].link = 1;-----// 77
-----cur = cur->next[*c];-----// 97 ----else st[q].link = st[p].to[c-BASE];-----// 6a
-----if (!cur) cur = go;-----// 01 ----return 1; }-----// 29
-----for (out_node *out = cur->out; out; out = out->next)-----// d7 ----last = st[p].to[c-BASE];-----// 42
-----res.push_back(out->keyword);-----// 7c ----return 0; } }-----// ec
-----}-----// 56
-----return res;-----// 6b
-----}-----// 3e
};-----// de
```

4.3. The Z algorithm.

```
int* z_values(const string &s) {-----// 4d
----int n = size(s);-----// 97
----int* z = new int[n];-----// c4
----int l = 0, r = 0;-----// 1c
----z[0] = n;-----// 98
----rep(i,1,n) {-----// b2
----z[i] = 0;-----// 4c
----if (i > r) {-----// 6d
----l = r = i;-----// 24
----while (r < n && s[r - l] == s[r]) r++;-----// 68
----z[i] = r - l; r--;-----// 07
----} else if (z[i - l] < r - i + 1) z[i] = z[i - l];-----// 6f
----else {-----// a8
----l = i;-----// 55
----while (r < n && s[r - l] == s[r]) r++;-----// 2c
----z[i] = r - l; r--; } }-----// 13
----return z;-----// 78
}-----// 16
```

4.4. Eertree.

```
5. MATHEMATICS

5.1. Big Integer.
struct intx {-----// cf
----intx() { normalize(1); }-----// 6c
----intx(string n) { init(n); }-----// b9
----intx(int n) { stringstream ss; ss << n; init(ss.str()); }-----// 36
----intx(const intx& other) : sign(other.sign), data(other.data) { }-----// 3b
----int sign;-----// 26
----vector<unsigned int> data;-----// 19
----static const int dcnt = 9;-----// 12
----static const unsigned int radix = 1000000000U;-----// f0
----int size() const { return data.size(); }-----// 29
----void init(string n) {-----// 13
----intx res; res.data.clear();-----// 4e
----if (n.empty()) n = "0";-----// 99
----if (n[0] == '-') res.sign = -1, n = n.substr(1);-----// 3b
----for (int i = n.size() - 1; i >= 0; i -= intx::dcnt) {-----// e7
----unsigned int digit = 0;-----// 98
----for (int j = intx::dcnt - 1; j >= 0; j--) {-----// 72
----int idx = i - j;-----// cd
----if (idx < 0) continue;-----// 52
----digit = digit * 10 + (n[idx] - '0');-----// 1f
----}-----// c0
----res.data.push_back(digit);-----// 07
```

Reykjavík University14

```
-----}-----// fb
--data = res.data;-----// 7d
--normalize(res.sign);-----// 76
--}-----// 6e
--intx& normalize(int nsign) {-----// 3b
--if (data.empty()) data.push_back(0);-----// fa
--for (int i = data.size() - 1; i > 0 && data[i] == 0; i--)-----// 27
--    data.erase(data.begin() + i);-----// 67
--sign = data.size() == 1 && data[0] == 0 ? 1 : nsign;-----// ff
--return *this;-----// 40
--}-----// ac
--friend ostream& operator <<(ostream& outs, const intx& n) {-----// 0d
--if (n.sign < 0) outs << '-';-----// c0
--bool first = true;-----// 33
--for (int i = n.size() - 1; i >= 0; i--) {-----// 63
--    if (first) outs << n.data[i], first = false;-----// 33
--    else {-----// 1f
--        unsigned int cur = n.data[i];-----// 0f
--        stringstream ss; ss << cur;-----// 8c
--        string s = ss.str();-----// 64
--        int len = s.size();-----// 0d
--        while (len < intx::dcnt) outs << '0', len++;-----// 0a
--        outs << s;-----// 97
--    }-----// f7
--}-----// e9
--return outs;-----// cf
--}-----// b9
--string to_string() const { stringstream ss; ss << *this; return ss.str(); }// fc
--bool operator <(const intx& b) const {-----// 21
--if (sign != b.sign) return sign < b.sign;-----// cf
--if (size() != b.size())-----// 4d
--    return sign == 1 ? size() < b.size() : size() > b.size();-----// 4d
--for (int i = size() - 1; i >= 0; i--) if (data[i] != b.data[i])-----// 35
--    return sign == 1 ? data[i] < b.data[i] : data[i] > b.data[i];-----// 27
--return false;-----// ca
--}-----// 32
--intx operator -(const intx& b) const { intx res(*this); res.sign *= -1; return res; }// 9d
--friend intx abs(const intx& n) { return n < 0 ? -n : n; }-----// 02
--intx operator +(const intx& b) const {-----// f8
--if (sign > 0 && b.sign < 0) return *this - (-b);-----// 36
--if (sign < 0 && b.sign > 0) return b - (*this);-----// 70
--if (sign < 0 && b.sign < 0) return -((*this) + (-b));-----// 59
--intx c; c.data.clear();-----// 18
--unsigned long long carry = 0;-----// 5c
--for (int i = 0; i < size() || i < b.size() || carry; i++) {-----// e3
--    carry += (i < size() ? data[i] : 0ULL) +-----// 91
--    (i < b.size() ? b.data[i] : 0ULL);-----// 0c
--    c.data.push_back(carry % intx::radix);-----// 86
--    carry /= intx::radix;-----// fd
--}-----// 50
--return c.normalize(sign);-----// 20
--}-----// 70
--intx operator -(const intx& b) const {-----// 53
--if (sign > 0 && b.sign < 0) return *this + (-b);-----// 8f
--if (sign < 0 && b.sign > 0) return -(*this + b);-----// 1b
--if (sign < 0 && b.sign < 0) return (-b) - (-*this);-----// a1
--if (*this < b) return -(b - *this);-----// 36
--intx c; c.data.clear();-----// 6b
--long long borrow = 0;-----// f8
--rep(i,0,size()) {-----// a7
--    borrow = data[i] - borrow - (i < b.size() ? b.data[i] : 0ULL);-----// a5
--    c.data.push_back(borrow < 0 ? intx::radix + borrow : borrow);-----// 9b
--    borrow = borrow < 0 ? 1 : 0;-----// fb
--}-----// dd
--return c.normalize(sign);-----// 5c
--}-----// 5e
--intx operator *(const intx& b) const {-----// b3
--intx c; c.data.assign(size() + b.size() + 1, 0);-----// 3a
--rep(i,0,size()) {-----// 0f
--    long long carry = 0;-----// 15
--    for (int j = 0; j < b.size() || carry; j++) {-----// 95
--        if (j < b.size()) carry += (long long)data[i] * b.data[j];-----// 6d
--        carry += c.data[i + j];-----// c6
--        c.data[i + j] = carry % intx::radix;-----// a8
--        carry /= intx::radix;-----// dc
--    }-----// e3
--}-----// f0
--return c.normalize(sign * b.sign);-----// 09
--}-----// a7
--friend pair<intx,intx> divmod(const intx& n, const intx& d) {-----// 40
--assert(!(d.size() == 1 && d.data[0] == 0));-----// 42
--intx q, r; q.data.assign(n.size(), 0);-----// 5e
--for (int i = n.size() - 1; i >= 0; i--) {-----// 52
--    r.data.insert(r.data.begin(), 0);-----// cb
--    r = r + n.data[i];-----// ea
--    long long k = 0;-----// dd
--    if (d.size() < r.size())-----// 4d
--        k = (long long)intx::radix * r.data[d.size()];-----// d2
--    if (d.size() - 1 < r.size()) k += r.data[d.size() - 1];-----// af
--    k /= d.data.back();-----// 85
--    r = r - abs(d) * k;-----// 3b
--    // if (r < 0) for (ll t = 1LL << 62; t >= 1; t >>= 1) {-----// 0e
--    //-----intx dd = abs(d) * t;-----// 9d
--    //-----while (r + dd < 0) r = r + dd, k -= t; }-----// a1
--    while (r < 0) r = r + abs(d), k--;-----// cb
--    q.data[i] = k;-----// 1a
--}-----// 3c
--return pair<intx, intx>(q.normalize(n.sign * d.sign), r);-----// 9e
--}-----// a7
--intx operator /(const intx& d) const {-----// 22
--return divmod(*this,d).first; }-----// c3
--intx operator %(const intx& d) const {-----// 32
```



```
-----return divmod(*this,d).second * sign; }-----// 0c
};-----// 64

5.1.1. Fast Multiplication.
#include "intx.cpp"-----// 83
#include "fft.cpp"-----// 13
-----// e0
intx fastmul(const intx &an, const intx &bn) {-----// ab
----string as = an.to_string(), bs = bn.to_string();-----// 32
----int n = size(as), m = size(bs), l = 1,-----// dc
-----len = 5, radix = 100000,-----// 4f
-----*a = new int[n], alen = 0,-----// b8
-----*b = new int[m], blen = 0;-----// 0a
----memset(a, 0, n << 2);-----// 1d
----memset(b, 0, m << 2);-----// 01
----for (int i = n - 1; i >= 0; i -= len, alen++)-----// 6e
-----for (int j = min(len - 1, i); j >= 0; j--)-----// 43
-----a[alen] = a[alen] * 10 + as[i - j] - '0';-----// 14
----for (int i = m - 1; i >= 0; i -= len, blen++)-----// b6
-----for (int j = min(len - 1, i); j >= 0; j--)-----// ae
-----b[blen] = b[blen] * 10 + bs[i - j] - '0';-----// 9b
----while (l < 2*max(alen,blen)) l <= 1;-----// 51
----cpx *A = new cpx[l], *B = new cpx[l];-----// 0d
----rep(i,0,l) A[i] = cpx(i < alen ? a[i] : 0, 0);-----// ff
----rep(i,0,l) B[i] = cpx(i < blen ? b[i] : 0, 0);-----// 7f
----fft(A, l); fft(B, l);-----// 77
----rep(i,0,l) A[i] *= B[i];-----// 1c
----fft(A, l, true);-----// ec
----ull *data = new ull[l];-----// f1
----rep(i,0,l) data[i] = (ull)(round(real(A[i])));-----// e2
----rep(i,0,l-1)-----// c8
-----if (data[i] >= (unsigned int)(radix)) {-----// 03
-----data[i+1] += data[i] / radix;-----// 48
-----data[i] %= radix;-----// 94
-----}-----// 47
----int stop = l-1;-----// 92
----while (stop > 0 && data[stop] == 0) stop--;-----// 5b
----stringstream ss;-----// a6
----ss << data[stop];-----// f3
----for (int i = stop - 1; i >= 0; i--)-----// 7b
-----ss << setfill('0') << setw(len) << data[i];-----// 41
----delete[] A; delete[] B;-----// dd
----delete[] a; delete[] b;-----// 77
----delete[] data;-----// 5e
----return intx(ss.str());-----// 88
}-----// d8

5.2. Binomial Coefficients. The binomial coefficient  $\binom{n}{k} = \frac{n!}{k!(n-k)!}$  is the number of ways to choose
k items out of a total of n items.
int nck(int n, int k) {-----// f6
----if (n - k < k) k = n - k;-----// 18
----int res = 1;-----// cb
-----rep(i,1,k+1) res = res * (n - (k - i)) / i;-----// 16
----return res;-----// 6d
}-----// 3d

5.3. Euclidean algorithm.
int gcd(int a, int b) { return b == 0 ? a : gcd(b, a % b); }-----// d9

The extended Euclidean algorithm computes the greatest common divisor d of two integers a, b
and also finds two integers x, y such that  $a \times x + b \times y = d$ .
int egcd(int a, int b, int& x, int& y) {-----// 85
----if (b == 0) { x = 1; y = 0; return a; }-----// 7b
----else {-----// 00
-----int d = egcd(b, a % b, x, y);-----// 34
-----x -= a / b * y;-----// 4a
-----swap(x, y);-----// 26
-----return d;-----// db
----}-----// 9e
}-----// 40

5.4. Trial Division Primality Testing.
bool is_prime(int n) {-----// 6c
----if (n < 2) return false;-----// c9
----if (n < 4) return true;-----// d9
----if (n % 2 == 0 || n % 3 == 0) return false;-----// 0f
----if (n < 25) return true;-----// ef
----int s = static_cast<int>(sqrt(static_cast<double>(n)));-----// 64
----for (int i = 5; i <= s; i += 6)-----// 6c
-----if (n % i == 0 || n % (i + 2) == 0) return false;-----// e9
----return true; }-----// 43

5.5. Miller-Rabin Primality Test.
#include "mod_pow.cpp"-----// c7
bool is_probable_prime(ll n, int k) {-----// be
----if (~n & 1) return n == 2;-----// d1
----if (n <= 3) return n == 3;-----// 39
----int s = 0; ll d = n - 1;-----// 37
----while (~d & 1) d >>= 1, s++;-----// 35
----while (k--) {-----// c8
-----ll a = (n - 3) * rand() / RAND_MAX + 2;-----// 06
-----ll x = mod_pow(a, d, n);-----// 64
-----if (x == 1 || x == n - 1) continue;-----// 9b
-----bool ok = false;-----// 03
-----rep(i,0,s-1) {-----// 13
-----x = (x * x) % n;-----// 90
-----if (x == 1) return false;-----// 5c
-----if (x == n - 1) { ok = true; break; }-----// a1
-----}-----// 3a
-----if (!ok) return false;-----// 37
----} return true; }-----// fe
```

5.6. Sieve of Eratosthenes.

```
vi prime_sieve(int n) {-----// 40
---int mx = (n - 3) >> 1, sq, v, i = -1;-----// 27
---vi primes;-----// 8f
---bool* prime = new bool[mx + 1];-----// ef
---memset(prime, 1, mx + 1);-----// 28
---if (n >= 2) primes.push_back(2);-----// f4
---while (++i <= mx) if (prime[i]) {-----// 73
-----primes.push_back(v = (i << 1) + 3);-----// be
-----if ((sq = i * ((i << 1) + 6) + 3) > mx) break;-----// 2d
-----for (int j = sq; j <= mx; j += v) prime[j] = false; }-----// 2e
---while (++i <= mx) if (prime[i]) primes.push_back((i << 1) + 3);-----// 29
---delete[] prime; // can be used for O(1) lookup-----// 36
---return primes; }-----// 72
```

5.7. Modular Multiplicative Inverse.

```
#include "egcd.cpp"-----// 55
-----// e8
int mod_inv(int a, int m) {-----// 49
---int x, y, d = egcd(a, m, x, y);-----// 3e
---if (d != 1) return -1;-----// 20
---return x < 0 ? x + m : x;-----// 3c
}-----// 69
```

5.8. Chinese Remainder Theorem.

```
#include "egcd.cpp"-----// 55
int crt(const vi& as, const vi& ns) {-----// c3
---int cnt = size(as), N = 1, x = 0, r, s, l;-----// 55
---rep(i,0,cnt) N *= ns[i];-----// b1
---rep(i,0,cnt) egcd(ns[i], l = N/ns[i], r, s), x += as[i] * s * l;-----// 21
---return mod(x, N); }-----// b2
```

5.9. Linear Congruence Solver. A function that returns all solutions to $ax \equiv b \pmod n$, modulo n .

```
#include "egcd.cpp"-----// 55
vi linear_congruence(int a, int b, int n) {-----// c8
---int x, y, d = egcd(a, n, x, y);-----// 7a
---vi res;-----// f5
---if (b % d != 0) return res;-----// 30
---int x0 = mod(b / d * x, n);-----// 48
---rep(k,0,d) res.push_back(mod(x0 + k * n / d, n));-----// 7e
---return res;-----// fe
}-----// c0
```

5.10. Numeric Integration.

```
double integrate(double (*f)(double), double a, double b,-----// 76
---double delta = 1e-6) {-----// c0
---if (abs(a - b) < delta)-----// 38
---return (b-a)/8 *-----// 56
-----((f(a) + 3*f((2*a+b)/3) + 3*f((a+2*b)/3) + f(b)));-----// e1
---return integrate(f, a,-----// 64
```

```
-----((a+b)/2, delta) + integrate(f, (a+b)/2, b, delta);-----// 0c
}-----// 4b
```

5.11. Fast Fourier Transform. The Cooley-Tukey algorithm for quickly computing the discrete Fourier transform. The `fft` function only supports powers of twos. The `czf` function implements the Chirp Z-transform and supports any size, but is slightly slower.

```
#include <complex>-----// 8e
typedef complex<long double> cpx;-----// 25
// NOTE: n must be a power of two-----// 14
void fft(cpx *x, int n, bool inv=false) {-----// 36
---for (int i = 0, j = 0; i < n; i++) {-----// f9
---if (i < j) swap(x[i], x[j]);-----// 44
---int m = n>>1;-----// 9c
---while (1 <= m && m <= j) j -= m, m >>= 1;-----// fe
---j += m;-----// 11
---}-----// d0
---for (int mx = 1; mx < n; mx <= 1) {-----// 15
---cpx wp = exp(cpx(0, (inv ? -1 : 1) * pi / mx)), w = 1;-----// 79
---for (int m = 0; m < mx; m++, w *= wp) {-----// dc
---for (int i = m; i < n; i += mx <= 1) {-----// 6a
---cpx t = x[i + mx] * w;-----// 12
---x[i + mx] = x[i] - t;-----// 73
---x[i] += t;-----// 0e
---}-----// 14
---}-----// a4
}-----// bf
---if (inv) rep(i,0,n) x[i] /= cpx(n);-----// 16
}-----// 1c
void czf(cpx *x, int n, bool inv=false) {-----// c5
---int len = 2*n+1;-----// bc
---while (len & (len - 1)) len &= len - 1;-----// 65
---len <= 1;-----// 21
---cpx w = exp(-2.0L * pi / n * cpx(0,1)),-----// 45
---*c = new cpx[n], *a = new cpx[len],-----// 4e
---*b = new cpx[len];-----// 30
---rep(i,0,n) c[i] = pow(w, (inv ? -1.0 : 1.0)*i/2);-----// 9e
---rep(i,0,n) a[i] = x[i] * c[i], b[i] = 1.0L/c[i];-----// e9
---rep(i,0,n-1) b[len - n + i + 1] = 1.0L/c[n-i-1];-----// 9f
---fft(a, len); fft(b, len);-----// 63
---rep(i,0,len) a[i] *= b[i];-----// 58
---fft(a, len, true);-----// 2d
---rep(i,0,n) {-----// ff
---x[i] = c[i] * a[i];-----// 77
---if (inv) x[i] /= cpx(n);-----// b1
---}-----// 27
---delete[] a;-----// 0a
---delete[] b;-----// 5c
---delete[] c;-----// f8
}-----// c6
```

5.12. Formulas.

- Number of ways to choose k objects from a total of n objects where order matters and each item can only be chosen once: $P_k^n = \frac{n!}{(n-k)!}$
- Number of ways to choose k objects from a total of n objects where order matters and each item can be chosen multiple times: n^k
- Number of permutations of n objects, where there are n_1 objects of type 1, n_2 objects of type 2, \dots , n_k objects of type k : $\binom{n}{n_1, n_2, \dots, n_k} = \frac{n!}{n_1! \times n_2! \times \dots \times n_k!}$
- Number of ways to choose k objects from a total of n objects where order does not matter and each item can only be chosen once:
 $\binom{n}{k} = \binom{n-1}{k-1} + \binom{n-1}{k} = \binom{n}{n-k} = \prod_{i=1}^k \frac{n-(k-i)}{i} = \frac{n!}{k!(n-k)!}$, $\binom{n}{0} = 1$, $\binom{0}{k} = 0$
- Number of ways to choose k objects from a total of n objects where order does not matter and each item can be chosen multiple times: $f_k^n = \binom{n+k-1}{k} = \frac{(n+k-1)!}{k!(n-1)!}$
- Number of integer solutions to $x_1 + x_2 + \dots + x_n = k$ where $x_i \geq 0$: f_k^n
- Number of subsets of a set with n elements: 2^n
- $|A \cup B| = |A| + |B| - |A \cap B|$
- $|A \cup B \cup C| = |A| + |B| + |C| - |A \cap B| - |A \cap C| - |B \cap C| + |A \cap B \cap C|$
- Number of ways to walk from the lower-left corner to the upper-right corner of an $n \times m$ grid by walking only up and to the right: $\binom{n+m}{m}$
- Number of strings with n sets of brackets such that the brackets are balanced:
 $C_n = \sum_{k=0}^{n-1} C_k C_{n-1-k} = \frac{1}{n+1} \binom{2n}{n}$
- Number of triangulations of a convex polygon with n points, number of rooted binary trees with $n+1$ vertices, number of paths across an $n \times n$ lattice which do not rise above the main diagonal: C_n
- Number of permutations of n objects with exactly k ascending sequences or *runs*:
 $\langle n \rangle_k = \left\langle \binom{n}{n-k-1} \right\rangle = k \left\langle \binom{n-1}{k} \right\rangle + (n-k+1) \left\langle \binom{n-1}{k-1} \right\rangle = \sum_{i=0}^k (-1)^i \binom{n+1}{i} (k+1-i)^n$, $\langle n \rangle = \left\langle \binom{n}{n-1} \right\rangle = 1$
- Number of permutations of n objects with exactly k cycles: $\left[\begin{smallmatrix} n \\ k-1 \end{smallmatrix} \right] = \left[\begin{smallmatrix} n-1 \\ k-1 \end{smallmatrix} \right] + (n-1) \left[\begin{smallmatrix} n-1 \\ k \end{smallmatrix} \right]$
- Number of ways to partition n objects into k sets: $\left\{ \begin{smallmatrix} n \\ k \end{smallmatrix} \right\} = k \left\{ \begin{smallmatrix} n-1 \\ k-1 \end{smallmatrix} \right\} + \left\{ \begin{smallmatrix} n-1 \\ k-1 \end{smallmatrix} \right\}$, $\left\{ \begin{smallmatrix} n \\ 0 \end{smallmatrix} \right\} = \left\{ \begin{smallmatrix} n \\ n \end{smallmatrix} \right\} = 1$
- Number of permutations of length n that have no fixed points (derangements): $D_0 = 1, D_1 = 0, D_n = (n-1)(D_{n-1} + D_{n-2})$
- Number of permutations of length n that have exactly k fixed points: $\binom{n}{k} D_{n-k}$
- **Jacobi symbol**: $\left(\frac{a}{b}\right) = a^{(b-1)/2} \pmod{b}$
- **Heron's formula**: A triangle with side lengths a, b, c has area $\sqrt{s(s-a)(s-b)(s-c)}$ where $s = \frac{a+b+c}{2}$.
- **Pick's theorem**: A polygon on an integer grid containing i lattice points and having b lattice points on the boundary has area $i + \frac{b}{2} - 1$.
- **Divisor sigma**: The sum of divisors of n to the x th power is $\sigma_x(n) = \prod_{i=0}^r \frac{p_i^{(a_i+1)x} - 1}{p_i^x - 1}$ where $n = \prod_{i=0}^r p_i^{a_i}$ is the prime factorization.
- **Divisor count**: A special case of the above is $\sigma_0(n) = \prod_{i=0}^r (a_i + 1)$.
- **Euler's totient**: The number of integers less than n that are coprime to n are $n \prod_{p|n} \left(1 - \frac{1}{p}\right)$ where each p is a distinct prime factor of n .
- **König's theorem**: In any bipartite graph, the number of edges in a maximum matching is equal to the number of vertices in a minimum vertex cover.
- The number of vertices of a graph is equal to its minimum vertex cover number plus the size of a maximum independent set.
- $\gcd(2^a - 1, 2^b - 1) = 2^{\gcd(a,b)} - 1$

5.13. **Numbers and Sequences.** Some random prime numbers: 1031, 32771, 1048583, 33554467, 1073741827, 34359738421, 1099511627791, 35184372088891, 1125899906842679, 36028797018963971.

6.1. Primitives.

```
#include <complex>-----// 8e
#define P(p) const point &p-----// b8
#define L(p0, p1) P(p0), P(p1)-----// 30
#define C(p0, r) P(p0), double r-----// 08
#define PP(pp) pair<point,point> &pp-----// a1
typedef complex<double> point;-----// 9e
double dot(P(a), P(b)) { return real(conj(a) * b); }-----// 4a
double cross(P(a), P(b)) { return imag(conj(a) * b); }-----// f3
point rotate(P(p), double radians = pi / 2, P(about) = point(0,0)) { -----// 0b
----return (p - about) * exp(point(0, radians)) + about; }-----// f5
point reflect(P(p), L(about1, about2)) {-----// 45
----point z = p - about1, w = about2 - about1;-----// 74
----return conj(z / w) * w + about1; }-----// d1
point proj(P(u), P(v)) { return dot(u, v) / dot(u, u) * u; }-----// 98
point normalize(P(p), double k = 1.0) { -----// a9
----return abs(p) == 0 ? point(0,0) : p / abs(p) * k; } //TODO: TEST-----// 1c
bool parallel(L(a, b), L(p, q)) { return abs(cross(b - a, q - p)) < EPS; }-----// 74
double ccw(P(a), P(b), P(c)) { return cross(b - a, c - b); }-----// ab
bool collinear(P(a), P(b), P(c)) { return abs(ccw(a, b, c)) < EPS; }-----// 95
bool collinear(L(a, b), L(p, q)) { -----// de
----return abs(ccw(a, b, p)) < EPS && abs(ccw(a, b, q)) < EPS; }-----// 27
double angle(P(a), P(b), P(c)) {-----// 93
----return acos(dot(b - a, c - b) / abs(b - a) / abs(c - b)); }-----// a2
double signed_angle(P(a), P(b), P(c)) {-----// 46
----return asin(cross(b - a, c - b) / abs(b - a) / abs(c - b)); }-----// 80
double angle(P(p)) { return atan2(imag(p), real(p)); }-----// c0
point perp(P(p)) { return point(-imag(p), real(p)); }-----// 3c
double progress(P(p), L(a, b)) {-----// c7
----if (abs(real(a) - real(b)) < EPS)-----// 7d
-----return (imag(p) - imag(a)) / (imag(b) - imag(a));-----// b7
----else return (real(p) - real(a)) / (real(b) - real(a)); }-----// 6c
bool intersect(L(a, b), L(p, q), point &res, bool segment = false) {-----// b4
----// NOTE: check for parallel/collinear lines before calling this function---// 88
----point r = b - a, s = q - p;-----// 54
----double c = cross(r, s), t = cross(p - a, s) / c, u = cross(p - a, r) / c;---// 29
----if (segment && (t < 0-EPS || t > 1+EPS || u < 0-EPS || u > 1+EPS))-----// 30
-----return false;-----// c0
----res = a + t * r;-----// 88
----return true;-----// 03
}-----// 92
point closest_point(L(a, b), P(c), bool segment = false) {-----// 06
----if (segment) {-----// 90
-----if (dot(b - a, c - b) > 0) return b;-----// 93
-----if (dot(a - b, c - a) > 0) return a;-----// bb
-----}-----// d5
----double t = dot(c - a, b - a) / norm(b - a);-----// 61
----return a + t * (b - a);-----// 4f
}-----// 19
```

```
double line_segment_distance(L(a,b), L(c,d)) {-----// f6
---double x = INFINITY;-----// 8c
---if (abs(a - b) < EPS && abs(c - d) < EPS) x = abs(a - c);-----// 5f
---else if (abs(a - b) < EPS) x = abs(a - closest_point(c, d, a, true));-----// 97
---else if (abs(c - d) < EPS) x = abs(c - closest_point(a, b, c, true));-----// 68
---else if ((ccw(a, b, c) < 0) != (ccw(a, b, d) < 0) &&-----// fa
----- (ccw(c, d, a) < 0) != (ccw(c, d, b) < 0)) x = 0;-----// bb
---else {-----// 5b
-----x = min(x, abs(a - closest_point(c,d, a, true)));-----// 07
-----x = min(x, abs(b - closest_point(c,d, b, true)));-----// 75
-----x = min(x, abs(c - closest_point(a,b, c, true)));-----// 48
-----x = min(x, abs(d - closest_point(a,b, d, true)));-----// 75
---}-----// 60
---return x;-----// 57
}-----// 8e
int intersect(C(A, rA), C(B, rB), point & res1, point & res2) {-----// ca
---double d = abs(B - A);-----// 06
---if ((rA + rB) < (d - EPS) || d < abs(rA - rB) - EPS) return 0;-----// 5d
---double a = (rA*rA - rB*rB + d*d) / 2 / d, h = sqrt(rA*rA - a*a);-----// 5e
---point v = normalize(B - A, a), u = normalize(rotate(B-A), h);-----// da
---res1 = A + v + u, res2 = A + v - u;-----// c2
---if (abs(u) < EPS) return 1; return 2;-----// 95
}-----// 4e
int intersect(L(A, B), C(0, r), point & res1, point & res2) {-----// e4
---double h = abs(0 - closest_point(A, B, 0));-----// f4
---if(r < h - EPS) return 0;-----// 89
---point H = proj(0 - A, B - A) + A, v = normalize((B - A), sqrt(r*r - h*h));// a9
---res1 = H + v; res2 = H - v;-----// ab
---if(abs(v) < EPS) return 1; return 2;-----// f7
}-----// b8
int tangent(P(A), C(0, r), point & res1, point & res2) {-----// 15
---point v = 0 - A; double d = abs(v);-----// 2c
---if (d < r - EPS) return 0;-----// 14
---double alpha = asin(r / d), L = sqrt(d*d - r*r);-----// 45
---v = normalize(v, L);-----// 10
---res1 = A + rotate(v, alpha); res2 = A + rotate(v, -alpha);-----// 56
---if (abs(r - d) < EPS || abs(v) < EPS) return 1;-----// 1d
---return 2;-----// 97
}-----// 46
void tangent_outer(point A, double rA, point B, double rB, PP(P), PP(Q)) {-----// 61
---if (rA - rB > EPS) { swap(rA, rB); swap(A, B); }-----// 2a
---double theta = asin((rB - rA)/abs(A - B));-----// 0a
---point v = rotate(B - A, theta + pi/2), u = rotate(B - A, -(theta + pi/2));// e3
---u = normalize(u, rA);-----// 30
---P.first = A + normalize(v, rA); P.second = B + normalize(v, rB);-----// 08
---Q.first = A + normalize(u, rA); Q.second = B + normalize(u, rB);-----// 2a
}-----// 2d

6.2. Polygon.
#include "primitives.cpp"-----// e0
typedef vector<point> polygon;-----// b3
```

```
double polygon_area_signed(polygon p) {-----// 31
---double area = 0; int cnt = size(p);-----// a2
---rep(i,1,cnt-1) area += cross(p[i] - p[0], p[i + 1] - p[0]);-----// 51
---return area / 2; }-----// 66
double polygon_area(polygon p) { return abs(polygon_area_signed(p)); }-----// a4
#define CHK(f,a,b,c) (f(a) < f(b) && f(b) <= f(c) && ccw(a,c,b) < 0)-----// 8f
int point_in_polygon(polygon p, point q) {-----// 5d
---int n = size(p); bool in = false; double d;-----// 69
---for (int i = 0, j = n - 1; i < n; j = i++)-----// f3
-----if (collinear(p[i], q, p[j]) &&-----// 9d
-----0 <= (d = progress(q, p[i], p[j])) && d <= 1)-----// 4b
-----return 0;-----// b3
---for (int i = 0, j = n - 1; i < n; j = i++)-----// 67
-----if (CHK(real, p[i], q, p[j]) || CHK(real, p[j], q, p[i]))-----// b4
-----in = !in;-----// ff
---return in ? -1 : 1; }-----// ba
// pair<polygon, polygon> cut_polygon(const polygon &poly, point a, point b) {-// 0d
//---- polygon left, right;-----// 0a
//---- point it(-100, -100);-----// 5b
//---- for (int i = 0, cnt = poly.size(); i < cnt; i++) {-----// 70
//----- int j = i == cnt-1 ? 0 : i + 1;-----// 02
//----- point p = poly[i], q = poly[j];-----// 44
//----- if (ccw(a, b, p) <= 0) left.push_back(p);-----// 8d
//----- if (ccw(a, b, p) >= 0) right.push_back(p);-----// 43
//----- // myintersect = intersect where-----// ba
//----- // (a,b) is a line, (p,q) is a line segment-----// 7e
//----- if (myintersect(a, b, p, q, it))-----// 6f
//----- left.push_back(it), right.push_back(it);-----// 8a
//---- }-----// e0
//---- return pair<polygon, polygon>(left, right);-----// 3d
// }-----// 07

6.3. Convex Hull.
#include "polygon.cpp"-----// 58
#define MAXN 1000-----// 09
point hull[MAXN];-----// 43
bool cmp(const point &a, const point &b) {-----// 32
---return abs(real(a) - real(b)) > EPS ?-----// 44
---real(a) < real(b) : imag(a) < imag(b); }-----// 40
int convex_hull(polygon p) {-----// cd
---int n = size(p), l = 0;-----// 67
---sort(p.begin(), p.end(), cmp);-----// 3d
---rep(i,0,n) {-----// e4
-----if (i > 0 && p[i] == p[i - 1]) continue;-----// c7
-----while (l >= 2 && ccw(hull[l - 2], hull[l - 1], p[i]) >= 0) l--;-----// 62
-----hull[l++] = p[i];-----// bd
-----}-----// d2
---int r = l;-----// 30
---for (int i = n - 2; i >= 0; i--) {-----// 59
-----if (p[i] == p[i + 1]) continue;-----// af
-----while (r - l >= 1 && ccw(hull[r - 2], hull[r - 1], p[i]) >= 0) r--;-----// 4d
```

```
-----hull[r++] = p[i];-----// f5
--}------// f6
---return l == 1 ? 1 : r - 1;-----// a6
}------// 6d
```

6.4. Line Segment Intersection.

```
#include "primitives.cpp"-----// e0
bool line_segment_intersect(L(a, b), L(c, d), point &A, point &B) {-----// 6c
---if (abs(a - b) < EPS && abs(c - d) < EPS) {-----// db
--A = B = a; return abs(a - d) < EPS; }-----// ee
---else if (abs(a - b) < EPS) {-----// 03
--A = B = a; double p = progress(a, c,d);-----// c9
-----return 0.0 <= p && p <= 1.0-----// 8a
-----&& (abs(a - c) + abs(d - a) - abs(d - c)) < EPS; }-----// 27
---else if (abs(c - d) < EPS) {-----// 26
--A = B = c; double p = progress(c, a,b);-----// d9
-----return 0.0 <= p && p <= 1.0-----// 8e
-----&& (abs(c - a) + abs(b - c) - abs(b - a)) < EPS; }-----// 4f
---else if (collinear(a,b, c,d)) {-----// bc
--double ap = progress(a, c,d), bp = progress(b, c,d);-----// a7
--if (ap > bp) swap(ap, bp);-----// b1
--if (bp < 0.0 || ap > 1.0) return false;-----// 0c
--A = c + max(ap, 0.0) * (d - c);-----// f6
--B = c + min(bp, 1.0) * (d - c);-----// 5c
--return true; }-----// ab
---else if (parallel(a,b, c,d)) return false;-----// ca
---else if (intersect(a,b, c,d, A, true)) {-----// 10
--B = A; return true; }-----// bf
--return false;-----// b7
}------// 8b
-----// e6
```

6.5. Great-Circle Distance. Computes the distance between two points (given as latitude/longitude coordinates) on a sphere of radius r .

```
double gc_distance(double pLat, double pLong,-----// 7b
--double qLat, double qLong, double r) {-----// a4
---pLat *= pi / 180; pLong *= pi / 180;-----// ee
---qLat *= pi / 180; qLong *= pi / 180;-----// 75
---return r * acos(cos(pLat) * cos(qLat) * cos(pLong - qLong) +-----// e3
-----sin(pLat) * sin(qLat));-----// 1e
-----// 60
}------// 3f
```

6.6. Triangle Circumcenter. Returns the unique point that is the same distance from all three points. It is also the center of the unique circle that goes through all three points.

```
#include "primitives.cpp"-----// e0
point circumcenter(point a, point b, point c) {-----// 76
---b -= a, c -= a;-----// 41
---return a + perp(b * norm(c) - c * norm(b)) / 2.0 / cross(b, c);-----// 7a
}------// c3
```

6.7. Closest Pair of Points.

```
#include "primitives.cpp"-----// e0
-----// 85
struct cmpx { bool operator ()(const point &a, const point &b) {-----// 01
-----return abs(real(a) - real(b)) > EPS ?-----// e9
-----real(a) < real(b) : imag(a) < imag(b); } };-----// 53
struct cmpy { bool operator ()(const point &a, const point &b) {-----// 6f
-----return abs(imag(a) - imag(b)) > EPS ?-----// 0b
-----imag(a) < imag(b) : real(a) < real(b); } };-----// a4
double closest_pair(vector<point> pts) {-----// f1
--sort(pts.begin(), pts.end(), cmpx());-----// 0c
--set<point, cmpy> cur;-----// bd
--set<point, cmpy>::const_iterator it, jt;-----// a6
--double mn = INFINITY;-----// f9
--for (int i = 0, l = 0; i < size(pts); i++) {-----// ac
-----while (real(pts[i]) - real(pts[l]) > mn) cur.erase(pts[l++]);-----// 8b
-----it = cur.lower_bound(point(-INFINITY, imag(pts[i]) - mn));-----// fc
-----jt = cur.upper_bound(point(INFINITY, imag(pts[i]) + mn));-----// 39
-----while (it != jt) mn = min(mn, abs(*it - pts[i])), it++;-----// 09
-----cur.insert(pts[i]); }-----// 82
--return mn; }-----// 4c
```

6.8. 3D Primitives.

```
#define P(p) const point3d &p-----// a7
#define L(p0, p1) P(p0), P(p1)-----// 0f
#define PL(p0, p1, p2) P(p0), P(p1), P(p2)-----// 67
struct point3d {-----// 63
--double x, y, z;-----// e6
--point3d() : x(0), y(0), z(0) { }-----// af
--point3d(double _x, double _y, double _z) : x(_x), y(_y), z(_z) { }-----// fc
--point3d operator+(P(p)) const {-----// 17
-----return point3d(x + p.x, y + p.y, z + p.z); }-----// 8e
--point3d operator-(P(p)) const {-----// fb
-----return point3d(x - p.x, y - p.y, z - p.z); }-----// 83
--point3d operator-() const {-----// 89
-----return point3d(-x, -y, -z); }-----// d4
--point3d operator*(double k) const {-----// 4d
-----return point3d(x * k, y * k, z * k); }-----// fd
--point3d operator/(double k) const {-----// 95
-----return point3d(x / k, y / k, z / k); }-----// 58
--double operator%(P(p)) const {-----// d1
-----return x * p.x + y * p.y + z * p.z; }-----// 09
--point3d operator*(P(p)) const {-----// 4f
-----return point3d(y*p.z - z*p.y, z*p.x - x*p.z, x*p.y - y*p.x); }-----// ed
--double length() const {-----// 3e
-----return sqrt(*this % *this); }-----// 05
--double distTo(P(p)) const {-----// dd
-----return (*this - p).length(); }-----// 57
--double distTo(P(A), P(B)) const {-----// bd
-----// A and B must be two different points-----// 4e
-----return ((*this - A) * (*this - B)).length() / A.distTo(B); }-----// 6e
```



```
---point3d normalize(double k = 1) const {-----// db
-----// length() must not return 0-----// 3c
-----return (*this) * (k / length()); }-----// d4
---point3d getProjection(P(A), P(B)) const {-----// 86
---point3d v = B - A;-----// 64
-----return A + v.normalize((v % (*this - A)) / v.length()); }-----// 53
---point3d rotate(P(normal)) const {-----// 55
-----// normal must have length 1 and be orthogonal to the vector-----// eb
-----return (*this) * normal; }-----// 5c
---point3d rotate(double alpha, P(normal)) const {-----// 21
-----return (*this) * cos(alpha) + rotate(normal) * sin(alpha); }-----// 82
---point3d rotatePoint(P(0), P(axe), double alpha) const{-----// 7a
-----point3d Z = axe.normalize(axe % (*this - 0));-----// ba
-----return 0 + Z + (*this - 0 - Z).rotate(alpha, 0); }-----// 38
---bool isZero() const {-----// 64
-----return abs(x) < EPS && abs(y) < EPS && abs(z) < EPS; }-----// 15
---bool isOnLine(L(A, B)) const {-----// 30
-----return ((A - *this) * (B - *this)).isZero(); }-----// 58
---bool isInSegment(L(A, B)) const {-----// f1
-----return isOnLine(A, B) && ((A - *this) % (B - *this)) < EPS; }-----// d9
---bool isInSegmentStrictly(L(A, B)) const {-----// 0e
-----return isOnLine(A, B) && ((A - *this) % (B - *this)) < -EPS; }-----// ba
---double getAngle() const {-----// 0f
-----return atan2(y, x); }-----// 40
---double getAngle(P(u)) const {-----// d5
-----return atan2((*this * u).length(), *this % u); }-----// 79
---bool isOnPlane(PL(A, B, C)) const {-----// 8e
-----return abs((A - *this) * (B - *this) % (C - *this)) < EPS; } };;-----// 74
int line_line_intersect(L(A, B), L(C, D), point3d &O){-----// dc
---if (abs((B - A) * (C - A) % (D - A)) > EPS) return 0;-----// 6a
---if (((A - B) * (C - D)).length() < EPS)-----// 79
-----return A.isOnLine(C, D) ? 2 : 0;-----// 09
---point3d normal = ((A - B) * (C - B)).normalize();-----// bc
---double s1 = (C - A) * (D - A) % normal;-----// 68
---O = A + ((B - A) / (s1 + ((D - B) * (C - B) % normal))) * s1;-----// 56
---return 1; }-----// a7
int line_plane_intersect(L(A, B), PL(C, D, E), point3d &O) {-----// 09
---double V1 = (C - A) * (D - A) % (E - A);-----// c1
---double V2 = (D - B) * (C - B) % (E - B);-----// 29
---if (abs(V1 + V2) < EPS)-----// 81
-----return A.isOnPlane(C, D, E) ? 2 : 0;-----// d5
---O = A + ((B - A) / (V1 + V2)) * V1;-----// 38
---return 1; }-----// ce
bool plane_plane_intersect(P(A), P(nA), P(B), P(nB), point3d &P, point3d &Q) {--// 5a
---point3d n = nA * nB;-----// 49
---if (n.isZero()) return false;-----// 03
---point3d v = n * nA;-----// d7
---P = A + (n * nA) * ((B - A) % nB / (v % nB));-----// 1a
---Q = P + n;-----// 9c
---return true; }-----// 1a
```

6.9. Polygon Centroid.

```
#include "polygon.cpp"-----// 58
point polygon_centroid(polygon p) {-----// 79
---double cx = 0.0, cy = 0.0;-----// d5
---double mnx = 0.0, mny = 0.0;-----// 22
---int n = size(p);-----// 2d
---rep(i,0,n)-----// 08
-----mnx = min(mnx, real(p[i])),-----// c6
-----mny = min(mny, imag(p[i]));-----// 84
---rep(i,0,n)-----// 3f
-----p[i] = point(real(p[i]) - mnx, imag(p[i]) - mny);-----// 49
---rep(i,0,n) {-----// 3c
-----int j = (i + 1) % n;-----// 5b
-----cx += (real(p[i]) + real(p[j])) * cross(p[i], p[j]);-----// 4f
-----cy += (imag(p[i]) + imag(p[j])) * cross(p[i], p[j]); }-----// 4a
---return point(cx, cy) / 6.0 / polygon_area_signed(p) + point(mnx, mny); }--// a1

6.10. Formulas. Let  $a = (a_x, a_y)$  and  $b = (b_x, b_y)$  be two-dimensional vectors.


- $a \cdot b = |a||b| \cos \theta$ , where  $\theta$  is the angle between  $a$  and  $b$ .
- $a \times b = |a||b| \sin \theta$ , where  $\theta$  is the signed angle between  $a$  and  $b$ .
- $a \times b$  is equal to the area of the parallelogram with two of its sides formed by  $a$  and  $b$ . Half of that is the area of the triangle formed by  $a$  and  $b$ .



7. OTHER ALGORITHMS

7.1. 2SAT.
#include "../graph/scc.cpp"-----// c3
-----// 63
bool two_sat(int n, const vii& clauses, vi& all_truthy) {-----// f4
---all_truthy.clear();-----// 31
---vvi adj(2*n+1);-----// 7b
---rep(i,0,size(clauses)) {-----// 76
-----adj[-clauses[i].first + n].push_back(clauses[i].second + n);-----// eb
-----if (clauses[i].first != clauses[i].second)-----// bc
-----adj[-clauses[i].second + n].push_back(clauses[i].first + n);-----// f0
---}-----// da
---pair<union_find, vi> res = scc(adj);-----// 00
---union_find scc = res.first;-----// 20
---vi dag = res.second;-----// ed
---vi truth(2*n+1, -1);-----// c7
---for (int i = 2*n; i >= 0; i--) {-----// 50
---int cur = order[i] - n, p = scc.find(cur + n), o = scc.find(-cur + n);--// 4f
---if (cur == 0) continue;-----// cd
---if (p == o) return false;-----// d0
---if (truth[p] == -1) truth[p] = 1;-----// d3
---truth[cur + n] = truth[p];-----// 50
---truth[o] = 1 - truth[p];-----// 8c
---if (truth[p] == 1) all_truthy.push_back(cur);-----// 55
---}-----// c3
---return true;-----// eb
}-----// 6b
```


7.2. Stable Marriage.

```
vi stable_marriage(int n, int** m, int** w) {-----// e4
---queue<int> q;-----// f6
---vi at(n, 0), eng(n, -1), res(n, -1); vvi inv(n, vi(n));-----// c3
---rep(i,0,n) rep(j,0,n) inv[i][w[i][j]] = j;-----// f1
---rep(i,0,n) q.push(i);-----// d8
---while (!q.empty()) {-----// 68
---    int curm = q.front(); q.pop();-----// e2
---    for (int &i = at[curm]; i < n; i++) {-----// 7e
---        int curw = m[curm][i];-----// 95
---        if (eng[curw] == -1) { }-----// f7
---        else if (inv[curw][curm] < inv[curw][eng[curw]])-----// d6
---            q.push(eng[curw]);-----// 2e
---        else continue;-----// 1d
---        res[eng[curw] = curm] = curw, ++i; break;-----// a1
---    }-----// c4
---}-----// 3d
---return res;-----// 42
}-----// bf
```

7.3. Algorithm X.

```
bool handle_solution(vi rows) { return false; }-----// 63
struct exact_cover {-----// 95
---struct node {-----// 7e
---    node *l, *r, *u, *d, *p;-----// 19
---    int row, col, size;-----// ae
---    node(int _row, int _col) : row(_row), col(_col) {-----// c9
---        size = 0; l = r = u = d = p = NULL; }-----// c3
---};-----// c1
---int rows, cols, *sol;-----// 7b
---bool **arr;-----// e6
---node *head;-----// fe
---exact_cover(int _rows, int _cols) : rows(_rows), cols(_cols), head(NULL) {--// b6
---    arr = new bool*[rows];-----// cf
---    sol = new int[rows];-----// 5f
---    rep(i,0,rows)-----// 9b
---        arr[i] = new bool[cols], memset(arr[i], 0, cols);-----// dd
---    }-----// 21
---    void set_value(int row, int col, bool val = true) { arr[row][col] = val; }--// 9e
---    void setup() {-----// a3
---        node ***ptr = new node**[rows + 1];-----// bd
---        rep(i,0,rows+1) {-----// 76
---            ptr[i] = new node*[cols];-----// eb
---            rep(j,0,cols)-----// cd
---                if (i == rows || arr[i][j]) ptr[i][j] = new node(i, j);-----// 16
---                else ptr[i][j] = NULL;-----// d2
---            }-----// ac
---        rep(i,0,rows+1) {-----// fc
---            rep(j,0,cols) {-----// 51
---                if (!ptr[i][j]) continue;-----// f7
---                int ni = i + 1, nj = j + 1;-----// 7a
```

```
-----while (true) {-----// fc
-----    if (ni == rows + 1) ni = 0;-----// 4c
-----    if (ni == rows || arr[ni][j]) break;-----// 8d
-----    ++ni;-----// 68
-----}-----// ad
-----    ptr[i][j]->d = ptr[ni][j];-----// 84
-----    ptr[ni][j]->u = ptr[i][j];-----// 66
-----    while (true) {-----// 7f
-----        if (nj == cols) nj = 0;-----// de
-----        if (i == rows || arr[i][nj]) break;-----// 4c
-----        ++nj;-----// c5
-----    }-----// 72
-----    ptr[i][j]->r = ptr[i][nj];-----// 60
-----    ptr[i][nj]->l = ptr[i][j];-----// 82
-----}-----// 0b
-----}-----// 16
-----head = new node(rows, -1);-----// 66
-----head->r = ptr[rows][0];-----// 3e
-----ptr[rows][0]->l = head;-----// 8c
-----head->l = ptr[rows][cols - 1];-----// 6a
-----ptr[rows][cols - 1]->r = head;-----// c1
-----rep(j,0,cols) {-----// 92
-----    int cnt = -1;-----// d4
-----    rep(i,0,rows+1)-----// bd
-----        if (ptr[i][j]) cnt++, ptr[i][j]->p = ptr[rows][j];-----// f3
-----    ptr[rows][j]->size = cnt;-----// c2
-----}-----// b9
-----rep(i,0,rows+1) delete[] ptr[i];-----// a5
-----delete[] ptr;-----// 72
}-----// 19
#define COVER(c, i, j) \
c->r->l = c->l, c->l->r = c->r; \
for (node *i = c->d; i != c; i = i->d) \
for (node *j = i->r; j != i; j = j->r) \
j->d->u = j->u, j->u->d = j->d, j->p->size--;
#define UNCOVER(c, i, j) \
for (node *i = c->u; i != c; i = i->u) \
for (node *j = i->l; j != i; j = j->l) \
j->p->size++, j->d->u = j->u->d = j; \
c->r->l = c->l->r = c;
bool search(int k = 0) {-----// f9
if (head == head->r) {-----// 75
vi res(k);-----// 90
rep(i,0,k) res[i] = sol[i];-----// 2a
sort(res.begin(), res.end());-----// 63
return handle_solution(res);-----// 11
}-----// 3d
node *c = head->r, *tmp = head->r;-----// a3
for ( ; tmp != head; tmp = tmp->r) if (tmp->size < c->size) c = tmp;-----// 41
if (c == c->d) return false;-----// 02
```

```
-----COVER(c, i, j);-----// f6
----bool found = false;-----// 8d
----for (node *r = c->d; !found && r != c; r = r->d) {-----// 78
-----sol[k] = r->row;-----// c0
-----for (node *j = r->r; j != r; j = j->r) { COVER(j->p, a, b); }-----// f9
-----found = search(k + 1);-----// fb
-----for (node *j = r->l; j != r; j = j->l) { UNCOVER(j->p, a, b); }-----// 87
-----}-----// 7c
-----UNCOVER(c, i, j);-----// a7
-----return found;-----// c0
----}-----// d2
};-----// d7
```

7.4. *nth* Permutation.

```
vector<int> nth_permutation(int cnt, int n) {-----// 78
----vector<int> idx(cnt), per(cnt), fac(cnt);-----// 9e
----rep(i,0,cnt) idx[i] = i;-----// bc
----rep(i,1,cnt+1) fac[i - 1] = n % i, n /= i;-----// 2b
----for (int i = cnt - 1; i >= 0; i--)-----// f9
-----per[cnt - i - 1] = idx[fac[i]], idx.erase(idx.begin() + fac[i]);-----// ee
----return per;-----// ab
}-----// 37
```

7.5. Cycle-Finding.

```
ii find_cycle(int x0, int (*f)(int)) {-----// a5
----int t = f(x0), h = f(t), mu = 0, lam = 1;-----// 8d
----while (t != h) t = f(t), h = f(f(h));-----// 79
----h = x0;-----// 04
----while (t != h) t = f(t), h = f(h), mu++;-----// 9d
----h = f(t);-----// 00
----while (t != h) h = f(h), lam++;-----// 5e
----return ii(mu, lam);-----// b4
}-----// 42
```

7.6. Dates.

```
int intToDay(int jd) { return jd % 7; }-----// 89
int dateToInt(int y, int m, int d) {-----// 96
----return 1461 * (y + 4800 + (m - 14) / 12) / 4 +-----// a8
----367 * (m - 2 - (m - 14) / 12 * 12) / 12-----// d1
----3 * ((y + 4900 + (m - 14) / 12) / 100) / 4 +-----// be
----d - 32075;-----// e0
}-----// fa
void intToDate(int jd, int &y, int &m, int &d) {-----// a1
----int x, n, i, j;-----// 00
----x = jd + 68569;-----// 11
----n = 4 * x / 146097;-----// 2f
----x -= (146097 * n + 3) / 4;-----// 58
----i = (4000 * (x + 1)) / 1461001;-----// 0d
----x -= 1461 * i / 4 - 31;-----// 09
----j = 80 * x / 2447;-----// 3d
----d = x - 2447 * j / 80;-----// eb
----x = j / 11;-----// b7
```

```
----m = j + 2 - 12 * x;-----// 82
----y = 100 * (n - 49) + i + x;-----// 70
}-----// af
```

8. USEFUL INFORMATION

8.1. Tips & Tricks.

- How fast does our algorithm have to be? Can we use brute-force?
- Does order matter?
- Is it better to look at the problem in another way? Maybe backwards?
- Are there subproblems that are recomputed? Can we cache them?
- Do we need to remember everything we compute, or just the last few iterations of computation?
- Does it help to sort the data?
- Can we speed up lookup by using a map (tree or hash) or an array?
- Can we binary search the answer?
- Can we add vertices/edges to the graph to make the problem easier? Can we turn the graph into some other kind of a graph (perhaps a DAG, or a flow network)?
- Make sure integers are not overflowing.
- Is it better to compute the answer modulo n ? Perhaps we can compute the answer modulo m_1, m_2, \dots, m_k , where m_1, m_2, \dots, m_k are pairwise coprime integers, and find the real answer using CRT?
- Are there any edge cases? When $n = 0, n = -1, n = 1, n = 2^{31} - 1$ or $n = -2^{31}$? When the list is empty, or contains a single element? When the graph is empty, or contains a single vertex? When the graph contains self-loops? When the polygon is concave or non-simple?
- Can we use exponentiation by squaring?

8.2. Fast Input Reading.

```
void readn(register int *n) {-----// dc
----int sign = 1;-----// 32
----register char c;-----// a5
----*n = 0;-----// 35
----while((c = getc_unlocked(stdin)) != '\n') {-----// f3
----switch(c) {-----// 0c
----case '-': sign = -1; break;-----// 28
----case ' ': goto hell;-----// fd
----case '\n': goto hell;-----// 79
----default: *n *= 10; *n += c - '0'; break;-----// c0
----}-----// 2d
----}-----// c3
hell:-----// ba
----*n *= sign;-----// a0
}-----// 67
```

8.3. Bit Hacks.

- $n \& -n$ returns the first set bit in n .
 - $n \& (n - 1)$ is 0 only if n is a power of two.
 - `snoob(x)` returns the next integer that has the same amount of bits set as x . Useful for iterating through subsets of some specified size.
- ```
int snoob(int x) {-----
----int y = x & -x, z = x + y;-----
----return z | ((x ^ z) >> 2) / y;-----
}-----
```