

viRUs

Team Reference Document

04/12/2015

CONTENTS

1.	Code Templates	2	5.7.	Divisor Sieve	15
1.1.	Basic Configuration	2	5.8.	Modular Multiplicative Inverse	15
1.2.	C++ Header	2	5.9.	Primitive Root	15
1.3.	Java Template	2	5.10.	Chinese Remainder Theorem	15
2.	Data Structures	2	5.11.	Linear Congruence Solver	15
2.1.	Union-Find	2	5.12.	Numeric Integration	15
2.2.	Segment Tree	2	5.13.	Fast Fourier Transform	15
2.3.	Fenwick Tree	3	5.14.	Number-Theoretic Transform	16
2.4.	Matrix	3	5.15.	Tridiagonal Matrix Algorithm	16
2.5.	Cartesian Tree	4	5.16.	Mertens Function	16
2.6.	Misof Tree	4	5.17.	Numbers and Sequences	17
2.7.	Sqrt Decomposition	4	6.	Geometry	17
2.8.	Monotonic Queue	5	6.1.	Primitives	17
2.9.	Convex Hull Trick	5	6.2.	Lines	17
3.	Graphs	5	6.3.	Circles	17
3.1.	Single-Source Shortest Paths	5	6.4.	Polygon	18
3.2.	Strongly Connected Components	6	6.5.	Convex Hull	18
3.3.	Cut Points and Bridges	6	6.6.	Line Segment Intersection	18
3.4.	Euler Path	7	6.7.	Great-Circle Distance	18
3.5.	Bipartite Matching	7	6.8.	Triangle Circumcenter	19
3.6.	Maximum Flow	8	6.9.	Closest Pair of Points	19
3.7.	Minimum Cost Maximum Flow	8	6.10.	3D Primitives	19
3.8.	All Pairs Maximum Flow	9	6.11.	Polygon Centroid	20
3.9.	Heavy-Light Decomposition	10	6.12.	Rotating Calipers	20
3.10.	Centroid Decomposition	10	6.13.	Formulas	20
3.11.	Least Common Ancestors, Binary Jumping	11	7.	Other Algorithms	20
3.12.	Tarjan's Off-line Lowest Common Ancestors Algorithm	11	7.1.	2SAT	20
3.13.	Maximum Density Subgraph	11	7.2.	Stable Marriage	21
3.14.	Maximum Weighted Independent Set in a Bipartite Graph	11	7.3.	Algorithm X	21
4.	Strings	11	7.4.	n th Permutation	22
4.1.	The Knuth-Morris-Pratt algorithm	11	7.5.	Cycle-Finding	22
4.2.	The Z algorithm	12	7.6.	Dates	22
4.3.	Suffix Array	12	7.7.	Simulated Annealing	22
4.4.	Aho-Corasick Algorithm	12	7.8.	Fast Input Reading	23
4.5.	eerTree	13	7.9.	Bit Hacks	23
4.6.	Suffix Automaton	13	7.10.	The Twelfefold Way	23
4.7.	Hashing	14	8.	Useful Information	24
5.	Mathematics	14	9.	Misc	24
5.1.	Binomial Coefficients	14	9.1.	Debugging Tips	24
5.2.	Euclidean algorithm	14	9.2.	Solution Ideas	24
5.3.	Trial Division Primality Testing	14	10.	Formulas	25
5.4.	Miller-Rabin Primality Test	14	10.1.	Markov Chains	25
5.5.	Pollard's ρ algorithm	14	10.2.	Burnside's Lemma	25
5.6.	Sieve of Eratosthenes	14	10.3.	Bézout's identity	25
			10.4.	Misc	25
				Practice Contest Checklist	26

1. CODE TEMPLATES

1.1. Basic Configuration.

1.1.1. .bashrc.

```
xset r rate 150 100-----// dd
set -o vi-----// f4
-----// 08
function check {-----// f6
---IFS=-----// 17
---s=""-----// 22
---cat $1 | while read l; do-----// 81
-----s="$s$(echo $l | sed 's/\s//g')\n"-----// d0
-----h=$(echo -ne "$s" | md5sum)-----// 27
-----echo "${h:0:2} $l"-----// 1b
---done-----// aa
}-----// a7
# setxkbmap -option caps:escape dvorak is-----// 18
# setxkbmap en_US-----// 97
alias c='cd'-----// 7e
alias l='ls -lh'-----// 36
alias la='ls -lah'-----// 7c
```

ProTip™: setxkbmap dvorak on qwerty: o.yqtxmal ekrpat

1.1.2. .vimrc.

```
set nosp et sw=4 ts=4 sts=4 si cindent hi=1000 nu ru noeb showcmd showmode-----// bb
syn on | colorscheme slate-----// e5
```

1.2. C++ Header. A C++ header.

```
#include <bits/stdc++.h>-----// 84
using namespace std;-----// 16
template <class T> int size(const T &x) { return x.size(); }-----// 5f
#define rep(i,a,b) for (__typeof(a) i=(a); i<(b); ++i)-----// 6c
#define iter(it,c) for (__typeof((c).begin()) it = (c).begin(); it != (c).end(); ++it)
typedef pair<int, int> ii;-----// 44
typedef vector<int> vi;-----// 9d
typedef vector<ii> vii;-----// eb
typedef long long ll;-----// 47
const int INF = ~(1<<31); // 2147483647-----// 10
-----// b2
const double EPS = 1e-9;-----// d5
const double pi = acos(-1);-----// 67
typedef unsigned long long ull;-----// ff
typedef vector<vi> vvi;-----// 4b
typedef vector<vii> vvii;-----// 36
template <class T> T mod(T a, T b) { return (a % b + b) % b; }-----// d5
```

1.3. Java Template. A Java template.

```
import java.util.*;-----// 37
import java.math.*;-----// 89
import java.io.*;-----// 28
-----// a3
public class Main {-----// 17
```

```
----public static void main(String[] args) throws Exception {-----// 02
-----Scanner in = new Scanner(System.in);-----// ef
-----PrintWriter out = new PrintWriter(System.out, false);-----// 62
-----// code-----// e6
-----out.flush();-----// 56
----}-----// 79
}-----// 00
```

2. DATA STRUCTURES

2.1. Union-Find.

```
struct union_find {-----// 42
---vi p; union_find(int n) : p(n, -1) { }-----// 28
---int find(int x) { return p[x] < 0 ? x : p[x] = find(p[x]); }-----// ba
---bool unite(int x, int y) {-----// 6c
---int xp = find(x), yp = find(y);-----// 64
---if (xp == yp) return false;-----// 0b
---if (p[xp] > p[yp]) swap(xp,yp);-----// 78
---p[xp] += p[yp], p[yp] = xp;-----// 88
---return true; }-----// 1f
---int size(int x){ return -p[find(x)]; } };
```

2.2. Segment Tree.

```
#ifdef SEG_MIN-----// 03
const int ID = INF;-----// 56
int f(int a, int b) { return min(a, b); }-----// 4f
#else-----// 0e
const int ID = 0;-----// 3e
int f(int a, int b) { return a + b; }-----// dd
#endif-----// 16
struct segment_tree {-----// ab
---int n; vi data, lazy;-----// dd
---segment_tree() {}-----// 93
---segment_tree(const vi &arr) : n(size(arr)), data(4*n), lazy(4*n,INF) {-----// f1
---mk(arr, 0, n-1, 0); }-----// e9
---int mk(const vi &arr, int l, int r, int i) {-----// 12
---if (l == r) return data[i] = arr[l];-----// 5b
---int m = (l + r) / 2;-----// de
---return data[i] = f(mk(arr, l, m, 2*i+1), mk(arr, m+1, r, 2*i+2)); }-----// 0a
---int query(int a, int b) { return q(a, b, 0, n-1, 0); }-----// f6
---int q(int a, int b, int l, int r, int i) {-----// 22
---propagate(l, r, i);-----// 12
---if (r < a || b < l) return ID;-----// c7
---if (a <= l && r <= b) return data[i];-----// ce
---int m = (l + r) / 2;-----// 7a
---return f(q(a, b, l, m, 2*i+1), q(a, b, m+1, r, 2*i+2)); }-----// 5c
---void update(int i, int v) { u(i, v, 0, n-1, 0); }-----// 90
---int u(int i, int v, int l, int r, int j) {-----// 02
---propagate(l, r, j);-----// ae
---if (r < i || i < l) return data[j];-----// 92
---if (l == i && r == i) return data[j] = v;-----// 4a
---int m = (l + r) / 2;-----// cb
```

```

-----return data[j] = f(u(i, v, l, m, 2*j+1), u(i, v, m+1, r, 2*j+2)); }-----// 34
---void range_update(int a, int b, int v) { ru(a, b, v, 0, n-1, 0); }-----// 71
---int ru(int a, int b, int v, int l, int r, int i) {-----// e0
-----propagate(l, r, i);-----// 19
-----if (l > r) return ID;-----// cc
-----if (r < a || b < l) return data[i];-----// d9
-----if (a <= l && r <= b) return (lazy[i] = v) * (r - l + 1) + data[i];-----// 06
-----int m = (l + r) / 2;-----// cc
-----return data[i] = f(ru(a, b, v, l, m, 2*i+1),-----// cc
-----ru(a, b, v, m+1, r, 2*i+2));-----// 2b
-----}-----// 0b
---void propagate(int l, int r, int i) {-----// a7
-----if (l > r || lazy[i] == INF) return;-----// 5f
-----data[i] += lazy[i] * (r - l + 1);-----// 44
-----if (l < r) {-----// 28
-----if (lazy[2*i+1] == INF) lazy[2*i+1] = lazy[i];-----// 4e
-----else lazy[2*i+1] += lazy[i];-----// 1e
-----if (lazy[2*i+2] == INF) lazy[2*i+2] = lazy[i];-----// de
-----else lazy[2*i+2] += lazy[i];-----// 74
-----}-----// 1f
-----lazy[i] = INF;-----// f8
---}-----// 41
};-----// ae

```

2.2.1. Persistent Segment Tree.

```

int segcnt = 0;-----// cf
struct segment {-----// 68
---int l, r, lid, rid, sum;-----// fc
} segs[2000000];-----// dd
int build(int l, int r) {-----// 2b
---if (l > r) return -1;-----// 4e
---int id = segcnt++;-----// a8
---segs[id].l = l;-----// 90
---segs[id].r = r;-----// 19
---if (l == r) segs[id].lid = -1, segs[id].rid = -1;-----// ee
---else {-----// fe
-----int m = (l + r) / 2;-----// 14
-----segs[id].lid = build(l, m);-----// e3
-----segs[id].rid = build(m + 1, r); }-----// 69
---segs[id].sum = 0;-----// 21
---return id; }-----// c5
int update(int idx, int v, int id) {-----// b8
---if (id == -1) return -1;-----// bb
---if (idx < segs[id].l || idx > segs[id].r) return id;-----// fb
---int nid = segcnt++;-----// b3
---segs[nid].l = segs[id].l;-----// 78
---segs[nid].r = segs[id].r;-----// ca
---segs[nid].lid = update(idx, v, segs[id].lid);-----// 92
---segs[nid].rid = update(idx, v, segs[id].rid);-----// 06
---segs[nid].sum = segs[id].sum + v;-----// 1a
---return nid; }-----// e6

```

```

int query(int id, int l, int r) {-----// a2
---if (r < segs[id].l || segs[id].r < l) return 0;-----// 17
---if (l <= segs[id].l && segs[id].r <= r) return segs[id].sum;-----// ad
---return query(segs[id].lid, l, r) + query(segs[id].rid, l, r); }-----// ee

```

2.3. Fenwick Tree.

```

struct fenwick_tree {-----// 98
---int n; vi data;-----// d3
---fenwick_tree(int _n) : n(_n), data(vi(n)) { }-----// db
---void update(int at, int by) {-----// 76
-----while (at < n) data[at] += by, at |= at + 1; }-----// fb
---int query(int at) {-----// 71
---int res = 0;-----// c3
-----while (at >= 0) res += data[at], at = (at & (at + 1)) - 1;-----// 37
---return res; }-----// e4
---int rsq(int a, int b) { return query(b) - query(a - 1); }-----// be
};-----// 57
struct fenwick_tree_sq {-----// d4
---int n; fenwick_tree x1, x0;-----// 18
---fenwick_tree_sq(int _n) : n(_n), x1(fenwick_tree(n)),-----// 2e
-----x0(fenwick_tree(n)) { }-----// 7c
---// insert f(y) = my + c if x <= y-----// 17
---void update(int x, int m, int c) { x1.update(x, m); x0.update(x, c); }-----// 45
---int query(int x) { return x*x1.query(x) + x0.query(x); }-----// 73
};-----// 13
void range_update(fenwick_tree_sq &s, int a, int b, int k) {-----// 89
---s.update(a, k, k * (1 - a)); s.update(b+1, -k, k * b); }-----// 7f
int range_query(fenwick_tree_sq &s, int a, int b) {-----// 15
---return s.query(b) - s.query(a-1); }-----// f3

```

2.4. Matrix.

```

template<class K> bool eq(K a, K b) { return a == b; }-----// 2a
template<> bool eq<double>(double a, double b) { return abs(a - b) < EPS; }-----// a7
template<class T> struct matrix {-----// 0a
---int rows, cols, cnt; vector<T> data;-----// a1
---inline T& at(int i, int j) { return data[i * cols + j]; }-----// 5c
---matrix(int r, int c) : rows(r), cols(c), cnt(r * c) {-----// 56
-----data.assign(cnt, T(0)); }-----// e3
---matrix(const matrix& other) : rows(other.rows), cols(other.cols),-----// b5
-----cnt(other.cnt), data(other.data) { }-----// c1
---T& operator()(int i, int j) { return at(i, j); }-----// 29
---matrix<T> operator +(const matrix& other) {-----// 33
-----matrix<T> res(*this); rep(i,0,cnt) res.data[i] += other.data[i];-----// f8
-----return res; }-----// 09
---matrix<T> operator -(const matrix& other) {-----// 91
-----matrix<T> res(*this); rep(i,0,cnt) res.data[i] -= other.data[i];-----// 7b
-----return res; }-----// 9a
---matrix<T> operator *(T other) {-----// 99
-----matrix<T> res(*this); rep(i,0,cnt) res.data[i] *= other;-----// 05
-----return res; }-----// 8c
---matrix<T> operator *(const matrix& other) {-----// 31
-----matrix<T> res(rows, other.cols);-----// 4c

```

```

-----rep(i,0,rows) rep(j,0,other.cols) rep(k,0,cols)-----// ae
-----res(i, j) += at(i, k) * other.data[k * other.cols + j];-----// 17
-----return res; }-----// 65
---matrix<T> pow(int p) {-----// 53
---matrix<T> res(rows, cols), sq(*this);-----// 87
---rep(i,0,rows) res(i, i) = T(1);-----// 9d
---while (p) {-----// 79
---    if (p & 1) res = res * sq;-----// 62
---    p >>= 1;-----// 79
---    if (p) sq = sq * sq;-----// 35
---} return res; }-----// 22
---matrix<T> rref(T &det, int &rank) {-----// 2a
---matrix<T> mat(*this); det = T(1), rank = max(rows, cols);-----// 7a
---for (int r = 0, c = 0; c < cols; c++) {-----// 8e
---    int k = r;-----// 5b
---    while (k < rows && eq<T>(mat(k, c), T(0))) k++;-----// 3e
---    if (k >= rows) { rank--; continue; }-----// 1a
---    if (k != r) {-----// c4
---        det *= T(-1);-----// 55
---        rep(i,0,cols)-----// e1
---            swap(mat.at(k, i), mat.at(r, i));-----// 7d
---    } det *= mat(r, r);-----// b6
---    T d = mat(r,c);-----// 66
---    rep(i,0,cols) mat(r, i) /= d;-----// d1
---    rep(i,0,rows) {-----// f6
---        T m = mat(i, c);-----// 05
---        if (i != r && !eq<T>(m, T(0)))-----// 1a
---            rep(j,0,cols) mat(i, j) -= m * mat(r, j);-----// 7b
---    } r++;-----// c5
---} return mat; }-----// b3
---matrix<T> transpose() {-----// 59
---matrix<T> res(cols, rows);-----// 5b
---rep(i,0,rows) rep(j,0,cols) res(j, i) = at(i, j);-----// 92
---return res; } }-----// df

```

2.5. Cartesian Tree.

```

struct node {-----// 36
---int x, y, sz;-----// e5
---node *l, *r;-----// 4d
---node(int _x, int _y) : x(_x), y(_y), sz(1), l(NULL), r(NULL) { } }-----// 19
int tsize(node* t) { return t ? t->sz : 0; }-----// 42
void augment(node *t) { t->sz = 1 + tsize(t->l) + tsize(t->r); }-----// 1d
pair<node*,node*> split(node *t, int x) {-----// 1d
---if (!t) return make_pair((node*)NULL,(node*)NULL);-----// fd
---if (t->x < x) {-----// 0a
---    pair<node*,node*> res = split(t->r, x);-----// b4
---    t->r = res.first; augment(t);-----// 4d
---    return make_pair(t, res.second); }-----// e0
---pair<node*,node*> res = split(t->l, x);-----// b7
---t->l = res.second; augment(t);-----// 74
---return make_pair(res.first, t); }-----// 46

```

```

node* merge(node *l, node *r) {-----// 3c
---if (!l) return r; if (!r) return l;-----// f0
---if (l->y > r->y) { l->r = merge(l->r, r); augment(l); return l; }-----// be
---r->l = merge(l, r->l); augment(r); return r; }-----// c0
node* find(node *t, int x) {-----// b4
---while (t) {-----// 51
---    if (x < t->x) t = t->l;-----// 32
---    else if (t->x < x) t = t->r;-----// da
---    else return t; }-----// 0b
---return NULL; }-----// ae
node* insert(node *t, int x, int y) {-----// 78
---if (find(t, x) != NULL) return t;-----// 2f
---pair<node*,node*> res = split(t, x);-----// ca
---return merge(res.first, merge(new node(x, y), res.second)); }-----// 0d
node* erase(node *t, int x) {-----// 4d
---if (!t) return NULL;-----// 7b
---if (t->x < x) t->r = erase(t->r, x);-----// 7c
---else if (x < t->x) t->l = erase(t->l, x);-----// 48
---else { node *old = t; t = merge(t->l, t->r); delete old; }-----// 22
---if (t) augment(t); return t; }-----// a3
int kth(node *t, int k) {-----// b3
---if (k < tsize(t->l)) return kth(t->l, k);-----// 64
---else if (k == tsize(t->l)) return t->x;-----// 97
---else return kth(t->r, k - tsize(t->l) - 1); }-----// f0

```

2.6. Misof Tree.

```

#define BITS 15-----// 7b
struct misof_tree {-----// fe
---int cnt[BITS][1<<BITS];-----// aa
---misof_tree() { memset(cnt, 0, sizeof(cnt)); }-----// b0
---void insert(int x) { for (int i = 0; i < BITS; cnt[i++][x]++, x >>= 1); }-----// 5a
---void erase(int x) { for (int i = 0; i < BITS; cnt[i++][x]--, x >>= 1); }-----// 49
---int nth(int n) {-----// 8a
---    int res = 0;-----// a4
---    for (int i = BITS-1; i >= 0; i--)-----// 99
---        if (cnt[i][res <= 1] <= n) n -= cnt[i][res], res |= 1;-----// f4
---    return res;-----// 3a
---}-----// b5
};-----// 0a

```

2.7. Sqrt Decomposition.

```

struct segment {-----// b2
---vi arr;-----// 8c
---segment(vi _arr) : arr(_arr) { } }-----// 11
vector<segment> T;-----// a1
int K;-----// dc
void rebuild() {-----// 17
---    int cnt = 0;-----// 14
---    rep(i,0,size(T))-----// b1
---        cnt += size(T[i].arr);-----// d1
---    K = static_cast<int>(ceil(sqrt(cnt)) + 1e-9);-----// 4c
---    vi arr(cnt);-----// 14

```

```
---for (int i = 0, at = 0; i < size(T); i++)-----// 79
-----rep(j,0,size(T[i].arr))-----// a4
-----arr[at++] = T[i].arr[j];-----// f7
---T.clear();-----// 4c
---for (int i = 0; i < cnt; i += K)-----// 79
-----T.push_back(segment(vi(arr.begin()+i, arr.begin()+min(i+K, cnt))));-----// f0
}-----// 03
int split(int at) {-----// 71
---int i = 0;-----// 8a
---while (i < size(T) && at >= size(T[i].arr))-----// 6c
---at -= size(T[i].arr), i++;-----// 9a
---if (i >= size(T)) return size(T);-----// 83
---if (at == 0) return i;-----// 49
---T.insert(T.begin() + i + 1, segment(vi(T[i].arr.begin() + at, T[i].arr.end())));
---T[i] = segment(vi(T[i].arr.begin(), T[i].arr.begin() + at));-----// af
---return i + 1;-----// ac
}-----// ea
void insert(int at, int v) {-----// 5f
---vi arr; arr.push_back(v);-----// 6a
---T.insert(T.begin() + split(at), segment(arr));-----// 67
}-----// cc
void erase(int at) {-----// be
---int i = split(at); split(at + 1);-----// da
---T.erase(T.begin() + i);-----// 6b
}-----// 4b
```

2.8. Monotonic Queue.

```
struct min_stack {-----// d8
---stack<int> S, M;-----// fe
---void push(int x) {-----// 20
-----S.push(x);-----// e2
-----M.push(M.empty() ? x : min(M.top(), x)); }-----// 92
---int top() { return S.top(); }-----// f1
---int mn() { return M.top(); }-----// 02
---void pop() { S.pop(); M.pop(); }-----// fd
---bool empty() { return S.empty(); }-----// d2
};-----// 74
struct min_queue {-----// b4
---min_stack inp, outp;-----// 3d
---void push(int x) { inp.push(x); }-----// 6b
---void fix() {-----// 5d
-----if (outp.empty()) while (!inp.empty())-----// 3b
-----outp.push(inp.top()), inp.pop();-----// 8e
-----}-----// 3f
---int top() { fix(); return outp.top(); }-----// dc
---int mn() {-----// 39
-----if (inp.empty()) return outp.mn();-----// 01
-----if (outp.empty()) return inp.mn();-----// 90
-----return min(inp.mn(), outp.mn()); }-----// 97
---void pop() { fix(); outp.pop(); }-----// 4f
```

```
---bool empty() { return inp.empty() && outp.empty(); }-----// 65
};-----// 60
```

2.9. Convex Hull Trick.

```
struct convex_hull_trick {-----// 16
---vector<pair<double,double> > h;-----// b4
---double intersect(int i) {-----// 9b
-----return (h[i+1].second-h[i].second)/(h[i].first-h[i+1].first); }-----// b9
---void add(double m, double b) {-----// a4
-----h.push_back(make_pair(m,b));-----// f9
-----while (size(h) >= 3) {-----// f6
-----int n = size(h);-----// d8
-----if (intersect(n-3) < intersect(n-2)) break;-----// 07
-----swap(h[n-2], h[n-1]);-----// bf
-----h.pop_back(); } }-----// 4b
---double get_min(double x) {-----// b0
-----int lo = 0, hi = size(h) - 2, res = -1;-----// 5b
-----while (lo <= hi) {-----// 24
-----int mid = lo + (hi - lo) / 2;-----// 5a
-----if (intersect(mid) <= x) res = mid, lo = mid + 1;-----// 1d
-----else hi = mid - 1; }-----// b6
-----return h[res+1].first * x + h[res+1].second; } }-----// 84
```

3. GRAPHS

3.1. Single-Source Shortest Paths.

3.1.1. Dijkstra’s algorithm.

```
int *dist, *dad;-----// 46
struct cmp {-----// a5
---bool operator()(int a, int b) {-----// bb
-----return dist[a] != dist[b] ? dist[a] < dist[b] : a < b; }-----// e6
};-----// 41
pair<int*, int*> dijkstra(int n, int s, vii *adj) {-----// 53
---dist = new int[n];-----// 84
---dad = new int[n];-----// 05
---rep(i,0,n) dist[i] = INF, dad[i] = -1;-----// 80
---set<int, cmp> pq;-----// 98
---dist[s] = 0, pq.insert(s);-----// 1f
---while (!pq.empty()) {-----// 47
-----int cur = *pq.begin(); pq.erase(pq.begin());-----// 58
-----rep(i,0,size(adj[cur])) {-----// a6
-----int nxt = adj[cur][i].first,-----// a4
-----ndist = dist[cur] + adj[cur][i].second;-----// 3a
-----if (ndist < dist[nxt]) pq.erase(nxt),-----// 2d
-----dist[nxt] = ndist, dad[nxt] = cur, pq.insert(nxt);-----// eb
-----}-----// d2
---}-----// df
---return pair<int*, int*>(dist, dad);-----// e3
}-----// 9b
```

3.1.2. Bellman-Ford algorithm.

```

int* bellman_ford(int n, int s, vii* adj, bool& has_negative_cycle) {-----// cf
---has_negative_cycle = false;-----// 47
---int* dist = new int[n];-----// 7f
---rep(i,0,n) dist[i] = i == s ? 0 : INF;-----// df
---rep(i,0,n-1) rep(j,0,n) if (dist[j] != INF)-----// 4d
-----rep(k,0,size(adj[j]))-----// 88
-----dist[adj[j][k].first] = min(dist[adj[j][k].first],-----// e1
-----dist[j] + adj[j][k].second);-----// 18
---rep(j,0,n) rep(k,0,size(adj[j]))-----// f8
---if (dist[j] + adj[j][k].second < dist[adj[j][k].first])-----// 37
-----has_negative_cycle = true;-----// f1
---return dist;-----// 78
}-----// a9

```

3.1.3. IDA* algorithm.

```

int n, cur[100], pos;-----// 48
int calch() {-----// 88
---int h = 0;-----// 4a
---rep(i,0,n) if (cur[i] != 0) h += abs(i - cur[i]);-----// 9b
---return h;-----// c6
}-----// c8
int dfs(int d, int g, int prev) {-----// 12
---int h = calch();-----// 5d
---if (g + h > d) return g + h;-----// 15
---if (h == 0) return 0;-----// ff
---int mn = INF;-----// 7e
---rep(di,-2,3) {-----// 0d
-----if (di == 0) continue;-----// 0a
-----int nxt = pos + di;-----// 76
-----if (nxt == prev) continue;-----// 39
-----if (0 <= nxt && nxt < n) {-----// 68
-----swap(cur[pos], cur[nxt]);-----// 35
-----swap(pos,nxt);-----// 64
-----mn = min(mn, dfs(d, g+1, nxt));-----// 22
-----swap(pos,nxt);-----// 84
-----swap(cur[pos], cur[nxt]);-----// 3b
-----}-----// 46
-----if (mn == 0) break;-----// 8f
---}-----// d3
---return mn;-----// da
}-----// f8
int idastar() {-----// 22
---rep(i,0,n) if (cur[i] == 0) pos = i;-----// 6b
---int d = calch();-----// 38
---while (true) {-----// 18
-----int nd = dfs(d, 0, -1);-----// 42
-----if (nd == 0 || nd == INF) return d;-----// b5
-----d = nd;-----// f7
---}-----// f9
}-----// 82

```

3.2. Strongly Connected Components.

3.2.1. Kosaraju's algorithm.

```

#include "../data-structures/union_find.cpp"-----// 5e
-----// 11
vector<bool> visited;-----// 66
vi order;-----// 9b
-----// a5
void scc_dfs(const vvi &adj, int u) {-----// a1
---int v; visited[u] = true;-----// e3
---rep(i,0,size(adj[u]))-----// 2d
---if (!visited[v = adj[u][i]]) scc_dfs(adj, v);-----// a2
---order.push_back(u);-----// 02
}-----// 53
-----// 63
pair<union_find, vi> scc(const vvi &adj) {-----// c2
---int n = size(adj), u, v;-----// f8
---order.clear();-----// 20
---union_find uf(n);-----// a8
---vi dag;-----// 61
---vvi rev(n);-----// c5
---rep(i,0,n) rep(j,0,size(adj[i])) rev[adj[i][j]].push_back(i);-----// 7e
---visited.resize(n, fill(visited.begin(), visited.end(), false));-----// 80
---rep(i,0,n) if (!visited[i]) scc_dfs(rev, i);-----// 4e
---fill(visited.begin(), visited.end(), false);-----// 59
---stack<int> S;-----// bb
---for (int i = n-1; i >= 0; i--) {-----// 96
-----if (visited[order[i]]) continue;-----// db
-----S.push(order[i], dag.push_back(order[i]));-----// 68
-----while (!S.empty()) {-----// 9e
-----visited[u = S.top()] = true, S.pop(), uf.unite(u, order[i]);-----// b3
-----rep(j,0,size(adj[u])) if (!visited[v = adj[u][j]]) S.push(v);-----// 1b
-----}-----// 61
---}-----// 57
---return pair<union_find, vi>(uf, dag);-----// 2b
}-----// 92

```

3.3. Cut Points and Bridges.

```

#define MAXN 5000-----// f7
int low[MAXN], num[MAXN], curnum;-----// d7
void dfs(const vvi &adj, vi &cp, vii &bri, int u, int p) {-----// 22
---low[u] = num[u] = curnum++;-----// a3
---int cnt = 0; bool found = false;-----// 97
---rep(i,0,size(adj[u])) {-----// ae
-----int v = adj[u][i];-----// 56
-----if (num[v] == -1) {-----// 3b
-----dfs(adj, cp, bri, v, u);-----// ba
-----low[u] = min(low[u], low[v]);-----// be
-----cnt++;-----// e0
-----found = found || low[v] >= num[u];-----// 30
-----if (low[v] > num[u]) bri.push_back(ii(u, v));-----// bf
-----} else if (p != v) low[u] = min(low[u], num[v]); }-----// 76

```


Reykjavík University

3.4. Euler Path.

3.5. Bipartite Matching.

3.5.1. Alternating Paths algorithm.

3.5.2. Hopcroft-Karp algorithm.

Running time is $O(|E|\sqrt{|V|})$.

3.5.2. Hopcroft-Karp algorithm.

3.6. Maximum Flow.

3.6.1. *Dinic’s algorithm.* An implementation of Dinic’s algorithm that runs in $O(|V|^2|E|)$.

```
#define MAXV 2000-----// ba
int q[MAXV], d[MAXV];-----// e6
struct flow_network {-----// 12
    struct edge {-----// 1e
        int v, cap, nxt;-----// ab
        edge() { }-----// 38
        edge(int _v, int _cap, int _nxt) : v(_v), cap(_cap), nxt(_nxt) { }-----// bc
    };-----// 6e
    int n, ecnt, *head, *curh;-----// 46
    vector<edge> e, e_store;-----// 1f
    flow_network(int _n, int m = -1) : n(_n), ecnt(0) {-----// d3
        e.reserve(2 * (m == -1 ? n : m));-----// 24
        head = new int[n], curh = new int[n];-----// 6b
        memset(head, -1, n * sizeof(int));-----// 56
    }-----// 77
    void destroy() { delete[] head; delete[] curh; }-----// f6
    void reset() { e = e_store; }-----// 87
    void add_edge(int u, int v, int uv, int vu = 0) {-----// cd
        e.push_back(edge(v, uv, head[u])); head[u] = ecnt++;-----// c9
        e.push_back(edge(u, vu, head[v])); head[v] = ecnt++;-----// 89
    }-----// 14
    int augment(int v, int t, int f) {-----// 3f
        if (v == t) return f;-----// 6d
        for (int &i = curh[v], ret; i != -1; i = e[i].nxt)-----// f9
            if (e[i].cap > 0 && d[e[i].v] + 1 == d[v])-----// cc
                if ((ret = augment(e[i].v, t, min(f, e[i].cap))) > 0)-----// 1f
                    return (e[i].cap -= ret, e[i^1].cap += ret, ret);-----// ac
        return 0;-----// 19
    }-----// fd
    int max_flow(int s, int t, bool res = true) {-----// 31
        if(s == t) return 0;-----// 9d
        e_store = e;-----// 57
        int f = 0, x, l, r;-----// 0e
        while (true) {-----// b5
            memset(d, -1, n * sizeof(int));-----// a8
            l = r = 0, d[q[r++] = t] = 0;-----// 0e
            while (l < r)-----// 7a
                for (int v = q[l++], i = head[v]; i != -1; i = e[i].nxt)-----// a2
                    if (e[i^1].cap > 0 && d[e[i].v] == -1)-----// 29
                        d[q[r++] = e[i].v] = d[v]+1;-----// 28
                if (d[s] == -1) break;-----// a0
            memcpy(curh, head, n * sizeof(int));-----// 10
            while ((x = augment(s, t, INF)) != 0) f += x;-----// a6
        }-----// 96
        if (res) reset();-----// 21
        return f;-----// b6
    }-----// 1b
};-----// 3b
```

3.7. Minimum Cost Maximum Flow. Running time is $O(|V|^2|E|\log|V|)$. NOTE: Doesn’t work on negative weights!

```
#define MAXV 2000-----// ba
int d[MAXV], p[MAXV], pot[MAXV];-----// 80
struct cmp {-----// d1
    bool operator()(int i, int j) {-----// 8a
        return d[i] == d[j] ? i < j : d[i] < d[j];-----// 89
    }-----// df
};-----// cf
struct flow_network {-----// eb
    struct edge {-----// 9a
        int v, cap, cost, nxt;-----// ad
        edge(int _v, int _cap, int _cost, int _nxt)-----// ec
            : v(_v), cap(_cap), cost(_cost), nxt(_nxt) { }-----// c4
    };-----// ad
    int n, ecnt, *head;-----// 46
    vector<edge> e, e_store;-----// 4b
    flow_network(int _n, int m = -1) : n(_n), ecnt(0) {-----// dd
        e.reserve(2 * (m == -1 ? n : m));-----// e6
        memset(head = new int[n], -1, n << 2);-----// 6c
    }-----// f3
    void destroy() { delete[] head; }-----// ac
    void reset() { e = e_store; }-----// 88
    void add_edge(int u, int v, int cost, int uv, int vu=0) {-----// b4
        e.push_back(edge(v, uv, cost, head[u])); head[u] = ecnt++;-----// 43
        e.push_back(edge(u, vu, -cost, head[v])); head[v] = ecnt++;-----// 53
    }-----// 16
    int min_cost_max_flow(int s, int t, bool res = true) {-----// 6d
        if (s == t) return ii(0, 0);-----// 34
        e_store = e;-----// 70
        memset(pot, 0, n << 2);-----// 24
        int f = 0, c = 0, v;-----// d4
        while (true) {-----// 29
            memset(d, -1, n << 2);-----// fd
            memset(p, -1, n << 2);-----// b7
            set<int, cmp> q;-----// d8
            q.insert(s); d[s] = 0;-----// 1d
            while (!q.empty()) {-----// 04
                int u = *q.begin();-----// dd
                q.erase(q.begin());-----// 20
                for (int i = head[u]; i != -1; i = e[i].nxt) {-----// 02
                    if (e[i].cap == 0) continue;-----// 1c
                    int cd = d[u] + e[i].cost + pot[u] - pot[v = e[i].v];-----// 1d
                    if (d[v] == -1 || cd < d[v]) {-----// d2
                        if (q.find(v) != q.end()) q.erase(q.find(v));-----// e2
                        d[v] = cd; p[v] = i;-----// f7
                        q.insert(v);-----// 74
                    }-----// 6c
                }-----// 1b
            }-----// da
            if (p[t] == -1) break;-----// 09
```


Reykjavík University9

```
-----int x = INF, at = p[t];-----// e8
-----while (at != -1) x = min(x, e[at].cap), at = p[e[at^1].v];-----// 32
-----at = p[t], f += x;-----// 43
-----while (at != -1)-----// 53
-----e[at].cap -= x, e[at^1].cap += x, at = p[e[at^1].v];-----// 95
-----c += x * (d[t] + pot[t] - pot[s]);-----// 44
-----rep(i,0,n) if (p[i] != -1) pot[i] += d[i];-----// 86
-----}-----// 4e
-----if (res) reset();-----// d7
-----return ii(f, c);-----// 9f
-----}-----// 4c
};-----// ec
```

A second implementation that is slower but works on negative weights.

```
struct flow_network {-----// 81
--struct mcmf_edge {-----// f6
--int u, v;-----// e1
--ll w, c;-----// b4
--mcmf_edge* rev;-----// 9d
--mcmf_edge(int _u, int _v, ll _w, ll _c, mcmf_edge* _rev = NULL) {-----// ea
--u = _u; v = _v; w = _w; c = _c; rev = _rev;-----// 83
--}-----// 02
--};-----// b9
--int n;-----// b4
--vector<pair<int, pair<ll, ll> > > adj;-----// 72
--flow_network(int _n) {-----// 55
--n = _n;-----// fa
--adj = new vector<pair<int, pair<ll, ll> > >[n];-----// bb
--}-----// bd
--void add_edge(int u, int v, ll cost, ll cap) {-----// 79
--adj[u].push_back(make_pair(v, make_pair(cap, cost)));-----// c8
--}-----// ed
--pair<ll,ll> min_cost_max_flow(int s, int t) {-----// ea
--vector<mcmf_edge*>* g = new vector<mcmf_edge*>[n];-----// ce
--for (int i = 0; i < n; i++) {-----// 57
--for (int j = 0; j < size(adj[i]); j++) {-----// 37
--mcmf_edge *cur = new mcmf_edge(i, adj[i][j].first,-----// 21
--adj[i][j].second.first, adj[i][j].second.second),-----// 56
--*rev = new mcmf_edge(adj[i][j].first, i, 0,-----// 48
--adj[i][j].second.second, cur);-----// b1
--cur->rev = rev;-----// ef
--g[i].push_back(cur);-----// 1d
--g[adj[i][j].first].push_back(rev);-----// 05
--}-----// ba
--}-----// 83
--ll flow = 0, cost = 0;-----// 68
--mcmf_edge** back = new mcmf_edge*[n];-----// e5
--ll* dist = new ll[n];-----// 50
--while (true) {-----// 65
--for (int i = 0; i < n; i++) back[i] = NULL, dist[i] = INF;-----// d0
--dist[s] = 0;-----// 5e
--for (int i = 0; i < n - 1; i++)-----// be
```

```
-----for (int j = 0; j < n; j++)-----// 6e
-----if (dist[j] != INF)-----// e3
-----for (int k = 0; k < size(g[j]); k++)-----// 85
-----if (g[j][k]->w > 0 && dist[j] + g[j][k]->c <-----// 7f
-----dist[g[j][k]->v]) {-----// 6d
-----dist[g[j][k]->v] = dist[j] + g[j][k]->c;-----// cf
-----back[g[j][k]->v] = g[j][k];-----// 3d
-----}-----// f3
-----mcmf_edge* cure = back[t];-----// b4
-----if (cure == NULL) break;-----// ab
-----ll cap = INF;-----// 7a
-----while (true) {-----// ad
-----cap = min(cap, cure->w);-----// c3
-----if (cure->u == s) break;-----// 82
-----cure = back[cure->u];-----// 45
-----}-----// 91
-----assert(cap > 0 && cap < INF);-----// ae
-----cure = back[t];-----// b9
-----while (true) {-----// 2a
-----cost += cap * cure->c;-----// f8
-----cure->w -= cap;-----// d1
-----cure->rev->w += cap;-----// cf
-----if (cure->u == s) break;-----// 8c
-----cure = back[cure->u];-----// 60
-----}-----// 09
-----flow += cap;-----// f2
-----}-----// be
-----// instead of deleting g, we could also-----// e0
-----// use it to get info about the actual flow-----// 6c
-----for (int i = 0; i < n; i++)-----// eb
-----for (int j = 0; j < size(g[i]); j++)-----// 82
-----delete g[i][j];-----// 06
-----delete[] g;-----// 23
-----delete[] back;-----// 5a
-----delete[] dist;-----// b9
-----return make_pair(flow, cost);-----// ec
-----}-----// ad
};-----// bf
```

3.8. All Pairs Maximum Flow.

3.8.1. *Gomory-Hu Tree.* An implementation of the Gomory-Hu Tree. The spanning tree is constructed using Gusfield's algorithm in $O(|V|^2)$ plus $|V| - 1$ times the time it takes to calculate the maximum flow. If Dinic's algorithm is used to calculate the max flow, the running time is $O(|V|^3|E|)$. NOTE: Not sure if it works correctly with disconnected graphs.

```
#include "dinic.cpp"-----// 58
-----// 25
bool same[MAXV];-----// 59
pair<vii, vvi> construct_gh_tree(flow_network &g) {-----// 77
--int n = g.n, v;-----// 5d
--vii par(n, ii(0, 0)); vvi cap(n, vi(n, -1));-----// 49
--rep(s,1,n) {-----// 9e
```

```
-----int l = 0, r = 0;-----// 08
-----par[s].second = g.max_flow(s, par[s].first, false);-----// 54
-----memset(d, 0, n * sizeof(int));-----// c8
-----memset(same, 0, n * sizeof(bool));-----// c9
-----d[q[r++] = s] = 1;-----// dd
-----while (l < r) {-----// 45
-----    same[v = q[l++]] = true;-----// c5
-----    for (int i = g.head[v]; i != -1; i = g.e[i].nxt)-----// 66
-----        if (g.e[i].cap > 0 && d[g.e[i].v] == 0)-----// 21
-----            d[q[r++] = g.e[i].v] = 1;-----// dd
-----    }-----// 44
-----    rep(i,s+1,n)-----// 71
-----    if (par[i].first == par[s].first && same[i]) par[i].first = s;-----// 97
-----    g.reset();-----// d8
-----}-----// 93
---rep(i,0,n) {-----// 14
---    int mn = INF, cur = i;-----// 59
---    while (true) {-----// b8
---        cap[cur][i] = mn;-----// 8d
---        if (cur == 0) break;-----// fb
---        mn = min(mn, par[cur].second), cur = par[cur].first;-----// 4d
---    }-----// aa
---}-----// 90
---return make_pair(par, cap);-----// 62
}-----// b3
int compute_max_flow(int s, int t, const pair<vii, vvi> &gh) {-----// 93
---if (s == t) return 0;-----// 33
---int cur = INF, at = s;-----// e7
---while (gh.second[at][t] == -1)-----// 42
---    cur = min(cur, gh.first[at].second), at = gh.first[at].first;-----// 8d
---return min(cur, gh.second[at][t]);-----// 54
}-----// 46
```

3.9. Heavy-Light Decomposition.

```
#include "../data-structures/segment_tree.cpp"-----// 16
struct HLD {-----// 25
---int n, curhead, curloc;-----// d9
---vi sz, head, parent, loc;-----// 81
---vvi adj; segment_tree values;-----// 13
---HLD(int _n) : n(_n), sz(n, 1), head(n), parent(n, -1), loc(n), adj(n) {-----// 1c
-----    vi tmp(n, ID); values = segment_tree(tmp); }-----// f0
---void add_edge(int u, int v) { adj[u].push_back(v), adj[v].push_back(u); }-----// 77
---void update_cost(int u, int v, int c) {-----// 7b
-----    if (parent[v] == u) swap(u, v); assert(parent[u] == v);-----// db
-----    values.update(loc[u], c); }-----// 50
---int csz(int u) {-----// 7c
-----    rep(i,0,size(adj[u])) if (adj[u][i] != parent[u])-----// a5
-----        sz[u] += csz(adj[parent[adj[u][i]] = u][i]);-----// c2
-----    return sz[u]; }-----// 75
---void part(int u) {-----// c3
-----    head[u] = curhead; loc[u] = curloc++;-----// 63
```

```
-----int best = -1;-----// 27
-----rep(i,0,size(adj[u]))-----// 49
-----    if (adj[u][i] != parent[u] && (best == -1 || sz[adj[u][i]] > sz[best]))-----// 26
-----        best = adj[u][i];-----// c4
-----    if (best != -1) part(best);-----// 92
-----    rep(i,0,size(adj[u]))-----// e8
-----        if (adj[u][i] != parent[u] && adj[u][i] != best)-----// 88
-----            part(curhead = adj[u][i]); }-----// 78
---void build(int r = 0) { curloc = 0, csz(curhead = r), part(r); }-----// 74
---int lca(int u, int v) {-----// 43
---    vi uat, vat; int res = -1;-----// 51
---    while (u != -1) uat.push_back(u), u = parent[head[u]];-----// 6d
---    while (v != -1) vat.push_back(v), v = parent[head[v]];-----// 8a
---    u = size(uat) - 1, v = size(vat) - 1;-----// ae
---    while (u >= 0 && v >= 0 && head[uat[u]] == head[vat[v]])-----// a2
---        res = (loc[uat[u]] < loc[vat[v]] ? uat[u] : vat[v]), u--, v--;-----// 91
---    return res; }-----// 72
---int query_upto(int u, int v) { int res = ID;-----// 69
---    while (head[u] != head[v])-----// a4
---        res = f(res, values.query(loc[head[u]], loc[u])),-----// 8c
---        u = parent[head[u]];-----// ea
---    return f(res, values.query(loc[v] + 1, loc[u])); }-----// 53
---int query(int u, int v) { int l = lca(u, v);-----// 5b
---    return f(query_upto(u, l), query_upto(v, l)); } }-----
```

3.10. Centroid Decomposition.

```
#define MAXV 100100-----// 86
#define LGMAXV 20-----// aa
int jmp[MAXV][LGMAXV],-----// 6d
path[MAXV][LGMAXV],-----// 9d
sz[MAXV], seph[MAXV],-----// cf
shortest[MAXV];-----// 6b
struct centroid_decomposition {-----// 99
---int n; vvi adj;-----// e9
---centroid_decomposition(int _n) : n(_n), adj(n) { }-----// 46
---void add_edge(int a, int b) { adj[a].push_back(b), adj[b].push_back(a); }-----// bc
---int dfs(int u, int p) {-----// 8f
---    sz[u] = 1;-----// c8
---    rep(i,0,size(adj[u])) if (adj[u][i] != p) sz[u] += dfs(adj[u][i], u);-----// 78
---    return sz[u]; }-----// f4
---void makepaths(int sep, int u, int p, int len) {-----// 84
---    jmp[u][seph[sep]] = sep, path[u][seph[sep]] = len;-----// d9
---    int bad = -1;-----// af
---    rep(i,0,size(adj[u])) {-----// f4
---        if (adj[u][i] == p) bad = i;-----// cf
---        else makepaths(sep, adj[u][i], u, len + 1);-----// f2
---    }-----// 8a
---    if (p == sep) swap(adj[u][bad], adj[u].back()), adj[u].pop_back(); }-----// 07
---void separate(int h=0, int u=0) {-----// 03
---    dfs(u,-1); int sep = u;-----// b5
---    down: iter(nxt,adj[sep])-----// 04
```



```
-----return i - m;-----// e9
-----// or j = pit[j];-----// ce
-----}-----// 85
-----}-----// 35
-----else if (j > 0) j = pit[j];-----// 43
-----else i++; }-----// b8
----delete[] pit; return -1; }-----// e3
```

4.2. The Z algorithm.

```
int* z_values(const string &s) {-----// 4d
----int n = size(s);-----// 97
----int* z = new int[n];-----// c4
----int l = 0, r = 0;-----// 1c
----z[0] = n;-----// 98
----rep(i,1,n) {-----// b2
----z[i] = 0;-----// 4c
----if (i > r) {-----// 6d
----l = r = i;-----// 24
----while (r < n && s[r - l] == s[r]) r++;-----// 68
----z[i] = r - l; r--;-----// 07
----} else if (z[i - l] < r - i + 1) z[i] = z[i - l];-----// 6f
----else {-----// a8
----l = i;-----// 55
----while (r < n && s[r - l] == s[r]) r++;-----// 2c
----z[i] = r - l; r--; } }-----// 13
----return z;-----// 78
}-----// 16
```

4.3. Suffix Array. An $O(n \log^2 n)$ construction of a Suffix Tree.

```
struct entry { ii nr; int p; };-----// f9
bool operator <(const entry &a, const entry &b) { return a.nr < b.nr; }-----// 77
struct suffix_array {-----// 87
----string s; int n; vvi P; vector<entry> L; vi idx;-----// b6
----suffix_array(string _s) : s(_s), n(size(s)) {-----// a3
----L = vector<entry>(n), P.push_back(vi(n)), idx = vi(n);-----// 12
----rep(i,0,n) P[0][i] = s[i];-----// 5c
----for (int stp = 1, cnt = 1; cnt >> 1 < n; stp++, cnt <= 1) {-----// 86
----P.push_back(vi(n));-----// 53
----rep(i,0,n)-----// 6f
----L[L[i].p = i].nr = ii(P[stp - 1][i],-----// e2
----i + cnt < n ? P[stp - 1][i + cnt] : -1);-----// 43
----sort(L.begin(), L.end());-----// 5f
----rep(i,0,n)-----// a8
----P[stp][L[i].p] = i > 0 &&-----// 3a
----L[i].nr == L[i - 1].nr ? P[stp][L[i - 1].p] : i;-----// 55
----}-----// 8b
----rep(i,0,n) idx[P[size(P) - 1][i]] = i;-----// 17
----}-----// d9
----int lcp(int x, int y) {-----// 71
----int res = 0;-----// d6
----if (x == y) return n - x;-----// bc
----for (int k = size(P) - 1; k >= 0 && x < n && y < n; k--)-----// fe
```

```
-----if (P[k][x] == P[k][y]) x += 1 << k, y += 1 << k, res += 1 << k;-----// b7
-----return res;-----// bc
-----}-----// f1
};-----// f6
```

4.4. Aho-Corasick Algorithm.

```
struct aho_corasick {-----// 78
----struct out_node {-----// 3e
----string keyword; out_node *next;-----// f0
----out_node(string k, out_node *n) : keyword(k), next(n) { }-----// 26
----};-----// b9
----struct go_node {-----// 40
----map<char, go_node*> next;-----// 6b
----out_node *out; go_node *fail;-----// 3e
----go_node() { out = NULL; fail = NULL; }-----// 0f
----};-----// c0
----go_node *go;-----// b8
----aho_corasick(vector<string> keywords) {-----// 4b
----go = new go_node();-----// 77
----iter(k, keywords) {-----// f2
----go_node *cur = go;-----// a2
----iter(c, *k)-----// 6e
----cur = cur->next.find(*c) != cur->next.end() ? cur->next[*c] :-----// 97
----(cur->next[*c] = new go_node());-----// af
----cur->out = new out_node(*k, cur->out);-----// 3f
----}-----// eb
----queue<go_node*> q;-----// 2c
----iter(a, go->next) q.push(a->second);-----// db
----while (!q.empty()) {-----// 07
----go_node *r = q.front(); q.pop();-----// e0
----iter(a, r->next) {-----// 18
----go_node *s = a->second;-----// 55
----q.push(s);-----// b5
----go_node *st = r->fail;-----// 53
----while (st && st->next.find(a->first) == st->next.end())-----// 0e
----st = st->fail;-----// b3
----if (!st) st = go;-----// 0b
----s->fail = st->next[a->first];-----// c1
----if (s->fail) {-----// 98
----if (!s->out) s->out = s->fail->out;-----// ad
----else {-----// 5b
----out_node* out = s->out;-----// b8
----while (out->next) out = out->next;-----// b4
----out->next = s->fail->out;-----// 62
----}-----// a6
----}-----// 81
----}-----// 55
----}-----// bf
----}-----// de
----vector<string> search(string s) {-----// c4
----vector<string> res;-----// 79
```

```
-----go_node *cur = go;-----// 85
-----iter(c, s) {-----// 57
-----while (cur && cur->next.find(*c) == cur->next.end())-----// df
-----cur = cur->fail;-----// b1
-----if (!cur) cur = go;-----// 92
-----cur = cur->next[*c];-----// 97
-----if (!cur) cur = go;-----// 01
-----for (out_node *out = cur->out; out; out = out->next)-----// d7
-----res.push_back(out->keyword);-----// 7c
-----}-----// 56
-----return res;-----// 6b
-----}-----// 3e
};-----// de
```

4.5. eerTree.

```
#define MAXN 100100-----// 29
#define SIGMA 26-----// e2
#define BASE 'a'-----// a1
char *s = new char[MAXN];-----// db
struct state {-----// 33
----int len, link, to[SIGMA];-----// 24
} *st = new state[MAXN+2];-----// 57
struct eertree {-----// 78
----int last, sz, n;-----// ba
----eertree() : last(1), sz(2), n(0) {-----// 83
-----st[0].len = st[0].link = -1;-----// 3f
-----st[1].len = st[1].link = 0; }-----// 34
----int extend() {-----// c2
----char c = s[n++]; int p = last;-----// 25
----while (n - st[p].len - 2 < 0 || c != s[n - st[p].len - 2]) p = st[p].link;
----if (!st[p].to[c-BASE]) {-----// 82
----int q = last = sz++;-----// 42
----st[p].to[c-BASE] = q;-----// fc
----st[q].len = st[p].len + 2;-----// c5
----do { p = st[p].link;-----// 04
----} while (p != -1 && (n < st[p].len + 2 || c != s[n - st[p].len - 2]));
----if (p == -1) st[q].link = 1;-----// 77
----else st[q].link = st[p].to[c-BASE];-----// 6a
----return 1; }-----// 29
----last = st[p].to[c-BASE];-----// 42
----return 0; } }-----// ec
```

4.6. **Suffix Automaton.** Minimum automata that accepts all suffixes of a string with $O(n)$ construction. The automata itself is a DAG therefore suitable for DP, examples are counting unique substrings, occurrences of substrings and suffix.

```
// TODO: Add longest common subsring-----// 0e
const int MAXL = 100000;-----// 31
struct suffix_automaton {-----// e0
----vi len, link, occur, cnt;-----// 78
----vector<map<char,int> > next;-----// 90
----vector<bool> isclone;-----// 7b
----ll *occuratleast;-----// f2
```

```
----int sz, last;-----// 7d
----string s;-----// f2
----suffix_automaton() : len(MAXL*2), link(MAXL*2), occur(MAXL*2), next(MAXL*2),
----isclone(MAXL*2) { clear(); }-----// a3
----void clear(){ sz = 1; last = len[0] = 0; link[0] = -1; next[0].clear();-----// aa
----isclone[0] = false; }-----// 26
----bool issubstr(string other){-----// 3b
----for(int i = 0, cur = 0; i < size(other); ++i){-----// 7f
----if(cur == -1) return false; cur = next[cur][other[i]]; }-----// 54
----return true; }-----// 1a
----void extend(char c){ int cur = sz++; len[cur] = len[last] + 1;-----// 1d
----next[cur].clear(); isclone[cur] = false; int p = last;-----// a9
----for(; p != -1 && !next[p].count(c); p = link[p]){ next[p][c] = cur; }-----// 6f
----if(p == -1){ link[cur] = 0; }-----// 18
----else{ int q = next[p][c];-----// 34
----if(len[p] + 1 == len[q]){ link[cur] = q; }-----// 4d
----else { int clone = sz++; isclone[clone] = true;-----// 57
----len[clone] = len[p] + 1;-----// 8c
----link[clone] = link[q]; next[clone] = next[q];-----// 76
----for(; p != -1 && next[p].count(c) && next[p][c] == q; p = link[p]){
----next[p][c] = clone; }-----// 32
----link[q] = link[cur] = clone;-----// 73
----} } last = cur; }-----// b9
----void count(){-----// e7
----cnt=vi(sz, -1); stack<ii> S; S.push(ii(0,0));map<char,int>::iterator i;-----// 56
----while(!S.empty()){-----// 4c
----ii cur = S.top(); S.pop();-----// 67
----if(cur.second){-----// 78
----for(i = next[cur.first].begin();i != next[cur.first].end();++i){
----cnt[cur.first] += cnt[(*i).second]; } }-----// da
----else if(cnt[cur.first] == -1){-----// 99
----cnt[cur.first] = 1; S.push(ii(cur.first, 1));-----// bd
----for(i = next[cur.first].begin();i != next[cur.first].end();++i){
----S.push(ii((*i).second, 0)); } } } }-----// 61
----string lexicok(ll k){-----// 8b
----int st = 0; string res; map<char,int>::iterator i;-----// cf
----while(k){ for(i = next[st].begin(); i != next[st].end(); ++i){-----// 69
----if(k <= cnt[(*i).second]){ st = (*i).second;-----// ec
----res.push_back((*i).first); k--; break;-----// 63
----} else { k -= cnt[(*i).second]; } } }-----// ee
----return res; }-----// 0b
----void countoccur(){-----// ad
----for(int i = 0; i < sz; ++i){ occur[i] = 1 - isclone[i]; }-----// 1b
----vii states(sz);-----// dc
----for(int i = 0; i < sz; ++i){ states[i] = ii(len[i],i); }-----// 97
----sort(states.begin(), states.end());-----// 8d
----for(int i = size(states)-1; i >= 0; --i){ int v = states[i].second;-----// a4
----if(link[v] != -1) { occur[link[v]] += occur[v]; } } }-----// cc
};-----// 32
-----// 56
```

4.7. **Hashing.** Modulus should be a large prime. Can also use multiple instances with different moduli to minimize chance of collision.

```
struct hasher { int b = 311, m; vi h, p;-----// 61
---hasher(string s, int _m) : m(_m), h(size(s)+1), p(size(s)+1) {-----// f6
-----p[0] = 1; h[0] = 0;-----// d3
-----rep(i,0,size(s)) p[i+1] = (ll)p[i] * b % m;-----// 8a
-----rep(i,0,size(s)) h[i+1] = ((ll)h[i] * b + s[i]) % m; }-----// 10
---int hash(int l, int r) {-----// b2
-----return (h[r+1] + m - (ll)h[l] * p[r-l+1] % m) % m; } };------// 26
```

5. MATHEMATICS

5.1. **Binomial Coefficients.** The binomial coefficient $\binom{n}{k} = \frac{n!}{k!(n-k)!}$ is the number of ways to choose k items out of a total of n items. Also contains an implementation of Lucas' theorem for computing the answer modulo a prime p .

```
int nck(int n, int k) {-----// f6
---if (n < k) return 0;-----// 55
---k = min(k, n - k);-----// bd
---int res = 1;-----// e6
---rep(i,1,k+1) res = res * (n - (k - i)) / i;-----// 4d
---return res;-----// 1f
}-----// 6c
int nck(int n, int k, int p) {-----// cf
---int res = 1;-----// 5c
---while (n || k) {-----// e2
-----res *= nck(n % p, k % p);-----// cc
-----res %= p, n /= p, k /= p;-----// 0a
---}-----// d9
---return res;-----// 30
}-----// 0a
```

5.2. Euclidean algorithm.

```
int gcd(int a, int b) { return b == 0 ? a : gcd(b, a % b); }-----// d9
```

The extended Euclidean algorithm computes the greatest common divisor d of two integers a, b and also finds two integers x, y such that $a \times x + b \times y = d$.

```
int egcd(int a, int b, int& x, int& y) {-----// 85
---if (b == 0) { x = 1; y = 0; return a; }-----// 7b
---else {-----// 00
-----int d = egcd(b, a % b, x, y);-----// 34
-----x -= a / b * y;-----// 4a
-----swap(x, y);-----// 26
-----return d;-----// db
---}-----// 9e
}-----// 40
```

5.3. Trial Division Primality Testing.

```
bool is_prime(int n) {-----// 6c
---if (n < 2) return false;-----// c9
---if (n < 4) return true;-----// d9
---if (n % 2 == 0 || n % 3 == 0) return false;-----// 0f
---if (n < 25) return true;-----// ef
---int s = static_cast<int>(sqrt(static_cast<double>(n)));-----// 64
```

```
---for (int i = 5; i <= s; i += 6)-----// 6c
-----if (n % i == 0 || n % (i + 2) == 0) return false;-----// e9
---return true; }-----// 43
```

5.4. Miller-Rabin Primality Test.

```
#include "mod_pow.cpp"-----// c7
bool is_probable_prime(ll n, int k) {-----// be
---if (~n & 1) return n == 2;-----// d1
---if (n <= 3) return n == 3;-----// 39
---int s = 0; ll d = n - 1;-----// 37
---while (~d & 1) d >>= 1, s++;-----// 35
---while (k--) {-----// c8
-----ll a = (n - 3) * rand() / RAND_MAX + 2;-----// 06
-----ll x = mod_pow(a, d, n);-----// 64
-----if (x == 1 || x == n - 1) continue;-----// 9b
-----bool ok = false;-----// 03
-----rep(i,0,s-1) {-----// 13
-----x = (x * x) % n;-----// 90
-----if (x == 1) return false;-----// 5c
-----if (x == n - 1) { ok = true; break; }-----// a1
-----}-----// 3a
-----if (!ok) return false;-----// 37
---} return true; }-----// fe
```

5.5. Pollard's ρ algorithm.

```
// public static int[] seeds = new int[] {2,3,5,7,11,13,1031};-----// 1d
// public static BigInteger rho(BigInteger n, BigInteger seed) {-----// 03
//---- int i = 0,-----// 00
//---- k = 2;-----// 79
//---- BigInteger x = seed,-----// cc
//---- y = seed;-----// 31
//---- while (i < 1000000) {-----// 10
//---- i++;-----// 8c
//---- x = (x.multiply(x).add(n).subtract(BigInteger.ONE)).mod(n);-----// 74
//---- BigInteger d = y.subtract(x).abs().gcd(n);-----// ce
//---- if (!d.equals(BigInteger.ONE) && !d.equals(n)) {-----// b9
//---- return d;-----// 3b
//---- }-----// 7c
//---- if (i == k) {-----// 2c
//---- y = x;-----// 89
//---- k = k*2;-----// 1d
//---- }-----// 10
//---- }-----// 96
//---- return BigInteger.ONE;-----// 62
// }-----// d7
```

5.6. Sieve of Eratosthenes.

```
vi prime_sieve(int n) {-----// 40
---int mx = (n - 3) >> 1, sq, v, i = -1;-----// 27
---vi primes;-----// 8f
---bool* prime = new bool[mx + 1];-----// ef
---memset(prime, 1, mx + 1);-----// 28
```



```
---if (n >= 2) primes.push_back(2);-----// f4
---while (++i <= mx) if (prime[i]) {------// 73
-----primes.push_back(v = (i << 1) + 3);-----// be
-----if ((sq = i * ((i << 1) + 6) + 3) > mx) break;-----// 2d
-----for (int j = sq; j <= mx; j += v) prime[j] = false; }-----// 2e
---while (++i <= mx) if (prime[i]) primes.push_back((i << 1) + 3);-----// 29
---delete[] prime; // can be used for O(1) lookup-----// 36
---return primes; }-----// 72
```

5.7. Divisor Sieve.

```
vi divisor_sieve(int n) {-----// 7f
---vi minimalDiv(n+1, 2), primes;-----// 37
---if(n>=2) primes.push_back(2);-----// 27
---minimalDiv[0] = 0;-----// 02
---for(int k=1;k<=n;k+=2) minimalDiv[k] = k;-----// e6
---for(int k=3;k<=n;k+=2) {------// 5d
-----if(minimalDiv[k] == k) primes.push_back(k);-----// 75
-----rep(i, 1, size(primes))-----// 49
-----if(primes[i] > minimalDiv[k] || primes[i]*k > n) break;-----// 53
-----else minimalDiv[primes[i]*k] = primes[i];-----// 90
---}-----// 9d
---return primes; }-----// 93
-----// a8
```

5.8. Modular Multiplicative Inverse.

```
#include "egcd.cpp"-----// 55
-----// e8
int mod_inv(int a, int m) {------// 49
---int x, y, d = egcd(a, m, x, y);-----// 3e
---if (d != 1) return -1;-----// 20
---return x < 0 ? x + m : x;-----// 3c
}-----// 69
```

5.9. Primitive Root.

```
#include "mod_pow.cpp"-----// c7
ll primitive_root(ll m) {------// 8a
---vector<ll> div;-----// f2
---for (ll i = 1; i*i <= m-1; i++) {------// ca
-----if ((m-1) % i == 0) {------// 85
-----if (i < m) div.push_back(i);-----// fd
-----if (m/i < m) div.push_back(m/i); }-----// f2
---rep(x,2,m) {------// 57
---bool ok = true;-----// 17
-----iter(it,div) if (mod_pow(x, *it, m) == 1) { ok = false; break; }-----// a4
---if (ok) return x; }-----// 55
---return -1; }-----// 15
```

5.10. Chinese Remainder Theorem.

```
#include "egcd.cpp"-----// 55
int crt(const vi& as, const vi& ns) {------// c3
---int cnt = size(as), N = 1, x = 0, r, s, l;-----// 55
---rep(i,0,cnt) N *= ns[i];-----// b1
```

```
---rep(i,0,cnt) egcd(ns[i], l = N/ns[i], r, s), x += as[i] * s * l;-----// 21
---return mod(x, N); }-----// b2
```

5.11. Linear Congruence Solver. A function that returns all solutions to $ax \equiv b \pmod n$, modulo n .

```
#include "egcd.cpp"-----// 55
vi linear_congruence(int a, int b, int n) {------// c8
---int x, y, d = egcd(a, n, x, y);-----// 7a
---vi res;-----// f5
---if (b % d != 0) return res;-----// 30
---int x0 = mod(b / d * x, n);-----// 48
---rep(k,0,d) res.push_back(mod(x0 + k * n / d, n));-----// 7e
---return res;-----// fe
}-----// c0
```

5.12. Numeric Integration.

```
double integrate(double (*f)(double), double a, double b,-----// 76
-----double delta = 1e-6) {------// c0
---if (abs(a - b) < delta)-----// 38
---return (b-a)/8 *-----// 56
----- (f(a) +3*f((2*a+b)/3) + 3*f((a+2*b)/3) + f(b));-----// e1
---return integrate(f, a,-----// 64
----- (a+b)/2, delta) + integrate(f, (a+b)/2, b, delta);-----// 0c
}-----// 4b
```

5.13. Fast Fourier Transform. The Cooley-Tukey algorithm for quickly computing the discrete Fourier transform. The fft function only supports powers of twos. The czt function implements the Chirp Z-transform and supports any size, but is slightly slower.

```
#include <complex>-----// 8e
typedef complex<long double> cpx;-----// 25
// NOTE: n must be a power of two-----// 14
void fft(cpx *x, int n, bool inv=false) {------// 36
---for (int i = 0, j = 0; i < n; i++) {------// f9
-----if (i < j) swap(x[i], x[j]);-----// 44
-----int m = n>>1;-----// 9c
-----while (1 <= m && m <= j) j -= m, m >>= 1;-----// fe
-----j += m;-----// 11
-----}-----// d0
---for (int mx = 1; mx < n; mx <= 1) {------// 15
---cpx wp = exp(cpx(0, (inv ? -1 : 1) * pi / mx)), w = 1;-----// 79
---for (int m = 0; m < mx; m++, w *= wp) {------// dc
---for (int i = m; i < n; i += mx << 1) {------// 6a
---cpx t = x[i + mx] * w;-----// 12
---x[i + mx] = x[i] - t;-----// 73
---x[i] += t;-----// 0e
---}-----// 14
---}-----// a4
---}-----// bf
---if (inv) rep(i,0,n) x[i] /= cpx(n);-----// 16
}-----// 1c
void czt(cpx *x, int n, bool inv=false) {------// c5
---int len = 2*n+1;-----// bc
```

```
---while (len & (len - 1)) len &= len - 1;-----// 65
---len <= 1;-----// 21
---cpx w = exp(-2.0L * pi / n * cpx(0,1)),-----// 45
-----*c = new cpx[n], *a = new cpx[len],-----// 4e
-----*b = new cpx[len];-----// 30
---rep(i,0,n) c[i] = pow(w, (inv ? -1.0 : 1.0)*i/2);-----// 9e
---rep(i,0,n) a[i] = x[i] * c[i], b[i] = 1.0L/c[i];-----// e9
---rep(i,0,n-1) b[len - n + i + 1] = 1.0L/c[n-i-1];-----// 9f
---fft(a, len); fft(b, len);-----// 63
---rep(i,0,len) a[i] *= b[i];-----// 58
---fft(a, len, true);-----// 2d
---rep(i,0,n) {-----// ff
-----x[i] = c[i] * a[i];-----// 77
-----if (inv) x[i] /= cpx(n);-----// b1
-----}-----// 27
---delete[] a;-----// 0a
---delete[] b;-----// 5c
---delete[] c;-----// f8
}-----// c6
```

5.14. Number-Theoretic Transform.

```
#include "../mathematics/primitive_root.cpp"-----// 8c
int mod = 998244353, g = primitive_root(mod),-----// 9c
---ginv = mod_pow(g, mod-2, mod), inv2 = mod_pow(2, mod-2, mod);-----// 75
#define MAXN (1<<22)-----// 94
struct Num {-----// c5
---int x;-----// 02
---Num(ll _x=0) { x = (_x%mod+mod)%mod; }-----// 1b
---Num operator +(const Num &b) { return x + b.x; }-----// 08
---Num operator -(const Num &b) const { return x - b.x; }-----// 89
---Num operator *(const Num &b) const { return (ll)x * b.x; }-----// e3
---Num operator /(const Num &b) const { return (ll)x * b.inv().x; }-----// 2a
---Num inv() const { return mod_pow((ll)x, mod-2, mod); }-----// d3
---Num pow(int p) const { return mod_pow((ll)x, p, mod); }-----// d5
} T1[MAXN], T2[MAXN];-----// d5
void ntt(Num x[], int n, bool inv = false) {-----// 24
---Num z = inv ? ginv : g;-----// 00
---z = z.pow((mod - 1) / n);-----// 45
---for (ll i = 0, j = 0; i < n; i++) {-----// fe
-----if (i < j) swap(x[i], x[j]);-----// eb
-----ll k = n>>1;-----// 02
-----while (1 <= k && k <= j) j -= k, k >>= 1;-----// d2
-----j += k; }-----// c4
---for (int mx = 1, p = n/2; mx < n; mx <= 1, p >>= 1) {-----// a2
-----Num wp = z.pow(p), w = 1;-----// 35
-----for (int k = 0; k < mx; k++, w = w*wp) {-----// 42
-----for (int i = k; i < n; i += mx << 1) {-----// 9a
-----Num t = x[i + mx] * w;-----// 22
-----x[i + mx] = x[i] - t;-----// d0
-----x[i] = x[i] + t; } } }-----// 1e
---if (inv) {-----// 6c
```

```
-----Num ni = Num(n).inv();-----// 18
-----rep(i,0,n) { x[i] = x[i] * ni; } } }-----// 72
void inv(Num x[], Num y[], int l) {-----// ee
---if (l == 1) { y[0] = x[0].inv(); return; }-----// 71
---inv(x, y, l>>1);-----// bd
---// NOTE: maybe l<<2 instead of l<<1-----// 24
---rep(i,l>>1,l<<1) T1[i] = y[i] = 0;-----// dd
---rep(i,0,l) T1[i] = x[i];-----// f7
---ntt(T1, l<<1); ntt(y, l<<1);-----// a5
---rep(i,0,l<<1) y[i] = y[i]*2 - T1[i] * y[i] * y[i];-----// bc
---ntt(y, l<<1, true); }-----// 40
void sqrt(Num x[], Num y[], int l) {-----// 44
---if (l == 1) { assert(x[0].x == 1); y[0] = 1; return; }-----// 64
---sqrt(x, y, l>>1);-----// a7
---inv(y, T2, l>>1);-----// 3b
---rep(i,l>>1,l<<1) T1[i] = T2[i] = 0;-----// 1c
---rep(i,0,l) T1[i] = x[i];-----// 08
---ntt(T2, l<<1); ntt(T1, l<<1);-----// 7e
---rep(i,0,l<<1) T2[i] = T1[i] * T2[i];-----// 9f
---ntt(T2, l<<1, true);-----// eb
---rep(i,0,l) y[i] = (y[i] + T2[i]) * inv2; }-----// b8
```

5.15. **Tridiagonal Matrix Algorithm.** Solves a tridiagonal system of linear equations $a_i x_{i-1} + b_i x_i + c_i x_{i+1} = d_i$ where $a_1 = c_n = 0$. Beware of numerical instability.

```
#define MAXN 5000-----// f7
long double A[MAXN], B[MAXN], C[MAXN], D[MAXN], X[MAXN];-----// d8
void solve(int n) {-----// 01
---C[0] /= B[0]; D[0] /= B[0];-----// 94
---rep(i,1,n-1) C[i] /= B[i] - A[i]*C[i-1];-----// 6b
---rep(i,1,n) D[i] = (D[i] - A[i] * D[i-1]) / (B[i] - A[i] * C[i-1]);-----// 33
---X[n-1] = D[n-1];-----// c7
---for (int i = n-2; i>=0; i--) X[i] = D[i] - C[i] * X[i+1]; }-----// ad
```

5.16. **Mertens Function.** Mertens function is $M(n) = \sum_{i=1}^n \mu(i)$. Let $L \approx (n \log \log n)^{2/3}$ and the algorithm runs in $O(n^{2/3})$. Can also be easily changed to compute the summatory Φ .

```
#define L 9000000-----// 27
int mob[L], mer[L];-----// f1
unordered_map<ll,ll> mem;-----// 30
ll M(ll n) {-----// de
---if (n < L) return mer[n];-----// 1c
---if (mem.find(n) != mem.end()) return mem[n];-----// 79
---ll ans = 0, done = 1;-----// 48
---for (ll i = 2; i*i <= n; i++) ans += M(n/i), done = i;-----// 41
---for (ll i = 1; i*i <= n; i++) ans += mer[i] * (n/i - max(done, n/(i+1)));-----// 43
---return mem[n] = 1 - ans; }-----// c2
void sieve() {-----// b9
---for (int i = 1; i < L; i++) mer[i] = mob[i] = 1;-----// f7
---for (int i = 2; i < L; i++) {-----// 8e
---if (mer[i]) {-----// 8b
---mob[i] = -1;-----// e5
---for (int j = i+i; j < L; j += i)-----// f0
---mer[j] = 0, mob[j] = (j/i)%i == 0 ? 0 : -mob[j/i];-----// 26
```

```
-----}-----// aa
-----mer[i] = mob[i] + mer[i-1]; } }-----// 3b
```

5.17. **Numbers and Sequences.** Some random prime numbers: 1031, 32771, 1048583, 33554467, 1073741827, 34359738421, 1099511627791, 35184372088891, 1125899906842679, 36028797018963971.

6. GEOMETRY

6.1. Primitives.

```
#define P(p) const point &p-----// 2e
#define L(p0, p1) P(p0), P(p1)-----// cf
#define C(p0, r) P(p0), double r-----// f1
#define PP(pp) pair<point,point> &pp-----// e5
typedef complex<double> point;-----// 6a
double dot(P(a), P(b)) { return real(conj(a) * b); }-----// d2
double cross(P(a), P(b)) { return imag(conj(a) * b); }-----// 8a
point rotate(P(p), double radians = pi / 2, P(about) = point(0,0)) {-----// 23
----return (p - about) * exp(point(0, radians)) + about; }-----// 25
point reflect(P(p), L(about1, about2)) {-----// 50
----point z = p - about1, w = about2 - about1;-----// 8b
----return conj(z / w) * w + about1; }-----// 83
point proj(P(u), P(v)) { return dot(u, v) / dot(u, u) * u; }-----// e7
point normalize(P(p), double k = 1.0) {-----// 5f
----return abs(p) == 0 ? point(0,0) : p / abs(p) * k; }-----// 4a
double ccw(P(a), P(b), P(c)) { return cross(b - a, c - b); }-----// 27
bool collinear(P(a), P(b), P(c)) { return abs(ccw(a, b, c)) < EPS; }-----// b3
double angle(P(a), P(b), P(c)) {-----// 61
----return acos(dot(b - a, c - b) / abs(b - a) / abs(c - b)); }-----// c7
double signed_angle(P(a), P(b), P(c)) {-----// 4a
----return asin(cross(b - a, c - b) / abs(b - a) / abs(c - b)); }-----// 40
double angle(P(p)) { return atan2(imag(p), real(p)); }-----// e6
point perp(P(p)) { return point(-imag(p), real(p)); }-----// d9
double progress(P(p), L(a, b)) {-----// b3
----if (abs(real(a) - real(b)) < EPS)-----// 5e
-----return (imag(p) - imag(a)) / (imag(b) - imag(a));-----// 5e
----else return (real(p) - real(a)) / (real(b) - real(a)); }-----// 31
-----// 53
-----// 46
```

6.2. Lines.

```
#include "primitives.cpp"-----// e0
-----// 85
bool collinear(L(a, b), L(p, q)) {-----// 2f
----return abs(ccw(a, b, p)) < EPS && abs(ccw(a, b, q)) < EPS; }-----// 3e
bool parallel(L(a, b), L(p, q)) { return abs(cross(b - a, q - p)) < EPS; }-----// 8d
point closest_point(L(a, b), P(c), bool segment = false) {-----// f2
----if (segment) {-----// f4
-----if (dot(b - a, c - b) > 0) return b;-----// 88
-----if (dot(a - b, c - a) > 0) return a;-----// 75
-----}-----// ce
----double t = dot(c - a, b - a) / norm(b - a);-----// 62
----return a + t * (b - a);-----// 6e
}-----// 8c
```

```
double line_segment_distance(L(a,b), L(c,d)) {-----// f3
----double x = INFINITY;-----// 64
----if (abs(a - b) < EPS && abs(c - d) < EPS) x = abs(a - c);-----// a5
----else if (abs(a - b) < EPS) x = abs(a - closest_point(c, d, a, true));-----// 23
----else if (abs(c - d) < EPS) x = abs(c - closest_point(a, b, c, true));-----// 53
----else if ((ccw(a, b, c) < 0) != (ccw(a, b, d) < 0) &&-----// 6d
----- (ccw(c, d, a) < 0) != (ccw(c, d, b) < 0)) x = 0;-----// bf
----else {-----// e1
-----x = min(x, abs(a - closest_point(c,d, a, true)));-----// 29
-----x = min(x, abs(b - closest_point(c,d, b, true)));-----// fe
-----x = min(x, abs(c - closest_point(a,b, c, true)));-----// 81
-----x = min(x, abs(d - closest_point(a,b, d, true)));-----// e4
----}-----// c5
----return x;-----// b7
}-----// 27
bool intersect(L(a, b), L(p, q), point &res, bool segment = false) {-----// d2
----// NOTE: check for parallel/collinear lines before calling this function---// 1b
----point r = b - a, s = q - p;-----// 34
----double c = cross(r, s), t = cross(p - a, s) / c, u = cross(p - a, r) / c;-----// 0b
----if (segment && (t < 0-EPS || t > 1+EPS || u < 0-EPS || u > 1+EPS))-----// e4
-----return false;-----// e3
----res = a + t * r;-----// 47
----return true;-----// 05
}-----// 44
-----// cc
```

6.3. Circles.

```
#include "primitives.cpp"-----// e0
int intersect(C(A, rA), C(B, rB), point & res1, point & res2) {-----// 3b
----double d = abs(B - A);-----// 5c
----if ((rA + rB) < (d - EPS) || d < abs(rA - rB) - EPS) return 0;-----// 39
----double a = (rA*rA - rB*rB + d*d) / 2 / d, h = sqrt(rA*rA - a*a);-----// 9b
----point v = normalize(B - A, a), u = normalize(rotate(B-A), h);-----// 79
----res1 = A + v + u, res2 = A + v - u;-----// 24
----if (abs(u) < EPS) return 1; return 2;-----// 82
}-----// bb
int intersect(L(A, B), C(0, r), point & res1, point & res2) {-----// 0e
----double h = abs(0 - closest_point(A, B, 0));-----// 24
----if(r < h - EPS) return 0;-----// df
----point H = proj(0 - A, B - A) + A, v = normalize((B - A), sqrt(r*r - h*h));// 19
----res1 = H + v; res2 = H - v;-----// 40
----if(abs(v) < EPS) return 1; return 2;-----// 37
}-----// 46
int tangent(P(A), C(0, r), point & res1, point & res2) {-----// aa
----point v = 0 - A; double d = abs(v);-----// 49
----if (d < r - EPS) return 0;-----// ca
----double alpha = asin(r / d), L = sqrt(d*d - r*r);-----// 3f
----v = normalize(v, L);-----// 3f
----res1 = A + rotate(v, alpha); res2 = A + rotate(v, -alpha);-----// be
----if (abs(r - d) < EPS || abs(v) < EPS) return 1;-----// bb
----return 2;-----// b9
```

```
// f4
void tangent_outer(point A, double rA, point B, double rB, PP(P), PP(Q)) {--// 83
---if (rA - rB > EPS) { swap(rA, rB); swap(A, B); }--// 82
---double theta = asin((rB - rA)/abs(A - B));--// 37
---point v = rotate(B - A, theta + pi/2), u = rotate(B - A, -(theta + pi/2));--// 00
---u = normalize(u, rA);--// 44
---P.first = A + normalize(v, rA); P.second = B + normalize(v, rB);--// d2
---Q.first = A + normalize(u, rA); Q.second = B + normalize(u, rB);--// 23
}--// b5
```

6.4. Polygon.

```
#include "primitives.cpp"--// e0
typedef vector<point> polygon;--// b3
double polygon_area_signed(polygon p) {--// 31
---double area = 0; int cnt = size(p);--// a2
---rep(i,1,cnt-1) area += cross(p[i] - p[0], p[i + 1] - p[0]);--// 51
---return area / 2; }--// 66
double polygon_area(polygon p) { return abs(polygon_area_signed(p)); }--// a4
#define CHK(f,a,b,c) (f(a) < f(b) && f(b) <= f(c) && ccw(a,c,b) < 0)--// 8f
int point_in_polygon(polygon p, point q) {--// 5d
---int n = size(p); bool in = false; double d;--// 69
---for (int i = 0, j = n - 1; i < n; j = i++)--// f3
-----if (collinear(p[i], q, p[j]) &&--// 9d
-----0 <= (d = progress(q, p[i], p[j])) && d <= 1)--// 4b
-----return 0;--// b3
---for (int i = 0, j = n - 1; i < n; j = i++)--// 67
-----if (CHK(real, p[i], q, p[j]) || CHK(real, p[j], q, p[i]))--// b4
-----in = !in;--// ff
---return in ? -1 : 1; }--// ba
// pair<polygon, polygon> cut_polygon(const polygon &poly, point a, point b) {--// 0d
//--- polygon left, right;--// 0a
//--- point it(-100, -100);--// 5b
//--- for (int i = 0, cnt = poly.size(); i < cnt; i++) {--// 70
//----- int j = i == cnt-1 ? 0 : i + 1;--// 02
//----- point p = poly[i], q = poly[j];--// 44
//----- if (ccw(a, b, p) <= 0) left.push_back(p);--// 8d
//----- if (ccw(a, b, p) >= 0) right.push_back(p);--// 43
//----- // myintersect = intersect where--// ba
//----- // (a,b) is a line, (p,q) is a line segment--// 7e
//----- if (myintersect(a, b, p, q, it))--// 6f
//----- left.push_back(it), right.push_back(it);--// 8a
//--- }--// e0
//--- return pair<polygon, polygon>(left, right);--// 3d
// }--// 07
```

6.5. Convex Hull. NOTE: Doesn't work on some weird edge cases. (A small case that included three collinear lines would return the same point on both the upper and lower hull.)

```
#include "polygon.cpp"--// 58
#define MAXN 1000--// 09
point hull[MAXN];--// 43
bool cmp(const point &a, const point &b) {--// 32
---return abs(real(a) - real(b)) > EPS ?--// 44
```

```
real(a) < real(b) : imag(a) < imag(b); }--// 40
int convex_hull(polygon p) {--// cd
---int n = size(p), l = 0;--// 67
---sort(p.begin(), p.end(), cmp);--// 3d
---rep(i,0,n) {--// e4
-----if (i > 0 && p[i] == p[i - 1]) continue;--// c7
-----while (l >= 2 && ccw(hull[l - 2], hull[l - 1], p[i]) >= 0) l--;--// 62
-----hull[l++] = p[i];--// bd
---}--// d2
---int r = l;--// 30
---for (int i = n - 2; i >= 0; i--) {--// 59
-----if (p[i] == p[i + 1]) continue;--// af
-----while (r - l >= 1 && ccw(hull[r - 2], hull[r - 1], p[i]) >= 0) r--;--// 4d
-----hull[r++] = p[i];--// f5
---}--// f6
---return l == 1 ? 1 : r - 1;--// a6
}--// 6d
```

6.6. Line Segment Intersection.

```
#include "primitives.cpp"--// e0
#include "lines.cpp"--// 54
bool line_segment_intersect(L(a, b), L(c, d), point &A, point &B) {--// 34
---if (abs(a - b) < EPS && abs(c - d) < EPS) {--// 74
---A = B = a; return abs(a - d) < EPS; }--// 37
---else if (abs(a - b) < EPS) {--// 07
---A = B = a; double p = progress(a, c,d);--// 6c
---return 0.0 <= p && p <= 1.0--// 4c
---&& (abs(a - c) + abs(d - a) - abs(d - c)) < EPS; }--// d2
---else if (abs(c - d) < EPS) {--// a0
---A = B = c; double p = progress(c, a,b);--// c0
---return 0.0 <= p && p <= 1.0--// fb
---&& (abs(c - a) + abs(b - c) - abs(b - a)) < EPS; }--// 15
---else if (collinear(a,b, c,d)) {--// 49
---double ap = progress(a, c,d), bp = progress(b, c,d);--// 34
---if (ap > bp) swap(ap, bp);--// e0
---if (bp < 0.0 || ap > 1.0) return false;--// 14
---A = c + max(ap, 0.0) * (d - c);--// 14
---B = c + min(bp, 1.0) * (d - c);--// 26
---return true; }--// bd
---else if (parallel(a,b, c,d)) return false;--// fc
---else if (intersect(a,b, c,d, A, true)) {--// 78
---B = A; return true; }--// 7d
---return false;--// 4b
}--// 05
--// 83
```

6.7. Great-Circle Distance. Computes the distance between two points (given as latitude/longitude coordinates) on a sphere of radius *r*.

```
double gc_distance(double pLat, double pLong,--// 7b
---double qLat, double qLong, double r) {--// a4
---pLat *= pi / 180; pLong *= pi / 180;--// ee
---qLat *= pi / 180; qLong *= pi / 180;--// 75
```

```
---return r * acos(cos(pLat) * cos(qLat) * cos(pLong - qLong) +-----// e3
-----sin(pLat) * sin(qLat));-----// 1e
-----// 60
}-----// 3f
```

6.8. **Triangle Circumcenter.** Returns the unique point that is the same distance from all three points. It is also the center of the unique circle that goes through all three points.

```
#include "primitives.cpp"-----// e0
point circumcenter(point a, point b, point c) {-----// 76
---b -= a, c -= a;-----// 41
---return a + perp(b * norm(c) - c * norm(b)) / 2.0 / cross(b, c);-----// 7a
}-----// c3
```

6.9. **Closest Pair of Points.**

```
#include "primitives.cpp"-----// e0
-----// 85
struct cmpx { bool operator()(const point &a, const point &b) {-----// 01
-----return abs(real(a) - real(b)) > EPS ?-----// e9
-----real(a) < real(b) : imag(a) < imag(b); } };-----// 53
struct cmpy { bool operator()(const point &a, const point &b) {-----// 6f
---return abs(imag(a) - imag(b)) > EPS ?-----// 0b
-----imag(a) < imag(b) : real(a) < real(b); } };-----// a4
double closest_pair(vector<point> pts) {-----// f1
---sort(pts.begin(), pts.end(), cmpx());-----// 0c
---set<point, cmpy> cur;-----// bd
---set<point, cmpy>::const_iterator it, jt;-----// a6
---double mn = INFINITY;-----// f9
---for (int i = 0, l = 0; i < size(pts); i++) {-----// ac
-----while (real(pts[i]) - real(pts[l]) > mn) cur.erase(pts[l++]);-----// 8b
-----it = cur.lower_bound(point(-INFINITY, imag(pts[i]) - mn));-----// fc
-----jt = cur.upper_bound(point(INFINITY, imag(pts[i]) + mn));-----// 39
-----while (it != jt) mn = min(mn, abs(*it - pts[i])), it++;-----// 09
---cur.insert(pts[i]); }-----// 82
---return mn; }-----// 4c
```

6.10. **3D Primitives.**

```
#define P(p) const point3d &p-----// a7
#define L(p0, p1) P(p0), P(p1)-----// 0f
#define PL(p0, p1, p2) P(p0), P(p1), P(p2)-----// 67
struct point3d {-----// 63
---double x, y, z;-----// e6
---point3d() : x(0), y(0), z(0) {}-----// af
---point3d(double _x, double _y, double _z) : x(_x), y(_y), z(_z) {}-----// fc
---point3d operator+(P(p)) const {-----// 17
-----return point3d(x + p.x, y + p.y, z + p.z); }-----// 8e
---point3d operator-(P(p)) const {-----// fb
-----return point3d(x - p.x, y - p.y, z - p.z); }-----// 83
---point3d operator-() const {-----// 89
-----return point3d(-x, -y, -z); }-----// d4
---point3d operator*(double k) const {-----// 4d
-----return point3d(x * k, y * k, z * k); }-----// fd
---point3d operator/(double k) const {-----// 95
```

```
-----return point3d(x / k, y / k, z / k); }-----// 58
---double operator%(P(p)) const {-----// d1
-----return x * p.x + y * p.y + z * p.z; }-----// 09
---point3d operator*(P(p)) const {-----// 4f
-----return point3d(y*p.z - z*p.y, z*p.x - x*p.z, x*p.y - y*p.x); }-----// ed
---double length() const {-----// 3e
-----return sqrt(*this % *this); }-----// 05
---double distTo(P(p)) const {-----// dd
-----return (*this - p).length(); }-----// 57
---double distTo(P(A), P(B)) const {-----// bd
-----// A and B must be two different points-----// 4e
-----return ((*this - A) * (*this - B)).length() / A.distTo(B); }-----// 6e
---point3d normalize(double k = 1) const {-----// db
-----// length() must not return 0-----// 3c
-----return (*this) * (k / length()); }-----// d4
---point3d getProjection(P(A), P(B)) const {-----// 86
---point3d v = B - A;-----// 64
-----return A + v.normalize((v % (*this - A)) / v.length()); }-----// 53
---point3d rotate(P(normal)) const {-----// 55
-----// normal must have length 1 and be orthogonal to the vector-----// eb
-----return (*this) * normal; }-----// 5c
---point3d rotate(double alpha, P(normal)) const {-----// 21
-----return (*this) * cos(alpha) + rotate(normal) * sin(alpha); }-----// 82
---point3d rotatePoint(P(0), P(axe), double alpha) const {-----// 7a
---point3d Z = axe.normalize(axe % (*this - 0));-----// ba
-----return 0 + Z + (*this - 0 - Z).rotate(alpha, 0); }-----// 38
---bool isZero() const {-----// 64
-----return abs(x) < EPS && abs(y) < EPS && abs(z) < EPS; }-----// 15
---bool isOnLine(L(A, B)) const {-----// 30
-----return ((A - *this) * (B - *this)).isZero(); }-----// 58
---bool isInSegment(L(A, B)) const {-----// f1
-----return isOnLine(A, B) && ((A - *this) % (B - *this)) < EPS; }-----// d9
---bool isInSegmentStrictly(L(A, B)) const {-----// 0e
-----return isOnLine(A, B) && ((A - *this) % (B - *this)) < -EPS; }-----// ba
---double getAngle() const {-----// 0f
-----return atan2(y, x); }-----// 40
---double getAngle(P(u)) const {-----// d5
-----return atan2((*this * u).length(), *this % u); }-----// 79
---bool isOnPlane(PL(A, B, C)) const {-----// 8e
-----return abs((A - *this) * (B - *this) % (C - *this)) < EPS; } };-----// 74
int line_line_intersect(L(A, B), L(C, D), point3d &O){-----// dc
---if (abs((B - A) * (C - A) % (D - A)) > EPS) return 0;-----// 6a
---if (((A - B) * (C - D)).length() < EPS)-----// 79
-----return A.isOnLine(C, D) ? 2 : 0;-----// 09
---point3d normal = ((A - B) * (C - B)).normalize();-----// bc
---double s1 = (C - A) * (D - A) % normal;-----// 68
---0 = A + ((B - A) / (s1 + ((D - B) * (C - B) % normal))) * s1;-----// 56
---return 1; }-----// a7
int line_plane_intersect(L(A, B), PL(C, D, E), point3d &O) {-----// 09
---double V1 = (C - A) * (D - A) % (E - A);-----// c1
---double V2 = (D - B) * (C - B) % (E - B);-----// 29
```



```
---if (abs(V1 + V2) < EPS)-----// 81 // int h = convex_hull(pts);-----// 9c
---return A.isOnPlane(C, D, E) ? 2 : 0;-----// d5 // double mx = 0;-----// f1
---O = A + ((B - A) / (V1 + V2)) * V1;-----// 38 // if (h > 1) {-----// 26
---return 1; }-----// ce //---- int a = 0,-----// e6
bool plane_plane_intersect(P(A), P(nA), P(B), P(nB), point3d &P, point3d &Q) {--// 5a //----- b = 0;-----// df
---point3d n = nA * nB;-----// 49 //---- rep(i,0,h) {-----// 1d
---if (n.isZero()) return false;-----// 03 //----- if (hull[i].first < hull[a].first)-----// ac
---point3d v = n * nA;-----// d7 //----- a = i;-----// b1
---P = A + (n * nA) * ((B - A) % nB / (v % nB));-----// 1a //----- if (hull[i].first > hull[b].first)-----// 02
---Q = P + n;-----// 9c //----- b = i;-----// 84
---return true; }-----// 1a //---- }-----// 1e
//---- caliper A(hull[a], pi/2), B(hull[b], 3*pi/2);-----// 60
//---- double done = 0;-----// 3c
//---- while (true) {-----// 31
//----- mx = max(mx, abs(point(hull[a].first,hull[a].second)-----// e3
//----- - point(hull[b].first, hull[b].second)));-----// 24
//----- double tha = A.angle_to(hull[(a+1)%h]),-----// 57
//----- thb = B.angle_to(hull[(b+1)%h]);-----// f1
//----- if (tha <= thb) {-----// 91
//----- A.rotate(tha);-----// c9
//----- B.rotate(tha);-----// f4
//----- a = (a+1) % h;-----// d4
//----- A.move_to(hull[a]);-----// b3
//----- } else {-----// 56
//----- A.rotate(thb);-----// 56
//----- B.rotate(thb);-----// 38
//----- b = (b+1) % h;-----// 96
//----- B.move_to(hull[b]);-----// 38
//----- }-----// bc
//----- done += min(tha, thb);-----// d2
//----- if (done > pi) {-----// c2
//----- break;-----// e8
//----- }-----// 37
//---- }-----// ac
// }-----// 9c
```

6.11. Polygon Centroid.

```
#include "polygon.cpp"-----// 58
point polygon_centroid(polygon p) {-----// 79
---double cx = 0.0, cy = 0.0;-----// d5
---double mnx = 0.0, mny = 0.0;-----// 22
---int n = size(p);-----// 2d
---rep(i,0,n)-----// 08
-----mnx = min(mnx, real(p[i])),-----// c6
-----mny = min(mny, imag(p[i]));-----// 84
---rep(i,0,n)-----// 3f
-----p[i] = point(real(p[i]) - mnx, imag(p[i]) - mny);-----// 49
---rep(i,0,n) {-----// 3c
-----int j = (i + 1) % n;-----// 5b
-----cx += (real(p[i]) + real(p[j])) * cross(p[i], p[j]);-----// 4f
-----cy += (imag(p[i]) + imag(p[j])) * cross(p[i], p[j]); }-----// 4a
---return point(cx, cy) / 6.0 / polygon_area_signed(p) + point(mnx, mny); }---// a1
```

6.12. Rotating Calipers.

```
#include "primitives.cpp"-----// e0
struct caliper {-----// 8e
---ii pt;-----// 05
---double angle;-----// d4
---caliper(ii _pt, double _angle) : pt(_pt), angle(_angle) { }-----// 35
---double angle_to(ii pt2) {-----// 8b
-----double x = angle - atan2(pt2.second - pt.second, pt2.first - pt.first);// 1e
-----while (x >= pi) x -= 2*pi;-----// 4a
-----while (x <= -pi) x += 2*pi;-----// a3
-----return x; }-----// 7d
---void rotate(double by) {-----// 57
-----angle -= by;-----// 5d
-----while (angle < 0) angle += 2*pi;-----// 03
---}-----// 20
---void move_to(ii pt2) { pt = pt2; }-----// 37
---double dist(const caliper &other) {-----// 68
-----point a(pt.first,pt.second),-----// d7
-----b = a + exp(point(0,angle)) * 10.0,-----// 2e
-----c(other.pt.first, other.pt.second);-----// 71
-----return abs(c - closest_point(a, b, c));-----// 58
---} }-----// 4b
-----// c5
```

6.13. Formulas. Let $a = (a_x, a_y)$ and $b = (b_x, b_y)$ be two-dimensional vectors.

- $a \cdot b = |a||b| \cos \theta$, where θ is the angle between a and b .
- $a \times b = |a||b| \sin \theta$, where θ is the signed angle between a and b .
- $a \times b$ is equal to the area of the parallelogram with two of its sides formed by a and b . Half of that is the area of the triangle formed by a and b .
- Euler’s formula: $V - E + F = 2$
- Side lengths a, b, c can form a triangle iff. $a + b > c$, $b + c > a$ and $a + c > b$.
- Sum of internal angles of a regular convex n -gon is $(n - 2)\pi$.

7. OTHER ALGORITHMS

7.1. 2SAT.

```
#include "../graph/scc.cpp"-----// c3
-----// 63
bool two_sat(int n, const vii& clauses, vi& all_truthy) {-----// f4
---all_truthy.clear();-----// 31
```



```
---vvi adj(2*n+1);-----// 7b
---rep(i,0,size(clauses)) {-----// 76
-----adj[-clauses[i].first + n].push_back(clauses[i].second + n);-----// eb
-----if (clauses[i].first != clauses[i].second)-----// bc
-----adj[-clauses[i].second + n].push_back(clauses[i].first + n);-----// f0
---}-----// da
---pair<union_find, vi> res = scc(adj);-----// 00
---union_find scc = res.first;-----// 20
---vi dag = res.second;-----// ed
---vi truth(2*n+1, -1);-----// c7
---for (int i = 2*n; i >= 0; i--) {-----// 50
-----int cur = order[i] - n, p = scc.find(cur + n), o = scc.find(-cur + n);--// 4f
-----if (cur == 0) continue;-----// cd
-----if (p == o) return false;-----// d0
-----if (truth[p] == -1) truth[p] = 1;-----// d3
-----truth[cur + n] = truth[p];-----// 50
-----truth[o] = 1 - truth[p];-----// 8c
-----if (truth[p] == 1) all_truthy.push_back(cur);-----// 55
---}-----// c3
---return true;-----// eb
}-----// 6b
```

7.2. Stable Marriage.

```
vi stable_marriage(int n, int** m, int** w) {-----// e4
---queue<int> q;-----// f6
---vi at(n, 0), eng(n, -1), res(n, -1); vvi inv(n, vi(n));-----// c3
---rep(i,0,n) rep(j,0,n) inv[i][w[i][j]] = j;-----// f1
---rep(i,0,n) q.push(i);-----// d8
---while (!q.empty()) {-----// 68
---int curm = q.front(); q.pop();-----// e2
---for (int &i = at[curm]; i < n; i++) {-----// 7e
---int curw = m[curm][i];-----// 95
---if (eng[curw] == -1) { }-----// f7
---else if (inv[curw][curm] < inv[curw][eng[curw]])-----// d6
---q.push(eng[curw]);-----// 2e
---else continue;-----// 1d
---res[eng[curw] = curm] = curw, ++i; break;-----// a1
---}-----// c4
---}-----// 3d
---return res;-----// 42
}-----// bf
```

7.3. Algorithm X.

```
bool handle_solution(vi rows) { return false; }-----// 63
struct exact_cover {-----// 95
---struct node {-----// 7e
---node *l, *r, *u, *d, *p;-----// 19
---int row, col, size;-----// ae
---node(int _row, int _col) : row(_row), col(_col) {-----// c9
---size = 0; l = r = u = d = p = NULL; }-----// c3
---};-----// c1
---int rows, cols, *sol;-----// 7b
```

```
---bool **arr;-----// e6
---node *head;-----// fe
---exact_cover(int _rows, int _cols) : rows(_rows), cols(_cols), head(NULL) {--// b6
---arr = new bool*[rows];-----// cf
---sol = new int[rows];-----// 5f
---rep(i,0,rows)-----// 9b
---arr[i] = new bool[cols], memset(arr[i], 0, cols);-----// dd
---}-----// 21
---void set_value(int row, int col, bool val = true) { arr[row][col] = val; }--// 9e
---void setup() {-----// a3
---node ***ptr = new node**[rows + 1];-----// bd
---rep(i,0,rows+1) {-----// 76
---ptr[i] = new node*[cols];-----// eb
---rep(j,0,cols)-----// cd
---if (i == rows || arr[i][j]) ptr[i][j] = new node(i, j);-----// 16
---else ptr[i][j] = NULL;-----// d2
---}-----// ac
---rep(i,0,rows+1) {-----// fc
---rep(j,0,cols) {-----// 51
---if (!ptr[i][j]) continue;-----// f7
---int ni = i + 1, nj = j + 1;-----// 7a
---while (true) {-----// fc
---if (ni == rows + 1) ni = 0;-----// 4c
---if (ni == rows || arr[ni][j]) break;-----// 8d
---++ni;-----// 68
---}-----// ad
---ptr[i][j]->d = ptr[ni][j];-----// 84
---ptr[ni][j]->u = ptr[i][j];-----// 66
---while (true) {-----// 7f
---if (nj == cols) nj = 0;-----// de
---if (i == rows || arr[i][nj]) break;-----// 4c
---++nj;-----// c5
---}-----// 72
---ptr[i][j]->r = ptr[i][nj];-----// 60
---ptr[i][nj]->l = ptr[i][j];-----// 82
---}-----// 0b
---}-----// 16
---head = new node(rows, -1);-----// 66
---head->r = ptr[rows][0];-----// 3e
---ptr[rows][0]->l = head;-----// 8c
---head->l = ptr[rows][cols - 1];-----// 6a
---ptr[rows][cols - 1]->r = head;-----// c1
---rep(j,0,cols) {-----// 92
---int cnt = -1;-----// d4
---rep(i,0,rows+1)-----// bd
---if (ptr[i][j]) cnt++, ptr[i][j]->p = ptr[rows][j];-----// f3
---ptr[rows][j]->size = cnt;-----// c2
---}-----// b9
---rep(i,0,rows+1) delete[] ptr[i];-----// a5
---delete[] ptr;-----// 72
}-----// 19
```

```
#define COVER(c, i, j) \
    c->r->l = c->l, c->l->r = c->r; \
    for (node *i = c->d; i != c; i = i->d) \
        for (node *j = i->r; j != i; j = j->r) \
            j->d->u = j->u, j->u->d = j->d, j->p->size--; \
#define UNCOVER(c, i, j) \
    for (node *i = c->u; i != c; i = i->u) \
        for (node *j = i->l; j != i; j = j->l) \
            j->p->size++, j->d->u = j->u->d = j; \
    c->r->l = c->l->r = c; \
bool search(int k = 0) { \
    if (head == head->r) { \
        vi res(k); \
        rep(i,0,k) res[i] = sol[i]; \
        sort(res.begin(), res.end()); \
        return handle_solution(res); \
    } \
    node *c = head->r, *tmp = head->r; \
    for ( ; tmp != head; tmp = tmp->r) if (tmp->size < c->size) c = tmp; \
    if (c == c->d) return false; \
    COVER(c, i, j); \
    bool found = false; \
    for (node *r = c->d; !found && r != c; r = r->d) { \
        sol[k] = r->row; \
        for (node *j = r->r; j != r; j = j->r) { COVER(j->p, a, b); } \
        found = search(k + 1); \
        for (node *j = r->l; j != r; j = j->l) { UNCOVER(j->p, a, b); } \
    } \
    UNCOVER(c, i, j); \
    return found; \
} \
};
```

7.4. nth Permutation.

```
vector<int> nth_permutation(int cnt, int n) { \
    vector<int> idx(cnt), per(cnt), fac(cnt); \
    rep(i,0,cnt) idx[i] = i; \
    rep(i,1,cnt+1) fac[i - 1] = n % i, n /= i; \
    for (int i = cnt - 1; i >= 0; i--) \
        per[cnt - i - 1] = idx[fac[i]], idx.erase(idx.begin() + fac[i]); \
    return per; \
}
```

7.5. Cycle-Finding.

```
int find_cycle(int x0, int (*f)(int)) { \
    int t = f(x0), h = f(t), mu = 0, lam = 1; \
    while (t != h) t = f(t), h = f(f(h)); \
    h = x0; \
    while (t != h) t = f(t), h = f(h), mu++; \
    h = f(t); \
    while (t != h) h = f(h), lam++; \
}
```

```
return ii(mu, lam); \
}
```

7.6. Dates.

```
int intToDay(int jd) { return jd % 7; } \
int dateToInt(int y, int m, int d) { \
    return 1461 * (y + 4800 + (m - 14) / 12) / 4 + \
        367 * (m - 2 - (m - 14) / 12 * 12) / 12 - \
        3 * ((y + 4900 + (m - 14) / 12) / 100) / 4 + \
        d - 32075; \
} \
void intToDate(int jd, int &y, int &m, int &d) { \
    int x, n, i, j; \
    x = jd + 68569; \
    n = 4 * x / 146097; \
    x -= (146097 * n + 3) / 4; \
    i = (4000 * (x + 1)) / 1461001; \
    x -= 1461 * i / 4 - 31; \
    j = 80 * x / 2447; \
    d = x - 2447 * j / 80; \
    x = j / 11; \
    m = j + 2 - 12 * x; \
    y = 100 * (n - 49) + i + x; \
}
```

7.7. Simulated Annealing. An example use of Simulated Annealing to find a permutation of length n that maximizes $\sum_{i=1}^{n-1} |p_i - p_{i+1}|$.

```
double curtime() { return static_cast<double>(clock()) / CLOCKS_PER_SEC; } \
int simulated_annealing(int n, double seconds) { \
    default_random_engine rng; \
    uniform_real_distribution<double> randfloat(0.0, 1.0); \
    uniform_int_distribution<int> randint(0, n - 2); \
    // random initial solution \
    vi sol(n); \
    rep(i,0,n) sol[i] = i + 1; \
    random_shuffle(sol.begin(), sol.end()); \
    // initialize score \
    int score = 0; \
    rep(i,1,n) score += abs(sol[i] - sol[i-1]); \
    int iters = 0; \
    double T0 = 100.0, T1 = 0.001, \
        progress = 0, temp = T0, \
        starttime = curtime(); \
    while (true) { \
        if (!(iters & ((1 << 4) - 1))) { \
            progress = (curtime() - starttime) / seconds; \
            temp = T0 * pow(T1 / T0, progress); \
            if (progress > 1.0) break; \
            // random mutation \
            int a = randint(rng); \
            // compute delta for mutation \
            int delta = 0; \

```

```
-----if (a > 0) delta += abs(sol[a+1] - sol[a-1]) - abs(sol[a] - sol[a-1]);-// 94
-----if (a+2 < n) delta += abs(sol[a] - sol[a+2]) - abs(sol[a+1] - sol[a+2]);
-----// maybe apply mutation-----// fb
-----if (delta >= 0 || randfloat(rng) < exp(delta / temp)) {------// 81
-----swap(sol[a], sol[a+1]);-----// b3
-----score += delta;-----// db
-----// if (score >= target) return;-----// 4d
-----}------// 5c
-----iters++; }-----// 28
---return score; }-----// ba
```

7.8. Fast Input Reading.

```
void readn(register int *n) {------// dc
---int sign = 1;-----// 32
---register char c;-----// a5
---*n = 0;-----// 35
---while((c = getc_unlocked(stdin)) != '\n') {------// f3
-----switch(c) {------// 0c
-----case '-': sign = -1; break;-----// 28
-----case ' ': goto hell;-----// fd
-----case '\n': goto hell;-----// 79
-----default: *n *= 10; *n += c - '0'; break;-----// c0
-----}------// 2d
---}------// c3
hell:-----// ba
---*n *= sign;-----// a0
}------// 67
```

7.9. Bit Hacks.

```
int snoob(int x) {------// 73
---int y = x & -x, z = x + y;-----// 12
---return z | ((x ^ z) >> 2) / y;-----// 97
}------// 14
```

#labeled rooted trees
#labeled unrooted trees
 $\sum_{i=1}^n i^2 = n(n+1)(2n+1)/6$
 $!n = n \times!(n-1) + (-1)^n$
 $\sum_{i=1}^n \binom{n}{i} F_i = F_{2n}$
 $\sum_{k=0}^n \binom{k}{m} = \binom{n+1}{m+1}$
 $a \equiv b \pmod{x, y} \Rightarrow a \equiv b \pmod{\text{lcm}(x, y)}$
 $ac \equiv bc \pmod{m} \Rightarrow a \equiv b \pmod{\frac{m}{\text{gcd}(c, m)}}$
 $p \text{ prime} \Leftrightarrow (p-1)! \equiv -1 \pmod{p}$
 $\sigma_x(n) = \prod_{i=0}^r \frac{p_i^{(a_i+1)x-1}}{p_i^x-1}$
 $\sum_{k=0}^m (-1)^k \binom{n}{k} = (-1)^m \binom{n-1}{m}$
 $2^{\omega(n)} = O(\sqrt{n})$
 $d = v_i t + \frac{1}{2} a t^2$
 $v_f = v_i + a t$

n^{n-1}
 n^{n-2}
 $\sum_{i=1}^n i^3 = n^2(n+1)^2/4$
 $!n = (n-1)!(n-1)!(n-2)!$
 $\sum_i \binom{n-i}{i} = F_{n+1}$
 $\sum_{d|n} \phi(d) = n$
 $(\sum_{d|n} \sigma_0(d))^2 = \sum_{d|n} \sigma_0(d)^3$
 $\text{gcd}(n^a - 1, n^b - 1) = n^{\text{gcd}(a, b)} - 1$
 $\sigma_0(n) = \prod_{i=0}^r (a_i + 1)$
 $\sum_{i=1}^n 2^{\omega(i)} = O(n \log n)$
 $v_f^2 = v_i^2 + 2ad$
 $d = \frac{v_i + v_f}{2} t$

7.10. The Twelfefold Way. Putting n balls into k boxes.

Balls	same	distinct	same	distinct	
Boxes	same	same	distinct	distinct	Remarks
-	$p_k(n)$	$\sum_{i=0}^k \left\{ \begin{matrix} n \\ i \end{matrix} \right\}$	$\binom{n+k-1}{k-1}$	k^n	$p_k(n)$: #partitions of n into $\leq k$ positive parts
size ≥ 1	$p(n, k)$	$\left\{ \begin{matrix} n \\ k \end{matrix} \right\}$	$\binom{n-1}{k-1}$	$k! \left\{ \begin{matrix} n \\ k \end{matrix} \right\}$	$p(n, k)$: #partitions of n into k positive parts
size ≤ 1	$[n \leq k]$	$[n \leq k]$	$\binom{k}{n}$	$n! \binom{k}{n}$	$[cond]$: 1 if $cond = true$, else 0

Catalan	$C_0 = 1, C_n = \frac{1}{n+1} \binom{2n}{n} = \sum_{i=0}^{n-1} C_i C_{n-i-1} = \frac{4n-2}{n+1} C_{n-1}$	
Stirling 1st kind	$\begin{bmatrix} 0 \\ 0 \end{bmatrix} = 1, \begin{bmatrix} n \\ 0 \end{bmatrix} = \begin{bmatrix} n \\ 0 \end{bmatrix} = 0, \begin{bmatrix} n \\ k \end{bmatrix} = (n-1) \begin{bmatrix} n-1 \\ k \end{bmatrix} + \begin{bmatrix} n-1 \\ k-1 \end{bmatrix}$	#perms of n objs with exactly k cycles
Stirling 2nd kind	$\left\{ \begin{matrix} n \\ 1 \end{matrix} \right\} = \left\{ \begin{matrix} n \\ n \end{matrix} \right\} = 1, \left\{ \begin{matrix} n \\ k \end{matrix} \right\} = k \left\{ \begin{matrix} n-1 \\ k \end{matrix} \right\} + \left\{ \begin{matrix} n-1 \\ k-1 \end{matrix} \right\}$	#ways to partition n objs into k nonempty sets
Euler	$\left\langle \begin{matrix} n \\ 0 \end{matrix} \right\rangle = \left\langle \begin{matrix} n \\ n-1 \end{matrix} \right\rangle = 1, \left\langle \begin{matrix} n \\ k \end{matrix} \right\rangle = (k+1) \left\langle \begin{matrix} n-1 \\ k \end{matrix} \right\rangle + (n-k) \left\langle \begin{matrix} n-1 \\ k-1 \end{matrix} \right\rangle$	#perms of n objs with exactly k ascents
Euler 2nd Order	$\left\langle\!\left\langle \begin{matrix} n \\ k \end{matrix} \right\rangle\!\right\rangle = (k+1) \left\langle\!\left\langle \begin{matrix} n-1 \\ k \end{matrix} \right\rangle\!\right\rangle + (2n-k-1) \left\langle\!\left\langle \begin{matrix} n-1 \\ k-1 \end{matrix} \right\rangle\!\right\rangle$	#perms of $1, 1, 2, 2, \dots, n, n$ with exactly k ascents
Bell	$B_1 = 1, B_n = \sum_{k=0}^{n-1} B_k \binom{n-1}{k} = \sum_{k=0}^n \left\{ \begin{matrix} n \\ k \end{matrix} \right\}$	#partitions of $1..n$ (Stirling 2nd, no limit on k)

8. USEFUL INFORMATION	* Knuth optimization	– Kirchoff’s matrix tree theorem
9. MISC	· $dp[i][j] = \min_{i < k < j} \{dp[i][k] + dp[k][j] + C[i][j]\}$	– Prüfer sequences
9.1. Debugging Tips.	· $A[i][j - 1] \leq A[i][j] \leq A[i + 1][j]$	– Lovász Toggle
• Stack overflow? Recursive DFS on tree that is actually a long path?	· $O(n^3)$ to $O(n^2)$	– Look at the DFS tree (which has no cross-edges)
• Floating-point numbers	· sufficient: QI and $C[b][c] \leq C[a][d], a \leq b \leq c \leq d$	• Mathematics
– Getting NaN? Make sure <code>acos</code> etc. are not getting values out of their range (perhaps <code>1+eps</code>).	• Greedy	– Is the function multiplicative?
– Rounding negative numbers?	• Randomized	– Look for a pattern
– Outputting in scientific notation?	• Optimizations	– Permutations
• Wrong Answer?	– Use bitset (/64)	* Consider the cycles of the permutation
– Read the problem statement again!	– Switch order of loops (cache locality)	– Functions
– Are multiple test cases being handled correctly? Try repeating the same test case many times.	• Process queries offline	* Sum of piecewise-linear functions is a piecewise-linear function
– Integer overflow?	– Mo’s algorithm	* Sum of convex (concave) functions is convex (concave)
– Think very carefully about boundaries of all input parameters	• Square-root decomposition	– Modular arithmetic
– Try out possible edge cases:	• Precomputation	* Chinese Remainder Theorem
* $n = 0, n = -1, n = 1, n = 2^{31} - 1$ or $n = -2^{31}$	• Efficient simulation	* Linear Congruence
* List is empty, or contains a single element	– Mo’s algorithm	– Sieve
* n is even, n is odd	– Sqrt decomposition	– System of linear equations
* Graph is empty, or contains a single vertex	– Store 2^k jump pointers	– Values too big to represent?
* Graph is a multigraph (loops or multiple edges)	• Data structure techniques	* Compute using the logarithm
* Polygon is concave or non-simple	– Sqrt buckets	* Divide everything by some large value
– Is initial condition wrong for small cases?	– Store 2^k jump pointers	• Logic
– Are you sure the algorithm is correct?	– 2^k merging trick	– 2-SAT
– Explain your solution to someone.	• Counting	– XOR-SAT (Gauss elimination or Bipartite matching)
– Are you using any functions that you don’t completely understand? Maybe STL functions?	– Inclusion-exclusion principle	• Meet in the middle
– Maybe you (or someone else) should rewrite the solution?	– Generating functions	• Only work with the smaller half ($\log(n)$)
• Run-Time Error?	• Graphs	• Strings
– Is it actually Memory Limit Exceeded?	– Can we model the problem as a graph?	– Trie (maybe over something weird, like bits)
	– Can we use any properties of the graph?	– Suffix array
	– Strongly connected components	– Suffix automaton (+DP?)
	– Cycles (or odd cycles)	– Aho-Corasick
	– Bipartite (no odd cycles)	– <code>eerTree</code>
	* Bipartite matching	– Work with $S + S$
	* Hall’s marriage theorem	• Hashing
	* Stable Marriage	• Euler tour, tree to array
	– Cut vertex/bridge	• Segment trees
	– Biconnected components	– Lazy propagation
	– Degrees of vertices (odd/even)	– Persistent
	– Trees	– Implicit
	* Heavy-light decomposition	– Segment tree of X
	* Centroid decomposition	• Geometry
	* Least common ancestor	– Minkowski sum (of convex sets)
	– Eulerian path/circuit	– Rotating calipers
	– Chinese postman problem	– Sweep line (horizontally or vertically?)
	– Topological sort	– Sweep angle
	– (Min-Cost) Max Flow	– Convex hull
	– Min Cut	• Fix a parameter (possibly the answer).
	* Maximum Density Subgraph	• Are there few distinct values?
	– Huffman Coding	• Binary search
	– Min-Cost Arborescence	• Sliding Window (+ Monotonic Queue)
	– Steiner Tree	

- Computing a Convolution? Fast Fourier Transform
- Exact Cover (+ Algorithm X)
- Cycle-Finding
- What is the smallest set of values that identify the solution? The cycle structure of the permutation? The powers of primes in the factorization?
- Look at the complement problem
 - Minimize something instead of maximizing
- Immediately enforce necessary conditions. (All values greater than 0? Initialize them all to 1)
- Add large constant to negative numbers to make them positive
- Counting/Bucket sort

10. FORMULAS

- **Jacobi symbol:** $\left(\frac{a}{b}\right) = a^{(b-1)/2} \pmod{b}$
- **Heron’s formula:** A triangle with side lengths a, b, c has area $\sqrt{s(s-a)(s-b)(s-c)}$ where $s = \frac{a+b+c}{2}$.
- **Pick’s theorem:** A polygon on an integer grid containing i lattice points and having b lattice points on the boundary has area $i + \frac{b}{2} - 1$.
- **Euler’s totient:** The number of integers less than n that are coprime to n are $n \prod_{p|n} \left(1 - \frac{1}{p}\right)$ where each p is a distinct prime factor of n .
- **König’s theorem:** In any bipartite graph $G = (L \cup R, E)$, the number of edges in a maximum matching is equal to the number of vertices in a minimum vertex cover. Let U be the set of unmatched vertices in L , and Z be the set of vertices that are either in U or are connected to U by an alternating path. Then $K = (L \setminus Z) \cup (R \cap Z)$ is the minimum vertex cover.
- A minumum Steiner tree for n vertices requires at most $n - 2$ additional Steiner vertices.
- The number of vertices of a graph is equal to its minimum vertex cover number plus the size of a maximum independent set.
- **Wilson’s theorem:** $(n - 1)! \equiv -1 \pmod{n}$ iff. n is prime
- **Lagrange polynomial** through points $(x_0, y_0), \dots, (x_k, y_k)$ is
$$L(x) = \sum_{j=0}^k y_j \prod_{\substack{0 \leq m \leq k \\ m \neq j}} \frac{x - x_m}{x_j - x_m}$$
- **Hook length formula:** If λ is a Young diagram and $h_\lambda(i, j)$ is the hook-length of cell (i, j) , then then the number of Young tableaux $d_\lambda = n! / \prod h_\lambda(i, j)$.
- **Möbius inversion formula:** If $f(n) = \sum_{d|n} g(d)$, then $g(n) = \sum_{d|n} \mu(d) f(n/d)$. If $f(n) = \sum_{m=1}^n g(\lfloor n/m \rfloor)$, then $g(n) = \sum_{m=1}^n \mu(m) f(\lfloor \frac{n}{m} \rfloor)$.

10.1. **Markov Chains.** A Markov Chain can be represented as a weighted directed graph of states, where the weight of an edge represents the probability of transitioning over that edge in one timestep. Let $P^{(m)} = (p_{ij}^{(m)})$ be the probability matrix of transitioning from state i to state j in m timesteps, and note that $P^{(1)}$ is the adjacency matrix of the graph. **Chapman-Kolmogorov:** $p_{ij}^{(m+n)} = \sum_k p_{ik}^{(m)} p_{kj}^{(n)}$. It follows that $P^{(m+n)} = P^{(m)} P^{(n)}$ and

$P^{(m)} = P^m$. If $p^{(0)}$ is the initial probability distribution (a vector), then $p^{(0)} P^{(m)}$ is the probability distribution after m timesteps.

The return times of a state i is $R_i = \{m \mid p_{ii}^{(m)} > 0\}$, and i is *aperiodic* if $\gcd(R_i) = 1$. A MC is aperiodic if any of its vertices is aperiodic. A MC is *irreducible* if the corresponding graph is strongly connected.

A distribution π is stationary if $\pi P = \pi$. If MC is irreducible then $\pi_i = 1/\mathbb{E}[T_i]$, where T_i is the expected time between two visits at i . π_j/π_i is the expected number of visits at j in between two consecutive visits at i . A MC is *ergodic* if $\lim_{m \rightarrow \infty} p^{(0)} P^m = \pi$. A MC is ergodic iff. it is irreducible and aperiodic.

A MC for a random walk in an undirected weighted graph (unweighted graph can be made weighted by adding 1-weights) has $p_{uv} = w_{uv} / \sum_x w_{ux}$. If the graph is connected, then $\pi_u = \sum_x w_{ux} / \sum_v \sum_x w_{vx}$. Such a random walk is aperiodic iff. the graph is not bipartite.

An *absorbing* MC is of the form $P = \begin{pmatrix} Q & R \\ 0 & I_r \end{pmatrix}$. Let $N = \sum_{m=0}^\infty Q^m = (I_t - Q)^{-1}$. Then, if starting in state i , the expected number of steps till absorption is the i -th entry in $N1$. If starting in state i , the probability of being absorbed in state j is the (i, j) -th entry of NR .

Many problems on MC can be formulated in terms of a system of recurrence relations, and then solved using Gaussian elimination.

10.2. **Burnside’s Lemma.** Let G be a finite group that acts on a set X . For each g in G let X^g denote the set of elements in X that are fixed by g . Then the number of orbits

$$|X/G| = \frac{1}{|G|} \sum_{g \in G} |X^g|$$

10.3. **Bézout’s identity.** If (x, y) is any solution to $ax + by = d$ (e.g. found by the Extended Euclidean Algorithm), then all solutions are given by

$$\left(x + k \frac{b}{\gcd(a, b)}, y - k \frac{a}{\gcd(a, b)}\right)$$

10.4. **Misc.**

10.4.1. *Determinants and PM.*

$$\begin{aligned} \det(A) &= \sum_{\sigma \in S_n} \operatorname{sgn}(\sigma) \prod_{i=1}^n a_{i, \sigma(i)} \\ \operatorname{perm}(A) &= \sum_{\sigma \in S_n} \prod_{i=1}^n a_{i, \sigma(i)} \\ pf(A) &= \frac{1}{2^n n!} \sum_{\sigma \in S_{2n}} \operatorname{sgn}(\sigma) \prod_{i=1}^n a_{\sigma(2i-1), \sigma(2i)} \\ &= \sum_{M \in \operatorname{PM}(n)} \operatorname{sgn}(M) \prod_{(i, j) \in M} a_{i, j} \end{aligned}$$

10.4.2. *BEST Theorem.* Number of OST given by Kirchoff’s Theorem (remove r/c with root) $\# \operatorname{OST}(G, r) \cdot \prod_v (d_v - 1)!$

10.4.3. *Primitive Roots.* Only exists when n is $2, 4, p^k, 2p^k$, where p odd prime. Assume n prime. Number of primitive roots $\phi(\phi(n))$ Let g be primitive root. All primitive roots are of the form g^k where $k, \phi(p)$ are coprime.
 k -roots: $g^{i \cdot \phi(n)/k}$ for $0 \leq i < k$

10.4.4. *Sum of primes.* For any multiplicative f :

$$S(n, p) = S(n, p - 1) - f(p) \cdot (S(n/p, p - 1) - S(p - 1, p - 1))$$

10.4.5. *Floor.*

$$\begin{aligned} \lfloor \lfloor x/y \rfloor / z \rfloor &= \lfloor x/(yz) \rfloor \\ x \% y &= x - y \lfloor x/y \rfloor \end{aligned}$$

PRACTICE CONTEST CHECKLIST

- How many operations per second? Compare to local machine.
- What is the stack size?
- How to use printf/scanf with long long/long double?
- Is `__int128` available?
- Does MLE give RTE or MLE as a verdict? What about stack overflow?
- What is `RAND_MAX`?
- How does the judge handle extra spaces (or missing new-lines) in the output?
- Look at documentation for programming languages.
- Try different programming languages: C++ and Java.
- Try the submit script.
- Try local programs: `i?python[23]`, `factor`.
- Try submitting with `assert(false)` and `assert(false)`.
- Return-value from `main`.
- Look for directory with sample test cases.
- Remove this page from the notebook.