index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <meta http-equiv="X-UA-Compatible" content="ie=edge">
    <title>Exception Handling</title>
    <link rel="stylesheet" href="./css/bootstrap.min.css">
</head>
<body>
    <div class="container">
        <div class="row">
            <div class="col-sm-12">
                <h1 class="text-primary">Divide two numbers</h1>
                <form class="form-inline" id="form">
                    <div class="form-group">
                        <label for="num1">Num 1: </label>
                          
                        <input type="number" name="num1" id="num1"</pre>
class="form-control">
                    </div>
                      
                    <div class="form-group">
                        <label for="num2">Num 2: </label>
                          
                        <input type="number" name="num2" id="num2"</pre>
class="form-control">
                    </div>
                      
                    <button type="submit" class="btn btn-</pre>
primary">Divide</button>
                </form>
                <br>
                <h4 id="ans" class="text-success"></h4>
                <h4 id="error" class="text-danger"></h4>
            </div>
        </div>
    </div>
    <script src="./js/bootstrap.min.js"></script>
    <script src="./js/jquery-3.3.1.min.js"></script>
    <script>
        $(document).ready(function () {
            $('#form').submit(function (e) {
                e.preventDefault();
                $('#ans').text('');
                $('#error').text('');
```

```
const num1 = $('#num1').val();
const num2 = $('#num2').val();
try {
    if (num2 == 0) {
        throw new Error('Denominator cannot be zero')
    }
    const ans = num1 / num2;
    $('#ans').text('Answer = ' + ans);
} catch (error) {
    $('#error').text(error);
}
});
</script>
</body>
</html>
```

