



BKT 119-500F-11T

Compressore con 2 gruppi  
pompani bicilindrici traino  
cinghia, su serbatoi fissi  
da 500 e 900 litri.

Compressor with 2 belt-driven  
two-cylinder compressor  
pumps, stationary 500- or  
900-litre tank.

Kompressor mit 2  
keilriemengetriebenen  
Aggregaten, auf 500-  
oder 900 Liter Behälter.

Codice Code	Prodotto Product	L x D x H (cm)	kg	lbs	tot.	2 010000 036495
883BQ2A822	BKT 113-500F-8T	208 x 70 x 145	259	569,8	—	8017750196367
883QI2A822	BKT 114-500F-11T	208 x 70 x 145	301	662,2	—	8017750224879
883IT2A822	BKT 119-500F-11T	208 x 70 x 145	301	662,2	—	8017750189147
883IQ2A822	BKT 119-500F-15T	208 x 70 x 145	328	721,6	—	8017750189154
893BW2A822	BKT 120-900F-20T	233 x 83 x 176	529	1166,2	—	8017750241715

t	Codice Code	Prodotto Product	Vol/Ph	kW	HP	Model	l/min.	m³/h	c.f.m.	bar	p.s.i.	R.P.M.	n°	n°	dB(A)	L x D x H (cm)	kg	lbs
FISSI BISTADIO TRIFASE "TANDEM" TELEAVVIATI   STATIONARY STAR-DELTA DOUBLE-STAGE THREE-PHASE "TANDEM"   STATIONÄR STERN-DREIECK DOPPELSTUFE 3 PHASIG "TANDEM"																		
500	883BQ2A822	BKT 113-500F-8T •	400/3	3+3	4+4	2-BK113	860	51,6	30,4	10	145	1310	2	2	83	200 x 60 x 115	225	495
500	883QI2A822	BKT 114-500F-11T •	400/3	4+4	5,5+5,5	2-BK114	1160	69,6	20,5	10	145	1370	2	2	80	200 x 60 x 125	267	588,6
500	883IT2A822	BKT 119-500F-11T •	400/3	4+4	5,5+5,5	2-BK119	1348	80,9	47,6	10	145	1220	2	2	83	200 x 60 x 125	267	588,6
500	883IQ2A822	BKT 119-500F-15T •	400/3	5,5+5,5	7,5+7,5	2-BK119	1680	100,8	59,4	10	145	1250	2	2	83	200 x 60 x 120	294	648,2
900	893BW2A822	BKT 120-900F-20T • <b>NEW</b>	400/3	7,5+7,5	10+10	BK120	2160	129,3	76,3	10	145	1100	2	2	83	212 x 80 x 155	482	1060,4

Sui modelli con avviamento stella-triangolo  
la centralina non è cablata.

On the star-delta models the control unit  
is not wired to the power connection.

Bei den Modellen mit Stern-Dreieck Schaltung ist  
lediglich die Stromzuführung bauseitig zu verlegen.