

blib Code Reference v1.2

David Hobach

Contents

blib	3
Disclaimer	3
Coding Conventions	3
Library Usage	4
Dependencies	5
Imports	5
Global Variables	5
Global Aliases	6
Functions	7
args	17
Dependencies	18
Imports	18
Global Variables	18
Functions	18
arr	21
Dependencies	21
Functions	21
cdoc	23
Dependencies	23
Functions	23
daemon	28
Dependencies	29
Imports	29
Global Variables	29
Functions	29
date	32
Dependencies	32
Functions	32
delay	33
Dependencies	34
Functions	34
dmcrypt	35
Dependencies	35
Imports	35

	Functions	35
flog		37
	Dependencies	38
	Imports	38
	Global Variables	38
	Functions	38
fs		43
	Dependencies	43
	Functions	43
http		46
	Dependencies	46
	Global Variables	46
	Functions	46
ini		47
	Dependencies	48
	Functions	48
keys		50
	Dependencies	50
	Imports	50
	Functions	50
multithreading/ipcm		52
	Dependencies	53
	Imports	53
	Functions	53
multithreading/ipcv		55
	Dependencies	55
	Functions	55
multithreading/mtx		57
	Dependencies	57
	Imports	58
	Functions	58
multithreading/multiw		61
	Dependencies	61
	Functions	61
os/osid		62
	Dependencies	63
	Functions	63
os/qubes4/dom0		65
	Dependencies	65
	Imports	66
	Functions	66
proc		79
	Dependencies	79
	Functions	79
str		80
	Dependencies	80

Functions	80
tcolors	81
Dependencies	81
Global Variables	81
Functions	81
traps	81
Dependencies	81
Functions	81
types	83
Dependencies	83
Global Variables	83
Functions	83
ui	85
Dependencies	85
Functions	85
Reference List	85

blib

blib - a bash library

The basic functions which are imported by default.

Copyright (C) 2018 David Hobach LGPLv3

version: Execute `blib version` or use `b_version`.

Disclaimer

This program is free software: you can redistribute it and/or modify it under the terms of the Lesser GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the

Lesser GNU General Public License for more details.

You should have received a copy of the Lesser GNU General Public License along with this program. If not, see <https://www.gnu.org/licenses/>.

The above statements apply to all modules of blib if not mentioned otherwise.

Coding Conventions

1. embrace the KISS principle

2. some general guidelines: <http://www.kfirlavi.com/blog/2012/11/14/defensive-bash-programming/>
3. use `b_[module]_[camel case function name]` to denote functions meant to be used by users of the library, `B_[module]_[upper case var name]` for global variables
4. use `BLIB_[module]_[upper case var name]` for global variables (to be avoided whenever possible) not meant to be used by library users (“private” variables); library users can use setters or getters
5. use the `BLIB_STORE` with the above naming conventions for “private” variables whenever possible
6. use `blib_[module]_[camel case function name]` to denote private functions not meant to be used by library users; the function name should not contain any underscores
7. the `blib` module itself is the only exception which can use `b_`, `B_`, `blib_`, `BLIB_` without module name
8. prefixes such as `t_`, `T_` and `UTD_` are exclusively related to test code
9. set exit codes (`!= 0 -> issue`) wherever it makes sense
10. keep the global namespace clean whenever possible
11. declare `-g` must be used in order to allow sourcing from a function (`b_import`)
12. modules must implement a function such as
`b_[module]_getDeps`
returns: newline-separated list of dependencies of the module
13. modules should provide a header similar to that of the `blib` source file in order to make the documentation generation work
14. modules may be placed in subfolders of arbitrary depth
15. use 0 to indicate true and 1 to indicate false for variables; for exit codes use a non-zero exit code to indicate the number of errors
16. functions should be tagged with the following tags, if applicable:
@StateChanging - the function changes the internal state of the script in a way that will not propagate to supershells (e.g. global variables) and should thus not be called from subshells (unless the user wants the state to only change in that shell)
@B_E - the function uses `B_E` for error handling and may thus behave differently depending on the implemented error handler

Library Usage

with the default bash options:

```
source blib
b_checkVersion 1 0 || { >&2 echo "This script depends on blib (https://github.com/3hhh/blib)"
b_import [module]
```

Dependencies

dirname
readlink
whoami
sort
cat
mktemp
rm
mv
su

Imports

[“traps” || B_E]

Global Variables

B_TEST_MODE

blib/B_TEST_MODE

blib will set this variable to 0, if blib is running in test mode.

This variable may be used to bypass code during testing, if bats cannot test that code due to its limitations (e.g. for EXIT traps which bats uses for itself).

B_CALLER_NAME

blib/B_CALLER_NAME

Name of the executable or script as String which called blib and any child libraries.

B_ERR

blib/B_ERR

Global variable used for error handling throughout blib, cf. B_E.

It is recommended to always set an at least partially static error message on confirmed errors as variables may be empty (which would indicate “no error” for B_E).

B_RC

blib/B_RC

Can be used to set the return code for B_E in the case of an error. It defaults to 1.

This should be set to an integer value between 1 and 255. Any other value may cause undefined behaviour.

B_LIB_DIR

blib/B_LIB_DIR

Path of the blib installation directory.

B_CONF_DIR

blib/B_CONF_DIR

Path to blib configuration directory. Modules may create subfolders named by their module name there. May not exist.

B_SCRIPT

blib/B_SCRIPT

Global variable which can be used to obtain the two global variables B_SCRIPT_DIR and B_SCRIPT_NAME as follows:

```
eval "$B_SCRIPT"
```

B_SCRIPT_NAME

blib/B_SCRIPT_NAME

Path of the sourced or executed bash script executing the eval (symlinks are resolved) of B_SCRIPT.

B_SCRIPT_DIR

blib/B_SCRIPT_DIR

Name of the sourced or executed bash script executing the eval (symlinks are resolved) of B_SCRIPT.

Global Aliases

Alias expansion is automatically enabled by blib as it is required for its core functionality. So if you have strange aliases defined in your shell environment, this may cause undefined blib behaviour.

B_E

blib/B_E

The blib error handler: All blib modules use it whenever execution errors require special handling that the currently executing code cannot achieve.

Syntax:

```
B_ERR="This is an error message." ; B_E ;
```

If you need to set the return/exit code, you can do it with B_RC:

```
B_ERR="This is another error message." ; B_RC=6 ; B_E ;
```

Calling B_E means:

Check B_ERR for an error message and if there is one, handle it. It can be placed at the end of a line or on its own line. B_E will then process the error message in the way defined by the error handler (cf. b_defaultErrorHandler) and stop any further execution of code in the current context (function, script, ...) returning a non-zero exit code (1) unless the described error was fixed. In the latter unlikely case it'll let execution proceed.

More examples:

```
#handle a potentially failing command:  
cmd || { B_ERR="cmd failed." ; B_E }
```

```
#capture stdout of a potentially failing command:  
local out=  
out="$(cmd)" || { B_ERR="cmd failed." ; B_E }
```

```
#handle multiple potentially failing commands in a try/catch like manner:  
(  
    set -e  
    cmd1  
    cmd2  
    cmd3  
) #NOTE: || doesn't work here!  
if [ $? -ne 0 ] ; then  
    B_ERR="Some commands failed."  
    B_E  
fi
```

The error handler can be re-defined at runtime with b_setErrorHandler.

Functions

b__printStackTrace [skip level]

blib/b__printStackTrace

[skip level]: skip that many levels of the stack trace (optional, default: 1 - skip this function call)

print the current stack trace in a human readable way

returns: stack trace with the first levels skipped as defined

b__nop

blib/b__nop

Do nothing.

returns: nothing; sets a zero exit code

b__version [part]

blib/b__version

Get the version of this blib instance.

[part]: Optional parameter defining the part of the version to retrieve (0: all as String (default), 1: major as Integer, 2: minor as Integer).

returns: blib version as string; always sets a zero exit code

b__checkVersion [minimum allowed major] [minimum allowed minor] [maximum allowed major] [maximum allowed minor]

blib/b__checkVersion

Check whether the currently running blib instance meets the given blib version requirements.

To e.g. make sure you're on blib version 1.1 or higher, use

```
source blib
b__checkVersion 1 2 || { >&2 echo "This script depends on blib (https://github.com/3hhh/blib)"
```

[minimum allowed major]: The lowest acceptable major version number (default: 0).

[minimum allowed minor]: The lowest acceptable minor version number (default: 0).

[maximum allowed major]: The highest acceptable major version number (default: infinite).

[maximum allowed minor]: The highest acceptable minor version number (default: infinite).

returns: Sets a zero exit code, if and only if the currently running blib instance meets the version requirements.

b__defaultErrorHandler [error out] [send err] [send stack trace]

blib/b__defaultErrorHandler

The blib default error handler.

As any error handler it must

1. handle the error message (if not the error itself) lying in B_ERR

2. not take any non-numeric arguments
3. not error out itself
4. implement the below *[error out]* as its first parameter (to make `b_setBE` work)
5. ideally use `b_error` to send error messages to the user
6. return one of the following exit codes:
 - a) 0: **if and only if** the error was fixed entirely and the caller may ignore the error (i.e. probably never)
 - b) 1: The error wasn't fixed. Functions should return to their caller indicating an error (non-zero status code). Direct shell calls will exit. `B_ERR` is **not** reset to blank, i.e. the next call to `B_E` in the same context will cause another error. The caller may use this to either *throw* the error further or handle and clear the error.
 - c) 2: Force a stop of execution in the current shell / error out.

[error out]: Whether or not to call exit after the error message handling, if the error couldn't be handled (default: 0 = always error out / call exit). If set to 1, `B_E` will allow e.g. functions to return to their callers.

[send err]: Whether or not to send the error message to the user (default: 0 = send).

[send stack trace]: Whether or not to send a stack trace to the user (default: 0 = send).

returns: see the description above

b_setBE [error out]

blib/b_setBE

Set the [error out] behaviour of the currently configured error handler.

Contrary to `b_setErrorHandler` this function may be called by `blib` modules as all error handlers are required to support [error out] as parameter.

Example for switching the error out behaviour:

```
b_setBE 1
funcThatMayCallB_E #without subshell
ret=$?
b_resetErrorHandler
```

[error out]: see `b_defaultErrorHandler` (default: 0)

returns: nothing, always sets a zero exit code

@StateChanging

b_setErrorHandler [handler]

blib/b_setErrorHandler

Set the error handler for all future executions of B_E in the current scope.

You can do this in e.g. subshells to limit the effect.

blib modules should only use this function if absolutely necessary to temporarily modify the error behaviour whilst making sure that b_resetErrorHandler is called in the end. Otherwise it will prevent library users from setting the general behaviour in their scripts.

Usually you do not want to write an entirely new handler, but modify the b_defaultErrorHandler parameters with this setter or use b_setBE for that.

[handler]: Function to handle errors. See b_defaultErrorHandler for details.

returns: nothing

@StateChanging

b_resetErrorHandler [reset B_ERR]

blib/b_resetErrorHandler

Set the error handler to whatever it was before the last call to b_setErrorHandler or b_setBE.

[reset B_ERR]: Whether or not to also reset B_ERR (default: true/0).

returns: nothing, always sets a zero exit code

@StateChanging

b_getErrorHandler

blib/b_getErrorHandler

Get the currently for B_E configured error handler.

returns: the error handler function

b_silence [function] [param 1] .. [param p]

blib/b_silence

Call the given function with its parameters in the current shell context whilst suppressing all of its output to both stdout and stderr. Anything written to B_ERR however is passed to B_E (which can still write to stderr).

This function is useful when you want to keep an error message set with B_ERR, but discard everything else.

In contrast **yourfunction &> /dev/null** may also drop the error message, if you're using an error handler (see B_E) that writes to stdout or stderr.

[function]: The function to execute.

[param p]: An arbitrary number of function parameters.

returns: Sets the status code of the called function, but doesn't print anything. B_E is called on errors.

@B_E

b_defaultMessageHandler [message type] [message] [first part] [last part]

blib/b_defaultMessageHandler

Handles the given message by printing information to stdout and errors to stderr. This is the default message handler used by blib. It can be changed by b_setMessageHandler.

Message handler implementations must support at least the parameters of this function, but may add additional parameters. If an handler implementation does not support partial messages (i.e. the [first part] and [last part] parameters), it should be chained to a b_cachingMessageHandler.

[message type]: 0=informational message, 1=error message.

[message]: String representing the message.

[first part]: If set to 0, assume that the given message is the first part of an overall chain of messages (default: 0).

[last part]: If set to 0, assume that the given message is the final part of an overall chain of messages (default: 0).

returns: Nothing. Never causes errors.

b_cachingMessageHandler [message handler] [message type] [message] [first part] [last part]

blib/b_cachingMessageHandler

A message handler implementation which caches partial messages for a receiving message handler that cannot handle them until they are completed.

Use `b_initCachingMessageHandler` && `b_setMessageHandler "b_cachingMessageHandler [your message handler]"` to set your receiving message handler as message handler to cache messages for. This implementation uses the `b_getDefaultMessageHandlerIntermediate` as separator between partial messages.

[message handler]: The function implementing the receiving message handler. It must handle the [message type] and the [message].

[message type]: See b_defaultMessageHandler.

[message]: See b_defaultMessageHandler.

[first part]: See b_defaultMessageHandler.

[last part]: See b_defaultMessageHandler.

returns: Nothing. Never causes errors.

b_initCachingMessageHandler [maximum message type]

blib/b_initCachingMessageHandler

Initializes a new cache for a b_cachingMessageHandler. This function *must* be called at least once before using b_cachingMessageHandler.

[maximum message type]: Maximum message type for which to allocate caches (default: 1 -> allocate caches for 0..1/info..error).

returns: Nothing.

@B_E

b_setDefaultMessageHandlerIntermediate [intermediate]

blib/b_setDefaultMessageHandlerIntermediate

[intermediate]: String to use as intermediate between two message parts with b_defaultMessageHandler, i.e. the resulting message should be [part 1][intermediate][part 2]. Default: Space.

returns: Nothing.

b_getDefaultMessageHandlerIntermediate

blib/b_getDefaultMessageHandlerIntermediate

Get the currently configured intermediate string for the b_defaultMessageHandler.

returns: The intermediate String.

b_setDefaultMessageHandlerPrefix [message type] [prefix]

blib/b_setDefaultMessageHandlerPrefix

Set the prefix to use for the default message handler and the given message type.

[message type]: 0=informational message, 1=error message.

[prefix]: A string to prefix all messages of the given type.

b_getDefaultMessageHandlerPrefix [message type]

blib/b_getDefaultMessageHandlerPrefix

Get the prefix used for the default message handler and the given message type.

[message type]: 0=informational message, 1=error message.

returns: The currently configured prefix.

b_info [message] [first part] [last part] [message handler param 1] ...
[message handler param n]

blib/b_info

Send an informational message to the user. The message is dispatched via the currently configured message handler (default: `b_defaultMessageHandler`).

[message]: to send

[first part]: If set to 0, assume that the given message is the first part of an overall chain of messages (default: 0).

[last part]: If set to 0, assume that the given message is the final part of an overall chain of messages (default: 0).

[message handler param i]: Arbitrary parameters to pass to the currently configured message handler (cf. `b_setMessageHandler`).

returns: Nothing, always sets a zero exit code.

b_error [message] [first part] [last part] [message handler param 1]
... [message handler param n]

blib/b_error

Send an error message to the user *without* erroring out. The message is dispatched via the currently configured message handler (default: `b_defaultMessageHandler`).

99.9% of all users will want to use the combination of `B_ERR` and `B_E` for proper error handling instead.

[message]: to send

[first part]: If set to 0, assume that the given message is the first part of an overall chain of messages (default: 0).

[last part]: If set to 0, assume that the given message is the final part of an overall chain of messages (default: 0).

[message handler param i]: Arbitrary parameters to pass to the currently configured message handler (cf. `b_setMessageHandler`).

returns: Nothing, always sets a zero exit code.

b_setMessageHandler [handler]

blib/b_setMessageHandler

Set the handler used to send messages to the user. By default, `b_defaultMessageHandler` is used.

[handler]: Function to handle the messages. See `b_defaultMessageHandler` for the requirements.

returns: Nothing.

b__getMessageHandler

blib/b__getMessageHandler

Get the currently configured message handler.

returns: The message handler.

b__enforceUser [user name]

blib/b__enforceUser

enforce that the user is the given one and if not, exit the script and set a non-zero status code

[user name]: user name to check against

returns: nothing

@B_E

b__isFunction [potential function name]

blib/b__isFunction

check whether the given function is defined

returns: zero exit code if the function is defined

b__getBlibModules

blib/b__getBlibModules

get all available blib module names as a newline-separated list

returns: all available blib module names as newline-separated list

b__listContains [list] [entry]

blib/b__listContains

check whether the given list contains the given entry

[list]: newline-separated list

[entry]: string to be found on a single line within the list (equality check)

returns: a zero exit code if the list contains the entry; a non-zero exit code otherwise

b__checkDeps [list]

blib/b__checkDeps

check whether the given list of dependencies is met by the system running this function.

[list]: newline-separated list of binaries or commands that the system must be able to execute

returns: list of dependencies not met; a non-zero exit code is set, if the list contains elements

b__blib__getDeps

blib/b__blib__getDeps

Get the dependencies of this module.

returns: newline-separated list of dependencies of this module

b__import [module] [double import]

blib/b__import

Import the given module into the current context.

[module]: relative path of the module to import (relative to the blib/lib root directory)

[double import]: if set to 1, import the given module regardless of whether it was imported before (default: 0 = don't do duplicate imports)

returns: nothing, errors out if the import failed and sets a non-zero status code; if the import was successful or previously done, a zero exit code is set

@StateChanging

@B_E

b__generateStandalone [function] [module dep 1] .. [module dep n] -
[function dep 1] .. [function dep d] - [function param 1] .. [function
param p]

blib/b__generateStandalone

Create a standalone variant of blib in a single file running the given function when called (sourcing that file will only make the functions available) and print that file to stdout.

The current execution state is not retained.

[function]: The function to call when the generated script is executed. All script parameters when calling [output file] are passed to this function. The function must be available in the current context.

[module dep i]: Names of the modules to include in the standalone file. They do not need to be imported. They are loaded in the specified order.

[-]: Dash used as separator between the various types of arguments. If none is provided, all parameters are assumed to be modules.

[function dep j]: An arbitrary number of functions that need to be added in order to satisfy the dependencies of the function to call (e.g. if function A is meant to be called, but uses function B internally, you'll have to pass B as one of its dependencies). Dependencies that can be found in added modules should *not* be added.

[function param p]: Static parameters to add to the function as single String. Dynamic parameters should be passed to the generated script.

returns: Sets a zero exit code and prints the output file to stdout on success. May error out otherwise.

@B_E

b_execFuncInCurrentContext [function] [module dep 1] .. [module dep n] - [function param 1] .. [function param p]

blib/b_execFuncInCurrentContext

Execute the given function in the current context.

[function]: The function to execute.

[module dep i]: Names of the modules required by the function. They do not need to be imported by the function itself.

[-]: A dash as separator character between the various parameters.

[function param p]: An arbitrary number of function parameters.

returns: Whatever the executed function returns.

b_execFuncAs [user] [function] [module dep 1] .. [module dep n] - [function dep 1] .. [function dep d] - [function param 1] .. [function param p]

blib/b_execFuncAs

Attempt to execute the Bash function as the given user.

Whether or not this works highly depends on the underlying OS and its (sudo & su) configuration. In particular this function may cause further execution to wait for the user to type in the password of the requested user.

If the given user is identical to the current user, `b_execFuncAs` may decide to run the function in the current context. Otherwise it may run in a different process, i.e. all initialization and state may be lost. Thus make sure to create any required state within your function.

[user]: User to execute the function as (default: root).

[function]: The function to execute.

[module dep i]: Names of the modules required by the function. They do not need to be imported by the function itself. They are loaded in the specified order.

[-]: A dash as separator character between the various parameters.

[function dep j]: An arbitrary number of functions that need to be added in order to satisfy the dependencies of the function to call (e.g. if function A is meant to be called, but uses function B internally, you'll have to pass B as one of its dependencies). Dependencies that can be found in added modules should *not* be added.

[function param p]: An arbitrary number of function parameters.

returns: Whatever the executed function returns. A non-zero exit code may also indicate that the user switch didn't work. In particular `B_E` is *not* called if the executed function returns an error.

@B_E

b_isModule [module name]

blib/b_isModule

Test whether the given name represents a blib module name.

returns: sets a zero exit code if the given name is a valid module name

args

Stateful argument parser for bash.

Regular arguments and options are parsed via `b_args_parse`. Afterwards they can be retrieved via `b_args_get` and `b_args_getOption`. Options may have parameters, can be repeated and combined.

The module can also check the correctness of options. All remaining correctness checks (e.g. for regular or option parameters) are left to the user of this module.

Conventions:

- Options always start with - and may occur everywhere.

- Single character options may be combined, e.g. `-ajh` will be considered the same as `-a -j -h`. Long options such as `--option` cannot be combined.
Recommendation: Use long options for those options which require parameters and single letter options for everything else.
- Everything after a space-separated double dash (`--`) is not considered an option, but a regular argument.

Copyright (C) 2019 David Hobach LGPLv3
0.8

Dependencies

no dependencies

Imports

types

Global Variables

B_ARGS

args/B_ARGS

Array of regular/non-option arguments in the order of their appearance.
Instead of using it directly, it is recommended to use `b_args_get` instead. The array may be removed in future versions.

B_ARGS_OPTS

args/B_ARGS_OPTS

Map of options. `[option]_[index]` is used as key with `[index]` starting at zero. The values are the option parameters (if any). Multiple option parameters are separated by tabs.

The latter separator can be changed via `b_args_setOptionParamSeparator` before calling `b_args_parse`.

The index will only increase if options are repeated.

Instead of using it directly, it is recommended to use `b_args_getOption` instead. The array may be removed in future versions.

Functions

b_args_getDeps

args/b_args_getDeps

Get the dependencies of this module.

returns: newline-separated list of dependencies of this module

b__args__setOptionParamSeparator [separator]

args/b__args__setOptionParamSeparator

Set the separator for multiple option parameters.

[separator]: String to use as separator for multiple option parameters.

returns: Nothing.

b__args__getOptionParamSeparator

args/b__args__getOptionParamSeparator

Get the separator for multiple option parameters.

returns: Nothing.

b__args__init [allow flag] [option 1] [option param count 1] ... [option n] [option param count n]

args/b__args__init

Initialize the args module. It is recommended to call this function before using this module, if you want to achieve any non-default behaviour.

[allow flag]: If set to 0, assume that non-specified options do not have any parameters (default). If set to 1, enforce that only the given options are allowed and otherwise error out.

[option i]: An allowed option including its leading - prefix.

[option param count i]: Number of expected parameters for that option. The parameters must directly follow the option. If less parameters are found, the parser will error out.

returns: Nothing, always sets a zero exit code.

@StateChanging

@B_E

b__args__parse [arguments]

args/b__args__parse

Parse the given arguments.

Call b__args__init before parsing, if you desire any non-default parsing behaviour.

[arguments]: The arguments meant to be parsed, usually "\$@".

returns: Sets a zero exit code on success and calls B_E otherwise.

@StateChanging

@B_E

b_args_assertOptions [option 1] ... [option n]

args/b_args_assertOptions

Assert that the parsed options contain only the given allowed options (or less).

[option i]: Option to check against.

[returns]: Sets a zero exit code, if the current parsed state contains only allowed options and errors out with B_E otherwise. Prints a list of invalid options in the error case.

@B_E

b_args_get [index] [fallback]

args/b_args_get

Get the argument at the given index.

[index]: Index of the argument to retrieve, starting at 0.

[fallback]: Value to return, if the given index was provided as empty argument or is missing. Default: empty String

returns: The argument at the given index. An *empty* (existing!) argument will cause the fallback to be returned with a zero exit code. If no argument was found at that index, a nonzero exit code is set and the fallback is returned.

b_args_getInt [index] [fallback]

args/b_args_getInt

Convenience wrapper for b_args_get that also checks the type of the argument to be an integer.

returns: See b_args_get. Also sets a nonzero exit code, if the argument is not an integer.

b_args_getCount

args/b_args_getCount

Get the number of arguments.

returns: Number of arguments.

b_args_getOption [option] [fallback] [repeat index] [parameter index]

args/b_args_getOption

Check whether the given option is set and retrieve its parameter, if it was.

[option]: String defining the option, e.g. `--option` or `-a`.

[fallback]: Value to return if the option did not have any parameter or was not set. Default: empty String

[repeat index]: Index of the option to retrieve, if the option was repeated multiple times (default: 0 = first option).

[parameter index]: Index of the option parameter to retrieve, starting at 0 (default: return all option parameters, separated by `b_args_getOptionParamSeparator`).

returns: The option parameter, if the option was set. The fallback is returned and a zero exit code is set, if the option was set, but an *empty* (existing!) parameter was provided. A nonzero exit code indicates that the option was not set (the fallback is still returned).

b_args_getOptionInt [option] [fallback] [repeat index] [parameter index]

args/b_args_getOptionInt

Convenience wrapper for `b_args_getOption` that also checks the type of the option to be an integer.

returns: See `b_args_getOption`. Also sets a nonzero exit code, if the option is not an integer.

b_args_getOptionCount

args/b_args_getOptionCount

Get the number of options that were set.

returns: Number of options (incl. repeated options).

arr

Collection of array related functions.

Copyright (C) 2018 David Hobach LGPLv3
0.2

Dependencies

printf

Functions

b_arr_getDeps

arr/b_arr_getDeps

Get the dependencies of this module.

returns: newline-separated list of dependencies of this module

b_arr_join [delimiter] [array]

arr/b_arr_join

Join the given array; elements are separated with the given delimiter. The array is not checked to exist.

[delimiter]: String to use as delimiter.

[array]: Expanded array to join, e.g. “\${arr[@]}”.

returns: Joined version of the array. The exit code is always zero.

b_arr_toList [array]

arr/b_arr_toList

Create a newline-separated list from the given array.

[array]: Expanded array to join, e.g. “\${arr[@]}”.

returns: List version of the array. The exit code is always zero.

b_arr_contains [element] [array]

arr/b_arr_contains

Check whether an array contains an element.

[element]: element to check for its existence in the array

[array]: expanded array to check, e.g. “\${arr[@]}”

returns: an exit code of 0, if the element was found and 1 otherwise

b_arr_mapsAreEqual [map spec 1] [map spec 2]

arr/b_arr_mapsAreEqual

Check whether the two given maps/associative arrays are equal.

[map spec 1]: First map specification to check. Since maps cannot be passed directly to functions in Bash 4.2, you’ll have to use “\$(declare -p "yourmap")” instead.

[map spec 1]: Second map specification to check.

returns: an exit code of 0, if the maps are equal and 1 otherwise; B_E is only triggered on programming errors

@B_E

cdoc

Generate code documentation in many formats (e.g. html, pdf, manpage, ...) from code comments.

Lines applicable for the documentation in your code are assumed to match static (configurable) regular expressions. These lines are then fed to pandoc in order to generate a single html page (or pdf, manpage, ...) as documentation. If no conversion is required (input format = desired output format), pandoc is bypassed.

It should be possible to use this way of generating code documentation with most programming languages (incl. bash). The defaults however are set for bash and the blib way of documenting its code, i.e. you'll have to use the getters and setters of this module if you want something different. For instance the default is to check for lines starting with `#+` (a special bash comment line) and add everything afterwards to the output documentation.

Various callback functions can be used to add content to the output of `b_cdoc__generate`. See the documentation of that function for details.

Copyright (C) 2018 David Hobach LGPLv3
0.2

Dependencies

mv
rm
mktemp

Functions

b_cdoc__getDeps

cdoc/b_cdoc__getDeps

Get the dependencies of this module.

returns: newline-separated list of dependencies of this module

b_cdoc__setExtractionRegex [regex]

cdoc/b_cdoc__setExtractionRegex

Set the regular expression used to check for matching lines in code files. The first match (`${BASH_REMATCH[1]}`) is added to the documentation output.

returns: nothing

@StateChanging

b_cdoc__getExtractionRegex

cdoc/b_cdoc__getExtractionRegex

See the setter.

returns: The property that was set.

b_cdoc__setFileFilterCallback [callback function name]

cdoc/b_cdoc__setFileFilterCallback

Set the function to call by `b_cdoc__generate` exactly once right after it computed the list of applicable source code files.

The callback function should be declared as follows:

```
callback_function_name [file list]
[file list]: newline-separated list of files (no directories!)
              that b_cdoc__generate computed for document generation
              (in that order)
returns:      the newline-separated list to use by b_cdoc__generate for
              document generation (default: the input); a non-zero exit
              code will abort further processing
```

returns: nothing

@StateChanging

b_cdoc__getFileFilterCallback

cdoc/b_cdoc__getFileFilterCallback

See the setter.

returns: The property that was set.

b_cdoc__setDocumentBeginCallback [callback function name]

cdoc/b_cdoc__setDocumentBeginCallback

Set the function to call by `b_cdoc__generate` exactly once right before it starts generating the output document.

The callback function should be declared as follows:

```
callback_function_name [document output file] [document output format]
[document output file]: path to the document output file
                        (may not exist and should not be written to)
[document output format]: chosen output format
returns: whatever should be added at the beginning of the output document;
        a non-zero exit code will abort further processing
```


@StateChanging

See the setter.

returns: nothing

@StateChanging

See the setter.

[document output file]: path to the document output file

(may not exist and should not be written to)
[document output format]: chosen output format
returns: whatever should be added to the end of the output
document; a non-zero exit code will abort further processing

returns: nothing

@StateChanging

b_cdoc_getDocumentEndCallback

cdoc/b_cdoc_getDocumentEndCallback

See the setter.

returns: The property that was set.

b_cdoc_setSpaceCallback [callback function name]

cdoc/b_cdoc_setSpaceCallback

Set the function to call by b_cdoc_generate each time it hits “space” (non-matching lines) between two matching lines.

The callback function should be declared as follows:

callback_function_name [matching line] [input file] [previous space count] [document output
[matching line]: The first matching line before which no match was found.
[input file]: The original input file.
[previous space count]: The number of times this function was previously
called for the currently processed file.
[document output format]: chosen output format
returns: whatever should be added in front of the matching line;
a non-zero exit code will abort further processing

returns: nothing

@StateChanging

b_cdoc_getSpaceCallback

cdoc/b_cdoc_getSpaceCallback

See the setter.

returns: The property that was set.

**b_cdoc_generate [input files] [output file] [output format] [additional
pandoc options]**

cdoc/b_cdoc_generate

Generate a documentation file from the given list of input files or directories.

pseudo code description for the document generation:

1. call the file filter callback to obtain the final list of input source code files to use for document generation, respect the order (default: use all files passed as input)
2. call the document begin callback function with the output file path to get user-specific output (default: do nothing)
3. for all input files:
 - i. for all lines of a file:
 - a) store lines matching `b_cdoc_getExtractionRegex` in a variable *o*
 - b) between any two matching lines for `b_cdoc_getExtractionRegex` that had a non-matching line in between them: call the space callback function (default: add an empty line to the output)
 - ii. pass *o* and the file name to the post processing callback function (default: return the input) - users could add e.g. the file name as section header here
 - iii. add the output of the post processing function to the output document
4. call the document end callback function with the output file path to get user-specific output (default: do nothing)
5. do all necessary output conversions using pandoc

[input files]: Newline-separated list of files or directories to generate the documentation from. The given order is respected; directories are recursively searched for files. It is currently assumed that these files are encoded in UTF-8.

[output file]: Path to the documentation file to generate. Should not exist.

[output format]: The target format of the documentation to generate. See pandoc for a list of available output formats. If none is specified, pandoc is bypassed and the input format is chosen as output format. Passing “pandoc” will let pandoc decide based on the extension of the output file.

[additional pandoc options]: All remaining parameters will be directly passed to pandoc. If none are provided, `-s` is implicitly added as default.

returns: Sets a non-zero exit code and exits the script on errors. output from pandoc and other calls may be printed. Otherwise nothing is returned.

@B_E

b_cdoc_generateBlibStyle [input files] [output file base path] [output format] [delete existing]

cdoc/b_cdoc_generateBlibStyle

A convenience wrapper for `b_cdoc_generate` which sets various reasonable parameters depending on the output format.

[input files]: see `b_cdoc_generate`

[output file base path]: path to a directory and base file name where to store the generated output documentation file; the final file name may differ as it is chosen by this function

[output format]: currently one of raw|html|pdf|man is supported (default: raw)

[delete existing]: whether or not to delete previously created output files (default: true/0); if set to false (1), the function will error out if a previously created file was found

returns: full path to the created documentation file on success; otherwise the function may error out

@B_E

Callback Functions

b_cdoc_cbPrintNewline

cdoc/b_cdoc_cbPrintNewline

Prints a newline character.

returns: nothing

b_cdoc_cbPrintFirstParam [param]

cdoc/b_cdoc_cbPrintFirstParam

Prints the first parameter.

[param]: The parameter to print.

returns: the first parameter

daemon

Module providing access to a single background process providing some service (daemon). Exiting the foreground control process will *not* terminate the background process. Attempting to start multiple background daemons will be prevented in a thread-safe way.

Each background process is assumed to implement a **daemon_main** function and must be identified by a unique String.

If you need to exchange data with the background service, please have a look at the multithreading/ipcv or multithreading/ipcm modules.

Known Issue:

Since the daemon cannot detach from its session via **setsid** in bash, the daemon will remain in the process group of its parent. So killing the parent with e.g. Ctrl-C will cause the parent group including the daemon to terminate. As a workaround, users may either ignore SIGINT requests or make sure the parent exits as soon as possible (recommended).

Copyright (C) 2019 David Hobach LGPLv3
0.4

Dependencies

kill
umask
mkdir
rm
mktemp

Imports

multithreading/mtx
proc

Global Variables

B_DAEMON_ID

daemon/B_DAEMON_ID

Contains the ID of the daemon, if and only if the current process is the daemon process.

Functions

b_daemon_getDeps

daemon/b_daemon_getDeps

Get the dependencies of this module.

returns: newline-separated list of dependencies of this module

b_daemon_init [quiet flag] [main name] [stdout file] [stderr file]
[umask setting]

daemon/b_daemon_init

Init the module paramters. It is necessary to call this method *before* using any other of this module unless you want to use the default paramters.

[quiet flag]: If set to 0 (default), don't print anything to stdout during the execution of start|stop|restart|status. Otherwise use b_info to print informational messages.

[main name]: Name of the main loop function to execute in the background process. Returning from that function will exit the background process. Default: **daemon_main**

[stdout file]: Where the background process should write its stdout stream to (default: /dev/null). Lines are appended.

[stderr file]: Where the background process should write its stderr stream to (default: /dev/null). Lines are appended.

[umask settings]: The umask settings to apply to the daemon (default: 0).

returns: Nothing.

@StateChanging

b_daemon_start [id] [arg 1] ... [arg n]

daemon/b_daemon_start

Start the background process.

If you need to start it as a different user, simply run this function as a different user with e.g. (b_execFuncAs)[#b_execFuncAs]. Please keep in mind that control processes must have the permission to send signals to the daemon PID though.

[id]: Unique identifying String of the daemon to distinguish it from others.

[arg i]: An arbitrary number of arguments which can be passed to the main loop.

returns: Sets a zero exit code on success. Otherwise sets a non-zero exit code. In particular B_E is called, if the daemon is already running.

@B_E

b_daemon_stop [id] [termination signal] [kill timeout]

daemon/b_daemon_stop

Stop the background process.

[id]: Unique identifying String of the daemon to distinguish it from others.

[termination signal]: A number specifying the signal to send to the daemon (default: 15 / SIGTERM). See `kill -l` for an overview.

[kill timeout]: Time in seconds after which the background process will be killed, if it remains unresponsive to the termination signal (default: 0 = wait indefinitely).

returns: Sets a zero exit code, if the daemon terminated by itself. An exit code of 2 indicates that the daemon had to be killed. An exit code of 3 means that it wasn't running. B_E is called on unexpected errors.

@B_E

b_daemon_restart [id] [termination signal] [kill timeout] [arg 1] ...
[arg n]

daemon/b_daemon_restart

Restart the background process.

[id]: Unique identifying String of the daemon to distinguish it from others.

[termination signal]: See b_daemon_stop.

[kill timeout]: See b_daemon_stop.

[arg i]: An arbitrary number of arguments which can be passed to the main loop.

returns: See b_daemon_start.

@B_E

b_daemon_statusPid [id]

daemon/b_daemon_statusPid

Check the status of the background process.

Doesn't print informational messages to stdout.

[id]: Unique identifying String of the daemon to distinguish it from others.

returns: The PID and sets a zero exit code, if the daemon is running and a non-zero exit code otherwise. B_E is only called on exceptional errors.

@B_E

b_daemon_status [id]

daemon/b_daemon_status

Check the status of the background process and print informational messages to stdout (if configured).

[id]: Unique identifying String of the daemon to distinguish it from others.

returns: Sets a zero exit code, if the daemon is running and a non-zero exit code otherwise. B_E is only called on exceptional errors.

@B_E

b_daemon_getPid [id]

daemon/b_daemon_getPid

Get the process ID of the background process.

[id]: Unique identifying String of the daemon to distinguish it from others.

returns: The process ID and sets a zero exit code, if it could be obtained. Please note that the process may be dead anyway (use `b_daemon_statusPid` for that). Otherwise a non-zero exit code is set. `B_E` is only called on exceptional errors.

@B_E

date

Collection of date and time related functions.

Copyright (C) 2018 David Hobach LGPLv3
0.3

Dependencies

date

Functions

`b_date_getDeps`

date/b_date_getDeps

Get the dependencies of this module.

returns: newline-separated list of dependencies of this module

`b_date_add [date] [time] [unit] [format] [utc flag]`

date/b_date_add

Add the given number of seconds to the given date.

[date]: date to add seconds to; the format must be understood by the Unix date utility

[time]: amount of time to add

[unit]: unit of the time to add, may be one of d (days), h (hours) m (minutes), s (seconds, default)

[format]: output format of the date, in Unix date notation (default: use the localized output)

[utc flag]: if set to 0, use UTC as time zone if not specified for the input *and* use it for the output (default: 1 = local time zone)

returns: The input date with the given number of seconds added, in the requested format; returns a non-zero exit code on errors.

@B_E

b_date_addDays [date] [days] [format] [utc flag]

date/b_date_addDays

Convenience wrapper to b_date_add with days.

[days]: number of days to add

b_date_diff [date 1] [date 2] [unit]

date/b_date_diff

Get the amount of time between the two dates, i.e. [date 2] - [date 1].

[date 2], [date 1]: the two dates to subtract; the time part is assumed to be identical if not specified within the dates

[unit]: unit of the result, may be one of d (days), h (hours) m (minutes), s (seconds, default)

returns: The amount of time between the given two dates [date 2] - [date 1], rounded down. Returns a non-zero exit code on errors.

@B_E

b_date_getFileModAge [file] [unit]

date/b_date_getFileModAge

Get the time that passed since the last modification of the file.

[file]: Full path to the file to check.

[unit]: unit of the time to retrieve, may be one of d (days), h (hours) m (minutes), s (seconds, default)

returns: The amount of time in the given unit since the last modification. May be rounded down. Sets a non-zero exit code on errors.

@B_E

delay

Simplistic module to delay commands to a future time.

Requires polling.

All timestamps in this module must be integers and a larger timestamp must denote a time *after* a smaller timestamp.

Copyright (C) 2019 David Hobach LGPLv3

0.3

Dependencies

no dependencies

B_DELAY_EXECUTED

delay/B_DELAY_EXECUTED

The number of commands executed during the last invocation of `b_delay_execute`.

Functions

b_delay_getDeps

delay/b_delay_getDeps

Get the dependencies of this module.

returns: newline-separated list of dependencies of this module

b_delay_to [timestamp] [command]

delay/b_delay_to

Delay the given command to be executed at the given time.

[timestamp]: An integer timestamp (e.g. `$SECONDS`, Unix timestamp in s/ms/ns, ...).

[command]: The command to execute at the given time.

returns: Nothing.

@StateChanging

b_delay_execute [timestamp]

delay/b_delay_execute

Execute all commands which are due at the given time.

[timestamp]: Integer timestamp representing the current point in time.

returns: Nothing. The exit code is equal to the number of commands with a non-zero exit code. `B_DELAY_EXECUTED` is updated with the number of commands executed.

@StateChanging

b__delay__getCommandAt [timestamp]

delay/b__delay__getCommandAt

Get the set of commands to be executed at the given point in time.

[timestamp]: Integer timestamp denoting the time for which to retrieve the commands.

returns: The commands to execute at that time.

dmcrypt

Abstraction layer for cryptsetup / dm-crypt.

Features:

- automatic management of dm-crypt devices
- password support for non-tty environments

Copyright (C) 2020 David Hobach LGPLv3
0.6

Dependencies

dirname
mkdir
head
md5sum
readlink

Imports

ui

Functions

b__dmcrypt__getDeps

dmcrypt/b__dmcrypt__getDeps

Get the dependencies of this module.

returns: newline-separated list of dependencies of this module

b__dmcrypt__init [ui mode]

dmcrypt/b__dmcrypt__init

Initialize this module. This function *must* be called at least once before using any of the other functions.

[ui mode]: How to request a password from the user: auto|gui|tty (default: auto).

returns: Nothing.

@StateChanging

@B_E

b_dmccrypt_getMapperName [path]

dmccrypt/b_dmccrypt_getMapperName

Get the name of the dm-crypt mapper for a given path.

[path]: Full path to an encrypted file.

returns: A mapper name. This doesn't necessarily mean that the encrypted container is open. Use `b_dmccrypt_isOpen` for that.

@B_E

b_dmccrypt_createLuks [path] [size] [fs type] [entropy source] [password prompt] [dm-crypt option 1] ... [dm-crypt option n]

dmccrypt/b_dmccrypt_createLuks

Create an encrypted luks container file at the given location.

This function may request a password from the user and usually requires root access rights.

[path]: Full path to the encrypted file to create.

[size]: Filesystem size in bytes to create. Supported suffixes: b 512, kB 1000, K 1024, MB 10001000, M 10241024, GB 100010001000, G 102410241024

[fs type]: Filesystem to create inside the encrypted container. If none is specified (default), no file system is created.

[entropy source]: Source of entropy to use for the file setup (default: /dev/urandom).

[password prompt]: Prompt string to ask the user for his password (optional).

[dm-crypt option i]: These options are directly passed to `cryptsetup`.

returns: Sets a zero exit code on success and errors out with `B_E` otherwise.

@B_E

b_dmccrypt_open [path] [mount point] [output var] [password prompt] [dm-crypt option 1] ... [dm-crypt option n]

dmccrypt/b_dmccrypt_open

Open/Decrypt the given container and optionally mount it.

[path]: Full path to the encrypted file.

[mount point]: Where to mount the decrypted data (optional). If no mount point is specified, it will not be mounted.

[output var]: The name of the variable to write the created device to (optional).

[password prompt]: Prompt string to ask the user for his password (optional).

[dm-crypt option i]: These options are directly passed to **cryptsetup**.

returns: Sets a zero exit code on success.

@B_E

b_dmccrypt_close [path] [dm-crypt option 1] ... [dm-crypt option n]

dmccrypt/b_dmccrypt_close

Close the given encrypted container.

[path]: Full path to the encrypted file.

[dm-crypt option i]: These options are directly passed to **cryptsetup**.

returns: A zero exit code on success. The exit code may also be zero for non-existing or already closed containers.

@B_E

b_dmccrypt_isOpen [path]

dmccrypt/b_dmccrypt_isOpen

Check whether the given encrypted container is open (not necessarily mounted).

[path]: Full path to the encrypted file.

returns: Sets a zero exit code, if and only if the container is open. B_E is only called for exceptional errors.

@B_E

flog

Flexible log writer for bash supporting arbitrary piped output (files, network streams, stdout, stderr, ...) in a user-defined output format.

Log files can be automatically reduced to their last X lines.

In order to log to the system log, please use the **logger** command instead. This library is mostly meant for application logs handled in a more custom manner.

Currently only a single writer per instance of this library/thread is kept in memory, but you can user multiple one after another or in multiple threads. Each writer should have a dedicated log file to write to.

Exact format of log entries:

```
[header] [message]
[header]: Can be arbitrarily defined in the
          respective callback function. If nothing
          is defined, the below default header
          is used:
[default header] = '[default date] '
[default date]: current date in the format as used
                 by date +"%F %T %Z" (the format can be changed)
```

Copyright (C) 2018 David Hobach LGPLv3
0.3

Dependencies

date
tail
cat
mktemp

Imports

fs

Global Variables

B_FLOG_SEV

flog/B_FLOG_SEV

Global map for human readable severities which may be used by users of this script.

It was inspired by the severities of RFC5424.

Currently supported values: emergency|alert|critical|crit|error|err|warning|warn|notice|informational|info|debug

Functions

b_flog_printSeverity [severity]

flog/b_flog_printSeverity

[severity]: see b_flog_init

Print the given severity in a way for logging. This function is meant to be used as building block for header functions.

returns: a printed version of the given severity for logging

b__flog__close

flog/b__flog__close

close the currently open log; is automatically called, but users may want to call it themselves to force the respective file descriptor to be closed before the program is ended

returns: nothing

@StateChanging

b__flog__init [log file name] [header callback function] [log reduction lines]

flog/b__flog__init

Initialize this log writer. This function **must** be called before any others.

[log file name]: name of the log file to write to; special files such as /dev/stdout, /dev/stderr (default), /dev/tcp, /dev/udp are supported if your bash version supports them; the file doesn't need to exist, but directories above it must exist

[header callback function]: optional name of the function to be called whenever a new log entry is generated; the function must be defined as follows:

[header callback function] [severity]

[severity]: see [b__flog__log](#b__flog__log)

returns: the full header meant to be used for the current moment in time with the given severity (without knowing the message details) and sets a non-zero exit code on errors; errors may cause the message to be logged without header

[log reduction lines]: if set to a positive integer, reduce the log file approximately to that number of lines during logging (default: 3000) - see b__flog__setLogReductionLinesApprox for details; this option has no effect on non-file outputs (stdout, network output, ...)

returns: sets a non-zero exit code on errors and may exit the script

@StateChanging

@B__E

b__flog__log [message] [severity]

flog/b__flog__log

Log the given message with the given optional severity.

[message]: message to log

[severity]: users may pass arbitrary numbers or even Strings here, but it is recommended to stick to the priorities defined in `$BLIB_FLOG_SEV` (default: `#{B_FLOG_SEV["info"]}`)

returns: sets a non-zero exit code on errors and may exit the script

@B_E

b_flogErrorHandler [error out] [print stderr] [print stack trace] [print log errors] [log stack trace] [severity]

flog/b_flogErrorHandler

An alternative to `b_defaultErrorHandler` which will log program errors using `flog`.

[error out]: see `b_defaultErrorHandler` (default: 0)

[print stderr]: see `b_defaultErrorHandler` (default: 1 / log only)

[print stack trace]: see `b_defaultErrorHandler` (default: 1 / log only)

[print log errors]: whether or not to print errors related to the logging itself to `stderr` (default: 0 / print)

[log stack trace]: whether or not to log the stack trace (default: 1 / do not log it)

[severity]: the severity to use for all errors, defaults to `#{B_FLOG_SEV["critical"]}`

returns: see `b_defaultErrorHandler`

b_flog_getDeps

flog/b_flog_getDeps

Get the dependencies of this module.

returns: newline-separated list of dependencies of this module

b_flog_getDateFormat

flog/b_flog_getDateFormat

Get the date format used for the header by this log writer (see “man date” for explanations).

returns: see above

b_flog_setDateFormat [format string]

flog/b_flog_setDateFormat

Set the date format used for the header by this log writer (see “man date” for explanations).

returns: nothing

@StateChanging

b_flog_getLogReductionLinesLowerBound

flog/b_flog_getLogReductionLinesLowerBound

Get the number of lines that the log file will at least have after a log file reduction.

returns: see above

b_flog_getLogReductionLinesUpperBound

flog/b_flog_getLogReductionLinesUpperBound

Get the maximum number of lines that the log file will have before it is reduced.

returns: see above

b_flog_setLogReductionLinesLowerBound [bound]

flog/b_flog_setLogReductionLinesLowerBound

Set the number of lines that the log file will at least have after a log file reduction.

[bound]: number of lines to use for that bound

returns: nothing

@StateChanging

b_flog_setLogReductionLinesUpperBound

flog/b_flog_setLogReductionLinesUpperBound

Set the maximum number of lines that the log file will have before it is reduced.

[bound]: number of lines to use for that bound

returns: nothing

@StateChanging

b_flog_setLogReductionLinesApprox [line count]

flog/b_flog_setLogReductionLinesApprox

Set the number of average number of lines that the log file should have; counts ≤ 0 indicate no limit.

[line count]: reduce the log after reaching $1.2 \times [\text{line count}]$ lines to $0.8 \times [\text{line count}]$ lines

returns: nothing

@StateChanging

b_flog_getHeaderFunction

flog/b_flog_getHeaderFunction

Get the name of the header callback function that is used.

returns: see above

b_flog_setHeaderFunction [header function]

flog/b_flog_setHeaderFunction

Set the name of the header callback function to be used.

[header function]: name of the header function to use

returns: nothing

@StateChanging

Header Functions

b_flog_defaultHeader [severity]

flog/b_flog_defaultHeader

Default header callback function used with **b_flog_init**.

[severity]: the default header ignores the severity

returns: the default header meant to be used for the current moment in time

b_flog_headerDateSeverity [severity]

flog/b_flog_headerDateSeverity

An alternative to the default header callback function which appends the severity to the default header.

[severity]: see **b_flog_init**

returns: the default header with the severity appended

b_flog_headerDateScriptSeverity [severity]

flog/b_flog_headerDateScriptSeverity

An alternative to the default header callback function which appends the calling script and the severity to the default header.

[severity]: see **b_flog_init**

returns: the default header with the calling script and severity appended

fs

Collection of file and file system related functions.

Copyright (C) 2018 David Hobach LGPLv3
0.3

Dependencies

wc
findmnt
mktemp
mount
head
stat
rm
sync

Functions

b_fs_getDeps

fs/b_fs_getDeps

Get the dependencies of this module.

returns: newline-separated list of dependencies of this module

b_fs_isEmptyDir [dir]

fs/b_fs_isEmptyDir

Check whether the given directory is empty or non-existing. It is not checked whether the passed parameter is a file preventing a directory from being created.

[dir]: full path to the directory to check

returns: a zero exit code if the directory does not exist or is empty

b_fs_getLineCount [file]

fs/b_fs_getLineCount

Get the number of lines of the given file.

[file]: full path to a file

returns: the number of lines; a non-zero exit code is set on errors

@B_E

b_fs_waitForFile [file] [maximum time]

fs/b_fs_waitForFile

Sleep until the given file appears. The check interval is 1s.

[file]: full path to the file or directory to wait for

[maximum time]: maximum time in s to wait for the file to appear (default: forever)

returns: Sets a zero exit code if the file appeared and a non-zero exit code on a timeout.

b_fs_getMountpoints [device]

fs/b_fs_getMountpoints

Get all mountpoints for the given device.

[device]: Full path to the device (incl. /dev/) for which to obtain the mountpoints.

returns: A newline-separated list of mountpoints where the given device is mounted to. Sets a non-zero exit code if no such mountpoints were found.

b_fs_mountIfNecessary [device] [mount point] [enforce]

fs/b_fs_mountIfNecessary

Mount the given device if it isn't already mounted.

[device]: Full path to the device (incl. /dev/) to mount.

[mount point]: Full path where to mount the device. If no mount point is specified, a /tmp/ mount point is chosen. Non-existing directories are created. Is ignored if another mount point already exists.

[enforce]: If set to 0, enforce the given mount point to be used in addition to potentially existing ones (default: 1).

returns: The chosen mount point or a newline-separated list of existing mount points on success; sets a non-zero exit code on failure.

@B_E

b_fs_createLoopDeviceIfNecessary [file]

fs/b_fs_createLoopDeviceIfNecessary

Create a loop device for the given file if no old one exists. Usually requires root access rights.

[file]: File for which to create a loop device.

returns: Created loop device or previously used one (incl. /dev/). Sets a non-zero exit code, if no device could be created.

@B_E

b_fs_removeUnusedLoopDevice [device|file]

fs/b_fs_removeUnusedLoopDevice

Remove a loop device, if and only if it is unused by the operating system. Otherwise mark it for removal once it becomes unused. Usually requires root access rights.

[device|file]: Full path (incl. /dev/) to the loop device or to the backing file.

returns: Sets a zero exit code, if the loop device was not used and could thus be successfully removed *or* does not exist. A nonzero exit code indicates that the device is still being used. B_E is called on other errors.

@B_E

b_fs_parseSize [string] [check flag]

fs/b_fs_parseSize

Parse human-readable file system sizes that include units.

[string]: A string denoting a file system size of the format [number][unit]. Unit may be one of KB 1000, K 1024, MB 10001000, M 10241024, GB 100010001000, G 102410241024, and so on for T, P. If no unit is provided, the number is assumed to denote bytes. The number must be an integer.

[check flag]: Check whether the result makes sense (default: 0/true). This check will make integer overflows less likely.

returns: The respective number of bytes meant with the given string. B_E is called on parsing errors.

@B_E

b_fs_removeWithOverwrite [file] [randomness source]

fs/b_fs_removeWithOverwrite

Overwrite the given file with random data, then remove it. This is meant to prevent a potential reconstruction of the file after its removal.

Warning: The reconstruction may still work on some types of file systems or physical storage systems (e.g. on flash disks).

[file]: Full path to the file to remove. Directories are currently not supported.

[randomness source]: Device to use as source of random data (default: /dev/urandom).

returns: Nothing. B_E is called on errors.

@B_E

http

Collection of http related functions.

Copyright (C) 2018 David Hobach LGPLv3
0.2

Dependencies

curl

Global Variables

B_HTTP_CHECKURLS

http/B_HTTP_CHECKURLS

Each call to b_http_getOnlineStatus causes one of the URLs in this array to be visited.

It is recommended to pick a relatively large number of URLs with SSL support to remain relatively anonymous, if b_http_getOnlineStatus is called multiple times.

Defaults to the European/US Alexa Top 10 (which hopefully blends in to the masses).

Functions

b_http_getDeps

http/b_http_getDeps

Get the dependencies of this module.

returns: newline-separated list of dependencies of this module

b_http_rawUrlEncode [string]

http/b_http_rawUrlEncode

Encode the given string according to RFC 3986.

[string]: to encode

returns: Returns a string in which all non-alphanumeric characters except `-.~` have been replaced with a percent (%) sign followed by two hex digits. This is the encoding described in RFC 3986 for protecting literal characters from being interpreted as special URL delimiters, and for protecting URLs from being

mangled by transmission media with character conversions (like some email systems). A non-zero exit code is set on errors.

@B_E

b_http_rawUrlDecode [string]

http/b_http_rawUrlDecode

Decode the given string encoded with `b_str_rawUrlEncode` or an equivalent function.

[string]: to decode

returns: The literal string with all hex characters replaced; a non-zero exit code is set on errors.

b_http_getOnlineStatus [timeout]

http/b_http_getOnlineStatus

Find out whether we are online or not by attempting an http connection. One of `B_HTTP_CHECKURLS` is possibly visited during the process.

[timeout]: Timeout in seconds for hanging checks (default: 5).

returns: 0, if we're online, 1 if only DNS works, 2 if neither DNS nor http(s) worked, 3 if the check timed out; `B_E` will be called if the status cannot be determined.

@B_E

ini

Stateful ini reader for bash.

Currently only a single file per instance of this library/thread is kept in memory, but you can read multiple files one after another or in multiple threads.

Implementation Specifics:

- names/keys & values are case sensitive
- comment lines may start with `;` or `#`
- whitespace lines are ignored
- duplicate names may result in undefined behaviour (usually the second will override the first)
- all characters following the `=` are considered part of the value (incl. whitespace); whitespace before and after the value may be trimmed by the getters though (check their description)
- values are not interpreted (e.g. quotes, escape characters, ...)
- whitespace around keys and around section qualifiers is ignored

Copyright (C) 2018 David Hobach LGPLv3
0.5

Dependencies

no dependencies

Functions

b__ini_getDeps

ini/b__ini_getDeps

Get the dependencies of this module.

returns: newline-separated list of dependencies of this module

b__ini_read [ini file]

ini/b__ini_read

read the given ini file and keep it in thread-local memory so that subsequent calls to the b__ini_get functions will return the values from the ini file; subsequent calls to this function will update the internal state to represent the file last read in this thread

[ini file]: path to the ini file to read

returns: an error message on errors and sets a non-zero exit code on errors

@StateChanging

@B__E

b__ini_get [name] [section]

ini/b__ini_get

get the value for the ini entry with the given name as String in raw format

[name]: name/key of the ini entry to retrieve

[section]: section where to look for the entry with the given name (default: without section)

returns: value of the ini entry matching exactly the given section and name incl. any whitespace; a non-zero exit code is set if such an entry wasn't found

b__ini_getString [name] [section]

ini/b__ini_getString

get the value for the ini entry with the given name as String and remove all whitespace around the returned String

[name]: name/key of the ini entry to retrieve

[section]: section where to look for the entry with the given name (default: without section)

returns: value of the ini entry matching exactly the given section and name excl. any whitespace around; a non-zero exit code is set if such an entry wasn't found

b_ini_getInt [name] [section]

ini/b_ini_getInt

get the value for the ini entry with the given name as integer

[name]: see b_ini_get

[section]: see b_ini_get

returns: see b_ini_get; additionally it is checked whether the return value is an integer (if not, a non-zero exit code of 2 is set and the return value is undefined)

b_ini_getBool [name] [section]

ini/b_ini_getBool

get the value for the ini entry with the given name as boolean

[name]: see b_ini_get

[section]: see b_ini_get

returns: see b_ini_get; 0 is returned via echo for true, 1 for false; the exit code indicates a potential error during parsing (2) or a missing entry (1) and *not* true/false

b_ini_assertNames [section 1] [name 1] ... [name n] – [section 2]
[name 1] ... [name m]

ini/b_ini_assertNames

Assert that the given sections contains *at most* the given names and no additional ones.

This is a useful function to detect user mistakes and should be called right after b_ini_read.

Multiple sections can be separated with “–”.

[section]: see b_ini_get

[name]: see b_ini_get

returns: Sets a zero exit code if and only if the last read ini file doesn't contain any additional names. Otherwise B_E is triggered. B_ERR will list the invalid names.

@B_E

keys

Simple *system-wide* cryptographic key store protected by a master password.

A key store is only opened when necessary. It'll remain open from then on until an application calls `b_keys_close`.

It can be found at `/etc/blib/keys/keys.lks`.

Usually requires root access rights.

Features:

- thread safe: no write operation can happen to a closed key store (`b_keys_close` and write operations are single threaded only)
- retrieved keys are read-only unless managed via this interface

Copyright (C) 2020 David Hobach LGPLv3
0.5

Dependencies

mkdir
cat
readlink
cp
rm
findmnt

Imports

fs
dmccrypt
multithreading/mtx

Functions

b_keys_getDeps

keys/b_keys_getDeps

Get the dependencies of this module.

returns: newline-separated list of dependencies of this module

b_keys_init [app id] [auto create] [ui mode] [password prompt] [wait time]

keys/b_keys_init

Initialize this module. This function *must* be called at least once before any other function except `b_keys_create` can be used.

Will open the key store, if it's closed.

[app id]: Unique application ID (recommended: `$B_SCRIPT_NAME`).

[auto create]: Automatically create a new key store, if none exists (default: 0 = do it). Users may create their own key store using `cryptsetup` otherwise.

[ui mode]: How to request the master password from the user: `auto|gui|tty` (default: `auto`).

[password prompt]: Prompt string to ask the user for his password (optional).

[wait time]: Maximum time in ms to wait for another process writing to a key (default: 300) (-1 = indefinitely).

returns: Sets a zero exit code on success and errors out with `B_E` otherwise.

@StateChanging

@B_E

@B_E

b_keys_add [key id] [key path] [keep flag]

keys/b_keys_add

Add the given key to the key store.

[key id]: Unique identifier for the key to add.

[key path]: Full path to the key to add.

[keep flag]: Keep the [key path] file after a successful copy operation (default: 0 / keep). If set to 1, it is safely removed from disk.

returns: Sets a zero exit code on success and errors out with `B_E` otherwise.

@B_E

b_keys_get [key id]

keys/b_keys_get

Retrieve the given key from the store. If you need the content as String, please use `b_keys_getContent`.

[key id]: Unique identifier for the key to retrieve.

returns: Path to the key. It may not exist, if the key store was closed in the meantime or the provided ID does not exist.

@B_E

b__keys__getContent [key id]

keys/b__keys__getContent

Retrieve the given key content from the store. For binary keys please use `b__keys__get`.

[key id]: Unique identifier for the key to retrieve.

returns: The key content as String. If it doesn't exist or other errors occurred, `B_E` is called.

@B_E

b__keys__delete [key id] [backup]

keys/b__keys__delete

Delete the given key from the key store.

[key id]: Unique identifier for the key to delete.

[backup]: Whether (0) or not (1) to create a backup (default: 0).

returns: Sets a zero exit code on success and errors out with `B_E` otherwise.

@B_E

b__keys__close

keys/b__keys__close

Close the key store, if necessary.

returns: Sets a zero exit code on success (closed key store) and errors out with `B_E` otherwise.

@B_E

multithreading/ipcm

An inter-process map implementation.

The map is available to all running processes during a single boot session.

Both reading and writing to the map can be done from any number of processes.

Overall Features	
# readers	multiple
# writers	multiple
read consistency	always
write consistency	always
blocking	on writes

Copyright (C) 2019 David Hobach LGPLv3
0.2

Dependencies

no dependencies

Imports

multithreading/ipcv

multithreading/mtx

Functions

b_ipcm_getDeps

multithreading/ipcm/b_ipcm_getDeps

Get the dependencies of this module.

returns: newline-separated list of dependencies of this module

b_ipcm_setNamespace [namespace]

multithreading/ipcm/b_ipcm_setNamespace

Set the common process namespace to use. All processes inside the same namespace share a common state.

It is recommended to call this function a single time before any other functions of this module. Otherwise the default namespace, which may include unrelated processes, is used.

[namespace]: Name of the namespace to set.

returns: Errors out, if the name is unacceptable.

@StateChanging

@B_E

b_ipcm_getNamespace

multithreading/ipcm/b_ipcm_getNamespace

Retrieve the currently used namespace.

returns: The currently used namespace.

b_ipcm_change [key] [change function] [maximum time]

multithreading/ipcm/b_ipcm_change

Change the given key/value combination inside the map in a thread-safe way. May wait for changes done by other processes.

[key]: A global unique identifier for the given value.

[change function]: Name of the function to execute the change of the value. It will be called with the current key as first parameter and the current value as second. It is expected to print the new value to set for this key. A non-zero exit code will cause b_ipcm_change to abort the change.

[maximum time]: maximum time in ms to wait for other processes to complete their operation (default: -1 = indefinitely)

returns: A zero exit code and prints the new value, if the change succeeded. An exit code of B_RC+1 indicates that the change function returned a non-zero exit code. B_E is called otherwise.

@B_E

b_ipcm_get [key] [fallback]

multithreading/ipcm/b_ipcm_get

Retrieve the data found at the given key.

[key]: A global unique identifier for the data to retrieve.

[fallback]: Data to return if nothing was found for the given key (default: empty).

returns: Sets a zero exit code and returns the data found on success. If no data was found, the fallback data is returned and a zero exit code is set. B_E is called on errors.

b_ipcm_unsetNamespace [namespace] [maximum time]

multithreading/ipcm/b_ipcm_unsetNamespace

Unsets the given namespace and all keys stored within it.

It is recommended to call this function when all processes finished their work.

[namespace]: The namespace to unset (default: the current namespace).

[maximum time]: maximum time in ms to wait for other processes to complete their operation (default: 0 = indefinitely)

returns: Sets a zero exit code only upon successful removal. Otherwise B_E is triggered.

@B_E

multithreading/ipcv

Provides means for inter-process communication (ipc) via global bash variables (v).

This implementation uses shared memory, i.e. it should be reasonably fast.

Only a single process or thread is assumed to be writing (i.e. use `b_ipcv_save`) a variable at a time and multiple processes may read it (using e.g. `b_ipcv_load`). If you need to write a single variable from multiple processes, please consider using the `multithreading/mtx` module or similar locking means in combination with this module (or just `multithreading/ipcm`).

Overall Features	
# readers	multiple
# writers	single
read consistency	always
write consistency	only for one writer
blocking	never

Copyright (C) 2018 David Hobach LGPLv3
0.3

Dependencies

findmnt
mkdir
mktemp
mv
rm

Functions

b_ipcv_getDeps

multithreading/ipcv/b_ipcv_getDeps

Get the dependencies of this module.

returns: newline-separated list of dependencies of this module

b_ipcv_save [namespace] [var name 1] .. [var name n]

multithreading/ipcv/b_ipcv_save

Save the current values of the given variables so that they are made available for other processes under the given namespace.

Please note that each variable is saved atomically, but individually. I.e. if you need multiple values to be updated at the same time, please use a single variable (e.g. a map).

[namespace]: Name for a common group under which the given variables should be saved. The combination of [namespace] and [variable name] must be a unique identifier across all processes running on the system.

[var name i]: The name of the global variable to make accessible for other processes. An arbitrary number of variable names can be specified.

returns: Nothing, but a non-zero exit code indicates failed variable save attempts. A failed save attempt also triggers B_E.

@B_E

b_ipcv_load [namespace] [var name 1] .. [var name n]

multithreading/ipcv/b_ipcv_load

Load the given variables from the given namespace into the current process context.

[namespace]: Name of the group under which the variable was saved with b_ipcv_save. Must exist.

[var name i]: Name of the variable to load. Multiple names can be specified.

returns: A non-zero exit code indicates the number of variables that could not be loaded unless some unexpected error occurred and B_E is triggered. Please note that a failed load attempt/unavailable variable does generally not trigger B_E.

@B_E

b_ipcv_loadNamespace [namespace] [check existence]

multithreading/ipcv/b_ipcv_loadNamespace

Load all variables that can be loaded for the given namespace into the current process context.

[namespace]: Name of the group for which to load all available variables.

[check existence]: Whether or not to make sure that the namespace to load exists (default: 0/check). Otherwise non-existing namespaces will not cause an error.

returns: Sets a zero exit code on success. Failing to load any single available variable will always trigger B_E.

@B_E

b_ipcv_unset [namespace] [var name 1] .. [var name n]

multithreading/ipcv/b_ipcv_unset

Unset/Remove the given variables from the global namespace.

Please note that the variables will remain set in your current process context, if they were set before. Use the standard bash **unset** for that.

[namespace]: Group where the given variables belong to.

[var name i]: Name of the variable to remove. Multiple may be specified.

returns: The number of variables which could not be unset. B_E is not triggered for these.

@B_E

b_ipcv_unsetNamespace [namespace]

multithreading/ipcv/b_ipcv_unsetNamespace

Remove the given global namespace and all variables it contains.

Please note that the variables will remain set in your current process context, if they were set before. Use the standard bash **unset** for that.

[namespace]: To remove.

returns: Sets a zero exit code only upon successful removal. Otherwise B_E is triggered.

@B_E

multithreading/mtx

Collection of mutex related functions.

Mutex: Only a single process may have it at any point in time.

Semaphore: A specific maximum number of processes may have it at any point in time.

See the keys module source code for an example on how to use this mutex implementation efficiently.

Copyright (C) 2018 David Hobach LGPLv3

0.3

Dependencies

mkdir

touch

sleep

rm

rmdir

cat
mktemp

Imports

proc

Functions

b_mtx_getDeps

multithreading/mtx/b_mtx_getDeps

Get the dependencies of this module.

returns: newline-separated list of dependencies of this module

b_mtx_setSleepTime [ms]

multithreading/mtx/b_mtx_setSleepTime

Sets the time to sleep for this module whenever active polling is done (default: 500).

[ms]: time in milliseconds between active polling requests for e.g. mutexes done by this module; must be an integer

returns: Nothing, always sets a zero exit code.

b_mtx_getSleepTime

multithreading/mtx/b_mtx_getSleepTime

Gets the time to sleep for this module whenever active polling is done.

returns: The currently set time to sleep in ms.

b_mtx_create [base dir]

multithreading/mtx/b_mtx_create

Allocate a new mutex without claiming it (use `b_mtx_try` for that).

[base dir]: Path to an *existing* directory where to store the mutex (default: not specified). By default this module will pick a temporary location. If you need a mutex that persists across reboots, please set a directory that persists across reboots here. The path should point to a local, non-network file system destination. The module must be able to create remove files or directories there at will.

returns: A string identifying the mutex (mutex ID). Sets a non-zero exit code on errors.

@B_E

b_mtx_release [mutex] [block ID]

multithreading/mtx/b_mtx_release

Release the given mutex so that it can be used by other block IDs/threads.

[mutex]: A mutex obtained via b_mtx_create.

[block ID]: The block ID for which to release the mutex (default: \$).

returns: Sets a non-zero exit code if the mutex could not be removed as another process is blocking it and a zero exit code on successful removal.

b_mtx_forceRelease [mutex]

multithreading/mtx/b_mtx_forceRelease

Release the given mutex so that it can be used by other blockIDs/threads.
Warning: This function can remove mutexes from other threads and should generally *only* be used for the removal of mutexes which are known to be stale by the calling application.

[mutex]: A mutex obtained via b_mtx_create.

returns: Nothing and sets a zero exit code.

b_mtx_pass [mutex] [block ID]

multithreading/mtx/b_mtx_pass

Pass a blocked mutex to another block ID (i.e. change the block ID of the given mutex).

You should only do this if you currently own the mutex and the new process is ready to take over.

[mutex]: A mutex obtained via b_mtx_create.

[block ID]: The block ID to set for the given mutex.

returns: Sets a zero exit code on success and a non-zero exit code otherwise.

@B_E

b_mtx_try [mutex] [block ID] [claim stale] [claim own]

multithreading/mtx/b_mtx_try

Attempt to obtain the given mutex. Return immediately even if it cannot be obtained.

[mutex]: A mutex obtained via `b_mtx_create`. You may also use a static and otherwise unused directory path as mutex and share it across all relevant processes.

[block ID]: The ID to use by which to block (default: running (sub)shell process id \$\$). This should be the process ID of the process attempting to obtain the mutex or you should know what you're doing. If you're in a subshell that should deploy a mutex against other subshells, store their `$BASHPID` and call the function with that.

[claim stale]: If set to 0, claim the mutex even if it is still blocked by some other process, but that process isn't running anymore. If set to 1 (default), the function returns without obtaining the mutex. In general this should only be used in situations where a mutex has a high probability of being stale (e.g. application start).

[claim own]: If set to 0 (default), claim the mutex if it appears to be blocked by the provided block ID. If set to 1, consider it blocked even then.

returns: The function incl. parameters to execute to remove the mutex if it was obtained and an error message stating the reason otherwise. The provided function *should* be called as part of an exit trap of the calling script or via `eval`. Sets an exit code of 0, if the mutex was obtained. An exit code of 1 is set, if the mutex was blocked and another non-zero exit code if some other error occurred (the mutex might be blocked even then).

Example code:

```
local mutex=""
local mutexRet=""
mutex="$(b_mtx_create)" || { B_ERR="Failed to create a mutex." ; B_E }
mutexRet="$(b_mtx_try "$mutex")" \
|| { B_ERR="Failed to obtain the mutex $mutex. Reason: $mutexRet" ; B_E }
#assuming the mutex is only meant to be removed after full
#execution of the script:
trap "$mutexRet" EXIT
#direct removal:
#b_mtx_release "$mutex"
```

b_mtx_waitFor [mutex] [block ID] [claim stale] [maximum time]

multithreading/mtx/b_mtx_waitFor

Wait for the given mutex to become available. This will block script execution.

[mutex]: see `b_mtx_try`

[block ID]: see `b_mtx_try`

[claim stale]: see `b_mtx_try`

[maximum time]: maximum time in ms to wait for the mutex to become available (default: -1 = indefinitely)

returns: see `b_mtx_try`

multithreading/multiw

Allow multiple processes to write to a *virtual* file at the same time without causing write inconsistencies (written data from each process mangled with each other).

This is achieved by keeping one file per process and relies on the assumption that both replacing and reading a symlink on your Linux distribution is atomic.

In order for this to work, all write operations must go through this module.

Currently reading only returns the data written by the process which wrote last. If you need some sort of appending, it makes more sense to deploy a mutex using e.g. the `multithreading/mtx` module.

Overall Features	
# readers	multiple
# writers	multiple
read consistency	partial, last writer wins
write consistency	always
blocking	never

Copyright (C) 2019 David Hobach LGPLv3
0.2

Dependencies

shuf
mv
ln
stat
rm

Functions

b_multiw_getDeps

multithreading/multiw/b_multiw_getDeps

Get the dependencies of this module.

returns: newline-separated list of dependencies of this module

b_multiw__setMaxHangTime [seconds]

multithreading/multiw/b_multiw_setMaxHangTime

Set the maximum time that a process is expected to hang between two instructions. This is relevant for various internal guarantees.

[seconds]: Time in seconds that a process hangs at most.

returns: Nothing.

@StateChanging

b_multiw__getMaxHangTime

multithreading/multiw/b_multiw_getMaxHangTime

Get the maximum time that a process is expected to hang between two instructions. This is relevant for various internal guarantees.

returns: Time in seconds.

b_multiw__write [file path]

multithreading/multiw/b_multiw_write

Write all data lying in stdin to the given *virtual* file in a thread-safe way.

[file path]: Full path to the virtual file to write to. Must not be a regular file (but may not exist).

returns: A zero exit code, if the write operation was successful and a non-zero exit code otherwise.

@B_E

b_multiw__remove [file path]

multithreading/multiw/b_multiw_remove

Remove the given virtual file *and all of its revisions*.

This function should only be called when all processes finished reading and writing. It is recommended to use it over the standard Linux `rm` as the latter will leave remnants behind.

returns: A zero exit code on success.

@B_E

os/osid

Functions for operating system identification.

Copyright (C) 2018 David Hobach LGPLv3
0.2

Dependencies

no dependencies

Functions

b_osid_getDeps

os/osid/b_osid_getDeps

Get the dependencies of this module.

returns: newline-separated list of dependencies of this module

b_osid_init [force]

os/osid/b_osid_init

[force]: if set to 0, force an init even if it would otherwise not be necessary (default: 1 - only initialize if it didn't happen before)

Initialize the osid module. It should normally *not* be necessary to call this function directly, but it will be called by the osid module internally as needed.

returns: May error out and set a non-zero exit code on failures.

b_osid_isDebian

os/osid/b_osid_isDebian

Check whether the OS running this function is a Debian Linux.

returns: Sets a zero exit code if the check returns true. Does not print any output.

b_osid_isDebianLike

os/osid/b_osid_isDebianLike

Check whether the OS running this function is a Debian Linux or one of its derivatives (e.g. ubuntu).

returns: Sets a zero exit code if the check returns true. Does not print any output.

b_osid_isOpenSuse

os/osid/b_osid_isOpenSuse

Check whether the OS running this function is a OpenSUSE.

returns: Sets a zero exit code if the check returns true. Does not print any output.

b__osid__isFedora

os/osid/b__osid__isFedora

Check whether the OS running this function is a Fedora Linux.

returns: Sets a zero exit code if the check returns true. Does not print any output.

b__osid__isCentOS

os/osid/b__osid__isCentOS

Check whether the OS running this function is a CentOS.

returns: Sets a zero exit code if the check returns true. Does not print any output.

b__osid__isRedHat

os/osid/b__osid__isRedHat

Check whether the OS running this function is a RedHat Linux.

returns: Sets a zero exit code if the check returns true. Does not print any output.

b__osid__isUbuntu

os/osid/b__osid__isUbuntu

Check whether the OS running this function is an Ubuntu Linux.

returns: Sets a zero exit code if the check returns true. Does not print any output.

b__osid__isFedoraLike

os/osid/b__osid__isFedoraLike

Check whether the OS running this function is a Fedora Linux or one of its derivatives (e.g. CentOS, Red Hat, Qubes OS).

returns: Sets a zero exit code if the check returns true. Does not print any output.

b__osid__isQubesDom0

os/osid/b__osid__isQubesDom0

Check whether the OS running this function is a Qubes OS in dom0.

returns: Sets a zero exit code if the check returns true. Does not print any output.

b__osid__isQubesVM

os/osid/b__osid__isQubesVM

Check whether the OS running this function is a Qubes OS in a VM.

returns: Sets a zero exit code if the check returns true. Does not print any output.

os/qubes4/dom0

Collection of functions supporting scripting in Qubes OS 4.x dom0.

Important: Whenever you parse output from VMs to dom0, you **must** be extra careful and assume it totally untrusted as parsing bugs are a plausible attack vector for compromised VMs. Passing data to potentially compromised VMs of course also exposes that data's confidentiality.

Copyright (C) 2019 David Hobach LGPLv3
0.5

Dependencies

qvm-run
qvm-block
qvm-ls
qvm-shutdown
qvm-check
qvm-pool
qubes-prefs
qubesdb-write
qubesdb-rm
dirname
basename
mktemp
ps
sleep
cat
timeout
dd
tee

xxd
python3
kill
losetup
setuid
sort
tar

Imports

fs

ui

proc

types

Functions

b_dom0_getDeps

os/qubes4/dom0/b_dom0_getDeps

Get the dependencies of this module.

returns: newline-separated list of dependencies of this module

b_dom0_setVMDeps [list] [keep defaults]

os/qubes4/dom0/b_dom0_setVMDeps

Set the dependencies for all VMs used with this module to the given list of binaries.

These dependencies are checked before *any* execution of commands in *any* VM; in particular whenever `b_dom0_qvmRun`, `b_dom0_execIn`, `b_dom0_execStrIn` or `b_dom0_execFuncIn` are called.

[list]: Newline-separated list of binaries or commands that VMs must be able to execute.

[keep defaults]: If set to 0 (default), merge the default list of dependencies with the supplied one. Otherwise only keep the supplied list of dependencies.

returns: Nothing.

@StateChanging

b_dom0_getVMDeps

os/qubes4/dom0/b_dom0_getVMDeps

Getter for `b_dom0_setVMDeps`.

returns: The current list of dependencies for VMs.

b_dom0_qvmRun [parameter 1] ... [parameter n]

os/qubes4/dom0/b_dom0_qvmRun

A wrapper for qvm-run which sets reasonable defaults for shell scripting and applies various fixes.

Most calls to qvm-run should be made via this function rather than interacting with qvm-run directly as the Qubes OS qvm-run was designed with interactive shell usage in mind whereas this wrapper is intended for bash developers.

Particular features:

- a certain set of reasonable default parameters is used: -p -q -n -u root
- -n was set as auto-starting VMs during Bash scripting can heavily influence the user experience (imagine the VM being shut down manually by the user whilst a bash script is running -> constant restarts)
- stdin is redirected to /dev/null by default to avoid potential security implications (accidental reads from dom0 stdin passed to a VM); this can be overridden using -stdin
- stdout has the VM output and the exit code is the one of the VM
- distinguished exit conditions (executed command failed vs. qvm-run failed)
- workarounds for known Qubes bugs wrt qvm-run may be implemented here (e.g. qubes issues #3083, #4476, #4633 in the past)
- VM dependencies set with b_dom0_setVMDeps are checked

Please note that calling this function will make your script wait for the execution of the commands in the client VM.

Wherever possible, this function should be combined with b_silence as the VM output shouldn't be trusted. Otherwise please keep in mind that **both** stdout *and* stderr may have untrusted output which may even contain binary data. In order to validate against binary data you can e.g. use b_types_parseString.

[parameters]: Any parameters supported by qvm-run. If you pass -a, the default -n will be overridden. If you pass -u, the default root user is overridden. If you pass -v, -q will be overridden. If you pass -stdin, even stdin is passed to qvm-run. -p can be overridden by using /dev/null redirection. Only the short parameter versions are supported.

returns: Sets the exit code of qvm-run and prints its output. May error out using B_E if qvm-run itself fails.

@B_E

b_dom0_getDispVMs

os/qubes4/dom0/b_dom0_getDispVMs

Get a list of all currently existing disposable VMs.

[returns]: The currently existing disposable VMs as newline-separated list.

@B_E

b_dom0_startDispVM [template]

os/qubes4/dom0/b_dom0_startDispVM

Start a dispVM from the given template in the background and return its name. The disposable VM will remain started until it is shut down. If you only wish to execute a single command, please use `b_dom0_qvmRun` with the `-dispVM` parameter.

It may take a while for this function to obtain the name of the dispVM.

[template]: The template to use for the dispVM. If no template is specified, use the default Qubes template.

returns: Name of the dispVM that was started and sets a zero exit code on success. This function may error out.

@B_E

b_dom0_execIn [vm] [file] [user]

os/qubes4/dom0/b_dom0_execIn

Execute the file as bash code in the given VM and wait for it to finish.

See `b_dom0_qvmRun` for various notes and words of caution.

[vm]: Name of the VM where to execute the given string. The VM is assumed to be started.

[file]: Bash file to execute in the given VM.

[user]: user as which to execute the bash file (default: root)

returns: Whatever the executed Bash code prints in the VM to stderr or stdout; the status code is set to the one of the executed Bash code on success (0). Non-zero exit codes and error messages may come from both this function as well as the code executed in the given VM.

@B_E

b_dom0_execStrIn [vm] [string] [user]

os/qubes4/dom0/b_dom0_execStrIn

Execute the String as bash code in the given VM and wait for it to finish.

Convenience wrapper for `b_dom0_execIn`.

See `b_dom0_qvmRun` for various notes and words of caution.

[vm]: see `b_dom0_execIn`

[string]: Bash String to execute in the given VM.

[user]: see `b_dom0_execIn`

returns: see `b_dom0_execIn`; `B_E` is *not* called if the executed command returns an error

@B_E

b_dom0_execFuncIn [vm] [user] [function] [module dep 1] .. [module dep n] - [function dep 1] .. [function dep d] - [function param 1] .. [function param p]

os/qubes4/dom0/b_dom0_execFuncIn

Execute the Bash function in the given VM and wait for it to finish.

Convenience wrapper for `b_dom0_execIn`.

See `b_dom0_qvmRun` for various notes and words of caution.

[vm]: see `b_dom0_execIn`

[user]: see `b_dom0_execIn`

[function]: Name of the function as it is declared in the current scope.

[module dep i]: Names of the modules required by the function. They do not need to be imported by the function itself.

[-]: A dash as separator character between the various parameters.

[function dep j]: An arbitrary number of functions that need to be added in order to satisfy the dependencies of the function to call (e.g. if function A is meant to be called, but uses function B internally, you'll have to pass B as one of its dependencies). Dependencies that can be found in added modules must *not* be added.

[function param p]: An arbitrary number of function parameters.

returns: see `b_dom0_execIn`; `B_E` is *not* called if the executed command returns an error

@B_E

b_dom0_waitForFileIn [vm] [file] [maximum time]

os/qubes4/dom0/b_dom0_waitForFileIn

Convenience wrapper for `b_fs_waitForFile`.

[vm]: VM where to execute.

@B_E

b_dom0_isMountedIn [vm] [device]

os/qubes4/dom0/b_dom0_isMountedIn

Check whether the device is mounted in the given VM.

[vm]: VM where to execute.

[device]: Full path to the device (incl. /dev/) to check.

returns: Sets a zero exit code if the device is mounted in the VM; a non-zero exit code means that it's either not mounted or some other error occurred.

@B_E

b_dom0_mountIfNecessary [vm] [device] [mount point] [enforce]

os/qubes4/dom0/b_dom0_mountIfNecessary

Mount the given device in the target VM if it isn't already mounted there. Actually a wrapper for b_fs_mountIfNecessary.

[vm]: VM where to execute.

[device]: Full path to the device (incl. /dev/) to mount.

[mount point]: Full path where to mount the device. If no mount point is specified, a /tmp/ mount point is chosen. Non-existing directories are created. Is ignored if another mount point already exists.

[enforce]: If set to 0, enforce the given mount point to be used in addition to potentially existing ones (default: 1).

returns: The chosen mount point or a newline-separated list of existing mount points on success; sets a non-zero exit code on failure. As these strings are returned from the VM, extra care must be taken when parsing them.

@B_E

b_dom0_createLoopDeviceIfNecessary [vm] [file]

os/qubes4/dom0/b_dom0_createLoopDeviceIfNecessary

Create a loop device for the file in the given VM if no old one exists. Actually a wrapper for b_fs_createLoopDeviceIfNecessary.

This usually requires root privileges.

[vm]: VM where to execute.

[file]: File for which to create a loop device.

returns: Created loop device or previously used one (incl. /dev/). Sets a non-zero exit code, if no device could be created.

@B_E

b_dom0_removeUnusedLoopDevice [vm] [device|file] [type] [map]

os/qubes4/dom0/b_dom0_removeUnusedLoopDevice

Remove a loop device from the given VM, if it is *neither* used by Qubes OS *nor* by the given VM.

Important: Calling this function may cause the device to be removed as soon as it becomes unused by the VM (and the VM *only!*). So if you called this function, you should *not* use the device any further from dom0 with e.g. `qvm-block` afterwards - even if it wasn't removed.

[vm]: VM where to remove the loop device.

[device|file]: Full path (incl. `/dev/`) to the loop device or to the backing file inside the VM.

[type]: Whether the given path represents a loop device (0) or the backing file (1). If not specified, a device will be assumed, if and only if the path starts with `/dev/`.

[map]: Optional output from a previous call to `b_dom0_parseQvmBlock`. If none is specified, this function will internally call `b_dom0_parseQvmBlock`.

returns: Sets a zero exit code, if the loop device was not used and could thus be successfully removed *or* does not exist. A nonzero exit code indicates that the device is still being used. `B_E` is called on other errors.

@B_E

b_dom0_copy [dom0 file] [target VM] [target VM dir] [overwrite] [parent dir]

os/qubes4/dom0/b_dom0_copy

Grab a file or directory in dom0 and push it to the given file path in the target VM.

[dom0 file]: location of the dom0 file or directory to read from, assumed to exist

[target VM]: VM to write to, assumed to exist. Must be started.

[target VM dir]: full path to the parent directory in the target VM to copy the file or directory to; non-existing parent directories are created; the name is taken from the name of the file/directory in dom0

[overwrite]: Whether or not to overwrite an existing [destination file] (default: 0 = overwrite).

[parent dir]: Set this to 0, if the [target VM dir] is the target *parent* directory (default) and to 1 if it includes the target file or folder *name* as last element.

returns: Sets an exit code of 0, if everything went fine, and a non-zero exit code otherwise.

@B_E

b_dom0_crossCopy [source VM] [source file] [target VM] [target VM dir] [overwrite] [parent dir]

os/qubes4/dom0/b_dom0_crossCopy

Cross copy a file or directory from one VM to another, initiated by dom0. No user prompt is displayed.

[source VM]: Where to copy the source file from. Must be started.

[source file]: The file or directory to copy.

[target VM]: Where to copy the file to. Must be started.

[target VM dir]: full path to the parent directory in the target VM to copy the file or directory to; non-existing parent directories are created; the name is taken from the name of the file/directory in dom0

[overwrite]: Whether or not to overwrite an existing [destination file] (default: 0 = overwrite).

[parent dir]: Set this to 0, if the [target VM dir] is the target *parent* directory (default) and to 1 if it includes the target file or folder *name* as last element.

returns: Sets an exit code of 0, if everything went fine, and a non-zero exit code otherwise.

@B_E

b_dom0_ensureRunning [vm 1] ... [vm n]

os/qubes4/dom0/b_dom0_ensureRunning

Start the given VMs if needed.

[vm i]: The VM to start.

returns: Nothing. B_E will be called for VMs that could not be started (maybe they don't exist?).

@B_E

b_dom0_isRunning [vm 1] ... [vm n]

os/qubes4/dom0/b_dom0_isRunning

Check whether the given VMs are running *and* fully operational / not hanging / not booting.

In contrast **qvm-check --running [vm]** returns true for VMs which are currently booting and **qvm-ls** doesn't check whether the OS of a VM is hanging.

[vm i]: The VM to check.

returns: Nothing. B_E will be called for VMs that are not running (or don't exist?).

@B_E

b_dom0_isHalted [vm 1] ... [vm n]

os/qubes4/dom0/b_dom0_isHalted

Check whether the given VMs are halted.

[vm i]: The VM to check.

returns: Nothing. B_E will be called for VMs that are not halted (or don't exist?).

@B_E

b_dom0_ensureHalted [vm 1] ... [vm n]

os/qubes4/dom0/b_dom0_ensureHalted

Shut down the given VMs if needed.

[vm i]: The VM to halt.

returns: Nothing. B_E will be called for VMs that could not be halted (maybe they don't exist?).

@B_E

b_dom0_exists [vm]

os/qubes4/dom0/b_dom0_exists

Check whether the given VM exists.

[vm]: The VM to check.

returns: Sets a zero exit code, if the VM exists a non-zero exit code otherwise.

b_dom0_openCrypt [vm] [device] [mapper name] [rw flag] [mount point] [key file] [additional options] [password prompt]

os/qubes4/dom0/b_dom0_openCrypt

In the given VM, open the given crypto device with dm-crypt and mount it to the mount point.

[vm]: The VM where to open the crypto device.

[device]: Full path to the device (incl. /dev/) to open.

[mapper name]: The name to assign to the decrypted version of the crypto block device. The created decrypted device will be found at `/dev/mapper/[mapper name]`.

[rw flag]: 0=open read-write, 1=open read-only (default: 0)

[mount point]: Where to mount the decrypted data to. Non-existing directories will be created. If no mount point is specified, it will not be mounted (default).

[key file]: Full vm path to the key to use for decryption. If none is specified, password-based decryption is assumed and stdin will be read to obtain the password.

[additional options]: Single string with additional cryptsetup parameters to pass on (default: none). They are passed *as-is*, i.e. you'll have to take care of proper escaping etc. yourself.

[password prompt]: Optional string to use when the user is required to provide a decryption password.

returns: nothing (except for user interaction prompts if no key file is provided), but sets a non-zero exit code on errors

@B_E

b_dom0_closeCrypt [vm] [mapper name] [mount point]

os/qubes4/dom0/b_dom0_closeCrypt

Close a crypto device opened with `b_dom0_openCrypt`.

[vm]: The VM where to close the crypto device.

[mapper name]: The name used when it was opened.

[mount point]: If the decrypted data is mounted inside the [vm], please specify the mount point here so that it can be unmounted before closing the device. Otherwise the function will attempt to close the device without unmounting (likely to fail).

returns: nothing, but sets a non-zero exit code on errors

@B_E

b_dom0_parseQvmBlock [variable name] [input]

os/qubes4/dom0/b_dom0_parseQvmBlock

Parse data from `qvm-block ls` to an associative array.

The indices of the associative array will be of the format `[counter]_[field]` (counters run from 0 (inclusive) to max (exclusive)).

The special index “max” is equal to the number of lines. It can be used for iterations over the map.

Currently supported [field] values: backend|device id|id|description|used by|read-only|frontend-dev

[variable name]: Name of the associative array to use as output.

[input]: Optional output from a previous `qvm-block ls` call; if none is specified, this function will execute the call and use its output.

returns: A string specifying an associative array in bash syntax. You can eval that string to obtain all relevant data or use the more convenient `b_dom0_getQvmBlockInfo`. On errors `B_E` is called.

@B_E

b_dom0_getQvmBlockInfo [map] [retrieve field] [filter field 1] [filter value 1] .. [filter field n] .. [filter value n]

os/qubes4/dom0/b_dom0_getQvmBlockInfo

Convenience function to retrieve information from the output of `b_dom0_parseQvmBlock`. Searches for the given filter values in the given fields and retrieves the first field value matching all filters.

More simple, but less flexible than `b_dom0_parseQvmBlock`.

[map]: Optional output from a previous call to `b_dom0_parseQvmBlock`. If none is specified, this function will internally call `b_dom0_parseQvmBlock`.

[retrieve field]: Name of the field to retrieve.

[filter field i]: Name of any field supported by `b_dom0_parseQvmBlock`.

[filter value i]: The value to search for in [filter field i] (equality check).

returns: The value of the requested field and sets a zero exit code on success. Sets a non-zero exit code if no matching value could be found. On errors `B_E` is called.

@B_E

b_dom0_attachFile [dom0 file] [target VM] [rw flag] [force]

os/qubes4/dom0/b_dom0_attachFile

Attach the given file from dom0 (!) as block device to the target VM.

The function may attempt to acquire root privileges (and thus display a password prompt).

[dom0 file]: Full path to the file *in dom0* to attach.

[target VM]: VM to attach the file to. Must be started.

[rw flag]: If set to 0, attaches the dom0 file in r/w (read-write) mode. If set to 1 (default), attaches the file in r/o (read only) mode.

[force]: If set to 0, attempt to force Qubes OS to recognize the device (default: 1). This is required for e.g. VM images.

returns: The full path to the device created in the target VM and sets a zero exit code on success. Otherwise a non-zero exit code is set.

@B_E

b_dom0_attachVMDisk [source VM] [target VM] [rw flag]

os/qubes4/dom0/b_dom0_attachVMDisk

Attach the entire private disk image (private.img) of the source VM to the target VM.

Warning: This is contradictory to all Qubes principles and should only be done if you know exactly what you're doing. Qubes OS even has some countermeasures to prevent accidental use of this feature which are bypassed here.

[source VM]: Name of the VM whose private disk to attach to the target VM. *All data* of that VM will be shared with the target VM. Will be shut down as part of this function and must remain shut down as long as the disk is attached.

[target VM]: VM where to attach the disk as block device to. Must be started.

[rw flag]: If set to 0, attaches the disk file in r/w (read-write) mode. If set to 1 (default), attaches the file in r/o (read only) mode.

returns: The full path to the device created in the target VM and sets a zero exit code on success. Otherwise a non-zero exit code is set. Please call `b_dom0_detachDevice` with the `clean` flag for the detach operation.

@B_E

b_dom0_crossAttachDevice [source VM] [source device] [target VM] [rw flag]

os/qubes4/dom0/b_dom0_crossAttachDevice

Attach the given block device from the source VM to the target VM. This is merely a convenience wrapper for `qvm-block attach`.

[source VM]: VM where the source file can be found.

[source device]: Device to attach to the [target VM].

[target VM]: VM to attach the device to. Must be started.

[rw flag]: If set to 0, attaches the [source device] in r/w (read-write) mode. If set to 1 (default), attaches the file in r/o (read only) mode.

returns: The full path to the device created in the target VM and sets a zero exit code on success. Otherwise a non-zero exit code is set.

@B_E

b_dom0_crossAttachFile [source VM] [source file] [target VM] [rw flag]

os/qubes4/dom0/b_dom0_crossAttachFile

Attach the given file from the source VM as block device to the target VM.

[source VM]: VM where the source file can be found.

[source file]: File to attach as block device.

[target VM]: VM to attach the file to. Must be started.

[rw flag]: If set to 0, attaches the [source file] in r/w (read-write) mode. If set to 1 (default), attaches the file in r/o (read only) mode.

returns: The full path to the device created in the target VM and sets a zero exit code on success. Otherwise a non-zero exit code is set.

@B_E

b_dom0_detachDevice [vm] [device] [clean flag]

os/qubes4/dom0/b_dom0_detachDevice

Attempts to detach the given device from the VM. This may fail if the VM is using the device and thus it is usually a better idea to just shut the VM down.

[vm]: VM from which to detach the device.

[device]: Full path to the device in the VM. E.g. the return values of `b_dom0_crossAttachFile`, `b_dom0_attachFile` or `b_dom0_attachVMDisk`.

[clean flag]: Also wipe the device from the Qubes DB, if it's there (default: 1).

returns: nothing, but sets a zero exit code on success

@B_E

b_dom0_enterEventLoop [callback function] [heartbeat interval]

os/qubes4/dom0/b_dom0_enterEventLoop

Enter a blocking loop to react to Qubes OS events. `b_dom0_disconnectEventLoop` can be used to disconnect from the event loop asynchronously, e.g. from exit traps.

If you want to obtain an overview of Qubes OS events, please use the `qwatch` utility manually.

[callback function]: Name of the function to call for *every* Qubes OS event. Since the number of events may be high, the function should do appropriate filtering at high performance.

The callback function should be declared as follows:

`callback_function_name [subject] [event name] [event info] [timestamp]`
`[subject]`: The subject name Qubes OS provides. Usually the VM for which the event was reported. 'None' appears to mean 'dom0'.
`[event name]`: Name of the event for which the callback function was called.
`[event info]`: May contain additional information about the event (e.g. arguments).
`[timestamp]`: When the event was received in ms since EPOCH.
returns: Nothing. A non-zero exit code will abort further processing.
`[heartbeat interval]`: Interval in ms at which to send heartbeat events (default: no heartbeat events).

returns: Nothing, but uses the exit code of the last callback function execution as its own. Sets an exit code of 0, if the event loop was terminated by `b_dom0_disconnectEventLoop`. `B_E` is only called on exceptional errors.

@StateChanging

@B_E

b_dom0_disconnectEventLoop

os/qubes4/dom0/b_dom0_disconnectEventLoop

Send a termination request to a dom0 event loop started with `b_dom0_enterEventLoop`. This is useful to exit the event loop from outside of it.

returns: A non-zero exit code indicates that either no active event loop existed or the signal sending failed. Never errors out to be suitable for e.g. exit traps.

@StateChanging

b_dom0_testMultiple [vm] [operator] [list]

os/qubes4/dom0/b_dom0_testMultiple

Run multiple **test** checks inside the given VM with a single `qvm-run` call.

`[vm]`: Where to run the checks.

`[operator]`: The test operator to use for the list of parameters, e.g. `-f`.

`[list]`: Newline-separated list of parameters to check, e.g. a list of files for the `-f` operator.

returns: The subset of the list that matched the operator and sets a zero exit code on success.

@B_E

proc

Collection of process and thread related functions.

Copyright (C) 2018 David Hobach LGPLv3
0.2

Dependencies

tail
timeout

Functions

b__proc_getDeps

proc/b__proc_getDeps

Get the dependencies of this module.

returns: newline-separated list of dependencies of this module

b__proc_pidExists [pid]

proc/b__proc_pidExists

Check whether the given process ID exists on the system.

[pid]: process ID to check for existence (process exists)

returns: A zero exit code, if it exists and a non-zero exit code if it doesn't; this function attempts to check the existence of the given process across *all* users, but it cannot guarantee correctness if the user running this script has very low privileges.

b__proc_childExists [pid]

proc/b__proc_childExists

Check whether the given process ID exists *and* is a *direct* child of the calling bash process.

[pid]: process ID to check

returns: A zero exit code, if the caller is a parent of the given pid.

b__proc_waitForPid [pid] [maximum time]

proc/b__proc_waitForPid

Wait for the given process to exit. If it doesn't exist, exit immediately.

[pid]: Process ID of the process to wait for. Doesn't need to be a child.

[maximum time]: Maximum time in seconds to wait for the process to exit (default: 0 = indefinitely).

returns: Nothing, always sets a zero exit code. Use `b__proc__pidExists` if you need to know whether the process finished.

str

Collection of string related functions.

Copyright (C) 2018 David Hobach LGPLv3
0.1

Dependencies

no dependencies

Functions

b__str__getDeps

str/b__str__getDeps

Get the dependencies of this module.

returns: newline-separated list of dependencies of this module

b__str__stripQuotes [string]

str/b__str__stripQuotes

Remove any single or double quotes around the given string.

[string]: string which might be enclosed in single or double quotes (' or ")

returns: [string] without the enclosed single or double quotes, if there were any; if none were found the original string is returned; the exit code is always zero

b__str__trim [string]

str/b__str__trim

remove any whitespace from around a string

[string]: string to trim

returns: [string] beginning and ending without whitespace; the exit code is always zero

tcolors

Defines some tput related constants. In order to change terminal colors you can then use something such as

```
echo "$(tput setaf ${B_TCOLORS[red]})This is red, \  
$(tput setaf ${B_TCOLORS[blue]})this blue, $(tput sgr0)this normal."
```

tput can do a lot more than colors, see: man tput & man terminfo.

Copyright (C) 2018 David Hobach LGPLv3

0.1

Dependencies

tput

Global Variables

B_TCOLORS

tcolors/B_TCOLORS

Global map for human readable colors to tput style color identifiers.

Currently supported values: black|red|green|yellow|blue|magenta|cyan|white

Functions

b_tcolors__getDeps

tcolors/b_tcolors__getDeps

Get the dependencies of this module.

returns: newline-separated list of dependencies of this module

traps

Collection of trap related functions.

Copyright (C) 2018 David Hobach LGPLv3

0.2

Dependencies

no dependencies

Functions

b_traps__getDeps

traps/b_traps__getDeps

Get the dependencies of this module.

returns: newline-separated list of dependencies of this module

b_traps_getCodeFor [signal]

traps/b_traps_getCodeFor

Retrieve the current trap code / commands for the given signal.

returns: The current code and sets a zero exit code on success.

@B_E

b_traps_add [code] [signal] [tag] [append flag]

traps/b_traps_add

Add the given commands to the given trap signal.

[code]: Whatever should be added to the trap.

[signal]: Name of the signal to add the commands to.

[tag]: An optional *unique* marker for these commands so that they can be removed with `b_traps_remove` later on.

[append flag]: Whether to append the new commands to the end (0: default) or insert them in the beginning (1).

returns: Whatever the internal call to *trap* to set the new trap returns.

@B_E

b_traps_prepend [code] [signal] [tag]

traps/b_traps_prepend

Prepend the given commands to the ones currently existing for the given trap signal.

Convenience wrapper to `b_traps_add` with [append flag] set to 1.

[code]: see `b_traps_add`

[signal]: see `b_traps_add`

[tag]: see `b_traps_add`

returns: see `b_traps_add`

@B_E

b_traps_remove [signal] [tag]

traps/b_traps_remove

Remove the commands tagged with the given tag from the signal trap.

[signal]: Name of the signal to remove the commands from.

[tag]: The *unique* marker to identify the commands to be removed.

returns: Nothing, but sets a zero exit code on success. May error out if the tag isn't found or the internal trap call failed.

@B_E

types

Functions for data type checks and conversions.

Copyright (C) 2018 David Hobach LGPLv3

0.2

Dependencies

mktemp

mkfifo

rm

wc

strings

tee

head

Global Variables

B_TYPES_ENCODINGS

types/B_TYPES_ENCODINGS

Global map for human readable string encodings which can be used for `b_types_parseString`.

Currently supported values: 7-bit|8-bit|16-bit-bigendian|16-bit-littleendian|32-bit-bigendian|32-bit-littleendian

See the strings manpage for further explanations.

Functions

b_types_getDeps

types/b_types_getDeps

Get the dependencies of this module.

returns: newline-separated list of dependencies of this module

b__types__parseString [encoding]

types/b__types__parseString

Checks whether whatever is lying in stdin is a string (and not binary) and if so, prints it to stdout.

Important:

- bash has major issues whenever binary data is involved. For example equality checks may return undefined results. So whenever you are unsure as to whether a variable is a string or not, better pass it thorough this function.
- The input is taken from *stdin* rather than as parameter as binary parameters may also cause issues (special bytes etc.).
- Even builtins such as **echo** do not necessarily play well with binary data. So it is recommended to pipe binary data through this function before further processing.

Examples:

```
#check a file
```

```
b__types__parseString < "/path/to/potential/binary" > /dev/null && echo "It is a string file."
```

```
#read parts of a file as string
```

```
str="$(dd if="/path/to/another/file" bs=1 skip=8 | b__types__parseString)"  
[ $? -eq 0 ] && echo "Found the following string: $str"
```

[encoding]: The encoding of the string lying in stdin. Use `B__TYPES__ENCODINGS` for this parameter. Defaults to `${B__TYPES__ENCODINGS["7-bit"]}`, which makes sense in 99% of all cases as scripts should use ASCII only anyway (when no user-interaction is involved) in order to remain portable. Keep in mind that bash also needs to support the target encoding in order to support further processing.

returns: The data as String, if the input data was found to be a String. If no String was found to be lying in stdin, the output is an undefined string and a non-zero exit code is set. `B__E` is only called on exceptional errors.

@B__E

b__types__isInteger [string]

types/b__types__isInteger

Check whether the given String is an integer (positive or negative) or not.

[string]: The string to check. If it may be binary data, please make sure to pass it through `b__types__parseString` first.

returns: Nothing, but sets a zero exit code if and only if the given string represents an integer.

ui

Collection of user interface and user interaction related functions.

Copyright (C) 2020 David Hobach LGPLv3
0.2

Dependencies

no dependencies

Functions

b_ui_getDeps

ui/b_ui_getDeps

Get the dependencies of this module.

returns: newline-separated list of dependencies of this module

b_ui_passwordPrompt [output var] [ui mode] [prompt string]

ui/b_ui_passwordPrompt

Prompt the user for a password. Should run inside the parent process (i.e. not inside a subshell).

Once you do not need the password anymore, it is recommended to wipe it from memory as such:

```
#overwrite the password in memory with zeroes, then free it  
pass="${pass//?/0}" ; pass=""
```

[output var]: The name of the variable to write the password to.

[ui mode]: How to request the password from the user: auto|gui|tty (default: auto).

[prompt string]: The string to present to the user asking for the password (default: "Password:").

returns: Nothing. Sets a non-zero exit code on errors.

@B_E

Reference List

B_ARGS

b_args_assertOptions

b_args_get

b_args_getCount

b_args_getDeps
b_args_getInt
b_args_getOption
b_args_getOptionCount
b_args_getOptionInt
b_args_getOptionParamSeparator
b_args_init
B_ARGS_OPTS
b_args_parse
b_args_setOptionParamSeparator
b_arr_contains
b_arr_getDeps
b_arr_join
b_arr_mapsAreEqual
b_arr_toList
b_blib_getDeps
b_cachingMessageHandler
B_CALLER_NAME
b_cdoc_cbPrintFirstParam
b_cdoc_cbPrintNewline
b_cdoc_generate
b_cdoc_generateBlibStyle
b_cdoc_getDeps
b_cdoc_getDocumentBeginCallback
b_cdoc_getDocumentEndCallback
b_cdoc_getExtractionRegex
b_cdoc_getFileFilterCallback
b_cdoc_getPostProcessingCallback
b_cdoc_getSpaceCallback
b_cdoc_setDocumentBeginCallback
b_cdoc_setDocumentEndCallback

b_cdoc_setExtractionRegex
b_cdoc_setFileFilterCallback
b_cdoc_setPostProcessingCallback
b_cdoc_setSpaceCallback
b_checkDeps
b_checkVersion
B_CONF_DIR
b_daemon_getDeps
b_daemon_getPid
B_DAEMON_ID
b_daemon_init
b_daemon_restart
b_daemon_start
b_daemon_status
b_daemon_statusPid
b_daemon_stop
b_date_add
b_date_addDays
b_date_diff
b_date_getDeps
b_date_getFileModAge
b_defaultErrorHandler
b_defaultMessageHandler
b_delay_execute
B_DELAY_EXECUTED
b_delay_getCommandAt
b_delay_getDeps
b_delay_to
b_dmccrypt_close
b_dmccrypt_createLuks
b_dmccrypt_getDeps

b_dmccrypt__getMapperName
b_dmccrypt__init
b_dmccrypt__isOpen
b_dmccrypt__open
b_dom0__attachFile
b_dom0__attachVMDisk
b_dom0__closeCrypt
b_dom0__copy
b_dom0__createLoopDeviceIfNecessary
b_dom0__crossAttachDevice
b_dom0__crossAttachFile
b_dom0__crossCopy
b_dom0__detachDevice
b_dom0__disconnectEventLoop
b_dom0__ensureHalted
b_dom0__ensureRunning
b_dom0__enterEventLoop
b_dom0__execFuncIn
b_dom0__execIn
b_dom0__execStrIn
b_dom0__exists
b_dom0__getDeps
b_dom0__getDispVMs
b_dom0__getQvmBlockInfo
b_dom0__getVMDeps
b_dom0__isHalted
b_dom0__isMountedIn
b_dom0__isRunning
b_dom0__mountIfNecessary
b_dom0__openCrypt
b_dom0__parseQvmBlock

b_dom0_qvmRun
b_dom0_removeUnusedLoopDevice
b_dom0_setVMDeps
b_dom0_startDispVM
b_dom0_testMultiple
b_dom0_waitForFileIn
B_E
b_enforceUser
B_ERR
b_error
b_execFuncAs
b_execFuncInCurrentContext
b_flog_close
b_flog_defaultHeader
b_flogErrorHandler
b_flog_getDateFormat
b_flog_getDeps
b_flog_getHeaderFunction
b_flog_getLogReductionLinesLowerBound
b_flog_getLogReductionLinesUpperBound
b_flog_headerDateScriptSeverity
b_flog_headerDateSeverity
b_flog_init
b_flog_log
b_flog_printSeverity
b_flog_setDateFormat
b_flog_setHeaderFunction
b_flog_setLogReductionLinesApprox
b_flog_setLogReductionLinesLowerBound
b_flog_setLogReductionLinesUpperBound
B_FLOG_SEV

b_fs_createLoopDeviceIfNecessary
b_fs_getDeps
b_fs_getLineCount
b_fs_getMountpoints
b_fs_isEmptyDir
b_fs_mountIfNecessary
b_fs_parseSize
b_fs_removeUnusedLoopDevice
b_fs_removeWithOverwrite
b_fs_waitForFile
b_generateStandalone
b_getBlibModules
b_getDefaultMessageHandlerIntermediate
b_getDefaultMessageHandlerPrefix
b_getErrorHandler
b_getMessageHandler
B_HTTP_CHECKURLS
b_http_getDeps
b_http_getOnlineStatus
b_http_rawUrlDecode
b_http_rawUrlEncode
b_import
b_info
b_ini_assertNames
b_ini_get
b_ini_getBool
b_ini_getDeps
b_ini_getInt
b_ini_getString
b_ini_read
b_initCachingMessageHandler

b_ipcm_change
b_ipcm_get
b_ipcm_getDeps
b_ipcm_getNamespace
b_ipcm_setNamespace
b_ipcm_unsetNamespace
b_ipcv_getDeps
b_ipcv_load
b_ipcv_loadNamespace
b_ipcv_save
b_ipcv_unset
b_ipcv_unsetNamespace
b_isFunction
b_isModule
b_keys_add
b_keys_close
b_keys_delete
b_keys_get
b_keys_getContent
b_keys_getDeps
b_keys_init
B_LIB_DIR
b_listContains
b_mtx_create
b_mtx_forceRelease
b_mtx_getDeps
b_mtx_getSleepTime
b_mtx_pass
b_mtx_release
b_mtx_setSleepTime
b_mtx_try

b__mtx__waitFor
b__multiw__getDeps
b__multiw__getMaxHangTime
b__multiw__remove
b__multiw__setMaxHangTime
b__multiw__write
b__nop
b__osid__getDeps
b__osid__init
b__osid__isCentOS
b__osid__isDebian
b__osid__isDebianLike
b__osid__isFedora
b__osid__isFedoraLike
b__osid__isOpenSuse
b__osid__isQubesDom0
b__osid__isQubesVM
b__osid__isRedHat
b__osid__isUbuntu
b__printStackTrace
b__proc__childExists
b__proc__getDeps
b__proc__pidExists
b__proc__waitForPid
B__RC
b__resetErrorHandler
B__SCRIPT
B__SCRIPT__DIR
B__SCRIPT__NAME
b__setBE
b__setDefaultMessageHandlerIntermediate

b_setDefaultMessageHandlerPrefix
b_setErrorHandler
b_setMessageHandler
b_silence
b_str_getDeps
b_str_stripQuotes
b_str_trim
B_TCOLORS
b_tcolors_getDeps
B_TEST_MODE
b_traps_add
b_traps_getCodeFor
b_traps_getDeps
b_traps_prepend
b_traps_remove
B_TYPES_ENCODINGS
b_types_getDeps
b_types_isInteger
b_types_parseString
b_ui_getDeps
b_ui_passwordPrompt
b_version