






Road network

Each **road**

- has an **identification** e.g. **D907**
- is composed by a **series of ordered edges** (simple linestrings)

Markers are positioned along the roads e.g. Their position is often measured with a **GPS** **(X,Y)**






Topology

The road network is a **GRAPH** built with **edges** and **nodes**

- each edge has a **start and end node**
- an edge can have
 - a **previous** edge
 - a **next** edge
- **intersecting edges** are cut by a **node** (if they are on the same level)





Position & references


This simple organization of **roads**, **edges** and **markers** allows to determine a position of any object based on:

- a **road code**: D902
- a **marker code**: 1
- an **abscissa**: 500m

You can also provide an optional **offset**: 3m and **side**: left

Any point within a distance of **50m** of any road will have its **references**:

D902 PR 1 + 500m (3m left)





Linear referencing

Each data object, **point** or **(multi)linestring**, is defined by its **references** calculated from the road network:

- **Points:** trees, street lights, car accidents, etc.
- **Linestrings:** paintings, safety barriers, roadworks, etc.

We must be able to:


- **calculate the references** from the object geometry
- **create a geometry** based on given references
 - a **point**
 - a **multi-linestring** between 2 references





Corner cases

Discontinuity: edges could have been deleted (or have changed status)



Roundabouts have their own road code `GIR D35-D80` and cut the other roads




Image 1




Image 2






Context

Funded by the **Département du Calvados** (French department)

Calvados



LE DÉPARTEMENT

Objectives

- They would like to **get rid of a proprietary software & use only FOSS4G tools**
- The data must be stored in a **PostgreSQL database** 
- **Visualization & Editing** must be done **inside QGIS** , with the help of a **plugin**
- **Calculations** (references, geometry editing) must be made available for **Lizmap Web Client** 

RoadNetwork

A QGIS plugin

With the power of PostgreSQL & PostGIS





Database model



All the logic is stored inside a
PostgreSQL database

A simple set of **tables**: **roads**, **edges**, **nodes**, **markers**, **glossary**, **managed_objects** + **views**

Many **functions** to calculate references, geometries, among:


get_road_point_from_reference

get_road_substring_from_references

update_table_references_from_geometries

update_table_geometry_from_references

Trigger functions in charge of maintaining the road network **topology** (automatic node creation, split intersected edges, etc.)






Administration tools


QGIS **Processing algorithms** which allow to:

- **Create the database structure** with all the tables/functions, etc.
- **Upgrade the structure** automatically (if upgrading your plugin)
- **Create a QGIS administration project** with all the layers, styles, labels, actions, etc.
- **Import data** from template **edges** and **markers** tables






QGIS administration project






Tools - Quick search (CTRL+K)



Tools - Get references on map click (hover supported)






Editing rules

Data are not edited in the production schema **road_graph** but in a **dedicated editing sessions schema**

- The user creates a **polygon** and **clones an extract of the production data** in a sandbox
- **Editing** is made with **QGIS tools**: forms, topology
- QGIS **automatic transaction grouping** has been activated in the project: changes made with triggers are visible **live**
- A map tool helps to **create roundabouts**
- Modifications are then **merged back** into the **road_graph** schema





Managed objects

The **local authorities** manages a lot of data based on the road network : **roadworks**, **asphalt rehabilitation**, **road signs**, **hedge pruning**.

The **managed_objects** layer lists **all the PostgreSQL tables** impacted by any **graph modification**

	id	schema_name	table_name	geometry_type	update_policy_on_graph_change
1	1	managed	demo_trees	POINT	references
2	2	managed	demo_safety_barriers	MULTILINESTRING	geometry

When the user **merges the data from the editing session**, every impacted object is **automatically updated based on the rule** chosen by the admin user.

- **Point objects** are often not moved but their **references must be updated** Ex: **a road sign**
- **(Multi)Linestring objects** must often follow the changes, but we keep the start & point and only edit the nodes between. Ex: **a painting roadwork**



Conclusion

ISB France

The **QGIS plugin** is here to

- create/upgrade the **database structure**
- **visualize** the road network
- **position** with references & get references from position
- **edit data safely** in a sandbox and use algorithm to copy/merge the data
- **import** data

The main business logic really lies **inside the PostgreSQL database**

- **schemas** and **tables**, functions, triggers

RoadNetwork tools

Localisation

Road

D80

Marker

10

Offset

9.41

Abscissa

27.2

Side

right

Cumulative

10417.8

Find

Localisation (editing)

Road

Marker

Offset

Abscissa

Side

Cumulative

Find

Options

☐ Get references on hover ?

Thanks for your attention

Any questions ?

- **Contact:** info@3liz.com

- **Source code:**

<https://github.com/3liz/qgis-road-network-plugin/>



- **This presentation**

https://docs.3liz.org/presentations/2026-10-06_RoadNetwork-Plugin_QGIS_UC_Laax.html

