

Table of Contents

3M IoT Platform Guides

Devices

[Overview](#)

[Register a device](#)

[Register a simulated device](#)

[Simulating data](#)

[Monitor devices](#)

[Detect device issues](#)

[Connect a root cause analysis on an alert](#)

Architecture

[Overview](#)

[Storage](#)

[Cosmos Db](#)

[Blob Storage](#)

[Table Storage](#)

User Management

[Overview](#)

[For New Users](#)

[Request Access](#)

[User Administrators](#)

[Add System Admin](#)



3M IoT Platform Guides

Welcome to the public documentation on guides that cover common activities of working with the platform.

Managing Devices



OVERVIEW

This is what a card might look like.

User Manual



FIRST SECTION

This is what a card might look like.



Overview of IoT Devices on Azure

Conceptually, there are two types of devices that can be used in Azure: 1) Simulated and 2) Real.

Simulated devices are used to test connectivity and offer a quick way to evaluate functionality without needing to procure any hardware.

There are two types of real devices: IoT Edge device and IoT device.

If you'd like to learn more about the types of devices that can work with Azure check out Microsoft's [Device Catalog](#)

Device Registration

Before you can use a real or simulated device, you must first register it. Use the following links to get started:

- [Register a device](#)
- [Register a simulated device](#)

How to Register a Device

For a device to connect to the solution accelerator, it must identify itself to IoT Hub using valid credentials. You have the opportunity to save the device connection string that contains these credentials when you add the device to the solution. You include the device connection string in your client application later in this tutorial.

To add a device to your Remote Monitoring solution, complete the following steps on the Device Explorer page in the solution:

1. Choose + **New device**, and then choose **Real** as the **Device type**:

3M Serenity IoT DEV Platform

Device Explorer

Search devices...

Device name {}	Simulated	Device type	Firmware	Telemetry	Status
<input type="checkbox"/> BridgetteDemo	No	---	---	---	
<input type="checkbox"/> DemoDevice	No	---	---	---	
<input type="checkbox"/> groupTest2	No	---	---	---	
<input type="checkbox"/> joetest	No	---	---	messageSchema	
<input type="checkbox"/> rule_test	No	---	---	---	
<input type="checkbox"/> sah_test	No	---	---	---	
<input type="checkbox"/> sah_test1	No	---	---	---	
<input type="checkbox"/> sah_test	No	---	---	---	
<input type="checkbox"/> VisTest	No	---	---	messageSchema	

New device

Device

☐ IoT Edge device

☒ IoT device

Number of devices

1

Device ID

☒ Enter device ID

☐ System generated device IDs

Authentication type

☒ Symmetric key

☐ X.509

Authentication key

☒ Auto generate keys

☐ Enter keys manually

Primary Key

Secondary Key

Provision summary

1 Devices to provision

Apply Cancel

1. Enter a Device ID you wish to use to reference this device or allow the system to generate one for you. The value must be unique and connect include spaces.
2. Select the desired authentication type and either have the system generate authentication keys for you or provide your own. CRSL generally uses a Symmetric Key but your organization might prefer x509. Chose whichever is the most appropriate.
3. Select the preferred option for how to define keys. You have the choice between:
 - o Providing your own
 - o Auto Generating



How to Register a Simulated Device





User Management Overview

Describe all of what's covered in this guide. Describe the audiences. Put some cards in here for popular quick hits



Request Access



Add System Admin