



Table of Contents

3M IoT Platform Guides

Devices

[Overview](#)

[Register a device](#)

[Register a simulated device](#)

[Simulating data](#)

[Monitor devices](#)

[Detect device issues](#)

[Connect a root cause analysis on an alert](#)



3M IoT Platform Guides

The following guides offer insight into how to do day-to-day operations on the platform.

Devices

TODO: Describe this section.

Telemetry

TODO: Describe this section.



Overview of IoT Devices on Azure

Conceptually, there are two types of devices that can be used in Azure: 1) Simulated and 2) Real.

Simulated devices are used to test connectivity and offer a quick way to evaluate functionality without needing to procure any hardware.

There are two types of real devices: IoT Edge device and IoT device.

If you'd like to learn more about the types of devices that can work with Azure check out Microsoft's [Device Catalog](#)

Device Registration

Before you can use a real or simulated device, you must first register it. Use the following links to get started:

- [Register a device](#)
- [Register a simulated device](#)

How to Register a Device

For a device to connect to the solution accelerator, it must identify itself to IoT Hub using valid credentials. You have the opportunity to save the device connection string that contains these credentials when you add the device to the solution. You include the device connection string in your client application later in this tutorial.

To add a device to your Remote Monitoring solution, complete the following steps on the Device Explorer page in the solution:

1. Choose + **New device**, and then choose **Real** as the **Device type**:

The screenshot shows the '3M Serenity IoT DEV Platform' interface. The 'Device Explorer' section is active, displaying a table of devices. The 'New device' modal is open, showing the following configuration:

- Device type:** IoT device (selected)
- Number of devices:** 1
- Device ID:** Enter device ID (selected)
- Authentication type:** Symmetric key (selected)
- Authentication key:** Auto generate keys (selected)
- Provision summary:** 1 Devices to provision

1. Enter a Device ID you wish to use to reference this device or allow the system to generate one for you. The value must be unique and connect include spaces.
2. Select the desired authentication type and either have the system generate authentication keys for you or provide your own. CRSL generally uses a Symmetric Key but your organization might prefer x509. Chose whichever is the most appropriate.
3. Select the preferred option for how to define keys. You have the choice between:
 - o Providing your own
 - o Auto Generating



How to Register a Simulated Device