Piotr Król
Rafał Korszuń

HOW TO BUILD IOT SOLUTIONS USING CLOUD INFRASTRUCTURE ?

kleder

Agenda

- About Us
- Embedded Systems in IoT
- Cloud Infrastructure
- Demo

kleder

About Us

About
Piotr Król

Embedded Systems Consultant
freedom and liberty enthusiast
Open Source and Linux fan
chess player
productivity maniac and blogger

Twitter: @pietrushnic
Email: piotr.krol@3mdeb.com
Web: http://3mdeb.com
http://lmgtfy.com/?q=3mdeb

[3MDEB]

kleder

About
Rafał Korszuń

Software Architect / CEO at Kleder
Machine learning enthusiast
Cloud solutions evangelist
Excellent design maniac

Twitter: @rafalkorszun
Email: rafal.korszun@kleder.co
Web: http://kleder.co

kleder

Definitions

- Internet of Things (IoT)
  - Computing **concept** that describes a future where everyday physical objects will be connected to the Internet and be able to identify themselves to other devices.
- Embedded System
  - Is a special-purpose **computer system** designed to perform one or a few dedicated functions, often with real-time computing constraints.
- Cloud computing
  - Cloud computing is a general term for the delivery of **hosted services** over the Internet

kleder



Embedded Systems in IoT

Endpoint architecture - design

Key Factors

- The customer is always right
  - Cost
  - Use cases/requirements
  - Bill of materials
  - Time to market
  - Power source
- Experience
- Openness
- Regulation

Key Problems

- Security
- Firmware upgrade
- Connectivity
- Power consumption
- Provisioning

kleder

Endpoint architecture

- Expensive sensors
- Ready to use product
- Custom hardware
- Built-in:
  - Connectivity
  - Storage
  - MCU performance
- Complex firmware
  - NAT
  - ISP restrictions
  - OTA update



Endpoint architecture

- Existing infrastructure
- Plug and play
- Fixed sensor capability



Endpoint architecture

- Most popular
- Most flexible
- Dedicated hardware
- Lot of software



IoT - components

- Sensors

Sensor channel

MCU

IoT Hubs/Transceivers

IoT Hub channel



How IoT really look like ?

Credits to Michael Schloh von Bennewitz: https://fosdem.org/2016/schedule/event/deviot19/

Hardware and applications

- NRF24L01-based beacons
- Arduino and Raspberry Pi as controllers
- Location detection



kleder

Hardware and applications

- TI CC3200
- Tsunami and earthquake early detection system

Your own, personal seismograph and alert beacon

Straight out of the box, Brinco will deliver you early warnings of both tsunamis and earthquakes. All you have to do is provide an electrical outlet and WiFi access.

A SEISMOMETER | AN EARLY WARNING DEVICE | A COMMUNITY

Brinco is a product of OSOP, an internationally-respected manufacturer of high-powered seismographs and seismic software. OSOP's directors, Branden Christensen and Ángel Rodríguez, have been building seismographs for more than 15 years. OSOP has been investing in Brinco for the last two years. We completed our working prototype in May. Your support of this crowdfunding campaign will allow us to take Brinco into mass production and make it possible for homes, schools, and offices worldwide to get disaster warnings in time to get to safety.

Hardware and applications

- BeagleBone Black (TI AM3358)
- GPRS/GPS cape
- CAN shield
- Arduino as car emulator
- Logistics system (car location and diagnostics)



Hardware and applications

- ESP8266
- Retail selling/notification system



Cloud Infrastructure

Cloud-Oriented Architecture (COA)

Microservices principles

- Domain Driven Design
- Hide Implementation Details
- Decentralization
- Failure Isolation
- Continuous Delivery through DevOps Culture

kleder

Cloud Top 10 Risks (OWASP)

- Accountability & Data Risk
- User Identity Federation
- Regulatory Compliance
- Business Continuity & Resiliency
- User Privacy & Secondary Usage of Data
- Service & Data Integration
- Multi-tenancy & Physical Security
- Incidence Analysis & Forensics
- Infrastructure Security
- Non-production Environment Exposure

kleder

AWS Microservices Example

AWS communication



AWS SDK's

- Android
- Browser (JavaScript)
- iOS
- Java
- .NET
- Node.js (JavaScript)
- PHP
- Python
- Ruby
- Go
- C++

Cloud & Web interfaces

Cloud & Mobile Clients

Amazon IoT Model



Credits https://aws.amazon.com/iot/how-it-works/

Demo

Use case

- We have alarm installation in home
- There is only one sensor for window
- Alarm can be armed
- We want to use mobile device to control alarm system



kleder

Use case – High Level Architecture



Use case – Cloud infrastructure



Alarm Exchange Data

- window
  - 1 – close
  - 0 - open
- lock
  - 0 – disarmed
  - 1 – armed
- alarm
  - 0 – OFF
  - 1 – ON
- alarm_reset
  - Turn OFF alarm button indicator (0 – normal, 1 – pushed, 2- processed)


while (again) {
iN = -1;
again = false;
getline(cin, sInput);
system("cls");
stringstream(sInput) >> dblTemp;
iLength = sInput.length();
if (iLength < 4) {
again = true;
continue;
} else if (sInput[iLength - 3] != '.') {
again = true;

Live Demo

Solution Explanation

```
    GPIO.setup(16, GPIO.OUT)
    GPIO.output(16, True)
    GPIO.output(ALARM_PIN, False)
    GPIO.output(ALARM_LED_PIN, False)
    GPIO.add_event_detect(11, GPIO.FALLING, callback=alarm)

    while True:
        try:
            urllib.request.urlopen('http://www.google.com', timeout=2)
            mqttc = mqtt.Client(client_id=this_id, userdata=this_id)
            mqttc.on_log = on_log
            mqttc.on_message = on_message
            mqttc.on_connect = on_connect
            mqttc.on_disconnect = on_disconnect
            mqttc.on_subscribe = on_subscribe
            mqttc.on_unsubscribe = on_unsubscribe
            mqttc.on_publish = on_publish
            while not (os.path.isfile(CA_CERT)
                       and os.path.isfile(AWS_PEM)
                       and os.path.isfile(AWS_KEY)):
                log.error('lack of cert or keys, watting ... ')
                time.sleep(1)
            mqttc.tls_set(CA_CERT, certfile=AWS_PEM, keyfile=AWS_KEY,
                          tls_version=ssl.PROTOCOL_TLSv1_2)
            log.info("aws-iot-mqtt-pubsub connecting: {0}:{1}"
                     .format(AWS_MQTT_HOST, AWS_MQTT_PORT))
            mqttc.connect(AWS_MQTT_HOST, AWS_MQTT_PORT, 60)
            break
```

Demo IoT code flow



Data JSON

- Outcome data published in “desired”
- Incoming data from “reported” node
- Lock – green LED
- Alarm – red LED

```
{
  "desired": {
    "window": 1,
    "lock": 1,
    "alarm": 0,
    "alarm_reset": 0
  },
  "reported": {
    "window": 1,
    "lock": 1,
    "alarm": 0,
    "alarm_reset": 0
  }
}
```

Android Code Flow



Career Opportunity @ 3mdeb

- Embedded Systems Intern
- Embedded Systems Administrator
- Embedded C Developer
- Embedded Python Developer

- Sent CV to contact@3mdeb.com

Links

- Source code
  - Embedded device code: https://github.com/3mdeb/aws-iot-mqtt-pubsub
  - Mobile Application: https://github.com/rafalkorszun/awsIotExample
- Contact
  - http://kleder.co
  - http://3mdeb.com

kleder

Q&A

kleder

Thank You!