

文件(F) 编辑(E) 格式(O) 查看(V) 帮助(H)

```
<GlobalInfo lang="hr-HR, cs-CZ" name="LastName, FirstName" address="Street, ZipPostal, City, StateProvince" />
<GlobalInfo lang="hu-HU" name="LastName, FirstName" address="City, Street, ZipPostal, StateProvince" />
<GlobalInfo lang="ja-JP, ko-KR" name="LastName, FirstName" address="ZipPostal, StateProvince, City" />
<GlobalInfo lang="kk-KZ" name="FirstName, Initials, LastName" address="Country, StateProvince, City" />
<GlobalInfo lang="ru-RU" name="FirstName, Initials, LastName" address="Country, ZipPostal, StateProvince" />
<GlobalInfo lang="uk-UA" name="LastName, FirstName, Initials" address="Country, ZipPostal, StateProvince" />
<GlobalInfo lang="cy-GB" name="FirstName, Initials, LastName" address="Street, City, StateProvince" />
<GlobalInfo lang="fil-PH" name="FirstName, Initials, LastName" address="Street, ZipPostal, StateProvince" />
</GlobalInfos>
```

```
<system.web>
```

```
<machineKey validationKey="CB2721ABDAF8E9DC516D621D8B8BF13A2C9E8689A25303BF"
decryptionKey="E9D2490BD0075B51D1BA5288514514AF" validation="SHA1" decryption="3DES" />
<!--
```

Set client scripts location to version/scripts, so that request to WebRequest.axd will be :

```
-->
<webControls clientScriptsLocation="/ecp/15.1.225.42/scripts/" />
<!--
```

Enable HTTPOnly flag for server generated cookies.

We used to require secure (HTTPS) cookies too, but CAS-2-CAS scenarios can use just HTTP.

Please note that these settings can be overwritten programmatically. So we specify entries to provide a default settings for all cookies.