

January 17, 2012



**powerbroker<sup>®</sup> identity services**  
*Open Edition*

## 10-Minute Setup Guide for Mac

**Release 6.5**

**beyondtrust<sup>®</sup>**  
*privilege. made simple*

[www.beyondtrust.com](http://www.beyondtrust.com)

BeyondTrust  
2173 Salk Avenue  
Carlsbad, California 92008  
Phone: +1 818-575-4000



# PBIS Open 10-Minute Setup Guide for Mac

Revision/Update Information: January 17, 2012

Software Version: PowerBroker Identity Services Enterprise Edition 6.5

Revision Number: 0

## **COPYRIGHT NOTICE**

Copyright © 2012 BeyondTrust Software, Inc. All rights reserved. Use of this software and/or document, as and when applicable, is also subject to the terms and conditions of the license between the licensee and BeyondTrust Software, Inc. ("BeyondTrust") or BeyondTrust's authorized remarketer, if and when applicable.

## **TRADE SECRET NOTICE**

This software and/or documentation, as and when applicable, and the information and know-how they contain constitute the proprietary, confidential and valuable trade secret information of BeyondTrust and/or of the respective manufacturer or author, and may not be disclosed to others without the prior written permission of BeyondTrust. This software and/or documentation, as and when applicable, have been provided pursuant to an agreement that contains prohibitions against and/or restrictions on copying, modification and use.

## **DISCLAIMER**

BeyondTrust makes no representations or warranties with respect to the contents hereof. Other than, any limited warranties expressly provided pursuant to a license agreement, NO OTHER WARRANTY IS EXPRESSED AND NONE SHALL BE IMPLIED, INCLUDING WITHOUT LIMITATION THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR USE OR FOR A PARTICULAR PURPOSE.

## **LIMITED RIGHTS FARs NOTICE (If Applicable)**

If provided pursuant to FARs, this software and/or documentation, as and when applicable, are submitted with limited rights. This software and/or documentation, as and when applicable, may be reproduced and used by the Government with the express limitation that it will not, without the permission of BeyondTrust, be used outside the Government for the following purposes: manufacture, duplication, distribution or disclosure. (FAR 52.227.14(g)(2)(Alternate II))

## **LIMITED RIGHTS DFARS NOTICE (If Applicable)**

If provided pursuant to DFARS, use, duplication, or disclosure of this software and/or documentation by the Government is subject to limited rights and other restrictions, as set forth in the Rights in Technical Data – Noncommercial Items clause at DFARS 252.227-7013.

## **TRADEMARK NOTICES**

PowerBroker, PowerPassword, and PowerKeeper are registered trademarks of BeyondTrust. PowerSeries, PowerADvantage, PowerBroker Password Safe, PowerBroker Directory Integrator, PowerBroker Management Console, PowerBroker Desktops, PowerBroker Virtualization, PowerBroker Express, PowerBroker Databases, PowerBroker Windows Servers, PowerBroker Windows Desktops, and PowerBroker Identity Services are trademarks of BeyondTrust.

ssh® is a registered trademark of SSH Communications Security Corp in the United States and in certain other jurisdictions. The SSH logo, Tectia and tectia logo are trademarks of SSH Communications Security Corp and may be registered in certain jurisdictions. This application contains software powered by PKAIP®, the leading solution for enabling efficient and secure data storage and transmission. PKAIP® is provided by PKWARE, the inventor and continuing innovator of the ZIP file format. Used with permission.

## **FICTITIOUS USE OF NAMES**

All names of persons mentioned in this document are used fictitiously. Any resemblance to actual persons, living or dead is entirely coincidental.

## **OTHER NOTICES**

If and when applicable the following additional provisions are so noted:

The PowerBroker Identity Services Open software is free to download and use according to the terms of the Limited GPL 2.1 for client libraries and the GPL 2 for daemons. The licenses for PowerBroker Identity Services Enterprise and for PowerBroker Identity Services UID-GID Module are different. For complete information on the software licenses and terms of use for BeyondTrust products, see [www.beyondtrust.com](http://www.beyondtrust.com).



## Contents

<b>PBIS Open 10-Minute Setup Guide for Mac.....</b>	<b>7</b>
Install the Agent on Mac OS X, Join a Domain, and Log On.....	7
Step 1: Download PBIS Open.....	7
Step 2: Install PBIS Open on a Mac.....	7
Step 3: Join Active Directory.....	8
Step 4: Log On with AD Credentials.....	9



## PBIS Open 10-Minute Setup Guide for Mac

PowerBroker Identity Services Open Edition is an agent-based tool that allows you connect Linux, Unix, and Mac OS X computers to Microsoft Active Directory for consistent security policy across your entire environment.

To get started with PBIS Open, you need to install the PBIS agent, join a domain, and log on using Active Directory credentials. You can do so on [Mac OS X](#).

### Install the Agent on Mac OS X, Join a Domain, and Log On

This topic covers installing PowerBroker Identity Services Open Edition on a Mac, connecting it to an Active Directory domain, and logging on with your domain credentials.

Before you deploy PBIS Open in anything other than a test environment, you should read the overview of the agent, the chapter about installing the agent, the chapter about joining a domain, and the chapter about configuring the PBIS services.

#### Step 1: Download PBIS Open


Browse to [www.beyondtrust.com](http://www.beyondtrust.com) and click **Free Software**. Under PowerBroker Identity Services Open Edition click **Download Free Trial**. Enter your information and submit the form.

In the email message that you receive in response to the form you submitted, click the link under the Download section to open a webpage where you can download installers for different operating systems. On the webpage, right-click the download link for your platform and then save the installer to the desktop of your Mac.

**Important:** On an Intel-based Mac, install the **i386** version of the .dmg package. On a Mac that does not have an Intel chip, install the **powerpc** version of the .dmg package. On Mac OS X 10.6 (Snow Leopard), you must use the 10.6 universal installation package.


#### Step 2: Install PBIS Open on a Mac

To install the PBIS agent on a computer running Mac OS X, you must have administrative privileges on the Mac.

1. Log on to the Mac with a local account that has administrative privileges.
2. On the **Apple** menu , click **System Preferences**.
3. Under **Internet & Network**, click **Sharing**, and then select the **Remote Login** check box. Turning on Remote Login lets you access the Mac with SSH after you install PBIS.
4. On the Mac computer, go to the Desktop and double-click the PBIS .dmg file.
5. In the Finder window, double-click the PBIS .mpkg file.
6. Follow the instructions in the installation wizard.

### Step 3: Join Active Directory

After the wizard finishes installing PBIS Open, the Join Active Directory Domain dialog is displayed. If it does not appear or if you want to join the domain later, see the *PowerBroker Identity Services Open Installation and Administration Guide*.



The image shows a macOS dialog box titled "Join Active Directory Domain". It contains the following elements:

- A warning icon and text: "Active Directory requires that computer names be unique in an organization. If you wish, you may rename your computer by changing the name below."
- A "Computer name:" label and a text field containing "mac105int-2".
- A "Domain to join:" label and a text field containing "pbisdemo.com".
- A checked checkbox labeled "Assume default domain for logons".
- A "Specify short domain prefix:" label and an empty text field. Below it, text reads: "Example domain prefix: CORP or leave blank (uses same as domain above)".
- A section titled "Specify an Organizational Unit path for the computer account." containing:
  - A selected radio button labeled "Computers container or existing computer location."
  - An unselected radio button labeled "OU Path:" followed by an empty text field. Below it, text reads: "Example OU Path: Regional/Sales".
- "Cancel" and "Join" buttons at the bottom right.



To join a computer to a domain, you must have administrative privileges on the Mac and be a member of the Domain Administrator security group or have otherwise been granted privileges on the Active Directory domain that allow you to join computers to the domain.

1. In the **Computer name** box, type the local hostname of the Mac without the `.local` extension. Because of a limitation with Active Directory, the local hostname cannot be more than 15 characters. Also, `localhost` is not a valid name.
2. In the **Domain to join** box, enter the fully qualified domain name (FQDN) of your Active Directory domain. Example:  
`engineering.example.com`
3. Under **Organizational Unit**, you can join the computer to an organizational unit (OU) by selecting **OU Path** and then typing a path in the **OU Path** box. The OU path is from the top of the Active Directory domain down to the OU that you want.  
Or, to join the computer to the Computers container, select **Default to "Computers" container**.
4. Click **Join**.

To solve problems, see the *PowerBroker Identity Services Open Installation and Administration Guide*.

## Step 4: Log On with AD Credentials

After you have installed PBIS Open and joined the Mac computer to a domain, you can log on interactively with your Active Directory credentials.

1. Log out of the current session.
2. Log on to the Mac by using the name of your Active Directory user account in the form of `DOMAIN\username`, where `DOMAIN` is the Active Directory domain name.  
Example:

`example.com\kathy`

**Important:** If you log on from the command line, you must use a slash to escape the slash character, making the logon form  
`DOMAIN\\username`.

