

Week 6 Lab Activity - MVC Pattern

Question :-

Create a java program to do the following :

- 1. Design two text box (edit text) for receiving TWO numbers**
- 2. Create a java file and have a method to calculate the sum of it**
- 3. In main Activity(Controller file) java file , call the java file and execute the program**

//xml design file codes

```
<?xml version="1.0" encoding="utf-8"?>

<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"

    xmlns:app="http://schemas.android.com/apk/res-auto"

    xmlns:tools="http://schemas.android.com/tools"

    android:layout_width="match_parent"

    android:layout_height="match_parent"

    android:orientation="vertical"

    tools:context=".MainActivity">


    <EditText

        android:id="@+id/ed1"

        android:layout_width="match_parent"

        android:layout_height="wrap_content"

        android:ems="10"

        android:inputType="text"

        android:hint="enter 1" />
```

```
<EditText
    android:id="@+id/ed2"
    android:layout_width="match_parent"
    android:layout_height="wrap_content"
    android:ems="10"
    android:inputType="text"
    android:hint="enter num2" />
```

```
<Button
    android:id="@+id/b1"
    android:layout_width="match_parent"
    android:layout_height="wrap_content"
    android:text="add" />
```

```
<TextView
    android:id="@+id/tv1"
    android:layout_width="match_parent"
    android:layout_height="wrap_content"
    android:text="TextView" />
```

```
</LinearLayout>
```

//java file for illustrating MVC

package com.example.manoj;

public class model {

```
public int addData(int a, int b)  
{  
    return a+b;  
}  
}
```

//controller

```
package com.example.manoj;
```

```
import androidx.appcompat.app.AppCompatActivity;
```

```
import android.annotation.SuppressLint;
```

```
import android.os.Bundle;
```

```
import android.view.View;
```

```
import android.widget.Button;
```

```
import android.widget.EditText;
```

```
import android.widget.TextView;
```

```
public class MainActivity extends AppCompatActivity {
```

```
    EditText num1,num2;
```

```
    Button btn;
```

```
    model md;
```

```
    TextView tv;
```

```

@SuppressLint("MissingInflatedId")

@Override

protected void onCreate(Bundle savedInstanceState) {

    super.onCreate(savedInstanceState);

    setContentView(R.layout.activity_main);

    md=new model();

    num1=(EditText) findViewById(R.id.ed1);

    num2=(EditText) findViewById(R.id.ed2);

    btn=(Button) findViewById(R.id.b1);

    tv=(TextView)findViewById(R.id.tv1);


    btn.setOnClickListener(new View.OnClickListener() {

        @Override

        public void onClick(View view) {

            String n1=num1.getText().toString();

            String n2=num2.getText().toString();


            int p1=Integer.parseInt(n1);

            int p2=Integer.parseInt(n2);


            int add=md.addData(p1,p2);

            tv.setText("Add"+add);

        }
    }

```

});

}

}