Lab 9: Network Forensics 2

In this lab we will investigate the usage of regular expressions, and using Wireshark filters.

A Detecting content

For Table 1, and using a Wireshark filter, and Table 2, determine the required evidence. An example is:

http contains " $\x89\x50\x4E\x47$ "

No	PCap file	Evidence
1	http://asecuritysite.com/log/with_png.zip	Names of PNG files:
2	http://asecuritysite.com/log/with_pdf.pdf	Names of PDF files:
3	http://asecuritysite.com/log/with_gif.zip	Names of GIF files:
4	http://asecuritysite.com/log/with_jpg.zip	Names of JPG files:
5	http://asecuritysite.com/log/with_mp3.zip	Names of MP3 files:
6	http://asecuritysite.com/log/with_rar.zip	Names of RAR files:
7	http://asecuritysite.com/log/with_avi.zip	Names of AVI files:
8	http://asecuritysite.com/log/with_gz.zip	Names of GZ files:
9	http://asecuritysite.com/log/email_cc2.zip	Email addresses:
10	http://asecuritysite.com/log/email_cc2.zip	Credit card details:
11	http://asecuritysite.com/log/webpage.zip	IP address details:
12	http://asecuritysite.com/log/webpage.zip	Domain name details:

Table 2: Examples of signatures

PNG file	"\x89\x50\x4E\x47"
PDF file	"%PDF"
GIF file	"GIF89a"
ZIP file	"\x50\x4B\x03\x04"
JPEG file	"\xff\xd8"
MP3 file	"\x49\x44\x33"
RAR file	"\x52\x61\x72\x21\x1A\x07\x00"
AVI file	"\x52\x49\x46\x46"
SWF file	"\x46\x57\x53"
GZip file	"\x1F\x8B\x08"
Email addresses	"[a-zA-z0-9%+-]+@[a-zA-z0-9%+-]"
IP address	"[0-9]{1,3}\.[0-9]{1,3}\.[0-9]{1,3}.
Credit card details	"5\d{3}(\s -)?\d{4}(\s -)?\d{4}"
(Mastercard)	
Credit card details	"4\d{3}(\s -)?\d{4}(\s -)?\d{4}"
(Visa):	
Credit card details	"3\d{3}(\s -)?\d{6}(\s -)?\d{5}"
(Am Ex).	
Domain name:	"[a-zA-z0-9\-\.]+\.(com org net mil edu COM ORG NET MIL EDU UK)"

B Tshark

We can also process the network traces using Tshark, which is a command line version of Wireshark. For example we can search for a ZIP file with:

tshark -Y "http matches \"\x50\x4B\x03\x04\\"" -r with_zip.pcap -x -V > list and then view the **list** file.

Now repeat some of the example from the first part, and determine some of the details:

No	PCap file	Evidence
1	http://asecuritysite.com/log/with_png.zip	Frame numbers with content:
		IP addresses involved in exchange:
2	http://asecuritysite.com/log/with_pdf.pdf	Frame numbers with content:
		IP addresses involved in exchange:
3	http://asecuritysite.com/log/with_gif.zip	Frame numbers with content:
		IP addresses involved in exchange:
4	http://asecuritysite.com/log/with_jpg.zip	Frame numbers with content:

	IP addresses involved in exchange:

C Content identification

There are 30 files contained in this evidence bag:

http://asecuritysite.com/evidence.zip

Using a Hex Editor, see if you can match the magic number, and then change the file extension, and see if you can view them.

File	Type	What it contains	
file01			
file02			
file03			
file04			
file05			
file06			
file07			
file08			
file09			
file10			
file11			
file12			
file13			
file14			
file15			
file16			
file17			

file18	
file19	
file20	
file21	
file22	
file23	
file24	
file25	
file26	
file27	
file28	
file29	
file30	
file32	
file33	
file34	
file35	
file36	
file37	
file38	
file39	
file40	

There is a list of magic numbers here: $\underline{\text{http://asecuritysite.com/forensics/magic}}$

Additional

D RegEx

Using regex101.com, enter the following code:

There is not much we can do apart from contacting There is not much we can do apart from contacting f.smith@home.net to see if he would like to reboot the server at 192.168.0.1. If he can do this then I will call him on 444.3212.5431. My credit card details are 4321-4444-5412-2310 and 5430-5411-4333-5123 and my name on the card is Fred Smith. I really like the name domain fred@home. Overall our target areas are SW1 7AF and EH105DT. I tested the server last night, and I think the IP address is 10.0.0.1 and there are two MAC addresses which are 01:23:45:67:89:ab or it might be 00.11.22.33.44.55.

The book we will use is "At Home" and it can be bought on amazon.com or google.com, if you search for 978-1-4302-1998-9. My password is:

a1b2c3

Best regards,

Bert. EH14 1DJ +44 (960) 000 00 00 1/1/2009

Now, using the Python code generator, create Python code to detect the following:

- (i) Email address.
- (ii) MAC address.
- (iii) Credit card details.

Some hints are at: https://asecuritysite.com/dlp/day1

E Splunk

Using Splunk at http:// asecuritysite.com:8000 determine the following. You will be allocated a login. We can use regular expressions to find information. For example, to find the number of accesses from an IP address which starts with "182.", we can use:

```
get | regex _raw="182\.\d{1,3}\.\d{1,3}\.\d{1,3}"
```

Determine the number of accesses for GET from any address which begins with 182:

The security team search for an address that is ending with .22, and do a search with:

```
get | regex _raw="\d{1,3}.\d{1,3}.\d{1,3}.22"
```

But it picks up logs which do not include addresses with .22 at the end. What is the problem with the request, and how would you modify the request:

You are told that there's accesses to a file which ends in "a.html". Using a regular expression, such as:

Outline three HTML files which end with the characters 'a', or an 'e', and have '.html' as an extension:

A simple domain name check is:

If we now try:

```
\texttt{get} \; | \; \mathsf{regex} \; \_\mathsf{raw} = \texttt{"[a-zA-z0-9}-\] + \texttt{`.(com|org|net|mil|edu|COM|ORG|NET|MIL|EDU|UK)"}
```

we will return events with domain names:

Outline which ones have been added:

We can search for email addresses with:

$$get \mid regex \quad raw = "(?[\w\d\.\-]+\@[\w\d\.]+)"$$

Which email addresses are present:

We can search for times using regular expressions, such as:

How many GET requests where there at 22 minutes past the hour:

How many GET requests were made at 14 seconds past the minute: