V0.2.0

1 概述

1.1 关于本手册

Python V0.2.0 Gradio intel-agent

1.2 使用对象

Python

1.3 平台介绍

NVD arXiv CISA OSV

Claude Agent SDK

2 运行环境与启动

2.1 运行环境

Python 3.10 3.13 uv claude-agent-sdk Pydantic PyMongo Gradio Matplotlib pyproject.toml uv.lock

JSON MongoDB

2.2 安装与启动

uv sync --group dev .env.example .env .env

uv run web

GRADIO_SERVER_NAME GRADIO_SERVER_PORT http://127.0.0.1:8001/ 8000

2.3 进入与退出

127.0.0.1 Ctrl+C

3 采集配置

3.1 模型接口设置

.env INTEL_SDK_PROVIDER=deepseek DEEPSEEK_API_KEY DeepSeek deepseek-flash INTEL_SDK_MODEL INTEL_SDK_FAST_MODEL

DeepSeek https://api.deepseek.com/anthropic glm GLM_API_KEY ANTHROPIC_BASE_URL ANTHROPIC_AUTH_TOKEN

3.2 可选增强与存储配置

NVD_API_KEY GLM_API_KEY GLM embedding DeepSeek GLM INTEL_RELEVANCE_ENABLED INTEL_PLAYBOOK_ENABLED INTEL_PLAYBOOK_EMBED

JSON INTEL_MONGO_URI MongoDB INTEL_MONGO_DB MongoDB JSON

3.3 配置生效与状态确认

.env Gradio

“SDK ” Agent verbose trace [fallback]

4 平台首页与任务参数

4.1 功能入口

Collect Trace replay Database Memory Collect
Trace replay Database Memory

4.2 采集参数

Mode full incremental full incremental Incremental focus
prompt injection Window days full
Max rounds 4 Max API calls API 20
1 2 4
Verbose (live agent trace) Run collection Load latest run

4.3 结果区域

Run summary run_id run_mode Collected items

open_gaps stop_reason

5 全量情报采集

5.1 发起全量任务

Collect Mode full Max rounds Max API calls Verbose Run collection

5.2 覆盖范围与判定

RAG 18 Core 15 Extended Core Extended INTEL_COVERAGE_QUOTA 3

5.3 查看和复核结果

run_id

uv run intel-agent full --max-rounds 1 --max-api-calls 4 --verbose run_mode=bootstrap

6 增量情报采集

6.1 发起增量任务

Collect Mode incremental Incremental focus prompt injection agent tool abuse Window days Run collection adaptive OSV

6.2 时间范围与历史水位

NVD arXiv checkpoint 72 INTEL_INCREMENTAL_OVERLAP_HOURS --since uv run intel-agent incremental --focus "prompt injection" --since 2026-09-01 --max-rounds 1 --max-api-calls 4 --verbose UTC --window-days

6.3 理解增量结果

INTEL_INCREMENTAL_STRATEGY=legacy

7 情报态势与追踪回放

7.1 查看情报态势

“ ” Core

12 Extended

Extended Core

7.2 实时追踪

Collect Agent verbose trace

[fallback] API-call budget exhausted

7.3 回放历史日志

Trace replay run_id Load trace JSONL data/intel_agent/traces JSONL

--verbose Verbose

8 历史查询与数据导出

8.1 运行历史

Database Refresh store status Runs Limit List runs run_id

Download runs CSV CSV Collect Load latest run uv run intel-agent latest

8.2 情报条目检索

Items (global intel) Source Topic Text search Filter by run_id Limit Query items

item_id / Refresh source list run_id

8.3 导出与单次运行详情

Download items CSV data/exports Limit CSV UTF-8

Run detail run_id Load run + its items engine SDK

9 技巧库与存储维护

9.1 检索技巧库

Memory Refresh memory status Playbook (query strategies) Topic Source filter Status Text search Limit Load playbook entry_id

9.2 相关性缓存

Relevance embedding cache Topic Min embedding score Limit Load cache embedding CSV

9.3 文件保存与备份

JSON data/intel_runs/<run_id>.json latest.json data/intel_agent/playbook.jsonl data/intel_agent/relevance_cache.jsonl traces MongoDB runs items item_id

10 常见问题与操作示例

10.1 常见问题处理

[fallback]

INTEL_MONGO_URI Compose mongo:27017 27018

10.2 一次小预算采集示例

SDK deepseek-flash Collect full Max rounds 1 Max API calls 2 Verbose run_id Database run_id CSV Trace replay run_id

10.3 日常使用顺序