


15-112

Fundamentals of Programming

Week 2 - Lecture 1: Loops



Basic Building Blocks

Statements

Tells the computer to do something.

Data Types

Data is divided into different types.

Variables

Allows you to store data and access stored data.

Operators

Allows you to manipulate data.

Conditional Statements

Executes statements if a condition is satisfied.

Functions

Mini self-contained programs.

Basic Building Blocks

Statements

Tells the computer to do something.

Data Types

Data is divided into different types.

Variables

Allows you to store data and access stored data.

Operators

Allows you to manipulate data.

Conditional Statements

Executes statements if a condition is satisfied.

Functions

Mini self-contained programs.

Loops

Execute a block of code multiple times.

Loops give you wings !

My first ever program

**


*

My first ever program

```
print("*****")
print("*****")
print("*****")
print("*****")
print("*****")
print("*****")
print("*****")
print("*****")
print("*****")
print("*****")
print("****")
print("***")
print("**")
print("*")
```

There is a
better way!


2 types of loops in Python



while loop

for loop

while loop

 instruction1
 while(*expression*) :
 instruction2
 instruction3
 instruction4

The code in the block should change something related to the *expression*.

iteration: a single execution of the instructions in the loop body.

while loop example

```
def getPositiveInteger():  
    userInput = 0  
    while(userInput <= 0):  
        userInput = int(input("Enter a positive integer: "))  
    return userInput
```

while loop example

```
x = 0
```

```
while(x < 5):
```

```
    print("Value of x is", x)
```

```
    x += 10
```

```
    print("This line will be printed!")
```

```
print("bye")
```

while loop

Repeating a block a certain number of times:

```
counter = 1

while(counter <= 10):
    instruction1
    instruction2
    counter += 1
```

But never use while loops to do this.
Use for loops.

while loop example

```
def countToN(n):  
    counter = 1  
    while(counter <= n):  
        print(counter)  
        counter += 1
```

while loop example

```
def sumToN(n):  
    counter = 1  
    total = 0  
    while(counter <= n):  
        total += counter  
        counter += 1  
    return total
```

while loop example

```
def sumFromMToN(m, n):  
    counter = m  
    total = 0  
    while(counter <= n):  
        total += counter  
        counter += 1  
    return total
```

Again: never use while loops to do this.
Use for loops.

Common Loop Bug I

Off by 1 error

```
def sumToN(n):  
    total = 0  
    counter = 0  
    while (counter <= n):  
        counter += 1  
        total += counter  
    return total
```

Loop conditions that results in the loop body being executed either:

- 1 time too few
- 1 time too many

Manually check the first and last iterations!

Common Loop Bug 2

Infinite Loops

```
counter = 1
```

```
while (counter < 10):
```

```
    # Do some awesome complicated computation
```

```
    # ...
```

```
    # Then forget to increment counter
```

In the body you have to change something related to the *condition* being checked.

Example: leftmost digit

Write a function that

- takes an integer **n** as input,
- returns its leftmost digit.

e.g. 409283402013 should return 4

Idea:

Repeatedly get rid of rightmost digit until one digit is left.

```
def leftmostDigit(n):  
    while (n >= 10):  
        n = n // 10  
    return n
```

Example: leftmost digit

Write a function that

- takes an integer **n** as input,
- returns its leftmost digit.

e.g. 409283402013 should return 4

Idea:

Repeatedly get rid of rightmost digit until one digit is left.

```
def leftmostDigit(n):  
    n = abs(n)  
    while (n >= 10):  
        n = n // 10  
    return n
```

Example: n'th Awesome number

A number $m \geq 0$ is called “Awesome” if it is divisible by 3 or is divisible by 5.

Write a function that

- takes a positive number n as input,
- returns the n 'th Awesome number. (counting starts from 0)

Example: n'th Awesome number

A number $m \geq 0$ is called “Awesome” if it is divisible by 3 or is divisible by 5.

Write a function that

- takes a positive number n as input,
- returns the n 'th Awesome number. (counting starts from 0)

Pictorial solution:

0 1 2 3 4 5 6 7 8 9 ...



is Awesome?

yes

$n = 4$

found = 1

Example: n'th Awesome number

A number $m \geq 0$ is called “Awesome” if it is divisible by 3 or is divisible by 5.

Write a function that

- takes a positive number n as input,
- returns the n 'th Awesome number. (counting starts from 0)

Pictorial solution:

0 1 2 3 4 5 6 7 8 9 ...
 ↑

is Awesome?

no

$n = 4$

found = 1

Example: n'th Awesome number

A number $m \geq 0$ is called “Awesome” if it is divisible by 3 or is divisible by 5.

Write a function that

- takes a positive number n as input,
- returns the n 'th Awesome number. (counting starts from 0)

Pictorial solution:

0 1 2 3 4 5 6 7 8 9 ...



is Awesome?

no

$n = 4$

found = 1

Example: n'th Awesome number

A number $m \geq 0$ is called “Awesome” if it is divisible by 3 or is divisible by 5.

Write a function that

- takes a positive number n as input,
- returns the n 'th Awesome number. (counting starts from 0)

Pictorial solution:

0 1 2 3 4 5 6 7 8 9 ...



is Awesome?

yes

$n = 4$

found = 2

Example: n'th Awesome number

A number $m \geq 0$ is called “Awesome” if it is divisible by 3 or is divisible by 5.

Write a function that

- takes a positive number n as input,
- returns the n 'th Awesome number. (counting starts from 0)

Pictorial solution:

0 1 2 3 4 5 6 7 8 9 ...



is Awesome?

no

$n = 4$

found = 2

Example: n'th Awesome number

A number $m \geq 0$ is called “Awesome” if it is divisible by 3 or is divisible by 5.

Write a function that

- takes a positive number n as input,
- returns the n 'th Awesome number. (counting starts from 0)

Pictorial solution:

0 1 2 3 4 5 6 7 8 9 ...



is Awesome?

yes

$n = 4$

found = 3

Example: n'th Awesome number

A number $m \geq 0$ is called “Awesome” if it is divisible by 3 or is divisible by 5.

Write a function that

- takes a positive number n as input,
- returns the n 'th Awesome number. (counting starts from 0)

Pictorial solution:

0 1 2 3 4 5 6 7 8 9 ...



is Awesome?

yes

$n = 4$

found = 4

Example: n'th Awesome number

A number $m \geq 0$ is called “Awesome” if it is divisible by 3 or is divisible by 5.

Write a function that

- takes a positive number n as input,
- returns the n 'th Awesome number. (counting starts from 0)

Pictorial solution:

0 1 2 3 4 5 6 7 8 9 ...



is Awesome?

no

$n = 4$

found = 4

Example: n'th Awesome number

A number $m \geq 0$ is called “Awesome” if it is divisible by 3 or is divisible by 5.

Write a function that

- takes a positive number n as input,
- returns the n 'th Awesome number. (counting starts from 0)

Pictorial solution:

0 1 2 3 4 5 6 7 8 9 ...



is Awesome?

no

$n = 4$

found = 4

Example: n'th Awesome number

A number $m \geq 0$ is called “Awesome” if it is divisible by 3 or is divisible by 5.

Write a function that

- takes a positive number n as input,
- returns the n 'th Awesome number. (counting starts from 0)

Pictorial solution:

0 1 2 3 4 5 6 7 8 9 ...



$n = 4$

is Awesome?

found = 5

yes \longrightarrow return 9

Example: n'th Awesome number

Pictorial solution:

0 1 2 3 4 5 6 7 8 9 ...



$n = 4$

is Awesome?

found = 5

yes \rightarrow return 9

Algorithm:

- Let found = 0
- Go through every number 0, 1, 2, 3, ...:
 - if the number is Awesome, increment found
- When found > n , return corresponding number

Example: n'th Awesome number

- Let found = 0
- Go through every number 0, 1, 2, 3, ... :
 - if the number is Awesome, increment found
- When found > n, return corresponding number

def nthAwesome(n):

Example: n'th Awesome number

- Let found = 0
- Go through every number 0, 1, 2, 3, ... :
 - if the number is Awesome, increment found
- When found > n, return corresponding number

```
def nthAwesome(n):  
    found = 0
```


Example: n'th Awesome number

- Let found = 0
- Go through every number 0, 1, 2, 3, ... :
 - if the number is Awesome, increment found
- When found > n, return corresponding number

def nthAwesome(n):

 found = 0

 guess = 0

Example: n'th Awesome number

- Let found = 0
- Go through every number 0, 1, 2, 3, ... :
 - if the number is Awesome, increment found
- When found > n, return corresponding number

def nthAwesome(n):

found = 0

guess = -1

Example: n'th Awesome number

- Let found = 0
- Go through every number 0, 1, 2, 3, ...:
 - if the number is Awesome, increment found
- When found > n, return corresponding number

```
def nthAwesome(n):  
    found = 0  
    guess = -1  
    while (found <= n):
```

Example: n'th Awesome number

- Let found = 0
- Go through every number 0, 1, 2, 3, ... :
 - if the number is Awesome, increment found
- When found > n, return corresponding number

```
def nthAwesome(n):  
    found = 0  
    guess = -1  
    while (found <= n):  
        guess += 1
```

Example: n'th Awesome number

- Let found = 0
- Go through every number 0, 1, 2, 3, ...:
 - if the number is Awesome, increment found
- When found > n, return corresponding number

```
def nthAwesome(n):  
    found = 0  
    guess = -1  
    while (found <= n):  
        guess += 1  
        if (isAwesome(guess)):
```

Example: n'th Awesome number

- Let found = 0
- Go through every number 0, 1, 2, 3, ...:
 - if the number is Awesome, increment found
- When found > n, return corresponding number

```
def nthAwesome(n):  
    found = 0  
    guess = -1  
    while (found <= n):  
        guess += 1  
        if (isAwesome(guess)):  
            found += 1
```

Example: n'th Awesome number

- Let found = 0
- Go through every number 0, 1, 2, 3, ...:
 - if the number is Awesome, increment found
- When found > n, return corresponding number

```
def nthAwesome(n):  
    found = 0  
    guess = -1  
    while (found <= n):  
        guess += 1  
        if (isAwesome(guess)):  
            found += 1  
    return guess
```

Example: n'th Awesome number


```
def nthAwesome(n):  
    found = 0  
    guess = -1  
    while (found <= n):  
        guess += 1  
        if (isAwesome(guess)):  
            found += 1  
    return guess
```

```
def nthAwesome(n):  
    found = 0  
    guess = 0  
    while (found <= n):  
        if (isAwesome(guess)):  
            found += 1  
            guess += 1  
    return guess - 1
```

```
def isAwesome(m):  
    return ((m % 3) == 0) or ((m % 5) == 0)
```


2 types of loops in Python

while loop



for loop

for loop

for *var-name* **in** *sequence*:
 loop-body

```
for x in [1, 2, 3, 4, 5]:  
    print(x)
```



list (a data type in Python)

1st iteration: x = 1

2nd iteration: x = 2

3rd iteration: x = 3

4th iteration: x = 4

5th iteration: x = 5

for loop

for *var-name* **in** *sequence*:
 loop-body

```
for x in "Hello":  
    print(x)
```

A string is a sequence too

1st iteration: x = "H"

2nd iteration: x = "e"

3rd iteration: x = "l"

4th iteration: x = "l"

5th iteration: x = "o"

for loop

for *var-name* **in** *sequence*:
 loop-body

$\text{range}(n) \approx [0, 1, 2, \dots, n-1]$

```
for x in [0, 1, 2, 3, 4]:  
    print(x)
```

```
for x in range(5):  
    print(x)
```

for loop

for *var-name* **in** *sequence*:
 loop-body

```
def sumToN(n):  
    total = 0  
    for x in range(n+1):  
        total += x  
    return total
```

```
def sumToN(n):  
    total = 0  
    x = 0  
    while (x <= n):  
        total += x  
        x += 1  
    return total
```

For loop is the right choice here!

for loop

for *var-name* **in** *sequence*:
 loop-body

$\text{range}(m, n) \approx [m, m+1, m+2, \dots, n-1]$

```
def sumFromMToN(m, n):  
    total = 0  
    for x in range(m, n+1):  
        total += x  
    return total
```

for loop

for *var-name* **in** *sequence*:
 loop-body

$\text{range}(m, n, k) \approx [m, m+k, m+2k, \dots]$

```
def sumEveryKthFromMToN(m, n, k):  
    total = 0  
    for x in range(m, n+1, k):  
        total += x  
    return total
```

for loop

```
def sumOfOddsFromMToN(m, n):  
    total = 0  
    for x in range(m, n+1):  
        if (x % 2 == 1):  
            total += x  
    return total
```


for loop

```
def sumOfOddsFromMToN(m, n):  
    total = 0  
    for x in range(m, n+1):  
        if (x % 2 == 1):  
            total += x  
    return total
```

```
def sumOfOddsFromMToN(m, n):  
    if (m % 2 == 0): m += 1  
    total = 0  
    for x in range(m, n+1, 2):  
        total += x  
    return total
```

for loop

```
def sumOfOddsFromMToN(m, n):  
    if (n % 2 == 0): n -= 1  
    total = 0  
    for x in range(n, m-1, -2):  
        total += x  
    return total
```

Unclear code!!!

for loop vs while loop

```
for x in range(10):  
    print(x)
```

```
x = 0  
while(x < 10):  
    print(x)  
    x += 1
```

Use while loop when the number of iterations is *indefinite*.

e.g. continue to do something until a certain event

Exercise: Testing primality

Write a function that:

- Gets a positive integer input
- Returns **True** if the integer is **prime**
- Returns **False** otherwise

prime:

- greater than 1,
- is only divisible by 1 and itself

Exercise: Testing primality

Algorithm:

- Let n denote the input number.
- Go through every number from 2 to $n-1$.
- If one of these numbers divides n , then n is not prime.
- Otherwise, n is prime.

Exercise: Testing primality

Algorithm:

- Let n denote the input number.
- Go through **every** number from 2 to $n-1$.
- **If** one of these numbers divides n , then n is not prime.
- Otherwise, n is prime.

Exercise: Testing primality

- Let **n** denote the input number.
- Go through **every** number from 2 to **n-1**.
- **If** one of these numbers divides **n**, then **n** is not prime.
- Otherwise, **n** is prime.

```
def isPrime(n):  
    for possibleFactor in range(2, n):  
        # Check if possibleFactor divides n
```

Exercise: Testing primality

- Let n denote the input number.
- Go through **every** number from 2 to $n-1$.
- **If** one of these numbers divides n , then n is not prime.
- Otherwise, n is prime.

```
def isPrime(n):  
    for possibleFactor in range(2, n):  
        if (n % possibleFactor == 0): return False
```


Exercise: Testing primality

- Let n denote the input number.
- Go through **every** number from 2 to $n-1$.
- **If** one of these numbers divides n , then n is not prime.
- Otherwise, n is prime.

```
def isPrime(n):  
    for possibleFactor in range(2, n):  
        if (n % possibleFactor == 0): return False  
    return True
```

Exercise: Testing primality

- Let n denote the input number.
- Go through **every** number from 2 to $n-1$.
- **If** one of these numbers divides n , then n is not prime.
- Otherwise, n is prime.

```
def isPrime(n):  
    if (n < 2): return False  
    for possibleFactor in range(2, n):  
        if (n % possibleFactor == 0): return False  
    return True
```

Start thinking about running time

```
def isPrime(n):  
    if (n < 2): return False  
    for x in range(2, n):  
        if(n % x == 0): return False  
    return True
```

How many iterations?

In the worst case?
(worst possible n)

$\sim n$

What if the input is

2037035976334486086268445688409378161051468393665936250636140449354381299763336706183397371

(length of the input = number of digits = 90 $\sim \log n$)

Start thinking about running time

```
def fasterIsPrime(n):  
    if (n < 2): return False  
    maxFactor = round(n**0.5)  
    for x in range(2, maxFactor + 1):  
        if(n % x == 0): return False  
    return True
```

How many iterations?

In the worst case?
(worst possible n)

$\sim n^{0.5}$

Start thinking about running time

```
def fasterIsPrime(n):  
    if (n < 2): return False  
    if (n == 2): return True  
    if (n % 2 == 0): return False  
    maxFactor = round(n**0.5)  
    for x in range(3, maxFactor + 1, 2):  
        if (n % x == 0): return False  
    return True
```

How many iterations?

In the worst case?
(worst possible n)

$\sim n^{0.5} / 2$

Example: Find the n'th prime

Write a program that:

- Gets a positive integer **n** as input
 - Returns the **n**'th prime number
- Let found = **0**
 - Go through every number 2, 3, 4, 5, ... :
 - if the number is prime, increment found
 - When found > **n**, return the corresponding prime

Remember: We start counting from 0.

Example: Find the n'th prime

- Let found = 0
- Go through every number 2, 3, 4, 5, ... :
 - if the number is prime, increment found
- When found > n, return the corresponding prime

```
def nthPrime(n):  
    found = 0  
    guess = 0  
    while (found <= n):  
        guess += 1  
        if (isPrime(guess)):  
            found += 1  
    return guess
```

Need to use
while loop

Example: The factoring problem

Write a function that:

- gets a positive integer as input
- returns the smallest *factor* $\neq 1$


factor: divides the integer with no remainder.

Exercise

Example: The factoring problem

Why you should care about this problem:

If there is an efficient program to solve
the factoring problem



can break most cryptographic systems
used on the internet!


break
continue

break

Break out of the loop

```
def countToN(n):  
    counter = 1  
    while(True):  
        print(counter)  
        if(counter == n):  
            break  
        counter += 1
```

once this is executed,
you leave the loop body



break

In a while loop, condition is checked at the beginning

```
while (expression) :  
    ...
```

Using a break statement, can check condition anywhere

```
while (True) :  
    ...  
    if (expression) :  
        break  
    ...
```

break

Break out of the loop

```
def sumGivenNumbers():  
    total = 0  
    while(True):  
        x = input("Enter number (or 'done' to quit): ")  
        if(x == "done"):  
            break  
        else:  
            total += int(x)  
    return total  
  
print(sumGivenNumbers())
```

continue

Break out of the current iteration

```
def sumOfOddsToN(n):  
    total = 0  
    for x in range(1, n+1):  
        if(x % 2 == 0):  
            continue  
        total += x  
    return total
```

continue



once this is executed,
you skip to the next iteration

continue

Break out of the current iteration

```
def multiplyGivenNumbers():  
    # if 0 is given as input, we ignore it  
    product = 1  
    while(True):  
        x = input("Enter number (or 'done' to quit): ")  
        if(x == "done"):  
            break  
        elif(int(x) == 0):  
            continue  
        product *= int(x)  
    return product  
  
print(multiplyGivenNumbers())
```

Nested Loops

Nested loops

Many situations require one loop inside another loop.

```
for y in range(10):  
    for x in range(8):  
        # Body of the nested loop
```

Nested loops

Many situations require one loop inside another loop.

```
for y in range(10):  
    for x in range(8):  
        print("Hello")
```

How many times will “Hello” get printed?

Nested loops

Many situations require one loop inside another loop.

```
for y in range(4):  
    for x in range(y):  
        print("Hello")
```

y	# iterations of inner loop
0	0
1	1
2	2
3	3

How many times will “Hello” get printed?

Example: Draw a rectangle

Write a function that:

- Gets two integers, **height** and **width** as input
- Prints a rectangle with those dimensions

height = 4, width = 3

```
* * *  
* * *  
* * *  
* * *
```

Repeat 4 times:

- Print a row (3 stars)

Example: Draw a rectangle

Write a function that:

- Gets two integers, **height** and **width** as input
- Prints a rectangle with those dimensions

height = 4, width = 3

```
* * *  
* * *  
* * *  
* * *
```

Repeat 4 times:

Repeat 3 times:

- Print a star

Skip a line

Example: Draw a rectangle

Write a function that:

- Gets two integers, **height** and **width** as input
- Prints a rectangle with those dimensions

height = 4, width = 3

```
* * *  
* * *  
* * *  
* * *
```

```
for row in range(4):  
    for col in range(3):  
        print("*", end=" ")  
    print()
```

Example: Draw a rectangle

Write a function that:

- Gets two integers, **height** and **width** as input
- Prints a rectangle with those dimensions

height = 4, width = 3

```
* * *  
* * *  
* * *  
* * *
```

```
def printRectangle(height, width):  
    for row in range(height):  
        for col in range(width):  
            print("*", end= " ")  
        print()
```


Example

```
for y in range(4):  
    for x in range(5):  
        print("(" , x , "," , y , ")") , end=" "  
    print()
```

x →

y	(0 , 0)	(1 , 0)	(2 , 0)	(3 , 0)	(4 , 0)
↓	(0 , 1)	(1 , 1)	(2 , 1)	(3 , 1)	(4 , 1)
	(0 , 2)	(1 , 2)	(2 , 2)	(3 , 2)	(4 , 2)
	(0 , 3)	(1 , 3)	(2 , 3)	(3 , 3)	(4 , 3)

Example

```
for y in range(4):  
    for x in range(y):  
        print("(" , x , "," , y , ")", end=" ")  
    print()
```

```
\n  
( 0 , 1 )  
( 0 , 2 ) ( 1 , 2 )  
( 0 , 3 ) ( 1 , 3 ) ( 2 , 3 )
```

Example

```
for y in range(1, 10):  
    for x in range(1, 10):  
        print(y*x, end=" ")  
    print()
```

Multiplication table

```
for y in range(1, 10):  
    for x in range(1, 10):  
        print(y*x, end=" ")  
    print()
```

1	2	3	4	5	6	7	8	9
2	4	6	8	10	12	14	16	18
3	6	9	12	15	18	21	24	27
4	8	12	16	20	24	28	32	36
5	10	15	20	25	30	35	40	45
6	12	18	24	30	36	42	48	54
7	14	21	28	35	42	49	56	63
8	16	24	32	40	48	56	64	72
9	18	27	36	45	54	63	72	81

A trick to get rid of nested loops

Write a function for the inner loop.

Example: Write a function that:

- Gets an integer **height** as input
- Prints a right-angled triangle of that height

height = 5

**

*

```
def printStars(n):  
    for x in range(n):  
        print("*", end="")
```

```
def printTriangle(height):  
    for x in range(height):  
        printStars( ? )  
    print()
```

A trick to get rid of nested loops

Write a function for the inner loop.

Example: Write a function that:

- Gets an integer **height** as input
- Prints a right-angled triangle of that height

height = 5

**

*

```
def printStars(n):  
    for x in range(n):  
        print("*", end="")
```

```
def printTriangle(height):  
    for x in range(height):  
        printStars(height - x)  
    print()
```



```
#include <stdio.h>
int main(void)
{
    int count;

    for (count = 1; count <= 500; count++)
        printf("I will not throw paper airplanes in class.");
    return 0;
}
```

AMEND 10-3

NICE TRY.

