

SCANNING AND ENUMERATION

Ethical Hacking and Penetration


Eng. Zahra Rajeh, M.Sc.

OUTLINE

- TCP/Ip Networking
- Port Numbering
- Identifying Live Hosts
- Port Scanning
- Scanning tools
- Evasion
- Vulnerability Scanning
- Enumeration

INTRODUCTION

Scanning is the process of discovering systems on the network and taking a look at what open ports and applications may be running. With footprinting, we wanted to know how big the network was and some general information. In scanning, we'll go into the network and start touching each device to find out more about it.



TCP/IP NETWORKING

CONNECTIONLESS COMMUNICATION (UDP)


No connection is established before data transmission.

Data is sent immediately (fire-and-forget).

Fast and low overhead.

Does not guarantee delivery, ordering, or error recovery.

Suitable for applications where speed is more important than reliability (e.g., DNS, DHCP, VoIP).



CONNECTION-ORIENTED COMMUNICATION (TCP)

Establishes a connection before transmitting data.

Uses the Three-Way Handshake to initiate communication.

Provides reliable, ordered, and error-checked data delivery.

Supports acknowledgments, retransmissions, and flow control.

Suitable for applications requiring reliable communication (e.g., HTTP, HTTPS, FTP, SSH).

Source Port		Destination Port	
Sequence Number			
Acknowledgment Number			
Offset	Reserved	Flags URG ACK PSH RST SYN FIN	Window
Checksum			
Options			Padding
Data			

TCP COMMUNICATION FLAGS

- The TCP header contains six flags that control the transmission of data across a TCP connection.
- Four of these flags (SYN, ACK, FIN, and RST) govern the establishment, maintenance, and termination of a connection.
- The other two flags (PSH and URG) provide instructions to the system.
- The size of each flag is 1 bit.
- When a flag value is set to 1, that flag is turned on.



TCP COMMUNICATION FLAGS

SYN (Synchronize): This flag is set during initial communication establishment. It indicates negotiation of parameters and sequence numbers.

ACK (Acknowledgment): This flag is set as an acknowledgment to SYN flags. This flag is set on all segments after the initial SYN flag.

RST (Reset): This flag forces a termination of communications (in both directions).

FIN (Finish): This flag signifies an ordered close to communications.


PSH (Push): This flag forces the delivery of data without concern for any buffering. In other words, the receiving device need not wait for the buffer to fill up before processing the data.

URG (Urgent): When this flag is set, it indicates the data inside is being sent out of band. Cancelling a message mid-stream is one example.

TCP THREE-WAY HANDSHAKE

Establishes a reliable TCP connection before data transmission by synchronizing sequence numbers between the client and server.

Step	Flags	Description
1. SYN	SYN	Client requests a connection and sends an initial sequence number (Seq = x) .
2. SYN-ACK	SYN, ACK	Server accepts the request, acknowledges the client's sequence number (Ack = x + 1), and sends its own sequence number (Seq = y) .
3. ACK	ACK	Client acknowledges the server's sequence number (Ack = y + 1), completing the connection setup.



PORT NUMBERING

WHAT IS A PORT?

A **port number** is a logical identifier used by TCP and UDP to determine which application should receive incoming data.

How It Works

Every TCP/UDP packet contains:

- **Source Port** (sender's application)
- **Destination Port** (receiver's application)

The operating system uses the destination port to deliver the packet to the correct application.

WHAT IS A PORT?

Examples

- Web browser → **HTTP (Port 80)**
- Email client → **SMTP (Port 25)**
- Secure web → **HTTPS (Port 443)**

Think of a port as a room number in a building.
The IP address identifies the building, while the port identifies the correct room (application).

COMMON WELL-KNOWN PORTS

Port	Protocol	Service	Port	Protocol	Service
20/21	FTP	File Transfer Protocol	110	POP3	Email Retrieval
22	SSH	Secure Remote Login	143	IMAP	Email Retrieval
23	Telnet	Remote Login (Unencrypted)	161	SNMP	Network Management
25	SMTP	Email Sending	389	LDAP	Directory Services
53	DNS	Domain Name Service	443	HTTPS	Secure Web Browsing
67/68	DHCP	Automatic IP Assignment	445	SMB	Windows File Sharing
69	TFTP	Trivial File Transfer	3389	RDP	Remote Desktop
80	HTTP	Web Browsing			

PORT STATES

State	Meaning
LISTENING	Waiting for an incoming connection.
ESTABLISHED	Active connection between two hosts.
CLOSE_WAIT	Remote host has closed the connection.
TIME_WAIT	Local host has closed the connection but waits for delayed packets before fully closing.

Viewing Port States in Windows:

```
cmd>>netstat -an
```


SCANNING METHODOLOGY


Scanning is the process of actively collecting information about a target system or network after reconnaissance. It helps identify **live hosts, open ports, running services, operating systems, and potential vulnerabilities.**

Scanning methodology phases include the following steps:

1. Check for live systems. Something as simple as a ping can provide this. This gives you a list of what's actually alive on your network subnet
2. Check for open ports. Once you know which IP addresses are active, find what ports they're listening on.
3. Scan beyond IDS. Sometimes your scanning efforts need to be altered to avoid those pesky intrusion detection systems.

SCANNING METHODOLOGY

4. Perform banner grabbing. Banner grabbing and OS fingerprinting will tell you what operating system is on the machines and which services they are running.
5. Scan for vulnerabilities. Perform a more focused look at the vulnerabilities these machines haven't been patched for yet.
6. Draw network diagrams. A good network diagram will display all the logical and physical pathways to targets you might like.
7. Prepare proxies. This obscures your efforts to keep you hidden.





IDENTIFYING LIVE HOSTS

DISCOVER ACTIVE SYSTEMS

What is Host Discovery?

Host discovery is the process of identifying which devices on a network are **online (alive)** before performing further scanning.

Why is it Important?

- Identifies active hosts
- Eliminates inactive IP addresses
- Reduces scanning time
- Focuses later scans on reachable systems

Common Methods

- ICMP Ping
- ARP Scan (Local networks)
- TCP Ping
- UDP Ping

ICMP AND PING


What is ICMP?

Internet Control Message Protocol (ICMP) is a Network Layer protocol used for:

- Error reporting
- Network diagnostics
- Connectivity testing

ICMP AND PING

Type	Name	Purpose
0	Echo Reply	Host responds to a ping
3	Destination Unreachable	Host or network cannot be reached
8	Echo Request	Ping request sent by the scanner



NOTE: If a host replies with Echo Reply (Type 0), it is considered alive.

PING SWEEP

A Ping Sweep sends ICMP Echo Requests to multiple IP addresses within a network to discover active hosts.

Advantages

Fast

Simple

Efficient for discovering live hosts

Limitations

Firewalls may block ICMP.

Many systems disable ping responses.

IDS/IPS may detect ping sweeps.

Less effective in some IPv6 environments.

HOST DISCOVERY TOOLS

Tool	Purpose
Nmap / Zenmap	Host discovery and network scanning
Angry IP Scanner	Fast IP scanning
Advanced IP Scanner	Windows network scanner
SolarWinds Engineer Toolset	Network administration and discovery
OPUtils	IP address and switch management
SuperScan	Port and host scanner
Pinkie	Lightweight network utility

NOTE: Nmap is the most commonly used host discovery tool

PORT SCANNING

PORT SCANNING

Port scanning is the process of sending packets to a target system to determine which TCP/UDP ports are open, closed, or filtered.

Objectives

- Discover running services
- Identify open ports
- Detect operating systems and applications
- Find potential attack entry points


How It Works

A port scanner manipulates **TCP flags** and analyzes the target's responses to determine the state of each port.

COMMON TCP PORT SCAN TYPES

Scan Type	Also Called	Main Feature
TCP Connect Scan	Full Open Scan	Completes the TCP three-way handshake
SYN Scan	Half-Open / Stealth Scan	Stops before completing the handshake
FIN / NULL / XMAS Scan	Inverse TCP Flag Scan	Uses unusual TCP flags to probe ports
Idle Scan	Zombie Scan	Uses a third-party (idle) host to hide the attacker's IP

TCP CONNECT SCAN VS. SYN SCAN



INVERSE TCP FLAG SCANS “FIN / NULL / XMAS SCANS”

These scans send unusual TCP flag combinations instead of a SYN packet.

scanning type

Scan Type	Flags Sent
FIN Scan	FIN
NULL Scan	No Flags
XMAS Scan	FIN + PSH + URG

Expected Responses

Port State	Response
Open	No Response
Closed	RST

NOTE: the Purpose of these types of scan is to bypass simple firewalls and reduce detection

IDLE (ZOMBIE) SCAN

Instead of scanning the target directly, the attacker uses an idle (zombie) host to perform the scan.


How It Works

- Identify an idle (zombie) host.
- Send spoofed packets using the zombie's IP.
- Observe changes in the zombie's IP Identification (IPID) value.
- Determine whether the target port is open or closed.

IDLE (ZOMBIE) SCAN

Advantages

- Hides the attacker's real IP address
- Very stealthy
- Difficult to trace



SCANNING TOOLS

NMAP

- Network Mapper “Nmap” (<https://nmap.org>) is a security scanner for network exploration and hacking.
- It allows you to discover hosts, ports, and services on a computer network, thus creating a "map" of the network.
- It includes many mechanisms for port scanning (TCP and UDP), OS detection, version detection, ping sweeps, and so on.
- It sends specially crafted packets to the target host and then analyzes the responses to accomplish its goal.
- It scans networks of literally hundreds of thousands of machines.

NMAP

- Either a network administrator or an attacker can use this tool for their specific needs.
- Network administrators can use Nmap for network inventory, managing service upgrade schedules, and monitoring host or service uptime.
- Attackers use Nmap to extract information such as live hosts on the network, open ports, services (application name and version), type of packet filters/firewalls, MAC details, and OSs along with their versions.

NMAP

Syntax:

Nmap <option><Target IP address>

```
root@ip-10-10-228-132: ~  
File Edit View Search Terminal Help  
root@ip-10-10-228-132:~# nmap 10.10.228.0/24  
  
Starting Nmap 7.60 ( https://nmap.org ) at 2023-09-08 14:04 BST  
Nmap scan report for ip-10-10-228-37.eu-west-1.compute.internal (10.10.228.37)  
Host is up (0.00066s latency).  
Not shown: 998 closed ports  
PORT      STATE SERVICE  
22/tcp    open  ssh  
10000/tcp  open  snet-sensor-mgmt  
MAC Address: 02:08:4D:69:A1:B5 (Unknown)  
  
Nmap scan report for ip-10-10-228-45.eu-west-1.compute.internal (10.10.228.45)  
Host is up (0.00034s latency).  
Not shown: 999 closed ports  
PORT      STATE SERVICE  
22/tcp    open  ssh  
MAC Address: 02:5D:B5:5B:98:D5 (Unknown)  
  
Nmap scan report for ip-10-10-228-55.eu-west-1.compute.internal (10.10.228.55)  
Host is up (0.00021s latency).  
Not shown: 991 closed ports  
PORT      STATE SERVICE  
22/tcp    open  ssh  
80/tcp    open  http
```

COMMON NMAP DISCOVERY & SCANNING SWITCHES

Switch	Description	Switch	Purpose
-sS	TCP SYN Scan (Stealth Scan)	-sV	Service & Version Detection
-sT	TCP Connect Scan	-O	Operating System Detection
-sA	ACK Scan	-A	Aggressive Scan (OS, Version, Scripts, Traceroute)
-sF	FIN Scan	-Pn	Skip Host Discovery
-sI	Idle Scan	-oN	Save Normal Output
-sX	XMAS Scan	-T4	Fast Scan
-sW	Window Scan	-f	Fragment Packets (Evasion)

NMAP

Obtains list of open ports, OS details, MAC details, and services along with their versions

Zenmap
Scan Tools Profile Help

Target: 10.10.1.11 Profile:
Scan Cancel

Command: `nmap -p 1-65535 -T4 -A -v 10.10.1.11`

Hosts Services Nmap Output Ports / Hosts Topology Host Details Scans

OS Host
10.10.1.11

nmap -p 1-65535 -T4 -A -v 10.10.1.11 Details

Initiating NSE at 21:37
Completed NSE at 21:37, 0.00s elapsed
Nmap scan report for 10.10.1.11
Host is up (0.00s latency).
Not shown: 65519 closed ports

PORT	STATE	SERVICE	VERSION
21/tcp	open	tcpwrapped	
80/tcp	open	http	Microsoft IIS httpd 10.0
http-methods: Supported Methods: OPTIONS TRACE GET HEAD POST Potentially risky methods: TRACE _ http-server-header: Microsoft-IIS/10.0 _ http-title: IIS Windows			
135/tcp	open	msrpc	Microsoft Windows RPC
139/tcp	open	netbios-ssn	Microsoft Windows netbios-ssn
445/tcp	open	microsoft-ds?	
3389/tcp	open	ssl/ms-wbt-server?	
ssl-cert: Subject: commonName=Windows11 Issuer: commonName=Windows11 Public Key type: rsa Public Key bits: 2048 Signature Algorithm: sha256WithRSAEncryption Not valid before: 2022-01-26T05:45:33 Not valid after: 2022-07-28T05:45:33 MD5: 7587 15a5 0cb8 1140 5205 61f9 6c82 ef00 _ SHA-1: 0725 f739 42be 57c0 db67 b453 66de 500e 323e 7d5a _ ssl-date: 2022-03-15T04:37:19+00:00; 0s from scanner time.			

Filter Hosts

HPING3

- Hping3 (<http://www.hping.org>) is a command-line-oriented network scanning and packet crafting tool for the TCP/IP protocol that sends ICMP echo requests and supports TCP, UDP, ICMP, and raw-IP protocols.
- It performs network security auditing, firewall testing, remote OS fingerprinting, and other functions.
- It can send custom TCP/IP packets and display target replies similarly to a ping program with ICMP replies.
- Syntax: hping3

HPING3

```
hping3 -1 10.10.1.11 - Parrot Terminal
File Edit View Search Terminal Help
[ root@parrot ] - [ /home/attacker ]
# hping3 -1 10.10.1.11
HPING 10.10.1.11 (eth0 10.10.1.11): icmp mode set, 28 headers + 0 data bytes
len=28 ip=10.10.1.11 ttl=128 id=53015 icmp_seq=0 rtt=3.9 ms
len=28 ip=10.10.1.11 ttl=128 id=53016 icmp_seq=1 rtt=3.7 ms
len=28 ip=10.10.1.11 ttl=128 id=53017 icmp_seq=2 rtt=7.6 ms
len=28 ip=10.10.1.11 ttl=128 id=53018 icmp_seq=3 rtt=7.6 ms
len=28 ip=10.10.1.11 ttl=128 id=53019 icmp_seq=4 rtt=7.5 ms
len=28 ip=10.10.1.11 ttl=128 id=53020 icmp_seq=5 rtt=7.4 ms
len=28 ip=10.10.1.11 ttl=128 id=53021 icmp_seq=6 rtt=11.3 ms
len=28 ip=10.10.1.11 ttl=128 id=53022 icmp_seq=7 rtt=3.2 ms
len=28 ip=10.10.1.11 ttl=128 id=53023 icmp_seq=8 rtt=3.1 ms
len=28 ip=10.10.1.11 ttl=128 id=53024 icmp_seq=9 rtt=3.0 ms
^C
--- 10.10.1.11 hping statistic ---
10 packets transmitted, 10 packets received, 0% packet loss
round-trip min/avg/max = 3.0/5.8/11.3 ms
[ root@parrot ] - [ /home/attacker ]
#
```


NETSCANTOOLS PRO

- NetScanTools Pro (<https://www.netscantools.com>) is an investigation tool that allows you to troubleshoot, monitor, discover, and detect devices on your network.
- Using this tool, you can easily gather information about the local LAN as well as Internet users, IP addresses, ports, and so on.
- Attackers can find vulnerabilities and exposed ports in the target system.

NETSCANTOOLS PRO

demo - NetScanTools® Pro Demo Version Build 7-3-2019 based on version 11.06.3

File Edit Accessibility View IPv6 Help

Welcome

Click here to Buy Now! Manual Tools - Port Scanner

Automated Tools

Manual Tools (all)

Packet Generator

Passive Discovery

Ping - Enhanced

Ping - Graphical

Ping Scanner

Port Scanner

Favorite Tools

Active Discovery Tools

Passive Discovery Tools

DNS Tools

Packet Level Tools

External Tools

Application Info

For Help, press F1

Target Hostname or IP Address: 10.10.1.22 X

Port Range and Scan Mode

Port Range: Start 1 End 256

Scan Mode: ☒ TCP Full Connect ☐ UDP Ports Only ☐ TCP Full+UDP Ports ☐ TCP SYN Scan (Half Open) ☐ TCP Custom Scan

Use Target List When Scanning: ☐

Scan Complete - 256 ports scanned in 5 sec.

Network Interface: Ethernet (10.10.1.11) - Microsoft Hyper-V Network Adapter

Show All Scanned Port Results: ☐ Show TCP Summary: ☒ Show UDP Summary: ☐

Scan Range of Ports

Scan Common Ports

Edit Common Ports List

Edit Target List

Stop

Settings

Defaults

Connect Timeout: 2000

Read Timeout: 3000

Add Note

Jump To Automated

Reports

Add to Favorites

TCP Full Connect Response Summary

- 1: Active TCP Ports, 5
- 2: Active TCP Ports Returning Data, 0
- 3: TCP Ports Rejecting Connection, 0
- 4: No Response - Timeout, 251

IP Address	Port	Port Desc	Protocol	Results	Data Received
10.10.1.22	53	domain	TCP	Port Active	
10.10.1.22	80	http	TCP	Port Active	
10.10.1.22	88	kerberos	TCP	Port Active	
10.10.1.22	135	epmap	TCP	Port Active	
10.10.1.22	139	netbios-ssn	TCP	Port Active	

ICAP | NUM | SCRL



EVASION

WHAT IS SCAN EVASION?

Scan evasion refers to techniques used to reduce the chance of detection during scanning.

- Attackers attempt to hide their identity and scanning activities.
- Evasion techniques help bypass:
 - Firewalls
 - Intrusion Detection Systems (IDS)
 - Network monitoring tools

NOTE: The objective is not to make scanning faster, but to make it harder to detect.

COMMON SCAN EVASION TECHNIQUES

Major Evasion Techniques:

Packet
Fragmentation

IP Address
Spoofing

Proxy Servers

PACKET FRAGMENTATION

- A large packet is divided into multiple smaller fragments.
- Each fragment contains only part of the original packet.
- Some IDSs may have difficulty analyzing fragmented traffic.
- The destination host reassembles the fragments.

Example

- `nmap -sS -A -f 172.17.15.12`
- `-f` tells Nmap to send fragmented packets.

IP ADDRESS SPOOFING

- Forges the source IP address.
- Hides the attacker's identity.
- Common tools include:
 - Hping
 - Scapy
 - Nmap
 - Ettercap
 - Cain


PROXY SERVERS

A proxy acts as an intermediary between the scanner and the target.

The proxy forwards requests to the destination.

Network monitoring systems detect the proxy's IP rather than the attackers.

IP Spoofing	Proxy
Uses a fake source IP address	Uses a real intermediary server
May not receive replies	Replies are returned through the proxy
Hides identity	Hides both identity and location



PROXY CHAINS

A proxy chain routes traffic through multiple proxy servers before reaching the target.

Each proxy only knows the previous and next hop, making it more difficult to trace the source.

Multiple proxies provide greater anonymity than a single proxy.

Benefits	Limitations
• Hides the attacker's real IP address. • Makes traffic tracing more difficult. • Adds an extra layer of privacy during network communication.	• Increased communication delay (latency). • Depends on the reliability of each proxy server. • Some proxies may log user activity.

VULNERABILITY SCANNING

WHAT IS VULNERABILITY SCANNING

- Vulnerability scanning is the process of identifying known security weaknesses in a target system.
- It compares the target's configuration and software against a database of known vulnerabilities.
- Helps organizations discover s

Typical Vulnerabilities Detected

- Missing security patches
- Weak configurations
- Known Common Vulnerabilities and Exposures (CVEs)
- Outdated software versions
- Default or insecure settings

HOW VULNERABILITY SCANNING WORKS

The process of vulnerability scanning has five steps



A Typical Report Includes

Detected vulnerabilities

Severity level (Critical, High, Medium, Low)

Affected systems

Recommended remediation actions



COMMON VULNERABILITY SCANNING TOOLS

Tool	Description
Nessus	One of the most widely used commercial vulnerability scanners.
OpenVAS (Greenbone)	Free and open-source vulnerability scanner with extensive scanning capabilities.
Qualys VMDR	Cloud-based vulnerability management and compliance platform.
Microsoft Baseline Security Analyzer (MBSA)	Legacy Microsoft tool for identifying missing Windows updates and security misconfigurations.
GFI LanGuard	Performs vulnerability assessment, patch management, and network auditing.



ENUMERATION

ENUMERATION

- Enumeration is the process of actively collecting detailed information from a target system.
- It involves establishing connections with services and requesting specific information.
- The objective is to identify resources that may be useful during a security assessment.

Information That Can Be Enumerated

User
accounts

Shared
folders

Network
resources

Running
services

Group and
permission

SCANNING VS. ENUMERATION

Scanning	Enumeration
Identifies live hosts and open ports	Retrieves detailed information from discovered services
Answers "What is available?"	Answers "What information can be obtained?"
Less interactive	More interactive
Usually the first step	Performed after scanning

ENUMERATION TECHNIQUE

Banner
Grabbing

NetBIOS
Enumeration

SNMP
Enumeration


BANNER GRABBING

Banner-grabbing is an active enumeration technique. It sends a request to a service running on an open port. The service may respond with a banner containing useful information.

A Banner May Reveal

- Service name
- Software version
- Operating system information
- Web server type
- Mail server information

BANNER GRABBING



Banner Grabbing Process

Example

Suppose a web server returns:

HTTP/1.1 200 OK


Server: Microsoft-IIS/10.0

From this banner we learn:

Web server: **Microsoft IIS**

Version: **10.0**

Banner Grabbing



BANNER GRABBING

Common Banner Grabbing Tools

Tool	Purpose
Telnet	Connects to a TCP port and displays service responses.
Netcat (nc)	Reads and writes network data; commonly used for banner grabbing.
Nmap	Performs service detection and version identification.

NETBIOS ENUMERATION

NetBIOS (Network Basic Input/Output System) is a Windows networking technology used for communication and resource sharing within local networks.

It can reveal valuable information about a target, including:


- Computer name
- Workgroup or domain name
- Shared resources
- File and printer sharing status
- Network browser information

NETBIOS ENUMERATION

- NetBIOS is considered first for enumeration because it extracts information about the target network, such as NetBIOS name, username, workgroup/domain name, and MAC address.
- Attackers usually target the NetBIOS service because it is easy to exploit and runs on Windows systems even when not in use.
- NetBIOS uses:
 - TCP/UDP port 137
 - UDP port 138
 - TCP port 139

NETBIOS ENUMERATION

- **NetBIOS Enumerator**



SNMP ENUMERATION

- Simple Network Management Protocol (SNMP) is a networking protocol that allows network administrators to manage network devices from a remote location.
- SNMP consists of a manager and an agent.
 - The agent is installed by vendors in most network components, such as routers, switches, servers, firewalls, and wireless access points.
 - The manager is installed by the network administrator on a separate computer.


SNMP ENUMERATION

- SNMP holds two passwords to access and configure the SNMP agent from the SNMP manager:
 - **Read community string:** It is 'public' by default; it allows for the viewing of the device/system configuration
 - **Read/write community string:** It is 'private' by default; it allows remote editing of the configuration
- When administrators leave the community strings at the default setting, attackers can use these default community strings (passwords) to change or view the configuration of the device or system.

SNMP ENUMERATION

Snmp-check

Snmp-check (nothink.org) is a tool that allows the enumeration of SNMP devices and places the output in a user-friendly format.



```
snmp-check 10.10.1.22 - Parrot Terminal
File Edit View Search Terminal Help
[root@parrot:~]# snmp-check 10.10.1.22
snmp-check v1.9 - SNMP enumerator
Copyright (c) 2005-2015 by Matteo Cantoni (www.nothink.org)

[+] Try to connect to 10.10.1.22:161 using SNMPv1 and community 'public'

[*] System information:

Host IP address      : 10.10.1.22
Hostname             : Server2022.CEH.com
Description          : Hardware: Intel64 Family 6 Model 85 Stepping 7 AT/AT COMPATIBLE - S
Software: Windows Version 6.3 (Build 20348 Multiprocessor Free)
Contact              : -
Location             : -
Uptime snmp          : 01:50:32.79
Uptime system        : 334 days, 10:33:44.95
System date          : 2022-3-25 05:41:08.2
Domain               : CEH

[*] User accounts:

Guest
jason
Martin
Shiela
krbtgt
Administrator
```

Remember

