



The multi-scale landscape of community inconsistency in networks

Daekyung Lee¹, Sang Hoon Lee², Beom Jun Kim¹, Heetae Kim^{3(*)}

1)



2)




3)



supported by



*corresponding author, email:kimheetae@gmail.com




Modularity

$$\mathcal{H} = \frac{1}{2m} \sum_c \left(e_c - \gamma \frac{K_c^2}{2m} \right)$$

Number of intra-community links

Null model

- Community: Densely connected group of nodes
- Found by the maximization of object function
- Varying results in multiple realizations



Modularity


$$\mathcal{H} = \frac{1}{2m} \sum_c \left(e_c - \gamma \frac{K_c^2}{2m} \right)$$

Resolution parameter

- γ : resolution parameter of community structure
- No criterion to determine the proper resolution


3) *Sci. Rep.* 9 (2019) 8574

$$P(C_1) = 0.6$$





How similar? $\rightarrow S_{12} (0 \sim 1)^{3)}$

$$P(C_2) = 0.4$$



- Ensemble of community detection results from multiple realizations
- How diverse are the configurations in community ensemble?
- Using the element-centric similarity (EC) between each configuration pair




$$\Omega = \frac{1}{\langle S_{\alpha\beta} \rangle} = \left[\sum_{\alpha} \sum_{\beta} P(C_{\alpha}) P(C_{\beta}) S_{\alpha\beta} \right]^{-1}$$

$$= \frac{1}{P(C_1)^2 + P(C_2)^2 + 2P(C_1)P(C_2)S_{12}}$$


- Partition inconsistency: A measure to assess the stability of community ensemble
- Inverse of average similarity between all the configuration pairs

$$P(C_1) = 0.6$$



$$S_{12} = 1$$

$$P(C_2) = 0.4$$




$$\text{If } S_{12} = 1$$

$$\Omega = \frac{1}{\langle S_{\alpha\beta} \rangle} = \left[\sum_{\alpha} \sum_{\beta} P(C_{\alpha}) P(C_{\beta}) S_{\alpha\beta} \right]^{-1}$$

$$= \frac{1}{(P(C_1) + P(C_2))^2} = 1$$


- If all the configurations are same $\rightarrow \Omega = 1$ (minimum)

$$P(C_1) = \frac{1}{2}$$



$$S_{12} = 0$$

$$P(C_2) = \frac{1}{2}$$




if $S_{\alpha\beta} = 0$ for all distinct pairs


$$\Omega = \frac{1}{\langle S_{\alpha\beta} \rangle} = \left[\sum_{\alpha} \sum_{\beta} P(C_{\alpha}) P(C_{\beta}) S_{\alpha\beta} \right]^{-1}$$

$$= \frac{1}{\left(\frac{1}{2}\right)^2 + \left(\frac{1}{2}\right)^2} = \frac{1}{2 \times \left(\frac{1}{2}\right)^2} = 2$$


- If all the configurations are identical ($S = 0$) and appear with equal probability
- Ω = the number of configurations
- Partition Inconsistency denotes the effective number of configurations in community ensemble ⁷



- Resolution of community structure can be determined by Partition Inconsistency
- Comparison of two distinct resolutions



- Resolution of community structure can be determined by Partition Inconsistency
- Comparison of two distinct resolutions





- Synthetic formation of benchmark model network
- Hierarchical community structure



$$n = 1200$$

$$p = 0.24$$



$$E_i = \left[0, \frac{2}{3}\right]$$




- Result of single-level network
- Low consistency region corresponds to the ground truth of model network



- Result of double-level network
- Low consistency region reconstruct both levels




- Karate club network: A conventional benchmark of community structure
- Shows the lowest Ω when $n_c = 2 \rightarrow$ well matches with a prior knowledge




- A power grid network in Chile
- Shows low Ω in a wide range of $\gamma \rightarrow$ degeneracy of community structure?


(a) $\gamma = 0.2$




(b) $\gamma = 0.4$




(c) $\gamma = 0.6$



(d) $\gamma = 0.75$




Community structure





- Hierarchical community structure
- Smaller community structure emerges from larger communities

▪ Partition Inconsistency





$$\Omega = \frac{1}{\langle S_{\alpha\beta} \rangle} = \left[\sum_{\alpha} \sum_{\beta} P(C_{\alpha}) P(C_{\beta}) S_{\alpha\beta} \right]^{-1}$$

▪ Synthetic network




▪ Real network



Summary

- Introduced Pal to measure stability of community detection.
- Introduced Mel for node-level stability.
- Used both to analyze community structures across resolutions.
- Enables identifying optimal resolution and hierarchical organization.



1) Cat interrupting research (In Chile)

Thanks for your attention!