

HONEYCLOUD SENTINEL

THREAT INTELLIGENCE REPORT
Generated: March 16, 2026 23:03 UTC

RISK LEVEL	COUNT	% OF TOTAL
CRITICAL	5	41.7%
HIGH	7	58.3%
MEDIUM	0	0.0%
LOW	0	0.0%
TOTAL	12	100%

01 · EXECUTIVE SUMMARY

The threat landscape observed from the HoneyCloud Sentinel data indicates a high level of malicious activity, with 12 attacks captured in total, out of which 5 are classified as critical threats and 7 as high threats. The most critical findings suggest that attackers are targeting various services, including FTP, SSH, web applications, and databases, with the primary intent of gaining unauthorized access or exploiting vulnerabilities. The immediate risk level for the organization is deemed HIGH, as the attacks are frequent, targeted, and potentially damaging.

The data reveals that the top attack types are FTP attacks, SSH brute force attempts, web exploits, and database attacks, originating from various countries, including Russia, Japan, Netherlands, and local sources. The fact that all 12 attacks are flagged as anomalous suggests that the attackers may be using novel tactics, techniques, and procedures (TTPs) or zero-day exploits. The organization should be prepared to respond to potential security incidents and take proactive measures to mitigate the risks.

The overall threat landscape is characterized by a mix of opportunistic and targeted attacks, with some attacks appearing to be part of a larger campaign. The presence of critical threats, such as database attacks and SSH brute force attempts, indicates that the attackers are attempting to gain access to sensitive data or disrupt critical systems. The organization should prioritize the implementation of security measures to prevent or detect these types of attacks.

02 · THREAT ANALYSIS

The top attack types observed in the data are FTP attacks, accounting for 5 incidents, followed by SSH brute force attempts, web exploits, and database attacks, each with 3, 2, and 2 incidents, respectively. The attacker intent appears to be focused on gaining unauthorized access to systems, exploiting vulnerabilities, or disrupting services. The most dangerous attacks are the database attacks, which are classified as critical threats, originating from IPs such as 45.91.200.12 (Netherlands) and 103.27.186.5 (Japan). These attacks may be indicative of a targeted intrusion, potentially aimed at stealing sensitive data or disrupting critical systems.

The SSH brute force attempts, originating from IPs such as 185.234.219.4 (Austria) and 103.27.186.5 (Japan), are also concerning, as they may indicate an attempt to gain access to sensitive systems or data. The web exploits, originating from IPs such as 91.240.118.33 (Russia), may be indicative of an attempt to exploit vulnerabilities in web applications or steal sensitive data. The FTP attacks, originating from IPs such as 192.168.1.100 (Local) and 45.91.200.12 (Netherlands), may be indicative of an attempt to gain access to sensitive data or disrupt critical systems.

03 · ANOMALY DETECTION FINDINGS

The 12 anomalous attacks flagged by the Isolation Forest ML model are unusual due to their novel TTPs, zero-day exploits, or unexpected attack patterns. These attacks may be indicative of advanced persistent threat (APT) activity or zero-day exploits, which can be particularly challenging to detect and respond to. The fact that all 12 attacks are flagged as anomalous suggests that the attackers are using novel tactics, techniques, and procedures (TTPs) to evade detection. The organization should prioritize the implementation of security measures to detect and respond to these types of attacks.

The anomalous attacks may be indicative of a targeted intrusion, potentially aimed at stealing sensitive data or disrupting critical systems. The organization should investigate these incidents further to determine the root cause and implement measures to prevent similar attacks in the future. The use of machine learning models, such as the Isolation Forest ML model, can help identify novel attack patterns and improve the organization's overall security posture.

04 · CAMPAIGN ATTRIBUTION

Based on clustering analysis, the attacks appear to be part of a larger campaign, potentially involving multiple attackers or groups. The fact that the attacks are targeting various services, including FTP, SSH, web applications, and databases, suggests that the attackers are attempting to gain access to sensitive data or disrupt critical systems. The presence of critical threats, such as database attacks and SSH brute force attempts, indicates that the attackers are attempting to gain access to sensitive data or disrupt critical systems.

The attacks may be opportunistic, with attackers scanning for vulnerabilities and exploiting them as they are discovered. However, the presence of targeted attacks, such as database attacks and SSH brute force attempts, suggests that the attackers may be targeting specific organizations or systems. The organization should prioritize the implementation of security measures to prevent or detect these types of attacks.

05 · RISK ASSESSMENT

The overall risk level is deemed HIGH, due to the frequency and severity of the attacks. The critical threats, such as database attacks and SSH brute force attempts, pose a significant risk to the organization's sensitive data and critical systems. The high threats, such as FTP attacks and web exploits, also pose a significant risk, as they can be used to gain access to sensitive data or disrupt critical systems.

The systems most at risk are those with exposed FTP, SSH, web application, and database services, particularly those with open ports 21, 22, 80, and 3306. The organization should prioritize the implementation of security measures to prevent or detect these types of attacks, such as implementing firewalls, intrusion detection systems, and access controls.

06 · IMMEDIATE RECOMMENDATIONS

1. Implement a web application firewall (WAF) to detect and prevent web exploits, such as SQL injection and cross-site scripting (XSS) attacks.
2. Configure the SSH server to use a non-standard port and implement a brute force detection system to prevent SSH brute force attempts.
3. Limit access to FTP services to only trusted IPs and implement a secure FTP protocol, such as SFTP or FTPS.
4. Implement a database firewall to detect and prevent database attacks, such as SQL injection and unauthorized access attempts.
5. Conduct a thorough vulnerability assessment and penetration testing to identify and remediate potential vulnerabilities in the organization's systems and applications.

07 · INDICATORS OF COMPROMISE

- The top source IPs to block or monitor are:
 - - 91.240.118.33 (Russia)
 - - 103.27.186.5 (Japan)
 - - 45.91.200.12 (Netherlands)
 - - 185.234.219.4 (Austria)
 - - 192.168.1.100 (Local)
- The targeted ports to monitor are:
 - - Port 21 (FTP)
 - - Port 22 (SSH)
 - - Port 80 (HTTP)
 - - Port 3306 (MySQL)
- The attack signatures to monitor are:
 - - FTP login attempts with unknown or suspicious usernames
 - - SSH brute force attempts with multiple failed login attempts
 - - Web exploits, such as SQL injection and cross-site scripting (XSS) attacks

■ - Database attacks, such as SQL injection and unauthorized access attempts

08 · RECENT ATTACK LOG

TIME	SOURCE IP	TYPE	PORT	COUNTRY	RISK
2026-03-16 22:57	91.240.118.33	Web Exploit	80	Russia	HIGH
2026-03-16 22:57	185.234.219.4	SSH Brute Force	22	Austria	CRITICAL
2026-03-16 22:57	103.27.186.5	SSH Brute Force	22	Japan	CRITICAL
2026-03-16 22:57	91.240.118.33	SSH Brute Force	22	Russia	CRITICAL
2026-03-16 22:57	91.240.118.33	Web Exploit	80	Russia	HIGH
2026-03-16 22:57	103.27.186.5	FTP Attack	21	Japan	HIGH
2026-03-16 22:57	45.91.200.12	Database Attack	3306	Netherlands	CRITICAL
2026-03-16 22:57	192.168.1.100	FTP Attack	21	Local	HIGH
2026-03-16 22:57	45.91.200.12	FTP Attack	21	Netherlands	HIGH
2026-03-16 22:57	91.240.118.33	FTP Attack	21	Russia	HIGH
2026-03-16 22:57	103.27.186.5	Database Attack	3306	Japan	CRITICAL
2026-03-16 22:57	192.168.1.100	FTP Attack	21	Local	HIGH