1]
Write a program to count prime digit in a given number.
Note: Use following function declaration.
    Print the result in main.
    Take a number from user in main().
int count(int);

2]
Write a program to find out nth prime number from a given number.
Note: Use following function declaration.
    Print the result in main.
    Take a number and n value from user in main().
void findprime(int *,int *);

3]
Write a program to count armstrong number in a given range.
Note: Use following function declaration.
    Print the count in main().
    Take a range from user in main().
void armstrongcount(int *,int *,int*);

4]
Write a program to count set bit in a given number using function.
Take three number from user in main() and count set bit in each number
using function but print the count of set bit of three numbers in main().
Follow the given function declaration.
Void binary(int *,int *,int *);

5]
Write a program to print the binary of each prime digit present
in a given number.To find the prime digit use following function declaration.
But print the binary of each prime digit in main().
void primedigit(int *,int *);
Example:----int num=12345
Using function find prime digit but binary printing should through main().
        00000010
        00000011
        00000101
Take a number from user in main().

6]
Write a program to remove the digits which contain even set bit count.
Take input in main().
Delete the digit which contain even set bit count using function but print the result in main().
Follow the given function declaration.
Void even_delete(int *);

7]
Write a program to delete n bits from a given position in a given number.
Take number,n,pos from user in main().
Use following function declaration.
int deletebits(int,int,int);
Example: num=505; n=4 Pos=3
Before----- 00000000 00000000 00000001 11110100
After ----- 00000000 00000000 00000000 00011100
Print the result after delete in main().

8]
Write a program to count how many prime numbers are there in given array using function.
Take input in main function.
Print the count of prime numbers in main().
Follow the given function declaration.
void prime(int *,int *,int*);

9]
Write a program to count element in the array whose sum of digit is prime.
Take input in the main function.
Follow the given function declaration.
int array_sum(int *,int *);
Print the count in main().

10]
Write a program to delete armstrong number in integer array.
Follow the given function declaration.
Void armstrong(int *,int *);
void power(int*, int *,int *);
void delete(int *,int *);
Print the array after deletion in main().

11]
Write a program to check data in third nibble of each array element is prime or not if the data is prime then clear third nibble of each such array element.
Take array element from user.
Use following function declaration.
Void clear(int *,int *);
int prime(int *);
Print the result in main().
Example:--------int a[5]={513,10,768,1025,256};
Output:---------- {1,10,0,1025,256}

12]
Write a program to add each element of the array until the sum not become single digit. Then replace that element with the single digit sum.
Example: int a[5]={12345,2589,256,128,512};
Here first element is 12345 so add all digit 1+2+3+4+5=15 but 15 is not single digit so add again 1+5 so result is 6. So replace first element with 6.
Output: a[5]={6,6,4,2,8};
Note: Use the following function prototype.
Void add(int *,int *);
Print the result in main()

13]
Write a program to store strong number from one array into another array.
Take array element from user.
Use following function declaration.
void strong(int * ,int *,int *,int *);
Print the new array in main();
Example:-----int a[5]={1,78,145,2,45}
Output:----------b[ ]= {1,145,2}

14]
Write a program to replace each array element by the nth prime number from the given array element.
Here n is number of prime digit in a given number.
Example: int a[5]={12,2,3,4,5};
Output: a[5]={13,3,5,4,7};
Note: Use the following function prototype.
Void replace(int *,int *);
void prime(int *,int *);
Print the result in main().

15]
Write a program to reverse the number in the array if its first digit is odd.
Example: Int a[5]={123,245,312,599,600};
Output : a[5]={321,245,213,995,600};
int checkdigit(int);
void reverse(int *,int *);

16]
Write a program to reverse the word which contain vowel.
Follow the given function prototype.
Int checkvowel(char *);
void reverse(char *);
Example:-------char s[]="v26be4 abcd pqrst xyz"
Output:---------- "4eb62v dcba pqrst xyz"

17]
Write a program to replace all occurence of word "Bangalore" by Bengaluru in a string.
Follow the following function prototype.
char * findword(char *);
void replace(char *,int);

18]
Given an integer num, return *a string of its* **base 7** *representation*.

Example 1:

```
Input: num = 100 (Decimal number)
Output: "202"
```

Example 2:

```
Input: num = -7
Output: "-10"
```

Note: Use the following function prototype.
Char * hex (int *);

19]
Given a 32-bit integer num, return *a string representing its hexadecimal representation*. For negative integers, two's complement method is used.

Note: Use the following function prototype.
Char * hex (int *);

Example:--- Input int num=26;
Output string= "1a"

Input int num=256;
Output string ="100"

Input:---int num= -26;
Output:----"fffffe6"

20]
Write a Program to delete the lagest word in a string.

Follow the following function prototype.
Void largestword(char *,int *);
void delete(char *,int *);

For example: ABCD PQRSTU V26BE4
Output : ABCD

21]

Write a program to count the word in a string whose length is prime.
If the count of such words is prime then reverse the alternate word in a string.Otherwise print the string as it is.
Example:
Input Char s[20]=”ABC 1234 V26BE4 12 123”
3 words are there whose length is prime and as 3 is prime
So revesre the alternate words.
Output char s[20]=”CBA 1234 4EB62V 12 321”
Note: Use the following function declaration.
Void countword (char *,int *);
int checkprime(int *);
void reverse(char *);
Print the result in main()

22]
Write a program to reverse second nibble of each array element.
Note: Use following function declaration.
Take array element from user.
void reverse(int *,int *);
Example:---int a[5]={16,32,48,112,15}
Output:----- {128,64,192,224,15}
Print the result in main().

23]
Write a program to swap first two prime digits from left for each array element without reversing the array element.
Remaining digits in that array element should not disturbed.
Input---int a[5]={1234,2599,12,27,305};
Output ----int a[5]={1324,5299,12,72,503};
Note: Don’t reverse the array element.
Take array element from user.
Use following function declaration.
void reverse(int *,int *);
Print the result in main().

24]

Write a program to swap first digit and last digit in each array element if both digit contain even set bit count.
Take array element from user.
Follow the given function prototype.
Void swap(int *,int *);
void setbit(int *,int *)
Print the result in main().
Example:-----int a[5]={95,623,17,5430,47}
Output:------ {59,326,17,345,47}
Print the result in main().

25]
Write a program to extract data present in bits from 3 to 11 in each array element and store in another array.
Take array element from user.This is calculated assuming bit position starting at 0.
Extract data between position 3 and position 11 and position 3 and 11 also included.
Follow the given function prototype.
void extract(int *,int *,int *,int *,int *);
Example:-----int a[5]={7,255,5000,4095,75000};
Output:------ {0,31,113,511,41}
Print the result in main().

26]
Write a program to check data corresponding to first and fourth byte in a given integer is prime or not.
Use Following function prototype.
Void data(char *,int *);
To make the data you have to use char * only and above function.
Void primecheck(int*,int *);
Take number from user.
Write a generic code.
Print the result in main().
Example:
int num=0x01000001;
Now data corresponding to first and fourth byte is 257 which is prime.
Output = Prime.

27]

Write a program to delete the character in a string at a prime index and if that character set bit count is prime. So both condition should satisfy means character should be at prime index and it should contain prime number of set bit count.
Write a generic code.
Take string from user.
Use following function declaration.
Void prime(char *,int *);
void setbitcount(char *,int *);
void delete(char *,char *);
Example:ABCCGG GDEF KAG
Output: ABGG GDEF KG
A-----2 set bit count but not at prime index
B-----2 set bit count but not at prime index
C-----3 set bit count and present at prime index so delete it.

28]
Write a program to find a substring in a main string and if the substring found at prime index reverse that whole word.
Use following function prototype.
Void findsubstring(char *,char *,int *);
void primecheck(int *,int *);
Example: Input char main[50]=”ababc babc 3abc12 12ab”
char sub[30]=”abc”;
Output char main[]=”cbaba cbab 21cba3 12ab”

29]
Write a program to return from last first three prime element in an given array.
Take array element from user.
Use following function declaration.
Void prime(int *, int *, int *, int*);
Example:------int a[5]={10,11,12,13,17};
Print the result in main().
Output:------17,13,12
Example:---- int a[5]={10,16,14,17,19}
Output:------19,17

30]
Write a program to find a substring in a main string and if the substring found at prime index delete that whole word.
Use following function prototype.
Void findsubstring(char *,char *,int *);
void primecheck(int *,int *);
void delete(char *,int *);
Example: Input char main[50]=”29ababc 05babc 19abc60 ab12”
char sub[30]=”abc”;
Output char main[]=”ab12”