1]
Write a program to print the input string word by word.
Example:----char s[]="abcde 1234 V26BE4"
Output:------abcde
1234
v26be4

2]
Write a program to print the first character of each word given in a string.
Take string from user.
Example: char s[]="abcde 1234 v26be4"
Output:----a
----1
----v

3]
Write a program to print last character of each word given in a string.
Take string from user.
Example: char s[]="abcde 12345 v26be4"
Output:----e
----5
----4

4]
Write a program to count digits in a whole string.
Take string from user.
Example: char s[]="abcde 12345 v26be4"
Output:----Digits Count---8

5]
Write a program to count vowel in a given string.
Take string from user.
Example: char s[]="abcde 12345 v26be4"
Output:---- Vowel Count-----3

6]
Write a program to count prime digit present in a given string.
Take string from user.
Example: char s[]="Abcde 12345 v26be4"
Output:----Prime digit--4

7]
Write a program to make all small case letter to upper case in a given string.
Take string from user.
Example: char s[]="AbcDe 12345 V26Be4"
Output:---- “ABCDE 12345 V26BE4”

8]
Write a program to make all small case letter to upper case in only first word.
Take string from user.
Example: char s[]="abcde 12345 v26be4"
Output:---- "ABCDE 12345 v26be4"

9]
Write a program to make all small case letter to upper case in only last word.
Take string from user.
Example: char s[]="abcde 12345 v26be4"
Output:---- "abcde 12345 V26BE4"

10]
Write a program to make all small case letter to upper case except first and last word.
Take string from user.
Example:------char s[]="abcde 1234 pqrst v26be4"
Output:-------"abcde 1234 PQRST v26be4"

11]
Write a program to make first character of each word upper to lower(if it is upper case) or lower to upper case(if it is lower case).
Take string from user.
Example:-----char s[]="abcde 1234 Pqrst v26Be4"
Output:------- "Abcde 1234 pqrst V26Be4"

12]
Write a program to make last character of each word upper to lower(if it is upper case) or lower to upper case(if it is lower case).
Take string from user.
Example:-----char s[]="abcde 1234 Pqrst v26Be4 12ab"
Output:------- "abcdE 1234 PqrsT v26Be4 12aB"

13]
Write a program to print character in a given string which contain even set bit count.
Take string from user.
Example:-----char s[]="abcde 12345 v26be4"
Output:------- c,e,3,5,6,e

14]
Write a program to print binary of first and last character in each word of a given string.
Take string from user.
Example:-----char s[]="abcde 12345 v26be4"
Output:-------a---01100001
e---01100101
1---00110001
5---00110101
v---01110110
4---00110100

15]
Write a program to print the length of each word in a given string.
Take string from user.
Example:---char s[]="abcde 12345 v26be4"
Output------5 5 6

16]
Write a program to print the length of each word in a given string.
Take string from user. **Use goto to find length of each word.**
Example:---char s[]="abcde 12345 v26be4"
Output------5 5 6

17]
Write a program to print the length of first word in a given string.
Take string from user.
Example:---char s[]="abcde 12345 v26be4"
Output------5

18]
Write a program to print the length of last word in a given string.
Take string from user.
Example:---char s[]="abcde 12345 v26be4"
Output------6

19]
Write a program to print the length of each word except first and last word.
Take string from user.
Example:---char s[]="abcd 12345 pqrstuv wxyz v26be4"
Output------5 7 4

20]
Write a program to print the length of each word except first and last word.
Take string from user. **Use goto to find length.**
Example:---char s[]="abcd 12345 pqrstuv wxyz v26be4"
Output------5  7  4

21]
Write a program to print the count of the word in a given string whose length is prime.
Take string from user.
Example:---char s[]="abcd 12345 pqrstuv wxyz v26be4"
Output------2

22]
Write a program to print count of the word in a given string which contain vowel.
Take string from user.
Example:-----char s[]="abcd 1234 aeabcd"
Output:-------2

23]
Write a program to swap first and last character of each word given in a string.
Take string from user.
Example:---char s[]="abcd 12345 pqrstuv wxyz v26be4"
Output------ "dbca 52341 vqrstup zxyw 426bev"

24]
Write a program to delete digit in a given a string.
Take string from user.
Example:----- char s[]="ab123 p2g3h4 mno12"
Output:------ "ab pgh mno"

25]
Write a program to delete prime digit in a given string.
Take string from user.
Example:----char s[]="abc123 jh456 7778"
Output:------ "abc1 jh46 8"

26]
Write a program to delete char which contain prime set bit count.
Take string from user.
Example:-----char s[]="abc123 v26be4 pqrst"
Output:--------- "c3 6e qrt"

27]
Write a program to delete the duplicate character in a given string.
Take string from user.
Example:----char s[]="aaabaab123 ab";
Output:----- "123"

28]
Write a program to count word in a given string.
Take string from user.
Example:----char s[]="abcd 123 45"
Output:-------3
Example:----char s[]=" ab "
Output:-----1

29]
Write a program such that for every pair of adjacent word swap last character of the first word
with the first character of the second word.
Take string from user.
Example:-----char s[]="abcd pqrst 1234"
Output:------ "abcp dqrs1 t234"

30]
Write a program to delete last character of each word given in a string.
Take string from user.
Example:-----char s[]="abcd 1234 pqrst"
Output:------ "abc 123 pqrs"

31]
Write a program to count the word having largest length in a given string.
Take string from user.
Example:-----char s[]="abcd 12 43 defg 1234"
Output:--------3

32]
Write a program to print largest word in a given string.
Take string from user.
Example:-----char s[]="abcd 12 43 defg 1234"
Output:--------abcd
defg
1234

33]
Write a program to reverse first word in a given string.
Take string from user.
Example:-----char s[]="abcd 12 43 defg 1234"
Output:--------  "dcba 12 43 defg 1234"
Example:-----char s[]="ABCD"
Output:-------  "DCBA"

34]
Write a program to reverse last word in a given string.
Take string from user.
Example:-----char s[]="abcd 12 43 defg 1234"
Output:--------  "abcd 12 43 defg 4321"
Example:-----char s[]="ABCD"
Output:-------  "DCBA"

35]
Write a program to reverse all the word except first and last word in a given string.
Take string from user.
Example:-------char s[]="abcd 123 345 pqrs xyz"
Output:---------  "abcd 321 543 srqp xyz"

36]
Write a program to reverse all the largest word in a given string.
Take string from user.
Example:-----char s[]="Abcd 123 xy 23 jkl 1234"  (Largest word length is 4 so reverse all word
having length 4)
Output:------  "dcba 123 xy 23 jkl 4321"

37]
Write a program to reverse the word in a given string whose length is prime.
Take string from user.
Example:----char s[]="Abcd 123 345 wx abcd xy"
Output:------  "Abcd 321 543 xw abcd yx"

38]
Write a program to reverse all the word whose length is above 4 in a given string.
Take string from user.
Example:------char s[]="Abcd wxyz1 123 12345 123456"
Output:----------  "Abcd 1zyxw 123 54321 654321"

39]
Write a program to reverse the word in a given string which contain at least one prime digit.
Take string from user.
Example:-----char s[]="Abcd4 1468 2abcd3 2xyz";
Output:-----  "Abcd4 1468 3dcba2 zyx2"

40]
Write a program to reverse all the word in a given string whose first and last character is vowel.
Take string from user.
Example:------char s[]="Abcde 123ea dcba awxyo"
Output:-------  "edcbA 123ea dcba oyxwa"

41]
Write a program to reverse the words in a given string which contain at least one special character.
Take string from user.
Example:-----char s[]="A$bcd @wxyz @#1234 12346"
Output:--------  "dcb$A zyxw@ 4321#@ 12346"

42]
Write a program to reverse that word in a given string whose count is given by user.
Take string and count from user.
Example:------char s[]="ABcd 1234 wxyz pqrst";
Input---Count= 3 (As count enter is 3 so just reverse third word from starting)
Output:--------  "ABcd 1234 zyxw pqrst"

Example:------char s[]="ABcd 1234 wxyz pqrst";
Input---Count= -3 (As count enter is -3 so just reverse third word from last)
Output:--------  "ABcd 4321 wxyz pqrst"

43]
Write a program to count how many substring are present in main string.
Take main string and substring from user.
Example:------char main[]="aababc abababc abaababc ababcab"
  sub[]="abc"
Output:----------Substring present 4 times

44]
Write a program to find a word in a given string if that word is found then reverse all the occurrence of that word in a given string.
Take word and string from user.
Example:-------char s[]="abcd 1234 abcd12 abcd"
char word[]="abcd"
Output:------- "dcba 1234 dcba12 dcba"

45]
Write a program to delete the words in a given string whose length is prime.
Take string from user.
Example:------char s[]="pqrst 1234 we abcd 1234";
Output:------ "abcd 1234";

46]
Write a program to find a word in a given string if that word is found then delete all the occurrence of that word in a given string.
Take word and string from user.
Example:-------char s[]="abcd 1234 abcd12 abcd"
char word[]= "abcd"
Output:------- "1234 12"

47]
Write a program to delete a character whose data corresponding to second nibble is prime.
Take string from user.
Example:
Input char s[20]=”ayz V25BE1 cde”
Now data in second nibble of ‘a’ is 6 so as it is not a prime so character ‘a’ will not be deleted.
But data in second nibble of ‘y’ and ‘z’ is 7 so delete both character.
Output:
char s[20] = “a BE cde”
Don’t delete space. Because space ascii value second nibble data is prime.

48]
Write a program to find the word in a given string if that word is found replace that word with the given word.
Take string,word which we want to replace,word with which we want to replace from user.
Example:------char s[]=”ababcd12 a1ab1abcd3 abaabaabcd”;
char word[]=”abcd”;
char replace[]=”1234567”
Output:--------- “ab1234567 12 a1ab112345673 abaaba1234567”

Example:--------char s[]=”ababcd12 a1ab1abcd3 abaabaabcd”;
char word[]=”abcd”;
char replace[]=”12”
Output:---------- “ab1212 a1ab1123 abaaba12”

49]
Write a program to delete the first word from last whose length is prime in a given string.
Take string from user.
Example:-------char s[]=”abcde abcd 12345 wxyz” (“12345” is the first word from last whose legth is prime)
Output:---------- “abcde abcd wxyz”
Example:------char s[]=”12345”
Output:--------Nothing will print

50]
Given two non-negative integers `num1` and `num2` represented as strings, return the product of `num1` and `num2`, also represented as a string.
**Example 1:**

```
Input: num1 = "2", num2 = "3"
Output: "6"
```

**Example 2:**

```
Input: num1 = "123", num2 = "456"
Output: "56088"
```

51]
Write a program to sort the character in the words of minimum length.
For Example: Input char s[50]=”Abcd had 12345 dba”
Output char s[50]=”Abcd adh 12345 abd”

52]
Write a program to reverse alternate word in a given string.
Take string from user.
Example:-------char s[]=”abcd 1234 pqrst 56789”
Output;-------- “dcba 1234 tsrqp 56789”

53]
Take a float number from user and print that number in string format.
Input float f=12.005;
output Printf(“%s\n”,a); ---------12.005
where a is character array.
**Follow the following function prototype.**
**Char * floattoascii(char *,float);**

54]
Write a program to swap first two words from last whose length is prime in a given string. Take string from user.
Example1:------char s[]=”1234 abc abcde wxyz”
Output:-------- “1234 abcde abc wxyz”

Example2: char s[]=”12345 wxyz 5678 abc”
Output:------- “abc wxyz 5678 12345

Example3:------ char s[]=”12345 56789 wxyz pqrs”
Output:------- “56789 12345 wxyz pqrs”

55]
Given a string `s`, sort it in decreasing order based on the frequency of the characters. The frequency of a character is the number of times it appears in the string.
Return *the sorted string*. If there are multiple answers, return *any of them*.

Example : Input char s[]=”VV25BE11”
Output char s[]=”VV1125BE”

Input char s[]=”11213113”
Output char s[]=”1111332”
**Note: Use the following function prototype.**
**char * sort(char *);**

56]
Take one string from user.
For example char s[]=”V26BE4D”;
Write a program such that it will print following output.

```
      V
     V2
    V26
   V26B
  V26BE
 V26BE4
V26BE4D
 V26BE4
  V26BE
   V26B
    V26
     V2
      V
```

Write a generic program.
Take input as any string it should work for it.