

1.3 – Computer networks, connections and protocols – Past Exam Questions – Solutions

2022

Question			Answer	Mark	Guidance
3	(a)	(i)	1 mark each to max 3 <ul style="list-style-type: none"> • Slower transmission of data // less data can be transmitted at the same time // the transmission rate decreases // time to send/receive increases • (More devices mean) more data is being transmitted (at a time) • Bandwidth will be split between all the devices (sending data) // each device uses some of the bandwidth • ...this means that there is less bandwidth for each device • Devices have to wait longer before they can transmit // increased latency • If the maximum bandwidth is used then devices cannot transmit • Central device/switch/router has to handle more requests and may run slower • More collisions (likely) // higher error rate ... • ...more data has to be retransmitted • Loss of more packets ... • ...more data has to be retransmitted 	3	The question is why. More devices do not decrease the bandwidth of the network. They decrease the amount allocated/available to each device. Do not accept higher contention ratio. This term means the number of users on a connection, and is therefore repeating the question.
3	(a)	(ii)	1 mark e.g. <ul style="list-style-type: none"> • Bandwidth • Interference // by example • Wired // wireless // transmission medium • Type/amount of data being transmitted • Central hardware performance // by example e.g. router/switch • Error rate • Distance between nodes • Topology // physical layout • Wireless repeaters 	1	Do not award the number of users. Question is performance of network as a whole, not an individual device.
3	(b)		1 mark for each completed term A website is hosted on a web server . The computers that access the websites are called clients . The user enters a Uniform Resource Locator into a web browser. The web browser sends a request to the Domain Name Server for the matching IP (Internet Protocol) address. If found the IP address is returned. A request is then sent to the IP address for the website. An IPv4 address is made of 4 groups of digits. Each group can be between 0 and 255 . The groups of digits are separated by a full stop	7	Words are given so must match, however accept domain name system for domain name server, URL, DNS. Accept 0 and 255 in either order Do not allow server for web server because file server is another option and it will be ambiguous.
3	(c)		1 mark each to max 2 <ul style="list-style-type: none"> • Ethernet is used by (mostly) all manufacturers // Ethernet is used in many devices • To allow compatibility with other devices • Ethernet has a high bandwidth • Ethernet has inbuilt security • Ethernet is a proven/reliable connection • Ethernet is low cost for purchase/installation/maintenance (compared to other wired connections) 	2	Accept description of a standard, and/or benefits of Ethernet (i.e. why has this become a standard).
3	(d)		1 mark each to max 3 e.g. <ul style="list-style-type: none"> • Receive packets • Forward/sending/transmitting packets • Maintain a routing table // by description • Identify the most efficient path to the destination / correct IP / correct location • Assign IP addresses to nodes/devices • Converts packets from one protocol to another. 	3	Question is tasks carried out by a router, not the use of a router in a network.

3	(e)	1 mark each to max 2 e.g. <ul style="list-style-type: none"> Data cannot be understood if intercepted // The data will be meaningless So that only authorised users can access the confidential/personal/user/library data To follow legislation/DPA 	2	Question is transmission not storage Candidates might answer in terms of why encryption is good, or why the current system is not good. If the candidate has not clearly said which they are talking about (e.g. the current system or encryption means) then the reverse of each mark point can be given.
3	(f)	1 mark each e.g. Send email: SMTP // simple mail transfer protocol Access website securely: HTTPS // hypertext transfer protocol secure	2	Mark first answer in each line. If abbreviation is inaccurate, check if written out (and vice-versa).

Sample Paper

7	a	• A set of rules for communication	1 (AO1 1a)	1 mark only to be awarded for a correct definition.
7	b i	• A division of network functionality	1 (AO1 1a)	Candidate's responses may differ from the given answer but must represent conceptually the same thing. e.g. "a layer is where jobs/processes are split up" would receive the mark.
7	b ii	<ul style="list-style-type: none"> It is self-contained (1)... ...it allows different developers to concentrate on one aspect of the network (1) A layer can be taken out and edited without affecting other layers (1)... ...it promotes interoperability between vendors and systems (1) 	2 (AO1 1a)	1 mark to be awarded for the correct identification and 1 for a valid description up to a maximum of 2 marks.
7	c	• It is easy to add a new node or device	2	1 mark to be awarded for each correct
Question	Answer		Marks	Guidance
	<ul style="list-style-type: none"> Fewer data collisions can occur If a node or device fails it does not affect the rest of the network A signal does not need to be transmitted to all computers in the network 		(AO2 1b)	reason to a maximum of 2 marks. Any valid comparisons to other topologies can be awarded marks.

10	a	<ul style="list-style-type: none"> The computers are geographically remote/ distanced/ more than a mile apart Communication medium is not owned by the law firm 	1 (AO1 1a)	1 mark only to be awarded for a correct definition. Accept responses such as the company doesn't own the infrastructure. Do not accept 'Network over a wide area' or similar arrangement of wording.
10	b	<p>Two advantages from:</p> <ul style="list-style-type: none"> It would offer additional storage (1) so the company can take on more cases (1) It is a very efficient method of backing up data (1) and so saves the firm time and money (1) It would allow their employees to work from anywhere (1) so they can take cases from other countries (1) It is environmentally friendly (1) Easy to increase availability of storage (1) You don't need specialist network skills (1) so the firm don't need to employ more staff (1) The third party provides security (1) so the company saves money on staff and software/hardware (1) The third party provides backup (1) so the company saves money on staff and software/hardware (1) Cheaper as don't need own infrastructure (1) <p>Each advantage needs to be contextualised to gain 2 marks.</p>	4 (AO2 1b)	1 mark to be awarded for each correct advantage, with a mark for a discussion of the advantage related to the law firm. To a maximum of 2 advantages. The total number of marks to be awarded for this task is 4 marks. Responses which are not contextualised will gain a maximum of 1 mark per advantage (to a maximum of 2 advantages).

2021

7	a		1 mark per bullet either: <ul style="list-style-type: none">LAN is small geographical areaWAN is over a large geographical area or <ul style="list-style-type: none">LAN (usually) has own/dedicated infrastructureWAN uses external/shared infrastructure // by example (e.g. internet)	2	LAN is one building is NE - this does not make it a LAN. WAN is multiple buildings - NE, a LAN can be multiple buildings.																				
7	b		1 mark per bullet <ul style="list-style-type: none">Central switch labelled......all devices connected to central switch only (BOD not labelled switch)	2	Ignore anything superfluous																				
7	c	i	1 mark per section Wi-fi frequency <ul style="list-style-type: none">5GHz frequency can carry more data per second than a 2.4 GHz frequency // 5GHz frequency has can transfer data faster5GHz frequency has a shorter range so access may be limited Interference <ul style="list-style-type: none">Causes errors which means signals need retransmitting which makes more trafficObjects may limit range // objects can block the signal Number of current users <ul style="list-style-type: none">more traffic means the same bandwidth is split // each user has less bandwidth // more collisions // more users = more traffic/data sent Type of network traffic <ul style="list-style-type: none">transmitting videos/large files will take up more bandwidth than text files	4	Answer must be more than repeating the question, question is how																				
7	c	ii	1 mark e.g. <ul style="list-style-type: none">If using wireless or wiredError rateBandwidth	1	Accept others e.g. Topology Distance between nodes																				
7	e		1 mark for each row <table border="1"><thead><tr><th>Protocol</th><th>Email</th><th>Transferring files</th><th>Accessing websites</th></tr></thead><tbody><tr><td>POP</td><td>✓</td><td></td><td></td></tr><tr><td>FTP</td><td></td><td>✓</td><td></td></tr><tr><td>SMTP</td><td>✓</td><td></td><td></td></tr><tr><td>HTTPS</td><td></td><td></td><td>✓</td></tr></tbody></table>	Protocol	Email	Transferring files	Accessing websites	POP	✓			FTP		✓		SMTP	✓			HTTPS			✓	4	
Protocol	Email	Transferring files	Accessing websites																						
POP	✓																								
FTP		✓																							
SMTP	✓																								
HTTPS			✓																						


2020

2	a		1 mark for LAN 1 mark per bullet for justification to max 2 <ul style="list-style-type: none"> Small geographic area They will own the hardware // dedicated hardware // do not need to use outside hardware // controlled by Hope 	3	
2	b		Modem // router	1	Mark first given
2	c	i	1 mark per bullet to max 2 <ul style="list-style-type: none"> Wifi signal/bandwidth will be weaker/less because // 5GHz is only short range ...bedroom further away from WAP than kitchento get to bedroom has to go through floor/walls etc. 	2	
2	c	ii	1 mark per way e.g. <ul style="list-style-type: none"> Change to 2.4Ghz Install a signal booster // another WAP // mesh wifi Move WAP closer to the bedroom Remove obstructions // by example Reduce number of devices connected Change channel to one not being used in locality 	2	Reduce interference is NE - they need to say how this can be achieved
2	d		1 mark per bullet to max 3 e.g. <ul style="list-style-type: none"> No server (required for client-server) Computers are directly connected to each other Computers are independent / equal Decentralised Computers will have software installed/updated individually // no central installation/updates Computers will need own security // no central security Computers will have their own files // no central file storage Less initial cost / maintenance Specialist required to setup client-server Easier to add new devices Lesser need for file sharing If any device fails/is removed the remainder can continue 	3	Be careful MP1 is not just saying it does not need to connect to the server - the MP is that there is no server. Accept reasonable points in reverse.

2	e		<p>1 mark per benefit to max 4, 1 mark per drawback to max 4 e.g.</p> <p>Benefit</p> <ul style="list-style-type: none"> Can access files from any device ... e.g. they can instantly access the data from laptop and mobile phone Can access files from anywhere // Can access from anywhere with access to the Internet Can pay for auto-backups // don't have to backup manually Security may be higher than at home May be free of cost ... you do not need to buy more hardware Easier/quicker to share files with others More available storage space on her device Easier to increase storage capacity (not memory) Can be used a backup in case of data loss <p>Drawback</p> <ul style="list-style-type: none"> Cannot access files if no Internet access Not in control of security (bod less secure) ...data may be hacked/stolen May cost monthly fee ... which could be more long term than buying hardware May not be a backup // if cloud storage fails you have lost your data Data must be transferred to computer to read may be intercepted Connection may be slow ... therefore takes time to upload/download May be issues as to who owns the data If stop paying / leave subscription other storage for files needs to be found If login details are forgotten/lost may not have access to files 	6	<p>Mark breadth and depth of knowledge.</p> <p>1 mark for each valid point/expansion. Allow specific examples as expansions for each point.</p> <p>Mark benefits to max 4 first, then look for max 4 from drawbacks</p>
---	---	--	---	---	---

6	a		1 mark per bullet <ul style="list-style-type: none">All devices connected to at least one other componentAll devices connected to all devices (individually or through another and not only through the printer)	2																
6	b		1 mark for each row. <table><tr><th>Statement</th><th>True</th><th>False</th></tr><tr><td>Ethernet is a protocol</td><td>✓</td><td></td></tr><tr><td>Ethernet uses wireless data transmission</td><td></td><td>✓</td></tr><tr><td>Ethernet can transmit data up to 100Gbits per second</td><td>✓</td><td></td></tr><tr><td>Ethernet is within the TCP/IP stack</td><td>✓</td><td></td></tr></table>	Statement	True	False	Ethernet is a protocol	✓		Ethernet uses wireless data transmission		✓	Ethernet can transmit data up to 100Gbits per second	✓		Ethernet is within the TCP/IP stack	✓		4	2 ticks in 1 row = 0 mark
Statement	True	False																		
Ethernet is a protocol	✓																			
Ethernet uses wireless data transmission		✓																		
Ethernet can transmit data up to 100Gbits per second	✓																			
Ethernet is within the TCP/IP stack	✓																			
6	c	i	1 mark per bullet to max 3 <ul style="list-style-type: none">URL sent to DNS // request sent to DNS for/with URLDNS looks up/finds to IP in its databaseDNS returns IPIF not found, DNS sends to higher level DNS	3	Request sent to DNS is NE without saying the URL is sent. Only penalise missing or incorrect term for DNS once then FT															
6	c	ii	1 mark per bullet to max 3 e.g. <ul style="list-style-type: none">Destination IP/addressSender IP/addressPacket NumberPacket sizeNumber of packetsError detection method/value	3	Do not award MAC address															

2019

4	a	i	<p>1 mark per bullet</p> <ul style="list-style-type: none"> Four laptops/computers, a server and printer present and clearly identifiable (positions do not matter) Switch as a device clearly identifiable... ...all devices directly connected to the switch and only the switch (FT from MP2) <p>e.g.</p> 	<p>3 AO2 1a (3)</p>	<ul style="list-style-type: none"> Printer may be connected to the server or to the switch. Accept PC for laptop If the candidates has given server/switch or switch/server in the centre, mark the first one in their list. If they give server/switch, they do not get MP2, but allow access to MP3.
4	a	ii	<p>1 mark per bullet to max</p> <ul style="list-style-type: none"> To connect the devices together Receives data/packets/traffic Direct/send data/packets/traffic only to its destination Creates/generates a list of devices connected to it as it receives signals Uses MAC addresses of devices connected to it 	<p>2 AO1 1a (1) AO2 1a (1)</p>	<ul style="list-style-type: none"> Do not award information, penalise once. Do not award packet switching out of context. Accept MP3 by example
4	b	i	<p>1 mark per bullet to max 2</p> <ul style="list-style-type: none"> Wireless transmission is slower than cabled More devices/users could be connected e.g. mobile phones // increase in traffic ...reducing bandwidth available for each user // insufficient bandwidth for users/demand Wireless can be limited by interference ...such as walls that disrupt the signal // from other wireless networks/users 	<p>2 AO1 1b (1) AO2 1b (1)</p>	<ul style="list-style-type: none"> Bod - wireless has less bandwidth
4	b	ii	<p>1 mark per factor e.g.</p> <ul style="list-style-type: none"> Bandwidth available Number of users (using the network at the same time) (Number of) data collisions Interference // by example e.g. walls Distance data has to travel // signal strength Amount of data being transferred Applications being used Server/CPU performance Using a hub instead of a switch 	<p>2 AO1 1a (2)</p>	<ul style="list-style-type: none"> Do not accept wireless/wired connections Bod answers such as cable length
5	a		<p>1 mark per bullet to max 5</p> <ul style="list-style-type: none"> The website is hosted on a webserver The website/webserver has an IP address (Browser) sends URL to DNS URL has a linked IP DNS finds IP If DNS cannot find the IP it passes request to higher DNS ...if not found return error IP address sent back to the browser/computer (Browser) sends request to IP/webserver <u>Webserver</u> processes request for the website/webpage ...<u>webserver</u> sends the webpage/file/data to the user 	<p>5 AO1 1b (3) AO2 1b (2)</p>	<ul style="list-style-type: none"> Do not award 'the IP goes to the webserver' Allow domain name in place of URL 'DNS finds the IP of the URL it is given' gets 2 marks, 1 for URL has linked IP and 1 for DNS finds the IP MP 11 do not accept webserver <i>loads</i> the webpage on the user's computer
5	b	i	<p>1 mark per bullet to max 2</p> <ul style="list-style-type: none"> A layer can be removed/changed etc. ...without affecting any other layers Each layer has its own purpose // separates the purposes // self-contained ...so it does not need to consider what the other layers do ...so it can be programming individually Individual protocols are each smaller/simpler to manage Different layers can interface with different hardware 	<p>2 AO1 1a (1) AO1 1b (1)</p>	<ul style="list-style-type: none"> Do not award descriptions of what the layers do - the question asks why layers are used. Do not award vague answers e.g. layers make it easier to work with

5	b	ii	1 mark for each protocol.	4 AO2 1a (4)	<ul style="list-style-type: none">Mark first answer in each box										
<table><tr><th>Task</th><th>Protocol</th></tr><tr><td>Sending an email from one mail server to another</td><td>SMTP // Simple Mail Transfer Protocol</td></tr><tr><td>Transmitting a file from a client to a server</td><td>FTP // File Transfer Protocol</td></tr><tr><td>Viewing a website using a web browser</td><td>HTTP // Hypertext Transfer Protocol HTTPS // Hypertext Transfer Protocol Secure</td></tr><tr><td>Downloading an email to your computer</td><td>IMAP // Internet Message Access Protocol POP(3) // Post Office Protocol</td></tr></table>						Task	Protocol	Sending an email from one mail server to another	SMTP // Simple Mail Transfer Protocol	Transmitting a file from a client to a server	FTP // File Transfer Protocol	Viewing a website using a web browser	HTTP // Hypertext Transfer Protocol HTTPS // Hypertext Transfer Protocol Secure	Downloading an email to your computer	IMAP // Internet Message Access Protocol POP(3) // Post Office Protocol
Task	Protocol														
Sending an email from one mail server to another	SMTP // Simple Mail Transfer Protocol														
Transmitting a file from a client to a server	FTP // File Transfer Protocol														
Viewing a website using a web browser	HTTP // Hypertext Transfer Protocol HTTPS // Hypertext Transfer Protocol Secure														
Downloading an email to your computer	IMAP // Internet Message Access Protocol POP(3) // Post Office Protocol														

2018

Question	Answer			Mark	Guidance																		
2	(a)		1 mark for LAN 1 mark per bullet for justification to max 2 <ul style="list-style-type: none">• Small distance/geographical area by example e.g. same building/house• Connected by own hardware/infrastructure // not connecting through Internet // no hired/third-party infrastructure // dedicated connection	3 AO2 1a (2) AO2 1b (1)	Do not allow – in a local area, local needs to be quantified in some way. No marks for WAN.																		
2	(b)		1 mark per row <table border="1"><thead><tr><th>Description</th><th>Ethernet</th><th>Wifi</th></tr></thead><tbody><tr><td>A wired connection</td><td>✓</td><td></td></tr><tr><td>More likely to be affected by interference</td><td></td><td>✓</td></tr><tr><td>Data can be transmitted at a faster speed</td><td>✓</td><td></td></tr><tr><td>Wireless transmission</td><td></td><td>✓</td></tr><tr><td>Shorter transmission range before data is lost</td><td></td><td>✓</td></tr></tbody></table>	Description	Ethernet	Wifi	A wired connection	✓		More likely to be affected by interference		✓	Data can be transmitted at a faster speed	✓		Wireless transmission		✓	Shorter transmission range before data is lost		✓	5 AO1 1a (5)	0 mark for row with >1 tick
Description	Ethernet	Wifi																					
A wired connection	✓																						
More likely to be affected by interference		✓																					
Data can be transmitted at a faster speed	✓																						
Wireless transmission		✓																					
Shorter transmission range before data is lost		✓																					
2	(c)	i	1 mark per bullet to max 2 <ul style="list-style-type: none">• Directs packets/data to destination // directs packets/data in a network• Receives packets/data from the network/Internet• Forwards packets/data to other computers on the network/Internet• Connects (different) networks together // e.g. joins home network to Internet• Has (public) IP address for LAN• Designates (private) IP addresses to network nodes	2 AO1 1a (1) AO1 1b (1)	Controls flow of data as BOD for bullet 1. Bullet 1 needs to refer to the router directing the destination e.g. it is making a decision/choice on where to send it. Bullet 4 - it has to be referring to the connection between the Internet and home network, or forwarding of data between them. Just referring to accessing Internet is not enough. Do not allow information for data/packets																		
2	(c)	ii	1 mark per item to max 2 e.g. <ul style="list-style-type: none">• Network Interface card / NIC• Wireless access point / WAP• Wireless network interface card / WNIC / wi-fi card• Bridge• Switch• Hub• Repeater // wireless extender/booster• Server	2 AO1 1a (2)	Accept modem, power line adapter, Ethernet jack Must be an item of network hardware																		
2	(d)	i	Domain Name Server // DNS.	1 AO1 1a (1)	Allow Server/service/system																		

5	(a)		<ul style="list-style-type: none"> An agreement / set of rules / standard ...for how computers should communicate // how data is sent/received/transmitted on a network Example of what could be agreed in the protocol (e.g. speed / error checking / etc.) 	2 AO2 1b (2)	Do not award set of instructions for bullet 1
5	(b)	(i)	1 mark for protocol, 1 mark for description <ul style="list-style-type: none"> FTP / file transfer protocol Uses a client-server model // sends from client to server // sends from server to client 	2 AO2 1b (2)	If protocol wrong, no mark for description
5	(b)	(ii)	1 mark for protocol, 1 mark for description e.g. <ul style="list-style-type: none"> HTTPS / hyper text transfer protocol secure Encrypts the connection/data // Uses SSL/secure socket layer 	2 AO2 1b (2)	If protocol wrong, no mark for description
5	(c)		1 mark for IMAP, 1 mark for SMTP. IMAP <ul style="list-style-type: none"> Retrieves/accesses/downloads (a copy of an) e-mail Allows synchronisation/management of account SMTP: <ul style="list-style-type: none"> Sends/forwards/transmits e-mail 	2 AO1 1b (2)	Marks are for IMAP retrieving, SMTP sending. At this stage do not worry about where they are going. Question does not refer to email, so response must in some way refer to email/message. Sends/receives data is not enough.

2017

6	b	i	Modem/Router	1	
6	b	ii	max 2 marks per hardware device e.g. <ul style="list-style-type: none"> NIC... ...to connect Ethernet cable to computer Router... ...to receive and transmit data within the network/to send data around a network/to join networks together/to connect to the Internet Bridge... ...connect networks together Switch... ...to connect multiple devices together / directs traffic to its destination. Hub... ...to connect multiple devices together. Server... ...to store the data/manage the network/store backups Wireless Access Point/WAP... ...to allow for wireless transmission of data Cables... ...to connect devices together Modem... ...to connect computers via telephone lines // to covert digital data to analogue / to convert analogue data to digital. 	4	Accept any hardware device that can be used to create/set up/produce a network. Device must be different than answer given in 6bi Accept repeater / range extender / powerline adaptor etc.

2016

Question		Answer/Indicative Content	Marks	Guidance
7	a	<ul style="list-style-type: none"> • WAN is over a large geographical area/needs to transmit over a large distance // a LAN is over a small geographical area. • WAN uses <u>external</u> hardware/infrastructure/cables/network // LAN has its <u>own</u> infrastructure/cables/network/hardware due to distance/practicalities 	2	<p>NB Examples of infrastructure/hardware are allowed for WAN e.g. satellite, phone lines, Internet</p> <p>Allow LAN as <u>Ethernet</u> for second bullet</p> <p>NOT wide area for WAN</p>
7	b	<p>2 marks per benefit</p> <p>E.g.</p> <ul style="list-style-type: none"> • All files can be stored centrally • ...so workers can access files from any computer • ...all computers can update the central database/file • ...Peer-to-peer files might be stored on their own computers/spread across many computers • Backups are central • ...all data is backed up each time • ...individual computers do not need to backup their own data • ...Peer-to-peer may need to perform their own backups. • Monitor clients • ...to ensure they are working correctly • Upgrade software centrally • ...so you do not have to install on each computer individually • Central security (antivirus/firewall) • ...do not need to install protection on all computers • ...Peer-to-peer individual security may need to be installed on individual computers 	4	<p>Do not allow:</p> <ul style="list-style-type: none"> -easy to share data -"more secure"
7	c	<ul style="list-style-type: none"> • WWW is the web pages (that are stored on servers) • Internet is the infrastructure // collection of networks 	2	

2015

9	a	<p>e.g.</p> <ul style="list-style-type: none"> • record log on / log off times • remote access / view users' screens • audit printing • keylogging • monitor internet usage / downloads • monitoring emails / files sent / copied • inspect files in users' areas 	2	<p>Accept answers which show how the LAN is used to <u>monitor the work of employees</u> rather than advantages of using a LAN in general</p>
	b	<ul style="list-style-type: none"> • IP addresses can be changed / are allocated as needed • MAC addresses can't be changed / every device has a fixed MC address • IP(v4) addresses are 4 bytes long • MAC addresses are 6 bytes long • IP(v4) addresses are normally written in denary • MAC addresses are normally written in Hex • IP addresses are configured by software • MAC addresses are configured in hardware • IP addresses are used for routing across a WAN/internet • MAC addresses are only used within the LAN <p>[marks in pairs, maximum 2 pairs]</p>	4	<p>For bullets 3 and 4, accept answers where candidates refer to IPv6 being 16 bytes(128 bits). Award one mark if candidates state that IP addresses and MAC addresses are of different size.</p>

2014

1	a	<ul style="list-style-type: none"> Computers are <u>connected to each other</u> Restricted to a small geographical area/site/other suitable example <u>Dedicated</u> wired or WiFi connections 	2	<p>For the first bullet point candidates should be describing a network – just the idea that computers are connected to "something" is not enough.</p> <p>For the third bullet point, just "connected by cables" is not enough as there is no indication these are dedicated cables for the network.</p>
	b	<ul style="list-style-type: none"> One central hub/switch/router/server/connection point All computers/devices connected to this central point 	2	<p>Accept diagram which shows the points in the mark scheme. Note that if the diagram is not annotated or described one mark can still be given for the second bullet point.</p>
	c	<ul style="list-style-type: none"> bus ring 	2	<p>Accept other standard names of topologies that are not on the specification:</p> <ul style="list-style-type: none"> - line, linear (only as an alternative for bus) - tree/hierarchical, mesh - hybrid - loop(only as an alternative to ring) <p>Do not accept serial or circle</p>