

Hierarchical Projection as a Validity Layer for ESG Promise Verification: Multilingual Evidence

Sheng-Xun Chen
National Central University
Taoyuan, Taiwan
tom1030507@gmail.com

Hsin-Chen Han
National Central University
Taoyuan, Taiwan
0720samson@gmail.com

Chun-Wei Chen
National Central University
Taoyuan, Taiwan
aaronwayway@gmail.com

Shi-Yu Huang
National Central University
Taoyuan, Taiwan
huangshiyu0318@gmail.com

ABSTRACT

ESG promise verification requires jointly predicted fields to satisfy hard parent-child constraints, particularly when outputs are intended for audit-oriented use. We study hierarchical projection as a retraining-free validity layer for field-wise classifiers. Seven decision rules are compared on identical cross-fitted probabilities and test rows in Chinese, followed by projection-versus-argmax replication across English, French, Japanese, and Korean corpora. Projection reduces the Chinese invalid-tuple rate from 12.55% to zero by construction. Its official weighted macro-F1 contrast is undetected ($\Delta = -0.001$, $p_{\text{Holm}} = 1.000$), while pre-specified tuple accuracy improves by +0.035 ($p_{\text{Holm}} = .001$). Across 32 external backbone-by-loss arms, tuple accuracy improves in all 32, whereas weighted macro-F1 improves in 14. These results position hierarchical projection not as a guaranteed route to higher field-wise scores, but as a practical way to guarantee coherent outputs and repeatedly improve complete-output correctness, with field-score trade-offs varying across models and corpora.

KEYWORDS

ESG, promise verification, hierarchical classification, constrained decoding, evaluation metrics

1 INTRODUCTION

ESG promise verification is intended to support audit-oriented decisions, for which internal consistency is a basic requirement.

Promise status, verification timeline, evidence status, and evidence quality describe one claim, and their parent-child implications determine whether the combined output is usable as a coherent record. A paragraph predicted to contain no promise cannot coherently receive a substantive timeline, and a prediction of no evidence cannot coherently receive an evidence quality. Individually plausible field labels can therefore form an illegal tuple.

Field-wise weighted macro-F1 is a standard measure of classification quality for multi-field tasks, and it is the official ranking metric here. It does not, however, assess whether the four predictions form a jointly legal tuple. A validity-preserving rule may therefore repair an unsupported child without receiving a corresponding field-score gain. The weight the metric places on legality is not merely small: because each field is scored on its own, an illegal tuple still collects 44.3% of the available weighted field credit

on average, since a field answered correctly is paid for even when the ancestors that would license it were answered wrongly. We ask whether a retraining-free inference constraint can guarantee legal outputs, and how its effects differ under field-wise and whole-tuple evaluation.

We answer that question through a controlled decision comparison rather than a model or competition-performance claim. Seven rules consume identical cross-fitted base probabilities and test rows. Projection acts as a validity layer over those probabilities: it guarantees a legal tuple without changing the encoder or retraining the classifier. In Chinese, the confirmatory official-score family is null, yet pre-specified exact whole-tuple accuracy improves under projection. Across four ML-Promise languages, four backbones per language, and two fixed training objectives, tuple accuracy improves in all 32 external arms while weighted macro-F1 has a mixed sign. These are within-corpus decision contrasts; raw scores do not isolate language effects.

Our contributions are:

- (1) We formalize the supplied hierarchy as 17 legal tuples out of 120 and verify that all 2,000 audited Chinese paragraphs from 49 companies are legal.
- (2) We evaluate projection as a retraining-free validity layer in a seven-rule controlled comparison, reporting the complete confirmatory official-score family and the pre-specified tuple family, including adverse results.
- (3) We externally replicate the within-arm projection contrast across four languages and 32 backbone-by-loss arms, while keeping post-hoc metrics and structural/backbone screens explicitly exploratory.

2 RELATED WORK

The AI CUP task uses the four-part formulation described in the PromiseEval shared-task overview: identify an ESG promise, determine whether it has actionable evidence, assess the clarity of the promise-evidence pair, and assign a verification horizon [2]. ML-Promise is the associated multilingual corpus resource; we use its English, French, Japanese, and Korean releases for external replication [15]. This joint verification problem differs from ClimateBERT-NetZero, which detects corporate and national net-zero or reduction targets and supports analysis of their ambition, rather than jointly assessing promise status, evidence, evidence quality, and timing [14].

These dependent outputs form a compact instance of hierarchical text classification, in which labels occupy a supplied structure and coherent predictions respect its ancestor relations [13]. The AI CUP hierarchy comes from the task’s official field logic: we neither discover the hierarchy nor propose a new hierarchical architecture. Instead, we compare decision rules over the same field-wise probabilities while preserving or ignoring that given structure.

Yu et al. introduced path-constrained MicroF1 and MacroF1, under which a correct node receives credit only when all its ancestors are also correct [17]. Ji et al. later named this family *C-metrics* [11]. Our C-wF1 adapts Yu et al.’s principle to this field-based task and its official field-weighted macro-F1; it is therefore not the original C-MacroF1.

Plaud et al. observed from point estimates that constrained F1 variants did not globally change method rankings in their experiments [13]. That observation and our post-hoc paired contrast inference answer different questions: ranking a collection of models is not the same estimand as a paired difference between decision rules on shared rows and probabilities. Moreover, our hF changes both consistency treatment and macro-versus-micro aggregation. Of the two post-hoc metrics, only C-wF1 isolates the treatment of ancestor-inconsistent predictions while retaining the official field aggregation.

3 TASK AND DATA

Outputs and legal states. The task predicts four fields for each paragraph. We study the AI CUP 2026 VeriPromiseESG development release [1]. Its label inventory and parent–child logic follow PromiseEval [2]. Promise status (PS) is *Yes* or *No*. Verification timeline (VT) is *already*, *within two years*, *between two and five years*, *more than five years*, or *N/A*. Evidence status (ES) is *Yes*, *No*, or *N/A*; evidence quality (EQ) is *Clear*, *Not Clear*, *Misleading*, or *N/A*. These fields obey hard implications: PS=*No* requires VT=ES=EQ=*N/A*, whereas PS=*Yes* requires one of the four substantive timelines and ES in {*Yes*, *No*}. In turn, ES=*No* requires EQ=*N/A*, whereas ES=*Yes* requires one of the three substantive quality labels. Thus the Cartesian label space has $2 \times 5 \times 3 \times 4 = 120$ combinations, but only

$$1 + 4(1 + 3) = 17 \quad (1)$$

legal tuples: one for PS=*No*, and for each of four timelines either one ES=*No* state or three ES=*Yes* quality states.

Development-set audit. The release contains 2,000 labeled development paragraphs from 49 source reports and 49 companies. All 2,000 development rows obey the hierarchy, collectively realizing 15 of the 17 legal states (Table 1). The rarest EQ label, *Misleading*, has only two instances; we therefore make no improvement or significance claim for that class.

All 49 development reports also occur in the unlabeled competition test data. Because competition test labels are unavailable, we infer no label-derived test statistic. Each company contributes one report. Consequently, in this corpus a document-disjoint split is also company-disjoint, rather than a separate company-level experiment.

External replication corpora. ML-Promise provides labels in the same four fields [15]. After normalizing its releases to the common 17-state vocabulary, we retain 400 English paragraphs from

Table 1: AI CUP 2026 dataset composition and hierarchy audit.

Statistic	Development	Competition test
Paragraphs	2000	2000
Source reports (PDFs)	49	49
shared with other split	49	49
Companies	49	49
Gold labels available	Yes	No
Gold hierarchy-valid tuples	2000 / 2000	n/a
Legal states observed	15 / 17	n/a
<i>Rarest classes</i>		
within_2_years	34	n/a
Misleading	2	n/a

9 reports, 400 French paragraphs from 9 reports, and 400 Japanese paragraphs from 19 reports. The Korean release supplies labels, report URLs, and page numbers but no text; we extract the corresponding 500 PDF pages from 32 reports and use the first 384 tokens of each page. The extracted Korean text is not redistributed. Korean has no gold *Misleading* example, and its page-level input is not directly comparable to the paragraph inputs. We therefore interpret only within-corpus paired decision contrasts, never raw score differences between languages.

4 METHODS


4.1 Shared Base Models

For the Chinese study, we use hf1/chinese-roberta-wwm-ext-large as the fixed encoder. BERT-Large has 24 layers and hidden size 1024 [8]; the pinned HFL configuration matches those dimensions. Cui et al. document the checkpoint’s Chinese RoBERTa-WWM family: it uses whole-word masking, extended pretraining data, and no next-sentence prediction [7]. We mean-pool its token representations and attach four independent linear heads, one per field. The encoder is shared, but neither it nor the heads condition on predicted ancestors. The input is paragraph text only; report URL, company, ticker, and page metadata are excluded.

All fits use the same frozen fine-tuning recipe: maximum length 384, 12 epochs, minibatches of 8 with two-step gradient accumulation (effective size 16), and AdamW with backbone and head learning rates 2×10^{-5} and 10^{-4} . The schedule is cosine with 10% warm-up and layer-wise decay 0.9. The four cross-entropy losses use the official PS/VT/ES/EQ weights 0.20/0.15/0.30/0.35 and label smoothing 0.1. For Train size n , K_t classes present in field t , and class support $n_{t,c}$, the class weight is $\min\{10, n/(K_t n_{t,c})\}$ when $n_{t,c} \geq 5$, and 1 otherwise. Hierarchy masking is disabled. We average the last three epoch checkpoints and perform no label-driven early stopping.

For the external fixed arms, English uses RoBERTa-large [12] and French, Japanese, and Korean use XLM-R-large [5]. English robustness runs add large DeBERTa-v3 [9] and ELECTRA [4] checkpoints plus RoBERTa-base. The other languages add RemBERT [3],

(a) Task hierarchy



$$1 + 4 \times (1 + 3) = 17 \text{ legal tuples}$$

$$\text{of } 2 \times 5 \times 3 \times 4 = 120 \text{ combinations}$$

the other 103 are hierarchy-invalid

(b) Decision routes (alternatives, not stages)




Figure 1: The task hierarchy and the alternative decision routes. All routes consume identical base probabilities; projection and 17-state decoding guarantee a legal tuple, whereas independent argmax does not.

XLM-R-base, and mBERT [8]. The Chinese anchor adds three exploratory screens of its own, distinct from those English checkpoints: a Chinese DeBERTa-v2-320M [18], a Chinese ELECTRA-large discriminator [6], and the base-sized checkpoint of the primary encoder’s own family [7]. Every backbone uses the same maximum length, optimization recipe, three seeds, and five rotations. For each backbone we run the ordinary objective ($\lambda = 0$) and a fixed hierarchy-aware objective ($\lambda = 0.3$):

$$\mathcal{L} = \mathcal{L}_{\text{fields}} - \lambda \log \sum_{s \in \mathcal{S}} \prod_t p_{t,s_t}(x). \quad (2)$$

The second term is the semantic loss of Xu et al. [16]: it penalizes probability mass outside the 17 legal states without choosing which legal state is correct. Structural-loss and alternate-backbone comparisons are exploratory; the primary decision comparison uses $\lambda = 0$.

4.2 Metric-Aware Decision Calibration

Calibration is the second factor of the comparison: the results table crosses three calibration settings with the two validity-preserving output rules, and each rotation’s bias estimates are shared across both rules, which is what lets Table 2 be read as a factorial rather than as separate systems.

For field t and class c , decision calibration adds a class bias in log probability space:

$$z_{t,c}(x) = \log p_{t,c}(x) + b_{t,c}. \quad (3)$$

This changes decision boundaries and is not a claim of probability calibration. Each field’s bias vector is fitted by deterministic coordinate ascent with that field’s macro-F1 on the held-out Calibration partition as the objective, before either structured output rule is applied. The four objectives therefore decouple. Within every rotation, global and conditional biases are fitted separately; that rotation’s global fit is shared by M2/M5 and its conditional fit by M3/M6.

Global biases use every Calibration row. Conditional biases use all rows for PS, only gold PS=Yes rows for VT and ES, and only gold ES=Yes rows for EQ. The three child N/A classes are structurally absent from these subsets. Their biases are therefore unidentifiable and fixed as

$$b_{\text{VT},\text{N/A}} = b_{\text{ES},\text{N/A}} = b_{\text{EQ},\text{N/A}} = 0. \quad (4)$$

This has no effect on projection, which emits N/A only when its parent requires it. It does affect joint scores for (No, N/A, N/A, N/A); hence M6–M5 compares conditional with global estimation including their different estimable parameter sets.

Biases start at zero and are fitted by deterministic coordinate ascent over $[-3, 3]$ in increments of 0.05. Coordinates follow a fixed field and class order; a move requires a strict improvement, ties favor the smaller absolute bias (then the more negative value), and search stops after a pass without improvement or at 20 passes. Eligibility is determined from the corresponding Train subset: a class absent there is excluded from coordinate ascent and retains bias zero. Among Train-eligible classes, one absent from the matching Calibration subset also retains bias zero and is recorded as an absent-class fallback.

4.3 Validity-Preserving Output Rules

Complete projection. We treat projection as a validity layer over compatible field-wise probabilities, rather than as a new encoder or a claim of improved base-model accuracy. Projection is greedy and top-down. At each field it selects the highest-scoring class allowed by the chosen ancestors. Under PS=No, it sets VT, ES, and EQ to N/A. Under PS=Yes, it excludes N/A from VT and ES and chooses each field’s best substantive class. Under ES=No, EQ becomes N/A; under ES=Yes, projection chooses EQ’s best substantive class. These rules completely enforce both directions of every parent implication. This bidirectional projection always returns one of the 17 legal states; a one-way N/A overwrite would not.

Joint valid-state decoding. The alternative scores every s in the legal set $\mathcal{S}$ and returns

$$\hat{y} = \arg \max_{s \in \mathcal{S}} \sum_t \alpha_t \{\log p_{t,s_t}(x) + b_{t,s_t}\}, \quad \alpha_t = 1. \quad (5)$$

Fixing all task scales avoids giving the decoder additional tuned parameters.

Figure 1 summarizes seven *alternative* rules over identical cross-fitted base probabilities, not sequential stages: M0 is uncalibrated independent argmax; M1/M2/M3 use projection with respectively no, global, or conditional bias; and M4/M5/M6 use 17-state decoding with the same three bias choices. Only M0 can emit an illegal tuple.

5 EXPERIMENTAL DESIGN

We first define the shared evaluation protocols and inference. Table 2 then summarizes the controlled comparison interpreted in Section 6.

5.1 Cross-Fitted Evaluation Targets

We use five-way rotating three-way cross-fitting. For rotation k , Test is fold k , Calibration is fold $(k+1) \bmod 5$, and Train comprises the other three folds; the three partitions are mutually exclusive. After five rotations, every development paragraph has served as Test exactly once. We concatenate the 2,000 out-of-fold predictions and compute each metric once, rather than average fold-level F1 values whose present gold-label sets may differ. The three seeds 42, 123, and 456 each determine both a fold assignment and training randomness, so seed variation represents the complete pipeline.

The primary, document-disjoint protocol balances report row counts with a randomized greedy procedure. After a seeded shuffle, it processes reports from largest to smallest and randomly places each in one of the two currently lightest folds. It estimates unseen-report generalization and, given the corpus audit, is also company-disjoint.

The same-document protocol instead jointly stratifies by gold PS, ES, and VT. It shuffles rows within each joint-label bucket and deals them round-robin to the five folds. Every report represented in Calibration or Test must also occur in Train through a different paragraph. This estimates seen-report, unseen-paragraph generalization. The protocols are distinct estimands, not biased and unbiased versions of one quantity.

Within each protocol and seed, M0–M6 consume the same Test rows and base probabilities.

External runs use document-disjoint report grouping, three seeds, and five rotations. Each language has eight paired arms: four backbones under both $\lambda = 0$ and 0.3, giving 32 external arms. The fixed-arm table uses $\lambda = 0$: RoBERTa-large for English and XLM-R-large for the other three languages. Arm choice never depends on observed scores. The same-document protocol is descriptive and available only for the primary large backbone. The complete executed study contains 765 training artifacts and 1,050 row-level prediction files across five corpora.

5.2 Metrics and Inference

The field-wise weighted macro-F1 is a standard choice for multi-field classification, but it contains no term that assesses the joint

validity of a four-field tuple. For Chinese, the primary metric is the official weighted macro-F1,

$$\text{wF1} = 0.20F_{\text{PS}} + 0.15F_{\text{VT}} + 0.30F_{\text{ES}} + 0.35F_{\text{EQ}}, \quad (6)$$

where each F_t is field-level macro-F1 over classes present in the gold labels being scored. Because this denominator depends on gold support, per-class leverage differs by corpus: a unit gain on one EQ class contributes $0.35/3 = 0.1167$ to the Korean weighted total but $0.35/4 = 0.0875$ elsewhere. Pre-specified whole-tuple accuracy requires all four fields to match. Path-constrained weighted macro-F1 (C-wF1) and hierarchical F1 (hF) were adopted post hoc. C-wF1 retains the official field weights but counts a substantive child prediction as wrong when its predicted ancestors do not support it. Following the hierarchical precision/recall/F1 set-overlap definition [13], our hF micro-averages over emitted non-N/A field-value nodes: hP is total gold–prediction overlap divided by predicted nodes, hR divides the same overlap by gold nodes, and hF is their harmonic mean. For an inconsistent emitted tuple, we do not add missing ancestors before scoring; legal M1–M6 are unaffected because the conventions coincide for them. hF changes both consistency treatment and macro-versus-micro averaging, so the two supplementary metrics answer different questions.

ML-Promise has no official weighted metric. We therefore label its scores “AI CUP weights applied to ML-Promise.” All external comparisons remain paired within corpus, backbone, and λ .

For paired method contrasts, we perform a paired PDF-cluster bootstrap over 49 source-report clusters. Each of 10,000 replicates samples 49 reports with replacement using seed 20260814, applies the same sampled rows to both methods and all three seeds, computes the within-seed differences, and averages those differences. The five pre-specified contrasts are M1–M0, M3–M2, M4–M1, M6–M3, and M6–M5. M1–M0 changes only the output rule, with calibration held out of both arms; it is therefore the cleanest test of projection rather than the highest-scoring configuration. Our only confirmatory family applies Holm correction to these five contrasts on Chinese official wF1 [10]. Pre-specified Chinese tuple exact-match is a separate secondary family of five. Bracketed 95% intervals are uncorrected bootstrap percentile intervals; decisions use $p_{\text{Holm}} < .05$, not whether an interval excludes zero.

External replication was pre-registered around within-arm contrast directions; we additionally apply a report-cluster bootstrap only to the fixed English M1–M0 tuple contrast. We do not pool languages into a post-hoc significance test. C-wF1 and hF were added after the Chinese primary result, while structural-loss and alternate-backbone screens test robustness; all are exploratory and do not support confirmatory claims regardless of their nominal p -values.

6 RESULTS

Guaranteed validity and Chinese confirmatory evidence. Table 2 compares decision rules on identical base probabilities and Test rows. Independent argmax (M0) produces invalid tuples for 12.55% of document-disjoint predictions; projection and 17-state decoding (M1–M6) reduce this rate to zero by construction. This zero rate is a deterministic property of the validity layer, not evidence that the base model became more accurate. Pooled over both protocols, all seeds and all methods, M0 emits 1,527 illegal tuples in 12,000 rows,

Table 2: Document-disjoint cross-fitted results on the Chinese development set.

ID	Calibration	Decoding	wF1 (official)	PS	VT	ES	EQ	Tuple acc.	Invalid %
M0	None	Independent	0.572±0.003	0.796	0.464	0.650	0.424	0.359	12.6
M1	None	Projection	0.571±0.003	0.796	0.467	0.651	0.418	0.394	0.0
M2	Global	Projection	0.574±0.004	0.796	0.493	0.650	0.418	0.428	0.0
M3	Conditional	Projection	0.575±0.003	0.796	0.501	0.651	0.416	0.432	0.0
M4	None	17-state	0.571±0.005	0.799	0.468	0.648	0.420	0.388	0.0
M5	Global	17-state	0.576±0.001	0.796	0.493	0.649	0.423	0.430	0.0
M6	Conditional	17-state	0.567±0.008	0.784	0.494	0.634	0.418	0.427	0.0

Table 3: Chinese paired contrasts on the two pre-specified metrics. Official wF1 and tuple accuracy are separate Holm families of five. Intervals are uncorrected 95% report-cluster bootstrap intervals. Post-hoc C-wF1 and hF are discussed only in the text.

Metric	Contrast	Δ	95% CI	p_{Holm}
Weighted macro-F1 (official)	M1-M0	-0.001	[-0.006, 0.003]	1.000
	M3-M2	+0.001	[-0.004, 0.006]	1.000
	M4-M1	+0.000	[-0.005, 0.005]	1.000
	M6-M3	-0.008	[-0.018, 0.002]	0.416
	M6-M5	-0.008	[-0.016, -0.001]	0.171
Tuple accuracy	M1-M0	+0.035	[0.028, 0.043]	0.001
	M3-M2	+0.004	[-0.001, 0.008]	0.370
	M4-M1	-0.006	[-0.010, -0.002]	0.028
	M6-M3	-0.005	[-0.015, 0.004]	0.505
	M6-M5	-0.004	[-0.011, 0.004]	0.505

Table 4: Projection (M1) versus independent argmax (M0) on five corpora, each using its preselected primary backbone at $\lambda = 0$ and document-disjoint evaluation; values are means over three seeds. M1 guarantees 0% invalid output. The *N/A* and substantive net columns summarize changes in correct child predictions after projection. Official-score deltas should not be compared directly across corpora because macro-F1 averages over gold-present classes, and Korean contains no Misleading example.

Corpus	Rows	M0 illegal %	<i>N/A</i> net	Subst. net	Δ wF1	Δ tuple acc.
Chinese (AI CUP)	2,000	12.55	+395	-264	-0.0011	+0.0350
English	400	23.17	+148	-86	+0.0032	+0.0725
French	400	21.08	+150	-107	+0.0036	+0.0625
Japanese	400	31.25	+183	-245	-0.0131	+0.0708
Korean	500	22.73	+103	-148	-0.0192	+0.0293

and 95.2% of them break one of two rules: a substantive timeline under PS=No, or an evidence quality under ES=No. The failure is concentrated in predictions that deny a parent and then answer its children anyway, rather than spread evenly over the label space. The $\pm$ values are sample standard deviations across the three seeds. Because each seed determines both fold assignment and training randomness, they describe spread over the whole split-and-training pipeline, not a confidence interval.

Table 3 reports both pre-specified families in full. All five official wF1 contrasts are undetected after Holm correction. For the central M1-M0 contrast, $\Delta = -0.001$ with 95% interval $[-0.006, 0.003]$ and $p_{\text{Holm}} = 1.000$. This is absence of a detected difference; it does not establish a zero effect.

The null is not confined to that contrast. The seven decision rules span 0.0082 in official wF1, and that spread is itself a single contrast: M5 is the highest-scoring rule and M6 the lowest,

so the range equals $|M6 - M5|$, which has an interval excluding zero $[-0.016, -0.001]$ and still does not survive correction ($p_{\text{Holm}} = .171$). The largest gap between any two of the rules compared here is therefore below what this evaluation can resolve, which bounds what any decision-stage comparison on this benchmark can demonstrate.

Whole-tuple effects. Exact whole-tuple accuracy tells a different story. M1-M0 is $+0.035$ $[0.028, 0.043]$, $p_{\text{Holm}} = .001$. Conversely, joint legal-state decoding is not uniformly better: M4-M1 is -0.006 $[-0.010, -0.002]$, $p_{\text{Holm}} = .028$. Searching every legal state can therefore reduce whole-row correctness relative to greedy projection. The validity guarantee is shared, but the choice among legal tuples still matters.

The two calibration contrasts are also undetected. Conditional bias, fitted only on the subset each parent admits, is not distinguishable from global bias under either output rule (M3-M2 and M6-M5, on both pre-specified metrics). The hierarchy therefore constrains

the output rule usefully without also improving how the biases are estimated. The calibrated projection arms reach 0.428 and 0.432 on tuple accuracy against M1’s 0.394, a step no pre-specified contrast covers.

The post-hoc C-wF1 and hF M1–M0 point estimates are also positive (+0.004 and +0.003), but they do not alter the inferential hierarchy. In the same-document sensitivity analysis, C-wF1 remains positive at +0.002, while its interval $[-0.001, 0.005]$ crosses zero.

Multilingual replication. Table 4 fixes one arm per language before inspecting scores. Each uses document-disjoint evaluation and $\lambda = 0$.

In these fixed arms, projection has a positive N/A net and a negative substantive-class net in all five corpora. Whole-tuple accuracy rises in all five, whereas weighted macro-F1 rises only for English and French and falls for the other three.

Across all four external corpora and their four backbones at both loss settings, M1–M0 tuple accuracy is positive in 32/32 arms. The weighted macro-F1 contrast is positive in only 14/32: English 7/8, French 5/8, Japanese 0/8, and Korean 2/8. These are within-arm directions, not a raw score ranking across languages. Projection thus combines a deterministic validity guarantee with a repeated complete-tuple improvement, while its field-score effect is not directionally stable across arms.

For the pre-registered fixed English arm, the one-sided tuple effect is +0.0725. Its report-cluster bootstrap interval is $[0.0452, 0.1019]$ ($p = .0002$; nine report clusters). ML-Promise weighted scores use AI CUP weights applied to ML-Promise.

Exploratory robustness. On the Chinese anchor, structural loss lowers M0 invalidity from 12.55% to 5.18%; its pre-registered M1 wF1 effect is +0.00250 $[-0.00384, 0.00860]$ ($p = .427$). It also lowers invalidity in all 16 external language-by-backbone pairs, with mixed wF1 and tuple effects. The Chinese DeBERTa and ELECTRA screens likewise lack conclusive wF1 gains; the same-family base checkpoint’s lower invalidity contradicts a simple smaller-model mechanism.

7 DISCUSSION

The practical contribution of projection is its guarantee rather than a universal field-score gain. As a retraining-free layer over compatible field-wise probabilities, it enforces the supplied hierarchy in every arm and improves exact whole-tuple accuracy throughout the executed external matrix. Together with the Chinese pre-specified tuple gain, this repeated result shows that a validity layer can improve complete-output correctness without claiming that it improves the underlying encoder or the official score in every arm.

This guarantee is not cost-free in every scoring view. The measured ledger makes that trade-off explicit.

The N/A net is positive and the substantive-class net negative in all five fixed arms. If an independently predicted parent is wrong, projection may replace a correct substantive child with the structurally required N/A; when the parent is correct, the same operation can repair an unsupported child. Field-wise macro-F1 values these changes class by class, whereas tuple accuracy credits only four-field agreement. The field-score effect therefore varies across backbones and corpora. Post-hoc C-wF1 and hF point in the tuple

direction, but were chosen after the primary analysis and are not needed to establish the pre-specified secondary result.

Validity alone also does not identify the better structured rule. In Chinese, M4 scores all 17 legal states jointly yet loses tuple accuracy to greedy M1. Joint search can improve one field while changing another field that projection had already made correct. This adverse result cautions against treating a larger legal-state search as automatically superior; it does not imply that joint decoding must fail on other models or tasks.

7.1 Limitations

The corpora differ in language, reports, annotation distributions, and primary backbones, so the replication matrix is not a factorial estimate of a pure language effect. English and French each have only nine report clusters, and even Chinese inference resamples just 49. The 32/32 and 14/32 summaries are therefore descriptive directions across executed arms, not a pooled significance test. AI CUP weights applied to ML-Promise are not an official ML-Promise metric.

Korean has a further input mismatch: its 500 examples are first-384-token PDF pages rather than released paragraphs, and it has no gold *Misleading* example. We do not redistribute the extracted Korean text or source PDFs. The reported Korean predictions can be rescored, but retraining requires reconstructing the page inputs from their source documents.

Results for structural loss and other backbones remain exploratory. They show that reducing invalidity need not yield a conclusive gain on the official score, but the fixed loss weights and limited checkpoint set cannot characterize all training objectives or architectures. The Chinese rarest quality label has only two examples, Korean has none, and no class-level claim is licensed for it. Finally, each seed jointly changes folds and optimization randomness, so those sources of variation cannot be separated.

8 CONCLUSION

Hierarchical projection is not a guaranteed route to higher field-wise weighted macro-F1. It is instead a retraining-free validity layer that eliminates illegal tuples by construction and improves exact whole-tuple accuracy on the Chinese anchor and in all 32 evaluated external arms. Its field-score effect varies across models and corpora, but its logical guarantee does not. For audit-oriented tasks with dependent outputs, field-wise performance, whole-tuple correctness, and structural validity should therefore be reported together.

REFERENCES

- [1] AI CUP 2026 Organizers. 2026. ESG Sustainability Commitment Verification Competition 2026 (VeriPromiseESG4K). AIda competition website. https://www.aidea-web.tw/aicup_veripromiseesg
- [2] Chung-Chi Chen, Yohei Seki, Hakusen Shu, Anaïs Lhuissier, Juyeon Kang, Han-wool Lee, Min-Yuh Day, and Hiroya Takamura. 2025. SemEval-2025 Task 6: Multinational, Multilingual, Multi-Industry Promise Verification. In *Proceedings of the 19th International Workshop on Semantic Evaluation (SemEval-2025)*. Association for Computational Linguistics, Vienna, Austria, 2461–2471. <https://aclanthology.org/2025.semeval-1.321/>
- [3] Hyung Won Chung, Thibault Févry, Henry Tsai, Melvin Johnson, and Sebastian Ruder. 2021. Rethinking Embedding Coupling in Pre-trained Language Models. In *International Conference on Learning Representations*. <https://arxiv.org/abs/2010.12821>

- [4] Kevin Clark, Minh-Thang Luong, Quoc V. Le, and Christopher D. Manning. 2020. ELECTRA: Pre-training Text Encoders as Discriminators Rather Than Generators. In *International Conference on Learning Representations*. <https://arxiv.org/abs/2003.10555>
- [5] Alexis Conneau, Kartikay Khandelwal, Naman Goyal, Vishrav Chaudhary, Guillaume Wenzek, Francisco Guzmán, Edouard Grave, Myle Ott, Luke Zettlemoyer, and Veselin Stoyanov. 2020. Unsupervised Cross-lingual Representation Learning at Scale. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*. Association for Computational Linguistics, 8440–8451. <https://doi.org/10.18653/v1/2020.acl-main.747>
- [6] Yiming Cui, Wanxiang Che, Ting Liu, Bing Qin, Shijin Wang, and Guoping Hu. 2020. Revisiting Pre-Trained Models for Chinese Natural Language Processing. In *Findings of the Association for Computational Linguistics: EMNLP 2020*. Association for Computational Linguistics, 657–668. <https://doi.org/10.18653/v1/2020.findings-emnlp.58>
- [7] Yiming Cui, Wanxiang Che, Ting Liu, Bing Qin, and Ziqing Yang. 2021. Pre-Training With Whole Word Masking for Chinese BERT. *IEEE/ACM Transactions on Audio, Speech, and Language Processing* 29 (2021), 3504–3514. <https://doi.org/10.1109/TASLP.2021.3124365>
- [8] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*. Association for Computational Linguistics, Minneapolis, Minnesota, 4171–4186. <https://doi.org/10.18653/v1/N19-1423>
- [9] Pengcheng He, Jianfeng Gao, and Weizhu Chen. 2023. DeBERTaV3: Improving DeBERTa using ELECTRA-Style Pre-Training with Gradient-Disentangled Embedding Sharing. In *The Eleventh International Conference on Learning Representations*. <https://arxiv.org/abs/2111.09543>
- [10] Sture Holm. 1979. A Simple Sequentially Rejective Multiple Test Procedure. *Scandinavian Journal of Statistics* 6, 2 (1979), 65–70. <https://www.jstor.org/stable/4615733>
- [11] Ke Ji, Yixin Lian, Jingsheng Gao, and Baoyuan Wang. 2023. Hierarchical Verbalizer for Few-Shot Hierarchical Text Classification. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*. Association for Computational Linguistics, Toronto, Canada, 2918–2933. <https://doi.org/10.18653/v1/2023.acl-long.164>
- [12] Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. RoBERTa: A Robustly Optimized BERT Pretraining Approach. arXiv:1907.11692 [cs.CL] <https://arxiv.org/abs/1907.11692>
- [13] Roman Plaud, Matthieu Labeau, Antoine Saillenfest, and Thomas Bonald. 2024. Revisiting Hierarchical Text Classification: Inference and Metrics. In *Proceedings of the 28th Conference on Computational Natural Language Learning*. Association for Computational Linguistics, Miami, FL, USA, 231–242. <https://doi.org/10.18653/v1/2024.conll-1.18>
- [14] Tobias Schimanski, Julia Bingler, Mathias Kraus, Camilla Hyslop, and Markus Leippold. 2023. ClimateBERT-NetZero: Detecting and Assessing Net Zero and Reduction Targets. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, Singapore, 15745–15756. <https://doi.org/10.18653/v1/2023.emnlp-main.975>
- [15] Yohei Seki, Hakusen Shu, Anaïs Lhuissier, Hanwool Lee, Juyeon Kang, Min-Yuh Day, and Chung-Chi Chen. 2025. ML-Promise: A Multilingual Dataset for Corporate Promise Verification. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics. <https://aclanthology.org/2025.emnlp-main.1028/>
- [16] Jingyi Xu, Zilu Zhang, Tal Friedman, Yitao Liang, and Guy Van den Broeck. 2018. A Semantic Loss Function for Deep Learning with Symbolic Knowledge. In *Proceedings of the 35th International Conference on Machine Learning (Proceedings of Machine Learning Research, Vol. 80)*. PMLR, 5502–5511. <https://proceedings.mlr.press/v80/xu18h.html>
- [17] Chao Yu, Yi Shen, and Yue Mao. 2022. Constrained Sequence-to-Tree Generation for Hierarchical Text Classification. In *Proceedings of the 45th International ACM SIGIR Conference on Research and Development in Information Retrieval (Madrid, Spain)*. Association for Computing Machinery, New York, NY, USA, 1865–1869. <https://doi.org/10.1145/3477495.3531765>
- [18] Jiaxing Zhang, Ruyi Gan, Junjie Wang, Yuxiang Zhang, Lin Zhang, Ping Yang, Xinyu Gao, Ziwei Wu, Xiaoqun Dong, Junqing He, Jianheng Zhuo, Qi Yang, Yongfeng Huang, Xiayu Li, Yanghan Wu, Junyu Lu, Xinyu Zhu, Weifeng Chen, Ting Han, Kunhao Pan, Rui Wang, Hao Wang, Xiaojun Wu, Zhongshen Zeng, and Chongpei Chen. 2022. Fengshenbang 1.0: Being the Foundation of Chinese Cognitive Intelligence. *CoRR* abs/2209.02970 (2022). <https://arxiv.org/abs/2209.02970>