

# Living Documentation

Version 1.0.0-SNAPSHOT

# Table of Contents

<b>1. Introduction</b>	<b>1</b>
<b>2. Summary</b>	<b>2</b>
<b>3. Features</b>	<b>3</b>
<b>3.1. Manage database with Database Rider Core</b>	<b>3</b>
3.1.1. Scenario: Seed database using yml dataset	3
<b>3.2. Manage database with Database Rider CDI</b>	<b>5</b>
3.2.1. Scenario: Seed database using yml dataset	6
<b>3.3. Manage database with Database Rider Cucumber</b>	<b>8</b>
3.3.1. Scenario: Seed database using Database Rider in Cucumber tests	9
<b>3.4. Manage database with Database Rider and JUnit 5</b>	<b>11</b>
3.4.1. Scenario: Seed database using Database Rider in JUnit5 tests	11
<b>3.5. Dynamic data using scribable datasets</b>	<b>12</b>
3.5.1. Scenario: Seed database with groovy script in dataset	13
3.5.2. Scenario: Seed database with javascript in dataset	14
<b>3.6. Database assertion using expected datasets</b>	<b>15</b>
3.6.1. Scenario: Database assertion with yml dataset	15
3.6.2. Scenario: Database assertion with regular expression in expected dataset	16
3.6.3. Scenario: Database assertion with seeding before test execution	17
3.6.4. Scenario: Failling database assertion	18
3.6.5. Scenario: Database assertion using automatic transaction	19

# Chapter 1. Introduction

**Database Rider** aims for bringing [DBUnit](#) closer to your JUnit tests. Here are the main features:

- [JUnit rule](#) to integrate with DBUnit via annotations:

```
@Rule
public DBUnitRule dbUnitRule = DBUnitRule.instance(jdbcConnection);①

@Test
@DataSet(value = "datasets/yml/users.yml")
public void shouldSeedDataSet(){
    //database is seed with users.yml dataset
}
```

① The rule depends on a JDBC connection.

- [CDI integration](#) via interceptor to seed database without rule instantiation;
- JSON, YAML, XML, XLS, and CSV support;
- [Configuration](#) via annotations or yml files;
- [Cucumber](#) integration;
- Multiple database support;
- Date/time support in datasets;
- Scriptable datasets with groovy and javascript;
- Regular expressions in expected datasets;
- [JUnit 5](#) integration;
- [DataSet export](#);
- [Connection leak detection](#);
- Lot of [examples](#).

The project is composed by 5 modules:

- [Core](#): Contains the dataset executor and JUnit rule;
- [CDI](#): provides the DBUnit interceptor;
- [Cucumber](#): a CDI aware cucumber runner;
- [JUnit5](#): Comes with an [extension](#) for JUnit5.
- [Examples module](#).

# Chapter 2. Summary

Scenarios			Steps							Features: 6	
Passed	Failed	Total	Passed	Failed	Skipped	Pending	Undefined	Missing	Total	Duration	Status
Manage database with Database Rider Core											
1	0	1	4	0	0	0	0	0	4	000ms	passed
Manage database with Database Rider CDI											
1	0	1	4	0	0	0	0	0	4	01s 164ms	passed
Manage database with Database Rider Cucumber											
1	0	1	5	0	0	0	0	0	5	001ms	passed
Manage database with Database Rider and JUnit 5											
1	0	1	3	0	0	0	0	0	3	000ms	passed
Dynamic data using scribable datasets											
2	0	2	7	0	0	0	0	0	7	000ms	passed
Database assertion using expected datasets											
5	0	5	16	0	0	0	0	0	16	000ms	passed
Totals											
11	0	11	39	0	0	0	0	0	39	01s 167ms	

# Chapter 3. Features

## 3.1. Manage database with Database Rider Core

In order to manage database state in JUnit tests  
As a developer  
I want to use DBUnit in my tests.

Database Rider Core module brings [DBUnit](#) to your unit tests via [JUnit rules](#).

### Dependencies

To use it just add the following maven dependency:

```
<dependency>
  <groupId>com.github.dbunit-rules</groupId>
  <artifactId>core</artifactId>
  <version>1.0.0-SNAPSHOT</version>
  <scope>test</scope>
</dependency>
```

#### 3.1.1. Scenario: Seed database using yml dataset

*Given*

The following junit rules 🍌 (000ms)

```
@RunWith(JUnit4.class)
public class DBUnitRulesIt {
    Unresolved directive in documentation.adoc -
    include:../../src/test/java/com/github/dbunit/rules/DBUnitRulesIt.java
    [tags=rules]
}
```

- ① [EntityManagerProvider](#) is a simple Junit rule that creates a JPA entityManager for each test. DBUnit rule don't depend on EntityManagerProvider, it only needs a JDBC connection.
- ② DBUnit rule responsible for reading [@DataSet](#) annotation and prepare the database for each test.

*And*

The following dataset 🍌 (000ms)

*src/test/resources/dataset/yml/users.yml*

```
user:
  - id: 1
    name: "@realpestano"
  - id: 2
    name: "@dbunit"
tweet:
  - id: abcdef12345
    content: "dbunit rules!"
    date: "[DAY,NOW]"
    user_id: 1
follower:
  - id: 1
    user_id: 1
    follower_id: 2
```

*When*

The following test is executed: 🍷 (000ms)

```
Unresolved directive in documentation.adoc -  
include:../../../src/test/java/com/github/dbunit/rules/DBUnitRulesIt.java  
[tags=seedDatabase]
```



Source code of the above example can be [found here](#).

*Then*

The database should be seeded with the dataset content before test execution 🍷 (000ms)

## 3.2. Manage database with Database Rider CDI

In order to manage database state in **CDI** based tests  
As a developer  
I want to use DBUnit in a CDI test environment.

DBUnit CDI integration is done through a [CDI interceptor](#) which reads `@DataSet` to prepare database for CDI based tests.

CDI must be enabled in your test, see the following example:



```
@RunWith(CdiTestRunner.class) ①
@DBUnitInterceptor ②
public class DBUnitCDITest {

}
```

① [CdiTestRunner](#) is provided by [Apache Deltaspike](#) but you should be able to use other CDI test runners.

② Needed to activate DBUnit interceptor

## Dependencies

To use this module just add the following maven dependency:

```
<dependency>
  <groupId>com.github.dbunit-rules</groupId>
  <artifactId>cdi</artifactId>
  <version>1.0.0-SNAPSHOT</version>
  <scope>test</scope>
</dependency>
```

### 3.2.1. Scenario: Seed database using yaml dataset

*Given*



DBUnit interceptor is enabled in your test beans.xml: 🍌 (01s 164ms)

*src/test/resources/META-INF/beans.xml*

```
<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://java.sun.com/xml/ns/javaee"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://java.sun.com/xml/ns/javaee
http://java.sun.com/xml/ns/javaee/beans_1_0.xsd">
  <interceptors>

  <class>com.github.database.rider.cdi.DBUnitInterceptorImpl</class>
  </interceptors>
</beans>
```



Your test itself must be a CDI bean to be intercepted. if you're using [Deltaspike test control](#) just enable the following property in `test/resources/META-INF/apache-deltaspike.properties`:

```
deltaspike.testcontrol.use_test_class_as_cdi_bean=true
```

*And*

The following dataset 🍌 (000ms)

*src/test/resources/dataset/yml/users.yml*

```
Unresolved directive in documentation.adoc -
include:../../../../cdi/src/test/resources/datasets/yml/users.yml[]
```

*When*

The following test is executed: 🍷 (000ms)

```
Unresolved directive in documentation.adoc -  
include:../../../../cdi/src/test/java/com/github/dbunit/rules/cdi/DBUnitC  
DIIt.java[tags=seedDatabase]
```



Source code of the above example can be [found here](#).

Then

The database should be seeded with the dataset content before test execution 🍷 (000ms)

### 3.3. Manage database with Database Rider Cucumber

In order to manage database state in **BDD** tests  
As a BDD developer  
I want to use DBUnit along side my BDD tests.

DBUnit enters the BDD world through a dedicated JUnit runner which is based on [Cucumber](#) and [Apache DeltaSpike](#).

This runner just starts CDI within your BDD tests so you just have to use [Database Rider CDI interceptor](#) on Cucumber steps, here is the so called Cucumber CDI runner declaration:

```
Unresolved directive in documentation.adoc -  
include:../../../../src/test/java/com/github/dbunit/rules/bdd/DBUnitRulesBdd.java[]
```



As cucumber doesn't work with JUnit Rules, see [this issue](#), you won't be able to use Cucumber runner with *Database Rider Core* because its based on JUnit rules, but you can use DataSetExecutor in **@Before**, see [example here](#).

## Dependencies

Here is a set of maven dependencies needed by Database Rider Cucumber:



Most of the dependencies, except CDI container implementation, are bring by Database Rider Cucumber module transitively.

```
<dependency>
  <groupId>com.github.dbunit-rules</groupId>
  <artifactId>cucumber</artifactId>
  <version>1.0.0-SNAPSHOT</version>
  <scope>test</scope>
</dependency>
```

### *Cucumber dependencies*

Unresolved directive in documentation.adoc -  
include:../../../../cucumber/pom.xml[tags=cucumber-deps]

- ① You don't need to declare because it comes with Database Rider Cucumber module dependency.

### *DeltaSpike and CDI dependency*

Unresolved directive in documentation.adoc -  
include:../../../../cucumber/pom.xml[tags=deltaspike-cdi-deps]

- ① Also comes with DBUnit Rules Cucumber.
- ② You can use CDI implementation of your choice.

To use this module just add the following maven dependency:

## 3.3.1. Scenario: Seed database using Database Rider in Cucumber tests

### *Given*

The following feature 🍌 (001ms)

Unresolved directive in documentation.adoc -  
include:../../../../examples/jpa-productivity-boosters/src/test/resources/features/contacts.feature[]

### *And*

The following dataset 🍌 (000ms)

```
Unresolved directive in documentation.adoc -  
include:../../../../examples/jpa-productivity-  
boosters/src/test/resources/datasets/contacts.yml[]
```

*And*

The following Cucumber test 🍌 (000ms)

```
Unresolved directive in documentation.adoc -  
include:../../../../examples/jpa-productivity-  
boosters/src/test/java/com/github/dbunit/rules/examples/cucumber/Contac  
tFeature.java[]
```

*When*

The following cucumber steps are executed 🍌 (000ms)

```
Unresolved directive in documentation.adoc -  
include:../../../../examples/jpa-productivity-  
boosters/src/test/java/com/github/dbunit/rules/examples/cucumber/Contac  
tSteps.java[]
```

- ① As the Cucumber cdi runner enables CDI, you can use injection into your Cucumber steps.
- ② Here we use the Database Rider CDI interceptor to seed the database before step execution.



Source code for the example above can be [found here](#).

*Then*

The database should be seeded with the dataset content before step execution 🍌 (000ms)

## 3.4. Manage database with Database Rider and JUnit 5

In order to manage database state in [JUnit 5](#) integration tests

As a developer

I want to use DBUnit along side my JUnit 5 tests.

DBUnit is enabled in JUnit 5 tests through an [extension](#) named **DBUnitExtension**.

### Dependencies

To use the extension just add the following maven dependency:

```
<dependency>
  <groupId>com.github.dbunit-rules</groupId>
  <artifactId>junit5</artifactId>
  <version>1.0.0-SNAPSHOT</version>
  <scope>test</scope>
</dependency>
```

#### 3.4.1. Scenario: Seed database using Database Rider in JUnit5 tests

### Given

The following dataset 🍌 (000ms)

```
src/test/resources/dataset/users.yml
```

```
Unresolved directive in documentation.adoc -  
include:../../../../junit5/src/test/resources/datasets/users.yml[]
```

### When

The following junit5 test is executed 🍌 (000ms)

```
Unresolved directive in documentation.adoc -  
include:../../../../junit5/src/test/java/com/github/dbunit/rules/junit5/D  
BUnitJUnit5It.java[tags=declaration;connectionField;test]
```

- ① Enables DBUnit;
- ② JUnit 5 runner;
- ③ As JUnit5 requires **Java8** you can use lambdas in your tests;
- ④ DBUnitExtension will get connection by reflection so just declare a field or a method with **ConnectionHolder** as return type.



Source code of the above example can be [found here](#).

### Then

The database should be seeded with the dataset content before test execution 🍌 (000ms)

## 3.5. Dynamic data using scritable datasets

In order to have dynamic data in datasets  
As a developer  
I want to use scripts in DBUnit datasets.

Scritable datasets are backed by JSR 223. [2: Scripting for the Java Platform, for more information access the official [docs here](#)].

### **3.5.1. Scenario: Seed database with groovy script in dataset**

*Given*

Groovy script engine is on test classpath 👍 (000ms)

```
<dependency>
  <groupId>org.codehaus.groovy</groupId>
  <artifactId>groovy-all</artifactId>
  <version>2.4.6</version>
  <scope>test</scope>
</dependency>
```

*And*

The following dataset 👍 (000ms)

```
Unresolved directive in documentation.adoc -
include:../../../../core/src/test/resources/datasets/yml/groovy-with-
date-replacements.yml[]
```

① Groovy scripting is enabled by **groovy**: string.

*When*

The following test is executed: 👍 (000ms)

```
Unresolved directive in documentation.adoc -
include:../../../../core/src/test/java/com/github/dbunit/rules/ScriptRepl
acementsIt.java[tags=groovy]
```

*Then*

Dataset script should be interpreted while seeding the database 👍 (000ms)

### 3.5.2. Scenario: Seed database with javascript in dataset



Javascript engine comes within JDK so no additional classpath dependency is necessary.



*Given*

The following dataset 🍌 (000ms)

```
Unresolved directive in documentation.adoc -  
include:../../../../core/src/test/resources/datasets/yml/js-with-calc-  
replacements.yml[]
```

① Javascript scripting is enabled by `js:` string.

*When*

The following test is executed: 🍌 (000ms)

```
Unresolved directive in documentation.adoc -  
include:../../../../core/src/test/java/com/github/dbunit/rules/ScriptRepl  
acementsIt.java[tags=javascript-likes]
```

*Then*

Dataset script should be interpreted while seeding the database 🍌 (000ms)

## 3.6. Database assertion using expected datasets

In order to verify database state after test execution  
As a developer  
I want to assert database state with datasets.

### 3.6.1. Scenario: Database assertion with yml dataset

### Given

The following dataset 🍌 (000ms)

*expectedUsers.yml*

```
Unresolved directive in documentation.adoc -  
include:../../../../core/src/test/resources/datasets/yml/expectedUsers.yml[]
```

### When

The following test is executed: 🍌 (000ms)

```
Unresolved directive in documentation.adoc -  
include:../../../../core/src/test/java/com/github/dbunit/rules/ExpectedDataSetIt.java[tags=expectedDeclaration;expected]
```

① Clear database before to avoid conflict with other tests.

### Then

Test must pass because database state is as in expected dataset. 🍌 (000ms)

## 3.6.2. Scenario: Database assertion with regular expression in expected dataset

### *Given*

The following dataset 🍌 (000ms)

*expectedUsersRegex.yml*

```
Unresolved directive in documentation.adoc -  
include:../../../../core/src/test/resources/datasets/yml/expectedUsersReg  
ex.yml[]
```

### *When*

The following test is executed: 🍌 (000ms)

```
Unresolved directive in documentation.adoc -  
include:../../../../core/src/test/java/com/github/dbunit/rules/ExpectedDa  
taSetIt.java[tags=expectedRegex]
```

### *Then*

Test must pass because database state is as in expected dataset. 🍌 (000ms)

## **3.6.3. Scenario: Database assertion with seeding before test execution**

*Given*

The following dataset 🍌 (000ms)

*user.yml*

```
Unresolved directive in documentation.adoc -  
include:../../../../core/src/test/resources/datasets/yml/user.yml[]
```

*And*

The following dataset 🍌 (000ms)

*expectedUser.yml*

```
Unresolved directive in documentation.adoc -  
include:../../../../core/src/test/resources/datasets/yml/expectedUser.yml  
[]
```

*When*

The following test is executed: 🍌 (000ms)

```
Unresolved directive in documentation.adoc -  
include:../../../../core/src/test/java/com/github/dbunit/rules/ExpectedDa  
taSetIt.java[tags=expectedWithSeeding]
```

*Then*

Test must pass because database state is as in expected dataset. 🍌 (000ms)

### 3.6.4. Scenario: Failing database assertion

### Given

The following dataset 🍌 (000ms)

*expectedUsers.yml*

```
Unresolved directive in documentation.adoc -  
include:../../../../core/src/test/resources/datasets/yml/expectedUsers.yml[]
```

### When

The following test is executed: 🍌 (000ms)

```
Unresolved directive in documentation.adoc -  
include:../../../../core/src/test/java/com/github/dbunit/rules/ExpectedDataSetIt.java[tags=failingExpected]
```

### Then

Test must fail with following error: 🍌 (000ms)



```
junit.framework.ComparisonFailure: value (table=USER, row=0,  
col=name) expected:<[]expected user1> but was:<[non ]expected  
user1> at  
org.dbunit.assertion.JUnitFailureFactory.createFailure(JUnitFailureFactory.java:39) at  
org.dbunit.assertion.DefaultFailureHandler.createFailure(DefaultFailureHandler.java:97) at  
org.dbunit.assertion.DefaultFailureHandler.handle(DefaultFailureHandler.java:223) at ...
```

## 3.6.5. Scenario: Database assertion using automatic transaction

### Given

The following dataset 🍌 (000ms)

*expectedUsersRegex.yml*

```
Unresolved directive in documentation.adoc -  
include:../../../../core/src/test/resources/datasets/yml/expectedUsersReg  
ex.yml[]
```

### When

The following test is executed: 🍌 (000ms)

```
Unresolved directive in documentation.adoc -  
include:../../../../core/src/test/java/com/github/dbunit/rules/Transactio  
nIt.java[tags=transaction]
```



**Transactional** attribute will make Database Rider start a transaction before test and commit the transaction **after** test execution but **before** expected dataset comparison.

### Then

Test must pass because inserted users are committed to database and database state matches expected dataset. 🍌 (000ms)