

date 05/12/2016

page 1 of 3

MODEL: PJ-102AH | DESCRIPTION: DC POWER JACK

FEATURES

- 2.0 mm center pin
- 5.0 A rating
- right-angle orientation
- through hole
- tapered pins





SPECIFICATIONS

conditions/description	min	typ	max	units
		24		Vdc
			5.0	А
between terminal and mating plug between terminal in a closed circuit			50 30	mΩ
at 500 Vdc	100			МΩ
at 50/60Hz for 1 minute			500	Vac
	0.3		3	kg
any direction for 10 seconds			500	g
	-25		85	°C
		5,000		cycles
UL94V-0				
2011/65/EU				
	between terminal and mating plug between terminal in a closed circuit at 500 Vdc at 50/60Hz for 1 minute any direction for 10 seconds UL94V-0	between terminal and mating plug between terminal in a closed circuit at 500 Vdc 100 at 50/60Hz for 1 minute 0.3 any direction for 10 seconds -25	between terminal and mating plug between terminal in a closed circuit at 500 Vdc 100 at 50/60Hz for 1 minute 0.3 any direction for 10 seconds -25 5,000 UL94V-0	24 5.0 between terminal and mating plug between terminal in a closed circuit 30 at 500 Vdc 100 at 50/60Hz for 1 minute 500 0.3 3 any direction for 10 seconds 500 -25 85 5,000 UL94V-0


1. When measured at a current of less than $\overline{100}$ mA/1 kHz Note:

SOLDERABILITY


parameter	conditions/description	min	typ	max	units
wave soldering	dipped in solder pot for 5 ± 0.5 seconds	255	260	265	°C


MECHANICAL DRAWING


units: mm[inches] tolerance: $X.X \pm 0.2mm$ $X.XX \pm 0.1mm$ $X.XXX \pm 0.05mm$




	MATERIAL	PLATING
center pin	copper	nickel
terminal 1	brass	silver
terminal 2	copper alloy	silver
terminal 3	brass	silver
plastic	PBT	









MATING PLUG Jack Insertion Depth: 9.0 mm

SCHEMATIC	-1 -3 -2	
Model	PJ-102AH	
Center Pin	Ø2.0 mm	

Note:

REVISION HISTORY

rev.	description	date
1.0	initial release	11/17/2005
1.01	applied new spec template	01/08/2015
1.02	updated datasheet	05/12/2016

The revision history provided is for informational purposes only and is believed to be accurate.



Headquarters 20050 SW 112th Ave. Tualatin, OR 97062 800.275.4899

Fax 503.612.2383 cui.com techsupport@cui.com

CUI offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.