



规格说明: Specifications:

电气特性: Electrical:

1. 额定电流: Current Rating
1.5A/contact terminal
2. 额定电压: Voltage Rating
30V DC
3. 接触阻抗: Contact Resistance
30 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage:
500 V AC AT Sea Level
5. 绝缘阻抗: Insulation Resistance:
1000MΩCA ohms MIN

物理性能: Mechanical:

1. 插拔力: Connector Mate and Umate Force
Mate force: 3.75kgf (MAX)
Umate force: 1.02kgf (MIN)
2. 端子保持力: Terminal Retention
1.2kgf (MIN)

原材料: Material:

1. 塑胶: Housing:
Hing Temperature Thermoplastics,
UL 94V-0 PBT White
 2. 端子: Contact: Copper Alloy C2680
 3. 外壳: Shell: Copper Alloy C2680/SPCC
- 电镀: Finish:
1. 端子: Contact: Plated gold in Mating Area:
Tin On Solder Tails
2. 外壳: Shell:
Nickel Plating

深圳市华联倚电子有限公司				图号 (DWG NO)		单位 (UNIT): MM
品名 (ITEM NO)	USB B/F 90° DIP (弯脚)	版本 (REV)	A/2	日期 (DATE)	2011. 06. 18	比例 (SCALE) 1:1
料号 (PART NO)		设计 (DESIGN)	陈钦虎	审核 (CHECKED)		未注公差 TOLERANCE UNSPECIFIED X.X ±0.30 X.XX ±0.20 X.XXX ±0.10 X.X° ±5° X.X° ±2°
型号 (MODEL NO)	CP-UB007-1B	核准 (APPROVED)				