


2K1000\_PC\_EVB

TITLE	PAGE	TITLE	PAGE
COVER SHEET	1	BMC DEBUG CON	26
SYSTEM ARCHITECTURE	2	USB3.0	27
POWER ARCHITECTURE	3	RTC	28
CLOCK AND CRYSTAL	4	PGOOD	29
POWER ON SEQUENCE	5	CLOCK	30
DDR	6	REVISION HISTORY	31
DDR DIMM	7		
PCIE	8		
SATA USB GMAC	9		
USB GMAC SLOT	10		
DVO0 VGA	11		
DVO1 DVI	12		
MISC	13		
ACPI&SPI&I2C&UART	14		
AUDIO	15		
POWER	16		
ATX&BUTTON	17		
P5V_DUAL P1V8	18		
P1V2 P1V0	19		
P3V3SB P2V5SB P1VSB	20		
P1V5_DUAL DIMM_VTT	21		
VDD_RSM PEST	22		
CPU_VDD P2V5	23		
BMC CARD CON	24		
BMC RMII PHY	25		




### I2C分组说明


设备	目前挂在	I2C地址
DIMM_SLOT0	I2C0	1010 000X
AT24C16	I2C0	1010 111X
RTC-DS1338Z	I2C0	1101 000X
2K 3V3&1V5 current	I2C1	1101 111X
2K PEST&VDD current	I2C1	1101 100X
DVO0	GPIO0 and GPIO1	
DVO1	CAN0_TX and CAN1_RX	

2K1000 GMAC1 PHY\_RESETn: CAN1\_RX(GPIO)

<b>龙芯中科</b>		<b>龙芯中科技术有限公司</b>	
LOONGSON TECHNOLOGY		北京市海淀区稻香湖路中关村环保科技示范园龙芯产业园	
板卡名称 LS2K1000_PC_EVB			
Size	C	部门	芯片研发部
Date:	Thursday, August 02, 2018		Rev V1.2
Drawn By	Hejianxin	Checked By	Fuxinglan
Sheet 2 of 31			



<div><div>龙芯中科</div><div>LOONGSON TECHNOLOGY</div></div> <div><div>龙芯中科技术有限公司</div><div>北京市海淀区稻香湖路中关村环保科技示范园龙芯产业园</div></div>			
板卡名称LS2K1000_PC_EVB			
Size	C	部门	芯片研发部
Rev			V1.2
Date:	Thursday, August 02, 2018		Sheet 3 of 31
Drawn By	Hejianxin		Checked ByFuxinglan



<div><div>龙芯中科</div><div>LOONGSON TECHNOLOGY</div></div> <div><div>龙芯中科技术有限公司</div><div>北京市海淀区稻香湖路中关村环保科技示范园龙芯产业园</div></div>			
板卡名称LS2K1000_PC_EVB			
Size	C	部门	芯片研发部
			RevV1.2
Date:	Thursday, August 02, 2018		Sheet 4 of 31
Drawn By	Hejianxin		Checked ByFuxinglan

5	4	3	2	1
D				D
C				C
B				B
A				A
5	4	3	2	1




龙芯中科

LOONGSON TECHNOLOGY


龙芯中科技术有限公司  
北京市海淀区稻香湖路中关村环保科技示范园龙芯产业园

板卡名称LS2K1000\_PC\_EVB


Size	C	部门	芯片研发部	Rev	V1.2
Date:	Thursday, August 02, 2018			Sheet	5 of 31
Drawn By	Hejianxin		Checked By	Fuxinglan	





























<b>龙芯中科</b> LONGSON TECHNOLOGY			
龙芯中科技术有限公司 北京市海淀区前番湖路中关村环保科技示范园龙芯产业园			
板卡名称 LS2K1000_PC_EVB			
Size	C	部门	芯片研发部
Date:	Tuesday, November 13, 2018	Sheet	10 of 31
Drawn By	Hejiaxin	Checked By	Fuxingjian




## VGA CONNECTOR



CM2009 包含ESD,level-shift, buffer及sync信号 阻抗匹配  
PLACE AS CLOSE AS POSSIBLE TO VGA



<b>龙芯中科</b> LOONGSON TECHNOLOGY		<b>龙芯中科技术有限公司</b> 北京市海淀区稻香湖中关村环保科技示范园龙芯产业园	
板卡名称 LS2K1000_PC_EVB			
Size	C	部门	芯片研发部
Date:	Thursday, August 02, 2018		Sheet 11 of 31
Drawn By	Hejianxin		Checked By Fuxinglan






















龙芯中科

LOONGSON TECHNOLOGY

龙芯中科技术有限公司  
北京市海淀区稻香湖路中关村环保科技示范园龙芯产业园

板卡名称 LS2K1000_PC_EVB			
Size B	部门	芯片研发部	
Date: Thursday, August 02, 2018	Sheet 18 of 31		Rev V1.2
Drawn By Hejianxin	Checked By Fuxingjian		







龙芯中科



LOONGSON TECHNOLOGY

龙芯中科技术有限公司  
北京市海淀区稻香湖路中关村环保科技示范园龙芯产业园

板卡名称 LS2K1000_PC_EVB		
Size B	部门 芯片研发部	Rev V1.2
Date: Thursday, August 02, 2018		Sheet 19 of 31
Drawn By Hejianxin		Checked By Fuxingjian














<b>龙芯中科</b> LOONGSON TECHNOLOGY		<b>龙芯中科技术有限公司</b> 北京市海淀区稻香湖路中关村环保科技示范园龙芯产业园	
板卡名称 LS2K1000_PC_EVB			
Size B	部门 芯片研发部		Rev V1.2
Date: Thursday, August 02, 2018	Sheet 22 of 31		
Drawn By Hejianxin		Checked By Fuxingjian	




















#### BMC COM1





#### BMC COM2







Note:

1. Every Power trace (3.3V, 1.05V, 1.53V, 3.3V, 3.3V, 3.3V, 12V, 5V, VDDCH1-4) should be broad.
2. 2nd layer of all critical signal should be ground.
3. Every high speed signal trace (USB SSKFS, PCI Express) should be short as short as possible.
4. Every signal trace should be terminated with a resistor. The resistor should be used to be connected to GND lightly by tracing signal and broadly.
5. For signal traces, USB SSKFS, PCI Express, SATA+ USB HS (DOR + Ether, PCI, PATA + Other legacy) USB S5.5 PCI Express + SATA+ USB HS (DOR + Ether, PCI, PATA + Other legacy)
6. All any crossing for every trace except ground.
7. sufficient area of ground plane should be provided for every signal trace should be put.
7. Follow the basic of transmission trace pair when routing any signal trace.
8. Remove any impedance discontinuity.
9. Keep name length by each other.
10. Keep same width and
11. 6. The differential impedance of nominal value is as follows.
12. USB 3.0 I/O – 90ohm
13. PCI express Gen 1 (1.5GTS/s) – 100ohm
14. PCI express Gen 2 (5GTS/s) – 85ohm
15. PCI trace impedance would be a non-uniform value by the design rules.
16. The differential impedance of nominal value is as follows.
17. For more information please refer to USB3.0 Board Design Guide in design tool.






 <b>龙芯中科</b> LOONGSON TECHNOLOGY		<b>龙芯中科技术有限公司</b> 北京市海淀区稻香湖路中关村环保科技示范园龙芯产业园	
板卡名称 <b>LS2K1000_PC_EVB</b>			
Size <b>B</b>	部门 <b>芯片研发部</b>		Rev <b>V1.2</b>
Date: <b>Thursday, August 02, 2018</b>		Sheet <b>28</b> of <b>31</b>	
Drawn By <b>Hejiaxin</b>		Checked By <b>Fuxingjian</b>	



<div><div>龙芯中科</div><div>LOONGSON TECHNOLOGY</div></div> <div><div>龙芯中科技术有限公司</div><div>北京市海淀区稻香湖路中关村环保科技示范园龙芯产业园</div></div>			
板卡名称 LS2K1000_PC_EVB			
Size A	部门 芯片研发部		Rev V1.2
Date: Thursday, August 02, 2018		Sheet 29 of 31	
Drawn By Hejianxin		Checked By Fuxingjian	



龙芯中科

LOONGSON TECHNOLOGY

龙芯中科技术有限公司  
北京市海淀区稻香湖路中关村环保科技示范园龙芯产业园

板卡名称 LS2K1000_PC_EVB		
Size B	部门 芯片研发部	Rev V1.2
Date: Thursday, August 02, 2018		Sheet 30 of 31
Drawn By Hejianxin		Checked By Fuxingjian

2017.3.9 V1.1

- 1. Add NAND RDY# pull up
- 2. I2C0\_SDA and I2C1\_SCL exchange
- 3. Change JTAG sel pull down
- 4. Delet I2C pull up for clock generator
- 5. Change R781 to 150R
- 6. Change HDA to I2S
- 7. Add RTC chip
- 8. Change Dotest pull up to RTC-3V3
- 9. Change GMAC1 PHY layout
- 10. USE CAN RX for PHY1\_RSTn, NC watchdog disable
- 11. Put PCIe1 signals upside down
- 12. Change PCIE\_RSTn, Use GPIO(HDA\_SDI2)
- 13. Invert ACPI\_SYSRSTn
- 14. Change Si1164 to TFP410
- 15. Delet DIMM slot1

龙芯中科

LOONGSON TECHNOLOGY

龙芯中科技术有限公司

北京市海淀区稻香湖路中关村环保科技示范园龙芯产业园

板卡名称				LS2K1000_PC_EVB		
Size	C	部门	芯片研发部		Rev	V1.2
Date:	Thursday, August 02, 2018			Sheet	31	of 31
Drawn By	Fuxingjian		Checked By	<OrgAddr>		