



Data Transformation with dplyr Cheat Sheet



dplyr functions work with pipes and expect **tidy data**. In tidy data:



Each **variable** is in its own **column**



Each **observation**, or **case**, is in its own **row**

pipes
 $x \%>\% f(y)$
becomes $f(x, y)$

Summarise Cases

These apply **summary functions** to columns to create a new table. Summary functions take vectors as input and return one value (see back).



summarise(.data, ...)

Compute table of summaries. Also **summarise_()**.

summarise(mtcars, avg = mean(mpg))



count(x, ..., wt = NULL, sort = FALSE)

Count number of rows in each group defined by the variables in ... Also **tally()**.


count(iris, Species)

Variations

- **summarise_all()** - Apply funs to every column.
- **summarise_at()** - Apply funs to every column.
- **summarise_if()** - Apply funs to all cols of one type.

Group Cases

Use **group_by()** to create a "grouped" copy of a table. dplyr functions will manipulate each "group" separately and then combine the results.



mtcars %>%

group_by(cyl) %>%

summarise(avg = mean(mpg))

group_by(.data, ..., add = FALSE)

Returns copy of table grouped by ...

g_iris <- group_by(iris, Species)

ungroup(x, ...)


Returns ungrouped copy of table.

ungroup(g_iris)

Manipulate Cases


Extract Cases

Row functions return a subset of rows as a new table. Use a variant that ends in **_** for non-standard evaluation friendly code.




filter(.data, ...)

Extract rows that meet logical criteria. Also **filter_()**. *filter(iris, Sepal.Length > 7)*



distinct(.data, ..., .keep_all = FALSE)

Remove rows with duplicate values. Also **distinct_()**. *distinct(iris, Species)*




sample_frac(tbl, size = 1, replace = FALSE,

weight = NULL, .env = parent.frame())

Randomly select fraction of rows.

sample_frac(iris, 0.5, replace = TRUE)



slice(.data, ...)

Select rows by position. Also **slice_()**.

slice(iris, 10:15)

top_n(x, n, wt)

Select and order top n entries (by group if grouped data). *top_n(iris, 5, Sepal.Width)*

Logical and boolean operators to use with filter()

<	<=	is.na()	%in%		xor()
>	>=	!is.na()	!	&	

See **?base::logic** and **?Comparison** for help.

Arrange Cases




arrange(.data, ...)

Order rows by values of a column (low to high), use with **desc()** to order from high to low.

arrange(mtcars, mpg)

arrange(mtcars, desc(mpg))

Add Cases



add_row(.data, ..., .before = NULL,

.after = NULL)

Add one or more rows to a table.

add_row(faithful, eruptions = 1, waiting = 1)

Manipulate Variables

Extract Variables

Column functions return a set of columns as a new table. Use a variant that ends in **_** for non-standard evaluation friendly code.



select(.data, ...)

Extract columns by name. Also **select_if()**
select(iris, Sepal.Length, Species)

Use these helpers with **select()**,

e.g. *select(iris, starts_with("Sepal"))*

contains(match)

ends_with(match)

matches(match)

num_range(prefix, range)

one_of(...)


starts_with(match)

•, e.g. mpg:cyl

-, e.g. -Species

Make New Variables

These apply **vectorized functions** to columns. Vectorized funs take vectors as input and return vectors of the same length as output (see back).



mutate(.data, ...)

Compute new column(s).

mutate(mtcars, gpm = 1/mpg)



transmute(.data, ...)

Compute new column(s), drop others.

transmute(mtcars, gpm = 1/mpg)



mutate_all(.tbl, .funs, ...)

Apply funs to every column. Use with


funs(). *mutate_all(faithful, funs(log(.), log2(.)))*



mutate_at(.tbl, .cols, .funs, ...)

Apply funs to specific columns. Use with **funs()** and the helper functions for **select()**.


mutate_at(iris, -Species, funs(log(.)))



mutate_if(.tbl, .predicate, .funs, ...)

Apply funs to all columns of one type. Use with **funs()**.

mutate_if(iris, is.numeric, funs(log(.)))



rename(.data, ...)

Rename columns.

rename(iris, Length = Sepal.Length)

Vectorized Functions

to use with mutate()

mutate() and **transmute()** apply vectorized functions to columns to create new columns. Vectorized functions take vectors as input and return vectors of the same length as output.



Offsets

`dplyr::lag()` - Offset elements by 1
`dplyr::lead()` - Offset elements by -1

Cumulative Aggregates

`dplyr::cumall()` - Cumulative all()
`dplyr::cumany()` - Cumulative any()
`cummax()` - Cumulative max()
`dplyr::cummean()` - Cumulative mean()
`cummin()` - Cumulative min()
`cumprod()` - Cumulative prod()
`cumsum()` - Cumulative sum()

Rankings

`dplyr::cume_dist()` - Proportion of all values <=

`dplyr::dense_rank()` - rank with ties = min, no gaps

`dplyr::min_rank()` - rank with ties = min

`dplyr::ntile()` - bins into n bins

`dplyr::percent_rank()` - min_rank scaled to [0,1]

`dplyr::row_number()` - rank with ties = "first"

Math

`+`, `-`, `*`, `/`, `^`, `%/%`, `%%` - arithmetic ops
`log()`, `log2()`, `log10()` - logs
`<`, `<=`, `>`, `>=`, `!=`, `==` - logical comparisons

Misc

`dplyr::between()` - $x \geq \text{left} \ \& \ x \leq \text{right}$

`dplyr::case_when()` - multi-case if_else()

`dplyr::coalesce()` - first non-NA values by element across a set of vectors

`dplyr::if_else()` - element-wise if() + else()

`dplyr::na_if()` - replace specific values with NA

`pmax()` - element-wise max()
`pmin()` - element-wise min()

`dplyr::recode()` - Vectorized switch()

`dplyr::recode_factor()` - Vectorized switch() for factors

Summary Functions

to use with summarise()

summarise() applies summary functions to columns to create a new table. Summary functions take vectors as input and return single values as output.



Counts

`dplyr::n()` - number of values/rows
`dplyr::n_distinct()` - # of uniques
`sum(!is.na())` - # of non-NA's

Location

`mean()` - mean, also `mean(!is.na())`
`median()` - median

Logicals

`mean()` - Proportion of TRUE's
`sum()` - # of TRUE's

Position/Order

`dplyr::first()` - first value
`dplyr::last()` - last value
`dplyr::nth()` - value in nth location of vector

Rank

`quantile()` - nth quantile
`min()` - minimum value
`max()` - maximum value

Spread

`IQR()` - Inter-Quartile Range
`mad()` - mean absolute deviation
`sd()` - standard deviation
`var()` - variance

Row names

Tidy data does not use rownames, which store a variable outside of the columns. To work with the rownames, first move them into a column.

	A	B
1	a	t
2	b	u
3	c	v

 →

	C	A	B
1	a	t	
2	b	u	
3	c	v	

rownames_to_column()
Move row names into col.
`a <- rownames_to_column(iris, var = "C")`

A	B	C
a	t	1
b	u	2
c	v	3

 →

	A	B
1	a	t
2	b	u
3	c	v

column_to_rownames()
Move col in row names.
`column_to_rownames(a, var = "C")`

Also **has_rownames()**, **remove_rownames()**

Combine Tables

Combine Variables

x			y		
A	B	C	A	B	D
a	t	1	a	t	3
b	u	2	b	u	2
c	v	3	d	w	1

Use **bind_cols()** to paste tables beside each other as they are.

A	B	C	A	B	D
a	t	1	a	t	3
b	u	2	b	u	2
c	v	3	d	w	1

bind_cols(...)

Returns tables placed side by side as a single table.
BE SURE THAT ROWS ALIGN.

Use a "**Mutating Join**" to join one table to columns from another, matching values with the rows that they correspond to. Each join retains a different combination of values from the tables.

A	B	C	D
a	t	1	3
b	u	2	2
c	v	3	NA

left_join(x, y, by = NULL, copy=FALSE, suffix=c("x","y"),...)
Join matching values from y to x.

A	B	C	D
a	t	1	3
b	u	2	2
d	w	NA	1

right_join(x, y, by = NULL, copy = FALSE, suffix=c("x","y"),...)
Join matching values from x to y.

A	B	C	D
a	t	1	3
b	u	2	2

inner_join(x, y, by = NULL, copy = FALSE, suffix=c("x","y"),...)
Join data. Retain only rows with matches.

A	B	C	D
a	t	1	3
b	u	2	2
c	v	3	NA
d	w	NA	1

full_join(x, y, by = NULL, copy=FALSE, suffix=c("x","y"),...)
Join data. Retain all values, all rows.

A	B.x	C	B.y	D
a	t	1	t	3
b	u	2	u	2
c	v	3	NA	NA

Use **by = c("col1", "col2")** to specify the column(s) to match on.

left_join(x, y, by = "A")

A.x	B.x	C	A.y	B.y
a	t	1	d	w
b	u	2	b	u
c	v	3	a	t

Use a named vector, **by = c("col1" = "col2")**, to match on columns with different names in each data set.

left_join(x, y, by = c("C" = "D"))

A1	B1	C	A2	B2
a	t	1	d	w
b	u	2	b	u
c	v	3	a	t

Use **suffix** to specify suffix to give to duplicate column names.

left_join(x, y, by = c("C" = "D"), suffix = c("1", "2"))

Combine Cases

x			z		
A	B	C	A	B	C
a	t	1	c	v	3
b	u	2	d	w	4
c	v	3			

Use **bind_rows()** to paste tables below each other as they are.

DF	A	B	C
x	a	t	1
x	b	u	2
x	c	v	3
z	c	v	3
z	d	w	4

bind_rows(..., .id = NULL)

Returns tables one on top of the other as a single table. Set .id to a column name to add a column of the original table names (as pictured)

A	B	C
c	v	3

intersect(x, y, ...)

Rows that appear in both x and z.

A	B	C
a	t	1
b	u	2

setdiff(x, y, ...)

Rows that appear in both x but not z.

A	B	C
a	t	1
b	u	2
c	v	3
d	w	4

union(x, y, ...)

Rows that appear in x or z. (Duplicates removed). **union_all()** retains duplicates.

Use **setequal()** to test whether two data sets contain the exact same rows (in any order).

Extract Rows

x			y		
A	B	C	A	B	C
a	t	1	a	t	3
b	u	2	b	u	2
c	v	3	d	w	1

Use a "**Filtering Join**" to filter one table against the rows of another.

A	B	C
a	t	1
b	u	2

semi_join(x, y, by = NULL, ...)

Return rows of x that have a match in y.
USEFUL TO SEE WHAT WILL BE JOINED.

A	B	C
c	v	3

anti_join(x, y, by = NULL, ...)

Return rows of x that do not have a match in y. USEFUL TO SEE WHAT WILL NOT BE JOINED.