

Serverless Dataflows: A Decentralized Workflow Execution Engine with Predictive Planning

Diogo Alexandre Ferreira de Jesus

Thesis to obtain the Master of Science Degree in

Computer Science and Engineering

Supervisor: Luis Manuel Antunes Veiga

Examination Committee

Chairperson: Prof. Name of the Chairperson

Supervisor: Luis Manuel Antunes Veiga

Member of the Committee: Prof. Name of First Committee Member

October 2025

Declaration

I declare that this document is an original work of my own authorship and that it fulfills all the requirements of the Code of Conduct and Good Practices of the Universidade de Lisboa.

Acknowledgments

Abstract

Serverless computing has become a suitable cloud paradigm for many applications, prized for its operational ease, automatic scalability, and fine-grained pay-per-use pricing model. However, executing workflows, which are compositions of multiple tasks, in Function-as-a-Service (FaaS) environments remains inefficient. This inefficiency stems from the stateless nature of functions, and a heavy reliance on external services for intermediate data transfers and inter-function communication.

In this document, we introduce a decentralized DAG engine that leverages historical metadata to plan and influence task scheduling. Our solution encompasses metadata management, static workflow planning, and a worker-level scheduling strategy designed to drive workflow execution with minimal synchronization. We compare our scheduling approach against WUKONG, another decentralized serverless DAG engine. Our evaluation demonstrates that utilizing historical information significantly improves performance and reduces resource utilization for workflows running on serverless platforms.

Keywords

Cloud Computing; Serverless; FaaS; Serverless Workflows; Serverless DAGs; Metadata; Workflow Prediction

Resumo

A computação serverless tornou-se um paradigma de nuvem adequado para muitas aplicações, valorizado pela sua facilidade operacional, escalabilidade automática e modelo de preços granular baseado na utilização. Contudo, a execução de workflows, que são composições de múltiplas tarefas, em ambientes Function-as-a-Service (FaaS) permanece ineficiente. Esta ineficiência resulta da natureza *stateless* (sem estado) destas funções e de uma forte dependência de serviços externos para transferências de dados intermédios e comunicação entre funções.

Neste documento, apresentamos um motor de workflows serverless descentralizado que utiliza métricas recolhidas durante a execução para planear e influenciar o *scheduling* de tarefas. A nossa solução abrange a gestão de metadados, o planeamento estático de workflows e uma estratégia de *scheduling* ao nível dos workers concebida para conduzir a execução de workflows de uma forma descentralizada e com sincronização mínima. Comparamos a nossa abordagem com o WUKONG, outro motor de workflows serverless descentralizado. A nossa avaliação demonstra que a utilização de informação histórica melhora significativamente o desempenho e reduz a utilização de recursos para workflows executados em plataformas serverless.

Palavras Chave

Computação em Nuvem; Serverless; FaaS; Workflows Serverless; Serverless DAGs; Metadados; Previsão de Workflows

Contents

1	Introduction	1
1.1	Problem/Motivation	2
1.2	Gaps in prior work	3
1.3	Proposed Solution	3
1.4	Document Organization	3
2	Related Work	5
2.1	Serverless Computing	6
2.1.1	Advantages	7
2.1.2	Limitations	8
2.1.3	Research Efforts	9
2.2	Workflows	10
2.2.1	Workflow Definition Languages	10
2.2.2	Traditional Workflow Scheduling	11
2.2.3	Modern Workflow Scheduling	12
2.2.3.A	Stateful Serverless Functions	13
2.2.4	Serverless Workflow Scheduling	14
2.2.4.A	Workflow Scheduling Approaches	14
2.2.4.B	Relevant Workflow Schedulers	15
A –	DEWE v3	16
B –	PyWren	16
C –	Unum	16
D –	WUKONG	17
2.3	Discussion/Analysis	19
3	Architecture	21
3.1	Workflow Definition Language	22
3.2	Architecture	24
3.3	Metadata Management	26

3.4	Static Workflow Planning	29
3.4.1	Workflow Simulation	29
3.4.2	Planning Algorithms	29
3.4.3	Optimizations	34
3.5	Client	38
3.6	Decentralized Workers	40
4	Evaluation	45
4.1	Emulating FaaS environment	45
4.2	Research Questions	46
4.3	Experimental Setup	46
4.4	Results	46
4.4.1	Predictions Accuracy	46
4.4.2	SLA Fulfillment	46
4.4.3	Planners	46
4.4.4	Optimizations	46
4.4.5	Resource Usage	47
4.5	Discussion	47
5	Conclusion	49
5.1	Conclusions	49
5.2	System Limitations and Future Work	49
	Bibliography	49
A	Code of Project	55
B	A Large Table	57

List of Figures

3.1	Simple DAG example	23
3.2	Solution Architecture	25
3.3	Planned Workflow Execution Example	36
3.4	Choreographed Scheduling Example	42

List of Tables

List of Algorithms

1	Select Relevant Samples for Predictions	28
2	Worker Assignment Algorithm (used by Uniform and Non-Uniform planners)	32
3	Resource Downgrading Algorithm (used by Non-Uniform planner)	33

Listings

3.1	DAG definition example	22
3.2	Setting up and launching workflow execution	23
3.3	Task Predictions API	26
3.4	Overridable worker execution logic stages	38

1

Introduction

Contents

1.1 Problem/Motivation	2
1.2 Gaps in prior work	3
1.3 Proposed Solution	3
1.4 Document Organization	3

Function-as-a-Service (FaaS) represents a serverless cloud computing paradigm that simplifies application deployment by abstracting away infrastructure management. It provides automatic, elastic scalability—potentially without limit—along with a fine-grained, pay-per-use pricing model. This has led to its widespread adoption for event-driven systems, microservices, and web services on platforms like AWS Lambda [1], Azure Functions [2], and Google Cloud Functions [3]. These applications typically benefit the most from FaaS because they are lightweight, stateless, and characterized by highly variable or unpredictable workloads, allowing them to leverage serverless platforms' on-demand scalability and cost-efficiency.

This paradigm is also increasingly used to execute complex scientific and data processing workflows, such as the Cybershake [4] seismic hazard analysis or Montage [5], an astronomy image mosaicking workflow. These applications are structured as workflows—formally represented as Directed Acyclic

Graphs (DAGs) of interdependent tasks. However, efficiently executing these complex workflows on serverless platforms remains a significant challenge.

1.1 Problem/Motivation

Despite their advantages, serverless platforms present several limitations that complicate the execution of complex workflows. Since these platforms allow scaling down to zero resources to save costs, they can also introduce unpredictable latency, known as *cold starts* [6], particularly for short-lived functions, affecting overall workflow performance. The lack of *direct inter-function communication* [7] means that tasks often have to rely on external services, such as message brokers or databases to exchange intermediate data, which can increase overhead and reduce efficiency. Interoperability between platforms is further limited by the use of platform-specific workflow definition languages, which restricts the portability of workflows across different serverless environments. Additionally, while statelessness simplifies scaling and management, it can introduce overhead and complexity for applications that require continuity or coordination across multiple function invocations. Finally, developers have limited control over the underlying infrastructure, restricting the ability to optimize resource usage or tune performance for specific workloads.

Several solutions have emerged to address the limitations of serverless platforms. Stateful functions (e.g., AWS Step Functions [8], Azure Durable Functions [9], and Google Cloud Workflows [10]) expand the range of applications that can run on serverless platforms by maintaining state across multiple function invocations, coordinating complex workflows, and providing built-in fault tolerance. Other approaches tackle limitations at the runtime level, proposing extensions to FaaS platforms (e.g., FaaS\$T [11], Palette [12], Lambdata [13]) or entirely new serverless architectures (e.g., Apache OpenWhisk [14]).

Other research projects focus on improved orchestration and coordination mechanisms that work on top of FaaS platforms, such as Moyer et al. [15]’s hole punching approach to allow direct inter-function communication, Pheromone [16], Triggerflow [17], FaDO [18], and FMI [19]. These solutions aim to overcome the inherent limitations of stateless functions through intelligent middleware layers that optimize function coordination, data placement, and workflow execution without requiring modifications to the underlying FaaS infrastructure.

Finally, some workflow-focused solutions (e.g., WUKONG [20], Unum [21], DEWEv3 [22]) employ scheduling strategies and workflow-level optimizations to enhance efficiency, primarily by improving data locality to bring computation closer to the data and minimize reliance on external services.

1.2 Gaps in prior work

These workflow-focused approaches, however, often use the *same resources for all tasks* in a workflow and rely on "*one-step scheduling*", making decisions based solely on the immediate workflow stage without considering the broader context or the downstream effects of their decisions. This combination of homogeneous worker configurations and limited scheduling foresight can lead to inefficient use of resources when tasks have diverse requirements. Furthermore, the heuristic-based approaches used by other solutions can be inefficient in certain scenarios, as they lack mechanisms to adapt worker resource allocations to the specific needs of individual tasks. Moreover, we found no prior work that leverages metadata or historical metrics to inform scheduling decisions across an entire serverless workflow.

1.3 Proposed Solution

These research gaps motivated the central research question of this work: if we have knowledge of all DAG tasks, collect sufficient metrics on their behavior, and understand how they are composed to form the full workflow, can we leverage this information to make smarter scheduling decisions that minimize *makespan* (the total time taken to complete a workflow) and maximize resource efficiency in a FaaS environment?

To answer this research question, we propose a decentralized serverless workflow execution engine that leverages historical metadata from previous workflow runs to generate informed task allocation plans, which are then executed by FaaS workers in a choreographed manner, without needing a central scheduler. By relying on such planning, our approach aims to minimize the usage of external cloud storage services, which are often employed by similar solutions for intermediate data exchange and synchronization, while also avoiding the inefficiencies of homogeneous worker resource allocations.

1.4 Document Organization

The rest of this document is organized as follows: In Chapter 3 we do a background analysis on the serverless landscape, analyzing serverless platforms, offerings, open-source solutions and existing research work. In Chapter 4 we present our proposed solution, detailing its architecture and implementation of the core layers and components. In Chapter 5, we evaluate our proposed solution by comparing it with WUKONG's scheduling algorithm as well as with algorithms we have implemented. Finally, in Chapter 6 we conclude our work and discuss future directions for research.

2

Related Work

Contents

2.1	Serverless Computing	6
2.1.1	Advantages	7
2.1.2	Limitations	8
2.1.3	Research Efforts	9
2.2	Workflows	10
2.2.1	Workflow Definition Languages	10
2.2.2	Traditional Workflow Scheduling	11
2.2.3	Modern Workflow Scheduling	12
2.2.3.A	Stateful Serverless Functions	13
2.2.4	Serverless Workflow Scheduling	14
2.2.4.A	Workflow Scheduling Approaches	14
2.2.4.B	Relevant Workflow Schedulers	15
A –	DEWE v3	16
B –	PyWren	16
C –	Unum	16

D – WUKONG	17
2.3 Discussion/Analysis	19

In this section, we explore the serverless computing landscape, starting by exposing the architecture of a typical serverless computing platform, referencing the use cases for this new cloud computing model, and presenting both commercial and open-source offerings. We also delve into workflows, showing how they can be represented, how they are run and managed, and contrasting traditional frameworks for workflow management with more recent solutions that explore cloud technologies, including serverless. Then, we write about three extension proposals to the current serverless platforms design, aiming to improve data locality. We finish this section by presenting relevant workflow orchestrators and schedulers (serverful, serverless, and hybrid) for executing tasks, highlighting their advantages but also some of their limitations and inefficiencies.

2.1 Serverless Computing

Traditionally, cloud applications have been deployed on virtual machines, such as Amazon EC2 ¹, which provide full control over the operating system and runtime environment. This model allows predictable performance, flexible resource allocation, direct communication via local network interfaces between VMs, and the ability to run long-lived services, but it comes with significant operational overhead: developers must manage provisioning (which can take several minutes), scaling, patching, and fault tolerance.

Serverless computing addresses these challenges by abstracting away infrastructure management, enabling developers to focus solely on application logic. At the storage and database layer, serverless databases and object stores automatically scale with demand and charge based on actual usage. At the application level, **Backend-as-a-Service** (BaaS) platforms offer ready-to-use components like authentication and messaging. Finally, at the compute layer, **Function-as-a-Service** (FaaS) provides the most flexible and fine-grained model, allowing developers to deploy individual functions that execute on demand in response to events. In this document, we focus specifically on FaaS, as it is the model most relevant to our work.

The Function-as-a-Service (FaaS) model is now offered by major cloud providers, including Amazon (Lambda [1]), Google (Cloud Run Functions [3]), Microsoft (Azure Functions [2]), and Cloudflare (Workers [23]). In addition to these commercial offerings, several open-source runtimes such as OpenWhisk [14], OpenFaaS [24], and Knative [25] provide developers with alternatives for deploying FaaS in self-managed or hybrid environments.

¹<https://aws.amazon.com/pt/ec2/>

2.1.1 Advantages

Recent industry reports ² show that serverless computing has seen rapid adoption over the last few years. For example, in 2024 the global serverless computing market was estimated at USD 24.51 billion, and it is projected to more than double to USD 52.13 billion by 2030, with a compound annual growth rate (CAGR) of about 14.1%. Function-as-a-Service (FaaS) constitutes the majority service model, representing over 60% of serverless market share in 2024. This rapid growth highlights the increasing appeal of serverless architectures, which can be attributed to the following key benefits:

- **Operational Simplicity** means that developers are abstracted away from the underlying infrastructure management, without worrying about server maintenance, scaling, or provisioning. This enables faster development and deployment cycles;
- **Scalability** means the FaaS runtime handles increasing workloads by automatically provisioning additional computational capacity as demand grows, ensuring that applications remain responsive and performant. This makes the FaaS model ideal for applications with *highly variable* or *unpredictable* usage patterns, where we don't know *how many* or *when* requests will arrive;
- **Pay-per-use:** FaaS provides a pricing model where users are only charged for the resources used during the actual execution time over the memory used by their functions, rather than for pre-allocated resources (as in Infrastructure-as-a-Service).

Given these advantages, the serverless model is particularly attractive for applications with *highly variable* or *unpredictable* workloads, such as web services, event-driven pipelines, and real-time data processing. It also suits applications that benefit from rapid iteration and deployment, including microservices, and APIs, where minimizing operational overhead is crucial. Furthermore, serverless can be advantageous in cost-sensitive contexts, where pay-per-use pricing reduces expenses for workloads that do not require continuous execution.

These benefits make serverless computing attractive not only for simple, event-driven applications but also for more complex workflows. Serverless workflows are a composition of multiple computational tasks that are chained together to execute applications by orchestrating individual serverless functions into a coordinated sequence. Some workflows have been successfully experimented with on FaaS. Notable examples include ExCamera [26], a highly parallel video encoding system; Montage [5], an astronomical image mosaic generator; and CyberShake [4], a seismic hazard modeling framework.

²<https://www.grandviewresearch.com/industry-analysis/serverless-computing-market-report>

2.1.2 Limitations

While these advantages make serverless computing highly appealing for a wide range of applications, the model is not without its limitations. As adoption has grown, both practitioners and researchers have identified several technical and architectural challenges that hinder its broader applicability and performance. A number of studies have systematically analyzed these issues, among which Li et al. [27] provides a comprehensive overview of the benefits, challenges, and open research opportunities in the serverless landscape. The challenges mentioned include:

- **Startup Latencies:** It's the time it takes for a function to start executing user code. Cold starts (explained further) can be critical, especially for functions with short execution times;
- **Isolation:** In serverless, multiple users share the same computational resources (often the same Kernel). This makes it crucial to properly isolate execution environments of multiple users;
- **Scheduling Policies:** Traditional cloud computing policies were not designed to operate in dynamic and ephemeral environments, such as FaaS's;
- **Resource Configuration Complexity:** Despite the promise of abstracting infrastructure management, serverless platforms still require developers to manually configure resource allocations (such as memory limits and timeout values) for each function. This configuration significantly impacts both performance and cost, yet determining optimal settings remains a non-trivial task. While tools like AWS Lambda Power Tuning [28] have emerged to assist with empirical optimization through automated performance testing across different configurations, the burden of resource selection still falls on developers, partially undermining the serverless promise of infrastructure abstraction;
- **Fault-Tolerance:** Cloud platforms impose restrictions on developers by encouraging the development of *idempotent functions*. This makes it easier for providers to implement fault-tolerance by retrying failed function executions.

Hellerstein et al. [7] portrays FaaS as a "*Data-Shipping Architecture*", where data is intensively moved to code, through external storage services like databases, bucket storage or queues, to circumvent the limitation of inter-function direct communication. This can greatly degrade performance, while also incurring extra costs.

These limitations notably impact workflows—complex applications composed of multiple functions orchestrated into a Directed Acyclic Graph (DAG), where each function's output serves as input for subsequent functions. Such workflows are prevalent in scientific computing, data processing, and machine learning pipelines.

2.1.3 Research Efforts

To overcome some of the inherent limitations of traditional Function-as-a-Service (FaaS) platforms, several research initiatives have proposed architectural innovations aimed at improving performance, scalability, and orchestration. Apache OpenWhisk [14] adopts a fully event-driven, trigger-based architecture, in which functions are invoked automatically in response to events, allowing for more responsive execution and efficient resource utilization. Its design supports complex workflows and fine-grained control over function composition, making it suitable for latency-sensitive and distributed applications.

Building on similar principles, TriggerFlow [17] extends the trigger-based approach by implementing an *event-condition-action* paradigm, enabling efficient orchestration of complex workflows such as state machines and DAGs. This allows high-volume event processing, dynamic scaling, and improved fault tolerance, making it well-suited for long-running scientific and data-intensive workflows.

Another notable platform, OpenFaaS [24], fights *vendor lock-in* by emphasizing simplicity and portability, allowing developers to deploy serverless functions on a wide range of infrastructures while maintaining an event-driven execution model. Collectively, these platforms show how architectural innovations—particularly in event handling and workflow orchestration—can mitigate many of the performance and scalability limitations found in conventional FaaS systems.

While solutions such as OpenWhisk and TriggerFlow propose completely novel serverless architectures, others such as Palette Load Balancing [12], FaaS\$T [11], Pocket [29], Pheromone [16], and Lambda [13] propose extending either the FaaS runtime or the workflow definition language to address one of the most pressing limitation of the serverless paradigm: data management inefficiencies.

Palette [12] is a FaaS runtime extension that improves data locality by introducing the concept of “**colors**” as *locality hints*. These colors are parameters attached to function invocations, enabling the invoker to express the desired affinity between invocations without directly managing instances. Palette then uses these hints to route invocations with the same color to the same instance *if possible*, allowing for data produced by one invocation to be readily available to subsequent invocations, reducing the need for expensive data transfers, as it would be required in a typical FaaS runtime. This extra control that Palette provides can be used by workflow schedulers, which have insights on the data dependencies between tasks, to try co-locating tasks which share data dependencies, for example, leading to greater performance while also reducing resource utilization.

FaaS\$T (Function-as-a-Service Transparent Auto-scaling Cache) [11] tackles the same issue as Palette, locality, but does so on the data level, by adding a **transparent caching layer** into the FaaS runtime. Each application is assigned an in-memory *cachelet* that stores frequently accessed data, enabling subsequent invocations to reuse it without resorting to remote storage. Cachelets cooperate as a distributed cache using *consistent hashing* to share objects across instances, while pre-warming and auto-scaling mechanisms adapt the cache to workload demands. Unlike Palette, which requires user-provided hints,

FaaS operates automatically, preserving the simplicity of the serverless model, hence the "transparent" in its name.

Similarly, Lambdata [13] improves data locality by relying on explicit **data intents** provided by the developer. Functions declare which objects they will read and write, allowing the controller to co-locate invocations that share data dependencies on the same worker and reuse a local cache. This reduces remote storage accesses and data transfer overheads. Compared to Palette's flexible color hints, Lambdata's data intents are more precise but place stricter requirements on developers, while contrasting with FaaS's fully automated and distributed approach. Contrasting with Palette, Lambdata requires less effort from the developer, but at the cost of reduced flexibility.

2.2 Workflows

As stated before, workflows represent systematic methodologies for organizing and executing computational processes, providing a structured approach to designing, managing, and reproducing generic computations. Workflows have proven to be useful for many different use cases, from application payments and order processing, to data analytics pipelines that move and transform large datasets, to scientific computing and simulations where complex experiments are broken into manageable steps.

2.2.1 Workflow Definition Languages

At their conceptual core, most workflows can be represented as directed acyclic graphs (DAGs), which model computational processes by depicting tasks as nodes and their dependencies as edges connecting them. As an example of a typical web application workflow, consider an online payment process. When a user makes a purchase, the workflow can be represented as a DAG, where each task corresponds to a step in the transaction process. The first task may involve verifying the user's credentials, followed by tasks such as checking product availability, processing payment, and confirming the order. Each of these tasks *depends on* the successful completion of the previous step, with dependencies that ensure the correct order of operations. For instance, payment processing cannot proceed without confirming the product availability, and order confirmation only occurs once payment has been processed. This simple DAG structure ensures that each task is executed in sequence, while also *enabling parallel execution* where possible, such as checking product availability and verifying payment simultaneously.

Despite the existence of other ways to express workflows, due to the simplicity of writing and interpreting DAGs, most systems and libraries use this representation. For instance, Apache Airflow [30] uses DAGs to define and schedule workflows defined in Python. Similarly, Dask [31], a Python parallel computing library, also utilizes DAGs to represent task dependencies, enabling the parallel execution of tasks across clusters. DAGMan (Directed Acyclic Graph Manager) [32] is a way HTCondor [33] (dis-

tributed computing job manager) users can organize independent jobs into workflows, also in the form of DAGs.

However, there are more flexible alternatives to define workflows. YAWL (Yet Another Workflow Language) [34] is a *workflow language* that provides a highly expressive framework for workflow management, capable of supporting a wider range of workflow patterns. YAWL uses Petri networks [35] instead of DAGs to model workflows. This allows YAWL to handle more complex control-flow structures, such as loops, parallelism, and advanced synchronization patterns, offering greater flexibility and power in defining and managing intricate workflows.

While using more capable and flexible workflow languages, such as YAWL (Yet Another Workflow Language) allows the representation of more complex workflow patterns, most of the tools used for defining and running scientific workflows, like *Apache Airflow*, *Dask*, and HTCondor's DAGMan use the Directed Acyclic Graph format. This is because DAGs effectively model the majority of scientific workflows, which typically involve non-cyclic dependencies, making them simpler to compose, deploy, understand, debug, and visualize.

2.2.2 Traditional Workflow Scheduling

Going from a workflow definition to actual execution involves several key stages: provisioning resources to match computational demands, uploading code, dependencies, and data to ensure a consistent execution environment, scheduling tasks efficiently to optimize cost and performance, monitoring execution for performance and fault detection, and finally deprovisioning resources once the workflow completes. Traditional scheduling approaches from Grid and Cloud computing assume centralized control, which does not fully align with the ephemeral, stateless nature of serverless computing. Serverless platforms, however, can simplify many of these stages by automating resource scaling, data staging, fault handling, monitoring, and teardown, reducing operational overhead while adapting execution to dynamic workloads.

To alleviate some of the developers and researchers' pain points during these steps while scheduling workflows on more traditional *Infrastructure as a Service* (IaaS) platforms, several data processing and workflow scheduling frameworks have emerged. Among the platforms for **data processing pipelines** are Apache Spark [36], Apache Flink [37], and Apache Hadoop [38], which focus on processing and analyzing large datasets efficiently through parallel and distributed computing. On the **workflow scheduling and orchestration** side, traditional platforms include Apache Oozie [39] and HTCondor [33], which manage the execution and coordination of complex sequences of tasks, ensuring that dependencies are handled and resources are allocated effectively. These frameworks help streamline both the data processing and the management of workflows.

Apache Hadoop provided a foundation for large-scale data processing when it introduced the MapRe-

duce [40] paradigm, supported by HDFS and YARN [41] for reliable storage and resource management. Apache Spark provides a flexible distributed model with rich libraries for analytics and efficient task dependency management, while Apache Flink specializes in real-time stream processing with low latency and robust state handling. In terms of workflow orchestration, Apache Oozie specializes in coordinating Hadoop-based tasks, whereas HTCondor targets high-throughput scientific workflows, efficiently managing complex dependencies.

Similarly, Dask [31] and its distributed scheduler (Dask Distributed [42]) extend the familiar Python ecosystem to large-scale data and compute workloads, enabling parallel execution of array, dataframe, and machine learning operations across clusters, with a lightweight task graph scheduler that supports both batch and interactive computation. Together, these frameworks illustrate the range of solutions available for executing and coordinating workflows on top of the IaaS model, spanning batch and streaming data as well as data-centric and scientific computing environments.

While these frameworks address many critical aspects of resource provisioning, code and dependency management, and workflow monitoring, they rely on the *Infrastructure as a Service* (IaaS) model. While offering significant flexibility and control over the computing environment, *IaaS* comes with notable drawbacks as mentioned previously. A major challenge of IaaS platforms is the complexity of *managing and provisioning* virtual machines, storage, and network resources, which requires expertise and incurs significant overhead. Users must also handle scaling, load balancing, and fault tolerance manually, often leading to inefficiencies. Predicting resource requirements is difficult, often resulting in *over-* or *under-provisioning*, and the typical hourly billing model can further increase costs, particularly for short workflows that run for only a few minutes.

As highlighted previously, the *serverless* paradigm excels in scenarios where automatic scaling and cost-efficiency are essential, while also providing a much easier set-up process for developers by abstracting away the underlying infrastructure and only requiring the user to follow a few coding rules and minor configuration. Despite its current inefficiencies, the serverless model shows great potential for efficiently running the same types of data processing pipelines and workflows as those handled by the frameworks previously mentioned. Next, we will explore some of the most relevant solutions for scheduling serverless workflows.

2.2.3 Modern Workflow Scheduling

The limitations of IaaS-based frameworks, such as those mentioned previously, have led to a new generation of workflow orchestrators designed for flexibility, usability, and ease of deployment. Unlike earlier systems bound to static clusters and rigid DSLs, modern platforms embrace Python APIs, container-

ization³, and cloud-native⁴ principles. Tools such as Prefect [43], Dagster [44], and Airflow [30] prioritize developer productivity and observability, while Argo Workflows [45] leverages Kubernetes [46] as its native execution environment. Another interesting project is Apache Beam, a cloud-native *unified programming model* for batch and streaming data pipelines designed to be executed across multiple backends, with some of the most popular implementations being Google Cloud Dataflow [47]. These solutions mark a shift from infrastructure management toward higher-level abstractions that integrate seamlessly with cloud platforms and services.

2.2.3.A Stateful Serverless Functions

While modern orchestrators such as Argo, Prefect, Dagster, and Airflow provide powerful abstractions for coordinating workflows across diverse environments, they can be unnecessarily complex for developers who already rely on stateless serverless functions within a single cloud provider. In such cases, what is often required is not a general-purpose orchestration framework but a lightweight mechanism to compose stateless functions into more complex workflows, supporting coordination patterns such as *fan-out*, *fan-in*, and conditional branching. To address this gap, cloud providers have introduced *stateful serverless functions*, which augment the stateless Function-as-a-Service (FaaS) model with durable state management and execution control.

A **stateful serverless function** represents a workflow orchestration paradigm in which an external coordination layer manages the execution and state of multiple stateless function invocations. These orchestrators track workflow progress, preserve context across invocations, and handle retries, error propagation, and branching logic. A common mechanism across these platforms is the use of *snapshotting* or durable state persistence: the engine periodically records workflow state so that execution can be paused and later resumed without requiring all individual functions to remain active. By combining snapshotting with techniques such as event sourcing, persistent queues, and transactional state management, stateful orchestrators enable long-running workflows that can scale across distributed environments while remaining fault tolerant and cost efficient.

Prominent examples include AWS Step Functions [8], Google Cloud Workflows [10], Azure Durable Functions [9], and Cloudflare Workflows [48]. Despite differences in design and integration, they share the goal of simplifying complex coordination atop serverless platforms. AWS Step Functions offers JSON- or YAML-based state machines using the Amazon States Language (ASL)⁵, enabling workflows that may last up to one year. Google Cloud Workflows provides YAML- or JSON-based definitions with a maximum duration of 60 minutes per execution, tightly integrated with Google Cloud services such as BigQuery and Cloud Run. Azure Durable Functions follows a code-centric approach in which developers

³<https://aws.amazon.com/what-is/containerization/>

⁴<https://aws.amazon.com/what-is/cloud-native/>

⁵<https://docs.aws.amazon.com/step-functions/latest/dg/concepts-amazon-states-language.html>

write an *"orchestrator function"* in languages such as C#, JavaScript, or Python, with workflow durations of up to 30 days. Finally, Cloudflare Workflows emphasizes lightweight, edge-native ⁶ orchestration, optimized for event-driven scenarios at the edge.

Together, these services extend the applicability of serverless beyond short-lived, stateless tasks, enabling complex approval processes, data pipelines, machine learning training, and financial transaction workflows that require state persistence and long execution durations. At the same time, they shift the responsibility of orchestration away from developers, who would otherwise need to implement custom, serverful coordination layers.

The tradeoff, however, is strong vendor lock-in, since each provider enforces its own workflow representation and tight integration with its ecosystem, making portability and hybrid-cloud adoption more challenging. Furthermore, the user is billed for the orchestration service on top of the individual function executions, which can increase costs for long-running or highly parallel workflows compared to managing orchestration independently. In addition, the orchestrator can make suboptimal scheduling decisions, such as inefficient task placement or resource allocation, over which the user has little or no control, potentially impacting performance and cost efficiency.

2.2.4 Serverless Workflow Scheduling

Having discussed commercial stateful serverless functions and their advantages and limitations, we now turn to research-oriented approaches for orchestrating workflows in stateless serverless environments. Unlike managed offerings, some of these systems explore innovative scheduling strategies and trade-offs that are particularly relevant for our work.

2.2.4.A Workflow Scheduling Approaches

Workflow scheduling/orchestration in serverless environments can generally be categorized into three approaches:

- **Centralized scheduling:** In this approach, a single scheduler maintains a global view of the entire workflow, including task dependencies, resource availability, and execution progress. This allows the scheduler to make fine-grained decisions about task placement, load balancing, and prioritization, often optimizing for latency or resource utilization. However, the centralized model can become a bottleneck as workflow size and concurrency increase, introducing single points of failure. It also requires the scheduler to handle high-throughput metadata and state management, which can be challenging in highly dynamic serverless environments.

⁶<https://www.cloudflare.com/learning/serverless/glossary/what-is-edge-computing/>

- **Queue-based or message-driven scheduling:** Here, tasks are decoupled from execution using queues or message-passing systems. Producers submit tasks to a queue, and workers pull tasks asynchronously when they become idle. This design improves elasticity, as workers can scale independently of the workflow controller, and naturally provides fault tolerance—failed tasks can be retried by re-queuing. While it removes the single bottleneck of a centralized scheduler, queue-based systems may have less optimal global scheduling decisions, and additional logic may be needed to enforce task ordering or dependency constraints.
- **Decentralized and Choreographed scheduling:** In this model, the responsibility for orchestration is distributed across the worker nodes rather than concentrated in a central entity. Each node independently manages task execution, coordinates with peers, and propagates state updates as necessary. This approach eliminates the need for dedicated scheduler infrastructure, mitigates bottlenecks, and enables faster scaling to thousands of concurrent functions. However, this model introduces greater complexity in ensuring fault tolerance and consistent state propagation across distributed, ephemeral environments. Ensuring that tasks execute *exactly once* becomes particularly challenging, requiring stronger coordination and consensus mechanisms. To address these issues, algorithms such as Paxos [49], Raft [50], or coordination services like ZooKeeper [51] can be employed, along with localized snapshots or lightweight distributed state stores, to maintain workflow coherence and reliability without relying on centralized scheduling. Most existing solutions, however, assume that tasks are *idempotent*, so that repeated execution does not produce unintended side effects, simplifying failure recovery and avoiding the need for strict exactly-once guarantees.

2.2.4.B Relevant Workflow Schedulers

To illustrate the spectrum of serverless workflow scheduling strategies, we now discuss representative systems that embody each approach and inspired our work. DEWE v3 [22] demonstrates a hybrid (IaaS and FaaS) queue-based model, where tasks are distributed through dedicated queues depending on their expected execution time. PyWren [52] exemplifies a more centralized scheduling paradigm, in which the user or submission machine maintains control over task execution while workers simply carry out assigned functions. Finally, Unum [21] and WUKONG [20] showcase decentralized choreographed orchestration, distributing workflow logic across workers to achieve high scalability and reduced reliance on central schedulers. Examining these systems provides concrete examples of the trade-offs and optimizations inherent to each scheduling strategy.

A – DEWE v3 DEWE v3 [22] introduces an innovative hybrid approach to serverless workflow orchestration that combines the best aspects of both serverless and serverful computing models. This hybrid workflow execution engine intelligently distributes tasks based on their characteristics: *short tasks* are run on FaaS workers while *longer tasks* run on virtual machines. The system employs a queue-based job distribution mechanism where jobs expected to complete within FaaS limits are published to a common job queue for serverless execution, while long-running jobs are directed to a separate queue for local, serverful execution on dedicated servers.

Jobs that fail to execute on FaaS workers, for being longer than expected and exceeding execution limits imposed by the platform, are redirected to the serverful queue. This dual-execution model enables DEWE to accommodate workflows with diverse resource consumption patterns. This system proves particularly effective for scientific workflows, such as Montage [5], where task durations and resource requirements vary significantly. However, this hybrid approach introduces specific trade-offs. Latency-sensitive workflows may be slowed by job queuing overhead. In addition, hybrid deployments often lead to resource underutilization, as serverful workers may sit idle when most tasks are executed on FaaS. Finally, the centralized workflow manager can become a scalability bottleneck when handling many short tasks.

B – PyWren PyWren [52], representing one of the pioneering pure serverless approaches, demonstrates the potential and limitations of leveraging unmodified serverless infrastructure for distributed computation. Built atop AWS Lambda, PyWren focuses on executing arbitrary Python functions as stateless serverless functions with minimal user management overhead, automatically handling function execution, dependencies, S3 bucket storage for serialized code and intermediate data. The system is ideal for *embarrassingly parallel* workloads, also known as “*bag-of-tasks*” scenarios, with many independent, parallel tasks such as simple data transformations, scientific simulations, parallel model training, and large-scale media processing. While PyWren’s serverless orchestration model provides excellent scalability and removes the burden of infrastructure management, its simplicity limits its applicability. It is not well-suited for workflows with complex dependency structures or those that require sharing large intermediate results through object storage. Moreover, latency-sensitive applications are disadvantaged by function cold starts, since PyWren does not include mechanisms to mitigate their impact.

C – Unum Unum [21] takes a radically different approach from the two previous solutions by decentralizing orchestration logic entirely, eliminating the need for a standalone orchestrator service. This application-level serverless workflow orchestration system embeds orchestration logic directly into a library that wraps user-defined FaaS functions, leveraging an external scalable con-

sistent data store for coordination during fan-ins and execution correctness. Unum introduces an Intermediate Representation (IR) to capture information about workflow progression (nearby tasks) and relies only on minimal, common serverless APIs (function invocation and basic data store operations) available across cloud platforms. This design choice provides exceptional portability and cost-effectiveness, as it can run on unmodified serverless infrastructure.

Unum also can compile workflows defined in languages from providers like AWS Step Functions and Google Cloud Workflows into its IR format. However, Unum’s generic approach comes with trade-offs: it currently supports only statically defined control structures and cannot express workflows where the next step is determined dynamically at runtime, and it lacks data locality optimizations since it cannot force related tasks to execute on the same worker, with each function instance executing only its specific task before triggering the next function.

D – WUKONG WUKONG [20] represents the most sophisticated approach among these solutions, designed as a *decentralized choreographed locality-enhanced* serverless workflow engine. Built on top of Dask’s programming model and DAG generation capabilities [20], WUKONG reimagines the execution layer to address the limitations of traditional serverful models like Dask Distributed while maximizing the advantages of serverless computing. The system focuses on improving scale-out speed and enhancing data locality to minimize large object movement. WUKONG’s architecture is divided into static components (operating before workflow execution) and dynamic components (operating during execution). The static scheduler includes a **DAG Generator** that leverages Dask’s library to convert Python code into DAGs, a **Schedule Generator** that creates n static schedules for n root/leaf nodes (each containing every reachable task in a depth-first search starting at that node), **Initial Task Executor Invokers** that launches the first Lambda instances for each root task, and a **Subscriber Process** on the client that waits for and downloads final results. After receiving the initial schedules, FaaS workers (referenced to as *AWS Lambda Executors*) drive workflow execution. Workers execute tasks until they encounter a *fan-out*, at which point they transfer data to intermediate storage, execute 1 of the n fan-out tasks and invoke $N - 1$ new executors for the other tasks. Then, when they find a *fan-in*, the group of executors that reach the common fan-in node cooperate using a *dynamic scheduling* model to select only one executor to proceed. This coordination is managed through a shared **dependency counter** in a Key-Value Store (KVS). Each involved executor *atomically* updates this counter; the one whose update satisfies the final input dependency for the fan-in task will execute that task and continue along its static schedule. The other executors transfer their intermediate data to storage, and then stop their execution, decreasing the workflow parallelism.

Besides dynamic scheduling, WUKONG employs data locality optimization techniques designed

to avoid moving large data objects; **Task Clustering for Fan-Out Operations** allows executors to continue executing downstream tasks when a fan-out task produces large outputs, becoming the executor of multiple fan-out targets rather than just executing 1 and invoking $N - 1$ new executors; **Task Clustering for Fan-In Operations** enables executors to recheck dependencies after uploading large objects to storage, potentially executing fan-in tasks themselves if dependencies are satisfied during the upload process, potentially avoiding large downloads; **Delayed I/O** allows executors to hold off on writing large intermediate results to external storage until it is absolutely necessary. Instead of immediately storing data when some downstream tasks are not yet ready, the executor first runs any tasks that can proceed and then checks again if the remaining ones have become ready. If they have, the executor can execute them directly using the data already in memory, avoiding both the write and a later read from storage. Only when no further progress is possible are the results finally written out. This can reduce unnecessary data transfers.

These optimizations, combined with WUKONG’s decentralized scheduling approach, significantly enhance performance compared to both **Dask Distributed** and **PyWren** by minimizing data transfer overhead and eliminating central scheduler bottlenecks. However, WUKONG shares the limitation of supporting only statically defined control structures, requiring workflow DAGs to be known ahead-of-time, similarly to our proposed solution. Additionally, its optimization heuristics can lead to inefficiencies in certain scenarios: *Delayed I/O* may increase makespan and storage usage if dependencies aren’t met after retries; fan-in conflicts where multiple tasks produce large objects can result in resource waste depending on upload timing; and fan-out scenarios with small inputs may not justify the overhead of invoking multiple executors as it can make subsequent fan-in’s more expensive. Furthermore, WUKONG assumes a homogeneous execution environment, where all workers provide identical resources (e.g., each task is allocated 2 CPU cores and 512 MB of memory), which prevents tailoring resources to tasks with different computational or memory demands.

While WUKONG represents a significant advance in serverless workflow orchestration through its decentralization, its scheduling and optimizations remain limited. The system bases decisions only on the next stage of the workflow (i.e., one-to-one, fan-in, or fan-out transitions). We refer to this as *one-step scheduling*, since it relies solely on information about the next step. Crucially, WUKONG does not exploit the global knowledge of the workflow structure, even though the entire workflow structure is known before execution begins. Also, its optimizations rely on heuristic-based strategies that can lead to suboptimal performance when workflow behavior deviates from expected patterns.

2.3 Discussion/Analysis

The existing body of related work highlights a clear progression in workflow orchestration strategies, moving from traditional cluster-based frameworks to cloud-native platforms and finally to serverless execution engines. Cluster-based systems such as Hadoop, Spark, Flink, and Dask emphasize fine-grained control, strong data locality, and predictable performance, but they incur significant operational overhead, limited elasticity, and often require technical expertise to deploy and manage. Commercial cloud-native platforms like AWS Step Functions and Azure Durable Functions simplify deployment and management by abstracting state handling and orchestration, but they typically incur additional costs and are bound to vendor-specific ecosystems. Runtime extensions such as Palette, FaaS^T, and Lambdata tackle the core inefficiencies of serverless platforms by enhancing data locality and reducing communication overhead.

Serverless workflow engines like PyWren, Unum, and WUKONG represent the most direct attempts to build high-performance workflow execution on unmodified FaaS infrastructure. While PyWren demonstrates the feasibility of large-scale embarrassingly parallel workloads, it struggles with complex workflows. Unum advances decentralization by embedding orchestration logic directly into functions, achieving portability and cost efficiency, but it remains limited in its support for dynamic control structures and lacks optimizations for data locality. WUKONG achieves major improvements through decentralization and data-aware heuristics such as *Task Clustering* and *Delayed I/O*, delivering great scalability and cost efficiency. Taken together, these systems provided the most direct inspiration for our work, while also highlighting key open challenges that our approach seeks to address.

3

Architecture

Contents

3.1	Workflow Definition Language	22
3.2	Architecture	24
3.3	Metadata Management	26
3.4	Static Workflow Planning	29
3.4.1	Workflow Simulation	29
3.4.2	Planning Algorithms	29
3.4.3	Optimizations	34
3.5	Client	38
3.6	Decentralized Workers	40

In this chapter, we will present the architecture, as well as some implementation details of our decentralized serverless workflow execution engine. Here we will describe how a workflow is defined and configured, we will then present an architecture overview of the solution, followed by a more in-depth description of the main layers and components. We will go over how workflow plans are created, optimizations they can apply, and how they are executed in a choreographed manner by FaaS workers.

3.1 Workflow Definition Language

We will now present the *workflow language* with which users can create tasks and compose them into workflows. It is heavily inspired by WUKONG and Dask's: the user can create workflows by composing individual Python functions, as shown in Listing 3.1. In this example, we define two tasks, `task_a` and `task_b`, and then compose them into a DAG by passing their results as arguments to the next task. The resulting workflow structure is illustrated in Figure 3.1. Python's simplicity, readability, and widespread popularity, especially among data scientists and researchers, also motivated us to choose this language for defining workflows, lowering the barrier to entry while enabling powerful parallel execution.

In Dask and WUKONG, tasks are also created by decorating ¹ Python functions with a special decorator, named `@delayed` (equivalent to our `@DAGTask`), and then composed into a DAG by calling these decorated functions, similarly to our approach. The workflow execution is also triggered by calling `compute()` on the last/sink task, as shown in Listing 3.2.

Listing 3.1: DAG definition example

```
1  # 1) Task definition
2  @DAGTask
3  def task_a(a: int) -> int:
4      # ... user code logic ...
5      return a + 1
6
7  @DAGTask(forced_optimizations=[PreLoadOptimization()])
8  def task_b(*args: int) -> int:
9      # ... user code logic ...
10     return sum(args)
11
12 # 2) Task composition (DAG/Workflow)
13 a1 = task_a(10)
14 a2 = task_a(a1)
15 a3 = task_a(a1)
16 b1 = task_b(a2, a3)
17 a4 = task_a(b1)
```

When `task_a(a1)` is invoked, it doesn't actually run the user code. It instead creates a representation of the task, which can be passed as argument to other tasks. The workflow planning and execution only happens once `.compute()` is called on the last/sink task (`a4`), as shown in Listing 3.2. When `compute()` is called, we can create a representation of the entire workflow structure by backtracking the task dependencies.

¹<https://www.geeksforgeeks.org/python/decorators-in-python/>




Figure 3.1: Simple DAG example

Calling `task_a(10)` generates a corresponding task representation, `DAGTaskNode`, which captures essential information about the task. This includes a unique task identifier, the task's dependencies, which may be other tasks or “hardcoded” data. Hardcoded data refers to values that are known prior to workflow execution; in this example, the value 10 is hardcoded. In a text processing workflow, for instance, the bytes of a file to be analyzed would be considered hardcoded as long as they are available before the workflow starts and are passed as arguments to a task. If a task function argument is itself an instance of `DAGTaskNode`, as `a1` is in `task_a(a1)`, it is treated as a dependency of `task_a`. Once a `DAGTaskNode` is created, its upstream tasks and dependencies are automatically discovered. This enables constructing a representation of the entire workflow prior to its execution by backtracking the task dependencies, starting from the *sink node*.

Furthermore, the task function code is also embedded within the task representation, as a Python Callable. Later, the `DAGTaskNode` is serialized, using `cloudpickle` ², allowing it to be transmitted to storage, and retrieved by workers for execution.

Listing 3.2: Setting up and launching workflow execution

```

1 result = a4.compute(
2     dag_name="simpledag",
3     config=Worker.Config(
4         faas_gateway_address=...,
5         intermediate_storage_config=(ip, port, password),
6         metrics_storage_config=(ip, port, password),
7         planner_config=UniformPlanner.Config(
8             sla=sla,
9             worker_resource_configuration=TaskWorkerResourceConfiguration(memory_mb=1024),
10            optimizations=[PreLoadOptimization, TaskDupOptimization, PreWarmOptimization]
11        )
12    )
13 )

```

²<https://github.com/cloudpipe/cloudpickle>

One limitation of this DAG definition language is that it doesn't support "dynamic fan-outs" (e.g., creating a variable number of tasks depending on the result of another task) on a single workflow. This is a powerful and expressive feature, but that is seldom supported in other DAG definition languages (e.g., Dask, WUKONG, Unum, Oozie [39] do not support it). These languages require the user to split the workflow into multiple workflows, one for each *dynamic fan-out*: one workflow runs up to the task that generates a list of results, while a second workflow starts with a number of tasks that depends on the size or contents of that list.

Apache AirFlow ³ supports this feature through an extension to their DAG language, allowing a variable number of tasks to be created at run-time depending on the number of results produced by a previous task. Implementing similar functionality is possible, but it would reduce the accuracy of predictions. This is because we would also need to predict the expected fan-out size, and any errors in that prediction could amplify inaccuracies in the predictions for the rest of the workflow.

We will now present our solution architecture overview, highlighting the core layers of our decentralized serverless workflow execution engine.

3.2 Architecture

The overall architecture and logical flow of our decentralized serverless workflow execution engine is organized into 3 high-level layers. Figure 3.2 provides an overview of this architecture. The upper part represents the components that run on the user's machine, while the lower part represents the components that run outside the user's machine.

The user writes its workflows in Python (demonstrated in Section 3.1). First, a planning algorithm, chosen by the user, will run locally to generate a static workflow plan. This plan defines a task-to-worker mapping and other task-level optimization hints for FaaS workers. Once the plan is done, the client launches the initial workers for the root tasks, kicking off workflow execution. The user program then waits for a storage notification indicating workflow completion and then retrieves the final result from storage.

The following sections should provide a deeper understanding of each layer as well as how the user interacts with the system.

1. **Metadata Management:** Responsible for collecting and storing task metadata from previous executions. It also uses this metadata to provide predictions regarding task execution times, data transfer times, task output sizes, and worker startup times;
2. **Static Workflow Planning:** Receives the entire workflow, represented as a Directed Acyclic Graph

³<https://airflow.apache.org/docs/apache-airflow/stable/authoring-and-scheduling/dynamic-task-mapping.html>




Figure 3.2: Solution Architecture

(DAG), and a "planner" (an algorithm chosen by the user). This planner will use the predictions provided by Metadata Management to create a static plan/schedule to be followed by the workers;

3. **Scheduling:** This component is integrated into the workers, and it is responsible for executing the plan generated by the Static Workflow Planning layer, applying optimizations and delegating tasks as needed.

There are 3 distinct computational entities involved in this system:

- **User Computer:** Responsible for creating workflow plans, submitting them (triggering workflow execution), and receiving its results. The planning phase also happens on this computer, right before a workflow is submitted for execution;
- **Workers:** These are the FaaS workers (often running in containerized environments), that execute one or more tasks. The decentralization of our solution is due to the fact that these workers are responsible for scheduling of subsequent tasks, delegating tasks and launching new workers when

needed without requiring a central scheduler. Lastly, they are also responsible for collecting and uploading metadata;

- **Storage:** Consists of an *Intermediate Storage* for intermediate outputs which may be needed for subsequent tasks and a *Metadata Storage* for information crucial to workflow execution (e.g., notifications about task readiness and completion).

3.3 Metadata Management

The goal of the **Metadata Management** layer is to provide the most accurate task-wise predictions to help the planner algorithm chosen by the user to make better decisions. To achieve this, while the workflow is running we collect metrics about each task's execution. These metrics are stored in *Metadata Storage*: task execution time, data transfer size and time, task input and output sizes, and worker startup time.

Storing these metrics powers a prediction API, shown in Listing 3.3. To improve accuracy, metrics are kept separate for each workflow. As a result, even if two workflows use the same function or task code, their metrics are stored independently. This design choice reflects our assumption that different workflows may follow different execution patterns. To avoid introducing runtime overhead, metrics are only uploaded before the worker shuts down.

The prediction methods take an additional parameter, SLA (Service-level Agreement), which is specified by the user and influences the selection of prediction samples. For example, SLA="average" will use the average of the historical samples, whereas SLA=Percentile(80) will return a more conservative estimate, where the 80th percentile of the historical samples is used, providing a higher estimate. This parameter is provided by the user, and is used by the PredictionsProvider API to provide estimates based on historical data.

Listing 3.3: Task Predictions API

```
1 class PredictionsProvider:
2     def predict_output_size(function_name, input_size, sla) -> int
3
4     def predict_worker_startup_time(state: 'cold' | 'warm', resource_config, sla) -> float
5
6     def predict_data_transfer_time(data_size_bytes, resource_config, sla) -> float
7
8     def predict_execution_time(task_name, input_size, resource_config, sla) -> float
```

When collecting metrics such as worker startup time, data transfer time, and task execution time,

we associate them with the worker resource configuration used to execute the task (e.g., memory and CPU). To improve prediction accuracy, our method follows two strategies. If there are enough historical samples for the exact resource configuration being predicted, we use only those samples. Otherwise, when samples for the target configuration are insufficient, we apply a normalization approach: we adjust samples from other memory configurations to a baseline, use these normalized values to estimate execution time, and then rescale the result to the target configuration.

After filtering the samples by their resource configuration, we apply the sample selection algorithm shown in Algorithm 1, which identifies the most relevant historical samples for each prediction. Given a reference value (the value for which to predict), the method first computes a *baseline* from all available samples (line 2). The baseline is determined using the user-specified SLA, thereby adapting the prediction to user-defined expectations.

Next, the algorithm progressively searches for samples whose associated input sizes fall within increasing proximity thresholds relative to the reference value. Each threshold increment expands the acceptable distance range by 5% of the computed baseline, up to a maximum of 100%. Within each iteration, samples are categorized as being below, above, or exactly matching the reference value (lines 8-19), allowing the algorithm to maintain a symmetric distribution of samples around the target.

Once enough samples are found within a given threshold (line 21), they are sorted by proximity to the reference value (lines 23-24). The algorithm then selects up to a maximum number of samples (`max_samples`), prioritizing those closest to the reference and ensuring balance between samples above and below the target (lines 23-30). If the maximum capacity is not reached, the remaining slots are filled with the next-closest available samples (lines 32-34).

If even after considering all thresholds (up to 100% of the established baseline) no sufficient number of samples is found, the algorithm falls back to selecting the globally closest samples (lines 39-42). This guarantees that a prediction can always be made, even when the historical data is sparse, though it may not be as accurate.

In addition to using this algorithm to select the most relevant samples for each prediction, we restrict the samples to the same workflow and planner. For instance, data collected while executing the *Text Analysis* workflow with the *Uniform* planner will not be used to predict the execution time of the same workflow under the *Non-Uniform* planner. By limiting the sample set in this way, we ensure that the selected samples are directly comparable to the target scenario, reducing variability introduced by differing workflow behaviors or planner strategies.

This procedure ensures that the prediction leverages historical samples most similar to the target input, which tends to be very accurate when a workflow is executed multiple times with the same or similar workloads, allowing the estimates to become accurate without requiring many previous workflow instances.

Algorithm 1 Select Relevant Samples for Predictions

Require: *reference_value*, *all_samples*, *SLA*, *max_samples*, *min_samples*

Ensure: Set of values from samples closest to *reference_value*

```
1:  $\triangleright$  Compute baseline based on SLA percentile
2: baseline  $\leftarrow$  PERCENTILE( $\{comparable_{toref} \mid (value, comparable_{toref}) \in all\_samples\}, SLA$ )
3:  $\triangleright$  Try increasing thresholds to find enough samples
4: for threshold_pct  $\leftarrow$  5 to 100 step 5 do
5:   distance_threshold  $\leftarrow$  baseline  $\times$  (threshold_pct/100)
6:   below_samples  $\leftarrow$   $\emptyset$ , above_samples  $\leftarrow$   $\emptyset$ , exact_samples  $\leftarrow$   $\emptyset$ 
7:    $\triangleright$  Categorize samples by their position relative to reference
8:   for all  $(value, comparable_{toref}) \in all\_samples$  do
9:     signed_dist  $\leftarrow$  comparable_{toref} - reference_value
10:    if  $|signed\_dist| \leq distance\_threshold$  then
11:      if signed_dist < 0 then
12:        below_samples.ADD( $(|signed\_dist|, value)$ )
13:      else if signed_dist > 0 then
14:        above_samples.ADD( $(|signed\_dist|, value)$ )
15:      else
16:        exact_samples.ADD(value)
17:      end if
18:    end if
19:  end for
20:  total_found  $\leftarrow$   $|below\_samples| + |above\_samples| + |exact\_samples|$ 
21:  if total_found  $\geq min\_samples$  then
22:     $\triangleright$  Sort by distance and select balanced samples
23:    below_samples.SORTBYDISTANCE()
24:    above_samples.SORTBYDISTANCE()
25:    remaining  $\leftarrow$  max_samples -  $|exact\_samples|$ 
26:    per_side  $\leftarrow$   $\lfloor remaining/2 \rfloor$ 
27:     $\triangleright$  Select closest samples from each side
28:    selected  $\leftarrow$  exact_samples
29:    selected  $\leftarrow$  selected  $\cup$  below_samples[0 : min(per_side,  $|below\_samples|$ )]
30:    selected  $\leftarrow$  selected  $\cup$  above_samples[0 : min(per_side,  $|above\_samples|$ )]
31:     $\triangleright$  Fill remaining budget from available samples
32:    if  $|selected| < max\_samples$  then
33:      FILLREMAINING(selected, below_samples, above_samples, max_samples)
34:    end if
35:    return  $\{value \mid value \in selected\}$ 
36:  end if
37: end for
38:  $\triangleright$  Fallback: not enough samples even at 100% threshold
39: samples_with_dist  $\leftarrow$   $\{(|comparable_{toref} - reference\_value|, value) \mid (value, comparable_{toref}) \in all\_samples\}$ 
40: samples_with_dist.SORTBYDISTANCE()
41: return  $\{value \mid (dist, value) \in samples\_with\_dist[0 : min\_samples]\}$ 
```

3.4 Static Workflow Planning

This layer executes on the user side, and it receives the workflow representation and a workflow planning algorithm chosen and parametrized by the user (as shown in Listing 3.2). Its job is to execute the planning algorithm, providing it access to the predictions exposed by the Metadata Management layer (Section 3.3).

3.4.1 Workflow Simulation

The availability of predicting task execution time, data transfer latency, function I/O, and worker startup cost, exposed through the Metadata Management layer (Section 3.3), makes it possible to simulate the execution of an entire workflow instance.

To this end, we implemented a dedicated simulation module. The module accepts a workflow representation in which tasks are annotated with worker IDs, resource configurations, and optimizations. For each task, the simulator estimates a number of metrics, such as whether the worker should be cold or warm, the input and output sizes, execution time, time to download dependencies, time to upload output, and both the earliest start time and the corresponding completion time, allowing it to derive the expected overall *makespan* of the workflow as well as the critical path.

This simulation capability significantly facilitates the work of planning components. Planners can experiment with alternative resource configurations, task placement policies, and co-location strategies without executing the workflow in a live environment. The fidelity of the simulation results, however, is directly dependent on the accuracy of the predictive models exposed through the *Predictions API*.

3.4.2 Planning Algorithms

For each task, the planner assigns both a `worker_id` and a resource configuration (vCPUs and memory). The `worker_id` specifies the worker instance that must execute the task—analogous to the “colors” in Palette Load Balancing [12], but in our case this assignment is mandatory rather than advisory, giving strict control over execution locality. Two tasks assigned the same `worker_id` should be executed on the same worker instance. If `worker_id` is not specified, workers will, at run-time, have to decide whether to execute or delegate those tasks, similar to WUKONG’s [20] scheduling. We refer to these workers as “flexible workers”.

In our planners and implementation, we primarily focus on fixed `worker_ids`, as this approach provides planners with finer-grained control over task execution locality. It also reduces network overhead, since workers are aware of the specific tasks assigned to them and can simply subscribe to the corresponding `TASK_READY` events, eliminating the need for broad or repeated coordination messages.

Users can select from three provided planners or implement their own planner by implementing an interface. All planners have access to the predictions API as well as the workflow simulation. The planners the user can choose from are the following:

1. **WUKONG**: All tasks will use the same worker configuration (specified by the user) and won't be assigned a `worker_id`, meaning they will be executed by "*flexible workers*". This is a more dynamic scheduling approach, which tries to reproduce WUKONG's behavior, where tasks aren't tied to specific workers;
2. **Uniform**: Tasks share a common worker configuration specified by the user, with each task assigned a `worker_id` to allow for co-location of tasks.
3. **Non-Uniform**: Tasks can use different worker configurations (list of available resources is specified by the user). Each task is assigned a `worker_id`. This algorithm starts by assigning the best available resources to all tasks. Then it runs a resource downgrading algorithm that attempts to downgrade resources of workers *outside the critical path* as much as possible without introducing a new critical path.

Both the **Uniform** and **Non-Uniform** planners follow a two-phase approach for task allocation: resource configuration assignment followed by worker ID assignment. The planners differ in their resource allocation strategies. The **Uniform planner** applies a single, user-specified CPU and memory configuration to all tasks, while the **Non-Uniform planner** selects the most powerful configuration from the user-specified options for each task. After resource configuration, both planners employ the logic detailed in Algorithm 2 for worker ID assignment.

Algorithm 2 presents the worker assignment procedure used by our planner to distribute workflow tasks across workers, trying to achieve data locality while balancing computational load. The algorithm iterates over the DAG nodes in topological order, ensuring that upstream tasks are always processed before their dependents. Each node is assigned to a worker depending on the structure of its neighborhood (fan-in or fan-out pattern) and on predictions of task execution time and output size.

In this algorithm, root nodes (those without upstream dependencies), are grouped together for assignment (lines 7-8). For simple linear dependencies ($1 \rightarrow 1$ relationships), the downstream task inherits the same worker as its upstream task, allowing direct data reuse without intermediate storage (lines 11-12). When a node fans out to multiple downstream tasks ($1 \rightarrow N$), those downstream tasks are clustered together and assigned as a group (lines 14-15). Conversely, for fan-in patterns ($N \rightarrow 1$), the algorithm assigns the downstream node to the worker responsible for producing the largest upstream output (lines 18-20), maximizing data locality by placing the consumer task where the majority of input data already resides.

The `ASSIGNGROUP` function (lines 23-58) is responsible for clustering tasks into execution groups and assigning them to workers. After retrieving the predicted execution times and output sizes for each task (lines 26-27), the algorithm classifies tasks as either *long* or *short* depending on whether their predicted execution time is above or below the median (lines 26-30). This categorization allows the planner to balance worker load.

The function proceeds in four stages:

1. **Local clustering (lines 32-36):** If an upstream worker is available, a subset of *short* tasks with larger output sizes (up to a predefined maximum cluster size) is assigned to the same worker. This promotes *data locality*, reducing data transfer costs by executing tasks near their data sources;
2. **Balanced pairing (lines 38-44):** The algorithm pairs each remaining *long* task with a few *short* ones, creating mixed groups, distributing workload more evenly;
3. **Grouping remaining short tasks (lines 46-50):** Any remaining unassigned *short* tasks are grouped together and allocated to new workers, up to the maximum cluster size;
4. **Grouping remaining long tasks (lines 52-57):** This final phase is only reached when there are more long tasks than short ones, meaning some long tasks could not be paired in the previous phase. In such cases, the remaining long tasks are grouped into smaller clusters (half the normal cluster size) to try reducing resource contention.

After this, the **Non-Uniform** planner runs an additional algorithm, shown in Algorithm 3, that attempts to downgrade resources of workers *outside the critical path* as much as possible without introducing a new critical path, by iteratively simulating the effect of downgrading resources of workers *outside the critical path* with different configurations.

The algorithm begins by identifying workers whose tasks are outside the critical path (lines 3-9). Then, for each of those workers, we attempt to downgrade its resources by iterating through the list of use-provided resource configurations, simulating progressively weaker configurations (lines 11-41).

After a configuration is added to all tasks of the target worker (lines 17-21), the simulation layer (explained in Subsection 3.4.1) is used to simulate the critical path duration (line 23). If the downgrade does not increase the critical path time, it is accepted. This process repeats for each worker until no more configurations are available to experiment or the critical path time is exceeded, in which case it reverts to the previous *acceptable* resource configuration (line 35).

With the information they have access to, planners can estimate whether it is worthwhile to offload a task to a more powerful worker. This involves weighing the overhead of uploading the input data, waiting for the worker to be provisioned, and then executing the task, against the alternative of simply executing the task on the current, less powerful worker.

Algorithm 2 Worker Assignment Algorithm (used by Uniform and Non-Uniform planners)

Require: *nodes*, *predictions*, *MAX_CLUSTERING*

```
1: assigned  $\leftarrow \emptyset$  ▷ nodes are topologically sorted

2: for all  $n \in \text{nodes}$  do
3:   if  $n \in \text{assigned}$  then
4:     continue
5:   end if
6:   if  $n.\text{upstream} = \emptyset$  then ▷ root nodes
7:      $\text{roots} \leftarrow \{r \in \text{nodes} \mid r.\text{upstream} = \emptyset \wedge r \notin \text{assigned}\}$ 
8:      $\text{ASSIGNGROUP}(\text{null}, \text{roots})$ 
9:   else if  $|n.\text{upstream}| = 1$  then ▷  $1 \rightarrow 1$  or  $1 \rightarrow N$ 
10:     $u \leftarrow n.\text{upstream}[0]$ 
11:    if  $|u.\text{downstream}| = 1$  then
12:       $\text{ASSIGNWORKER}([n], u.\text{worker})$  ▷ reuse worker
13:    else ▷  $1 \rightarrow N$ 
14:       $\text{fanout} \leftarrow \{d \in u.\text{downstream} \mid d \notin \text{assigned}\}$ 
15:       $\text{ASSIGNGROUP}(u.\text{worker}, \text{fanout})$ 
16:    end if
17:  else ▷  $N \rightarrow 1$  (assign to worker of upstream task with the largest total output)
18:     $\text{outputs} \leftarrow \{u.\text{worker} : \text{predictions.output\_size}(u) \mid u \in n.\text{upstream}\}$ 
19:     $\text{worker\_w\_greatest\_acc\_output} \leftarrow \arg \max_{w \in \text{outputs}} \text{outputs}[w]$ 
20:     $\text{ASSIGNWORKER}([n], \text{best})$ 
21:  end if
22: end for

23: function  $\text{ASSIGNGROUP}(\text{up\_worker}, \text{tasks})$ 
24:   if  $\text{tasks} = \emptyset$  then return
25:   end if
26:    $\text{exec\_t} \leftarrow \{t : \text{predictions.exec\_time}(t) \mid t \in \text{tasks}\}$ 
27:    $\text{out\_sz} \leftarrow \{t : \text{predictions.output\_size}(t) \mid t \in \text{tasks}\}$ 
28:    $\text{median} \leftarrow \text{MEDIAN}(\text{exec\_t.values}())$ 
29:    $\text{longs} \leftarrow \{t \in \text{tasks} \mid \text{exec\_t}[t] > \text{median}\}$ 
30:    $\text{shorts} \leftarrow \text{SORTLARGEROUTPUTFIRST}(\{t \in \text{tasks} \mid \text{exec\_t}[t] \leq \text{median}\})$ 
31:   ▷ 1) cluster short tasks with bigger outputs on upstream worker
32:   if  $\text{up\_worker} \neq \text{null} \wedge \text{shorts} \neq \emptyset$  then
33:      $\text{cluster} \leftarrow \text{shorts}[0 : \text{MAX\_CLUSTERING}]$ 
34:      $\text{ASSIGNWORKER}(\text{cluster}, \text{up\_worker})$ 
35:      $\text{shorts} \leftarrow \text{shorts}[\text{MAX\_CLUSTERING} : ]$ 
36:   end if
37:   ▷ 2) pair long tasks with remaining short tasks (1 long per group)
38:   while  $\text{longs} \neq \emptyset \wedge \text{shorts} \neq \emptyset$  do
39:      $\text{cluster} \leftarrow [\text{longs}[0]] + \text{shorts}[0 : \text{MAX\_CLUSTERING} - 1]$ 
40:      $\text{worker\_id} \leftarrow \text{NEWWORKERID}$ 
41:      $\text{ASSIGNWORKER}(\text{cluster}, \text{worker\_id})$ 
42:      $\text{longs} \leftarrow \text{longs}[1 : ]$ 
43:      $\text{shorts} \leftarrow \text{shorts}[\text{MAX\_CLUSTERING} - 1 : ]$ 
44:   end while
45:   ▷ 3) group remaining short tasks
46:   while  $\text{shorts} \neq \emptyset$  do
47:      $\text{worker\_id} \leftarrow \text{NEWWORKERID}$ 
48:      $\text{ASSIGNWORKER}(\text{shorts}[0 : \text{MAX\_CLUSTERING}], \text{worker\_id})$ 
49:      $\text{shorts} \leftarrow \text{shorts}[\text{MAX\_CLUSTERING} : ]$ 
50:   end while
51:   ▷ 4) group remaining longs (half-size)
52:    $\text{half} \leftarrow \max(1, \lfloor \text{MAX\_CLUSTERING}/2 \rfloor)$  32
53:   while  $\text{longs} \neq \emptyset$  do
54:      $\text{worker\_id} \leftarrow \text{NEWWORKERID}$ 
55:      $\text{ASSIGNWORKER}(\text{longs}[0 : \text{half}], \text{worker\_id})$ 
56:      $\text{longs} \leftarrow \text{longs}[\text{half} : ]$ 
57:   end while
58: end function
```

Algorithm 3 Resource Downgrading Algorithm (used by Non-Uniform planner)

Require: *dag, nodes, critical_path_ids, original_cp_time, configs, predictions*

```
1: workers_outside  $\leftarrow \emptyset$ 

2:                                     ▷ 1) Identify workers outside the critical path
3: for all n  $\in$  nodes do                                     ▷ nodes are topologically sorted
4:   wid  $\leftarrow$  n.worker_id
5:   if n.id  $\notin$  critical_path_ids  $\wedge \forall cp \in dag.critical\_path\_nodes : wid \neq cp.worker\_id$  then
6:     workers_outside  $\leftarrow$  workers_outside  $\cup \{wid\}$ 
7:   end if
8: end for
9: nodes_outside_cp  $\leftarrow \{n \in nodes \mid n.id \notin critical\_path\_ids\}$ 

10:                                     ▷ 2) Attempt downgrade for each worker outside critical path
11: for all wid  $\in$  workers_outside do
12:   last_acceptable_rc  $\leftarrow \{n.id : n.config \mid n \in nodes\_outside\_cp \wedge n.worker\_id = wid\}$ 

13:                                     ▷ Iterate through weaker configurations (skip strongest at index 0)
14:   for i  $\leftarrow 1$  to  $|configs| - 1$  do
15:     trial  $\leftarrow configs[i].CLONE(wid)$ 

16:                                     ▷ Apply trial configuration to all nodes of this worker
17:     for all n  $\in$  nodes_outside_cp do
18:       if n.worker_id = wid then
19:         n.config  $\leftarrow$  trial
20:       end if
21:     end for

22:                                     ▷ Recompute workflow timing with predictions
23:     cp_time  $\leftarrow$  SIMULATECRITICALPATHTIME(dag)

24:     if cp_time = original_cp_time then
25:                                     ▷ Downgrade acceptable, record as last acceptable state
26:       for all n  $\in$  nodes_outside_cp do
27:         if n.worker_id = wid then
28:           last_acceptable_rc[n.id]  $\leftarrow$  n.config
29:         end if
30:       end for
31:     else
32:                                     ▷ Downgrade increases critical path, revert and move on to the next worker
33:       for all n  $\in$  nodes_outside_cp do
34:         if n.worker_id = wid then
35:           n.config  $\leftarrow$  last_acceptable_rc[n.id]
36:         end if
37:       end for
38:       break                                     ▷ move to next worker
39:     end if
40:   end for
41: end for
```

To facilitate the implementation of new planners, the Python class `AbstractDAGPlanner`, from which all planners must inherit, provides a set of utility methods: a method to perform a topological sort of the DAG nodes, ensuring that we don't iterate on a node without first iterating on its upstream nodes; a method to estimate the input size of a task by summing the sizes of its hardcoded inputs and the predicted outputs of its upstream tasks; a method to simulate the execution of an entire workflow, returning predicted metrics for all tasks; and a method to compute the critical path of the workflow using the results of the simulation.

One of these validations ensures that *all tasks assigned to the same worker form a continuous, uninterrupted branch* within the workflow graph. In other words, a worker cannot be assigned to a group of tasks, skipped for intermediate ones along the dependency chain, and later reassigned to a downstream task. This rule introduces structural predictability, ensuring that task assignments for a given worker remain contiguous in the DAG. As a result, when delegating tasks, the system can determine whether a worker is already running and can simply receive a `TASK_READY` event (as described in Section 3.6), or whether a new worker launch is required. This constraint implicitly encourages planners to allocate tasks in ways that minimize worker idle time.

3.4.3 Optimizations

Aside from `worker_id` and resource assignments, planners can also apply different **optimizations** to further improve the workflow execution. The optimizations a planner can use are selected by the user, as shown in Listing 3.2. We provide three optimizations: **pre-warm**, **pre-load** and **task-dup**, but it is also possible to create new optimizations and define how workers should react to them. Now, we will describe the three base optimizations and how they are assigned to tasks:

1. **pre-warm**(`worker_config`, `delay_s`) [Pre-warming Workers]:

- *Interpretation*: Tasks/Nodes with this optimization should perform a special invocation to the FaaS gateway that forces it to launch a new worker with the specified resource configuration `worker_config`. This can be used to warm up workers ahead of time and mask cold start latencies;
- *Assignment Logic*: For workers expected to experience cold starts, we identify an **optimal worker** to perform *pre-warming*. The goal is to increase the probability that a container will be ready for our *target worker* when it is needed. The algorithm searches for tasks whose execution window (starting at earliest predicted start) align with a *pre-warming interval*, balancing two objectives: the pre-warmed worker should neither go cold before it is required nor be warmed too late. Once identified, the pre-warming optimization is attached to this node, which performs a special “empty invocation” to the FaaS gateway to initialize the worker. The

optimization includes a *delay*, specifying the offset from the *optimal worker's* start time to when the pre-warm request should be triggered. As soon as the optimal worker starts, it launches Python coroutines that wait for `delay_s` seconds before executing the pre-warm request.

2. **pre-load** [Pre-Loading Dependencies]:

- *Interpretation:* Workers assigned to tasks or nodes with this optimization should begin downloading the task's dependencies as early as possible. This prevents scenarios where a worker must fetch all dependencies at once. The optimization is effective only if the worker is active before executing the task, allowing it to download dependencies in parallel with other ongoing tasks. This is implemented by having the worker receive completion notifications from the *Metadata Storage* for all tasks upstream of the optimized task;
- *Assignment Logic:* It is an iterative process of assigning the optimization to nodes that have more than a configurable number of upstream dependencies assigned to another worker. After assigning each `pre-load` optimization, the workflow simulation is re-run: if the predicted makespan increases, the optimization is removed; if the makespan decreases but the critical path changes, the algorithm restarts with the new path. This process repeats until no further improvements are possible, or the algorithm hits a fixed iteration limit.

3. **task-dup** [Task Duplication]:

- *Interpretation:* Tasks or nodes with this optimization can be executed by other workers if doing so helps unlock dependent tasks more quickly. The task could be "duplicated" by workers that depend on its output. It is a trade-off between performance and resource utilization, allowing potentially faster execution at the cost of using additional compute resources. It is similar to the `pre-load` optimization, but more aggressive/costly, as instead of downloading dependencies as soon as they're ready, `task-dup` can execute the tasks that produce those dependencies locally;
- *Assignment Logic:* This optimization is assigned to tasks that have at least one downstream dependency scheduled on a different worker. The actual duplication decision is made dynamically at run time, based on a time-saving prediction: a task will only be duplicated if executing it locally (including downloading dependencies of the duppable task) is expected to complete earlier than waiting for its original execution and data transfer. When a *duppable* task (i.e., one marked with this optimization) begins execution on its assigned worker, it records a start timestamp in shared storage. Downstream tasks use this information to evaluate whether duplication would still save time or if it is faster to wait for the original execution to complete and download the output once ready on storage. When "*duplicating*" a task, its worker won't

upload the output to storage nor emit TASK_READY or TASK_COMPLETED events. The output is only kept local to the worker to avoid the need for extra synchronization with the original worker assigned to the duplicated task and other tasks dependent on it. Furthermore, emitting TASK_READY or TASK_COMPLETED events for duplicated tasks would also be misleading, as other workers might assume that the task's output is already available in storage, only to later discover that it is not.

Because planners may sometimes lack sufficient information to make optimal decisions about optimization assignments, it is important to not only allow the user to select optimizations at the workflow-level, but also allow them the flexibility to specify optimizations at the *task-level*. An example of this feature is shown in Listing 3.1, where the user requests that task_b attempt to use the *pre-load* optimization.

Once these optimizations are assigned, workflow planning is complete, and workers can begin execution. Because planning occurs on the user's machine (i.e., the machine launching the workflow), it is responsible for initiating the workflow by starting the initial workers. From that point onward, workers dynamically invoke additional workers as needed, following a choreographed, decentralized execution model.




Figure 3.3: Planned Workflow Execution Example

To illustrate this execution model, Figure 3.3 provides a visual trace of how a planned workflow would be executed. The diagram depicts the workflow with the optimizations and worker_id assignments for each task. The non-dashed arrows represent task dependencies, while the dashed arrows represent

interactions with the *Intermediate Storage* to either upload or download task data. We can see that task outputs are only uploaded to storage when there is at least one downstream task that depends on it and is assigned to another worker.

It is also worth noting that the planner assigned Task 6 to Worker 2. This decision might be due to Worker 2 being more powerful than Worker 1, and because the output of Task 5 is larger than that of Tasks 4 and 5. Therefore, even if the task were executed on a more powerful worker (such as Worker 3, which handled Task 3), the potential performance gain would not offset the additional time or resources required. This is an example of a planner deciding to co-locate Tasks 5 and 6 on the same worker to reduce data movement.

Regarding **optimizations**, we can see Task 1 pre-warming Worker 3, by making a dummy invocation to the FaaS gateway, in an attempt to make it available before Task 3 needs it. The pre-load optimization is used in Task 5, where the planner decided that Worker 2 should start downloading the external dependencies for Task 6 (Task 3 and Task 4) as soon as they are available. This pre-loading can begin as soon as Task 6's dependencies are ready in storage, potentially overlapping with Task 2's execution instead of Task 5, as shown in the figure.

Optimizations are implemented by re-defining worker execution logic at certain stages. The methods that a planner can implement in order to override default worker execution logic are shown in Listing 3.4: `wel_on_worker_ready` method is called once the worker starts executing, and the provided optimizations use it to subscribe to `TASK_READY` and `TASK_COMPLETED` events for specific tasks, and schedule *pre-warm* coroutines; `wel_before_task_handling` is called before task's dependencies are downloaded; `wel_override_handle_inputs` is called after discovering which tasks dependencies are not yet present locally and need fetching; `wel_before_task_execution` is called after all dependencies have been gathered and right before task's execution. `wel_override_should_upload_output` is called before task's execution and its output determines whether the task output should be uploaded to storage (e.g., tasks that are "*dupped*" don't upload their output, it remains local for other tasks of the same worker); `wel_update_dependency_counters` is called after a task's output is handled and the default behavior updates the *Dependency Counters* (explained in the next Section 3.6) of the downstream tasks. The `task-dup`, for example, overrides this method to prevent updating dependency counters when duplicating tasks. This is necessary because duplicated tasks do not upload their outputs to storage; therefore, incrementing the dependency counters would incorrectly signal to other workers that dependent tasks are ready to execute, even though some of their required inputs are still missing; lastly, `wel_override_handle_downstream` is called, and the objective of the default implementation is to decide which of the downstream tasks that became ready should this worker execute, and which tasks should be delegated to other workers.

Listing 3.4: Overridable worker execution logic stages

```
1  async def wel_on_worker_ready(planner, storage, dag, this_worker)
2
3  async def wel_before_task_handling(planner, storage, dag, this_worker,
    current_task)
4
5  async def wel_override_handle_inputs(
6      planner, storage, dag, this_worker, current_task,
        upstream_tasks_without_cached_results, worker_resource_config,
        task_dependencies: dict
7  ) -> tuple[list, list[str], CoroutineType | None] | None
8
9  async def wel_before_task_execution(planner, storage, dag, this_worker,
    current_task)
10
11  async def wel_override_should_upload_output(
12      planner, storage, dag, this_worker, current_task
13  ) -> bool | None
14
15  async def wel_update_dependency_counters(
16      planner, storage, dag, this_worker, current_task
17  ) -> list | None
18
19  async def wel_override_handle_downstream(
20      planner, storage, dag, this_worker, current_task, downstream_tasks_ready
21  ) -> list | None
```

After a plan is created and validated, the workflow representation is serialized using *cloudpickle* (as mentioned before) and uploaded to storage. The plan is embedded directly within this representation, allowing each worker to identify both the tasks it is responsible for executing and the ones it must delegate to other workers. Now, we will explain the process of submitting the workflow and initiating its execution.

3.5 Client

In this section we will cover the role of the client application, which is where the workflow tasks are created and composed, as well as where the workflow execution is parametrized and initiated.

The `.compute(configuration)` method, which can be called on any `DAGTaskNode` reference, receives the configuration object, which contains information on how to connect to both *Intermediate Storage* and *Metadata Storage*, as well as the planner to be used, along with its configuration. The planner configuration includes the **SLA**, which will be used for the predictions made by the Predictions API

(described in Section 3.3), the **resource configurations** that the planner is allowed to assign workers, and the list of **optimizations** that the planner should try to apply. Before the client calls `compute()`, it can first generate a visualization of the DAG structure. This capability allows users to inspect and verify the workflow's dependencies and overall structure in advance, before submitting it for execution.

When the client calls `compute()`, there are a couple of steps before the initial serverless workers are invoked. First, since `compute` is called on the sink node of the workflow, we discover the entire workflow by backtracking until we find the root nodes. Then, some basic validation happens to check if there are no other nodes without downstream nodes, ensuring there's only one sink node. At this stage, a few optimizations are made in order to reduce the size of the workflow representation. This is important because if the workflow representation is below a threshold we can send it in the invocation to FaaS workers without having to rely on storage, saving on both performance and storage costs.

One of these optimizations involves special handling of large hardcoded inputs. When a task receives a large input that is already known before workflow execution begins, this input would normally be embedded directly within the `DAGTaskNode` representation. However, because workers exchange this representation among themselves, embedding large inputs would lead to unnecessary data transfers and inefficiency. To address this, we detect all large hardcoded input objects and replace them with unique references. During execution, workers can use these references to retrieve the corresponding inputs from storage only when needed. The client is responsible for uploading these large input objects to *Intermediate Storage* prior to workflow execution.

Before uploading hardcoded data, the client first loads all relevant metrics required for workflow prediction and then invokes the selected planner algorithm. This process updates the workflow representation with worker assignment information and optimization details. As mentioned earlier, predictions are based on samples collected from the same type of workflow and planner to improve their accuracy. To determine which samples correspond to which workflow, we differentiate workflows by appending a *hash* of their graph composition, defined by the task names and their dependency relationships, to the workflow's unique identifier. Workflow identifiers sharing the same hash are thus considered to represent the same workflow type. After a plan is created, an image of the predicted metrics, worker assignments and optimizations is generated and stored on the client machine, which can help the user to better understand the plan created by the planner.

After a plan is created and embedded in the DAG representation, the client invokes the workers assigned to the root nodes. It provides each worker with the corresponding task identifiers, enabling them to begin executing their respective branches of the workflow. Afterward, the client uses Pub/Sub to subscribe to the `TASK_COMPLETED` event associated with the workflow's final task. Once this event is received, the client retrieves the result from *Intermediate Storage* and returns it to the user. From the user's perspective, invoking `compute()` behaves like calling a regular function, returning the expected

result, while the actual execution is transparently handled by serverless workers.

During workflow execution, the client can monitor the workflow's progress through a simple web dashboard implemented with Streamlit ⁴. The dashboard visualizes the workflow graph, indicating which tasks have been completed and which remain pending. In the following section, we describe in detail how workers operate, including how they follow the plan, handle task dependencies, and coordinate through event-based communication to achieve decentralized workflow execution.

3.6 Decentralized Workers

Since our target execution platform is FaaS, each worker is implemented as a FaaS handler. Owing to the decentralized design, workers are responsible not only for executing tasks but also for coordinating scheduling decisions in a choreographed manner. Upon invocation by the FaaS gateway, a worker receives a **configuration** containing connection details for storage and the gateway, along with SLA parameters and related metadata. It also receives a list of **immediate task identifiers** that define the workflow branches it should manage (executing its own tasks and delegating the rest to other workers) as well as the corresponding **upstream outputs**, which may be complete or partial depending on whether the worker that spawned this worker already had this data available locally or not. Finally, the invocation includes either the **workflow representation** itself or a **workflow instance identifier** used to fetch it from *Metadata Storage* if it exceeds a size threshold (300KB in our setup).

In this initial stage, the worker calls the `we1_on_worker_ready` method on all optimizations. Then, it subscribes to `TASK_READY` events for all tasks assigned to it that depend on tasks assigned to other workers. To begin executing tasks, the worker launches a Python *asyncio* ⁵ *coroutine* for each branch, starting from the provided **immediate task identifiers**. From this point, the main *coroutine* simply waits for all assigned tasks to complete, and then runs the cleanup logic, which deletes intermediate data from storage, flushes metrics and metadata to *Metadata Storage*, and closes storage connections.

Each branch of task handling runs concurrently in its own *coroutine*, and follows these sequential phases when running without optimizations:

1. **Gathering Dependencies:** Check which dependencies are missing (not downloaded yet) and download them from storage. Some dependencies might be present in the local representation of the DAG if `task-dup` or `pre-load` were applied, if the same worker executed some of the upstream tasks, or if the worker already downloaded large hardcoded data (explained previously in Section 3.5) because previous tasks needed it;
2. **Executing Task:** After gathering all task dependencies (upstream task outputs and hardcoded

⁴<https://streamlit.io/>

⁵<https://docs.python.org/3/library/asyncio.html>

data), it executes the task's code. Its function code is embedded within the workflow representation so it can be easily executed by the workers, similarly to WUKONG. This enables the worker to remain generic, capable of receiving and executing arbitrary task code (excluding async functions, since *cloudpickle* can't serialize them). Tasks' code execute on a separate thread, to avoid slowing down or even blocking (e.g., if the task code calls `time.sleep()`) the main thread, where the other coroutines are running: both task branch execution and other internal coroutines (i.e., Redis pub/sub listener, and delayed pre-warm requests);

3. **Handling Output:** This phase is responsible for evaluating whether it's necessary to upload the task's output to storage and emitting a `TASK_COMPLETED` event. A tasks' output is uploaded if there is at least one downstream task assigned to a different worker, or if it's the sink/last task of the workflow;
4. **Updating Dependency Counters:** For each downstream task, the worker performs an *atomic increment and get* operation on a "*Dependency Counter*" (inspired by WUKONG [20]) stored in *Metadata Storage*, which tracks how many dependencies of a task have been satisfied. If the counter sees that the value returned is the same as the number of dependencies for a downstream task, the worker emits a `TASK_READY` event for that task, signaling other workers or workers that aren't active yet that the task became ready to execute;
5. **Delegating Downstream Tasks:** After updating dependency counters, the worker knows which tasks became *ready*. The worker then consults the execution plan to determine how to proceed for each of those tasks: for tasks assigned to the same worker and has no remaining unfulfilled dependencies, the worker will execute it (one *coroutine* for each task); for tasks assigned to another worker **that is already active**, a `TASK_READY` event is emitted; for tasks assigned to another worker **that is not active**, this worker launches the target worker, indicating the branches (*immediate task identifiers*) it should execute. Because of the planner validation mentioned in Section 3.4.2, it is possible for a worker to know, at any point in time, whether another worker is already active or not just by looking at the workflow representation and respective plan.

For exchanging events among workers, we use Redis's Pub/Sub ⁶. Both *Intermediate Storage* and *Metadata Storage* are also implemented in Redis for deployment simplicity. These events are `TASK_READY` and `TASK_COMPLETED`, and are implemented as Pub/Sub channels, where the channel name is a composition of "notification-task-ready-" and the unique Task ID. Since the same worker can subscribe to the same event multiple times, we assign unique subscription identifiers that are local to each worker. This allows the worker to unsubscribe from individual event subscriptions safely, without inadvertently removing other listeners that might depend on the same event.

⁶<https://redis.io/glossary/pub-sub/>

We will now go over a practical example of how we use these events are used to coordinate decentralized scheduling. Figure 3.4 presents an example of a workflow with four workers (A, B, C, and D) and eight tasks (T1-T8).

In this example, tasks complete in the following order: T1, T2, T3, T4, T5, T6, T7, and T8. The text in the arrows represent the order of actions performed by the worker who executed the task from which the arrow starts, where each action is separated by a semicolon. When T1 finishes, its worker will increment the dependency counter of T5 because it knows, by looking at the workflow representation, that T5 depends on other tasks from another worker. This storage operation returns "1", but T5 has 2 dependencies (T1 and T2) and as such, it isn't READY to execute. Then T1's worker sees T4 and since it's assigned to it, and it doesn't have any other dependencies, it schedules it for execution locally. Lastly T1 will see that T3 doesn't depend on any other tasks, meaning it is also ready for execution and, since it is assigned to another worker (Worker C), it sends a request to the FaaS gateway to launch Worker C, providing the branches it should execute.

Then, when T3 finishes execution, its worker will see that T7 depends on external tasks, so it updates the dependency counter of T7 and remains idle waiting for the TASK_READY event for T7. Later, T4 finishes, realizes that T7 is meant to execute on another worker, increments its dependency counter, realizes all dependencies are met, and emits a TASK_READY event for T7, to which Worker C will react to by start executing T7. Once T5 finishes execution, it realizes that T6 depends on external tasks, increments its dependency counter, realizes all dependencies are met, and since it's assigned to itself, it schedules it for execution locally.

Finally, T6 finishes, increments the dependency counter of T8 (because it has other dependencies), but since it's still missing 1 dependency, it exits. Later, then T7 finishes, it increments the dependency counter of T8 and realizes all dependencies are met and that the worker assigned to T8 (Worker D) isn't active yet, so it makes a request to the FaaS gateway to invoke this worker. Once T8 finishes, it emits a TASK_COMPLETED event which is received by the client, who then downloads the result from *Intermediate Storage*.




Figure 3.4: Choreographed Scheduling Example

By delegating downstream tasks to workers, our approach eliminates the need for a central scheduler, a common component in many existing FaaS-based workflow engines. This decentralization increases flexibility and scalability, as workers can dynamically invoke additional workers as needed, following a choreographed decentralized execution model.

A workflow is considered complete once the output of the final (sink) task is available in storage. The worker that uploads this final result is also responsible for cleaning up all intermediate results before shutting down. This worker emits a `TASK_COMPLETED` event for the sink task, triggering the client to retrieve the final result from *Intermediate Storage*.

Having described the design and implementation of the system, we now turn to its evaluation. The next section presents the experimental setup, results, and analysis used to assess the strengths and weaknesses of our approach.

4

Evaluation

Contents

4.1	Emulating FaaS environment	45
4.2	Research Questions	46
4.3	Experimental Setup	46
4.4	Results	46
4.4.1	Predictions Accuracy	46
4.4.2	SLA Fulfillment	46
4.4.3	Planners	46
4.4.4	Optimizations	46
4.4.5	Resource Usage	47
4.5	Discussion	47

4.1 Emulating FaaS environment

TODO: mention docker containers and the gateway (http server), its capabilities (prewarm), warm time, max concurrent containers. internal container handling

4.2 Research Questions

TODO: What do we want to prove/show/evaluate

TODO: what metrics allow that

4.3 Experimental Setup

TODO: VM, cpus, memory, docker and python installed

TODO: client, docker faas gateway, and databases running on it

TODO: storage interactions have an artificial delay increment of 20ms, considering 10ms each direction (<https://www.cloudping.co/> shows around 30 ms RTT across different regions and under 10ms RTT across same region)

TODO: what types of metrics were collected

4.4 Results

4.4.1 Predictions Accuracy

TODO:

4.4.2 SLA Fulfillment

TODO:

4.4.3 Planners

TODO:

4.4.4 Optimizations

TODO:

4.4.5 Resource Usage

TODO:

4.5 Discussion

TODO: summary of results analysis

TODO: wukong comparison

5

Conclusion

Contents

5.1	Conclusions	49
5.2	System Limitations and Future Work	49

5.1 Conclusions

5.2 System Limitations and Future Work

Bibliography

- [1] Aws lambda. [Online]. Available: <https://aws.amazon.com/pt/lambda/>
- [2] Azure functions. [Online]. Available: <https://azure.microsoft.com/en-us/products/functions>
- [3] Google cloud run functions. [Online]. Available: <https://cloud.google.com/functions>
- [4] R. Graves, T. H. Jordan, S. Callaghan, E. Deelman, E. Field, G. Juve, C. Kesselman, P. Maechling, G. Mehta, K. Milner, D. Okaya, P. Small, and K. Vahi, "Cybershake: A physics-based seismic hazard model for southern california," *Pure and Applied Geophysics*, vol. 168, no. 3, pp. 367–381, 2011. [Online]. Available: <https://doi.org/10.1007/s00024-010-0161-6>
- [5] J. C. Jacob, D. S. Katz, G. B. Berriman, J. C. Good, A. Laity, E. Deelman, C. Kesselman, G. Singh, M.-H. Su, T. Prince, and R. Williams, "Montage: A grid portal and software toolkit for science-grade astronomical image mosaicking," *International Journal of Computational Science and Engineering*, vol. 4, no. 2, pp. 73–87, 2009. [Online]. Available: <https://doi.org/10.1504/IJCSE.2009.026999>
- [6] M. Golec, G. K. Walia, M. Kumar, F. Cuadrado, S. S. Gill, and S. Uhlig, "Cold start latency in serverless computing: A systematic review, taxonomy, and future directions," *ACM Computing Surveys*, vol. 57, no. 3, pp. 1–36, 2024.
- [7] J. M. Hellerstein, J. Faleiro, J. E. Gonzalez, J. Schleier-Smith, V. Sreekanti, A. Tumanov, and C. Wu, "Serverless computing: One step forward, two steps back," *arXiv preprint arXiv:1812.03651*, 2018.
- [8] Aws step functions. [Online]. Available: <https://aws.amazon.com/en/step-functions/>
- [9] Azure durable functions. [Online]. Available: <https://learn.microsoft.com/en-us/azure/azure-functions/durable/durable-functions-overview>
- [10] Google cloud workflows. [Online]. Available: <https://cloud.google.com/workflows>
- [11] F. Romero, G. I. Chaudhry, I. n. Goiri, P. Gopa, P. Batum, N. J. Yadwadkar, R. Fonseca, C. Kozyrakis, and R. Bianchini, "FaaS\$: A transparent auto-scaling cache for serverless applications," in *Proceedings of the ACM Symposium on Cloud Computing*, ser. SoCC '21. New

- York, NY, USA: Association for Computing Machinery, 2021, p. 122–137. [Online]. Available: <https://doi.org/10.1145/3472883.3486974>
- [12] M. Abdi, S. Ginzburg, C. Lin, J. M. Faleiro, I. Goiri, G. I. Chaudhry, R. Bianchini, D. S. Berger, and R. Fonseca, “Palette load balancing: Locality hints for serverless functions,” in *EuroSys*. ACM, May 2023. [Online]. Available: <https://www.microsoft.com/en-us/research/publication/palette-load-balancing-locality-hints-for-serverless-functions/>
- [13] Y. Tang and J. Yang, “Lambdata: Optimizing serverless computing by making data intents explicit,” in *2020 IEEE 13th International Conference on Cloud Computing (CLOUD)*. IEEE, 2020, pp. 294–303.
- [14] Apache openwhisk. [Online]. Available: <https://openwhisk.apache.org/>
- [15] D. Moyer and D. S. Nikolopoulos, “Punching holes in the cloud: Direct communication between serverless functions,” in *Serverless Computing: Principles and Paradigms*. Springer, 2023, pp. 15–41.
- [16] M. Yu, T. Cao, W. Wang, and R. Chen, “Pheromone: Restructuring serverless computing with data-centric function orchestration,” *IEEE Transactions on Networking*, vol. 33, no. 1, pp. 226–240, 2025.
- [17] P. G. López, A. Arjona, J. Sampé, A. Slominski, and L. Villard, “Triggerflow: trigger-based orchestration of serverless workflows,” in *Proceedings of the 14th ACM International Conference on Distributed and Event-Based Systems*, ser. DEBS ’20. New York, NY, USA: Association for Computing Machinery, 2020, pp. 3–14. [Online]. Available: <https://doi.org/10.1145/3401025.3401731>
- [18] C. P. Smith, A. Jindal, M. Chadha, M. Gerndt, and S. Benedict, “Fado: Faas functions and data orchestrator for multiple serverless edge-cloud clusters,” in *2022 IEEE 6th International Conference on Fog and Edge Computing (ICFEC)*, 2022, pp. 17–25.
- [19] M. Copik, R. Böhringer, A. Calotoiu, and T. Hoefler, “Fmi: Fast and cheap message passing for serverless functions,” in *Proceedings of the 37th ACM International Conference on Supercomputing*, ser. ICS ’23. New York, NY, USA: Association for Computing Machinery, 2023, p. 373–385. [Online]. Available: <https://doi.org/10.1145/3577193.3593718>
- [20] B. Carver, J. Zhang, A. Wang, A. Anwar, P. Wu, and Y. Cheng, “Wukong: A scalable and locality-enhanced framework for serverless parallel computing,” in *Proceedings of the 11th ACM symposium on cloud computing*, 2020, pp. 1–15.

- [21] D. H. Liu, A. Levy, S. Noghabi, and S. Burckhardt, "Doing more with less: Orchestrating serverless applications without an orchestrator," in *20th USENIX Symposium on Networked Systems Design and Implementation (NSDI 23)*, 2023, pp. 1505–1519.
- [22] Q. Jiang, Y. C. Lee, and A. Y. Zomaya, "Serverless execution of scientific workflows," in *International Conference on Service-Oriented Computing*. Springer, 2017, pp. 706–721.
- [23] Cloudflare workers. [Online]. Available: <https://workers.cloudflare.com/>
- [24] Openfaas. [Online]. Available: <https://www.openfaas.com/>
- [25] Knative. [Online]. Available: <https://knative.dev/docs/>
- [26] S. Fouladi, R. S. Wahby, B. Shacklett, K. V. Balasubramaniam, W. Zeng, R. Bhalerao, A. Sivaraman, G. Porter, and K. Winstein, "Encoding, fast and slow:{Low-Latency} video processing using thousands of tiny threads," in *14th USENIX Symposium on Networked Systems Design and Implementation (NSDI 17)*, 2017, pp. 363–376.
- [27] Y. Li, Y. Lin, Y. Wang, K. Ye, and C. Xu, "Serverless computing: State-of-the-art, challenges and opportunities," *IEEE Transactions on Services Computing*, vol. 16, no. 2, pp. 1522–1539, 2023.
- [28] A. Casalboni, "AWS Lambda Power Tuning," <https://github.com/alexcasalboni/aws-lambda-power-tuning>, 2024.
- [29] A. Klimovic, Y. Wang, P. Stuedi, A. Trivedi, J. Pfefferle, and C. Kozyrakis, "Pocket: Elastic ephemeral storage for serverless analytics," in *13th USENIX Symposium on Operating Systems Design and Implementation (OSDI 18)*. Carlsbad, CA: USENIX Association, Oct. 2018, pp. 427–444. [Online]. Available: <https://www.usenix.org/conference/osdi18/presentation/klimovic>
- [30] Apache airflow. [Online]. Available: <https://airflow.apache.org/>
- [31] Dask - python parallel computing framework. [Online]. Available: <https://www.dask.org/>
- [32] Dagman. [Online]. Available: <https://htcondor.readthedocs.io/en/latest/automated-workflows/dagman-introduction.html>
- [33] Htcondor. [Online]. Available: <https://htcondor.org/>
- [34] W. M. Van Der Aalst and A. H. Ter Hofstede, "Yawl: yet another workflow language," *Information systems*, vol. 30, no. 4, pp. 245–275, 2005.
- [35] Petri nets. [Online]. Available: https://en.wikipedia.org/wiki/Petri_net
- [36] Apache spark. [Online]. Available: <https://spark.apache.org/>

- [37] Apache flink. [Online]. Available: <https://flink.apache.org/>
- [38] Apache hadoop. [Online]. Available: <https://hadoop.apache.org/>
- [39] Apache oozie. [Online]. Available: <https://oozie.apache.org/>
- [40] J. Dean and S. Ghemawat, “Mapreduce: simplified data processing on large clusters,” vol. 51, no. 1. New York, NY, USA: Association for Computing Machinery, Jan. 2008, pp. 107–113. [Online]. Available: <https://doi.org/10.1145/1327452.1327492>
- [41] Hadoop yarn. [Online]. Available: <https://hadoop.apache.org/docs/current/hadoop-yarn/hadoop-yarn-site/YARN.html>
- [42] Dask distributed. [Online]. Available: <https://distributed.dask.org/en/stable/>
- [43] Prefect. [Online]. Available: <https://www.prefect.io/>
- [44] Dagster. [Online]. Available: <https://dagster.io/>
- [45] Argo workflows. [Online]. Available: <https://argoproj.github.io/workflows/>
- [46] Kubernetes. [Online]. Available: <https://kubernetes.io/>
- [47] Google dataflow. [Online]. Available: <https://cloud.google.com/products/dataflow?hl=en>
- [48] Cloudflare workflows. [Online]. Available: <https://www.cloudflare.com/developer-platform/products/workflows/>
- [49] L. Lamport, “Paxos made simple,” *ACM SIGACT News (Distributed Computing Column)* 32, 4 (Whole Number 121, December 2001), pp. 51–58, 2001.
- [50] D. Ongaro and J. Ousterhout, “In search of an understandable consensus algorithm,” in *Proceedings of the 2014 USENIX Conference on USENIX Annual Technical Conference*, ser. USENIX ATC’14. USA: USENIX Association, 2014, p. 305–320.
- [51] P. Hunt, M. Konar, F. P. Junqueira, and B. Reed, “{ZooKeeper}: Wait-free coordination for internet-scale systems,” in *2010 USENIX Annual Technical Conference (USENIX ATC 10)*, 2010.
- [52] E. Jonas, Q. Pu, S. Venkataraman, I. Stoica, and B. Recht, “Occupy the cloud: Distributed computing for the 99%,” in *Proceedings of the 2017 symposium on cloud computing*, 2017, pp. 445–451.



Code of Project

B

A Large Table