







Cisco Packet Tracer

File Edit Options View Tools Extensions Window Help

Logical Physical x: 100 y: 100

1041 R0

2000 S0

PC-PT PC0

PC-PT PC1

IOS Command Line Interface

```
Router(config-if)#  
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up  
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up  
Router(config-if)#exit  
Router(config)#interface list 1 psmm 192.168.0.0 0.0.0.0 255  
Router(config)#ip nat pool white-address 100.10.11.77 100.10.11.99 netmask 255.255.255.0  
Router(config)#ip nat inside source list 1 pool white-address  
Router(config)#  
% Invalid input detected at '^' marker.  
Router(config)#ip nat inside source list 1 pool white-address  
Router(config)#ip nat fa0/0  
Router(config)#ip nat inside  
Router(config)#ip nat fa0/1  
Router(config)#ip nat outside  
Router(config)#ip nat fa0/1  
Router(config)#end  
Router#  
RTSP-6-CONFIG_1: Configured from console by console  
Router#  
Router#show ip  
Router#show ip nat  
Router#show ip nat ss  
Router#show ip nat translations  
Pro Inside Global Inside Local Outside Local Outside Global  
icmp 100.10.11.79:2 192.168.0.2:2 100.10.10.2:2 100.10.10.2:2  
icmp 100.10.11.79:3 192.168.0.2:3 100.10.10.2:3 100.10.10.2:3  
icmp 100.10.11.79:4 192.168.0.2:4 100.10.10.2:4 100.10.10.2:4  
icmp 100.10.11.79:5 192.168.0.2:5 100.10.10.2:5 100.10.10.2:5  
icmp 100.10.11.79:6 192.168.0.2:6 100.10.10.2:6 100.10.10.2:6  
icmp 100.10.11.79:7 192.168.0.2:7 100.10.10.2:7 100.10.10.2:7  
icmp 100.10.11.79:8 192.168.0.2:8 100.10.10.2:8 100.10.10.2:8  
Router#
```

Copy Paste

Time: 00:14:16

Scenario 0

New Delete

Toggle PCU List Window

Activación Windows

Para activar Windows, vaya a la sección "Parámetros".

18:16 08.04.2025