MCP PRODUCTION · SPEC REVISION 2026-07-28

Replica-dependent request diagnosis

The worksheet from lesson 1.1 of MCP Production: what to record for each attempt, and what each record does and doesn't establish, before you touch the load balancer.

Use synthetic, read-only inputs before testing an ambiguous write.

EVIDENCE	RECORD	WHAT IT ESTABLISHES
Request ID	A distinct ID for each attempt	Response correlation
Intended operation	Method, addressed tool, arguments	Input held constant
Destination	Observed replica label	Actual routing, not intended routing
Response	Status, envelope, result category	Observable outcome
Configuration	Application artifact and data connection	Candidate replica differences
Fresh process	Result before client-specific setup	Dependence on prior process history

- [ ] Verify that both destinations were exercised.
- [ ] Compare direct calls with calls through the entry point.
- [ ] Separate missing object context from inaccessible application storage.
- [ ] Treat an object reference separately from permission to use it.
- [ ] State exactly which tools and failure conditions the test covered.

An identity-tool test is not evidence of durable writes or workflow recovery.

> **Where this goes next.** Lessons 1.4 to 1.6 build the same contract in TypeScript and Python and send calls through alternating replicas until both give the same answer, in lab 1. The course: runsclean.com/courses/mcp-production/