

A Universal Robotic Control System using Reinforcement Learning with Limited Feedback

Abstract

Our abstract.

1 Introduction

Introduction here.

2 Neural Network Background

The human brain is composed of billions of neurons, interconnected electrically excitable cells that form the basis of our intelligence. Each neuron has synapses that receive electrical signals from multiple other neurons. If the sum of these inputs is greater than a certain value, the neuron fires, generating a voltage down its axon. The axon, or the output of the neuron cell, is itself connected to a synapse of another neuron. The interconnections of these neurons form a massive network, where a huge number of inputs are processed in parallel to a set of outputs. The basis of artificial neural networks is to simulate the mathematical properties of these neurons in order to perform similar tasks of mass parallel computation.

2.1 Single Artificial Neuron



Figure 1: Single Neuron Diagram

An artificial neuron is simply a mathematical model of a biological neuron, and therefore its functionality is very similar. Each artificial neuron has multiple inputs, each one the output of a different neuron. In addition, each neuron has a weight for each input, a bias term, an activation function, and one output. The output of one neuron becomes the input of another, connected neurons. The output of a neuron is expressed mathematically for n inputs x and weights w , a bias term b , and activation function $O(x)$:

$$\text{activation} = \sum_{i=0}^{i=n} x_i w_i + b$$

$$\text{output} = O(\text{activation}).$$

A weight is a positive or negative number that governs the impact of its respective input on the neuron's single output. The bias term is a number that is added to the summation of weights and inputs. The bias term allows us to make affine transformations on the domain of the activation function.

In biologically inspired neurons, the activation function is a binary step function. If the activation function's input is less than a certain threshold, the output is zero. If it is greater than the threshold, the output is one. However, a binary output can be somewhat limiting for many applications of neural networks. For example, many of Fido's outputs are gradient rather than binary; as an example, Fido will have to set the brightness of an LED. Because of this, alternate activation functions giving gradient outputs are used. One such function is the sigmoid function, expressed as such:

$$O(a) = \frac{1}{1 + e^{-\frac{a}{p}}}, \quad (1)$$

for each output O , activation a , and constant p . The sigmoid activation function can also be graphed as below.




Figure 2: Sigmoid Function Graph

The sigmoid function provides us with a gradient output. However, output is still limited to positive values. An alternative activation function which allows outputs ranging from -1 to +1 is the hyperbolic tangent activation function.



Figure 3: Hyperbolic Tangent Function Graph

2.2 Feedforward Neural Network

A traditional method of arranging artificial neurons in a neural network is called a feedforward network. Neurons are connected as previously described: the output of each neuron is connected to one of the inputs of another neuron. These neurons are organized into layers, as described in the following figure:



Figure 4: Single Output Feedforward Network

The output of each neuron in a layer becomes an input of every neuron in the next layer. In this way, the original inputs of the neural network are “fed forward” layer by layer, starting from the first layer (the input layer), passing through any number of hidden layers, ending with the last layer (the output layer). The outputs of the neurons of the output layer are the outputs of the whole network.

A concrete example of a feedforward network is that of Fido. Sensor inputs such as light and sound are sent into the input layer. The outputs of the output layer’s neurons are used to change the speed of Fido’s motors, the color of Fido’s LEDs, and the sounds of Fido’s buzzers.

3 Learning Implementation

4 Simulation

The robot model chosen for simulation was modeled after easily producible robots on the same scale. The software driving the simulation was intended to be portable enough to work on a hardware implementation, and the model facilitates this goal as well. Additionally, the robot model would have to be easily trainable and debuggable when implemented in hardware; use of a Geiger counter as an input would be unfavorable. Lastly the sensors and design chosen had to facilitate the concept of natural learning, modeling after nature to some degree.

4.1 Robot Inputs and Outputs

Multiple inputs were modeled for simulation with outlets for control both by a human operator using sliders and by programmed handlers using a bridge class. A microphone and light sensor were chosen as clear, human modifiable inputs that model after nature and could easily be used for reinforcement training. An infrared light sensor was added as another easily controller variable in a testing setup: a human operator could easily bring closer and farther an IR LED for purposes of training. Additionally sensors for battery level, three axes of accelerometers, and three axes of




Figure 5: Screenshot of Fido Simulator GUI

gyroscopes were added as more complex inputs for Fido to master. The last sensor added was a three axis radio receiver. The purpose of the receiver was to allow location based training of the robot relative to a radio beacon, such as following the beacon or avoiding it. The radio sensor is a stand-in for Bluetooth, Wi-Fi, or any other radio technology; it is common practice in many areas of robotics to use radio beacons for localization.

Fido's outputs were chosen similarly. Two motors allow a drive mechanism known as differential drive, which will be discussed further in the following section. A buzzer of varying tone and frequency and a multicolor LED complete the set of outputs.

4.2 Implementation and Kinematics

A graphical user interface was made using the SFML multimedia library for C++. Sliders manually adjust inputs such as accelerometer and gyroscope axes, battery life, and temperature. A colored circle displays the output of the multicolor LED, while the frequency and volume of the piezoelectric

speaker are displayed on the bottom bar. Initially vectors of motor values were displayed graphically in the top right of the window. This made sense for initial testing purposes: both competition entrants are experienced with differential drive robots, and can easily visualize robot movement from robot vectors. However, as we decided to do more development on the simulator we wanted to allow more complex training on the simulator, such as path following. Such training requires a visual kinematic simulation of the robot model.




Figure 6: Differential Drive Kinematics Diagram

Fido's two motors are arranged in a differential drive arrangement. Driving the left motor acts as a force vector on the left side of the robot, creating a torque around the right wheel. The same applies with the right wheel. When both motors are activated together, the motor drives straight. Each motor has a value ranging from -100 to 100, where -100 is full power backwards, 0 is stopped, and 100 is full power forwards. In order to transform motor values into a plottable transformation, we must first model the movement that our robot will take.

Every movement the robot takes can be interpreted as a rotation of radius R around the ICC, or Instantaneous Center of Curvature. If the robot is moving straight, this radius is simply infinite. The robot travels at an angular velocity ω around the circle, and at any given moment is at the coordinates (x, y) and orientation θ . The length of the robot from wheel-center to wheel-center is defined as l , while the velocity vectors of each motor are defined as V_l and V_r respectively. The passing of time from the last call of motor values is defined as Δt . We can solve for R at any point using the following equation:

$$R = \frac{l}{2} \times \frac{V_l + V_r}{V_r - V_l}. \quad (2)$$

We can solve for ω using the following equation:

$$\omega = \frac{V_r - V_l}{l} \quad (3)$$

And the ICC location using the following equation:

$$ICC = \begin{bmatrix} x - R \sin \theta, & y + R \cos \theta \end{bmatrix} \quad (4)$$

We can then use these values to solve for the robot's new position, defined as coordinates (x', y') and orientation θ' .

$$\begin{bmatrix} x' \\ y' \\ \theta' \end{bmatrix} = \begin{bmatrix} \cos(\omega \Delta t) & -\sin(\omega \Delta t) & 0 \\ \sin(\omega \Delta t) & \cos(\omega \Delta t) & 0 \\ 0 & & 1 \end{bmatrix} \begin{bmatrix} x - ICC_x \\ y - ICC_y \\ \theta \end{bmatrix} + \begin{bmatrix} ICC_x \\ ICC_y \\ \omega \Delta t \end{bmatrix} \quad (5)$$

A brief inspection of these equations verify their performance in certain use cases. If $V_r = -V_l$ R becomes zero, as the robot turns around it's center. If $V_r = V_l$ R becomes infinite, as the robot is traveling in a straight line. However the methodology by which the equation simplifies in the case of $V_r = V_l$ involves division of zero, which can be problematic in computer programming. Therefore we must first check if $V_r = V_l$, and if so substitute an alternate equation as a simplification:

$$\begin{bmatrix} x' \\ y' \\ \theta' \end{bmatrix} = \begin{bmatrix} x + V_l \Delta t \cos \Theta \\ y + V_l \Delta t \sin \Theta \\ \theta \end{bmatrix} \quad (6)$$

The use of V_l in this equation rather than V_r is unimportant, as the values are equal. Using these equations were able to fully simulate Fido's kinematic model, and attach simulator motor inputs to Fido's outputs to visualize learning taking place. The black rectangle in the upper

right corner of the simulator is the robot, having been moved as part of training. The red dot near the rectangle is a graphical representation of a radio beacon. As adjusting sliders to represent the location of a radio beacon relative to the robot would be impractical, we decided to implement a beacon that could be placed and dragged by right clicking on the simulator. Simulated sensor readings of beacon strength on two axis are gathered using an inverse square law, as applies to radio waves in general. These readings are then displayed in the sliders and can be manually altered as well. The radio beacon can be removed by a human operator by pressing the P key. This has been especially helpful in the task of training Fido to follow a radio beacon.

5 Results

Results, testing, and applications go here.

5.1 Training Methods

5.2 Findings

5.3 Further Applications

6 Discussion

7 Conclusion

Restate, discuss further study, improving experimentation, etc.

References

- Dini, S., & Serrano, M. (2012). Combining q-learning with artificial neural networks in an adaptive light seeking robot.
- Dudek, G., & Jenkin, M. (2000). *Computational principles of mobile robotics*. New York, NY, USA: Cambridge University Press.
- Gaskett, C., Wettergreen, D., & Zelinsky, A. (1999). Q-learning in continuous state and action spaces. In *Australian joint conference on artificial intelligence* (pp. 417–428).
- Kim, D. S., & Papagelis, A. J. (n.d.). *Multi-layer perceptron: Artificial neural networks*. <http://www.cse.unsw.edu.au/cs9417ml/MLP2/>.
- MacLeod, C. (2010). *An introduction to practical neural networks and genetic algorithms for engineers and scientists* (Tech. Rep.). Robert Gordon University.
- Watkins, C. J. C. H. (1989). *Learning from delayed rewards* (Unpublished doctoral dissertation). University of Cambridge England.
- Werbos, P. (1974). Beyond regression: New tools for prediction and analysis in the behavioral sciences.