Do While loop

Python code	Output

Python code:

```
13 do while loop.py > ...
secret_word="python"
counter=0
while True:
    word=input("Enter the secret word: ")
    counter=counter+1
    if word==secret_word:
        print("correct word")
        break
    if word==secret_word  or counter>7:
        print("too many attempts")
        break
```

Output:

```
(base) PS D:\ML\assignments> &
Enter the secret word: k
Enter the secret word: k
Enter the secret word: k
Enter the secret word: k
Enter the secret word: k
Enter the secret word: k
Enter the secret word: k
Enter the secret word: k
too many attempts
(base) PS D:\ML\assignments> &
Enter the secret word: k
Enter the secret word: k
Enter the secret word: python
correct word
(base) PS D:\ML\assignments>
```

Types of function arguments

1. Default argument

Python code	output

Python code:

```
def newfunc(y,x=60,z=20):
    print("x: ",x)
    print("y: ",y)
    print("z: ",z)
newfunc(30)
```

output:

```
(base) PS D:\ML\
x:  60
y:  30
z:  20
```

2. Keyword Argument

Python code	Output

Python code:

```
#keyword argument
def sir(fname,lname):
    print(fname,lname)
sir(fname="Sachin",lname="Yadav")
sir(lname="Yadav",fname="Sachin")
```

Output:

```
Sachin Yadav
Sachin Yadav
(base) PS D:\ML\assign
```

3. Positional Arguments

Python code	output

`#Positional Arguments`
`def nameAge(name,age):`
`    print("hi, i am ",name)`
`    print("my age is ",age)`
`print("Case-1")`
`nameAge("Abhay",21)`
`print("Case-2")`
`nameAge(21,"Abhay")`
	`Case-1`
	`hi, i am  Abhay`
	`my age is  21`
	`Case-2`
	`hi, i am  21`
	`my age is  Abhay`
	`(base) PS D:\ML\assignments>`

4. Arbitrary Arguments

Python code	output

`#Arbitrary Arguments`
`def afunc(*args,**kargs):`
`    print("non-keywords Arguments (*args):")`
`    for arg in args:`
`        print(arg)`
`    print("\n Keyword argumnets (**kargs):")`
`    for key,value in kargs.items():`
`        print(f"{key}:{value}")`
`afunc('Hello','Abhay',first="Sachin", mid="yadav", last="sir CU")`
	`(base) PS D:\ML\assignments> & "`
	`non-keywords Arguments (*args):`
	`Hello`
	`Abhay`
	
	` Keyword argumnets (**kargs):`
	`first:Sachin`
	`mid:yadav`
	`last:sir CU`
	`(base) PS D:\ML\assignments>`