Synthetic Respondents Without Ambivalence?

A Population-Fidelity Audit of Qwen3.5-9B and Machine-Learning Reconstructions of Gender Attitudes in China

Song Ge

Wuhan University

October 29, 2026

Abstract

Large language models are increasingly used to simulate survey respondents, yet matching a plausible individual answer is not equivalent to recovering a population. This paper evaluates whether a locally deployed Qwen3.5-9B model can reproduce the marginal distributions, heterogeneity, and item structure of five gender-attitude questions in the Chinese General Social Survey (CGSS) 2012, 2018, and 2021. The design pairs 300 real respondent profiles with repeated zero-shot responses and compares them with matched human answers, the full weighted survey benchmark, and survey-trained machine-learning models using the same prediction-time attributes. Qwen3.5-9B produces large item-specific mean errors. Its mean marginal variance ratio is 0.794, but 68.2% of predictive variance comes from repeated draws within the same profile; the between-profile ratio is only 0.265. A joint five-item prompt also strengthens the housework item's association with the other attitudes. Stateless single-item calls reduce mean absolute correlation by 0.130 (profile-bootstrap 95% interval: 0.050 to 0.178), although the effect is concentrated in 2018 and independent presentation does not consistently recover the human structure. Histogram gradient boosting remains imperfect for individuals but reduces ordinal MAE from 1.175 to 0.921 and total variation from 0.282 to 0.071. Sparse profiles are therefore a real information limit, but not a sufficient explanation for this model's population distortion. A follow-up audit reads the model's option probabilities directly. In a preregistered factorial experiment, keeping the model's earlier answers in context raises the housework item's mean absolute correlation with the other items by 0.379 (95% interval: 0.339 to 0.410), and by 0.309 (0.271 to 0.338) when the earlier answers are sampled rather than fixed at their most probable values; the main effects of item visibility and output format are small. Given a respondent's real earlier answers, the model moves its housework prediction with them five to six times as steeply as the answers of CGSS respondents are related. The follow-up also found that the first audit's answers were generated inside the model's reasoning block; under the first-audit prompt, closing that block roughly doubles this coherence. In ordinal factor models, the housework item loads 0.16 on the common factor among CGSS respondents and 0.39 to 0.55 in the first-audit answers.

Keywords: synthetic respondents; large language models; machine learning; public opinion; gender attitudes; China

1 Introduction

A synthetic survey respondent can sound plausible without representing any population that exists. A language model asked to speak as a 45-year-old urban Chinese woman with a university education may produce an internally coherent answer to a gender-attitude question. The harder question is whether repeated answers from many such personas reproduce the distribution, heterogeneity, and relational structure observed among comparable people. For social science, these are not secondary properties. Population research depends on variation across respondents, covariance among attitudes, and differences between social groups, not only on whether a single response reads naturally.

Recent work has offered both optimistic and skeptical assessments of large language models as simulated respondents. Argyle et al. (2023) introduce the idea of "algorithmic fidelity," arguing that demographic conditioning can recover complex patterns in human opinion. Aher et al. (2023) similarly show that language models can replicate several established experimental findings, although they also identify systematic distortions. Other studies find substantial demographic misalignment (Santurkar et al., 2023) and warn that synthetic samples can reproduce means while compressing variance, changing regression coefficients, and responding sharply to prompt or model updates (Bisbee et al., 2024). This debate leaves two problems unresolved. First, much evaluation concerns broad American political attitudes, where average alignment can conceal failures in the internal structure of beliefs. Second, when persona-based predictions fail, it is unclear whether the model is at fault or whether the demographic profile simply contains too little information to predict an individual's attitude.

Gender attitudes in China provide a demanding test. Gender egalitarianism is not a single continuum on which every belief moves together. People may reject claims of male superiority and support women's employment while holding different views about responsibilities inside marriage. Research on uneven gender change and multiple egalitarianisms emphasizes precisely this combination of progress, persistence, and ambivalence (England, 2010; Knight and Brinton, 2017; Scarborough et al., 2019). Chinese research likewise distinguishes attitudes toward work and family and documents substantial variation across cohorts, regions, and social positions (Qian and Li, 2020; Yang, 2023). A model that substitutes a stereotyped "traditional" or "modern" persona for this differentiated structure may produce coherent answers while misrepresenting the population.

This paper audits that possibility using three waves of the Chinese General Social Survey (CGSS), comprising 31,856 respondents. The human benchmark contains five commonly used gender-attitude items. Four concern gendered family orientation, ability, marriage, and employment protection; the fifth asks whether spouses should share housework equally. In the survey, the first four items share moderate covariance, whereas equal-housework attitudes are only weakly related to them. From this benchmark, I select 100 profiles per wave using a stratified probability-proportional-to-size procedure. Qwen3.5-9B receives each profile's survey year, province, sex, age, education, hukou, urban residence, marital status, and relative economic position, but never the person's observed answers.

The central design adds a survey-trained comparison. A weighted marginal prior, multinomial logistic regression, and histogram gradient boosting receive the same profile features used in the language-model prompt. Their predictions are generated out of fold, ensuring that each matched respondent's answer is

held out during training. This is not an equal-training-budget contest: the supervised models observe CGSS outcomes, whereas Qwen3.5-9B is evaluated zero-shot. The comparison instead asks whether limited profile information is sufficient to explain the language model's failure. If every model performs similarly poorly, an information ceiling is the parsimonious explanation. If supervised learners remain imperfect at the individual level but recover population distributions that the language model misses, then sparse profiles cannot account for the full distortion.

Three results organize the analysis. First, Qwen3.5-9B's errors are item-specific rather than a uniform ideological shift. Second, repeated generation restores some marginal dispersion, but most of it reflects instability within the same profile rather than stable differences between profiles; item covariance also remains too strong relative to CGSS. Third, outcome-informed reference models using the same prediction-time attributes remain imperfect for individuals but recover population distributions substantially better. The joint-versus-independent experiment then asks how much of the excess item coherence is associated with presenting the battery in a shared context.

The contribution is methodological rather than causal. The paper does not estimate the effect of demographic traits on attitudes, nor does it identify which part of Qwen3.5-9B's training process produces the observed pattern. It instead demonstrates a way to separate two threats to synthetic-survey validity: limited information in persona attributes and additional distortion introduced by a zero-shot generative model. The results also show why evaluation must move beyond average accuracy. A synthetic population can be wrong because it has the wrong center, because it is too concentrated, or because it imposes relationships among attitudes that are weak or absent among humans.

2 From Human Ambivalence to Synthetic Coherence

2.1 What must a synthetic population reproduce?

Persona prompting treats a language model as a conditional generator. Let $\boldsymbol{X}_i$ denote the observed profile of respondent i, $Y_{ij} \in \{1, \ldots, 5\}$ the human response to item j, and $\widetilde{Y}_{ij}^{L}$ a language-model response:

$$\widetilde{Y}_{ijr}^{L} = g_\theta(\boldsymbol{X}_i, q_j, \xi_{ijr}) \,, \tag{1}$$

where q_j represents the question and prompt context, ξ_{ijr} is the stochastic decoding state in call r, and θ denotes the fixed model. This notation does not treat a requested but unverified seed as reproducible random control. A response may be plausible conditional on $\boldsymbol{X}_i$ without g_θ reproducing the human conditional distribution

$$\mathbb{P}(Y_{ij} = k \mid \boldsymbol{X}_i) \,, \qquad k \in \{1, \ldots, 5\}. \tag{2}$$

This distinction creates several levels of fidelity. Individual fidelity asks whether a generated response is close to the matched person's answer. Marginal fidelity asks whether the aggregate shares in the five categories are correct. Heterogeneity fidelity asks whether the synthetic sample preserves human variance. Relational fidelity asks whether item correlations and demographic gradients resemble those in the survey. Success at one level does not imply success at another. A model can miss many individuals but still generate

a calibrated population, or match an average while eliminating disagreement.

The distinction is especially important because survey answers are noisy and only partly predictable from demographics. Low individual accuracy does not by itself invalidate a population generator. Conversely, a model that deterministically assigns the modal attitude to every member of a demographic group may obtain tolerable accuracy while producing unusable data for variance estimates, subgroup comparisons, or measurement analysis.

2.2 Gender attitudes as a structural test

Gender ideology is a useful setting because inconsistency need not be measurement failure. Gender operates across individual, interactional, and institutional levels (Risman, 2004). Attitudes toward women's education or employment can draw on public rules and abstract equality, whereas judgments about housework implicate intimate bargaining, time, identity, and perceived personal costs. Theories of an uneven or stalled gender revolution therefore predict different rates and social bases of change across public opportunity and private responsibility (England, 2010). Empirical work similarly finds several forms of egalitarianism rather than one uniformly ordered scale (Knight and Brinton, 2017; Scarborough et al., 2019).

The Chinese setting adds institutional and cultural specificity. Women's participation in education and paid work has long been publicly legitimated, while household care and domestic work remain strongly organized through families. Studies of Chinese gender ideology accordingly distinguish work and family spheres and document mosaics of beliefs across generations and regions (Qian and Li, 2020; Yang, 2023). Education is associated with more egalitarian attitudes (Shu, 2004), but the strength of this relationship need not be identical across items.

For a language model, however, a demographic profile may cue a compressed social type: older, rural, and less educated personas may be rendered "traditional," while younger, urban, and educated personas may be rendered "modern." Because all five questions appear in one context, next-token generation may also favor consistency with earlier answers. I refer to the resulting possibility as *synthetic coherence*: a generated population exhibits stronger alignment among attitudes than the human population it is intended to represent.

The audit separates two candidate sources. Pretrained representations may map a profile to a stable one-dimensional stereotype; alternatively, a shared prompt may make later answers consistent with earlier ones. I therefore compare the joint five-item prompt with five stateless calls in which the full persona is repeated but the model never sees another item or any previous answer. A decline in A425's mean absolute correlation under independent presentation supports coherence induced by the joint-presentation condition. Strictly, the JSON schema also contracts from five keys to one, so the contrast identifies a presentation bundle—item co-presence, context history, and the associated output format—rather than an isolated psychological consistency pressure.

3 Data and Human Benchmark

3.1 CGSS samples

The human benchmark uses CGSS 2012, 2018, and 2021 (National Survey Research Center at Renmin University of China, 2021). CGSS is a repeated cross-sectional, multistage probability survey covering demographic characteristics, social attitudes, and behavior. The analysis sample requires a valid equal-housework response, at least three valid responses among the other four gender items, and complete profile variables and survey weights. The resulting samples contain 11,668 respondents in 2012, 12,478 in 2018, and 7,710 in 2021, for a pooled total of 31,856.

The five items ask whether respondents agree that: (A421) men should focus on careers and women on family; (A422) men are naturally more capable than women; (A423) for a woman, marrying well is better than doing well; (A424) women should be dismissed first during an economic downturn; and (A425) spouses should share housework equally. Original responses run from 1 (completely disagree) to 5 (completely agree). Because A421–A424 are traditional statements, I reverse them as $6 - Y$; A425 is already egalitarian and remains unchanged. Every reported score therefore ranges from 1 to 5 with higher values indicating a more egalitarian response.

A425 is a single positively worded item, not a complete measure of domestic gender relations. Its separation from A421–A424 can reflect domain content, wording, acquiescence, or single-item error. The paper therefore treats weak A425 covariance as a benchmark property to be reproduced, not as definitive proof of two latent constructs.

3.2 Human item structure

The full weighted survey provides two reference facts. First, A421–A424 share a repeatable common structure, while A425 is only weakly connected to it. The correlation between A425 and the four-item mean is 0.05, 0.10, and 0.11 across the three waves with survey weights (0.05, 0.08, and 0.09 without them). Second, the items differ sharply in marginal difficulty. Equal housework and opposition to employment discrimination receive high egalitarian scores, while attitudes about family orientation are less egalitarian. These differences make the battery a harder test than a set of redundant questions: a successful synthetic sample must recover both item-specific distributions and their limited covariance.

4 Computational Audit Design

4.1 Profile sampling and LLM generation

I draw 100 respondents from each wave. Sampling is stratified by sex, education group, and urban residence; allocations follow each stratum's weighted population share, and respondents are selected within strata with probabilities proportional to the CGSS weight. The resulting 300 profiles contain the same profile fields supplied to the supervised models. Human outcomes are withheld from the model-facing file.

The audit uses the open-weight Qwen3.5-9B model (Qwen Team, 2026), executed locally through LM Studio's OpenAI-compatible server on an Apple M4 computer with 24 GB of unified memory. The downloaded local variant occupies 5.98 GB. The primary prompt asks the model to answer as the described respondent, presents Chinese verbal labels with a one-to-one numerical mapping, and requires a schema-constrained JSON object. Decoding uses temperature 0.7 and top-p 0.9. LM Studio did not confirm that a requested seed was applied by the underlying sampler, so the analysis records requested seeds but treats repetitions as fresh stochastic calls rather than reproducible seeded draws.

The primary `neutral_verbal` condition is called five times for each of the 300 profiles, producing an empirical five-category distribution from 1,500 joint responses. The evaluation script rejects malformed JSON, missing keys, out-of-range scores, and verbal labels inconsistent with their numeric values. A first-draw analysis is retained as a sensitivity check, while the main analysis uses all five draws and decomposes their variance into between-profile and within-profile components.

The context experiment adds 1,500 stateless calls. For each profile, A421–A425 are presented separately in five new requests. Every request repeats the same persona and response scale but contains no conversation history, no other item, and no prior answer. The model, persona information, scale, and decoding settings are unchanged. The design varies shared context while necessarily shortening the structured-output schema from five item keys to one; this remaining format difference bounds the mechanism claim.

Correction (October 2026). A later check of the call path, using the runner, the response files, and the LM Studio server logs, found two features of these calls that the description above omits (Section 6). First, each request carried an integer-only response schema, so the model returned integer JSON without the verbal labels the prompt asked for, and the label-consistency check never applied. Second, LM Studio rendered Qwen3.5's chat template with thinking enabled, its default for this model, and the template does not recognise the `/no_think` line in the user message. Every answer, in the joint and in the stateless calls, was therefore generated inside an open reasoning block and returned in the `reasoning_content` field, which the runner read when `content` was empty. The results in Section 5 describe that configuration.

4.2 Survey-trained reference models

Supervised learning estimates predictive regularities in $P(Y \mid X)$; it does not identify the causal effect of a profile feature or substitute for a theory of attitude formation (Mullainathan and Spiess, 2017; Grimmer et al., 2021). Here it has a narrower diagnostic role. Outcome-informed references show what can be reconstructed from the same prediction-time profile once the mapping from profiles to answers has been calibrated on survey data. If those references also fail at the population level, sparse profiles are a sufficient explanation. If they remain imperfect for individuals but recover population distributions, the LLM introduces additional distortion.

Three references form a ladder of increasing flexibility. The survey-weighted marginal prior ignores X and assigns every test respondent the training fold's weighted category frequencies; it is a minimum test of base-rate calibration. Weighted multinomial logistic regression uses a softmax link and a linear-additive log-odds specification. Histogram gradient boosting (HGB) sequentially fits binned decision trees to negative

gradients of multiclass log loss, allowing nonlinear thresholds and interactions without prespecifying them (Friedman, 2001). Although the five categories are ordered, training treats them as five classes to avoid imposing proportional odds and to recover the full option distribution; ordinal MAE and ranked probability score restore distance information at evaluation. These models use scikit-learn 1.7.2 (Pedregosa et al., 2011). Formally,

$$\Pr(Y_i = k \mid X_i) = \frac{\exp(\alpha_k + X_i\beta_k)}{\sum_{c=1}^{5} \exp(\alpha_c + X_i\beta_c)} \tag{3}$$

defines the multinomial-logit probabilities, while HGB updates class-specific prediction functions as

$$F_k^{(t)}(X) = F_k^{(t-1)}(X) + \eta h_{tk}(X). \tag{4}$$

The former imposes linear additivity on the log-odds scale; the latter lets binned trees determine thresholds and interactions. Their performance gap therefore measures the predictive return to a more flexible function class, not a difference in identified causal effects.

All profile-conditioned models receive survey year, province, sex, age, years of education, urban hukou, urban residence, three-category marital status, partnership status, and relative economic position. Within each training fold, numerical predictors are median-imputed and standardized; categorical predictors are mode-imputed and one-hot encoded. The fitted transformations are then applied to the held-out fold. Training weights are normalized to mean one. HGB uses learning rate 0.06, at most 120 iterations, 15 leaves per tree, a minimum of 40 observations per leaf, $L_2 = 0.1$, and early stopping. Multinomial logit uses $C = 1$ and at most 600 iterations. Hyperparameters and random state are fixed in a versioned configuration rather than selected on the 300 audit profiles.

For the main benchmark, each item is evaluated using five-fold stratified out-of-fold prediction. A person's outcome is never used to fit the model that predicts that outcome. The 300 LLM profiles are then selected from these held-out predictions by exact `wave` and `row_id` keys. Because profile sampling already uses the CGSS weights in selection, matched-profile metrics give each selected profile equal weight. A second design trains on 2012 and 2018 and evaluates on 2021, providing an out-of-period test under distribution shift.

The reference models retain the full five-category probability vector rather than reducing it to the most likely class. Averaging those vectors across profiles directly reconstructs option shares, while their first and second moments determine predicted means and variances. This matters because an argmax classifier may achieve tolerable individual accuracy by repeatedly selecting the modal category while producing an implausibly concentrated population. The benchmark therefore evaluates both person-level loss and the population moments induced by probabilistic predictions.

The comparison fixes prediction-time information, not training information. The supervised models and marginal prior observe CGSS outcomes during training, whereas Qwen3.5-9B is zero-shot. Supervised models outperforming the LLM is therefore not, by itself, the finding. The diagnostic question is narrower: does limited information in $\boldsymbol{X}_i$ fully account for the LLM's errors, or does the LLM introduce additional population-level distortion beyond that information ceiling? Individual loss and population reconstruction are reported separately so that predictive uncertainty is not conflated with distributional failure.

A fourth, stratified joint-donor baseline samples a complete five-item response vector from a human respondent in the same wave, sex, education group, and urban-residence cell. Unlike item-wise classifiers, it preserves an empirical joint outcome vector. It is explicitly outcome-informed and cannot be interpreted as a zero-shot competitor; its role is to test whether sparse stratification necessarily destroys covariance structure.

Table 1: Reference ladder and diagnostic roles

Method	Uses Y in training	Uses X at prediction	Joint vector	Diagnostic role
Weighted marginal prior	Yes	No	No	Minimum base-rate calibration
Multinomial logit	Yes	Yes	No	Linear-additive conditional probabilities
HGB	Yes	Yes	No	Flexible nonlinear and interaction benchmark
Stratified joint donor	Yes	Partly	Yes	Recoverability of human joint structure
Qwen3.5-9B	No	Yes	Yes	Zero-shot population generator under audit

4.3 Evaluation metrics

Let $p_{mij}(k)$ be model m's predicted probability that respondent i chooses category k on item j, and let

$$\widehat{\mu}_{mij} = \sum_{k=1}^{5} k\, p_{mij}(k) \tag{5}$$

be the expected score. For Qwen3.5-9B, $p_{Lij}(k)$ is the empirical frequency across five stochastic calls; a first-draw version is retained as a sensitivity analysis. Individual error is summarized by

$$\mathrm{OMAE}_m = \frac{1}{NJ} \sum_{i=1}^{N} \sum_{j=1}^{J} |\widehat{\mu}_{mij} - Y_{ij}|\,. \tag{6}$$

For probabilistic references, population option shares are reconstructed without taking an argmax:

$$\widehat{\pi}_{mjk} = \frac{1}{N} \sum_{i=1}^{N} p_{mij}(k). \tag{7}$$

Ordinal probability quality is measured by the ranked probability score,

$$\mathrm{RPS}_{mij} = \frac{1}{4} \sum_{k=1}^{4} \left[\sum_{c=1}^{k} p_{mij}(c) - \mathbb{I}(Y_{ij} \le k) \right]^2, \tag{8}$$

which penalizes both miscalibration and errors that cross several response categories. Lower values are better.

For population distributions, let $\widehat{\pi}_{mjk}$ and π_{Hjk} denote model and human shares in category k. Total variation is

$$\mathrm{TV}_{mj} = \frac{1}{2} \sum_{k=1}^{5} \left| \widehat{\pi}_{mjk} - \pi_{Hjk} \right|. \tag{9}$$

I also report signed and absolute mean errors and a ranked probability score for probabilistic models. For Qwen3.5-9B, two variance ratios answer different questions. Marginal predictive dispersion is

$$R_{Lj}^{V,\mathrm{marg}} = \frac{\mathrm{Var}_{i,r}(\widetilde{Y}_{ijr}^{L})}{\mathrm{Var}_{H}(Y_j)}. \tag{10}$$

It combines stable differences between profiles with stochastic variation within a profile. Between-profile differentiation is therefore reported separately:

$$R_{Lj}^{V,\mathrm{between}} = \frac{\mathrm{Var}_{i}(\overline{Y}_{ij}^{L})}{\mathrm{Var}_{H}(Y_j)}, \qquad \overline{Y}_{ij}^{L} = \frac{1}{R} \sum_{r=1}^{R} \widetilde{Y}_{ijr}^{L}. \tag{11}$$

The first ratio asks how dispersed the final synthetic draws are; the second asks whether profiles receive stably different expected answers. Because the human denominator remains the observed cross-sectional variance, the latter is a diagnostic ratio rather than a symmetric decomposition of human conditional variance.

Relational fidelity is evaluated using the root mean squared difference between the human and synthetic item-correlation matrices and the mean absolute correlation between A425 and A421–A424. The context contrast is

$$\Delta r_{425} = \overline{|r_{425,1:4}|}_{\mathrm{joint}} - \overline{|r_{425,1:4}|}_{\mathrm{independent}}. \tag{12}$$

A profile-cluster bootstrap interval entirely above zero supports context-induced coherence; an interval containing zero is treated as suggestive rather than confirmatory. Signed pairwise correlations are also reported so that absolute values do not conceal reversals.

Uncertainty for the matched HGB–LLM error difference also comes from a profile-cluster bootstrap. Item-level absolute-error differences are first averaged within each profile, profiles are resampled within wave, and the statistic is recomputed 2,000 times. In the context experiment, all items and joint repeats belonging to a sampled profile move together. These intervals describe uncertainty around the matched audit set; they do not reproduce every stage of the original multistage survey design.

Finally, I draw 100 human respondents from each wave 1,000 times using the audit's original strata, allocation rule, and survey weights. The central 95% interval defines a task-specific sampling reference envelope. It is neither a confidence interval for the finite-population parameter nor a universal deployment threshold; it asks whether a 100-profile synthetic sample falls within the variation normally produced by a human sample of the same size under this design.

5 Results

5.1 The model misses item-specific opinion

Table 2 averages the three wave-specific means to show the main direction of error. Qwen3.5-9B does not shift every answer in the same ideological direction. It overstates egalitarianism on A421–A424, especially family orientation and male ability, but understates support for equal housework. The result is not a generic conservative or liberal bias. It is an item-structured reconstruction error that separates abstract and public-facing equality from a norm about private domestic responsibility.

Table 2: Average item means across CGSS waves

Item	CGSS weighted mean	Qwen3.5-9B mean	Error
A421 Family orientation	2.800	3.842	$+1.042$
A422 Male ability	3.174	4.250	$+1.076$
A423 Marriage over achievement	3.034	3.630	$+0.596$
A424 Dismiss women first	3.988	4.076	$+0.088$
A425 Equal housework	3.907	3.577	-0.330

Notes: Entries average the 2012, 2018, and 2021 item means, giving each wave equal weight. CGSS entries use the full weighted survey samples. All items are oriented so that higher values indicate greater gender egalitarianism. Qwen3.5-9B uses all five joint draws in the primary neutral verbal-label condition.

The pattern matters because aggregate error would conceal it. Positive errors on the first four items and the negative A425 error partly cancel if averaged with signs. Item-specific diagnostics instead show that the model constructs a population that is unusually egalitarian on general role and capability statements while remaining less supportive of equal domestic labor than the survey benchmark.

5.2 Variance compression and synthetic coherence

Pooling all five draws produces a median marginal variance ratio of 0.801 and a mean of 0.794 across the 15 wave-item cells. Taken alone, that result would suggest substantially improved heterogeneity. The decomposition changes the interpretation: 68.2% of Qwen3.5-9B's predictive variance arises within the same profile across stochastic calls, while the mean between-profile variance ratio is only 0.265. Random decoding restores some dispersion without recovering stable differentiation among social profiles.

The model also changes relationships among items. Table 3 reports the mean absolute correlation between A425 and the first four items. In weighted CGSS, that value remains near 0.05–0.08. Across the five joint repeats, Qwen3.5-9B ranges from 0.232 to 0.335. The joint generator pulls a weakly connected housework norm into a more coherent attitude package.

Table 3: Recovery of item-correlation structure

Wave	CGSS A425 mean $\lvert r \rvert$	Qwen3.5-9B A425 mean $\lvert r \rvert$	Matrix RMSE
2012	0.049	0.242	0.192
2018	0.078	0.335	0.184
2021	0.078	0.232	0.143

This establishes joint-output distortion but does not, by itself, identify a cognitive or computational mechanism. The independent-item contrast below tests whether the excess coherence changes when the other items and prior answers are removed from context.

5.3 Joint presentation amplifies coherence, but not uniformly

Across waves, A425's mean absolute correlation with the first four items falls from 0.270 under joint presentation to 0.139 under stateless independent calls. The profile-cluster bootstrap estimates a difference of 0.130 with a 95% interval of $[0.050,\ 0.178]$. Joint presentation therefore contributes to synthetic coherence in the pooled audit.

Table 4: A425 coherence under joint and independent presentation

Wave	Weighted CGSS	Joint	Independent	Joint − independent (95% interval)
2012	0.049	0.242	0.184	0.058 [−0.050, 0.191]
2018	0.078	0.335	0.065	0.270 [0.124, 0.338]
2021	0.078	0.232	0.169	0.062 [−0.065, 0.149]
Wave average	0.069	0.270	0.139	0.130 [0.050, 0.178]

The wave-specific results narrow the mechanism claim. The reduction is large and clearly estimated in 2018, where independent presentation approaches the human benchmark, but the intervals cross zero in 2012 and 2021. Signed correlations also change from uniformly positive under the joint prompt to several negative associations under independent presentation. Moreover, A422 and A424 retain variance ratios of only 0.22–0.44 in most independent wave cells. Removing shared context therefore weakens positive consistency pressure without reliably restoring the human joint distribution. Shared presentation is one source of synthetic coherence, not its sole cause.




Figure 1: Signed A425 item correlations under joint and independent presentation. The joint series averages five repeat-specific correlations.

5.4 Sparse profiles do not explain the full gap

Table 5 addresses the main alternative explanation. The supervised models are not highly accurate at the individual level: HGB's ordinal MAE is 0.921 and multinomial logit's is 0.935. Sparse demographics therefore impose a real information ceiling. Yet both recover aggregate distributions far better than Qwen3.5-9B. HGB's total variation is 0.071, compared with 0.282 for the LLM. Even the empirical marginal prior, which learns no mapping from profiles to attitudes, attains an MAE of 0.975 and total variation of 0.097.

Table 5: Matched-profile predictive and distributional performance

Model	Ordinal MAE	Abs. mean error	Total variation	Variance ratio
Empirical marginal prior	0.975	0.127	0.097	0.992
Multinomial logit	0.935	0.113	0.082	0.982
Histogram gradient boosting	**0.921**	**0.093**	**0.071**	0.986
Stratified joint donor	0.987	–	0.070	0.973
Qwen3.5-9B, zero-shot	1.175	0.712	0.282	0.794

Notes: Models are evaluated on the same 300 CGSS profiles used for LLM generation. ML predictions are out of fold. The empirical marginal prior uses training-fold outcome frequencies but no profile attributes. ML variance uses the full predictive probability distribution; the Qwen3.5-9B row uses the empirical option distribution from five draws per profile.




Figure 2: Same-profile comparison between survey-trained models and Qwen3.5-9B. Lower values indicate better performance. The absolute mean-error panel averages absolute cell-level mean errors rather than allowing positive and negative errors to cancel.

The paired comparison is also precise within the matched sample. Qwen3.5-9B's absolute ordinal error exceeds HGB's by 0.255 points; the profile-cluster bootstrap interval is $[0.205, 0.301]$. The five item errors belonging to one respondent are never treated as independent observations.

The joint donor supplies the relational counterpoint that item-wise classifiers cannot. Its correlation-matrix RMSE is 0.085 and its A425 mean absolute correlation is 0.105, compared with 0.173 and 0.270 for Qwen3.5-9B. Preserving complete human response vectors therefore recovers most of the joint structure without requiring a complex generator. This does not make the donor a zero-shot competitor; it demonstrates that sparse stratification does not mechanically require the excessive coherence produced by the LLM.

These findings do not establish that HGB is a superior model of human psychology. It is optimized on the outcomes being evaluated, while Qwen3.5-9B is not. Instead, they test a simpler account of the LLM results: that any method restricted to these demographic profiles must generate the same distorted population. Survey-trained models can remain uncertain about individuals while representing observed base rates and conditional variation more faithfully. Qwen3.5-9B adds a directionally patterned error beyond that limitation.

5.5 Out-of-period prediction

Random-fold comparisons allow the outcome-informed models to learn the marginal distribution of each survey year. A stricter test trains on 2012 and 2018 and predicts 2021. As Table 6 shows, every supervised reference deteriorates under temporal transfer. HGB's ordinal MAE rises to 0.942 on the matched 2021 profiles and its total variation rises to 0.107, indicating real distribution shift. This is substantively informative: even task-specific models cannot treat public opinion as time invariant.

Table 6: Temporal generalization: train on 2012 and 2018, test on 2021

Model	Ordinal MAE	RPS	Total variation	Variance ratio
Historical marginal prior	0.997	0.160	0.113	0.960
Multinomial logit	0.960	0.153	0.140	0.927
Histogram gradient boosting	**0.942**	**0.150**	**0.107**	0.955

On the 100 matched 2021 profiles, the historical references are compared with Qwen3.5-9B without allowing them to observe 2021 outcomes. This comparison still does not equalize training information—the references see historical CGSS labels—but it tests whether the LLM's 2021 fit is solely an artifact of allowing reference models to observe the target year's answers.

6 Follow-up Audit with Option Probabilities

6.1 Design

The follow-up audit replaces sampled answers with the model's probabilities for the five response options. The same Qwen3.5-9B weights are run locally through MLX. For each profile, item, and condition, one forward pass returns the next-token distribution after the assistant prefix, and the probabilities of the tokens `1`–`5` are renormalised over the scale; the mass on these tokens averages above 0.999. The output projection is applied in single precision to the final position only, because the default half-precision logits moved option probabilities by up to 0.031 depending on the computation path. Full-prompt computation is identical across runs. Item means in this section are on the original response scale (1 = completely disagree, 5 = completely agree), not the egalitarian coding used above; absolute errors and absolute correlations do not depend on the direction.

A preregistered $2 \times 2 \times 2$ experiment separates three features that the first audit bundled: whether the full item block is visible (A), whether the model's earlier answers remain in context (B), and whether the answer is a bare integer or JSON (C). Cells with history use the most probable earlier answers. The preregistration was committed before any CGSS profile was scored, and later changes are dated in its change log. The primary outcome is the mean absolute correlation between the expected score on A425 and the expected scores on A421–A424, computed across profiles within wave and averaged over waves, with a profile-cluster bootstrap of 2,000 replicates. The design has 12,000 forward passes.

6.2 Answer history drives synthetic coherence

Table 7: Factorial effects on A425 coherence (mean absolute correlation of expected scores)

Effect	Estimate	95% interval
A: item block visible	0.048	[0.022, 0.074]
B: answer history in context	0.379	[0.339, 0.410]
C: JSON output	0.013	[−0.013, 0.039]
A × B	0.024	[−0.034, 0.079]
A × C	0.237	[0.192, 0.286]
B × C	−0.035	[−0.091, 0.019]
A × B × C	−0.138	[−0.239, −0.044]

Interactions are differences of simple effects, not halved.

Answer history is the dominant source of coherence (Table 7). The four cells without history range from 0.39 to 0.58, close to the 0.45 obtained from the out-of-fold expected scores of the survey-trained gradient boosting model; the four cells with history range from 0.78 to 0.92. With these modal histories, output format has no detectable main effect, but its effect reverses with item visibility: JSON lowers coherence when only the target item is shown and raises it when the block is visible. The CGSS value of 0.069 is a response-level correlation and is not on the same scale as correlations between profile-level expected scores.

Marginal accuracy is sensitive to presentation. The mean absolute error of item means ranges from 0.30 (A0-B0-C0) to 1.06 (A1-B1-C0). The most accurate cell has a between-profile variance ratio of 0.09, so it gives nearly the same distribution to every profile. Calibration against matched respondents is poor in every cell: the mean log score lies between 1.97 and 3.06, worse than a uniform guess over five options ($\ln 5 \approx 1.61$), and the best ranked probability score, 0.191, compares with 0.149 for gradient boosting.

6.3 The thinking context of the first audit

Item means in the reference cell A1-B1-C1 were far from the first audit's (A421: 4.42 against 2.16), and an exploratory cell that restored a verbal label before each score lowered coherence (0.81 against 0.92) without moving the means. The correction in Section 4.1 suggested another source. A diagnostic scored A421 for the 300 first-audit prompts twice, once with the reasoning block open, as in the first audit, and once closed, as in the follow-up, holding everything else fixed.

Table 8: A421 under the first-audit prompt with the reasoning block open or closed

	Open (first audit)	Closed (follow-up)
Expected score after first-audit decoding ($T = 0.7$, top-p 0.9)	2.13	3.26
Mean log-likelihood of the 1,500 first-audit answers	-1.53	-8.30
First-audit answers with zero probability	15	395
Correlation with first-audit profile means	0.54	0.27

The first-audit sampled mean of A421 is 2.16.

Two exploratory cells extend the comparison to all five items. They were specified in the preregistration after the diagnostic and before they were run. Both use the first-audit system and user prompts and condition on the most probable earlier answers; V1-T1 leaves the reasoning block open and V1-T0 closes it (Table 9).

Table 9: The first-audit prompt with the reasoning block open or closed, five items

	V1-T1 (open)	V1-T0 (closed)	A1-B1-C1
A425 mean $\lvert r \rvert$	0.44	0.91	0.92
95% interval	[0.37, 0.50]	[0.90, 0.92]	[0.90, 0.93]
Mean absolute gap from first-audit item means	0.23	0.62	1.47
Mean absolute error against CGSS item means	0.68	0.36	0.95
Between-profile variance ratio	0.14	0.65	0.41
Matched log score	1.96	1.99	3.06

The gap from first-audit means applies the first-audit decoding ($T = 0.7$, top-p 0.9) to the option probabilities; the other rows use the probabilities at $T = 1$.

Closing the reasoning block raises A425 coherence by 0.47 (95% interval 0.41 to 0.54). With the block closed, the first-audit prompt cannot be distinguished from A1-B1-C1 on this outcome (difference -0.01, interval -0.03 to 0.01). The remaining differences between the two prompts, the system message and the wording, move the item means instead: with the block closed, the first-audit prompt is closer to the CGSS means than A1-B1-C1. The open block comes closest to the first-audit means. A421 and A425 are within 0.11 of them, while A422–A424 are 0.25 to 0.45 lower; the cells condition on the most probable earlier answers, whereas the first audit sampled them, so the procedures are not identical.

The factorial effects in Table 7 were all estimated with the reasoning block closed, and the design did not cross the reasoning context with A, B, and C. It therefore does not show how large the history effect is when the block is open. V1-T1 keeps the history in context and reaches 0.44, close to the 0.45 of the gradient boosting model. Like the other values in this section, it is computed from expected scores and is not on the scale of the first audit's 0.23 to 0.34, which was computed from sampled answers.

6.4 Measurement models

One-factor ordinal models (weighted least squares with mean- and variance-adjusted tests) were estimated for CGSS and for three synthetic populations: the most probable answers in A1-B1-C1 and in A0-B0-C0,

and the first-audit sampled answers as five replicate data sets of 300 profiles. All items are coded so that higher values are more egalitarian.

Table 10: Standardised loading of A425 in the one-factor model

Population	n	A425	Other items	Solution
CGSS, weighted	31,177	0.16	0.55–0.77	proper
First-audit answers (5 replicates)	300	0.39–0.55	0.66–0.92	proper
Follow-up modal answers, A1-B1-C1	300	1.02	0.88–0.99	improper
Follow-up modal answers, A0-B0-C0	300	0.57	−0.28–1.09	improper

In A0-B0-C0, A424 has a single category after sparse categories are merged and is dropped.

Among CGSS respondents, A425 is nearly separate from the other four items (Table 10). In every synthetic population it loads much more strongly on the common factor; across the five first-audit replicates the difference from CGSS is 0.23 to 0.39, with every 95% interval above zero. The modal-answer populations are close to deterministic, with polychoric correlations as high as 0.998, so their factor solutions are improper and a two-group model with A1-B1-C1 cannot be estimated. Between CGSS and each first-audit replicate, equal thresholds and equal loadings are rejected by the scaled difference test ($p < .001$), while the scaled CFI changes by less than 0.01; with a human sample about a hundred times larger, the loading differences are the more informative result. Graded-response models agree: the discrimination of A425 relative to the mean of the other items is 0.17 in CGSS and 0.30 to 0.53 in the first-audit replicates.

6.5 Robustness: sampled answer histories

The cells with history condition on the most probable earlier answers. The preregistered robustness check replaces them with five draws per profile from the model's own option distributions, each seeded by profile, cell, and path; the drawn answer to each item enters the history of the next. The four history cells give 30,000 scored prompts, and replaying the seeded draws reproduces every recorded history. Two outcomes are computed. The first (R2) is the primary outcome on the expected scores conditional on each sampled history, averaged over paths. The second (R1) uses the drawn answers themselves: the mean absolute correlation between drawn A425 answers and drawn A421–A424 answers across the 100 profiles of a wave, averaged over paths and waves. Cells without history draw their answers from the primary distributions. Unlike expected scores, drawn answers are on the scale of the human response-level benchmark.

Table 11: A425 coherence with modal and sampled answer histories

	Modal history (expected scores)	Sampled history (expected scores, R2)	Drawn answers (response level, R1)
A0-B0-C0	0.52	—	0.13
A0-B0-C1	0.39	—	0.16
A1-B0-C0	0.40	—	0.09
A1-B0-C1	0.58	—	0.21
A0-B1-C0	0.87	0.75	0.37
A0-B1-C1	0.78	0.75	0.44
A1-B1-C0	0.84	0.76	0.36
A1-B1-C1	0.92	0.87	0.57
B: answer history	0.379 [0.339, 0.410]	0.309 [0.271, 0.338]	0.288
C: JSON output	0.013 [−0.013, 0.039]	0.042 [0.015, 0.070]	0.106
A × B × C	−0.138 [−0.239, −0.044]	−0.197 [−0.290, −0.107]	0.048

Cells without history have no sampled-history counterpart; their R2 values equal the modal values. Human response-level comparators: full weighted CGSS 0.069; samples of 100 per wave, median 0.10 and 97.5th percentile 0.22; first audit 0.27. Response-level effects are given without intervals (see text).

Answer history remains the largest source of coherence (Table 11). Fixing the earlier answers at their most probable values overstates coherence by 0.06 to 0.12 in three of the four history cells; in A0-B1-C1 the difference is -0.03 (95% interval -0.05 to 0.00). The history effect falls from 0.379 to 0.309. The drawn answers allow a direct comparison with people. Without history, the four cells give response-level values of 0.09 to 0.21, within the range of human samples of 100 respondents per wave; with history they give 0.36 to 0.57, above that range and above the first audit's 0.27, which was generated with the reasoning block open. The survey-trained model gives 0.08. As noted below, values within the human range need not reflect a recovered structure.

Two factorial results are less robust. With sampled histories JSON output has a small positive main effect, and the three-way interaction changes sign at the response level. Item-mean errors change little (mean absolute error 0.35 to 0.97 across the history cells, against 0.31 to 1.06), and the between-profile variance ratio falls in three of the four history cells. Bootstrap percentile intervals for response-level correlations lie above the point estimates when the correlations are small (A1-B0-C0: 0.090, interval 0.099 to 0.141), because duplicated profiles in a resample inflate absolute correlations near zero; response-level intervals are therefore not interpreted.

6.6 Exploratory analyses

Three further analyses were added to the preregistration after its results were known and before the analyses were run. They are reported as exploratory and change no preregistered estimand.

Direction of the item-mean errors. In egalitarian coding, the first audit's answers were more egalitarian than CGSS on A421–A424 and less on A425 (Table 12). The same pattern appears under the first-audit prompt with the reasoning block open and in the follow-up when only the target item is shown with JSON output. In the four cells that show the item block, the model is less egalitarian than CGSS on A421–A424, and A425 is understated in six of the eight factorial cells. The item-specific pattern of Section 5 therefore describes the first-audit configuration; its sign is not a stable property of the model.

Table 12: Item-mean error against CGSS in egalitarian coding

	A421	A422	A423	A424	A425
CGSS mean	2.80	3.17	3.03	3.99	3.91
First-audit answers (reasoning open)	1.04	1.08	0.60	0.09	−0.33
V1-T1 (first-audit prompt, reasoning open)	0.80	1.16	0.74	0.27	−0.43
A0-B0-C1 (target item only, JSON)	0.37	1.10	0.90	0.77	−1.46
A1-B1-C1 (follow-up reference)	−1.22	−0.23	−0.69	−1.03	−1.56
A1-B0-C0 (item block, no history, integer)	−0.65	−0.36	−0.60	−1.30	0.01

Wave-averaged means. Rows below the first give the model mean minus the CGSS mean.

Subgroup gradients. Within wave, the egalitarian-coded expected scores of the 100 profiles were regressed on sex, years of education, age, and urban residence, the specification of the first audit, and compared with the weighted regression in the full CGSS sample. A regression coefficient of an expected score and of an observed answer estimate the same conditional mean, so the two are on one scale. Among CGSS respondents, urban residence and education go with more egalitarian answers on the public-role items but hardly with A425, while women differ from men more on A425 than on the public-role items (Table 13). The model extends the social gradients to the housework item. In seven of the eight factorial cells the urban-residence coefficient for A425 lies between 0.21 and 0.88, against 0.01 in CGSS, and every interval for the difference lies above zero; the first audit's sampled answers give 0.29. In CGSS the education coefficient is 0.036 larger for the public-role index than for A425; in every cell this difference is smaller (−0.070 to 0.015), and every interval for its difference from CGSS lies below zero. The gender gap on the public-role index exceeds the CGSS value in seven of the eight cells. Because many coefficients are compared, only patterns that hold across cells are described.

Table 13: Subgroup gradients, averaged over waves (egalitarian coding)

	CGSS		Follow-up, eight cells		First audit
Coefficient	Public	Housework	Public	Housework	Public / housework
Female	0.15	0.30	0.11–0.58	0.17–0.69	0.22 / 0.50
Years of education	0.055	0.019	0.017–0.084	0.011–0.098	0.018 / 0.073
Urban residence	0.16	0.01	0.13–0.36	0.03–0.88	0.19 / 0.29

Public: mean of A421–A424. Housework: A425. Models also include age in decades.

Response-level coherence of the survey-trained model. Five draws per profile from the out-of-fold gradient boosting distributions give a response-level A425 coherence of 0.08; the median for human samples of 100 per wave is 0.10. A generator whose distributions barely differ between profiles produces low response-level correlations whatever its structure, so response-level values in the human range do not by themselves show that a structure is recovered.

Respondent histories. If the model's coherence came only from building on its own earlier answers, giving it a person's real answers should help it as much as it helps a survey-trained model. In the cells H-A1-B1-C1 and H-A0-B1-C0 the prompts are those of A1-B1-C1 and A0-B1-C0, but the history before each item holds the matched CGSS respondent's own answers to the earlier items; 296 profiles with all five answers give 1,184 forward passes per cell (Table 14). Against the cell without history, the respondent's answers in H-A1-B1-C1 improve the model's predictions of A423 and A424 (log-score differences -0.37 and -0.45, both intervals below zero) but make A425 much worse ($+1.76$, interval 1.42 to 2.13). In H-A0-B1-C0 they improve the log score on all four items, A425 included (-0.29, interval -0.49 to -0.10), while A425's ranked probability score gets worse ($+0.058$, interval 0.041 to 0.075). Gradient boosting with the same history improves on every item and on both scores, A425 included (log score -0.095). Whether a respondent's answers help the model predict A425 therefore depends on the cell and the score. The history dependence does not: given a respondent's answers, the model moves its expected A425 score with their mean at a slope of 0.65 in H-A1-B1-C1 and 0.55 in H-A0-B1-C0, five to six times the weighted CGSS slope of 0.11 and 0.56 and 0.46 above gradient boosting with history (intervals 0.49 to 0.62 and 0.39 to 0.53). With its own earlier answers or with a respondent's, the model treats the housework item as following from the public-role items. H-A0-B1-C0 was scored after H-A1-B1-C1 and analysed once all profiles were complete.

Table 14: Calibration and history dependence with the respondent's own earlier answers

	Log score		Slope of A425 on
Source	A422–A424	A425	A421–A424 mean
H-A1-B1-C1 (respondent's history)	1.66	3.44	0.65 [0.59, 0.71]
A1-B1-C1 (model's modal history)	2.34	5.55	0.20
A1-B0-C1 (no history)	1.94	1.68	0.15
H-A0-B1-C0 (respondent's history)	1.49	2.82	0.55 [0.49, 0.61]
A0-B1-C0 (model's modal history)	1.84	3.00	0.19
A0-B0-C0 (no history)	2.05	3.11	0.12
Gradient boosting, respondent's history	1.23	1.15	0.09 [0.04, 0.14]
Gradient boosting, no history	1.41	1.25	0.05
CGSS, weighted (observed answers)			0.11

296 matched profiles. Log score: mean negative log probability of the respondent's answer (uniform guess: 1.61). Slope: within-wave least squares of the expected A425 score on the mean of the respondent's A421–A424 answers in egalitarian coding, averaged over waves.

7 Discussion

7.1 What the benchmark identifies

The strongest inference is comparative. Demographic profiles provide limited information about any one person's gender attitudes. That limitation is visible in the residual MAE of the survey-trained models and is consistent with the modest explanatory power of standard demographic regressions. However, sparse profiles do not force a model to produce the particular population generated by Qwen3.5-9B. Outcome-informed references recover marginal distributions and matched answers more accurately. The language model's error therefore combines an information ceiling with additional model-specific or prompt-specific distortion.

This distinction matters for evaluating synthetic respondents. Individual prediction and population reconstruction are different estimands. Social scientists may tolerate low exact-match accuracy if a generator is calibrated and preserves the relationships required for inference. The Qwen3.5-9B case fails several parts of this more permissive population test: it shifts item means, weakly differentiates profiles, and strengthens relationships around a housework norm that is only weakly connected to the other items in CGSS.

The context experiment shows that prompt architecture is part of the data-generating process. Presenting the battery jointly increases positive item binding in the pooled audit, but the effect is not stable across waves and stateless calls create their own variance compression and negative associations. Independent prompting is therefore not an automatic correction. The defensible inference is that shared presentation amplifies an existing structural tendency; the remaining distortion may reflect model representations, item-specific decoding, or the changed output schema.

The comparison also clarifies what the marginal prior does and does not show. It does not constitute an unsupervised or information-free baseline; it uses observed outcome frequencies from training data. Its role is to separate personalization from base-rate calibration. If a non-personalized prior outperforms Qwen3.5-9B, the LLM's demographic conditioning does not compensate for its incorrect implicit base rates. It does not mean a prior can replace a survey, because those base rates must first be measured.

7.2 Implications for gender-attitude research

The substantive pattern is not a generic left- or right-leaning shift. In the first-audit configuration, Qwen3.5-9B overstates egalitarianism on the first four traditional statements, especially family orientation and male ability, while understating support for equal housework. The follow-up shows that the sign of these errors changes with the configuration (Table 12), so a single ideological-bias label would conceal both the item-specific errors and their dependence on presentation. The model also over-associates A425 with the other items, most strongly when its earlier answers are in context, and in nearly every configuration it extends the social gradients of the public-role items to housework (Table 13). Both make human attitudes look more consistently ordered than they are.

This result returns to a central insight of multidimensional gender-ideology research: ambivalence can be socially meaningful. People can endorse equality in one setting and resist it in another. If synthetic respondents are optimized, prompted, or decoded in ways that favor internally consistent personas, they

may erase precisely the combinations that social scientists seek to explain. Such data would be particularly hazardous for scale construction, latent-class analysis, subgroup inference, or simulations of attitude change.

7.3 Limitations and next tests

Six limitations define the scope of the current evidence. First, both audits evaluate one open-weight model, and the follow-up uses a single 4-bit quantisation. The findings should be described as a Qwen3.5-9B case study until replicated across model families and parameter scales. Second, the first audit's five repeated draws give a coarser option distribution than direct candidate-option probabilities. The follow-up reads those probabilities, but with the reasoning block closed and a different prompt, so it does not re-estimate the first audit's calibration. Third, the first audit's joint-versus-independent contrast changes not only item co-presence but also the structured-output schema, so it identifies a presentation bundle rather than an isolated context mechanism. The follow-up factorial separates these features, but only with the reasoning block closed.

Fourth, the first audit's prompt conditions are not fully factorial. The original, neutral, verbal-label, and paraphrased prompts change more than one feature at a time and cannot separately identify the effects of social-desirability instructions, wording, and output format; the follow-up factorial varies presentation and output format but not instructions or wording. Fifth, the factorial conditions on the most probable earlier answers. The preregistered robustness check with sampled histories leaves answer history as the dominant effect, but it shows that fixing the earlier answers overstates coherence and that the null output-format effect depends on that choice. Sixth, the survey battery itself is imperfect. A425 is a single positively worded item, whereas A421–A424 are traditional statements that are reverse-coded. The human benchmark establishes that unconditional aggregation is questionable, but it cannot separate domain content from all wording and measurement effects.

The follow-up carried out the factorial experiment and the item-response analysis that the first audit lacked. Two extensions remain more informative than further descriptive metrics: a replication of the factorial with the reasoning block open, and a cross-model replication that can determine whether the observed distortions are specific to Qwen3.5-9B or recur across model families.

8 Conclusion

Synthetic respondents should be evaluated as populations, not merely as fluent impersonations. In this study, a locally deployed Qwen3.5-9B model fails to reproduce several basic properties of Chinese gender attitudes. It generates large, item-specific mean errors, weak stable differentiation among profiles, and stronger coherence between the equal-housework item and the other gender-attitude items than appears in CGSS. Stateless item presentation reduces this coherence on average but does not recover the human structure consistently across waves.

The follow-up audit narrows the mechanism. With the reasoning block closed, the model's own earlier answers are the main source of the extra coherence, whether those answers are fixed at their most probable values or sampled. Given a respondent's real earlier answers instead, it still ties the housework item to them

far more steeply than people's answers are tied together, while a survey-trained model given the same answers does not. The first audit's answers were written inside an open reasoning block, which changes both item means and coherence. In factor models of those answers, the housework item remains more tightly bound to the other attitudes than it is among CGSS respondents.

The survey-trained benchmark changes the interpretation of that failure. Sparse demographic profiles do limit individual prediction, but models using the same prediction-time features can recover the observed distributions substantially better after outcome calibration. The LLM's distortion therefore cannot be reduced to missing profile information alone. At the same time, the comparison does not establish a universal defect of language models or identify a single mechanism. It establishes a narrower methodological point: claims about synthetic populations require benchmarks for base rates, heterogeneity, and covariance, together with explicit accounting of what each model observes during training and prediction.

References

Aher, G. V., Arriaga, R. I., and Kalai, A. T. (2023). Using large language models to simulate multiple humans and replicate human subject studies. In *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, pages 337–371. PMLR.

Argyle, L. P., Busby, E. C., Fulda, N., Gubler, J. R., Rytting, C., and Wingate, D. (2023). Out of one, many: Using language models to simulate human samples. *Political Analysis*, 31(3):337–351.

Bisbee, J., Clinton, J. D., Dorff, C., Kenkel, B., and Larson, J. M. (2024). Synthetic replacements for human survey data? the perils of large language models. *Political Analysis*, 32(4):401–416.

England, P. (2010). The gender revolution: Uneven and stalled. *Gender & Society*, 24(2):149–166.

Friedman, J. H. (2001). Greedy function approximation: A gradient boosting machine. *The Annals of Statistics*, 29(5):1189–1232.

Grimmer, J., Roberts, M. E., and Stewart, B. M. (2021). Machine learning for social science: An agnostic approach. *Annual Review of Political Science*, 24:395–419.

Knight, C. R. and Brinton, M. C. (2017). One egalitarianism or several? two decades of gender-role attitude change in europe. *American Journal of Sociology*, 122(5):1485–1532.

Mullainathan, S. and Spiess, J. (2017). Machine learning: An applied econometric approach. *Journal of Economic Perspectives*, 31(2):87–106.

National Survey Research Center at Renmin University of China (2021). Chinese general social survey: 2012, 2018, and 2021. Survey data.

Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M., Prettenhofer, P., Weiss, R., Dubourg, V., Vanderplas, J., Passos, A., Cournapeau, D., Brucher, M., Perrot, M., and

Duchesnay, É. (2011). Scikit-learn: Machine learning in python. *Journal of Machine Learning Research*, 12(85):2825–2830.

Qian, Y. and Li, J. (2020). Separating spheres: Cohort differences in gender attitudes about work and family in china. *The China Review*, 20(2):19–51.

Qwen Team (2026). Qwen3.5-9b model card. Hugging Face model card. Accessed 15 July 2026.

Risman, B. J. (2004). Gender as a social structure: Theory wrestling with activism. *Gender & Society*, 18(4):429–450.

Santurkar, S., Durmus, E., Ladhak, F., Lee, C., Liang, P., and Hashimoto, T. (2023). Whose opinions do language models reflect? In *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, pages 29971–30004. PMLR.

Scarborough, W. J., Sin, R., and Risman, B. (2019). Attitudes and the stalled gender revolution: Egalitarianism, traditionalism, and ambivalence from 1977 through 2016. *Gender & Society*, 33(2):173–200.

Shu, X. (2004). Education and gender egalitarianism: The case of china. *Sociology of Education*, 77(4):311–336.

Yang, R. (2023). Mosaic of beliefs: Comparing gender ideology in china across generation, geography, and gender. *International Journal of Comparative Sociology*, 64(5):454–480.