

## CS392 – Quiz

Name: **Maheeth Reddy**

Roll No.: **1801CS31**

Date: **18-Apr-2021**


### Ans 1:

The given program attack.c, consists of a mistake. We are initializing the map variable (void pointer) in the main() function using mmap() function. One of the parameters to mmap() is mentioned as MAP\_SHARED flag. This causes the mapped memory to be shared between two processes. But, this flag is supposed to be MAP\_PRIVATE for the attack to happen successfully.

Shankar is trying to do a Dirty-COW attack. The three important steps in this attack are:

- (A) Make a copy of the mapped memory
- (B) Update the page table, so the virtual memory points to newly created physical memory
- (C) Write to the memory.

The principle behind the attack is to create a race condition like TOCTTOU. The steps A,B,C are not atomic in nature: they can be interrupted by other threads which creates a potential race condition leading to Dirty Cow vulnerability.<sup>1</sup>



Picture taken from slides

Consider the following scenario. If `madvice()` is executed between Steps B and C, Step B will make the virtual memory point to 2. But `madvice()` will change it back to 1, sort of negating Step B. This causes Step C to modify the physical memory marked by 1, instead of the private copy. Now, the read-only file

is modified, which Shankar had no permission to edit. Since this is a COW memory, when the write() system call is invoked, it triggers A,B,C without a double check.<sup>2</sup>