



Romel Cabiling ▾



Home

Home > My courses > 121 - WEB101 / CCS3218 > 04 Mark Up Text > Lesson Proper for Week 4

Lesson Proper for Week 4

Blank Space

You can insert blank spaces within a line of text to indent or add emphasis to your text. You can also use blank spaces to help position an element on a Web page, such as a graphic or photo. Type ` ` in the line where you want to add a blank space. To add multiple spaces, type the code multiple times. The code stands for nonbreaking space. Web browsers will not create a line break where you insert these characters.



Preformatted Text

You can use the preformatted tags, `<pre>` and `</pre>`, to keep the line breaks and spaces you enter for a paragraph or block of text. Web browsers ignore hard returns, line breaks, and extra spaces between words unless you insert the preformatted tags. If you type a paragraph with spacing just the way you want it, you can assign the preformatted tags to keep the spacing in place.





Comments

You can put comments into HTML pages to describe the page itself or to provide some kind of indication of the status of the page. Some source code control programs store the page status in comments, for example. Text in comments is ignored when the HTML file is parsed; comments never show up onscreen, that is why they are comments. Comments look like the following:

```
<!-- This is a comment -->
```

Special Characters

You can use HTML code to insert special characters into your Web page text. Special characters are characters that do not usually appear on your keyboard. The codes used to insert special characters are called **entities**. Entities consist of number or name codes preceded by an ampersand and ending with a semicolon, such as `½`; for the fraction $\frac{1}{2}$ or `¶`; for a paragraph symbol. Type the number or name code for the character, with an ampersand (&) before the code and a semicolon (;). The Web browser displays the designated character in the text.

The following table lists the common special characters you can insert.



| Description | Special Character | Code | Description | Special Character | Code |
|-------------------------|-------------------|----------|------------------------|-------------------|----------|
| copyright | © | © | small o, slash | ø | ø |
| registered trademark | ® | ® | em dash | — | — |
| trademark | ™ | ™ | en dash | – | – |
| paragraph mark | ¶ | ¶ | micro sign | μ | µ |
| nonbreaking space | | | macron | ˉ | ¯ |
| quotation mark | “ | " | superscript one | ¹ | ¹ |
| left angle quote | « | « | superscript two | ² | ² |
| right angle quote | » | » | superscript three | ³ | ³ |
| ampersand | & | & | one-half fraction | ½ | ½ |
| inverted exclamation | ¡ | ¡ | one-fourth fraction | ¼ | ¼ |
| inverted question mark | ¿ | ? | three-fourths fraction | ¾ | ¾ |
| broken vertical bar | | ¦ | degree sign | ° | ° |
| section sign | § | § | multiply sign | × | × |
| not sign | ¬ | ¬ | division sign | ÷ | ÷ |
| acute accent | ´ | ´ | plus-or-minus sign | ± | ± |
| cedilla | ¸ | ¸ | less-than sign | < | < |
| bullet | • | • | greater-than sign | > | > |
| capital N, tilde | Ñ | &NTilde; | dagger | † | † |
| small n, tilde | ñ | ñ | double dagger | ‡ | ‡ |
| capital A, tilde | Ã | Ã | cent sign | ¢ | ¢ |
| small a, tilde | ã | ã | pound sterling | £ | £ |
| capital A, grave accent | À | À | euro | € | € |
| small a, grave accent | à | à | yen sign | ¥ | ¥ |
| capital O, slash | Ø | Ø | general currency | ¤ | ¤ |

Formatting Text

If you use a word processor, you will be familiar with the ability to make text bold, italic, or underlined; these are just three of the ten options available to indicate how text can appear in HTML. The full list is bold, italic, monospaced, underlined, strikethrough, teletype, larger, smaller, superscripted, and subscripted text. Technically speaking, these elements affect only the presentation of a document and the markup is of no other use. You can also achieve a similar appearance using CSS. However, they are still commonly used.

✦ The < b > Element

The tag is used to display text in bold. The tag only makes the content within it display as bold, it does not give any extra importance to the text.

✦ The < i > Element

The <i> tag is used to display its content in italic. The <i> tag similar to only makes the including text display in italic font and does not give any extra emphasis to the text.

✦ The < u > Element (Deprecated)

✦ The < s > and < strike > Elements (Deprecated)

✦ The < tt > Element

✦ The < sup > Element

The <sup> tag is used for display text in superscript. The <sup> tag generally displays the text half a character above the baseline.

✦ The < sub > Element



The <sub> tag is used for display text in subscript. The <sub> tag generally displays the text half a character below the baseline.

✦ The Element

The tag is similar to the <s> tag, it is used to display a strike line through the content. The tag implies a removal from the document.

✦ The <big> Element

✦ The <small> Element

List Elements

Humans are natural list makers, and HTML provides elements for marking up three types of lists:

* Unordered lists

Collections of items that appear in no particular order

* Ordered lists

Lists in which the sequence of the items is important

* Description lists

Lists that consist of name and value pairs, including but not limited to terms and definitions

HTML lists used to present list of information in well-formed and semantic way. The most common forms of HTML lists are ordered and unordered lists.

✦ Ordered List

You can use numbered lists on your Web page to display all kinds of ordered lists. For example, you can use numbered lists to show steps or prioritize items.



↳ Also called a numbered list, displays information in a series using numbers or letters. An ordered list works well to organize items where sequence matters, such as in a series of steps. To mark an ordered list, insert the and tags at the start and end of the list. Mark each item in an unordered list with a set of list item tags and .

↳ An ordered list can use numbers, letters, or Roman numerals. The default option is to use Arabic numbers, such as 1, 2, and 3.



✦ Unordered List


You can add a bulleted list to your document to set a list of items apart from the rest of the page of text. You can use a bulleted list, also called an unordered list, when you do not need to show the items in a particular order.



- ✧ Also called a bulleted list, displays a small graphic called a bullet before each item of information. In an unordered list, the bulleted items can appear in any sequence. To mark an unordered list, insert the `` tag at the start of the list and the `` tag at the end of the list. Mark each item in an unordered list with a set of list item tags `` and ``.
- ✧ Unordered and ordered lists have optional bullet and number types.
- ✧ An unordered list can use one of three bullet options: disc, square, or circle. If no type is identified, the browser displays the default type, a disc. You can also specify an image to use as a bullet.

✦ Description list

You can use a definition list in your document to set text apart in the format of a glossary or dictionary.



- ✧ It contains terms and descriptions.
- ✧ Definition List makes use of following three tags.






- `<dl>` – Defines the start of the list
- `<dt>` – A term
- `<dd>` – Term definition
- `</dl>` – Defines the end of the list

The type Attribute






You can use type attribute for `` tag to specify the type of bullet you like. By default, a Web browser reads your bulleted list as disc type. To change different bullet you must add **type** attribute to the `` tag.

The different value of **type** attribute for unordered list are:

-  Circle
-  Square
-  Disc (default)

For example, if you want a square type, the code would read `<ul type="square">`.

The different value of **type** attribute for ordered list are:

-  upper-alpha → A → A. B. C. D.
-  lower-alpha → a → a. b. c. d.
-  upper-roman → I → I. II. III. IV.
-  lower-roman → i → i. ii. iii. iv.
-  decimal → 1 → 1. 2. 3. 4.

For example, if you want a I type, the code would read `<ol type="I">`.

The start Attribute


You can use start attribute for `` tag to specify the starting point of numbering you need. By default, a Web browser reads your numbered list coding and starts with the number 1. To start with a different number, you must add a **start** attribute to the `` tag.

The different value of **start** attribute are:

For example, if the numbering is to start at 5, the coding would read `<ol start="5" type="1">`.







Lesson in Module 4 CCS3218





◀ Preliminary Activity for Week 4

Jump to...



Analysis, Application, and Exploration for Week 4 ▶



Navigation

Home



Dashboard

Site pages

My courses

121 - CC106

121 - BPM101 / DM103

121 - OAELEC2

121 - ITE3

121 - MUL101

121 - ITSP2B

121 - WEB101 / CCS3218

Participants



Grades



General

01 Introduction to Internet and World Wide Web


02 Full Stack Development Overview

03 The Basics of HTML

04 Mark Up Text

 Preliminary Activity for Week 4

 **Lesson Proper for Week 4**

 Analysis, Application, and Exploration for Week 4

 Generalization for Week 4

 Evaluation for Week 4

 Assignment for Week 4

05 HTML Link, Image and Table

06 - Preliminary Examination

07 HTML Block, Inline Element and Forms Control

08 Introduction To Cascading Style Sheets

09 The Font Style Properties

10 The List and Table style properties

11 Advanced CSS

12 - Midterm Examination

13 JavaScript Basics

14 JavaScript Objects

15 Introduction to PHP

16 PHP Control Statement and Function

17 PHP Array and String

Courses

Fair Warning

NOTICE: Please be reminded that it has come to the attention of the Publishing Team of eLearning Commons that learning materials published and intended for ***free use only by students and faculty members within the eLearning Commons network were UNLAWFULLY uploaded in other sites without due and proper permission.***

PROSECUTION: Under Philippine law (Republic Act No. 8293), copyright infringement is punishable by the following: Imprisonment of between 1 to 3 years and a fine of between 50,000 to 150,000 pesos for the first offense. Imprisonment of 3 years and 1 day to six years plus a fine of between 150,000 to 500,000 pesos for the second offense.

COURSE OF ACTION: Whoever has maliciously uploaded these concerned materials are hereby given an ultimatum to take it down within 24-hours. Beyond the 24-hour grace period, our Legal Department shall initiate the proceedings in coordination with the National Bureau of Investigation for IP Address tracking, account owner identification, and filing of cases for prosecution.



2nd Semester Enrollment

A banner for the 2nd Semester Enrollment. The background is a blue-tinted image of a multi-story building with a 'BCP' sign on top. Overlaid text includes: 'visit www.bcp.edu.ph' in blue; 'Enrollment registration is now Ongoing' in large red letters; 'For 2nd Semester SY 2021 - 2022' in white letters on a blue background; 'We are accepting new students, returnees and transferees.' in white letters on a blue background; '“Be trained to be the best, Be linked to success”' in white letters; a BCP logo; an email icon with 'bcp-inquire@bcp.edu.ph'; and a phone icon with '(8)442-8601 | (8)518-8050'.

visit www.bcp.edu.ph

Enrollment registration is now Ongoing

For 2nd Semester SY 2021 - 2022





We are accepting new students, returnees and transferees.

“Be trained to be the best,
Be linked to success”

 bcp-inquire@bcp.edu.ph

 (8)442-8601 | (8)518-8050

Activities

-  Assignments
-  Forums
-  Quizzes
-  Resources

Bestlink College of the Philippines
College Department

Powered by [eLearning Commons](#)

